

	Section	Page
Changes to 1. Introduction	1	3
Changes to 2. The character set	17	8
Changes to 3. Input and output	25	11
Changes to 4. String handling	38	15
Changes to 5. On-line and off-line printing	54	17
Changes to 6. Reporting errors	72	21
Changes to 7. Arithmetic with scaled dimensions	99	24
Changes to 7b. Random numbers	110	25
Changes to 8. Packed data	128	25
Changes to 9. Dynamic memory allocation	133	27
Changes to 10. Data structures for boxes and their friends	151	28
Changes to 11. Memory layout	180	31
Changes to 12. Displaying boxes	191	32
Changes to 13. Destroying boxes	217	34
Changes to 14. Copying boxes	221	35
Changes to 15. The command codes	225	36
Changes to 16. The semantic nest	229	37
Changes to 17. The table of equivalents	238	40
Changes to 18. The hash table	274	57
Changes to 19. Saving and restoring equivalents	290	64
Changes to 20. Token lists	311	65
Changes to 21. Introduction to the syntactic routines	319	66
Changes to 22. Input stacks and states	322	66
Changes to 23. Maintaining the input stacks	343	69
Changes to 24. Getting the next token	354	71
Changes to 25. Expanding the next token	388	78
Changes to 26. Basic scanning subroutines	428	81
Changes to 27. Building token lists	490	82
Changes to 28. Conditional processing	513	83
Changes to 29. File names	537	84
Changes to 30. Font metric data	565	96
Changes to 31. Device-independent file format	610	105
Changes to 32. Shipping pages out	619	105
Changes to 32a. pdfTeX basic	672	115
Changes to 32b. pdfTeX output low-level subroutines	679	117
Changes to 32c. PDF page description	691	117
Changes to 32d. The cross-reference table	694	117
Changes to 32e. Font processing	703	117
Changes to 32f. PDF shipping out	727	117
Changes to 33. Packaging	816	121
Changes to 34. Data structures for math mode	856	121
Changes to 35. Subroutines for math mode	875	121
Changes to 36. Typesetting math formulas	895	122
Changes to 37. Alignment	944	124
Changes to 38. Breaking paragraphs into lines	989	124
Changes to 39. Breaking paragraphs into lines, continued	1038	124
Changes to 40. Pre-hyphenation	1068	124
Changes to 41. Post-hyphenation	1077	124
Changes to 42. Hyphenation	1096	125
Changes to 43. Initializing the hyphenation tables	1119	130
Changes to 44. Breaking vertical lists into pages	1144	136
Changes to 45. The page builder	1157	136

Changes to 46. The chief executive	1206	137
Changes to 47. Building boxes and lists	1233	139
Changes to 48. Building math lists	1314	142
Changes to 49. Mode-independent processing	1386	143
Changes to 50. Dumping and undumping the tables	1478	155
Changes to 51. The main program	1511	168
Changes to 52. Debugging	1519	176
Changes to 53. Extensions	1521	178
Changes to 53a. The extended features of ε -TeX	1649	196
Changes to 54/web2c. System-dependent changes for Web2c	1868	202
Changes to 54/web2c-string. The string recycling routines	1877	204
Changes to 54/web2c. More changes for Web2c	1879	205
Changes to 54/MLTeX. System-dependent changes for MLTeX	1882	206
Changes to 54/encTeX. System-dependent changes for encTeX	1896	213
Changes to 54/SyncTeX. The <i>Synchronize TeXnology</i>	1905	219
Changes to 54. System-dependent changes	1940	223
Changes to 55. Index	1942	224

March 16, 2024 at 12:15

2* The present implementation has a long ancestry, beginning in the summer of 1977, when Michael F. Plass and Frank M. Liang designed and coded a prototype based on some specifications that the author had made in May of that year. This original protoTeX included macro definitions and elementary manipulations on boxes and glue, but it did not have line-breaking, page-breaking, mathematical formulas, alignment routines, error recovery, or the present semantic nest; furthermore, it used character lists instead of token lists, so that a control sequence like `\halign` was represented by a list of seven characters. A complete version of TeX was designed and coded by the author in late 1977 and early 1978; that program, like its prototype, was written in the SAIL language, for which an excellent debugging system was available. Preliminary plans to convert the SAIL code into a form somewhat like the present “web” were developed by Luis Trabb Pardo and the author at the beginning of 1979, and a complete implementation was created by Ignacio A. Zabala in 1979 and 1980. The TeX82 program, which was written by the author during the latter part of 1981 and the early part of 1982, also incorporates ideas from the 1979 implementation of TeX in MESA that was written by Leonidas Guibas, Robert Sedgewick, and Douglas Wyatt at the Xerox Palo Alto Research Center. Several hundred refinements were introduced into TeX82 based on the experiences gained with the original implementations, so that essentially every part of the system has been substantially improved. After the appearance of “Version 0” in September 1982, this program benefited greatly from the comments of many other people, notably David R. Fuchs and Howard W. Trickey. A final revision in September 1989 extended the input character set to eight-bit codes and introduced the ability to hyphenate words from different languages, based on some ideas of Michael J. Ferguson.

No doubt there still is plenty of room for improvement, but the author is firmly committed to keeping TeX82 “frozen” from now on; stability and reliability are to be its main virtues.

On the other hand, the WEB description can be extended without changing the core of TeX82 itself, and the program has been designed so that such extensions are not extremely difficult to make. The *banner* string defined here should be changed whenever TeX undergoes any modifications, so that it will be clear which version of TeX might be the guilty party when a problem arises.

This program contains code for various features extending TeX, therefore this program is called ‘ ε -TeX’ and not ‘TeX’; the official name ‘TeX’ by itself is reserved for software systems that are fully compatible with each other. A special test suite called the “TRIP test” is available for helping to determine whether a particular implementation deserves to be known as ‘TeX’ [cf. Stanford Computer Science report CS1027, November 1984].

MLTeX will add new primitives changing the behaviour of TeX. The *banner* string has to be changed. We do not change the *banner* string, but will output an additional line to make clear that this is a modified TeX version.

A similar test suite called the “ ε -TRIP test” is available for helping to determine whether a particular implementation deserves to be known as ‘ ε -TeX’.

```

define eTeX_version = 2 { \eTeXversion }
define eTeX_revision ≡ ".6" { \eTeXrevision }
define eTeX_version_string ≡ `ˆ-2.6ˆ` { current  $\varepsilon$ -TeX version }

define eTeX_banner ≡ `This is  $\varepsilon$ -TeX, Version 3.141592653ˆ, eTeX_version_string
    { printed when  $\varepsilon$ -TeX starts }

define pdfTeX_version ≡ 140 { \pdfTeXversion }
define pdfTeX_revision ≡ "26" { \pdfTeXrevision }
define pdfTeX_version_string ≡ `ˆ-1.40.26ˆ` { current pdfTeX version }

define pdfTeX_banner ≡ `This is pdfTeX, Version 3.141592653ˆ, eTeX_version_string,
    pdfTeX_version_string { printed when pdfTeX starts }

define TeX_banner_k ≡ `This is TeXk, Version 3.141592653ˆ` { printed when TeX starts }
define TeX_banner ≡ `This is TeX, Version 3.141592653ˆ` { printed when TeX starts }

define banner ≡ pdfTeX_banner
define banner_k ≡ pdfTeX_banner

```

```

define TEX  $\equiv$  PDFTEX { change program name into PDFTEX }
define TeXXeT_code = 0 { the TeX--XgT feature is optional }
define eTeX_states = 1 { number of  $\varepsilon$ -TeX state variables in eqtb }

```

4* The program begins with a normal Pascal program heading, whose components will be filled in later, using the conventions of WEB. For example, the portion of the program called ‘⟨Global variables 13⟩’ below will be replaced by a sequence of variable declarations that starts in §13 of this documentation. In this way, we are able to define each individual global variable when we are prepared to understand what it means; we do not have to define all of the globals at once. Cross references in §13, where it says “See also sections 20, 26, . . .,” also make it possible to look at the set of all global variables, if desired. Similar remarks apply to the other portions of the program heading.

```

define mtype  $\equiv$  t@&y@&p@&e { this is a WEB coding trick: }
format mtype  $\equiv$  type { ‘mtype’ will be equivalent to ‘type’ }
format type  $\equiv$  true { but ‘type’ will not be treated as a reserved word }
⟨Compiler directives 9⟩
program TEX; { all file names are defined dynamically }
const ⟨Constants in the outer block 11*⟩
mtype ⟨Types in the outer block 18⟩
var ⟨Global variables 13⟩
procedure initialize; { this procedure gets things started properly }
var ⟨Local variables for initialization 19*⟩
begin ⟨Initialize whatever TeX might access 8*⟩
end;
⟨Basic printing procedures 57⟩
⟨Error handling procedures 78⟩

```

6* For Web2c, labels are not declared in the main program, but we still have to declare the symbolic names.

```

define start_of_TEX = 1 { go here when TeX’s variables are initialized }
define final_end = 9999 { this label marks the ending of the program }

```

7* Some of the code below is intended to be used only when diagnosing the strange behavior that sometimes occurs when TeX is being installed or when system wizards are fooling around with TeX without quite knowing what they are doing. Such code will not normally be compiled; it is delimited by the codewords ‘**debug . . . gubed**’, with apologies to people who wish to preserve the purity of English.

Similarly, there is some conditional code delimited by ‘**stat . . . tats**’ that is intended for use when statistics are to be kept about TeX’s memory usage. The **stat . . . tats** code also implements diagnostic information for `\tracingparagraphs`, `\tracingpages`, and `\tracingrestores`.

```

define debug  $\equiv$  ifdef(‘TEXMF_DEBUG’)
define gubed  $\equiv$  endif(‘TEXMF_DEBUG’)
format debug  $\equiv$  begin
format gubed  $\equiv$  end

define stat  $\equiv$  ifdef(‘STAT’)
define tats  $\equiv$  endif(‘STAT’)
format stat  $\equiv$  begin
format tats  $\equiv$  end

```

8* This program has two important variations: (1) There is a long and slow version called `INITEX`, which does the extra calculations needed to initialize `TEX`'s internal tables; and (2) there is a shorter and faster production version, which cuts the initialization to a bare minimum. Parts of the program that are needed in (1) but not in (2) are delimited by the codewords '`init...tini`' for declarations and by the codewords '`Init...Tini`' for executable code. This distinction is helpful for implementations where a run-time switch differentiates between the two versions of the program.

```

define init ≡ ifdef (‘INITEX’)
define tini ≡ endif (‘INITEX’)
define Init ≡
  init
  if ini_version then
    begin
define Tini ≡
  end ; tini
format Init ≡ begin
format Tini ≡ end
format init ≡ begin
format tini ≡ end

```

⟨ Initialize whatever `TEX` might access 8* ⟩ ≡

⟨ Set initial values of key variables 21 ⟩

Init ⟨ Initialize table entries (done by `INITEX` only) 182 ⟩ **Tini**

See also section 1913*.

This code is used in section 4*.

11* The following parameters can be changed at compile time to extend or reduce T_EX's capacity. They may have different values in INITEX and in production versions of T_EX.

```

define file_name_size ≡ maxint
define ssup_error_line = 255
define ssup_max_strings ≡ 2097151
    { Larger values than 65536 cause the arrays to consume much more memory. }
define ssup_trie_opcode ≡ 65535
define ssup_trie_size ≡ "3FFFFFF
define ssup_hyph_size ≡ 65535 { Changing this requires changing (un)dumping! }
define iinf_hyphen_size ≡ 610 { Must be not less than hyph_prime! }
define max_font_max = 9000 { maximum number of internal fonts; this can be increased, but
    hash_size + max_font_max should not exceed 29000. }
define font_base = 0 { smallest internal font number; must be ≥ min_quarterword; do not change this
    without modifying the dynamic definition of the font arrays. }
⟨ Constants in the outer block 11* ⟩ ≡
hash_offset = 514; { smallest index in hash array, i.e., hash_base }
    { Use hash_offset = 0 for compilers which cannot decrement pointers. }
trie_op_size = 35111;
    { space for "opcodes" in the hyphenation patterns; best if relatively prime to 313, 361, and 1009. }
neg_trie_op_size = -35111; { for lower trie_op_hash array bound; must be equal to -trie_op_size. }
min_trie_op = 0; { first possible trie op code for any language }
max_trie_op = ssup_trie_opcode; { largest possible trie opcode for any language }
pool_name = TEXMF_POOL_NAME; { this is configurable, for the sake of ML-TEX }
    { string of length file_name_size; tells where the string pool appears }
engine_name = TEXMF_ENGINE_NAME; { the name of this engine }
inf_mem_bot = 0; sup_mem_bot = 1; inf_main_memory = 3000; sup_main_memory = 256000000;
inf_trie_size = 8000; sup_trie_size = ssup_trie_size; inf_max_strings = 3000;
sup_max_strings = ssup_max_strings; inf_strings_free = 100; sup_strings_free = sup_max_strings;
inf_buf_size = 500; sup_buf_size = 30000000; inf_nest_size = 40; sup_nest_size = 4000;
inf_max_in_open = 6; sup_max_in_open = 127; inf_param_size = 60; sup_param_size = 32767;
inf_save_size = 600; sup_save_size = 30000000; inf_stack_size = 200; sup_stack_size = 30000;
inf_dvi_buf_size = 800; sup_dvi_buf_size = 65536; inf_font_mem_size = 20000;
sup_font_mem_size = 147483647; { integer-limited, so 2 could be prepended? }
sup_font_max = max_font_max; inf_font_max = 50; { could be smaller, but why? }
inf_pool_size = 32000; sup_pool_size = 40000000; inf_pool_free = 1000; sup_pool_free = sup_pool_size;
inf_string_vacancies = 8000; sup_string_vacancies = sup_pool_size - 23000;
sup_hash_extra = sup_max_strings; inf_hash_extra = 0; sup_hyph_size = ssup_hyph_size;
inf_hyph_size = iinf_hyphen_size; { Must be not less than hyph_prime! }
inf_expand_depth = 10; sup_expand_depth = 10000000;

```

See also sections 675, 679, 695, 721, and 1632.

This code is used in section 4*.

12* Like the preceding parameters, the following quantities can be changed at compile time to extend or reduce T_EX's capacity. But if they are changed, it is necessary to rerun the initialization program `INITEX` to generate new tables for the production T_EX program. One can't simply make helter-skelter changes to the following constants, since certain rather complex initialization numbers are computed from them. They are defined here using `WEB` macros, instead of being put into Pascal's `const` list, in order to emphasize this distinction.

```
define hash_size = 15000 { maximum number of control sequences; it should be at most about
    (mem_max - mem_min)/10; see also font_max }
define hash_prime = 8501 { a prime number equal to about 85% of hash_size }
define hyph_prime = 607 { another prime for hashing \hyphenation exceptions; if you change this,
    you should also change infn_hyphen_size. }
```

16* Here are some macros for common programming idioms.

```
define negate(#) ≡ # ← -# { change the sign of a variable }
define loop ≡ while true do { repeat over and over until a goto happens }
format loop ≡ xclause { WEB's xclause acts like 'while true do' }
define do_nothing ≡ { empty statement }
define return ≡ goto exit { terminate a procedure call }
format return ≡ nil
define empty = 0 { symbolic name for a null constant }
```

19* The original Pascal compiler was designed in the late 60s, when six-bit character sets were common, so it did not make provision for lowercase letters. Nowadays, of course, we need to deal with both capital and small letters in a convenient way, especially in a program for typesetting; so the present specification of TEX has been written under the assumption that the Pascal compiler and run-time system permit the use of text files with more than 64 distinguishable characters. More precisely, we assume that the character set contains at least the letters and symbols associated with ASCII codes '40 through '176; all of these characters are now available on most computer terminals.

Since we are dealing with more characters than were present in the first Pascal compilers, we have to decide what to call the associated data type. Some Pascals use the original name *char* for the characters in text files, even though there now are more than 64 such characters, while other Pascals consider *char* to be a 64-element subrange of a larger data type that has some other name.

In order to accommodate this difference, we shall use the name *text_char* to stand for the data type of the characters that are converted to and from *ASCII_code* when they are input and output. We shall also assume that *text_char* consists of the elements *chr(first_text_char)* through *chr(last_text_char)*, inclusive. The following definitions should be adjusted if necessary.

```
define text_char  $\equiv$  ASCII_code { the data type of characters in text files }
define first_text_char = 0 { ordinal number of the smallest element of text_char }
define last_text_char = 255 { ordinal number of the largest element of text_char }
```

\langle Local variables for initialization 19* $\rangle \equiv$

i: *integer*;

See also sections 181 and 1104.

This code is used in section 4*.

20* The TEX processor converts between ASCII code and the user's external character set by means of arrays *xord* and *xchr* that are analogous to Pascal's *ord* and *chr* functions.

⟨Global variables 13⟩ +≡

```

xord: array [text_char] of ASCII_code; { specifies conversion of input characters }
xchr: array [ASCII_code] of text_char; { specifies conversion of output characters }
xprn: array [ASCII_code] of ASCII_code; { non zero iff character is printable }
mubyte_read: array [ASCII_code] of pointer; { non zero iff character begins the multi byte code }
mubyte_write: array [ASCII_code] of str_number;
    { non zero iff character expands to multi bytes in log and write files }
mubyte_cswrite: array [0 .. 127] of pointer;
    { non null iff cs mod 128 expands to multi bytes in log and write files }
mubyte_skip: integer; { the number of bytes to skip in buffer }
mubyte_keep: integer; { the number of chars we need to keep unchanged }
mubyte_skeep: integer; { saved mubyte_keep }
mubyte_prefix: integer; { the type of mubyte prefix }
mubyte_tablein: boolean; { the input side of table will be updated }
mubyte_tableout: boolean; { the output side of table will be updated }
mubyte_relax: boolean; { the relax prefix is used }
mubyte_start: boolean; { we are making the token at the start of the line }
mubyte_sstart: boolean; { saved mubyte_start }
mubyte_token: pointer; { the token returned by read_buffer }
mubyte_stoken: pointer; { saved first token in mubyte primitive }
mubyte_sout: integer; { saved value of mubyte_out }
mubyte_slog: integer; { saved value of mubyte_log }
spec_sout: integer; { saved value of spec_out }
no_convert: boolean; { conversion suppressed by noconvert primitive }
active_noconvert: boolean; { true if noconvert primitive is active }
write_noexpanding: boolean; { true only if we need not write expansion }
cs_converting: boolean; { true only if we need csname converting }
special_printing: boolean; { true only if we need converting in special }
message_printing: boolean; { true if message or errmessage prints to string }

```

23* The ASCII code is “standard” only to a certain extent, since many computer installations have found it advantageous to have ready access to more than 94 printing characters. Appendix C of *The TeXbook* gives a complete specification of the intended correspondence between characters and TeX’s internal representation.

If TeX is being used on a garden-variety Pascal for which only standard ASCII codes will appear in the input and output files, it doesn’t really matter what codes are specified in *xchr*[0 .. ’37], but the safest policy is to blank everything out by using the code shown below.

However, other settings of *xchr* will make TeX more friendly on computers that have an extended character set, so that users can type things like ‘#’ instead of ‘\ne’. People with extended character sets can assign codes arbitrarily, giving an *xchr* equivalent to whatever characters the users of TeX are allowed to have in their input files. It is best to make the codes correspond to the intended interpretations as shown in Appendix C whenever possible; but this is not necessary. For example, in countries with an alphabet of more than 26 letters, it is usually best to map the additional letters into codes less than ’40. To get the most “permissive” character set, change ‘_’ on the right of these assignment statements to *chr*(*i*).

```

⟨Set initial values of key variables 21⟩ +≡
  { Initialize xchr to the identity mapping. }
  for i ← 0 to ’37 do xchr[i] ← i;
  for i ← ’177 to ’377 do xchr[i] ← i; { Initialize encTeX data. }
  for i ← 0 to 255 do mubyte_read[i] ← null;
  for i ← 0 to 255 do mubyte_write[i] ← 0;
  for i ← 0 to 127 do mubyte_cswrite[i] ← null;
  mubyte_keep ← 0; mubyte_start ← false; write_noexpanding ← false; cs_converting ← false;
  special_printing ← false; message_printing ← false; no_convert ← false; active_noconvert ← false;

```

24* The following system-independent code makes the *xord* array contain a suitable inverse to the information in *xchr*. Note that if *xchr*[*i*] = *xchr*[*j*] where *i* < *j* < ’177, the value of *xord*[*xchr*[*i*]] will turn out to be *j* or more; hence, standard ASCII code numbers will be used instead of codes below ’40 in case there is a coincidence.

```

⟨Set initial values of key variables 21⟩ +≡
  for i ← first_text_char to last_text_char do xord[chr(i)] ← invalid_code;
  for i ← ’200 to ’377 do xord[xchr[i]] ← i;
  for i ← 0 to ’176 do xord[xchr[i]] ← i; { Set xprn for printable ASCII, unless eight_bit_p is set. }
  for i ← 0 to 255 do xprn[i] ← (eight_bit_p ∨ ((i ≥ “_”) ∧ (i ≤ “~”))); { The idea for this dynamic
    translation comes from the patch by Libor Skarvada <libor@informatics.muni.cz> and Petr
    Sojka <sojka@informatics.muni.cz>. I didn’t use any of the actual code, though, preferring a
    more general approach. }
  { This updates the xchr, xord, and xprn arrays from the provided translate_filename. See the
    function definition in texmfmp.c for more comments. }
  if translate_filename then read_tcx_file;

```

26* Most of what we need to do with respect to input and output can be handled by the I/O facilities that are standard in Pascal, i.e., the routines called *get*, *put*, *eof*, and so on. But standard Pascal does not allow file variables to be associated with file names that are determined at run time, so it cannot be used to implement TeX; some sort of extension to Pascal’s ordinary *reset* and *rewrite* is crucial for our purposes. We shall assume that *name_of_file* is a variable of an appropriate type such that the Pascal run-time system being used to implement TeX can open a file whose external name is specified by *name_of_file*.

```

⟨Global variables 13⟩ +≡
name_of_file: ↑text_char;
name_length: 0 .. file_name_size;
    { this many characters are actually relevant in name_of_file (the rest are blank) }

```

27* All of the file opening functions are defined in C.

28* And all the file closing routines as well.

30* Input from text files is read one line at a time, using a routine called *input_ln*. This function is defined in terms of global variables called *buffer*, *first*, and *last* that will be described in detail later; for now, it suffices for us to know that *buffer* is an array of *ASCII_code* values, and that *first* and *last* are indices into this array representing the beginning and ending of a line of text.

```

⟨Global variables 13⟩ +≡
buffer: ↑ASCII_code; { lines of characters being read }
first: 0 .. buf_size; { the first unused position in buffer }
last: 0 .. buf_size; { end of the line just input to buffer }
max_buf_stack: 0 .. buf_size; { largest index used in buffer }

```

31* The *input_ln* function brings the next line of input from the specified file into available positions of the buffer array and returns the value *true*, unless the file has already been entirely read, in which case it returns *false* and sets $last \leftarrow first$. In general, the *ASCII_code* numbers that represent the next line of the file are input into $buffer[first]$, $buffer[first + 1]$, ..., $buffer[last - 1]$; and the global variable *last* is set equal to *first* plus the length of the line. Trailing blanks are removed from the line; thus, either $last = first$ (in which case the line was entirely blank) or $buffer[last - 1] \neq "_"$.

An overflow error is given, however, if the normal actions of *input_ln* would make $last \geq buf_size$; this is done so that other parts of TeX can safely look at the contents of $buffer[last + 1]$ without overstepping the bounds of the *buffer* array. Upon entry to *input_ln*, the condition $first < buf_size$ will always hold, so that there is always room for an “empty” line.

The variable *max_buf_stack*, which is used to keep track of how large the *buf_size* parameter must be to accommodate the present job, is also kept up to date by *input_ln*.

If the *bypass_eoln* parameter is *true*, *input_ln* will do a *get* before looking at the first character of the line; this skips over an *eoln* that was in *f*↑. The procedure does not do a *get* when it reaches the end of the line; therefore it can be used to acquire input from the user’s terminal as well as from ordinary text files.

Standard Pascal says that a file should have *eoln* immediately before *eof*, but TeX needs only a weaker restriction: If *eof* occurs in the middle of a line, the system function *eoln* should return a *true* result (even though *f*↑ will be undefined).

Since the inner loop of *input_ln* is part of TeX’s “inner loop”—each character of input comes in at this place—it is wise to reduce system overhead by making use of special routines that read in an entire array of characters at once, if such routines are available. The following code uses standard Pascal to illustrate what needs to be done, but finer tuning is often possible at well-developed Pascal sites.

We define *input_ln* in C, for efficiency. Nevertheless we quote the module ‘Report overflow of the input buffer, and abort’ here in order to make WEAVE happy, since part of that module is needed by e-TeX.

```
@{ Report overflow of the input buffer, and abort 35* }@}
```

32* The user's terminal acts essentially like other files of text, except that it is used both for input and for output. When the terminal is considered an input file, the file variable is called *term_in*, and when it is considered an output file the file variable is *term_out*.

```

define term_in  $\equiv$  stdin { the terminal as an input file }
define term_out  $\equiv$  stdout { the terminal as an output file }

⟨Global variables 13⟩ +=
init ini_version: boolean; { are we INITEX? }
dump_option: boolean; { was the dump name option used? }
dump_line: boolean; { was a %&f format line seen? }
tini
dump_name: const_cstring; { format name for terminal display }
bound_default: integer; { temporary for setup }
bound_name: const_cstring; { temporary for setup }
mem_bot: integer;
    { smallest index in the mem array dumped by INITEX; must not be less than mem_min }
main_memory: integer; { total memory words allocated in initex }
extra_mem_bot: integer; { mem_min  $\leftarrow$  mem_bot - extra_mem_bot except in INITEX }
mem_min: integer; { smallest index in TEX's internal mem array; must be min_halfword or more; must
    be equal to mem_bot in INITEX, otherwise  $\leq$  mem_bot }
mem_top: integer; { largest index in the mem array dumped by INITEX; must be substantially larger
    than mem_bot, equal to mem_max in INITEX, else not greater than mem_max }
extra_mem_top: integer; { mem_max  $\leftarrow$  mem_top + extra_mem_top except in INITEX }
mem_max: integer; { greatest index in TEX's internal mem array; must be strictly less than max_halfword;
    must be equal to mem_top in INITEX, otherwise  $\geq$  mem_top }
error_line: integer; { width of context lines on terminal error messages }
half_error_line: integer; { width of first lines of contexts in terminal error messages; should be between 30
    and error_line - 15 }
max_print_line: integer; { width of longest text lines output; should be at least 60 }
max_strings: integer; { maximum number of strings; must not exceed max_halfword }
strings_free: integer; { strings available after format loaded }
string_vacancies: integer; { the minimum number of characters that should be available for the user's
    control sequences and font names, after TEX's own error messages are stored }
pool_size: integer; { maximum number of characters in strings, including all error messages and help texts,
    and the names of all fonts and control sequences; must exceed string_vacancies by the total length of
    TEX's own strings, which is currently about 23000 }
pool_free: integer; { pool space free after format loaded }
font_mem_size: integer; { number of words of font_info for all fonts }
font_max: integer; { maximum internal font number; ok to exceed max_quarterword and must be at most
    font_base + max_font_max }
font_k: integer; { loop variable for initialization }
hyph_size: integer; { maximum number of hyphen exceptions }
trie_size: integer; { space for hyphenation patterns; should be larger for INITEX than it is in production
    versions of TEX. 50000 is needed for English, German, and Portuguese. }
buf_size: integer; { maximum number of characters simultaneously present in current lines of open files
    and in control sequences between \csname and \endcsname; must not exceed max_halfword }
stack_size: integer; { maximum number of simultaneous input sources }
max_in_open: integer;
    { maximum number of input files and error insertions that can be going on simultaneously }
param_size: integer; { maximum number of simultaneous macro parameters }
nest_size: integer; { maximum number of semantic levels simultaneously active }
save_size: integer; { space for saving values outside of current group; must be at most max_halfword }

```

```

dvi_buf_size: integer; { size of the output buffer; must be a multiple of 8 }
expand_depth: integer; { limits recursive calls to the expand procedure }
parse_first_line_p: cinttype; { parse the first line for options }
file_line_error_style_p: cinttype; { format messages as file:line:error }
eight_bit_p: cinttype; { make all characters printable by default }
halt_on_error_p: cinttype; { stop at first error }
halting_on_error_p: boolean; { already trying to halt? }
quoted_filename: boolean; { current filename is quoted }
  { Variables for source specials }
src_specials_p: boolean; { Whether src_specials are enabled at all }
insert_src_special_auto: boolean;
insert_src_special_every_par: boolean;
insert_src_special_every_parend: boolean;
insert_src_special_every_cr: boolean;
insert_src_special_every_math: boolean;
insert_src_special_every_hbox: boolean;
insert_src_special_every_vbox: boolean;
insert_src_special_every_display: boolean;

```

33* Here is how to open the terminal files. *t_open_out* does nothing. *t_open_in*, on the other hand, does the work of “rescanning,” or getting any command line arguments the user has provided. It’s defined in C.

```
define t_open_out ≡ { output already open for text output }
```

34* Sometimes it is necessary to synchronize the input/output mixture that happens on the user’s terminal, and three system-dependent procedures are used for this purpose. The first of these, *update_terminal*, is called when we want to make sure that everything we have output to the terminal so far has actually left the computer’s internal buffers and been sent. The second, *clear_terminal*, is called when we wish to cancel any input that the user may have typed ahead (since we are about to issue an unexpected error message). The third, *wake_up_terminal*, is supposed to revive the terminal if the user has disabled it by some instruction to the operating system. The following macros show how these operations can be specified with UNIX. *update_terminal* does an *fflush*. *clear_terminal* is redefined to do nothing, since the user should control the terminal.

```
define update_terminal ≡ fflush(term_out)
```

```
define clear_terminal ≡ do_nothing
```

```
define wake_up_terminal ≡ do_nothing { cancel the user’s cancellation of output }
```

35* We need a special routine to read the first line of \TeX input from the user's terminal. This line is different because it is read before we have opened the transcript file; there is sort of a "chicken and egg" problem here. If the user types ' $\backslash\text{input paper}$ ' on the first line, or if some macro invoked by that line does such an $\backslash\text{input}$, the transcript file will be named ' paper.log '; but if no $\backslash\text{input}$ commands are performed during the first line of terminal input, the transcript file will acquire its default name ' texput.log '. (The transcript file will not contain error messages generated by the first line before the first $\backslash\text{input}$ command.)

The first line is even more special if we are lucky enough to have an operating system that treats \TeX differently from a run-of-the-mill Pascal object program. It's nice to let the user start running a \TeX job by typing a command line like ' tex paper '; in such a case, \TeX will operate as if the first line of input were ' paper ', i.e., the first line will consist of the remainder of the command line, after the part that invoked \TeX .

The first line is special also because it may be read before \TeX has input a format file. In such cases, normal error messages cannot yet be given. The following code uses concepts that will be explained later. (If the Pascal compiler does not support non-local **goto**, the statement ' goto final_end ' should be replaced by something that quietly terminates the program.)

Routine is implemented in C; part of module is, however, needed for e- \TeX .

(Report overflow of the input buffer, and abort **35***) \equiv

```
begin cur_input.loc_field  $\leftarrow$  first; cur_input.limit_field  $\leftarrow$  last - 1; overflow("buffer_size", buf_size);
end
```

This code is used in sections **31*** and **1757**.

37* The following program does the required initialization. If anything has been specified on the command line, then *t_open_in* will return with *last* > *first*.

```
function init_terminal: boolean; { gets the terminal input started }
  label exit;
  begin t_open_in;
  if last > first then
    begin loc  $\leftarrow$  first;
    while (loc < last)  $\wedge$  (buffer[loc] =  $\backslash$ _) do incr(loc);
    if loc < last then
      begin init_terminal  $\leftarrow$  true; goto exit;
      end;
    end;
  loop begin wake_up_terminal; write(term_out,  $\backslash$ **); update_terminal;
  if  $\neg$ input_ln(term_in, true) then { this shouldn't happen }
    begin write_ln(term_out); write_ln(term_out,  $\backslash$ !_End_of_file_on_the_terminal..._why?);
    init_terminal  $\leftarrow$  false; return;
    end;
  loc  $\leftarrow$  first;
  while (loc < last)  $\wedge$  (buffer[loc] = "_") do incr(loc);
  if loc < last then
    begin init_terminal  $\leftarrow$  true; return; { return unless the line was all blank }
    end;
  write_ln(term_out,  $\backslash$ Please_type_the_name_of_your_input_file.);
  end;
exit: end;
```

38* **String handling.** Control sequence names and diagnostic messages are variable-length strings of eight-bit characters. Since Pascal does not have a well-developed string mechanism, TEX does all of its string processing by homegrown methods.

Elaborate facilities for dynamic strings are not needed, so all of the necessary operations can be handled with a simple data structure. The array *str_pool* contains all of the (eight-bit) ASCII codes in all of the strings, and the array *str_start* contains indices of the starting points of each string. Strings are referred to by integer numbers, so that string number *s* comprises the characters *str_pool*[*j*] for *str_start*[*s*] ≤ *j* < *str_start*[*s* + 1]. Additional integer variables *pool_ptr* and *str_ptr* indicate the number of entries used so far in *str_pool* and *str_start*, respectively; locations *str_pool*[*pool_ptr*] and *str_start*[*str_ptr*] are ready for the next string to be allocated.

String numbers 0 to 255 are reserved for strings that correspond to single ASCII characters. This is in accordance with the conventions of WEB, which converts single-character strings into the ASCII code number of the single character involved, while it converts other strings into integers and builds a string pool file. Thus, when the string constant "." appears in the program below, WEB converts it into the integer 46, which is the ASCII code for a period, while WEB will convert a string like "hello" into some integer greater than 255. String number 46 will presumably be the single character '.'; but some ASCII codes have no standard visible representation, and TEX sometimes needs to be able to print an arbitrary ASCII character, so the first 256 strings are used to specify exactly what should be printed for each of the 256 possibilities.

Elements of the *str_pool* array must be ASCII codes that can actually be printed; i.e., they must have an *xchr* equivalent in the local character set. (This restriction applies only to preloaded strings, not to those generated dynamically by the user.)

Some Pascal compilers won't pack integers into a single byte unless the integers lie in the range -128 .. 127. To accommodate such systems we access the string pool only via macros that can easily be redefined.

```
define si(#) ≡ # { convert from ASCII_code to packed_ASCII_code }
define so(#) ≡ # { convert from packed_ASCII_code to ASCII_code }
```

<Types in the outer block 18> +≡

```
pool_pointer = integer; { for variables that point into str_pool }
str_number = 0 .. ssup_max_strings; { for variables that point into str_start }
packed_ASCII_code = 0 .. 255; { elements of str_pool array }
```

39* <Global variables 13> +≡

```
str_pool: ↑packed_ASCII_code; { the characters }
str_start: ↑pool_pointer; { the starting pointers }
pool_ptr: pool_pointer; { first unused position in str_pool }
str_ptr: str_number; { number of the current string being created }
init_pool_ptr: pool_pointer; { the starting value of pool_ptr }
init_str_ptr: str_number; { the starting value of str_ptr }
```

47* The initial values of *str_pool*, *str_start*, *pool_ptr*, and *str_ptr* are computed by the INITEX program, based in part on the information that WEB has output while processing TEX.

<Declare additional routines for string recycling 1877*>

```
init function get_strings_started: boolean;
    { initializes the string pool, but returns false if something goes wrong }
```

```
label done, exit;
```

```
var k, l: 0 .. 255; { small indices or counters }
```

```
    g: str_number; { garbage }
```

```
begin pool_ptr ← 0; str_ptr ← 0; str_start[0] ← 0; <Make the first 256 strings 48>;
```

```
<Read the other strings from the TEX.POOL file and return true, or give an error message and return false 51*>;
```

```
exit: end;
```

```
    tini
```

49* The first 128 strings will contain 95 standard ASCII characters, and the other 33 characters will be printed in three-symbol form like `^^A` unless a system-dependent change is made here. Installations that have an extended character set, where for example `xchr['32] = '^'`, would like string `'32` to be printed as the single character `'32` instead of the three characters `'136, '136, '132` (`^^Z`). On the other hand, even people with an extended character set will want to represent string `'15` by `^^M`, since `'15` is `carriage_return`; the idea is to produce visible strings instead of tabs or line-feeds or carriage-returns or bell-rings or characters that are treated anomalously in text files.

Unprintable characters of codes 128–255 are, similarly, rendered `^^80–^^ff`.

The boolean expression defined here should be `true` unless TEX internal code number k corresponds to a non-troublesome visible symbol in the local character set. An appropriate formula for the extended character set recommended in *The TEXbook* would, for example, be `'k ∈ [0, '10 .. '12, '14, '15, '33, '177 .. '377]`. If character k cannot be printed, and $k < '200$, then character $k + '100$ or $k - '100$ must be printable; moreover, ASCII codes [`'41 .. '46, '60 .. '71, '136, '141 .. '146, '160 .. '171`] must be printable. Thus, at least 80 printable characters are needed.

```
<Character  $k$  cannot be printed 49*> ≡
(k < "□" ) ∨ (k > "˘")
```

This code is used in section 48.

51* <Read the other strings from the TEX.POOL file and return `true`, or give an error message and return `false` 51*> ≡

```
g ← loadpoolstrings((pool_size - string_vacancies));
if g = 0 then
  begin wake_up_terminal; write_ln(term_out, '!□You□have□to□increase□POOLSIZE.˘');
  get_strings_started ← false; return;
end;
get_strings_started ← true;
```

This code is used in section 47*.

52* Empty module

53* Empty module

54* On-line and off-line printing. Messages that are sent to a user's terminal and to the transcript-log file are produced by several '*print*' procedures. These procedures will direct their output to a variety of places, based on the setting of the global variable *selector*, which has the following possible values:

term_and_log, the normal setting, prints on the terminal and on the transcript file.

log_only, prints only on the transcript file.

term_only, prints only on the terminal.

no_print, doesn't print at all. This is used only in rare cases before the transcript file is open.

pseudo, puts output into a cyclic buffer that is used by the *show_context* routine; when we get to that routine we shall discuss the reasoning behind this curious mode.

new_string, appends the output to the current string in the string pool.

0 to 15, prints on one of the sixteen files for `\write` output.

The symbolic names '*term_and_log*', etc., have been assigned numeric codes that satisfy the convenient relations $no_print + 1 = term_only$, $no_print + 2 = log_only$, $term_only + 2 = log_only + 1 = term_and_log$.

Three additional global variables, *tally* and *term_offset* and *file_offset*, record the number of characters that have been printed since they were most recently cleared to zero. We use *tally* to record the length of (possibly very long) stretches of printing; *term_offset* and *file_offset*, on the other hand, keep track of how many characters have appeared so far on the current line that has been output to the terminal or to the transcript file, respectively.

```

define no_print = 16 { selector setting that makes data disappear }
define term_only = 17 { printing is destined for the terminal only }
define log_only = 18 { printing is destined for the transcript file only }
define term_and_log = 19 { normal selector setting }
define pseudo = 20 { special selector setting for show_context }
define new_string = 21 { printing is deflected to the string pool }
define max_selector = 21 { highest selector setting }

```

⟨Global variables 13⟩ +≡

```

log_file: alpha_file; { transcript of TEX session }
selector: 0 .. max_selector; { where to print a message }
dig: array [0 .. 22] of 0 .. 15; { digits in a number being output }
tally: integer; { the number of characters recently printed }
term_offset: 0 .. max_print_line; { the number of characters on the current terminal line }
file_offset: 0 .. max_print_line; { the number of characters on the current file line }
trick_buf: array [0 .. ssup_error_line] of ASCII_code; { circular buffer for pseudoprinting }
trick_count: integer; { threshold for pseudoprinting, explained later }
first_count: integer; { another variable for pseudoprinting }

```

59* An entire string is output by calling *print*. Note that if we are outputting the single standard ASCII character *c*, we could call *print*("c"), since "c" = 99 is the number of a single-character string, as explained above. But *print_char*("c") is quicker, so TEX goes directly to the *print_char* routine when it knows that this is safe. (The present implementation assumes that it is always safe to print a visible ASCII character.)

⟨Basic printing procedures 57⟩ +≡

```

procedure print(s : integer); { prints string s }
  label exit;
  var j: pool_pointer; { current character code position }
      nl: integer; { new-line character to restore }
  begin if s ≥ str_ptr then s ← "???" { this can't happen }
  else if s < 256 then
    if s < 0 then s ← "???" { can't happen }
    else begin if (selector > pseudo) ∧ (¬special_printing) ∧ (¬message_printing) then
      begin print_char(s); return; { internal strings are not expanded }
      end;
    if ((Character s is the current new-line character 262)) then
      if selector < pseudo then
        begin print_ln; no_convert ← false; return;
        end
      else if message_printing then
        begin print_char(s); no_convert ← false; return;
        end;
    if (mubyte_log > 0) ∧ (¬no_convert) ∧ (mubyte_write[s] > 0) then s ← mubyte_write[s]
    else if xprn[s] ∨ special_printing then
      begin print_char(s); no_convert ← false; return;
      end;
    no_convert ← false; nl ← new_line_char; new_line_char ← -1;
    { temporarily disable new-line character }
    j ← str_start[s];
    while j < str_start[s + 1] do
      begin print_char(so(str_pool[j])); incr(j);
      end;
    new_line_char ← nl; return;
    end;
  j ← str_start[s];
  while j < str_start[s + 1] do
    begin print_char(so(str_pool[j])); incr(j);
    end;
  exit: end;

```

61* Here is the very first thing that TEX prints: a headline that identifies the version number and format package. The *term_offset* variable is temporarily incorrect, but the discrepancy is not serious since we assume that this part of the program is system dependent.

```

⟨ Initialize the output routines 55 ⟩ +≡
  if src_specials_p ∨ file_line_error_style_p ∨ parse_first_line_p then wterm(banner_k)
  else wterm(banner);
  wterm(version_string);
  if format_ident = 0 then wterm_ln(␣(preloaded␣format=␣, dump_name, ␣)␣)
  else begin slow_print(format_ident); print_ln;
  end;
  if shellenabled_p then
  begin wterm(␣␣);
  if restrictedshell then
  begin wterm(␣restricted␣);
  end;
  wterm_ln(␣\write18␣enabled.␣);
  end;
  if src_specials_p then
  begin wterm_ln(␣␣Source␣specials␣enabled.␣)
  end;
  if translate_filename then
  begin wterm(␣␣); fputs(translate_filename, stdout); wterm_ln(␣␣);
  end;
  update_terminal;

```

62* The procedure *print_nl* is like *print*, but it makes sure that the string appears at the beginning of a new line.

```

⟨ Basic printing procedures 57 ⟩ +≡
procedure print_nl(s : str_number); { prints string s at beginning of line }
  begin if (selector < no_print) ∨ ((term_offset > 0) ∧ (odd(selector))) ∨
  ((file_offset > 0) ∧ (selector ≥ log_only)) then print_ln;
  print(s);
  end;

```

71* Here is a procedure that asks the user to type a line of input, assuming that the *selector* setting is either *term_only* or *term_and_log*. The input is placed into locations *first* through *last* - 1 of the *buffer* array, and echoed on the transcript file if appropriate.

This procedure is never called when *interaction* < *scroll_mode*.

```

define prompt_input(#) ≡
    begin wake_up_terminal; print(#); term_input;
    end { prints a string and gets a line of input }
procedure term_input; { gets a line from the terminal }
    var k: 0 .. buf_size; { index into buffer }
    begin update_terminal; { now the user sees the prompt for sure }
    if  $\neg$ input_ln(term_in, true) then
        begin limit  $\leftarrow$  0; fatal_error("End_of_file_on_the_terminal!");
        end;
    term_offset  $\leftarrow$  0; { the user's line ended with  $\langle$ return $\rangle$  }
    decr(selector); { prepare to echo the input }
    k  $\leftarrow$  first;
    while k < last do
        begin print_buffer(k)
        end;
    print_ln; incr(selector); { restore previous status }
    end;

```

73* The global variable *interaction* has four settings, representing increasing amounts of user interaction:

```

define batch_mode = 0 { omits all stops and omits terminal output }
define nonstop_mode = 1 { omits all stops }
define scroll_mode = 2 { omits error stops }
define error_stop_mode = 3 { stops at every opportunity to interact }
define unspecified_mode = 4 { extra value for command-line switch }
define print_err(#) ≡
    begin if interaction = error_stop_mode then wake_up_terminal;
    if file_line_error_style_p then print_file_line
    else print_nl("!␣");
    print(#);
    end

```

⟨Global variables 13⟩ +≡

```

interaction: batch_mode .. error_stop_mode; { current level of interaction }
interaction_option: batch_mode .. unspecified_mode; { set from command line }

```

74* ⟨Set initial values of key variables 21⟩ +≡

```

if interaction_option = unspecified_mode then interaction ← error_stop_mode
else interaction ← interaction_option;

```

81* The *jump_out* procedure just cuts across all active procedure levels. The body of *jump_out* simply calls ‘*close_files_and_terminate*;’ followed by a call on some system procedure that quietly terminates the program.

```

format noreturn ≡ procedure
define do_final_end ≡
    begin update_terminal; ready_already ← 0;
    if (history ≠ spotless) ∧ (history ≠ warning_issued) then uexit(1)
    else uexit(0);
    end

```

⟨Error handling procedures 78⟩ +≡

```

noreturn procedure jump_out;
    begin close_files_and_terminate; do_final_end;
    end;

```

82* Here now is the general *error* routine.

```

⟨Error handling procedures 78⟩ +≡
procedure error; { completes the job of error reporting }
  label continue, exit;
  var c: ASCII_code; { what the user types }
      s1, s2, s3, s4: integer; { used to save global variables when deleting tokens }
  begin if history < error_message_issued then history ← error_message_issued;
  print_char("."); show_context;
  if (halt_on_error_p) then
    begin { If close_files_and_terminate generates an error, we'll end up back here; just give up in that
      case. If files are truncated, too bad. }
    if (halting_on_error_p) then do_final_end; { quit immediately }
    halting_on_error_p ← true; history ← fatal_error_stop; jump_out;
    end;
  if interaction = error_stop_mode then ⟨Get user's advice and return 83⟩;
  incr(error_count);
  if error_count = 100 then
    begin print_nl("(That_makes_100_errors;_please_try_again.)"); history ← fatal_error_stop;
    jump_out;
    end;
  ⟨Put help message on the transcript file 90⟩;
exit: end;

```

84* It is desirable to provide an ‘E’ option here that gives the user an easy way to return from T_EX to the system editor, with the offending line ready to be edited. We do this by calling the external procedure *call_edit* with a pointer to the filename, its length, and the line number. However, here we just set up the variables that will be used as arguments, since we don't want to do the switch-to-editor until after TeX has closed its files.

There is a secret ‘D’ option available when the debugging routines haven't been commented out.

```

define edit_file ≡ input_stack[base_ptr]
⟨Interpret code c and return if done 84*⟩ ≡
  case c of
    "0", "1", "2", "3", "4", "5", "6", "7", "8", "9": if deletions_allowed then
      ⟨Delete c – "0" tokens and goto continue 88⟩;
  debug "D": begin debug_help; goto continue; end; gubed
  "E": if base_ptr > 0 then
    if input_stack[base_ptr].name_field ≥ 256 then
      begin edit_name_start ← str_start[edit_file.name_field];
      edit_name_length ← str_start[edit_file.name_field + 1] – str_start[edit_file.name_field];
      edit_line ← line; jump_out;
      end;
  "H": ⟨Print the help information and goto continue 89⟩;
  "I": ⟨Introduce new material from the terminal and return 87⟩;
  "Q", "R", "S": ⟨Change the interaction level and return 86⟩;
  "X": begin interaction ← scroll_mode; jump_out;
  end;
  othercases do_nothing
  endcases;
  ⟨Print the menu of available options 85⟩

```

This code is used in section 83.

93* The following procedure prints TEX's last words before dying.

```

define succumb ≡
  begin if interaction = error_stop_mode then interaction ← scroll_mode;
    { no more interaction }
  if log_opened then error;
  debug if interaction > batch_mode then debug_help;
  gubed
  history ← fatal_error_stop; jump_out; { irrecoverable error }
  end

⟨Error handling procedures 78⟩ +≡
noreturn procedure fatal_error(s : str_number); { prints s, and that's it }
  begin normalize_selector;
  print_err("Emergency_stop"); help1(s); succumb;
  end;

```

94* Here is the most dreaded error message.

```

⟨Error handling procedures 78⟩ +≡
noreturn procedure overflow(s : str_number; n : integer); { stop due to finiteness }
  begin normalize_selector; print_err("TeX_capacity_exceeded_sorry"); print(s);
  print_char("="); print_int(n); print_char("");
  help2("If_you_really_absolutely_need_more_capacity,"
  ("you_can_ask_a_wizard_to_enlarge_me."); succumb;
  end;

```

95* The program might sometime run completely amok, at which point there is no choice but to stop. If no previous error has been detected, that's bad news; a message is printed that is really intended for the TEX maintenance person instead of the user (unless the user has been particularly diabolical). The index entries for 'this can't happen' may help to pinpoint the problem.

```

⟨Error handling procedures 78⟩ +≡
noreturn procedure confusion(s : str_number); { consistency check violated; s tells where }
  begin normalize_selector;
  if history < error_message_issued then
    begin print_err("This_can't_happen"); print(s); print_char("");
    help1("I'm_broken_Please_show_this_to_someone_who_can_fix_can_fix");
    end
  else begin print_err("I_can't_go_on_meeting_you_like_this");
  help2("One_of_your_faux_pas_seems_to_have_wounded_me_deeply...")
  ("in_fact,I'm_barely_conscious_Please_fix_it_and_try_again.");
  end;
  succumb;
  end;

```

104* Physical sizes that a TeX user specifies for portions of documents are represented internally as scaled points. Thus, if we define an ‘sp’ (scaled point) as a unit equal to 2^{-16} printer’s points, every dimension inside of TeX is an integer number of sp. There are exactly 4,736,286.72 sp per inch. Users are not allowed to specify dimensions larger than $2^{30} - 1$ sp, which is a distance of about 18.892 feet (5.7583 meters); two such quantities can be added without overflow on a 32-bit computer.

The present implementation of TeX does not check for overflow when dimensions are added or subtracted. This could be done by inserting a few dozen tests of the form ‘if $x \geq '10000000000$ then *report_overflow*’, but the chance of overflow is so remote that such tests do not seem worthwhile.

TeX needs to do only a few arithmetic operations on scaled quantities, other than addition and subtraction, and the following subroutines do most of the work. A single computation might use several subroutine calls, and it is desirable to avoid producing multiple error messages in case of arithmetic overflow; so the routines set the global variable *arith_error* to *true* instead of reporting errors directly to the user. Another global variable, *remainder*, holds the remainder after a division.

define *remainder* \equiv *tex_remainder*

⟨Global variables 13⟩ +=

arith_error: *boolean*; { has arithmetic overflow occurred recently? }

remainder: *scaled*; { amount subtracted to get an exact division }

109* When TeX “packages” a list into a box, it needs to calculate the proportionality ratio by which the glue inside the box should stretch or shrink. This calculation does not affect TeX’s decision making, so the precise details of rounding, etc., in the glue calculation are not of critical importance for the consistency of results on different computers.

We shall use the type *glue_ratio* for such proportionality ratios. A glue ratio should take the same amount of memory as an *integer* (usually 32 bits) if it is to blend smoothly with TeX’s other data structures. Thus *glue_ratio* should be equivalent to *short_real* in some implementations of Pascal. Alternatively, it is possible to deal with glue ratios using nothing but fixed-point arithmetic; see *TUGboat* 3,1 (March 1982), 10–27. (But the routines cited there must be modified to allow negative glue ratios.)

define *set_glue_ratio_zero*(#) \equiv # \leftarrow 0.0 { store the representation of zero ratio }

define *set_glue_ratio_one*(#) \equiv # \leftarrow 1.0 { store the representation of unit ratio }

define *float*(#) \equiv # { convert from *glue_ratio* to type *real* }

define *unfloat*(#) \equiv # { convert from *real* to type *glue_ratio* }

define *float_constant*(#) \equiv #.0 { convert *integer* constant to *real* }

⟨Types in the outer block 18⟩ +=

128* **Packed data.** In order to make efficient use of storage space, TEX bases its major data structures on a *memory_word*, which contains either a (signed) integer, possibly scaled, or a (signed) *glue_ratio*, or a small number of fields that are one half or one quarter of the size used for storing integers.

If *x* is a variable of type *memory_word*, it contains up to four fields that can be referred to as follows:

<i>x.int</i>	(an <i>integer</i>)
<i>x.sc</i>	(a <i>scaled integer</i>)
<i>x.gr</i>	(a <i>glue_ratio</i>)
<i>x.hh.lh</i> , <i>x.hh.rh</i>	(two halfword fields)
<i>x.hh.b0</i> , <i>x.hh.b1</i> , <i>x.hh.rh</i>	(two quarterword fields, one halfword field)
<i>x.qqqq.b0</i> , <i>x.qqqq.b1</i> , <i>x.qqqq.b2</i> , <i>x.qqqq.b3</i>	(four quarterword fields)

This is somewhat cumbersome to write, and not very readable either, but macros will be used to make the notation shorter and more transparent. The Pascal code below gives a formal definition of *memory_word* and its subsidiary types, using packed variant records. TEX makes no assumptions about the relative positions of the fields within a word.

Since we are assuming 32-bit integers, a halfword must contain at least 16 bits, and a quarterword must contain at least 8 bits. But it doesn't hurt to have more bits; for example, with enough 36-bit words you might be able to have *mem_max* as large as 262142, which is eight times as much memory as anybody had during the first four years of TEX's existence.

N.B.: Valuable memory space will be dreadfully wasted unless TEX is compiled by a Pascal that packs all of the *memory_word* variants into the space of a single integer. This means, for example, that *glue_ratio* words should be *short_real* instead of *real* on some computers. Some Pascal compilers will pack an integer whose subrange is '0 .. 255' into an eight-bit field, but others insist on allocating space for an additional sign bit; on such systems you can get 256 values into a quarterword only if the subrange is '-128 .. 127'.

The present implementation tries to accommodate as many variations as possible, so it makes few assumptions. If integers having the subrange '*min_quarterword* .. *max_quarterword*' can be packed into a quarterword, and if integers having the subrange '*min_halfword* .. *max_halfword*' can be packed into a halfword, everything should work satisfactorily.

It is usually most efficient to have *min_quarterword* = *min_halfword* = 0, so one should try to achieve this unless it causes a severe problem. The values defined here are recommended for most 32-bit computers.

```

define min_quarterword = 0 {smallest allowable value in a quarterword }
define max_quarterword = 255 {largest allowable value in a quarterword }
define min_halfword ≡ -"FFFFFFF {smallest allowable value in a halfword }
define max_halfword ≡ "FFFFFFF {largest allowable value in a halfword }

```

129* Here are the inequalities that the quarterword and halfword values must satisfy (or rather, the inequalities that they mustn't satisfy):

⟨ Check the "constant" values for consistency 14 ⟩ +≡

```

init if (mem_min ≠ mem_bot) ∨ (mem_max ≠ mem_top) then bad ← 10;
tini
if (mem_min > mem_bot) ∨ (mem_max < mem_top) then bad ← 10;
if (min_quarterword > 0) ∨ (max_quarterword < 127) then bad ← 11;
if (min_halfword > 0) ∨ (max_halfword < 32767) then bad ← 12;
if (min_quarterword < min_halfword) ∨ (max_quarterword > max_halfword) then bad ← 13;
if (mem_bot - sup_main_memory < min_halfword) ∨ (mem_top + sup_main_memory ≥ max_halfword)
then bad ← 14;
if (max_font_max < min_halfword) ∨ (max_font_max > max_halfword) then bad ← 15;
if font_max > font_base + max_font_max then bad ← 16;
if (save_size > max_halfword) ∨ (max_strings > max_halfword) then bad ← 17;
if buf_size > max_halfword then bad ← 18;
if max_quarterword - min_quarterword < 255 then bad ← 19;

```

130* The operation of adding or subtracting *min_quarterword* occurs quite frequently in TeX, so it is convenient to abbreviate this operation by using the macros *qi* and *qo* for input and output to and from quarterword format.

The inner loop of TeX will run faster with respect to compilers that don't optimize expressions like ' $x + 0$ ' and ' $x - 0$ ', if these macros are simplified in the obvious way when *min_quarterword* = 0. So they have been simplified here in the obvious way.

The WEB source for TeX defines $hi(\#) \equiv \# + min_halfword$ which can be simplified when *min_halfword* = 0. The Web2C implementation of TeX can use $hi(\#) \equiv \#$ together with *min_halfword* < 0 as long as *max_halfword* is sufficiently large.

```
define qi(#)  $\equiv$  # { to put an eight_bits item into a quarterword }
define qo(#)  $\equiv$  # { to take an eight_bits item from a quarterword }
define hi(#)  $\equiv$  # { to put a sixteen-bit item into a halfword }
define ho(#)  $\equiv$  # { to take a sixteen-bit item from a halfword }
```

131* The reader should study the following definitions closely:

```
define sc  $\equiv$  int { scaled data is equivalent to integer }
```

<Types in the outer block 18> + \equiv

```
quarterword = min_quarterword .. max_quarterword; halfword = min_halfword .. max_halfword;
```

```
two_choices = 1 .. 2; { used when there are two variants in a record }
```

```
four_choices = 1 .. 4; { used when there are four variants in a record }
```

```
#include "texmfmem.h"; word_file = gzFile;
```

134* The *mem* array is divided into two regions that are allocated separately, but the dividing line between these two regions is not fixed; they grow together until finding their “natural” size in a particular job. Locations less than or equal to *lo_mem_max* are used for storing variable-length records consisting of two or more words each. This region is maintained using an algorithm similar to the one described in exercise 2.5–19 of *The Art of Computer Programming*. However, no size field appears in the allocated nodes; the program is responsible for knowing the relevant size when a node is freed. Locations greater than or equal to *hi_mem_min* are used for storing one-word records; a conventional AVAIL stack is used for allocation in this region.

Locations of *mem* between *mem_bot* and *mem_top* may be dumped as part of preloaded format files, by the INITEX preprocessor. Production versions of TEX may extend the memory at both ends in order to provide more space; locations between *mem_min* and *mem_bot* are always used for variable-size nodes, and locations between *mem_top* and *mem_max* are always used for single-word nodes.

The key pointers that govern *mem* allocation have a prescribed order:

$$\text{null} \leq \text{mem_min} \leq \text{mem_bot} < \text{lo_mem_max} < \text{hi_mem_min} < \text{mem_top} \leq \text{mem_end} \leq \text{mem_max}.$$

Empirical tests show that the present implementation of TEX tends to spend about 9% of its running time allocating nodes, and about 6% deallocating them after their use.

⟨Global variables 13⟩ +≡

yzmem: ↑*memory_word*; { the big dynamic storage area }
zmem: ↑*memory_word*; { the big dynamic storage area }
lo_mem_max: *pointer*; { the largest location of variable-size memory in use }
hi_mem_min: *pointer*; { the smallest location of one-word memory in use }

143* A call to *get_node* with argument *s* returns a pointer to a new node of size *s*, which must be 2 or more. The *link* field of the first word of this new node is set to null. An overflow stop occurs if no suitable space exists.

If *get_node* is called with $s = 2^{30}$, it simply merges adjacent free areas and returns the value *max_halfword*.

function *get_node*(*s* : *integer*): *pointer*; { variable-size node allocation }

label *found*, *exit*, *restart*;

var *p*: *pointer*; { the node currently under inspection }

q: *pointer*; { the node physically after node *p* }

r: *integer*; { the newly allocated node, or a candidate for this honor }

t: *integer*; { temporary register }

begin *restart*: *p* ← *rover*; { start at some free node in the ring }

repeat ⟨Try to allocate within node *p* and its physical successors, and **goto** *found* if allocation was possible 145⟩;

p ← *rlink*(*p*); { move to the next node in the ring }

until *p* = *rover*; { repeat until the whole list has been traversed }

if *s* = '1000000000' **then**

begin *get_node* ← *max_halfword*; **return**;

end;

if *lo_mem_max* + 2 < *hi_mem_min* **then**

if *lo_mem_max* + 2 ≤ *mem_bot* + *max_halfword* **then**

⟨Grow more variable-size memory and **goto** *restart* 144⟩;

overflow("main_memory_size", *mem_max* + 1 - *mem_min*); { sorry, nothing satisfactory is left }

found: *link*(*r*) ← *null*; { this node is now nonempty }

stat *var_used* ← *var_used* + *s*; { maintain usage statistics }

tats

⟨Initialize bigger nodes with SyncTEX information 1917*⟩;

get_node ← *r*;

exit: **end**;

153* An *hlist_node* stands for a box that was made from a horizontal list. Each *hlist_node* is seven words long, and contains the following fields (in addition to the mandatory *type* and *link*, which we shall not mention explicitly when discussing the other node types): The *height* and *width* and *depth* are scaled integers denoting the dimensions of the box. There is also a *shift_amount* field, a scaled integer indicating how much this box should be lowered (if it appears in a horizontal list), or how much it should be moved to the right (if it appears in a vertical list). There is a *list_ptr* field, which points to the beginning of the list from which this box was fabricated; if *list_ptr* is *null*, the box is empty. Finally, there are three fields that represent the setting of the glue: *glue_set(p)* is a word of type *glue_ratio* that represents the proportionality constant for glue setting; *glue_sign(p)* is *stretching* or *shrinking* or *normal* depending on whether or not the glue should stretch or shrink or remain rigid; and *glue_order(p)* specifies the order of infinity to which glue setting applies (*normal*, *fil*, *fill*, or *filll*). The *subtype* field is not used in TEX. In ε -TEX the *subtype* field records the box direction mode *box_lr*.

```

define synctex_field_size = 2 { Declare the SyncTEX field size to store the SyncTEX information: 2
    integers for file tag and line }
define sync_tag(#)  $\equiv$  mem[# - synctex_field_size].int { The tag subfield }
define sync_line(#)  $\equiv$  mem[# - synctex_field_size + 1].int { The line subfield }
define hlist_node = 0 { type of hlist nodes }
define box_node_size = 7 + synctex_field_size { number of words to allocate for a box node }
define width_offset = 1 { position of width field in a box node }
define depth_offset = 2 { position of depth field in a box node }
define height_offset = 3 { position of height field in a box node }
define width(#)  $\equiv$  mem[# + width_offset].sc { width of the box, in sp }
define depth(#)  $\equiv$  mem[# + depth_offset].sc { depth of the box, in sp }
define height(#)  $\equiv$  mem[# + height_offset].sc { height of the box, in sp }
define shift_amount(#)  $\equiv$  mem[# + 4].sc { repositioning distance, in sp }
define list_offset = 5 { position of list_ptr field in a box node }
define list_ptr(#)  $\equiv$  link(# + list_offset) { beginning of the list inside the box }
define glue_order(#)  $\equiv$  subtype(# + list_offset) { applicable order of infinity }
define glue_sign(#)  $\equiv$  type(# + list_offset) { stretching or shrinking }
define normal = 0 { the most common case when several cases are named }
define stretching = 1 { glue setting applies to the stretch components }
define shrinking = 2 { glue setting applies to the shrink components }
define glue_offset = 6 { position of glue_set in a box node }
define glue_set(#)  $\equiv$  mem[# + glue_offset].gr { a word of type glue_ratio for glue setting }

```

156* A *rule_node* stands for a solid black rectangle; it has *width*, *depth*, and *height* fields just as in an *hlist_node*. However, if any of these dimensions is -2^{30} , the actual value will be determined by running the rule up to the boundary of the innermost enclosing box. This is called a “running dimension.” The *width* is never running in an hlist; the *height* and *depth* are never running in a vlist.

```

define rule_node = 2 { type of rule nodes }
define rule_node_size = 4 + synctex_field_size { number of words to allocate for a rule node }
define null_flag  $\equiv$   $-1000000000$  {  $-2^{30}$ , signifies a missing item }
define is_running(#)  $\equiv$  (# = null_flag) { tests for a running dimension }

```

159* A *mark_node* has a *mark_ptr* field that points to the reference count of a token list that contains the user's `\mark` text. In addition there is a *mark_class* field that contains the mark class.

```

define mark_node = 4 { type of a mark node }
define small_node_size = 2 { number of words to allocate for most node types }
define medium_node_size = small_node_size + synctex_field_size { number of words to allocate for
    synchronized node types like math, kern, glue and penalty nodes }
define mark_ptr(#)  $\equiv$  link(# + 1) { head of the token list for a mark }
define mark_class(#)  $\equiv$  info(# + 1) { the mark class }

```

162* The *new_ligature* function creates a ligature node having given contents of the *font*, *character*, and *lig_ptr* fields. We also have a *new_lig_item* function, which returns a two-word node having a given *character* field. Such nodes are used for temporary processing as ligatures are being created.

function *new_ligature*(*f* : *internal_font_number*; *c* : *quarterword*; *q* : *pointer*): *pointer*;

```

var p: pointer; { the new node }
begin p  $\leftarrow$  get_node(small_node_size); type(p)  $\leftarrow$  ligature_node; font(lig_char(p))  $\leftarrow$  f;
character(lig_char(p))  $\leftarrow$  c; lig_ptr(p)  $\leftarrow$  q; subtype(p)  $\leftarrow$  0; new_ligature  $\leftarrow$  p;
end;

```

function *new_lig_item*(*c* : *quarterword*): *pointer*;

```

var p: pointer; { the new node }
begin p  $\leftarrow$  get_node(small_node_size); character(p)  $\leftarrow$  c; lig_ptr(p)  $\leftarrow$  null; new_lig_item  $\leftarrow$  p;
end;

```

165* A *math_node*, which occurs only in horizontal lists, appears before and after mathematical formulas. The *subtype* field is *before* before the formula and *after* after it. There is a *width* field, which represents the amount of surrounding space inserted by `\mathsurround`.

In addition a *math_node* with *subtype* > *after* and *width* = 0 will be (ab)used to record a regular *math_node* reinserted after being discarded at a line break or one of the text direction primitives (`\beginL`, `\endL`, `\beginR`, and `\endR`).

```

define math_node = 9 { type of a math node }
define before = 0 { subtype for math node that introduces a formula }
define after = 1 { subtype for math node that winds up a formula }
define M_code = 2
define begin_M_code = M_code + before { subtype for \beginM node }
define end_M_code = M_code + after { subtype for \endM node }
define L_code = 4
define begin_L_code = L_code + begin_M_code { subtype for \beginL node }
define end_L_code = L_code + end_M_code { subtype for \endL node }
define R_code = L_code + L_code
define begin_R_code = R_code + begin_M_code { subtype for \beginR node }
define end_R_code = R_code + end_M_code { subtype for \endR node }
define end_LR(#)  $\equiv$  odd(subtype(#))
define end_LR_type(#)  $\equiv$  (L_code * (subtype(#) div L_code) + end_M_code)
define begin_LR_type(#)  $\equiv$  (# - after + before)

```

function *new_math*(*w* : *scaled*; *s* : *small_number*): *pointer*;

```

var p: pointer; { the new node }
begin p  $\leftarrow$  get_node(medium_node_size); type(p)  $\leftarrow$  math_node; subtype(p)  $\leftarrow$  s; width(p)  $\leftarrow$  w;
new_math  $\leftarrow$  p;
end;

```

170* And here's a function that creates a glue node for a given parameter identified by its code number; for example, `new_param_glue(line_skip_code)` returns a pointer to a glue node for the current `\lineskip`.

```
function new_param_glue(n : small_number): pointer;
  var p: pointer; { the new node }
      q: pointer; { the glue specification }
  begin p ← get_node(medium_node_size); type(p) ← glue_node; subtype(p) ← n + 1; leader_ptr(p) ← null;
  q ← ⟨ Current mem equivalent of glue parameter number n 242 ⟩; glue_ptr(p) ← q;
  incr(glue_ref_count(q)); new_param_glue ← p;
  end;
```

171* Glue nodes that are more or less anonymous are created by `new_glue`, whose argument points to a glue specification.

```
function new_glue(q : pointer): pointer;
  var p: pointer; { the new node }
  begin p ← get_node(medium_node_size); type(p) ← glue_node; subtype(p) ← normal;
  leader_ptr(p) ← null; glue_ptr(p) ← q; incr(glue_ref_count(q)); new_glue ← p;
  end;
```

174* The `new_kern` function creates a kern node having a given width.

```
function new_kern(w : scaled): pointer;
  var p: pointer; { the new node }
  begin p ← get_node(medium_node_size); type(p) ← kern_node; subtype(p) ← normal; width(p) ← w;
  new_kern ← p;
  end;
```

176* Anyone who has been reading the last few sections of the program will be able to guess what comes next.

```
function new_penalty(m : integer): pointer;
  var p: pointer; { the new node }
  begin p ← get_node(medium_node_size); type(p) ← penalty_node; subtype(p) ← 0;
  { the subtype is not used }
  penalty(p) ← m; new_penalty ← p;
  end;
```

183* If TEX is extended improperly, the *mem* array might get screwed up. For example, some pointers might be wrong, or some “dead” nodes might not have been freed when the last reference to them disappeared. Procedures *check_mem* and *search_mem* are available to help diagnose such problems. These procedures make use of two arrays called *free* and *was_free* that are present only if TEX’s debugging routines have been included. (You may want to decrease the size of *mem* while you are debugging.)

define *free* \equiv *free_arr*

⟨Global variables 13⟩ +≡

{ The debug memory arrays have not been allocated yet. }

debug *free*: **packed array** [0 .. 9] **of** *boolean*; { free cells }

was_free: **packed array** [0 .. 9] **of** *boolean*; { previously free cells }

was_mem_end, *was_lo_max*, *was_hi_min*: *pointer*; { previous *mem_end*, *lo_mem_max*, and *hi_mem_min* }

panicking: *boolean*; { do we want to check memory constantly? }

gubed

192* Boxes, rules, inserts, whatsits, marks, and things in general that are sort of “complicated” are indicated only by printing ‘[]’.

```

procedure print_font_identifier(f : internal_font_number);
  begin if pdf_font_blink[f] = null_font then print_esc(font_id_text(f))
  else print_esc(font_id_text(pdf_font_blink[f]));
  if pdf_tracing_fonts > 0 then
    begin print("□"); print(font_name[f]);
    if font_size[f] ≠ font_dsize[f] then
      begin print("@""); print_scaled(font_size[f]); print("pt");
      end;
      print("");
    end
  else if pdf_font_expand_ratio[f] ≠ 0 then
    begin print("□(");
    if pdf_font_expand_ratio[f] > 0 then print("+");
    print_int(pdf_font_expand_ratio[f]); print(")");
    end;
  end;
procedure short_display(p : integer); { prints highlights of list p }
  var n : integer; { for replacement counts }
  begin while p > mem_min do
    begin if is_char_node(p) then
      begin if p ≤ mem_end then
        begin if font(p) ≠ font_in_short_display then
          begin if (font(p) > font_max) then print_char("*")
          else print_font_identifier(font(p));
          print_char("□"); font_in_short_display ← font(p);
          end;
          print_ASCII(go(character(p)));
        end;
      end
    else { Print a short indication of the contents of node p 193 };
    p ← link(p);
  end;
end;

```


194* The *show_node_list* routine requires some auxiliary subroutines: one to print a font-and-character combination, one to print a token list without its reference count, and one to print a rule dimension.

```

procedure print_font_and_char(p : integer); { prints char_node data }
  begin if p > mem_end then print_esc("CLOBBBERED.")
  else begin if (font(p) > font_max) then print_char("*")
    else print_font_identifier(font(p));
    print_char("□"); print_ASCII(qo(character(p)));
  end;
end;

procedure print_mark(p : integer); { prints token list data in braces }
  begin print_char("{");
  if (p < hi_mem_min) ∨ (p > mem_end) then print_esc("CLOBBBERED.")
  else show_token_list(link(p), null, max_print_line - 10);
  print_char("}");
end;

procedure print_rule_dimen(d : scaled); { prints dimension in rule node }
  begin if is_running(d) then print_char("*")
  else print_scaled(d);
end;

```

204* The code will have to change in this place if *glue_ratio* is a structured type instead of an ordinary *real*. Note that this routine should avoid arithmetic errors even if the *glue_set* field holds an arbitrary random value. The following code assumes that a properly formed nonzero *real* number has absolute value 2^{20} or more when it is regarded as an integer; this precaution was adequate to prevent floating point underflow on the author's computer.

```

⟨ Display the value of glue_set(p) 204* ⟩ ≡
  g ← float(glue_set(p));
  if (g ≠ float_constant(0)) ∧ (glue_sign(p) ≠ normal) then
    begin print(" ,□glue□set□");
    if glue_sign(p) = shrinking then print("□"); { The Unix pc folks removed this restriction with a
      remark that invalid bit patterns were vanishingly improbable, so we follow their example without
      really understanding it. if abs(mem[p + glue_offset].int) < '4000000 then print('?.?') else }
    if fabs(g) > float_constant(20000) then
      begin if g > float_constant(0) then print_char(">")
      else print("□<□");
      print_glue(20000 * unity, glue_order(p), 0);
      end
    else print_glue(round(unity * g), glue_order(p), 0);
    end

```

This code is used in section 202.

220* Now we are ready to delete any node list, recursively. In practice, the nodes deleted are usually charnodes (about 2/3 of the time), and they are glue nodes in about half of the remaining cases.

```

procedure flush_node_list(p : pointer); { erase list of nodes starting at p }
  label done; { go here when node p has been freed }
  var q: pointer; { successor to node p }
  begin while p ≠ null do
    begin q ← link(p);
    if is_char_node(p) then free_avail(p)
    else begin case type(p) of
      hlist_node, vlist_node, unset_node: begin flush_node_list(list_ptr(p)); free_node(p, box_node_size);
        goto done;
      end;
      rule_node: begin free_node(p, rule_node_size); goto done;
      end;
      ins_node: begin flush_node_list(ins_ptr(p)); delete_glue_ref(split_top_ptr(p));
        free_node(p, ins_node_size); goto done;
      end;
      whatsit_node: ⟨ Wipe out the whatsit node p and goto done 1606 ⟩;
      glue_node: begin fast_delete_glue_ref(glue_ptr(p));
        if leader_ptr(p) ≠ null then flush_node_list(leader_ptr(p));
        free_node(p, medium_node_size); goto done;
      end;
      kern_node, math_node, penalty_node: begin free_node(p, medium_node_size); goto done;
      end;
      margin_kern_node: begin free_avail(margin_char(p)); free_node(p, margin_kern_node_size);
        goto done;
      end;
      ligature_node: flush_node_list(lig_ptr(p));
      mark_node: delete_token_ref(mark_ptr(p));
      disc_node: begin flush_node_list(pre_break(p)); flush_node_list(post_break(p));
        end;
      adjust_node: flush_node_list(adjust_ptr(p));
      ⟨ Cases of flush_node_list that arise in mlists only 874 ⟩
      othercases confusion("flushing")
      endcases;
      free_node(p, small_node_size);
    done: end;
    p ← q;
  end;
end;

```

```

224* ⟨ Case statement to copy different types and set words to the number of initial words not yet
copied 224\* ⟩ ≡
case type(p) of
  hlist_node, vlist_node, unset_node: begin r ← get_node(box_node_size);
    ⟨ Copy the box SyncTEX information 1936\* ⟩;
    mem[r + 6] ← mem[p + 6]; mem[r + 5] ← mem[p + 5]; { copy the last two words }
    list_ptr(r) ← copy_node_list(list_ptr(p)); { this affects mem[r + 5] }
    words ← 5;
  end;
  rule_node: begin r ← get_node(rule_node_size); words ← rule_node_size − synctex_field_size;
    { SyncTEX: do not let TEX copy the SyncTEX information }
    ⟨ Copy the rule SyncTEX information 1937\* ⟩;
  end;
  ins_node: begin r ← get_node(ins_node_size); mem[r + 4] ← mem[p + 4]; add_glue_ref(split_top_ptr(p));
    ins_ptr(r) ← copy_node_list(ins_ptr(p)); { this affects mem[r + 4] }
    words ← ins_node_size − 1;
  end;
  whatsit_node: ⟨ Make a partial copy of the whatsit node p and make r point to it; set words to the
number of initial words not yet copied 1605 ⟩;
  glue_node: begin r ← get_node(medium_node_size); add_glue_ref(glue_ptr(p));
    ⟨ Copy the medium sized node SyncTEX information 1938\* ⟩;
    glue_ptr(r) ← glue_ptr(p); leader_ptr(r) ← copy_node_list(leader_ptr(p));
  end;
  kern_node, math_node, penalty_node: begin r ← get_node(medium_node_size);
    words ← medium_node_size;
  end;
  margin_kern_node: begin r ← get_node(margin_kern_node_size); fast_get_avail(margin_char(r));
    font(margin_char(r)) ← font(margin_char(p));
    character(margin_char(r)) ← character(margin_char(p)); words ← small_node_size;
  end;
  ligature_node: begin r ← get_node(small_node_size); mem[lig_char(r)] ← mem[lig_char(p)];
    { copy font and character }
    lig_ptr(r) ← copy_node_list(lig_ptr(p));
  end;
  disc_node: begin r ← get_node(small_node_size); pre_break(r) ← copy_node_list(pre_break(p));
    post_break(r) ← copy_node_list(post_break(p));
  end;
  mark_node: begin r ← get_node(small_node_size); add_token_ref(mark_ptr(p));
    words ← small_node_size;
  end;
  adjust_node: begin r ← get_node(small_node_size); adjust_ptr(r) ← copy_node_list(adjust_ptr(p));
    end; { words = 1 = small_node_size − 1 }
othercases confusion("copying")
endcases

```

This code is used in section [223](#).

227* The next codes are special; they all relate to mode-independent assignment of values to T_EX's internal registers or tables. Codes that are *max_internal* or less represent internal quantities that might be expanded by `\the`.

```

define toks_register = 71 {token list register ( \toks )}
define assign_toks = 72 {special token list ( \output, \everypar, etc. )}
define assign_int = 73 {user-defined integer ( \tolerance, \day, etc. )}
define assign_dimen = 74 {user-defined length ( \hsize, etc. )}
define assign_glue = 75 {user-defined glue ( \baselineskip, etc. )}
define assign_mu_glue = 76 {user-defined muglue ( \thinmuskip, etc. )}
define assign_font_dimen = 77 {user-defined font dimension ( \fontdimen )}
define assign_font_int = 78 {user-defined font integer ( \hyphenchar, \skewchar )}
define set_aux = 79 {specify state info ( \spacefactor, \prevdepth )}
define set_prev_graf = 80 {specify state info ( \prevgraf )}
define set_page_dimen = 81 {specify state info ( \pagegoal, etc. )}
define set_page_int = 82 {specify state info ( \deadcycles, \insertpenalties )}
    {( or \interactionmode )}
define set_box_dimen = 83 {change dimension of box ( \wd, \ht, \dp )}
define set_shape = 84 {specify fancy paragraph shape ( \parshape )}
    {(or \interlinepenalties, etc. )}
define def_code = 85 {define a character code ( \catcode, etc. )}
define def_family = 86 {declare math fonts ( \textfont, etc. )}
define set_font = 87 {set current font ( font identifiers )}
define def_font = 88 {define a font file ( \font )}
define register = 89 {internal register ( \count, \dimen, etc. )}
define max_internal = 89 {the largest code that can follow \the}
define advance = 90 {advance a register or parameter ( \advance )}
define multiply = 91 {multiply a register or parameter ( \multiply )}
define divide = 92 {divide a register or parameter ( \divide )}
define prefix = 93 {qualify a definition ( \global, \long, \outer )}
    {( or \protected )}
define let = 94 {assign a command code ( \let, \futurelet )}
define shorthand_def = 95 {code definition ( \chardef, \countdef, etc. )}
    {or \charsubdef}
define read_to_cs = 96 {read into a control sequence ( \read )}
    {( or \readline )}
define def = 97 {macro definition ( \def, \gdef, \xdef, \edef )}
define set_box = 98 {set a box ( \setbox )}
define hyph_data = 99 {hyphenation data ( \hyphenation, \patterns )}
define set_interaction = 100 {define level of interaction ( \batchmode, etc. )}
define letterspace_font = 101 {letterspace a font ( \letterspacefont )}
define pdf_copy_font = 102 {create a new font instance ( \pdfcopyfont )}
define partoken_name = 103 {set par.token name}
define max_command = 103 {the largest command code seen at big_switch}

```

229* **The semantic nest.** TEX is typically in the midst of building many lists at once. For example, when a math formula is being processed, TEX is in math mode and working on an mlist; this formula has temporarily interrupted TEX from being in horizontal mode and building the hlist of a paragraph; and this paragraph has temporarily interrupted TEX from being in vertical mode and building the vlist for the next page of a document. Similarly, when a \vbox occurs inside of an \hbox, TEX is temporarily interrupted from working in restricted horizontal mode, and it enters internal vertical mode. The “semantic nest” is a stack that keeps track of what lists and modes are currently suspended.

At each level of processing we are in one of six modes:

vmode stands for vertical mode (the page builder);

hmode stands for horizontal mode (the paragraph builder);

mmode stands for displayed formula mode;

–*vmode* stands for internal vertical mode (e.g., in a \vbox);

–*hmode* stands for restricted horizontal mode (e.g., in an \hbox);

–*mmode* stands for math formula mode (not displayed).

The mode is temporarily set to zero while processing \write texts.

Numeric values are assigned to *vmode*, *hmode*, and *mmode* so that TEX’s “big semantic switch” can select the appropriate thing to do by computing the value $abs(mode) + cur_cmd$, where *mode* is the current mode and *cur_cmd* is the current command code.

```
define vmode = 1 { vertical mode }
```

```
define hmode = vmode + max_command + 1 { horizontal mode }
```

```
define mmode = hmode + max_command + 1 { math mode }
```

```
procedure print_mode(m : integer); { prints the mode represented by m }
```

```
begin if m > 0 then
```

```
  case m div (max_command + 1) of
```

```
    0: print("vertical_mode");
```

```
    1: print("horizontal_mode");
```

```
    2: print("display_math_mode");
```

```
  end
```

```
else if m = 0 then print("no_mode")
```

```
  else case (-m) div (max_command + 1) of
```

```
    0: print("internal_vertical_mode");
```

```
    1: print("restricted_horizontal_mode");
```

```
    2: print("math_mode");
```

```
  end;
```

```
end;
```

```
procedure print_in_mode(m : integer); { prints the mode represented by m }
```

```
begin if m > 0 then
```

```
  case m div (max_command + 1) of
```

```
    0: print("^in_vertical_mode");
```

```
    1: print("^in_horizontal_mode");
```

```
    2: print("^in_display_math_mode");
```

```
  end
```

```
else if m = 0 then print("^in_no_mode")
```

```
  else case (-m) div (max_command + 1) of
```

```
    0: print("^in_internal_vertical_mode");
```

```
    1: print("^in_restricted_horizontal_mode");
```

```
    2: print("^in_math_mode");
```

```
  end;
```

```
end;
```

```

231* define mode  $\equiv$  cur_list.mode_field { current mode }
define head  $\equiv$  cur_list.head_field { header node of current list }
define tail  $\equiv$  cur_list.tail_field { final node on current list }
define eTeX_aux  $\equiv$  cur_list.eTeX_aux_field { auxiliary data for  $\varepsilon$ -TeX }
define LR_save  $\equiv$  eTeX_aux { LR stack when a paragraph is interrupted }
define LR_box  $\equiv$  eTeX_aux { prototype box for display }
define delim_ptr  $\equiv$  eTeX_aux { most recent left or right noad of a math left group }
define prev_graf  $\equiv$  cur_list.pg_field { number of paragraph lines accumulated }
define aux  $\equiv$  cur_list.aux_field { auxiliary data about the current list }
define prev_depth  $\equiv$  aux.sc { the name of aux in vertical mode }
define space_factor  $\equiv$  aux.hh.lh { part of aux in horizontal mode }
define clang  $\equiv$  aux.hh.rh { the other part of aux in horizontal mode }
define incompleat_noad  $\equiv$  aux.int { the name of aux in math mode }
define mode_line  $\equiv$  cur_list.ml_field { source file line number at beginning of list }

```

⟨Global variables 13⟩ +≡

```

nest:  $\uparrow$ list_state_record;
nest_ptr: 0 .. nest_size; { first unused location of nest }
max_nest_stack: 0 .. nest_size; { maximum of nest_ptr when pushing }
cur_list: list_state_record; { the “top” semantic state }
shown_mode:  $-mmode$  .. mmode; { most recent mode shown by \tracingcommands }
save_tail: pointer; { save tail so we can examine whether we have an auto kern before a glue }
prev_tail: pointer; { value of tail before the last call to tail.append }

```

233* We will see later that the vertical list at the bottom semantic level is split into two parts; the “current page” runs from *page_head* to *page_tail*, and the “contribution list” runs from *contrib_head* to *tail* of semantic level zero. The idea is that contributions are first formed in vertical mode, then “contributed” to the current page (during which time the page-breaking decisions are made). For now, we don’t need to know any more details about the page-building process.

⟨Set initial values of key variables 21⟩ +≡

```

nest_ptr  $\leftarrow$  0; max_nest_stack  $\leftarrow$  0; mode  $\leftarrow$  vmode; head  $\leftarrow$  contrib_head; tail  $\leftarrow$  contrib_head;
eTeX_aux  $\leftarrow$  null; save_tail  $\leftarrow$  null; prev_depth  $\leftarrow$  ignore_depth; mode_line  $\leftarrow$  0; prev_graf  $\leftarrow$  0;
shown_mode  $\leftarrow$  0;

```

{ The following piece of code is a copy of module 991: }

```

page_contents  $\leftarrow$  empty; page_tail  $\leftarrow$  page_head; { link(page_head)  $\leftarrow$  null; }
last_glue  $\leftarrow$  max_halfword; last_penalty  $\leftarrow$  0; last_kern  $\leftarrow$  0; last_node_type  $\leftarrow$   $-1$ ; page_depth  $\leftarrow$  0;
page_max_depth  $\leftarrow$  0;

```

```

237* ⟨ Show the auxiliary field, a 237* ⟩ ≡
  case abs(m) div (max_command + 1) of
0: begin print_nl("prevdepth_");
  if a.sc ≤ pdf_ignored_dimen then print("ignored")
  else print_scaled(a.sc);
  if nest[p].pg_field ≠ 0 then
    begin print("_prevgraf_"); print_int(nest[p].pg_field);
    if nest[p].pg_field ≠ 1 then print("_lines")
    else print("_line");
    end;
  end;
1: begin print_nl("spacefactor_"); print_int(a.hh.lh);
  if m > 0 then if a.hh.rh > 0 then
    begin print("_current_language_"); print_int(a.hh.rh); end;
  end;
2: if a.int ≠ null then
  begin print("this_will_begin_denominator_of:"); show_box(a.int); end;
end { there are no other cases }

```

This code is used in section 236.

238* **The table of equivalents.** Now that we have studied the data structures for TeX's semantic routines, we ought to consider the data structures used by its syntactic routines. In other words, our next concern will be the tables that TeX looks at when it is scanning what the user has written.

The biggest and most important such table is called *eqtb*. It holds the current “equivalents” of things; i.e., it explains what things mean or what their current values are, for all quantities that are subject to the nesting structure provided by TeX's grouping mechanism. There are six parts to *eqtb*:

- 1) *eqtb*[*active_base* .. (*hash_base* - 1)] holds the current equivalents of single-character control sequences.
- 2) *eqtb*[*hash_base* .. (*glue_base* - 1)] holds the current equivalents of multiletter control sequences.
- 3) *eqtb*[*glue_base* .. (*local_base* - 1)] holds the current equivalents of glue parameters like the current *baselineskip*.
- 4) *eqtb*[*local_base* .. (*int_base* - 1)] holds the current equivalents of local halfword quantities like the current box registers, the current “catcodes,” the current font, and a pointer to the current paragraph shape. Additionally region 4 contains the table with MLTeX's character substitution definitions.
- 5) *eqtb*[*int_base* .. (*dimen_base* - 1)] holds the current equivalents of fullword integer parameters like the current hyphenation penalty.
- 6) *eqtb*[*dimen_base* .. *eqtb_size*] holds the current equivalents of fullword dimension parameters like the current *hsize* or amount of hanging indentation.

Note that, for example, the current amount of *baselineskip* glue is determined by the setting of a particular location in region 3 of *eqtb*, while the current meaning of the control sequence ‘\baselineskip’ (which might have been changed by `\def` or `\let`) appears in region 2.

240* Many locations in *eqtb* have symbolic names. The purpose of the next paragraphs is to define these names, and to set up the initial values of the equivalents.

In the first region we have 256 equivalents for “active characters” that act as control sequences, followed by 256 equivalents for single-character control sequences.

Then comes region 2, which corresponds to the hash table that we will define later. The maximum address in this region is used for a dummy control sequence that is perpetually undefined. There also are several locations for control sequences that are perpetually defined (since they are used in error recovery).

```

define active_base = 1 {beginning of region 1, for active character equivalents }
define single_base = active_base + 256 {equivalents of one-character control sequences }
define null_cs = single_base + 256 {equivalent of \csname\endcsname }
define hash_base = null_cs + 1 {beginning of region 2, for the hash table }
define frozen_control_sequence = hash_base + hash_size {for error recovery }
define frozen_protection = frozen_control_sequence {inaccessible but definable }
define frozen_cr = frozen_control_sequence + 1 {permanent '\cr' }
define frozen_end_group = frozen_control_sequence + 2 {permanent '\endgroup' }
define frozen_right = frozen_control_sequence + 3 {permanent '\right' }
define frozen_fi = frozen_control_sequence + 4 {permanent '\fi' }
define frozen_end_template = frozen_control_sequence + 5 {permanent '\endtemplate' }
define frozen_endv = frozen_control_sequence + 6 {second permanent '\endtemplate' }
define frozen_relax = frozen_control_sequence + 7 {permanent '\relax' }
define end_write = frozen_control_sequence + 8 {permanent '\endwrite' }
define frozen_dont_expand = frozen_control_sequence + 9 {permanent '\notexpanded:' }
define prim_size = 2100 {maximum number of primitives }
define frozen_special = frozen_control_sequence + 10 {permanent '\special' }
define frozen_null_font = frozen_control_sequence + 12 + prim_size {permanent '\nullfont' }
define frozen_primitive = frozen_control_sequence + 11 {permanent '\pdfprimitive' }
define prim_eqtb_base = frozen_primitive + 1
define font_id_base = frozen_null_font - font_base {begins table of 257 permanent font identifiers }
define undefined_control_sequence = frozen_null_font + max_font_max + 1 {dummy location }
define glue_base = undefined_control_sequence + 1 {beginning of region 3 }

```

⟨Initialize table entries (done by INITEX only) 182⟩ +≡

```

eq_type(undefined_control_sequence) ← undefined_cs; equiv(undefined_control_sequence) ← null;
eq_level(undefined_control_sequence) ← level_zero;
for k ← active_base to eqtb_top do eqtb[k] ← eqtb[undefined_control_sequence];

```

248* Region 4 of *eqtb* contains the local quantities defined here. The bulk of this region is taken up by five tables that are indexed by eight-bit characters; these tables are important to both the syntactic and semantic portions of \TeX . There are also a bunch of special things like font and token parameters, as well as the tables of `\toks` and `\box` registers.

```

define par_shape_loc = local_base { specifies paragraph shape }
define output_routine_loc = local_base + 1 { points to token list for \output }
define every_par_loc = local_base + 2 { points to token list for \everypar }
define every_math_loc = local_base + 3 { points to token list for \everymath }
define every_display_loc = local_base + 4 { points to token list for \everydisplay }
define every_hbox_loc = local_base + 5 { points to token list for \everyhbox }
define every_vbox_loc = local_base + 6 { points to token list for \everyvbox }
define every_job_loc = local_base + 7 { points to token list for \everyjob }
define every_cr_loc = local_base + 8 { points to token list for \everycr }
define err_help_loc = local_base + 9 { points to token list for \errhelp }
define tex_toks = local_base + 10 { end of  $\TeX$ 's token list parameters }

define pdftex_first_loc = tex_toks { base for pdf $\TeX$ 's token list parameters }
define pdf_pages_attr_loc = pdftex_first_loc + 0 { points to token list for \pdfpagesattr }
define pdf_page_attr_loc = pdftex_first_loc + 1 { points to token list for \pdfpageattr }
define pdf_page_resources_loc = pdftex_first_loc + 2 { points to token list for \pdfpageresources }
define pdf_pk_mode_loc = pdftex_first_loc + 3 { points to token list for \pdfpkmode }
define pdf_toks = pdftex_first_loc + 4 { end of pdf $\TeX$ 's token list parameters }

define etex_toks_base = pdf_toks { base for  $\varepsilon$ - $\TeX$ 's token list parameters }
define every_eof_loc = etex_toks_base { points to token list for \everyeof }
define etex_toks = etex_toks_base + 1 { end of  $\varepsilon$ - $\TeX$ 's token list parameters }

define toks_base = etex_toks { table of 256 token list registers }

define etex_pen_base = toks_base + 256 { start of table of  $\varepsilon$ - $\TeX$ 's penalties }
define inter_line_penalties_loc = etex_pen_base { additional penalties between lines }
define club_penalties_loc = etex_pen_base + 1 { penalties for creating club lines }
define widow_penalties_loc = etex_pen_base + 2 { penalties for creating widow lines }
define display_widow_penalties_loc = etex_pen_base + 3 { ditto, just before a display }
define etex_pens = etex_pen_base + 4 { end of table of  $\varepsilon$ - $\TeX$ 's penalties }

define box_base = etex_pens { table of 256 box registers }
define cur_font_loc = box_base + 256 { internal font number outside math mode }
define xord_code_base = cur_font_loc + 1
define xchr_code_base = xord_code_base + 1
define xprn_code_base = xchr_code_base + 1
define math_font_base = xprn_code_base + 1
define cat_code_base = math_font_base + 48 { table of 256 command codes (the "catcodes") }
define lc_code_base = cat_code_base + 256 { table of 256 lowercase mappings }
define uc_code_base = lc_code_base + 256 { table of 256 uppercase mappings }
define sf_code_base = uc_code_base + 256 { table of 256 spacefactor mappings }
define math_code_base = sf_code_base + 256 { table of 256 math mode mappings }
define char_sub_code_base = math_code_base + 256 { table of character substitutions }
define int_base = char_sub_code_base + 256 { beginning of region 5 }

define par_shape_ptr  $\equiv$  equiv(par_shape_loc)
define output_routine  $\equiv$  equiv(output_routine_loc)
define every_par  $\equiv$  equiv(every_par_loc)
define every_math  $\equiv$  equiv(every_math_loc)
define every_display  $\equiv$  equiv(every_display_loc)
define every_hbox  $\equiv$  equiv(every_hbox_loc)
define every_vbox  $\equiv$  equiv(every_vbox_loc)

```

```

define every_job  $\equiv$  equiv(every_job_loc)
define every_cr  $\equiv$  equiv(every_cr_loc)
define err_help  $\equiv$  equiv(err_help_loc)
define pdf_pages_attr  $\equiv$  equiv(pdf_pages_attr_loc)
define pdf_page_attr  $\equiv$  equiv(pdf_page_attr_loc)
define pdf_page_resources  $\equiv$  equiv(pdf_page_resources_loc)
define pdf_pk_mode  $\equiv$  equiv(pdf_pk_mode_loc)
define toks(#)  $\equiv$  equiv(toks_base + #)
define box(#)  $\equiv$  equiv(box_base + #)
define cur_font  $\equiv$  equiv(cur_font_loc)
define fam_fnt(#)  $\equiv$  equiv(math_font_base + #)
define cat_code(#)  $\equiv$  equiv(cat_code_base + #)
define lc_code(#)  $\equiv$  equiv(lc_code_base + #)
define uc_code(#)  $\equiv$  equiv(uc_code_base + #)
define sf_code(#)  $\equiv$  equiv(sf_code_base + #)
define math_code(#)  $\equiv$  equiv(math_code_base + #)
      { Note: math_code(c) is the true math code plus min_halfword }
define char_sub_code(#)  $\equiv$  equiv(char_sub_code_base + #)
      { Note: char_sub_code(c) is the true substitution info plus min_halfword }

```

⟨Put each of TEX's primitives into the hash table 244⟩ +≡

```

primitive("output", assign_toks, output_routine_loc); primitive("everypar", assign_toks, every_par_loc);
primitive("everymath", assign_toks, every_math_loc);
primitive("everydisplay", assign_toks, every_display_loc);
primitive("everyhbox", assign_toks, every_hbox_loc); primitive("everyvbox", assign_toks, every_vbox_loc);
primitive("everyjob", assign_toks, every_job_loc); primitive("everycr", assign_toks, every_cr_loc);
primitive("errhelp", assign_toks, err_help_loc);
primitive("pdfpagesattr", assign_toks, pdf_pages_attr_loc);
primitive("pdfpageattr", assign_toks, pdf_page_attr_loc);
primitive("pdfpageresources", assign_toks, pdf_page_resources_loc);
primitive("pdfpkmode", assign_toks, pdf_pk_mode_loc);

```

254* Region 5 of *eqtb* contains the integer parameters and registers defined here, as well as the *del_code* table. The latter table differs from the *cat_code* .. *math_code* tables that precede it, since delimiter codes are fullword integers while the other kinds of codes occupy at most a halfword. This is what makes region 5 different from region 4. We will store the *eq_level* information in an auxiliary array of quarterwords that will be defined later.

```

define pretolerance_code = 0 { badness tolerance before hyphenation }
define tolerance_code = 1 { badness tolerance after hyphenation }
define line_penalty_code = 2 { added to the badness of every line }
define hyphen_penalty_code = 3 { penalty for break after discretionary hyphen }
define ex.hyphen_penalty_code = 4 { penalty for break after explicit hyphen }
define club_penalty_code = 5 { penalty for creating a club line }
define widow_penalty_code = 6 { penalty for creating a widow line }
define display_widow_penalty_code = 7 { ditto, just before a display }
define broken_penalty_code = 8 { penalty for breaking a page at a broken line }
define bin_op_penalty_code = 9 { penalty for breaking after a binary operation }
define rel_penalty_code = 10 { penalty for breaking after a relation }
define pre_display_penalty_code = 11 { penalty for breaking just before a displayed formula }
define post_display_penalty_code = 12 { penalty for breaking just after a displayed formula }
define inter_line_penalty_code = 13 { additional penalty between lines }
define double_hyphen_demerits_code = 14 { demerits for double hyphen break }
define final_hyphen_demerits_code = 15 { demerits for final hyphen break }
define adj_demerits_code = 16 { demerits for adjacent incompatible lines }
define mag_code = 17 { magnification ratio }
define delimiter_factor_code = 18 { ratio for variable-size delimiters }
define looseness_code = 19 { change in number of lines for a paragraph }
define time_code = 20 { current time of day }
define day_code = 21 { current day of the month }
define month_code = 22 { current month of the year }
define year_code = 23 { current year of our Lord }
define show_box_breadth_code = 24 { nodes per level in show_box }
define show_box_depth_code = 25 { maximum level in show_box }
define hbadness_code = 26 { hboxes exceeding this badness will be shown by hpack }
define vbadness_code = 27 { vboxes exceeding this badness will be shown by vpack }
define pausing_code = 28 { pause after each line is read from a file }
define tracing_online_code = 29 { show diagnostic output on terminal }
define tracing_macros_code = 30 { show macros as they are being expanded }
define tracing_stats_code = 31 { show memory usage if TeX knows it }
define tracing_paragraphs_code = 32 { show line-break calculations }
define tracing_pages_code = 33 { show page-break calculations }
define tracing_output_code = 34 { show boxes when they are shipped out }
define tracing_lost_chars_code = 35 { show characters that aren't in the font }
define tracing_commands_code = 36 { show command codes at big_switch }
define tracing_restores_code = 37 { show equivalents when they are restored }
define uc_hyph_code = 38 { hyphenate words beginning with a capital letter }
define output_penalty_code = 39 { penalty found at current page break }
define max_dead_cycles_code = 40 { bound on consecutive dead cycles of output }
define hang_after_code = 41 { hanging indentation changes after this many lines }
define floating_penalty_code = 42 { penalty for insertions held over after a split }
define global_defs_code = 43 { override \global specifications }
define cur_fam_code = 44 { current family }
define escape_char_code = 45 { escape character for token output }
define default_hyphen_char_code = 46 { value of \hyphenchar when a font is loaded }

```

```

define default_skew_char_code = 47 { value of \skewchar when a font is loaded }
define end_line_char_code = 48 { character placed at the right end of the buffer }
define new_line_char_code = 49 { character that prints as print.ln }
define language_code = 50 { current hyphenation table }
define left_hyphen_min_code = 51 { minimum left hyphenation fragment size }
define right_hyphen_min_code = 52 { minimum right hyphenation fragment size }
define holding_inserts_code = 53 { do not remove insertion nodes from \box255 }
define error_context_lines_code = 54 { maximum intermediate line pairs shown }
define tex_int_pars = 55 { total number of TeX's integer parameters }

define web2c_int_base = tex_int_pars { base for web2c's integer parameters }
define char_sub_def_min_code = web2c_int_base { smallest value in the charsubdef list }
define char_sub_def_max_code = web2c_int_base + 1 { largest value in the charsubdef list }
define tracing_char_sub_def_code = web2c_int_base + 2 { traces changes to a charsubdef def }
define tracing_stack_levels_code = web2c_int_base + 3
    { tracing input_stack level if tracingmacros positive }
define partoken_context_code = web2c_int_base + 4 { controlling where partoken inserted }
define show_stream_code = web2c_int_base + 5 { stream to output xray commands to }
define mubyte_in_code = web2c_int_base + 6 { if positive then reading mubytes is active }
define mubyte_out_code = web2c_int_base + 7 { if positive then printing mubytes is active }
define mubyte_log_code = web2c_int_base + 8 { if positive then print mubytes to log and terminal }
define spec_out_code = web2c_int_base + 9 { if positive then print specials by mubytes }
define web2c_int_pars = web2c_int_base + 10 { total number of web2c's integer parameters }

define pdftex_first_integer_code = web2c_int_pars { base for pdfTeX's integer parameters }
define pdf_output_code = pdftex_first_integer_code + 0 { switch on PDF output if positive }
define pdf_compress_level_code = pdftex_first_integer_code + 1 { compress level of streams }
define pdf_decimal_digits_code = pdftex_first_integer_code + 2
    { digits after the decimal point of numbers }
define pdf_move_chars_code = pdftex_first_integer_code + 3 { move chars 0..31 to higher area if possible }
define pdf_image_resolution_code = pdftex_first_integer_code + 4 { default image resolution }
define pdf_pk_resolution_code = pdftex_first_integer_code + 5 { default resolution of PK font }
define pdf_unique_resname_code = pdftex_first_integer_code + 6 { generate unique names for resouces }
define pdf_option_always_use_pdfpagebox_code = pdftex_first_integer_code + 7
    { if the PDF inclusion should always use a specific PDF page box }
define pdf_option_pdf_inclusion_errorlevel_code = pdftex_first_integer_code + 8
    { if the PDF inclusion should treat pdfs newer than pdf_minor_version as an error }
define pdf_major_version_code = pdftex_first_integer_code + 9
    { integer part of the PDF version produced }
define pdf_minor_version_code = pdftex_first_integer_code + 10
    { fractional part of the PDF version produced }
define pdf_force_pagebox_code = pdftex_first_integer_code + 11
    { if the PDF inclusion should always use a specific PDF page box }
define pdf_pagebox_code = pdftex_first_integer_code + 12 { default pagebox to use for PDF inclusion }
define pdf_inclusion_errorlevel_code = pdftex_first_integer_code + 13
    { if the PDF inclusion should treat pdfs newer than pdf_minor_version as an error }
define pdf_gamma_code = pdftex_first_integer_code + 14
define pdf_image_gamma_code = pdftex_first_integer_code + 15
define pdf_image_hicolor_code = pdftex_first_integer_code + 16
define pdf_image_apply_gamma_code = pdftex_first_integer_code + 17
define pdf_adjust_spacing_code = pdftex_first_integer_code + 18 { level of spacing adjusting }
define pdf_protrude_chars_code = pdftex_first_integer_code + 19
    { protrude chars at left/right edge of paragraphs }
define pdf_tracing_fonts_code = pdftex_first_integer_code + 20 { level of font detail in log }

```

```

define pdf_objcompresslevel_code = pdfTeX_first_integer_code + 21 { activate object streams }
define pdf_adjust_interword_glue_code = pdfTeX_first_integer_code + 22 { adjust interword glue? }
define pdf_prepend_kern_code = pdfTeX_first_integer_code + 23 { prepend kern before certain characters? }
define pdf_append_kern_code = pdfTeX_first_integer_code + 24 { append kern before certain characters? }
define pdf_gen_tounicode_code = pdfTeX_first_integer_code + 25 { generate ToUnicode for fonts? }
define pdf_draftmode_code = pdfTeX_first_integer_code + 26 { switch on draftmode if positive }
define pdf_inclusion_copy_font_code = pdfTeX_first_integer_code + 27 { generate ToUnicode for fonts? }
define pdf_suppress_warning_dup_dest_code = pdfTeX_first_integer_code + 28
    { suppress warning about duplicated destinations }
define pdf_suppress_warning_dup_map_code = pdfTeX_first_integer_code + 29
    { suppress warning about duplicated map lines }
define pdf_suppress_warning_page_group_code = pdfTeX_first_integer_code + 30
    { suppress warning about multiple pdfs with page group }
define pdf_info_omit_date_code = pdfTeX_first_integer_code + 31
    { omit generating CreationDate and ModDate }
define pdf_suppress_ptex_info_code = pdfTeX_first_integer_code + 32
    { suppress /PTEX.* entries in PDF dictionaries }
define pdf_omit_charset_code = pdfTeX_first_integer_code + 33
    { suppress /PTEX.* entries in PDF dictionaries }
define pdf_omit_info_dict_code = pdfTeX_first_integer_code + 34
    { suppress /PTEX.* entries in PDF dictionaries }
define pdf_omit_procset_code = pdfTeX_first_integer_code + 35
    { suppress /PTEX.* entries in PDF dictionaries }
define pdf_int_pars = pdfTeX_first_integer_code + 36 { total number of pdfTeX's integer parameters }
define etex_int_base = pdf_int_pars { base for  $\epsilon$ -TeX's integer parameters }
define tracing_assigns_code = etex_int_base { show assignments }
define tracing_groups_code = etex_int_base + 1 { show save/restore groups }
define tracing_ifs_code = etex_int_base + 2 { show conditionals }
define tracing_scan_tokens_code = etex_int_base + 3 { show pseudo file open and close }
define tracing_nesting_code = etex_int_base + 4 { show incomplete groups and ifs within files }
define pre_display_direction_code = etex_int_base + 5 { text direction preceding a display }
define last_line_fit_code = etex_int_base + 6 { adjustment for last line of paragraph }
define saving_vdiscards_code = etex_int_base + 7 { save items discarded from vlists }
define saving_hyph_codes_code = etex_int_base + 8 { save hyphenation codes for languages }
define eTeX_state_code = etex_int_base + 9 {  $\epsilon$ -TeX state variables }
define etex_int_pars = eTeX_state_code + eTeX_states { total number of  $\epsilon$ -TeX's integer parameters }
define synctex_code = etex_int_pars
define int_pars = synctex_code + 1 { total number of integer parameters }
define count_base = int_base + int_pars { 256 user \count registers }
define del_code_base = count_base + 256 { 256 delimiter code mappings }
define dimen_base = del_code_base + 256 { beginning of region 6 }
define del_code(#)  $\equiv$  eqtb[del_code_base + #].int
define count(#)  $\equiv$  eqtb[count_base + #].int
define int_par(#)  $\equiv$  eqtb[int_base + #].int { an integer parameter }
define pretolerance  $\equiv$  int_par(pretolerance_code)
define tolerance  $\equiv$  int_par(tolerance_code)
define line_penalty  $\equiv$  int_par(line_penalty_code)
define hyphen_penalty  $\equiv$  int_par(hyphen_penalty_code)
define ex_hyphen_penalty  $\equiv$  int_par(ex_hyphen_penalty_code)
define club_penalty  $\equiv$  int_par(club_penalty_code)
define widow_penalty  $\equiv$  int_par(widow_penalty_code)
define display_widow_penalty  $\equiv$  int_par(display_widow_penalty_code)

```

```

define broken_penalty ≡ int_par(broken_penalty_code)
define bin_op_penalty ≡ int_par(bin_op_penalty_code)
define rel_penalty ≡ int_par(rel_penalty_code)
define pre_display_penalty ≡ int_par(pre_display_penalty_code)
define post_display_penalty ≡ int_par(post_display_penalty_code)
define inter_line_penalty ≡ int_par(inter_line_penalty_code)
define double_hyphen_demerits ≡ int_par(double_hyphen_demerits_code)
define final_hyphen_demerits ≡ int_par(final_hyphen_demerits_code)
define adj_demerits ≡ int_par(adj_demerits_code)
define mag ≡ int_par(mag_code)
define delimiter_factor ≡ int_par(delimiter_factor_code)
define looseness ≡ int_par(looseness_code)
define time ≡ int_par(time_code)
define day ≡ int_par(day_code)
define month ≡ int_par(month_code)
define year ≡ int_par(year_code)
define show_box_breadth ≡ int_par(show_box_breadth_code)
define show_box_depth ≡ int_par(show_box_depth_code)
define hbadness ≡ int_par(hbadness_code)
define vbadness ≡ int_par(vbadness_code)
define pausing ≡ int_par(pausing_code)
define tracing_online ≡ int_par(tracing_online_code)
define tracing_macros ≡ int_par(tracing_macros_code)
define tracing_stats ≡ int_par(tracing_stats_code)
define tracing_paragraphs ≡ int_par(tracing_paragraphs_code)
define tracing_pages ≡ int_par(tracing_pages_code)
define tracing_output ≡ int_par(tracing_output_code)
define tracing_lost_chars ≡ int_par(tracing_lost_chars_code)
define tracing_commands ≡ int_par(tracing_commands_code)
define tracing_restores ≡ int_par(tracing_restores_code)
define uc_hyph ≡ int_par(uc_hyph_code)
define output_penalty ≡ int_par(output_penalty_code)
define max_dead_cycles ≡ int_par(max_dead_cycles_code)
define hang_after ≡ int_par(hang_after_code)
define floating_penalty ≡ int_par(floating_penalty_code)
define global_defs ≡ int_par(global_defs_code)
define cur_fam ≡ int_par(cur_fam_code)
define escape_char ≡ int_par(escape_char_code)
define default_hyphen_char ≡ int_par(default_hyphen_char_code)
define default_skew_char ≡ int_par(default_skew_char_code)
define end_line_char ≡ int_par(end_line_char_code)
define new_line_char ≡ int_par(new_line_char_code)
define language ≡ int_par(language_code)
define left_hyphen_min ≡ int_par(left_hyphen_min_code)
define right_hyphen_min ≡ int_par(right_hyphen_min_code)
define holding_inserts ≡ int_par(holding_inserts_code)
define error_context_lines ≡ int_par(error_context_lines_code)
define synctex ≡ int_par(synctex_code)
define char_sub_def_min ≡ int_par(char_sub_def_min_code)
define char_sub_def_max ≡ int_par(char_sub_def_max_code)
define tracing_char_sub_def ≡ int_par(tracing_char_sub_def_code)
define mubyte_in ≡ int_par(mubyte_in_code)

```

```

define mubyte_out ≡ int_par(mubyte_out_code)
define mubyte_log ≡ int_par(mubyte_log_code)
define spec_out ≡ int_par(spec_out_code)
define tracing_stack_levels ≡ int_par(tracing_stack_levels_code)
define partoken_context ≡ int_par(partoken_context_code)
define show_stream ≡ int_par(show_stream_code)
define pdf_adjust_spacing ≡ int_par(pdf_adjust_spacing_code)
define pdf_protrude_chars ≡ int_par(pdf_protrude_chars_code)
define pdf_tracing_fonts ≡ int_par(pdf_tracing_fonts_code)
define pdf_adjust_interword_glue ≡ int_par(pdf_adjust_interword_glue_code)
define pdf_prepend_kern ≡ int_par(pdf_prepend_kern_code)
define pdf_append_kern ≡ int_par(pdf_append_kern_code)
define pdf_gen_tounicode ≡ int_par(pdf_gen_tounicode_code)
define pdf_output ≡ int_par(pdf_output_code)
define pdf_compress_level ≡ int_par(pdf_compress_level_code)
define pdf_objcompresslevel ≡ int_par(pdf_objcompresslevel_code)
define pdf_decimal_digits ≡ int_par(pdf_decimal_digits_code)
define pdf_move_chars ≡ int_par(pdf_move_chars_code)
define pdf_image_resolution ≡ int_par(pdf_image_resolution_code)
define pdf_pk_resolution ≡ int_par(pdf_pk_resolution_code)
define pdf_unique_resname ≡ int_par(pdf_unique_resname_code)
define pdf_option_always_use_pdfpagebox ≡ int_par(pdf_option_always_use_pdfpagebox_code)
define pdf_option_pdf_inclusion_errorlevel ≡ int_par(pdf_option_pdf_inclusion_errorlevel_code)
define pdf_major_version ≡ int_par(pdf_major_version_code)
define pdf_minor_version ≡ int_par(pdf_minor_version_code)
define pdf_force_pagebox ≡ int_par(pdf_force_pagebox_code)
define pdf_pagebox ≡ int_par(pdf_pagebox_code)
define pdf_inclusion_errorlevel ≡ int_par(pdf_inclusion_errorlevel_code)
define pdf_gamma ≡ int_par(pdf_gamma_code)
define pdf_image_gamma ≡ int_par(pdf_image_gamma_code)
define pdf_image_hicolor ≡ int_par(pdf_image_hicolor_code)
define pdf_image_apply_gamma ≡ int_par(pdf_image_apply_gamma_code)
define pdf_draftmode ≡ int_par(pdf_draftmode_code)
define pdf_inclusion_copy_font ≡ int_par(pdf_inclusion_copy_font_code)
define pdf_suppress_warning_dup_dest ≡ int_par(pdf_suppress_warning_dup_dest_code)
define pdf_suppress_warning_dup_map ≡ int_par(pdf_suppress_warning_dup_map_code)
define pdf_suppress_warning_page_group ≡ int_par(pdf_suppress_warning_page_group_code)
define pdf_info_omit_date ≡ int_par(pdf_info_omit_date_code)
define pdf_suppress_ptex_info ≡ int_par(pdf_suppress_ptex_info_code)
define pdf_omit_charset ≡ int_par(pdf_omit_charset_code)
define pdf_omit_info_dict ≡ int_par(pdf_omit_info_dict_code)
define pdf_omit_procset ≡ int_par(pdf_omit_procset_code)
define tracing_assigns ≡ int_par(tracing_assigns_code)
define tracing_groups ≡ int_par(tracing_groups_code)
define tracing_ifs ≡ int_par(tracing_ifs_code)
define tracing_scan_tokens ≡ int_par(tracing_scan_tokens_code)
define tracing_nesting ≡ int_par(tracing_nesting_code)
define pre_display_direction ≡ int_par(pre_display_direction_code)
define last_line_fit ≡ int_par(last_line_fit_code)
define saving_vdiscards ≡ int_par(saving_vdiscards_code)
define saving_hyph_codes ≡ int_par(saving_hyph_codes_code)

```

(Assign the values *depth_threshold* ← *show_box_depth* and *breadth_max* ← *show_box_breadth* 254*) ≡

depth_threshold ← *show_box_depth*; *breadth_max* ← *show_box_breadth*

This code is used in section [216](#).

255* We can print the symbolic name of an integer parameter as follows.

```

procedure print_param(n : integer);
begin case n of
  pretolerance_code: print_esc("pretolerance");
  tolerance_code: print_esc("tolerance");
  line_penalty_code: print_esc("linepenalty");
  hyphen_penalty_code: print_esc("hyphenpenalty");
  ex_hyphen_penalty_code: print_esc("exhyphenpenalty");
  club_penalty_code: print_esc("clubpenalty");
  widow_penalty_code: print_esc("widowpenalty");
  display_widow_penalty_code: print_esc("displaywidowpenalty");
  broken_penalty_code: print_esc("brokenpenalty");
  bin_op_penalty_code: print_esc("binoppenalty");
  rel_penalty_code: print_esc("relpenalty");
  pre_display_penalty_code: print_esc("predisplaypenalty");
  post_display_penalty_code: print_esc("postdisplaypenalty");
  inter_line_penalty_code: print_esc("interlinepenalty");
  double_hyphen_demerits_code: print_esc("doublehyphendemerits");
  final_hyphen_demerits_code: print_esc("finalhyphendemerits");
  adj_demerits_code: print_esc("adjdemerits");
  mag_code: print_esc("mag");
  delimiter_factor_code: print_esc("delimiterfactor");
  looseness_code: print_esc("looseness");
  time_code: print_esc("time");
  day_code: print_esc("day");
  month_code: print_esc("month");
  year_code: print_esc("year");
  show_box_breadth_code: print_esc("showboxbreadth");
  show_box_depth_code: print_esc("showboxdepth");
  hbadness_code: print_esc("hbadness");
  vbadness_code: print_esc("vbadness");
  pausing_code: print_esc("pausing");
  tracing_online_code: print_esc("tracingonline");
  tracing_macros_code: print_esc("tracingmacros");
  tracing_stats_code: print_esc("tracingstats");
  tracing_paragraphs_code: print_esc("tracingparagraphs");
  tracing_pages_code: print_esc("tracingpages");
  tracing_output_code: print_esc("tracingoutput");
  tracing_lost_chars_code: print_esc("tracinglostchars");
  tracing_commands_code: print_esc("tracingcommands");
  tracing_restores_code: print_esc("tracingrestores");
  uc_hyph_code: print_esc("uchyph");
  output_penalty_code: print_esc("outputpenalty");
  max_dead_cycles_code: print_esc("maxdeadcycles");
  hang_after_code: print_esc("hangafter");
  floating_penalty_code: print_esc("floatingpenalty");
  global_defs_code: print_esc("globaldefs");
  cur_fam_code: print_esc("fam");
  escape_char_code: print_esc("escapechar");
  default_hyphen_char_code: print_esc("defaultthyphenchar");
  default_skew_char_code: print_esc("defaultskewchar");
  end_line_char_code: print_esc("endlinechar");

```

```

new_line_char_code: print_esc("newlinechar");
language_code: print_esc("language");
left_hyphen_min_code: print_esc("lefthyphenmin");
right_hyphen_min_code: print_esc("righthyphenmin");
holding_inserts_code: print_esc("holdinginserts");
error_context_lines_code: print_esc("errorcontextlines");
char_sub_def_min_code: print_esc("charsubdefmin");
char_sub_def_max_code: print_esc("charsubdefmax");
tracing_char_sub_def_code: print_esc("tracingcharsubdef");
mubyte_in_code: print_esc("mubytein");
mubyte_out_code: print_esc("mubyteout");
mubyte_log_code: print_esc("mubytelog");
spec_out_code: print_esc("specialout");
tracing_stack_levels_code: print_esc("tracingstacklevels");
partoken_context_code: print_esc("partokencontext");
show_stream_code: print_esc("showstream");

pdf_output_code: print_esc("pdfoutput");
pdf_compress_level_code: print_esc("pdfcompresslevel");
pdf_objcompresslevel_code: print_esc("pdfobjcompresslevel");
pdf_decimal_digits_code: print_esc("pdfdecimaldigits");
pdf_move_chars_code: print_esc("pdfmovechars");
pdf_image_resolution_code: print_esc("pdfimageresolution");
pdf_pk_resolution_code: print_esc("pdfpkresolution");
pdf_unique_resname_code: print_esc("pdfuniquerename");
pdf_option_always_use_pdfpagebox_code: print_esc("pdfoptionalwaysusepdfpagebox");
pdf_option_pdf_inclusion_errorlevel_code: print_esc("pdfoptionpdfinclusionerrorlevel");
pdf_major_version_code: print_esc("pdfmajorversion");
pdf_minor_version_code: print_esc("pdfminorversion");
pdf_force_pagebox_code: print_esc("pdfforcepagebox");
pdf_pagebox_code: print_esc("pdfpagebox");
pdf_inclusion_errorlevel_code: print_esc("pdfinclusionerrorlevel");
pdf_gamma_code: print_esc("pdfgamma");
pdf_image_gamma_code: print_esc("pdfimagegamma");
pdf_image_hicolor_code: print_esc("pdfimagehicolor");
pdf_image_apply_gamma_code: print_esc("pdfimageapplygamma");
pdf_adjust_spacing_code: print_esc("pdfadjustspacing");
pdf_protrude_chars_code: print_esc("pdfprotrudechars");
pdf_tracing_fonts_code: print_esc("pdftracingfonts");
pdf_adjust_interword_glue_code: print_esc("pdfadjustinterwordglue");
pdf_prepend_kern_code: print_esc("pdfprependkern");
pdf_append_kern_code: print_esc("pdfappendkern");
pdf_gen_tounicode_code: print_esc("pdfgentounicode");
pdf_draftmode_code: print_esc("pdfdraftmode");
pdf_inclusion_copy_font_code: print_esc("pdfinclusioncopyfonts");
pdf_suppress_warning_dup_dest_code: print_esc("pdfsuppresswarningdupdest");
pdf_suppress_warning_dup_map_code: print_esc("pdfsuppresswarningdupmap");
pdf_suppress_warning_page_group_code: print_esc("pdfsuppresswarningpagegroup");
pdf_info_omit_date_code: print_esc("pdfinfoomitdate");
pdf_suppress_ptex_info_code: print_esc("pdfsuppressptexinfo");
pdf_omit_charset_code: print_esc("pdfomitcharset");
pdf_omit_info_dict_code: print_esc("pdfomitinfodict");
pdf_omit_procset_code: print_esc("pdfomitprocset");

```

```
⟨synctex case for print_param 1910*⟩  
⟨Cases for print_param 1660⟩  
othercases print(" [unknown_ integer_ parameter!] ")  
endcases;  
end;
```

256* The integer parameter names must be entered into the hash table.

(Put each of TEX's primitives into the hash table 244) +≡

```

primitive("pretolerance", assign_int, int_base + pretolerance_code);
primitive("tolerance", assign_int, int_base + tolerance_code);
primitive("linepenalty", assign_int, int_base + line_penalty_code);
primitive("hyphenpenalty", assign_int, int_base + hyphen_penalty_code);
primitive("exhyphenpenalty", assign_int, int_base + ex_hyphen_penalty_code);
primitive("clubpenalty", assign_int, int_base + club_penalty_code);
primitive("widowpenalty", assign_int, int_base + widow_penalty_code);
primitive("displaywidowpenalty", assign_int, int_base + display_widow_penalty_code);
primitive("brokenpenalty", assign_int, int_base + broken_penalty_code);
primitive("binoppenalty", assign_int, int_base + bin_op_penalty_code);
primitive("relpenalty", assign_int, int_base + rel_penalty_code);
primitive("predisplaypenalty", assign_int, int_base + pre_display_penalty_code);
primitive("postdisplaypenalty", assign_int, int_base + post_display_penalty_code);
primitive("interlinepenalty", assign_int, int_base + inter_line_penalty_code);
primitive("doublehyphendemerits", assign_int, int_base + double_hyphen_demerits_code);
primitive("finalhyphendemerits", assign_int, int_base + final_hyphen_demerits_code);
primitive("adjdemerits", assign_int, int_base + adj_demerits_code);
primitive("mag", assign_int, int_base + mag_code);
primitive("delimiterfactor", assign_int, int_base + delimiter_factor_code);
primitive("looseness", assign_int, int_base + looseness_code);
primitive("time", assign_int, int_base + time_code);
primitive("day", assign_int, int_base + day_code);
primitive("month", assign_int, int_base + month_code);
primitive("year", assign_int, int_base + year_code);
primitive("showboxbreadth", assign_int, int_base + show_box_breadth_code);
primitive("showboxdepth", assign_int, int_base + show_box_depth_code);
primitive("hbadness", assign_int, int_base + hbadness_code);
primitive("vbadness", assign_int, int_base + vbadness_code);
primitive("pausing", assign_int, int_base + pausing_code);
primitive("tracingonline", assign_int, int_base + tracing_online_code);
primitive("tracingmacros", assign_int, int_base + tracing_macros_code);
primitive("tracingstats", assign_int, int_base + tracing_stats_code);
primitive("tracingparagraphs", assign_int, int_base + tracing_paragraphs_code);
primitive("tracingpages", assign_int, int_base + tracing_pages_code);
primitive("tracingoutput", assign_int, int_base + tracing_output_code);
primitive("tracinglostchars", assign_int, int_base + tracing_lost_chars_code);
primitive("tracingcommands", assign_int, int_base + tracing_commands_code);
primitive("tracingrestores", assign_int, int_base + tracing_restores_code);
primitive("uchyph", assign_int, int_base + uc_hyph_code);
primitive("outputpenalty", assign_int, int_base + output_penalty_code);
primitive("maxdeadcycles", assign_int, int_base + max_dead_cycles_code);
primitive("hangafter", assign_int, int_base + hang_after_code);
primitive("floatingpenalty", assign_int, int_base + floating_penalty_code);
primitive("globaldefs", assign_int, int_base + global_defs_code);
primitive("fam", assign_int, int_base + cur_fam_code);
primitive("escapechar", assign_int, int_base + escape_char_code);
primitive("defaultthyphenchar", assign_int, int_base + default_hyphen_char_code);
primitive("defaultskewchar", assign_int, int_base + default_skew_char_code);
primitive("endlinechar", assign_int, int_base + end_line_char_code);
primitive("newlinechar", assign_int, int_base + new_line_char_code);

```

```

primitive("language", assign_int, int_base + language_code);
primitive("lefthyphenmin", assign_int, int_base + left_hyphen_min_code);
primitive("righthyphenmin", assign_int, int_base + right_hyphen_min_code);
primitive("holdinginserts", assign_int, int_base + holding_inserts_code);
primitive("errorcontextlines", assign_int, int_base + error_context_lines_code);
if mltex_p then
  begin mltex_enabled_p ← true; { enable character substitution }
  if false then { remove the if-clause to enable \charsubdefmin }
    primitive("charsubdefmin", assign_int, int_base + char_sub_def_min_code);
    primitive("charsubdefmax", assign_int, int_base + char_sub_def_max_code);
    primitive("tracingcharsubdef", assign_int, int_base + tracing_char_sub_def_code);
  end;
if enctex_p then
  begin enctex_enabled_p ← true; primitive("mubytein", assign_int, int_base + mubyte_in_code);
  primitive("mubyteout", assign_int, int_base + mubyte_out_code);
  primitive("mubytelog", assign_int, int_base + mubyte_log_code);
  primitive("specialout", assign_int, int_base + spec_out_code);
  end;
primitive("tracingstacklevels", assign_int, int_base + tracing_stack_levels_code);
primitive("partokenname", partoken_name, 0);
primitive("partokencontext", assign_int, int_base + partoken_context_code);
primitive("showstream", assign_int, int_base + show_stream_code);
primitive("pdfoutput", assign_int, int_base + pdf_output_code);
primitive("pdfcompresslevel", assign_int, int_base + pdf_compress_level_code);
primitive("pdfobjcompresslevel", assign_int, int_base + pdf_objcompresslevel_code);
primitive("pdfdecimaldigits", assign_int, int_base + pdf_decimal_digits_code);
primitive("pdfmovechars", assign_int, int_base + pdf_move_chars_code);
primitive("pdfimageresolution", assign_int, int_base + pdf_image_resolution_code);
primitive("pdfpkresolution", assign_int, int_base + pdf_pk_resolution_code);
primitive("pdfuniquerename", assign_int, int_base + pdf_unique_rename_code);
primitive("pdfoptionpdfminorversion", assign_int, int_base + pdf_minor_version_code);
primitive("pdfoptionalwaysusepdfpagebox", assign_int,
  int_base + pdf_option_always_use_pdfpagebox_code);
primitive("pdfoptionpdfinclusionerrorlevel", assign_int,
  int_base + pdf_option_pdf_inclusion_errorlevel_code);
primitive("pdfmajorversion", assign_int, int_base + pdf_major_version_code);
primitive("pdfminorversion", assign_int, int_base + pdf_minor_version_code);
primitive("pdfforcepagebox", assign_int, int_base + pdf_force_pagebox_code);
primitive("pdfpagebox", assign_int, int_base + pdf_pagebox_code);
primitive("pdfinclusionerrorlevel", assign_int, int_base + pdf_inclusion_errorlevel_code);
primitive("pdfgamma", assign_int, int_base + pdf_gamma_code);
primitive("pdfimagegamma", assign_int, int_base + pdf_image_gamma_code);
primitive("pdfimagehicolor", assign_int, int_base + pdf_image_hicolor_code);
primitive("pdfimageapplygamma", assign_int, int_base + pdf_image_apply_gamma_code);
primitive("pdfadjustspacing", assign_int, int_base + pdf_adjust_spacing_code);
primitive("pdfprotrudechars", assign_int, int_base + pdf_protrude_chars_code);
primitive("pdftracingfonts", assign_int, int_base + pdf_tracing_fonts_code);
primitive("pdfadjustinterwordglue", assign_int, int_base + pdf_adjust_interword_glue_code);
primitive("pdfprependkern", assign_int, int_base + pdf_prepend_kern_code);
primitive("pdfappendkern", assign_int, int_base + pdf_append_kern_code);
primitive("pdfgentounicode", assign_int, int_base + pdf_gen_tounicode_code);
primitive("pdfdraftmode", assign_int, int_base + pdf_draftmode_code);

```

```

primitive("pdfinclusioncopyfonts", assign_int, int_base + pdf_inclusion_copy_font_code);
primitive("pdfsuppresswarningdupdest", assign_int, int_base + pdf_suppress_warning_dup_dest_code);
primitive("pdfsuppresswarningdupmap", assign_int, int_base + pdf_suppress_warning_dup_map_code);
primitive("pdfsuppresswarningpagegroup", assign_int, int_base + pdf_suppress_warning_page_group_code);
primitive("pdfinfoomitdate", assign_int, int_base + pdf_info_omit_date_code);
primitive("pdfsuppressptexinfo", assign_int, int_base + pdf_suppress_ptex_info_code);
primitive("pdfomitcharset", assign_int, int_base + pdf_omit_charset_code);
primitive("pdfomitinfodict", assign_int, int_base + pdf_omit_info_dict_code);
primitive("pdfomitprocset", assign_int, int_base + pdf_omit_procset_code);

```

258* The integer parameters should really be initialized by a macro package; the following initialization does the minimum to keep TEX from complete failure.

```

⟨Initialize table entries (done by INITEX only) 182⟩ +≡
  for k ← int_base to del_code_base - 1 do eqtb[k].int ← 0;
  char_sub_def_min ← 256; char_sub_def_max ← -1; { allow \charsubdef for char 0 }
  { tracing_char_sub_def ← 0 is already done }
  mag ← 1000; tolerance ← 10000; hang_after ← 1; max_dead_cycles ← 25; escape_char ← "\";
  end_line_char ← carriage_return;
  for k ← 0 to 255 do del_code(k) ← -1;
  del_code(".") ← 0; { this null delimiter is used in error recovery }
  show_stream ← -1;

```

259* The following procedure, which is called just before TEX initializes its input and output, establishes the initial values of the date and time. It calls a *date_and_time* C macro (a.k.a. *dateandtime*), which calls the C function *get_date_and_time*, passing it the addresses of *sys_time*, etc., so they can be set by the routine. *get_date_and_time* also sets up interrupt catching if that is conditionally compiled in the C code.

We have to initialize the *sys_* variables because that is what gets output on the first line of the log file. (New in 2021.)

```

procedure fix_date_and_time;
  begin date_and_time(sys_time, sys_day, sys_month, sys_year); time ← sys_time;
  { minutes since midnight }
  day ← sys_day; { day of the month }
  month ← sys_month; { month of the year }
  year ← sys_year; { Anno Domini }
  end;

```

270* Here is a procedure that displays the contents of *eqtb*[*n*] symbolically.

```

⟨Declare the procedure called print_cmd_chr 320⟩
stat procedure show_eqtb(n : pointer);
  begin if n < active_base then print_char("?") { this can't happen }
  else if (n < glue_base) ∨ ((n > eqtb_size) ∧ (n ≤ eqtb_top)) then ⟨Show equivalent n, in region 1 or 2 241⟩
  else if n < local_base then ⟨Show equivalent n, in region 3 247⟩
  else if n < int_base then ⟨Show equivalent n, in region 4 251⟩
  else if n < dimen_base then ⟨Show equivalent n, in region 5 260⟩
  else if n ≤ eqtb_size then ⟨Show equivalent n, in region 6 269⟩
  else print_char("?"); { this can't happen either }
  end;
tats

```

271* The last two regions of *eqtb* have fullword values instead of the three fields *eq_level*, *eq_type*, and *equiv*. An *eq_type* is unnecessary, but TeX needs to store the *eq_level* information in another array called *xeq_level*.

⟨ Global variables 13 ⟩ +≡

zeqtb: ↑*memory_word*;

xeq_level: **array** [*int_base* .. *eqtb_size*] **of** *quarterword*;

274* **The hash table.** Control sequences are stored and retrieved by means of a fairly standard hash table algorithm called the method of “coalescing lists” (cf. Algorithm 6.4C in *The Art of Computer Programming*). Once a control sequence enters the table, it is never removed, because there are complicated situations involving `\gdef` where the removal of a control sequence at the end of a group would be a mistake preventable only by the introduction of a complicated reference-count mechanism.

The actual sequence of letters forming a control sequence identifier is stored in the *str_pool* array together with all the other strings. An auxiliary array *hash* consists of items with two halfword fields per word. The first of these, called *next(p)*, points to the next identifier belonging to the same coalesced list as the identifier corresponding to *p*; and the other, called *text(p)*, points to the *str_start* entry for *p*’s identifier. If position *p* of the hash table is empty, we have *text(p)* = 0; if position *p* is either empty or the end of a coalesced hash list, we have *next(p)* = 0. An auxiliary pointer variable called *hash_used* is maintained in such a way that all locations *p* ≥ *hash_used* are nonempty. The global variable *cs_count* tells how many multiletter control sequences have been defined, if statistics are being kept.

A global boolean variable called *no_new_control_sequence* is set to *true* during the time that new hash table entries are forbidden.

```

define next(#) ≡ hash[#].lh  { link for coalesced lists }
define text(#) ≡ hash[#].rh  { string number for control sequence name }
define hash_is_full ≡ (hash_used = hash_base)  { test if all positions are occupied }
define font_id_text(#) ≡ text(font_id_base + #)  { a frozen font identifier’s name }

```

⟨Global variables 13⟩ +≡

```

hash: ↑two_halves;  { the hash table }
yhash: ↑two_halves;  { auxiliary pointer for freeing hash }
hash_used: pointer;  { allocation pointer for hash }
hash_extra: pointer;  { hash_extra = hash above eqtb_size }
hash_top: pointer;  { maximum of the hash array }
eqtb_top: pointer;  { maximum of the eqtb }
hash_high: pointer;  { pointer to next high hash location }
no_new_control_sequence: boolean;  { are new identifiers legal? }
cs_count: integer;  { total number of known identifiers }

```

275* ⟨Set initial values of key variables 21⟩ +≡

```

no_new_control_sequence ← true;  { new identifiers are usually forbidden }
prim_next(0) ← 0; prim_text(0) ← 0;
for k ← 1 to prim_size do prim[k] ← prim[0];

```

276* ⟨Initialize table entries (done by INITEX only) 182⟩ +≡

```

prim_used ← prim_size;  { nothing is used }
hash_used ← frozen_control_sequence;  { nothing is used }
hash_high ← 0; cs_count ← 0; eq_type(frozen_dont_expand) ← dont_expand;
text(frozen_dont_expand) ← "notexpanded"; eq_type(frozen_primitive) ← ignore_spaces;
equiv(frozen_primitive) ← 1; eq_level(frozen_primitive) ← level_one;
text(frozen_primitive) ← "pdfprimitive";

```

```

279* ⟨ Insert a new control sequence after  $p$ , then make  $p$  point to it 279* ⟩ ≡
begin if  $text(p) > 0$  then
  begin if  $hash\_high < hash\_extra$  then
    begin  $incr(hash\_high)$ ;  $next(p) \leftarrow hash\_high + eqtb\_size$ ;  $p \leftarrow hash\_high + eqtb\_size$ ;
    end
  else begin repeat if  $hash\_is\_full$  then  $overflow("hash\_size", hash\_size + hash\_extra)$ ;
     $decr(hash\_used)$ ;
    until  $text(hash\_used) = 0$ ; { search for an empty location in  $hash$  }
     $next(p) \leftarrow hash\_used$ ;  $p \leftarrow hash\_used$ ;
    end;
  end;
 $str\_room(l)$ ;  $d \leftarrow cur\_length$ ;
while  $pool\_ptr > str\_start[str\_ptr]$  do
  begin  $decr(pool\_ptr)$ ;  $str\_pool[pool\_ptr + l] \leftarrow str\_pool[pool\_ptr]$ ;
  end; { move current string up to make room for another }
for  $k \leftarrow j$  to  $j + l - 1$  do  $append\_char(buffer[k])$ ;
 $text(p) \leftarrow make\_string$ ;  $pool\_ptr \leftarrow pool\_ptr + d$ ;
stat  $incr(cs\_count)$ ; tats
end

```

This code is used in section [278](#).

284* Single-character control sequences do not need to be looked up in a hash table, since we can use the character code itself as a direct address. The procedure *print_cs* prints the name of a control sequence, given a pointer to its address in *eqtb*. A space is printed after the name unless it is a single nonletter or an active character. This procedure might be invoked with invalid data, so it is “extra robust.” The individual characters must be printed one at a time using *print*, since they may be unprintable.

The conversion from control sequence to byte sequence for encTEX is implemented here. Of course, the simplest way is to implement an array of string pointers with *hash_size* length, but we assume that only a few control sequences will need to be converted. So *mubyte_cswrite*, an array with only 128 items, is used. The items point to the token lists. First token includes a csname number and the second points the string to be output. The third token includes the number of another csname and fourth token its pointer to the string etc. We need to do the sequential searching in one of the 128 token lists.

⟨Basic printing procedures 57⟩ +≡

```

procedure print_cs(p : integer); { prints a purported control sequence }
  var q: pointer; s: str_number;
  begin if active_noconvert ∧ (no_convert) ∧ (eq_type(p) = let) ∧ (equiv(p) = normal + 11) then
    { noconvert }
    begin no_convert ← true; return;
  end;
  s ← 0;
  if cs_converting ∧ (no_convert) then
    begin q ← mubyte_cswrite[p mod 128];
    while q ≠ null do
      if info(q) = p then
        begin s ← info(link(q)); q ← null;
        end
      else q ← link(link(q));
    end;
  no_convert ← false;
  if s > 0 then print(s)
  else if p < hash_base then { single character }
    if p ≥ single_base then
      if p = null_cs then
        begin print_esc("csname"); print_esc("endcsname"); print_char("␣");
        end
      else begin print_esc(p - single_base);
        if cat_code(p - single_base) = letter then print_char("␣");
        end
      else if p < active_base then print_esc("IMPOSSIBLE.")
      else print(p - active_base)
    else if ((p ≥ undefined_control_sequence) ∧ (p ≤ eqtb_size)) ∨ (p > eqtb_top) then
      print_esc("IMPOSSIBLE.")
    else if (text(p) ≥ str_ptr) then print_esc("NONEXISTENT.")
    else begin if (p ≥ prim_eqtb_base) ∧ (p < frozen_null_font) then
      print_esc(prim_text(p - prim_eqtb_base) - 1)
    else print_esc(text(p));
    print_char("␣");
    end;
  exit: end;

```

287* Many of TeX's primitives need no *equiv*, since they are identifiable by their *eq_type* alone. These primitives are loaded into the hash table as follows:

```

⟨Put each of TeX's primitives into the hash table 244⟩ +≡
  primitive("□", ex_space, 0);
  primitive("/", ital_corr, 0);
  primitive("accent", accent, 0);
  primitive("advance", advance, 0);
  primitive("afterassignment", after_assignment, 0);
  primitive("aftergroup", after_group, 0);
  primitive("begingroup", begin_group, 0);
  primitive("char", char_num, 0);
  primitive("csname", cs_name, 0);
  primitive("delimiter", delim_num, 0);
  primitive("divide", divide, 0);
  primitive("endcsname", end_cs_name, 0);
  if enctex.p then
    begin primitive("endmubyte", end_cs_name, 10);
      end;
  primitive("endgroup", end_group, 0); text(frozen_end_group) ← "endgroup";
  eqtb[frozen_end_group] ← eqtb[cur_val];
  primitive("expandafter", expand_after, 0);
  primitive(0);
  primitive("letterspacefont", letterspace_font, 0);
  primitive("pdfcopyfont", pdf_copy_font, 0);
  primitive("fontdimen", assign_font_dimen, 0);
  primitive("halign", halign, 0);
  primitive("hrule", hrule, 0);
  primitive("ignorespaces", ignore_spaces, 0);
  primitive("insert", insert, 0);
  primitive("mark", mark, 0);
  primitive("mathaccent", math_accent, 0);
  primitive("mathchar", math_char_num, 0);
  primitive("mathchoice", math_choice, 0);
  primitive("multiply", multiply, 0);
  primitive("noalign", no_align, 0);
  primitive("noboundary", no_boundary, 0);
  primitive("noexpand", no_expand, 0);
  primitive("pdfprimitive", no_expand, 1);
  primitive("nonscript", non_script, 0);
  primitive("omit", omit, 0);
  primitive("parshape", set_shape, par_shape_loc);
  primitive("penalty", break_penalty, 0);
  primitive("prevgraf", set_prev_graf, 0);
  primitive("radical", radical, 0);
  primitive("read", read_to_cs, 0);
  primitive("relax", relax, 256); { cf. scan_file_name }
  text(frozen_relax) ← "relax"; eqtb[frozen_relax] ← eqtb[cur_val];
  primitive("setbox", set_box, 0);
  primitive("the", the, 0);
  primitive("toks", toks_register, mem_bot);
  primitive("vadjust", vadjust, 0);
  primitive("valign", valign, 0);

```

```
primitive("vcenter", vcenter, 0);  
primitive("vrule", vrule, 0);
```

288* Each primitive has a corresponding inverse, so that it is possible to display the cryptic numeric contents of *eqtb* in symbolic form. Every call of *primitive* in this program is therefore accompanied by some straightforward code that forms part of the *print_cmd_chr* routine below.

```

⟨ Cases of print_cmd_chr for symbolic printing of primitives 245 ⟩ +≡
accent: print_esc("accent");
advance: print_esc("advance");
after_assignment: print_esc("afterassignment");
after_group: print_esc("aftergroup");
assign_font_dimen: print_esc("fontdimen");
begin_group: print_esc("begingroup");
break_penalty: print_esc("penalty");
char_num: print_esc("char");
cs_name: print_esc("csname");
def_font: print_esc("font");
letterspace_font: print_esc("letterspacefont");
pdf_copy_font: print_esc("pdfcopyfont");
delim_num: print_esc("delimiter");
divide: print_esc("divide");
end_cs_name: if chr_code = 10 then print_esc("endmubyte")
  else print_esc("endcsname");
end_group: print_esc("endgroup");
ex_space: print_esc("␣");
expand_after: if chr_code = 0 then print_esc("expandafter")
  ⟨ Cases of expandafter for print_cmd_chr 1764 ⟩;
halign: print_esc("halign");
hrule: print_esc("hrule");
ignore_spaces: if chr_code = 0 then print_esc("ignorespaces")
  else print_esc("pdfprimitive");
insert: print_esc("insert");
ital_corr: print_esc("/");
mark: begin print_esc("mark");
  if chr_code > 0 then print_char("s");
end;
math_accent: print_esc("mathaccent");
math_char_num: print_esc("mathchar");
math_choice: print_esc("mathchoice");
multiply: print_esc("multiply");
no_align: print_esc("noalign");
no_boundary: print_esc("noboundary");
no_expand: if chr_code = 0 then print_esc("noexpand")
  else print_esc("pdfprimitive");
non_script: print_esc("nonscript");
omit: print_esc("omit");
radical: print_esc("radical");
read_to_cs: if chr_code = 0 then print_esc("read") ⟨ Cases of read for print_cmd_chr 1761 ⟩;
relax: print_esc("relax");
set_box: print_esc("setbox");
set_prev_graf: print_esc("prevgraf");
set_shape: case chr_code of
  par_shape_loc: print_esc("parshape");
  ⟨ Cases of set_shape for print_cmd_chr 1866 ⟩
end; { there are no other cases }

```

```
the: if chr_code = 0 then print_esc("the") ⟨Cases of the for print_cmd_chr 1688⟩;  
toks_register: ⟨Cases of toks_register for print_cmd_chr 1834⟩;  
vadjust: print_esc("vadjust");  
valign: if chr_code = 0 then print_esc("valign")  
  ⟨Cases of valign for print_cmd_chr 1703⟩;  
vcenter: print_esc("vcenter");  
vrule: print_esc("vrule");  
partoken_name: print_esc("partokenname");
```

293* \langle Global variables 13 $\rangle + \equiv$

```

save_stack:  $\uparrow$ memory_word;
save_ptr: 0 .. save_size; { first unused entry on save_stack }
max_save_stack: 0 .. save_size; { maximum usage of save stack }
cur_level: quarterword; { current nesting level for groups }
cur_group: group_code; { current group type }
cur_boundary: 0 .. save_size; { where the current level begins }

```

305* A global definition, which sets the level to *level_one*, will not be undone by *unsave*. If at least one global definition of *eqtb*[*p*] has been carried out within the group that just ended, the last such definition will therefore survive.

\langle Store *save_stack*[*save_ptr*] in *eqtb*[*p*], unless *eqtb*[*p*] holds a global value 305* $\rangle \equiv$

```

if (p < int_base)  $\vee$  (p > eqtb_size) then
  if eq_level(p) = level_one then
    begin eq_destroy(save_stack[save_ptr]); { destroy the saved value }
    stat if tracing_restores > 0 then restore_trace(p, "retaining");
    tats
    end
  else begin eq_destroy(eqtb[p]); { destroy the current value }
    eqtb[p]  $\leftarrow$  save_stack[save_ptr]; { restore the saved value }
    stat if tracing_restores > 0 then restore_trace(p, "restoring");
    tats
    end
  else if xq_level[p]  $\neq$  level_one then
    begin eqtb[p]  $\leftarrow$  save_stack[save_ptr]; xq_level[p]  $\leftarrow$  l;
    stat if tracing_restores > 0 then restore_trace(p, "restoring");
    tats
    end
  else begin stat if tracing_restores > 0 then restore_trace(p, "retaining");
    tats
    end

```

This code is used in section 304.

312* ⟨Check the “constant” values for consistency 14⟩ +≡
 if $cs_token_flag + eqtb_size + hash_extra > max_halfword$ **then** $bad \leftarrow 21$;
 if $(hash_offset < 0) \vee (hash_offset > hash_base)$ **then** $bad \leftarrow 42$;

322* **Input stacks and states.** This implementation of \TeX uses two different conventions for representing sequential stacks.

- 1) If there is frequent access to the top entry, and if the stack is essentially never empty, then the top entry is kept in a global variable (even better would be a machine register), and the other entries appear in the array $stack[0 .. (ptr - 1)]$. For example, the semantic stack described above is handled this way, and so is the input stack that we are about to study.
- 2) If there is infrequent top access, the entire stack contents are in the array $stack[0 .. (ptr - 1)]$. For example, the *save_stack* is treated this way, as we have seen.

The state of \TeX 's input mechanism appears in the input stack, whose entries are records with six fields, called *state*, *index*, *start*, *loc*, *limit*, and *name*. This stack is maintained with convention (1), so it is declared in the following way:

```
⟨Types in the outer block 18⟩ +=
  in_state_record = record state_field, index_field: quarterword;
                    start_field, loc_field, limit_field, name_field: halfword;
                    synctex_tag_field: integer; {stack the tag of the current file}
  end;
```

```
323* ⟨Global variables 13⟩ +=
input_stack: ↑in_state_record;
input_ptr: 0 .. stack_size; {first unused location of input_stack}
max_in_stack: 0 .. stack_size; {largest value of input_ptr when pushing}
cur_input: in_state_record; {the “top” input state, according to convention (1)}
```

324* We've already defined the special variable $loc \equiv cur_input.loc_field$ in our discussion of basic input-output routines. The other components of *cur_input* are defined in the same way:

```
define state  $\equiv$  cur_input.state_field {current scanner state}
define index  $\equiv$  cur_input.index_field {reference for buffer information}
define start  $\equiv$  cur_input.start_field {starting position in buffer}
define limit  $\equiv$  cur_input.limit_field {end of current line in buffer}
define name  $\equiv$  cur_input.name_field {name of the current file}
define synctex_tag  $\equiv$  cur_input.synctex_tag_field {SyncTeX tag of the current file}
```

326* Additional information about the current line is available via the *index* variable, which counts how many lines of characters are present in the buffer below the current level. We have $index = 0$ when reading from the terminal and prompting the user for each line; then if the user types, e.g., ‘\input paper’, we will have $index = 1$ while reading the file `paper.tex`. However, it does not follow that *index* is the same as the input stack pointer, since many of the levels on the input stack may come from token lists. For example, the instruction ‘\input paper’ might occur in a token list.

The global variable *in_open* is equal to the *index* value of the highest non-token-list level. Thus, the number of partially read lines in the buffer is $in_open + 1$, and we have $in_open = index$ when we are not reading a token list.

If we are not currently reading from the terminal, or from an input stream, we are reading from the file variable *input_file*[*index*]. We use the notation *terminal_input* as a convenient abbreviation for $name = 0$, and *cur_file* as an abbreviation for *input_file*[*index*].

The global variable *line* contains the line number in the topmost open file, for use in error messages. If we are not reading from the terminal, *line_stack*[*index*] holds the line number for the enclosing level, so that *line* can be restored when the current file has been read. Line numbers should never be negative, since the negative of the current line number is used to identify the user’s output routine in the *mode_line* field of the semantic nest entries.

If more information about the input state is needed, it can be included in small arrays like those shown here. For example, the current page or segment number in the input file might be put into a variable *page*, maintained for enclosing levels in ‘*page_stack*: **array** [1 .. *max_in_open*] **of** *integer*’ by analogy with *line_stack*.

```
define terminal_input  $\equiv$  (name = 0) { are we reading from the terminal? }
define cur_file  $\equiv$  input_file[index] { the current alpha_file variable }
```

⟨ Global variables 13 ⟩ +≡

in_open: 0 .. *max_in_open*; { the number of lines in the buffer, less one }

open_parens: 0 .. *max_in_open*; { the number of open text files }

input_file: ↑*alpha_file*;

line: *integer*; { current line number in the current source file }

line_stack: ↑*integer*;

source_filename_stack: ↑*str_number*;

full_source_filename_stack: ↑*str_number*;

328* Here is a procedure that uses *scanner_status* to print a warning message when a subfile has ended, and at certain other crucial times:

```

⟨Declare the procedure called runaway 328*⟩ ≡
procedure runaway;
  var p: pointer; { head of runaway list }
  begin if scanner_status > skipping then
    begin case scanner_status of
      defining: begin print_nl("Runaway␣definition"); p ← def_ref;
        end;
      matching: begin print_nl("Runaway␣argument"); p ← temp_head;
        end;
      aligning: begin print_nl("Runaway␣preamble"); p ← hold_head;
        end;
      absorbing: begin print_nl("Runaway␣text"); p ← def_ref;
        end;
    end; { there are no other cases }
    print_char("?"); print_ln; show_token_list(link(p), null, error_line - 10);
  end;
end;

```

This code is used in section 137.

330* The *param_stack* is an auxiliary array used to hold pointers to the token lists for parameters at the current level and subsidiary levels of input. This stack is maintained with convention (2), and it grows at a different rate from the others.

```

⟨Global variables 13⟩ +≡
param_stack: ↑pointer; { token list pointers for parameters }
param_ptr: 0 .. param_size; { first unused entry in param_stack }
max_param_stack: integer; { largest value of param_ptr, will be ≤ param_size + 9 }

```

340* But the trick is distracting us from our current goal, which is to understand the input state. So let's concentrate on the data structures that are being pseudoprinted as we finish up the *show_context* procedure.

```

⟨Pseudoprint the line 340*⟩ ≡
  begin_pseudoprint;
  if buffer[limit] = end_line_char then j ← limit
  else j ← limit + 1; { determine the effective end of the line }
  i ← start; mubyte_skeep ← mubyte_keep; mubyte_sstart ← mubyte_start; mubyte_start ← false;
  if j > 0 then
    while i < j do
      begin if i = loc then set_trick_count;
        print_buffer(i);
      end;
    mubyte_keep ← mubyte_skeep; mubyte_start ← mubyte_sstart

```

This code is used in section 334.

346* When a token list has been fully scanned, the following computations should be done as we leave that level of input. The *token_type* tends to be equal to either *backed_up* or *inserted* about 2/3 of the time.

```

procedure end_token_list; { leave a token-list input level }
  begin if token_type ≥ backed_up then { token list to be deleted }
    begin if token_type ≤ inserted then flush_list(start)
    else begin delete_token_ref(start); { update reference count }
      if token_type = macro then { parameters must be flushed }
        while param_ptr > param_start do
          begin decr(param_ptr); flush_list(param_stack[param_ptr]);
          end
        else if (token_type = output_text) ∧ (output_active) then
          fatal_error("Unbalanced_output_routine");
        end;
      end
    end
  else if token_type = u_template then
    if align_state > 500000 then align_state ← 0
    else fatal_error("(interwoven_alignment_preambles_are_not_allowed)");
  pop_input; check_interrupt;
end;

```

347* Sometimes TEX has read too far and wants to “unscan” what it has seen. The *back_input* procedure takes care of this by putting the token just scanned back into the input stream, ready to be read again. This procedure can be used only if *cur_tok* represents the token to be replaced. Some applications of TEX use this procedure a lot, so it has been slightly optimized for speed.

```

procedure back_input; { undoes one token of input }
  var p: pointer; { a token list of length one }
  begin while (loc = null) ∧ (token_type ≠ v_template) ∧ (token_type ≠ output_text) do end_token_list;
    { conserve stack space }
  p ← get_aval; info(p) ← cur_tok;
  if cur_tok < right_brace_limit then
    if cur_tok < left_brace_limit then decr(align_state)
    else incr(align_state);
  push_input; state ← token_list; start ← p; token_type ← backed_up; loc ← p;
    { that was back_list(p), without procedure overhead }
  end;

```

350* The *begin_file_reading* procedure starts a new level of input for lines of characters to be read from a file, or as an insertion from the terminal. It does not take care of opening the file, nor does it set *loc* or *limit* or *line*.

```

procedure begin_file_reading;
  begin if in_open = max_in_open then overflow("text_input_levels", max_in_open);
  if first = buf_size then overflow("buffer_size", buf_size);
  incr(in_open); push_input; index ← in_open; source_filename_stack[index] ← 0;
  full_source_filename_stack[index] ← 0; eof_seen[index] ← false; grp_stack[index] ← cur_boundary;
  if_stack[index] ← cond_ptr; line_stack[index] ← line; start ← first; state ← mid_line; name ← 0;
    { terminal_input is now true }
  ⟨Prepare terminal input SyncTEX information 1920*⟩;
end;

```

353* To get TeX's whole input mechanism going, we perform the following actions.

```

⟨ Initialize the input routines 353* ⟩ ≡
begin input_ptr ← 0; max_in_stack ← 0; source_filename_stack[0] ← 0;
full_source_filename_stack[0] ← 0; in_open ← 0; open_parens ← 0; max_buf_stack ← 0; grp_stack[0] ← 0;
if_stack[0] ← null; param_ptr ← 0; max_param_stack ← 0; first ← buf_size;
repeat buffer[first] ← 0; decr(first);
until first = 0;
scanner_status ← normal; warning_index ← null; first ← 1; state ← new_line; start ← 1; index ← 0;
line ← 0; name ← 0; force_eof ← false; align_state ← 1000000;
if  $\neg$ init_terminal then goto final_end;
limit ← last; first ← last + 1; { init_terminal has set loc and last }
end

```

This code is used in section 1518*.

354* **Getting the next token.** The heart of TEX's input mechanism is the *get_next* procedure, which we shall develop in the next few sections of the program. Perhaps we shouldn't actually call it the "heart," however, because it really acts as TEX's eyes and mouth, reading the source files and gobbling them up. And it also helps TEX to regurgitate stored token lists that are to be processed again.

The main duty of *get_next* is to input one token and to set *cur_cmd* and *cur_chr* to that token's command code and modifier. Furthermore, if the input token is a control sequence, the *eqtb* location of that control sequence is stored in *cur_cs*; otherwise *cur_cs* is set to zero.

Underlying this simple description is a certain amount of complexity because of all the cases that need to be handled. However, the inner loop of *get_next* is reasonably short and fast.

When *get_next* is asked to get the next token of a `\read` line, it sets *cur_cmd* = *cur_chr* = *cur_cs* = 0 in the case that no more tokens appear on that line. (There might not be any tokens at all, if the *end_line_char* has *ignore* as its catcode.)

Some additional routines used by the `encTEX` extension have to be declared at this point.

⟨Declare additional routines for `encTEX 1901*`⟩

```
360* ⟨Tell the user what has run away and try to recover 360*⟩ ≡
begin runaway; { print a definition, argument, or preamble }
if cur_cs = 0 then print_err("File_ended")
else begin cur_cs ← 0; print_err("Forbidden_control_sequence_found");
end;
⟨Print either 'definition' or 'use' or 'preamble' or 'text', and insert tokens that should lead to
recovery 361*⟩;
print("_of_"); sprint_cs(warning_index);
help4("I_suspect_you_have_forgotten_a_}^_,_causing_me")
("to_read_past_where_you_wanted_me_to_stop.")
("I'll_try_to_recover;_but_if_the_error_is_serious,")
("you'd_better_type_`E`_or_`X`_now_and_fix_your_file.");
error;
end
```

This code is used in section 358.

361* The recovery procedure can't be fully understood without knowing more about the TEX routines that should be aborted, but we can sketch the ideas here: For a runaway definition or a runaway balanced text we will insert a right brace; for a runaway preamble, we will insert a special `\cr` token and a right brace; and for a runaway argument, we will set *long_state* to *outer_call* and insert `\par`.

⟨Print either 'definition' or 'use' or 'preamble' or 'text', and insert tokens that should lead to recovery 361*⟩ ≡

```
p ← get_avail;
case scanner_status of
  defining: begin print("_while_scanning_definition"); info(p) ← right_brace_token + "}";
end;
  matching: begin print("_while_scanning_use"); info(p) ← par_token; long_state ← outer_call;
end;
  aligning: begin print("_while_scanning_preamble"); info(p) ← right_brace_token + "}"; q ← p;
  p ← get_avail; link(p) ← q; info(p) ← cs_token_flag + frozen_cr; align_state ← -1000000;
end;
  absorbing: begin print("_while_scanning_text"); info(p) ← right_brace_token + "}";
end;
end; { there are no other cases }
ins_list(p)
```

This code is used in section 360*.

363* Now we're ready to take the plunge into *get_next* itself. Parts of this routine are executed more often than any other instructions of TeX.

```

define switch = 25 { a label in get_next }
define start_cs = 26 { another }

procedure get_next; { sets cur_cmd, cur_chr, cur_cs to next token }
label restart, { go here to get the next input token }
  switch, { go here to eat the next character from a file }
  reswitch, { go here to digest it again }
  start_cs, { go here to start looking for a control sequence }
  found, { go here when a control sequence has been found }
  exit; { go here when the next input token has been got }
var k: 0 .. buf_size; { an index into buffer }
  t: halfword; { a token }
  i, j: 0 .. buf_size; { more indexes for encTeX }
  mubyte_incs: boolean; { control sequence is converted by mubyte }
  p: pointer; { for encTeX test if noexpanding }
  cat: 0 .. max_char_code; { cat_code(cur_chr), usually }
  c, cc: ASCII_code; { constituents of a possible expanded code }
  d: 2 .. 3; { number of excess characters in an expanded code }
begin restart: cur_cs ← 0;
if state ≠ token_list then ⟨Input from external file, goto restart if no input found 365*⟩
else ⟨Input from token list, goto restart if end of list or if a parameter needs to be expanded 379*⟩;
  ⟨If an alignment entry has just ended, take appropriate action 364⟩;
exit: end;

365* ⟨Input from external file, goto restart if no input found 365*⟩ ≡
begin switch: if loc ≤ limit then { current line not yet finished }
  begin { Use k instead of loc for type correctness. }
  k ← loc; cur_chr ← read_buffer(k); loc ← k; incr(loc);
  if (mubyte_token > 0) then
    begin state ← mid_line; cur_cs ← mubyte_token - cs_token_flag; goto found;
    end;
  reswitch: cur_cmd ← cat_code(cur_chr); ⟨Change state if necessary, and goto switch if the current
    character should be ignored, or goto reswitch if the current character changes to another 366⟩;
  end
else begin state ← new_line;
  ⟨Move to next line of file, or goto restart if there is no next line, or return if a \read line has
  finished 382⟩;
  check_interrupt; goto switch;
  end;
end

```

This code is used in section 363*.

376* Control sequence names are scanned only when they appear in some line of a file; once they have been scanned the first time, their *eqtb* location serves as a unique identification, so TEX doesn't need to refer to the original name any more except when it prints the equivalent in symbolic form.

The program that scans a control sequence has been written carefully in order to avoid the blowups that might otherwise occur if a malicious user tried something like ‘\catcode`15=0’. The algorithm might look at *buffer*[*limit* + 1], but it never looks at *buffer*[*limit* + 2].

If expanded characters like ‘^^A’ or ‘^^df’ appear in or just following a control sequence name, they are converted to single characters in the buffer and the process is repeated, slowly but surely.

```

⟨Scan a control sequence and set state ← skip_blanks or mid_line 376*⟩ ≡
  begin if loc > limit then cur_cs ← null_cs { state is irrelevant in this case }
  else begin start_cs: mubyte_incs ← false; k ← loc; mubyte_skeep ← mubyte_keep;
    cur_chr ← read_buffer(k); cat ← cat_code(cur_chr);
    if (mubyte_in > 0) ∧ (¬mubyte_incs) ∧ ((mubyte_skeep > 0) ∨ (cur_chr ≠ buffer[k])) then
      mubyte_incs ← true;
      incr(k);
      if mubyte_token > 0 then
        begin state ← mid_line; cur_cs ← mubyte_token − cs_token_flag; goto found;
        end;
      if cat = letter then state ← skip_blanks
      else if cat = spacer then state ← skip_blanks
      else state ← mid_line;
      if (cat = letter) ∧ (k ≤ limit) then ⟨Scan ahead in the buffer until finding a nonletter; if an expanded
        code is encountered, reduce it and goto start_cs; otherwise if a multiletter control sequence is
        found, adjust cur_cs and loc, and goto found 378*⟩
      else ⟨If an expanded code is present, reduce it and goto start_cs 377*⟩;
      mubyte_keep ← mubyte_skeep; cur_cs ← single_base + read_buffer(loc); incr(loc);
      end;
found: cur_cmd ← eq_type(cur_cs); cur_chr ← equiv(cur_cs);
  if cur_cmd ≥ outer_call then check_outer_validity;
  if write_noexpanding then
    begin p ← mubyte_cswrite[cur_cs mod 128];
    while p ≠ null do
      if info(p) = cur_cs then
        begin cur_cmd ← relax; cur_chr ← 256; p ← null;
        end
      else p ← link(link(p));
    end;
  end

```

This code is used in section 366.

377* Whenever we reach the following piece of code, we will have $cur_chr = buffer[k-1]$ and $k \leq limit + 1$ and $cat = cat_code(cur_chr)$. If an expanded code like $\text{\^{\^}A}$ or $\text{\^{\^}df}$ appears in $buffer[(k-1) .. (k+1)]$ or $buffer[(k-1) .. (k+2)]$, we will store the corresponding code in $buffer[k-1]$ and shift the rest of the buffer left two or three places.

```

⟨ If an expanded code is present, reduce it and goto start_cs 377* ⟩ ≡
  begin if  $buffer[k] = cur\_chr$  then if  $cat = sup\_mark$  then if  $k < limit$  then
    begin  $c \leftarrow buffer[k+1]$ ; if  $c < '200$  then { yes, one is indeed present }
      begin  $d \leftarrow 2$ ;
        if  $is\_hex(c)$  then if  $k+2 \leq limit$  then
          begin  $cc \leftarrow buffer[k+2]$ ; if  $is\_hex(cc)$  then  $incr(d)$ ;
            end;
          if  $d > 2$  then
            begin  $hex\_to\_cur\_chr$ ;  $buffer[k-1] \leftarrow cur\_chr$ ;
              end
            else if  $c < '100$  then  $buffer[k-1] \leftarrow c + '100$ 
              else  $buffer[k-1] \leftarrow c - '100$ ;
             $limit \leftarrow limit - d$ ;  $first \leftarrow first - d$ ;
            if  $mubyte\_in > 0$  then  $mubyte\_keep \leftarrow k - loc$ ;
            while  $k \leq limit$  do
              begin  $buffer[k] \leftarrow buffer[k+d]$ ;  $incr(k)$ ;
                end;
              goto start_cs;
            end;
          end;
        end;
      end;
    end
  end

```

This code is used in sections 376* and 378*.

```

378* ⟨Scan ahead in the buffer until finding a nonletter; if an expanded code is encountered, reduce it
and goto start_cs; otherwise if a multiletter control sequence is found, adjust cur_cs and loc, and
goto found 378*⟩ ≡
begin repeat cur_chr ← read_buffer(k); cat ← cat_code(cur_chr);
  if mubyte_token > 0 then cat ← escape;
  if (mubyte_in > 0) ∧ (¬mubyte_incs) ∧ (cat = letter) ∧ ((mubyte_skip > 0) ∨ (cur_chr ≠ buffer[k]))
    then mubyte_incs ← true;
    incr(k);
until (cat ≠ letter) ∨ (k > limit);
⟨If an expanded code is present, reduce it and goto start_cs 377*⟩;
if cat ≠ letter then
  begin decr(k); k ← k − mubyte_skip;
  end;
if k > loc + 1 then { multiletter control sequence has been scanned }
  begin if mubyte_incs then { multibyte in csname occurs }
    begin i ← loc; j ← first; mubyte_keep ← mubyte_skeep;
    if j − loc + k > max_buf_stack then
      begin max_buf_stack ← j − loc + k;
      if max_buf_stack ≥ buf_size then
        begin max_buf_stack ← buf_size; overflow("buffer_size", buf_size);
        end;
      end;
    while i < k do
      begin buffer[j] ← read_buffer(i); incr(i); incr(j);
      end;
      if j = first + 1 then cur_cs ← single_base + buffer[first]
      else cur_cs ← id_lookup(first, j − first);
      end
    else cur_cs ← id_lookup(loc, k − loc);
    loc ← k; goto found;
  end;
end

```

This code is used in section 376*.

379* Let's consider now what happens when *get_next* is looking at a token list.

```

⟨Input from token list, goto restart if end of list or if a parameter needs to be expanded 379*⟩ ≡
if loc ≠ null then { list not exhausted }
  begin t ← info(loc); loc ← link(loc); { move to next }
  if t ≥ cs.token_flag then { a control sequence token }
    begin cur_cs ← t − cs.token_flag; cur_cmd ← eq_type(cur_cs); cur_chr ← equiv(cur_cs);
    if cur_cmd ≥ outer_call then
      if cur_cmd = dont_expand then ⟨Get the next token, suppressing expansion 380⟩
      else begin if (cur_cs = end_write) ∧ (mode = 0) then
        fatal_error("Unbalanced_write_command");
        check_outer_validity;
      end;
    if write_noexpanding then
      begin p ← mubyte_cswrite[cur_cs mod 128];
      while p ≠ null do
        if info(p) = cur_cs then
          begin cur_cmd ← relax; cur_chr ← 256; p ← null;
          end
        else p ← link(link(p));
      end;
    end
  else begin cur_cmd ← t div '400; cur_chr ← t mod '400;
    case cur_cmd of
      left_brace: incr(align_state);
      right_brace: decr(align_state);
      out_param: ⟨Insert macro parameter and goto restart 381⟩;
      othercases do_nothing
    endcases;
  end;
end
else begin { we are done with this token list }
  end_token_list; goto restart; { resume previous level }
end

```

This code is used in section 363*.

385* If the user has set the *pausing* parameter to some positive value, and if nonstop mode has not been selected, each line of input is displayed on the terminal and the transcript file, followed by ‘=>’. TEX waits for a response. If the response is simply *carriage_return*, the line is accepted as it stands, otherwise the line typed is used instead of the line in the file.

```

procedure firm_up_the_line;
  var k: 0 .. buf_size; { an index into buffer }
  begin limit ← last;
  if pausing > 0 then
    if interaction > nonstop_mode then
      begin wake_up_terminal; print_ln; k ← start;
      while k < limit do
        begin print_buffer(k)
        end;
      first ← limit; prompt_input("=>"); { wait for user response }
      if last > first then
        begin for k ← first to last - 1 do { move line down in buffer }
          buffer[k + start - first] ← buffer[k];
        limit ← start + last - first;
        end;
      end;
    end;
  end;

```

388* **Expanding the next token.** Only a dozen or so command codes $> \text{max_command}$ can possibly be returned by *get_next*; in increasing order, they are *undefined_cs*, *expand_after*, *no_expand*, *input*, *if_test*, *fi_or_else*, *cs_name*, *convert*, *the*, *top_bot_mark*, *call*, *long_call*, *outer_call*, *long_outer_call*, and *end_template*.

The *expand* subroutine is used when $\text{cur_cmd} > \text{max_command}$. It removes a “call” or a conditional or one of the other special operations just listed. It follows that *expand* might invoke itself recursively. In all cases, *expand* destroys the current token, but it sets things up so that the next *get_next* will deliver the appropriate next token. The value of *cur_tok* need not be known when *expand* is called.

Since several of the basic scanning routines communicate via global variables, their values are saved as local variables of *expand* so that recursive calls don’t invalidate them.

```

⟨Declare the procedure called macro_call 415⟩
⟨Declare the procedure called insert_relax 405⟩
⟨Declare  $\epsilon$ -TEX procedures for expanding 1753⟩
procedure pass_text; forward;
procedure start_input; forward;
procedure conditional; forward;
procedure get_x_token; forward;
procedure conv_toks; forward;
procedure ins_the_toks; forward;
procedure expand;
  label reswitch;
  var t: halfword; { token that is being “expanded after” }
      b: boolean; { keep track of nested csnames }
      p, q, r: pointer; { for list manipulation }
      j: 0 .. buf_size; { index into buffer }
      cv_backup: integer; { to save the global quantity cur_val }
      cvl_backup, radix_backup, co_backup: small_number; { to save cur_val_level, etc. }
      backup_backup: pointer; { to save link(backup_head) }
      save_scanner_status: small_number; { temporary storage of scanner_status }
  begin incr(expand_depth_count);
  if expand_depth_count  $\geq$  expand_depth then overflow("expansion_depth", expand_depth);
  cv_backup  $\leftarrow$  cur_val; cvl_backup  $\leftarrow$  cur_val_level; radix_backup  $\leftarrow$  radix; co_backup  $\leftarrow$  cur_order;
  backup_backup  $\leftarrow$  link(backup_head);
reswitch: if cur_cmd  $<$  call then ⟨Expand a nonmacro 391⟩
  else if cur_cmd  $<$  end_template then macro_call
    else ⟨Insert a token containing frozen_endv 401⟩;
  cur_val  $\leftarrow$  cv_backup; cur_val_level  $\leftarrow$  cvl_backup; radix  $\leftarrow$  radix_backup; cur_order  $\leftarrow$  co_backup;
  link(backup_head)  $\leftarrow$  backup_backup; decr(expand_depth_count);
end;

```

393* The implementation of `\noexpand` is a bit trickier, because it is necessary to insert a special ‘*dont.expand*’ marker into TEX’s reading mechanism. This special marker is processed by *get.next*, but it does not slow down the inner loop.

Since `\outer` macros might arise here, we must also clear the *scanner.status* temporarily.

```

⟨Suppress expansion of the next token 393*⟩ ≡
begin save_scanner_status ← scanner_status; scanner_status ← normal; get_token;
scanner_status ← save_scanner_status; t ← cur_tok; back_input;
  { now start and loc point to the backed-up token t }
if (t ≥ cs_token_flag) ∧ (t ≠ end_write_token) then
  begin p ← get_avail; info(p) ← cs_token_flag + frozen_dont_expand; link(p) ← loc; start ← p;
  loc ← p;
  end;
end

```

This code is used in section 391.

```

398* ⟨Manufacture a control sequence name 398*⟩ ≡
begin r ← get_avail; p ← r; { head of the list of characters }
b ← is_in_csname; is_in_csname ← true;
repeat get_x_token;
  if cur_cs = 0 then store_new_token(cur_tok);
until cur_cs ≠ 0;
if (cur_cmd ≠ end_cs_name) ∨ (cur_chr ≠ 0) then ⟨Complain about missing \endcsname 399⟩;
is_in_csname ← b; ⟨Look up the characters of list r in the hash table, and set cur_cs 400⟩;
flush_list(r);
if eq_type(cur_cs) = undefined_cs then
  begin eq_define(cur_cs, relax, 256); { N.B.: The save_stack might change }
  end; { the control sequence will now match ‘\relax’ }
cur_tok ← cur_cs + cs_token_flag; back_input;
end

```

This code is used in section 391.

416* Before we put a new token list on the input stack, it is wise to clean off all token lists that have recently been depleted. Then a user macro that ends with a call to itself will not require unbounded stack space.

```

⟨Feed the macro body and its parameters to the scanner 416*⟩ ≡
while (loc = null) ∧ (token_type ≠ v_template) ∧ (token_type ≠ output_text) do end_token_list;
  { conserve stack space }
begin_token_list(ref_count, macro); name ← warning_index; loc ← link(r);
if n > 0 then
  begin if param_ptr + n > max_param_stack then
  begin max_param_stack ← param_ptr + n;
  if max_param_stack > param_size then overflow("parameter_stack_size", param_size);
  end;
  for m ← 0 to n - 1 do param_stack[param_ptr + m] ← pstack[m];
  param_ptr ← param_ptr + n;
  end

```

This code is used in section 415.

426* If the parameter consists of a single group enclosed in braces, we must strip off the enclosing braces. That's why *rbrace_ptr* was introduced.

```

⟨Tidy up the parameter just scanned, and tuck it away 426*⟩ ≡
  begin if ( $m = 1$ )  $\wedge$  ( $info(p) < right\_brace\_limit$ ) then
    begin  $link(rbrace\_ptr) \leftarrow null$ ;  $free\_avail(p)$ ;  $p \leftarrow link(temp\_head)$ ;  $pstack[n] \leftarrow link(p)$ ;  $free\_avail(p)$ ;
    end
  else  $pstack[n] \leftarrow link(temp\_head)$ ;
   $incr(n)$ ;
  if  $tracing\_macros > 0$  then
    if ( $tracing\_stack\_levels = 0$ )  $\vee$  ( $input\_ptr < tracing\_stack\_levels$ ) then
      begin  $begin\_diagnostic$ ;  $print\_nl(match\_chr)$ ;  $print\_int(n)$ ;  $print("<-")$ ;
       $show\_token\_list(pstack[n - 1], null, 1000)$ ;  $end\_diagnostic(false)$ ;
      end;
    end

```

This code is used in section 418.

```

427* ⟨Show the text of the macro being expanded 427*⟩ ≡
  begin  $begin\_diagnostic$ ;
  if  $tracing\_stack\_levels > 0$  then
    if  $input\_ptr < tracing\_stack\_levels$  then
      begin  $v \leftarrow input\_ptr$ ;  $print\_ln$ ;  $print\_char("\~")$ ;
      while  $v > 0$  do
        begin  $print\_char(". ")$ ;  $decr(v)$ ;
        end;
         $print\_cs(warning\_index)$ ;  $token\_show(ref\_count)$ ;
      end
    else begin  $print\_char("\~")$ ;  $print\_char("\~")$ ;  $print\_cs(warning\_index)$ ;
    end
  else begin  $print\_ln$ ;  $print\_cs(warning\_index)$ ;  $token\_show(ref\_count)$ ;
  end;
   $end\_diagnostic(false)$ ;
  end

```

This code is used in section 415.


```
440* 〈Fetch a character code from some table 440*〉 ≡
  begin scan_char_num;
  if m = xord_code_base then scanned_result(xord[cur_val])(int_val)
  else if m = xchr_code_base then scanned_result(xchr[cur_val])(int_val)
  else if m = xprn_code_base then scanned_result(xprn[cur_val])(int_val)
  else if m = math_code_base then scanned_result(ho(math_code(cur_val)))(int_val)
  else if m < math_code_base then scanned_result(equiv(m + cur_val))(int_val)
  else scanned_result(eqtb[m + cur_val].int)(int_val);
  end
```

This code is used in section 439.

510* Here we input on-line into the *buffer* array, prompting the user explicitly if $n \geq 0$. The value of n is set negative so that additional prompts will not be given in the case of multi-line input.

\langle Input for `\read` from the terminal 510* $\rangle \equiv$

```

if interaction > nonstop_mode then
  if  $n < 0$  then prompt_input("")
  else begin wake_up_terminal; print_ln; sprint_cs(r); prompt_input("=");  $n \leftarrow -1$ ;
  end
else begin limit  $\leftarrow 0$ ; fatal_error("***_(cannot_\read_from_terminal_in_nonstop_modes)");
end

```

This code is used in section 509.

527* \langle Either process `\ifcase` or set b to the value of a boolean condition 527* $\rangle \equiv$

```

case this_if of
  if_char_code, if_cat_code:  $\langle$  Test if two characters match 532  $\rangle$ ;
  if_int_code, if_dim_code:  $\langle$  Test relation between integers or dimensions 529  $\rangle$ ;
  if_odd_code:  $\langle$  Test if an integer is odd 530  $\rangle$ ;
  if_vmode_code:  $b \leftarrow (abs(mode) = vmode)$ ;
  if_hmode_code:  $b \leftarrow (abs(mode) = hmode)$ ;
  if_mmode_code:  $b \leftarrow (abs(mode) = mmode)$ ;
  if_inner_code:  $b \leftarrow (mode < 0)$ ;
  if_void_code, if_hbox_code, if_vbox_code:  $\langle$  Test box register status 531  $\rangle$ ;
  if_x_code:  $\langle$  Test if two tokens match 533  $\rangle$ ;
  if_eof_code: begin scan_four_bit_int_or_18;
    if cur_val = 18 then  $b \leftarrow \neg shellenabldp$ 
    else  $b \leftarrow (read\_open[cur\_val] = closed)$ ;
  end;
  if_true_code:  $b \leftarrow true$ ;
  if_false_code:  $b \leftarrow false$ ;
   $\langle$  Cases for conditional 1767  $\rangle$ 
  if_case_code:  $\langle$  Select the appropriate case and return or goto common_ending 535  $\rangle$ ;
  if_pdfprimitive_code: begin save_scanner_status  $\leftarrow scanner\_status$ ; scanner_status  $\leftarrow normal$ ; get_next;
    scanner_status  $\leftarrow save\_scanner\_status$ ;
    if cur_cs < hash_base then  $m \leftarrow prim\_lookup(cur\_cs - single\_base)$ 
    else  $m \leftarrow prim\_lookup(text(cur\_cs))$ ;
     $b \leftarrow ((cur\_cmd \neq undefined\_cs) \wedge (m \neq undefined\_primitive) \wedge (cur\_cmd = prim\_eq\_type(m)) \wedge (cur\_chr = prim\_equiv(m)))$ ;
  end;
end { there are no other cases }

```

This code is used in section 524.

539* The file names we shall deal with have the following structure: If the name contains ‘/’ or ‘:’ (for Amiga only), the file area consists of all characters up to and including the final such character; otherwise the file area is null. If the remaining file name contains ‘.’, the file extension consists of all such characters from the last ‘.’ to the end, otherwise the file extension is null.

We can scan such file names easily by using two global variables that keep track of the occurrences of area and extension delimiters:

```

⟨Global variables 13⟩ +≡
area_delimiter: pool_pointer; { the most recent ‘/’, if any }
ext_delimiter: pool_pointer; { the most recent ‘.’, if any }

```

540* Input files that can’t be found in the user’s area may appear in a standard system area called *TEX_area*. Font metric files whose areas are not given explicitly are assumed to appear in a standard system area called *TEX_font_area*. These system area names will, of course, vary from place to place.

In C, the default paths are specified separately.

541* Here now is the first of the system-dependent routines for file name scanning.

```

procedure begin_name;
  begin area_delimiter ← 0; ext_delimiter ← 0; quoted_filename ← false;
  end;

```

542* And here’s the second. The string pool might change as the file name is being scanned, since a new *\csname* might be entered; therefore we keep *area_delimiter* and *ext_delimiter* relative to the beginning of the current string, instead of assigning an absolute address like *pool_ptr* to them.

```

function more_name(c: ASCII_code): boolean;
  begin if (c = "␣") ∧ stop_at_space ∧ (¬quoted_filename) then more_name ← false
  else if c = "" then
    begin quoted_filename ← ¬quoted_filename; more_name ← true;
    end
  else begin str_room(1); append_char(c); { contribute c to the current string }
    if IS_DIR_SEP(c) then
      begin area_delimiter ← cur_length; ext_delimiter ← 0;
      end
    else if c = "." then ext_delimiter ← cur_length;
      more_name ← true;
    end;
  end;

```

543* The third. If a string is already in the string pool, the function *slow_make_string* does not create a new string but returns this string number, thus saving string space. Because of this new property of the returned string number it is not possible to apply *flush_string* to these strings.

```

procedure end_name;
  var temp_str: str_number; { result of file name cache lookups }
      j, s, t: pool_pointer; { running indices }
      must_quote: boolean; { whether we need to quote a string }
  begin if str_ptr + 3 > max_strings then overflow("number_of_strings", max_strings - init_str_ptr);
  str_room(6); { Room for quotes, if needed. }
  { add quotes if needed }
  if area_delimiter ≠ 0 then
    begin { maybe quote cur_area }
    must_quote ← false; s ← str_start[str_ptr]; t ← str_start[str_ptr] + area_delimiter; j ← s;
    while (¬must_quote) ∧ (j < t) do
      begin must_quote ← str_pool[j] = "␣"; incr(j);
      end;
    if must_quote then
      begin for j ← pool_ptr - 1 downto t do str_pool[j + 2] ← str_pool[j];
      str_pool[t + 1] ← "␣";
      for j ← t - 1 downto s do str_pool[j + 1] ← str_pool[j];
      str_pool[s] ← "␣";
      if ext_delimiter ≠ 0 then ext_delimiter ← ext_delimiter + 2;
      area_delimiter ← area_delimiter + 2; pool_ptr ← pool_ptr + 2;
      end;
    end; { maybe quote cur_name }
  s ← str_start[str_ptr] + area_delimiter;
  if ext_delimiter = 0 then t ← pool_ptr
  else t ← str_start[str_ptr] + ext_delimiter - 1;
  must_quote ← false; j ← s;
  while (¬must_quote) ∧ (j < t) do
    begin must_quote ← str_pool[j] = "␣"; incr(j);
    end;
  if must_quote then
    begin for j ← pool_ptr - 1 downto t do str_pool[j + 2] ← str_pool[j];
    str_pool[t + 1] ← "␣";
    for j ← t - 1 downto s do str_pool[j + 1] ← str_pool[j];
    str_pool[s] ← "␣";
    if ext_delimiter ≠ 0 then ext_delimiter ← ext_delimiter + 2;
    pool_ptr ← pool_ptr + 2;
    end;
  if ext_delimiter ≠ 0 then
    begin { maybe quote cur_ext }
    s ← str_start[str_ptr] + ext_delimiter - 1; t ← pool_ptr; must_quote ← false; j ← s;
    while (¬must_quote) ∧ (j < t) do
      begin must_quote ← str_pool[j] = "␣"; incr(j);
      end;
    if must_quote then
      begin str_pool[t + 1] ← "␣";
      for j ← t - 1 downto s do str_pool[j + 1] ← str_pool[j];
      str_pool[s] ← "␣"; pool_ptr ← pool_ptr + 2;
      end;
    end;
  end;

```

```

if area_delimiter = 0 then cur_area ← ""
else begin cur_area ← str_ptr; str_start[str_ptr + 1] ← str_start[str_ptr] + area_delimiter; incr(str_ptr);
  temp_str ← search_string(cur_area);
  if temp_str > 0 then
    begin cur_area ← temp_str; decr(str_ptr); { no flush_string, pool_ptr will be wrong! }
    for j ← str_start[str_ptr + 1] to pool_ptr - 1 do
      begin str_pool[j - area_delimiter] ← str_pool[j];
      end;
    pool_ptr ← pool_ptr - area_delimiter; { update pool_ptr }
    end;
  end;
if ext_delimiter = 0 then
  begin cur_ext ← ""; cur_name ← slow_make_string;
  end
else begin cur_name ← str_ptr;
  str_start[str_ptr + 1] ← str_start[str_ptr] + ext_delimiter - area_delimiter - 1; incr(str_ptr);
  cur_ext ← make_string; decr(str_ptr); { undo extension string to look at name part }
  temp_str ← search_string(cur_name);
  if temp_str > 0 then
    begin cur_name ← temp_str; decr(str_ptr); { no flush_string, pool_ptr will be wrong! }
    for j ← str_start[str_ptr + 1] to pool_ptr - 1 do
      begin str_pool[j - ext_delimiter + area_delimiter + 1] ← str_pool[j];
      end;
    pool_ptr ← pool_ptr - ext_delimiter + area_delimiter + 1; { update pool_ptr }
    end;
  cur_ext ← slow_make_string; { remake extension string }
  end;
end;

```

544* Conversely, here is a routine that takes three strings and prints a file name that might have produced them. (The routine is system dependent, because some operating systems put the file area last instead of first.)

```

define check_quoted(#) ≡ { check if string # needs quoting }
  if # ≠ 0 then
    begin j ← str_start[#];
    while (¬must_quote) ∧ (j < str_start[# + 1]) do
      begin must_quote ← str_pool[j] = "␣"; incr(j);
      end;
    end
define print_quoted(#) ≡ { print string #, omitting quotes }
  if # ≠ 0 then
    for j ← str_start[#] to str_start[# + 1] − 1 do
      if so(str_pool[j]) ≠ "" then print(so(str_pool[j]))

```

(Basic printing procedures 57) +≡

```

procedure print_file_name(n, a, e : integer);
  var must_quote: boolean; { whether to quote the filename }
      j: pool_pointer; { index into str_pool }
  begin must_quote ← false; check_quoted(a); check_quoted(n);
  check_quoted(e); { FIXME: Alternative is to assume that any filename that has to be quoted has at least
    one quoted component...if we pick this, a number of insertions of print_file_name should go away.
    must_quote := ((a ≠ 0) and (str_pool[str_start[a]] = "")) or ((n ≠ 0) and (str_pool[str_start[n]] = "")) or
    ((e ≠ 0) and (str_pool[str_start[e]] = "")); }
  if must_quote then print_char("");
  print_quoted(a); print_quoted(n); print_quoted(e);
  if must_quote then print_char("");
  end;

```

545* Another system-dependent routine is needed to convert three internal TEX strings into the *name_of_file* value that is used to open files. The present code allows both lowercase and uppercase letters in the file name.

```

define append_to_name(#) ≡
  begin c ← #;
  if ¬(c = "") then
    begin incr(k);
    if k ≤ file_name_size then name_of_file[k] ← xchr[c];
    end
  end
procedure pack_file_name(n, a, e : str_number);
  var k: integer; { number of positions filled in name_of_file }
      c: ASCII_code; { character being packed }
      j: pool_pointer; { index into str_pool }
  begin k ← 0;
  if name_of_file then libc_free(name_of_file);
  name_of_file ← xmalloc_array(ASCII_code, length(a) + length(n) + length(e) + 1);
  for j ← str_start[a] to str_start[a + 1] − 1 do append_to_name(so(str_pool[j]));
  for j ← str_start[n] to str_start[n + 1] − 1 do append_to_name(so(str_pool[j]));
  for j ← str_start[e] to str_start[e + 1] − 1 do append_to_name(so(str_pool[j]));
  if k ≤ file_name_size then name_length ← k else name_length ← file_name_size;
  name_of_file[name_length + 1] ← 0;
  end;

```

546* A messier routine is also needed, since format file names must be scanned before TEX's string mechanism has been initialized. We shall use the global variable *TEX_format_default* to supply the text for default system areas and extensions related to format files.

Under UNIX we don't give the area part, instead depending on the path searching that will happen during file opening. Also, the length will be set in the main program.

```
define format_area_length = 0 { length of its area part }
define format_ext_length = 4 { length of its '.fmt' part }
define format_extension = ".fmt" { the extension, as a WEB constant }
```

⟨Global variables 13⟩ +=

```
format_default_length: integer;
TEX_format_default: cstring;
```

547* We set the name of the default format file and the length of that name in C, instead of Pascal, since we want them to depend on the name of the program.

549* Here is the messy routine that was just mentioned. It sets *name_of_file* from the first *n* characters of *TEX_format_default*, followed by *buffer*[*a* .. *b*], followed by the last *format_ext_length* characters of *TEX_format_default*.

We dare not give error messages here, since TEX calls this routine before the *error* routine is ready to roll. Instead, we simply drop excess characters, since the error will be detected in another way when a strange file name isn't found.

```
procedure pack_buffered_name(n : small_number; a, b : integer);
  var k: integer; { number of positions filled in name_of_file }
      c: ASCII_code; { character being packed }
      j: integer; { index into buffer or TEX_format_default }
  begin if n + b - a + 1 + format_ext_length > file_name_size then
    b ← a + file_name_size - n - 1 - format_ext_length;
  k ← 0;
  if name_of_file then libc_free(name_of_file);
  name_of_file ← xmalloc_array(ASCII_code, n + (b - a + 1) + format_ext_length + 1);
  for j ← 1 to n do append_to_name(xord[ucharcast(TEX_format_default[j])]);
  for j ← a to b do append_to_name(buffer[j]);
  for j ← format_default_length - format_ext_length + 1 to format_default_length do
    append_to_name(xord[ucharcast(TEX_format_default[j])]);
  if k ≤ file_name_size then name_length ← k else name_length ← file_name_size;
  name_of_file[name_length + 1] ← 0;
end;
```


550* Here is the only place we use *pack_buffered_name*. This part of the program becomes active when a “virgin” TEX is trying to get going, just after the preliminary initialization, or when the user is substituting another format file by typing ‘&’ after the initial ‘**’ prompt. The buffer contains the first line of input in *buffer[loc .. (last - 1)]*, where *loc < last* and *buffer[loc] ≠ “ ”*.

{Declare the function called *open_fmt_file* 550*} ≡

```

function open_fmt_file: boolean;
  label found, exit;
  var j: 0 .. buf_size; { the first space after the format file name }
  begin j ← loc;
  if buffer[loc] = "&" then
    begin incr(loc); j ← loc; buffer[last] ← " ";
    while buffer[j] ≠ " " do incr(j);
    pack_buffered_name(0, loc, j - 1); { Kpathsea does everything }
    if w_open_in(fmt_file) then goto found;
    wake_up_terminal; wterm('Sorry, I can't find the format ');
    fputs(stringcast(name_of_file + 1), stdout); wterm(''; will try ');
    fputs(TEX_format_default + 1, stdout); wterm_ln(''.'); update_terminal;
    end; { now pull out all the stops: try for the system plain file }
    pack_buffered_name(format_default_length - format_ext_length, 1, 0);
  if ¬w_open_in(fmt_file) then
    begin wake_up_terminal; wterm('I can't find the format file ');
    fputs(TEX_format_default + 1, stdout); wterm_ln(''!'); open_fmt_file ← false; return;
    end;
  found: loc ← j; open_fmt_file ← true;
  exit: end;

```

This code is used in section 1482*.

551* Operating systems often make it possible to determine the exact name (and possible version number) of a file that has been opened. The following routine, which simply makes a TEX string from the value of *name_of_file*, should ideally be changed to deduce the full name of file *f*, which is the file most recently opened, if it is possible to do this in a Pascal program.

This routine might be called after string memory has overflowed, hence we dare not use ‘*str_room*’.

```

function make_name_string: str_number;
  var k: 1 .. file_name_size; {index into name_of_file }
      save_area_delimiter, save_ext_delimiter: pool_pointer;
      save_name_in_progress, save_stop_at_space: boolean;
  begin if (pool_ptr + name_length > pool_size) ∨ (str_ptr = max_strings) ∨ (cur_length > 0) then
      make_name_string ← "?"
  else begin for k ← 1 to name_length do append_char(xord[name_of_file[k]]);
      make_name_string ← make_string; { At this point we also set cur_name, cur_ext, and cur_area to
      match the contents of name_of_file. }
      save_area_delimiter ← area_delimiter; save_ext_delimiter ← ext_delimiter;
      save_name_in_progress ← name_in_progress; save_stop_at_space ← stop_at_space;
      name_in_progress ← true; begin_name; stop_at_space ← false; k ← 1;
      while (k ≤ name_length) ∧ (more_name(name_of_file[k])) do incr(k);
      stop_at_space ← save_stop_at_space; end_name; name_in_progress ← save_name_in_progress;
      area_delimiter ← save_area_delimiter; ext_delimiter ← save_ext_delimiter;
  end;
end;

function a_make_name_string(var f : alpha_file): str_number;
  begin a_make_name_string ← make_name_string;
  end;

function b_make_name_string(var f : byte_file): str_number;
  begin b_make_name_string ← make_name_string;
  end;

function w_make_name_string(var f : word_file): str_number;
  begin w_make_name_string ← make_name_string;
  end;

```

552* Now let's consider the “driver” routines by which TeX deals with file names in a system-independent manner. First comes a procedure that looks for a file name in the input by calling *get_x_token* for the information.

```

procedure scan_file_name;
  label done;
  var save_warning_index: pointer;
  begin save_warning_index ← warning_index; warning_index ← cur_cs;
    { store cur_cs here to remember until later }
  ⟨ Get the next non-blank non-relax non-call token 430 ⟩;
    { here the program expands tokens and removes spaces and \relaxes from the input. The \relax
    removal follows LuaTeX's implementation, and other cases of balanced text scanning. }
  back_input; { return the last token to be read by either code path }
  if cur_cmd = left_brace then scan_file_name_braced
  else begin name_in_progress ← true; begin_name; ⟨ Get the next non-blank non-call token 432 ⟩;
    loop begin if (cur_cmd > other_char) ∨ (cur_chr > 255) then { not a character }
      begin back_input; goto done;
    end; { If cur_chr is a space and we're not scanning a token list, check whether we're at the end
    of the buffer. Otherwise we end up adding spurious spaces to file names in some cases. }
    if (cur_chr = " ") ∧ (state ≠ token_list) ∧ (loc > limit) then goto done;
    if ¬more_name(cur_chr) then goto done;
    get_x_token;
    end;
  end;
done: end_name; name_in_progress ← false; warning_index ← save_warning_index;
  { restore warning_index }
end;

```

556* If some trouble arises when \TeX tries to open a file, the following routine calls upon the user to supply another file name. Parameter s is used in the error message to identify the type of file; parameter e is the default extension if none is given. Upon exit from the routine, variables cur_name , cur_area , cur_ext , and $name_of_file$ are ready for another attempt at file opening.

```

procedure prompt_file_name( $s, e : str\_number$ );
  label done;
  var  $k : 0 .. buf\_size$ ; { index into buffer }
       $saved\_cur\_name : str\_number$ ; { to catch empty terminal input }
       $saved\_cur\_ext : str\_number$ ; { to catch empty terminal input }
       $saved\_cur\_area : str\_number$ ; { to catch empty terminal input }
  begin if  $interaction = scroll\_mode$  then wake\_up\_terminal;
  if  $s = "input\_file\_name"$  then print\_err("I can't find file `");
  else print\_err("I can't write on file `");
  print\_file\_name( $cur\_name, cur\_area, cur\_ext$ ); print(".");
  if ( $e = ".tex"$ )  $\vee$  ( $e = ""$ ) then show\_context;
  print\_ln; print\_c\_string(prompt\_file\_name\_help\_msg);
  if ( $e \neq ""$ ) then
    begin print("; default file extension is `"); print( $e$ ); print("`");
    end;
  print(""); print\_ln; print\_nl("Please type another"); print( $s$ );
  if  $interaction < scroll\_mode$  then fatal\_error("*** (job aborted, file error in nonstop mode)");
   $saved\_cur\_name \leftarrow cur\_name$ ;  $saved\_cur\_ext \leftarrow cur\_ext$ ;  $saved\_cur\_area \leftarrow cur\_area$ ; clear\_terminal;
  prompt\_input(":"); { Scan file name in the buffer 557 };
  if ( $length(cur\_name) = 0$ )  $\wedge$  ( $cur\_ext = ""$ )  $\wedge$  ( $cur\_area = ""$ ) then
    begin  $cur\_name \leftarrow saved\_cur\_name$ ;  $cur\_ext \leftarrow saved\_cur\_ext$ ;  $cur\_area \leftarrow saved\_cur\_area$ ;
    end
  else if  $cur\_ext = ""$  then  $cur\_ext \leftarrow e$ ;
  pack\_cur\_name;
  end;

```

558* Here's an example of how these conventions are used. Whenever it is time to ship out a box of stuff, we shall use the macro *ensure_dvi_open*.

```

define log_name  $\equiv texmf\_log\_name$ 
define ensure_dvi_open  $\equiv$ 
  if  $output\_file\_name = 0$  then
    begin if  $job\_name = 0$  then open\_log\_file;
    pack\_job\_name(".dvi");
    while  $\neg b\_open\_out(dvi\_file)$  do prompt\_file\_name("file\_name\_for\_output", ".dvi");
     $output\_file\_name \leftarrow b\_make\_name\_string(dvi\_file)$ ;
    end

```

{ Global variables 13 } \equiv

```

dvi\_file: byte\_file; { the device-independent output goes here }
output\_file\_name: str\_number; { full name of the output file }
log\_name: str\_number; { full name of the log file }

```

560* The *open_log_file* routine is used to open the transcript file and to help it catch up to what has previously been printed on the terminal.

procedure *open_log_file*;

```

var old_setting: 0 .. max_selector; { previous selector setting }
    k: 0 .. buf_size; { index into months and buffer }
    l: 0 .. buf_size; { end of first input line }
    months: const_cstring;
begin old_setting ← selector;
if job_name = 0 then job_name ← get_job_name("texput");
pack_job_name(".fls"); recorder_change_filename(stringcast(name_of_file + 1)); pack_job_name(".log");
while ¬a_open_out(log_file) do { Try to get a different log file name 561 };
log_name ← a_make_name_string(log_file); selector ← log_only; log_opened ← true;
{ Print the banner line, including the date and time 562* };
if mltx_enabled_p then
begin wlog_cr; wlog('MLTeX_v2.2_enabled');
end;
if enctex_enabled_p then
begin wlog_cr; wlog(encTeX_banner); wlog(',_reencoding_enabled');
if translate_filename then
begin wlog_cr; wlog('_(\xordcode,_\xchrcode,_\xprncode_ overridden_by_TCX)');
end;
end;
input_stack[input_ptr] ← cur_input; { make sure bottom level is in memory }
print_nl("**"); l ← input_stack[0].limit_field; { last position of first line }
if buffer[l] = end_line_char then decr(l);
for k ← 1 to l do print(buffer[k]);
print_ln; { now the transcript file contains the first line of input }
selector ← old_setting + 2; { log_only or term_and_log }
end;
```

```

562* ⟨Print the banner line, including the date and time 562*⟩ ≡
  begin if src_specials_p ∨ file_line_error_style_p ∨ parse_first_line_p then wlog(banner_k)
  else wlog(banner);
  wlog(version_string); slow_print(format_ident); print("□"); print_int(sys_day); print_char("□");
  months ← ˆ□JANFEBMARAPRMYJUNJULAUJGSEPOCTNOVDECˆ;
  for k ← 3 * sys_month - 2 to 3 * sys_month do wlog(months[k]);
  print_char("□"); print_int(sys_year); print_char("□"); print_two(sys_time div 60); print_char(":");
  print_two(sys_time mod 60);
  if eTeX_ex then
    begin ; wlog_cr; wlog(ˆentering□extended□modeˆ);
    end;
  if shellenabled_p then
    begin wlog_cr; wlog(ˆ□ˆ);
    if restrictedshell then
      begin wlog(ˆrestricted□ˆ);
      end;
    wlog(ˆ□write18□enabled.ˆ);
    end;
  if src_specials_p then
    begin wlog_cr; wlog(ˆ□Source□specials□enabled.ˆ);
    end;
  if file_line_error_style_p then
    begin wlog_cr; wlog(ˆ□file:line:error□style□messages□enabled.ˆ);
    end;
  if parse_first_line_p then
    begin wlog_cr; wlog(ˆ□%&-line□parsing□enabled.ˆ);
    end;
  if translate_filename then
    begin wlog_cr; wlog(ˆ□(ˆ); fputs(translate_filename, log_file); wlog(ˆ);
    end;
  end

```

This code is used in section 560*.

563* Let's turn now to the procedure that is used to initiate file reading when an '`\input`' command is being processed. Beware: For historic reasons, this code foolishly conserves a tiny bit of string pool space; but that can confuse the interactive '`E`' option.

```

procedure start_input; { TEX will \input something }
  label done;
  var temp_str: str_number; v: pointer;
  begin scan_file_name; { set cur_name to desired file name }
  pack_cur_name;
  loop begin begin_file_reading; { set up cur_file and new level of input }
    tex_input_type ← 1; { Tell open_input we are \input. }
    { Kpathsea tries all the various ways to get the file. }
    if kpse_in_name_ok(stringcast(name_of_file + 1) ∧ a_open_in(cur_file, kpse_tex_format) then
      goto done;
    end_file_reading; { remove the level that didn't work }
    prompt_file_name("input_□file_□name", "");
  end;
done: name ← a_make_name_string(cur_file); source_filename_stack[in_open] ← name;
  full_source_filename_stack[in_open] ← make_full_name_string;
  if name = str_ptr - 1 then { we can try to conserve string pool space now }
    begin temp_str ← search_string(name);
    if temp_str > 0 then
      begin name ← temp_str; flush_string;
      end;
    end;
  if job_name = 0 then
    begin job_name ← get_job_name(cur_name); open_log_file;
    end; { open_log_file doesn't show_context, so limit and loc needn't be set to meaningful values yet }
  if term_offset + length(full_source_filename_stack[in_open]) > max_print_line - 2 then print_ln
  else if (term_offset > 0) ∨ (file_offset > 0) then print_char("□");
  print_char("("); incr(open_parens); slow_print(full_source_filename_stack[in_open]); update_terminal;
  if tracing_stack_levels > 0 then
    begin begin_diagnostic; print_ln; print_char("~"); v ← input_ptr - 1;
    if v < tracing_stack_levels then
      while v > 0 do
        begin print_char("."); decr(v);
        end
      else print_char("~");
      slow_print("INPUT_□"); slow_print(cur_name); slow_print(cur_ext); print_ln; end_diagnostic(false);
    end;
  state ← new_line; ⟨ Prepare new file SyncTEX information 1919* ⟩;
  ⟨ Read the first line of the new file 564 ⟩;
end;

```

574* So that is what TFM files hold. Since TEX has to absorb such information about lots of fonts, it stores most of the data in a large array called *font_info*. Each item of *font_info* is a *memory_word*; the *fix_word* data gets converted into *scaled* entries, while everything else goes into words of type *four_quarters*.

When the user defines `\font\font`, say, TEX assigns an internal number to the user's font `\font`. Adding this number to *font.id.base* gives the *eqtb* location of a “frozen” control sequence that will always select the font.

```
<Types in the outer block 18> +=
  internal_font_number = integer; { font in a char_node }
  font_index = integer; { index into font_info }
  nine_bits = min_quarterword .. non_char;
```

575* Here now is the (rather formidable) array of font arrays.

```
define non_char ≡ qi(256) { a halfword code that can't match a real character }
define non_address = 0 { a spurious bchar_label }

<Global variables 13> +=
font_info: ↑fmemory_word; { the big collection of font data }
fmem_ptr: font_index; { first unused word of font_info }
font_ptr: internal_font_number; { largest internal font number in use }
font_check: ↑four_quarters; { check sum }
font_size: ↑scaled; { “at” size }
font_dsize: ↑scaled; { “design” size }
font_params: ↑font_index; { how many font parameters are present }
font_name: ↑str_number; { name of the font }
font_area: ↑str_number; { area of the font }
font_bc: ↑eight_bits; { beginning (smallest) character code }
font_ec: ↑eight_bits; { ending (largest) character code }
font_glue: ↑pointer; { glue specification for interword space, null if not allocated }
font_used: ↑boolean; { has a character from this font actually appeared in the output? }
hyphen_char: ↑integer; { current \hyphenchar values }
skew_char: ↑integer; { current \skewchar values }
bchar_label: ↑font_index;
  { start of lig_kern program for left boundary character, non_address if there is none }
font_bchar: ↑nine_bits; { boundary character, non_char if there is none }
font_false_bchar: ↑nine_bits; { font_bchar if it doesn't exist in the font, otherwise non_char }
```

576* Besides the arrays just enumerated, we have directory arrays that make it easy to get at the individual entries in *font_info*. For example, the *char_info* data for character *c* in font *f* will be in *font_info*[*char_base*[*f*] + *c*].*qqqq*; and if *w* is the *width_index* part of this word (the *b0* field), the width of the character is *font_info*[*width_base*[*f*] + *w*].*sc*. (These formulas assume that *min_quarterword* has already been added to *c* and to *w*, since TEX stores its quarterwords that way.)

```
<Global variables 13> +=
char_base: ↑integer; { base addresses for char_info }
width_base: ↑integer; { base addresses for widths }
height_base: ↑integer; { base addresses for heights }
depth_base: ↑integer; { base addresses for depths }
italic_base: ↑integer; { base addresses for italic corrections }
lig_kern_base: ↑integer; { base addresses for ligature/kerning programs }
kern_base: ↑integer; { base addresses for kerns }
exten_base: ↑integer; { base addresses for extensible recipes }
param_base: ↑integer; { base addresses for font parameters }
```

577* <Set initial values of key variables 21> +=

578* T_EX always knows at least one font, namely the null font. It has no characters, and its seven parameters are all equal to zero.

⟨ Initialize table entries (done by INITEX only) [182](#) ⟩ +≡

580* Of course we want to define macros that suppress the detail of how font information is actually packed, so that we don't have to write things like

$$font_info[width_base[f] + font_info[char_base[f] + c].qqqq.b0].sc$$

too often. The WEB definitions here make $char_info(f)(c)$ the *four-quarters* word of font information corresponding to character c of font f . If q is such a word, $char_width(f)(q)$ will be the character's width; hence the long formula above is at least abbreviated to

$$char_width(f)(char_info(f)(c)).$$

Usually, of course, we will fetch q first and look at several of its fields at the same time.

The italic correction of a character will be denoted by $char_italic(f)(q)$, so it is analogous to $char_width$. But we will get at the height and depth in a slightly different way, since we usually want to compute both height and depth if we want either one. The value of $height_depth(q)$ will be the 8-bit quantity

$$b = height_index \times 16 + depth_index,$$

and if b is such a byte we will write $char_height(f)(b)$ and $char_depth(f)(b)$ for the height and depth of the character c for which $q = char_info(f)(c)$. Got that?

The tag field will be called $char_tag(q)$; the remainder byte will be called $rem_byte(q)$, using a macro that we have already defined above.

Access to a character's *width*, *height*, *depth*, and *tag* fields is part of TEX's inner loop, so we want these macros to produce code that is as fast as possible under the circumstances.

MLTEX will assume that a character c exists iff either exists in the current font or a character substitution definition for this character was defined using `\charsubdef`. To avoid the distinction between these two cases, MLTEX introduces the notion "effective character" of an input character c . If c exists in the current font, the effective character of c is the character c itself. If it doesn't exist but a character substitution is defined, the effective character of c is the base character defined in the character substitution. If there is an effective character for a non-existing character c , the "virtual character" c will get appended to the horizontal lists.

The effective character is used within $char_info$ to access appropriate character descriptions in the font. For example, when calculating the width of a box, MLTEX will use the metrics of the effective characters. For the case of a substitution, MLTEX uses the metrics of the base character, ignoring the metrics of the accent character.

If character substitutions are changed, it will be possible that a character c neither exists in a font nor there is a valid character substitution for c . To handle these cases $effective_char$ should be called with its first argument set to *true* to ensure that it will still return an existing character in the font. If neither c nor the substituted base character in the current character substitution exists, $effective_char$ will output a warning and return the character $font_bc[f]$ (which is incorrect, but can not be changed within the current framework).

Sometimes character substitutions are unwanted, therefore the original definition of $char_info$ can be used using the macro $orig_char_info$. Operations in which character substitutions should be avoided are, for example, loading a new font and checking the font metric information in this font, and character accesses in math mode.

```

define char_list_exists(#) ≡ (char_sub_code(#) > hi(0))
define char_list_accent(#) ≡ (ho(char_sub_code(#)) div 256)
define char_list_char(#) ≡ (ho(char_sub_code(#)) mod 256)
define char_info_end(#) ≡ # ] .qqqq
define char_info(#) ≡ font_info [ char_base[#] + effective_char [ true, #, char_info_end
define orig_char_info_end(#) ≡ # ] .qqqq
define orig_char_info(#) ≡ font_info [ char_base[#] + orig_char_info_end

```

```

define char_width_end(#) ≡ #.b0 ] .sc
define char_width(#) ≡ font_info [ width_base[#] + char_width_end
define char_exists(#) ≡ (#.b0 > min_quarterword)
define char_italic_end(#) ≡ (qo(#.b2)) div 4 ] .sc
define char_italic(#) ≡ font_info [ italic_base[#] + char_italic_end
define height_depth(#) ≡ qo(#.b1)
define char_height_end(#) ≡ (#) div 16 ] .sc
define char_height(#) ≡ font_info [ height_base[#] + char_height_end
define char_depth_end(#) ≡ (#) mod 16 ] .sc
define char_depth(#) ≡ font_info [ depth_base[#] + char_depth_end
define char_tag(#) ≡ ((qo(#.b2)) mod 4)

```

586* TEX checks the information of a TFM file for validity as the file is being read in, so that no further checks will be needed when typesetting is going on. The somewhat tedious subroutine that does this is called *read_font_info*. It has four parameters: the user font identifier *u*, the file name and area strings *nom* and *aire*, and the “at” size *s*. If *s* is negative, it’s the negative of a scale factor to be applied to the design size; *s* = −1000 is the normal case. Otherwise *s* will be substituted for the design size; in this case, *s* must be positive and less than 2048 pt (i.e., it must be less than 2^{27} when considered as an integer).

The subroutine opens and closes a global file variable called *tfm_file*. It returns the value of the internal font number that was just loaded. If an error is detected, an error message is issued and no font information is stored; *null_font* is returned in this case.

```

define bad_tfm = 11 { label for read_font_info }
define abort ≡ goto bad_tfm { do this when the TFM data is wrong }
⟨ Declare additional functions for MLTEX 1886* ⟩
function read_font_info(u : pointer; nom, aire : str_number; s : scaled): internal_font_number;
    { input a TFM file }
label done, bad_tfm, not_found;
var k: font_index; { index into font_info }
    name_too_long: boolean; { nom or aire exceeds 255 bytes? }
    file_opened: boolean; { was tfm_file successfully opened? }
    lf, lh, bc, ec, nw, nh, nd, ni, nl, nk, ne, np: halfword; { sizes of subfiles }
    f: internal_font_number; { the new font’s number }
    g: internal_font_number; { the number to return }
    a, b, c, d: eight_bits; { byte variables }
    qw: four_quarters; sw: scaled; { accumulators }
    bch_label: integer; { left boundary start location, or infinity }
    bchar: 0 .. 256; { boundary character, or 256 }
    z: scaled; { the design size or the “at” size }
    alpha: integer; beta: 1 .. 16; { auxiliary quantities used in fixed-point multiplication }
begin g ← null_font;
    ⟨ Read and check the font data; abort if the TFM file is malformed; if there’s no room for this font, say so
      and goto done; otherwise incr(font_ptr) and goto done 588 ⟩;
bad_tfm: ⟨ Report that the font won’t be loaded 587* ⟩;
done: if file_opened then b_close(tfm_file);
    read_font_info ← g;
end;

```

587* There are programs called TFtoPL and PLtoTF that convert between the TFM format and a symbolic property-list format that can be easily edited. These programs contain extensive diagnostic information, so TEX does not have to bother giving precise details about why it rejects a particular TFM file.

```

define start_font_error_message  $\equiv$  print_err("Font"); sprint_cs(u); print_char("=");
  print_file_name(nom, aire, "");
if s  $\geq$  0 then
  begin print("_at_"); print_scaled(s); print("pt");
  end
else if s  $\neq$  -1000 then
  begin print("_scaled_"); print_int(-s);
  end

```

\langle Report that the font won't be loaded 587* $\rangle \equiv$

```

start_font_error_message;
if file_opened then print("_not_loadable:_Bad_metric_(TFM)_file")
else if name_too_long then print("_not_loadable:_Metric_(TFM)_file_name_too_long")
  else print("_not_loadable:_Metric_(TFM)_file_not_found");
help5("I_wasn't_able_to_read_the_size_data_for_this_font,")
("so_I_will_ignore_the_font_specification.")
(" [Wizards_can_fix_TFM_files_using_TFtoPL/PLtoTF.]")
("You_might_try_inserting_a_different_font_spec;")
("e.g.,_type_\font<same_font_id>=<substitute_font_name>`."); error

```

This code is used in section 586*.

589* \langle Open *tfm_file* for input 589* $\rangle \equiv$

```

file_opened  $\leftarrow$  false; name_too_long  $\leftarrow$  (length(nom) > 255)  $\vee$  (length(aire) > 255);
if name_too_long then abort; {kpse_find_file will append the ".tfm", and avoid searching the disk
  before the font alias files as well.}
pack_file_name(nom, aire, "");
if  $\neg$ b_open_in(tfm_file) then abort;
file_opened  $\leftarrow$  true

```

This code is used in section 588.

590* Note: A malformed TFM file might be shorter than it claims to be; thus *eof*(*tfm_file*) might be true when *read_font_info* refers to *tfm_file* \uparrow or when it says *get*(*tfm_file*). If such circumstances cause system error messages, you will have to defeat them somehow, for example by defining *fget* to be '**begin** *get*(*tfm_file*); **if** *eof*(*tfm_file*) **then** abort; **end**'.

```

define fget  $\equiv$  tfm_temp  $\leftarrow$  getc(tfm_file)
define fbyte  $\equiv$  tfm_temp
define read_sixteen(#)  $\equiv$ 
  begin #  $\leftarrow$  fbyte;
  if # > 127 then abort;
  fget; #  $\leftarrow$  # * '400 + fbyte;
  end
define store_four_quarters(#)  $\equiv$ 
  begin fget; a  $\leftarrow$  fbyte; qw.b0  $\leftarrow$  qi(a); fget; b  $\leftarrow$  fbyte; qw.b1  $\leftarrow$  qi(b); fget; c  $\leftarrow$  fbyte;
  qw.b2  $\leftarrow$  qi(c); fget; d  $\leftarrow$  fbyte; qw.b3  $\leftarrow$  qi(d); #  $\leftarrow$  qw;
  end

```

596* We want to make sure that there is no cycle of characters linked together by *list_tag* entries, since such a cycle would get TEX into an endless loop. If such a cycle exists, the routine here detects it when processing the largest character code in the cycle.

```

define check_byte_range(#) ≡
    begin if (# < bc) ∨ (# > ec) then abort
    end
define current_character_being_worked_on ≡ k + bc - fmem_ptr
⟨ Check for charlist cycle 596* ⟩ ≡
begin check_byte_range(d);
while d < current_character_being_worked_on do
    begin qw ← orig_char_info(f)(d); { N.B.: not qi(d), since char_base[f] hasn't been adjusted yet }
    if char_tag(qw) ≠ list_tag then goto not_found;
    d ← qo(rem_byte(qw)); { next character on the list }
    end;
if d = current_character_being_worked_on then abort; { yes, there's a cycle }
not_found: end

```

This code is used in section 595.

```

600* define check_existence(#) ≡
    begin check_byte_range(#); qw ← orig_char_info(f)(#); { N.B.: not qi(#) }
    if ¬char_exists(qw) then abort;
    end
⟨ Read ligature/kern program 600* ⟩ ≡
bch_label ← '777777'; bchar ← 256;
if nl > 0 then
    begin for k ← lig_kern_base[f] to kern_base[f] + kern_base_offset - 1 do
        begin store_four_quarters(font_info[k].qqqq);
        if a > 128 then
            begin if 256 * c + d ≥ nl then abort;
            if a = 255 then
                if k = lig_kern_base[f] then bchar ← b;
            end
        else begin if b ≠ bchar then check_existence(b);
            if c < 128 then check_existence(d) { check ligature }
            else if 256 * (c - 128) + d ≥ nk then abort; { check kern }
            if a < 128 then
                if k - lig_kern_base[f] + a + 1 ≥ nl then abort;
            end;
        end;
        if a = 255 then bch_label ← 256 * c + d;
        end;
    for k ← kern_base[f] + kern_base_offset to exten_base[f] - 1 do store_scaled(font_info[k].sc);

```

This code is used in section 588.

602* We check to see that the TFM file doesn't end prematurely; but no error message is given for files having more than *lf* words.

```

⟨Read font parameters 602*⟩ ≡
  begin for k ← 1 to np do
    if k = 1 then { the slant parameter is a pure number }
      begin fget; sw ← fbyte;
      if sw > 127 then sw ← sw - 256;
      fget; sw ← sw * '400 + fbyte; fget; sw ← sw * '400 + fbyte; fget;
      font_info[param_base[f]].sc ← (sw * '20) + (fbyte div '20);
      end
    else store_scaled(font_info[param_base[f] + k - 1].sc);
  if feof(tfm_file) then abort;
  for k ← np + 1 to 7 do font_info[param_base[f] + k - 1].sc ← 0;
  end

```

This code is used in section 588.

603* Now to wrap it up, we have checked all the necessary things about the TFM file, and all we need to do is put the finishing touches on the data for the new font.

```

  define adjust(#) ≡ #[f] ← qo(#[f]) { correct for the excess min_quarterword that was added }
⟨Make final adjustments and goto done 603*⟩ ≡
  if np ≥ 7 then font_params[f] ← np else font_params[f] ← 7;
  hyphen_char[f] ← default_hyphen_char; skew_char[f] ← default_skew_char;
  if bch_label < nl then bchar_label[f] ← bch_label + lig_kern_base[f]
  else bchar_label[f] ← non_address;
  font_bchar[f] ← qi(bchar); font_false_bchar[f] ← qi(bchar);
  if bchar ≤ ec then
    if bchar ≥ bc then
      begin qw ← orig_char_info(f)(bchar); { N.B.: not qi(bchar) }
      if char_exists(qw) then font_false_bchar[f] ← non_char;
      end;
  font_name[f] ← nom; font_area[f] ← aire; font_bc[f] ← bc; font_ec[f] ← ec; font_glue[f] ← null;
  adjust(char_base); adjust(width_base); adjust(lig_kern_base); adjust(kern_base); adjust(exten_base);
  decr(param_base[f]); fmem_ptr ← fmem_ptr + lf; font_ptr ← f; g ← f; goto done

```

This code is used in section 588.

604* Before we forget about the format of these tables, let's deal with two of TEX's basic scanning routines related to font information.

⟨Declare procedures that scan font-related stuff 604*⟩ ≡

```

function test_no_ligatures(f : internal_font_number): integer;
  label exit;
  var c: integer;
  begin test_no_ligatures ← 1;
  for c ← font_bc[f] to font_ec[f] do
    if char_exists(orig_char_info(f)(c)) then
      if odd(char_tag(orig_char_info(f)(c))) then
        begin test_no_ligatures ← 0; return;
        end;
  exit: end;

function get_tag_code(f : internal_font_number; c : eight_bits): integer;
  var i: small_number;
  begin if is_valid_char(c) then
    begin i ← char_tag(orig_char_info(f)(c));
    if i = lig_tag then get_tag_code ← 1
    else if i = list_tag then get_tag_code ← 2
    else if i = ext_tag then get_tag_code ← 4
    else get_tag_code ← 0;
    end
  else get_tag_code ← -1;
  end;

procedure scan_font_ident;
  var f: internal_font_number; m: halfword;
  begin ⟨Get the next non-blank non-call token 432⟩;
  if (cur_cmd = def_font) ∨ (cur_cmd = letterspace_font) ∨ (cur_cmd = pdf_copy_font) then f ← cur_font
  else if cur_cmd = set_font then f ← cur_chr
    else if cur_cmd = def_family then
      begin m ← cur_chr; scan_four_bit_int; f ← equiv(m + cur_val);
      end
    else begin print_err("Missing_font_identifier");
      help2("I_was_looking_for_a_control_sequence_whose")
      ("current_meaning_has_been_defined_by_\font."); back_error; f ← null_font;
      end;
  cur_val ← f;
  end;

```

See also section 605.

This code is used in section 435.

608* When TeX wants to typeset a character that doesn't exist, the character node is not created; thus the output routine can assume that characters exist when it sees them. The following procedure prints a warning message unless the user has suppressed it.

```

procedure char_warning(f : internal_font_number; c : eight_bits);
  var old_setting: integer; { saved value of tracing_online }
  begin if tracing_lost_chars > 0 then
    begin old_setting ← tracing_online;
    if eTeX_ex ∧ (tracing_lost_chars > 1) then tracing_online ← 1;
    if tracing_lost_chars > 2 then print_err("Missing_character: There is no ")
    else begin begin_diagnostic; print_nl("Missing_character: There is no ")
      end;
    print_ASCII(c);
    if tracing_lost_chars > 2 then
      begin print(" "); print_hex(c); print(" ");
      end;
    print(" in font "); slow_print(font_name[f]);
    if tracing_lost_chars < 3 then print_char("!");
    tracing_online ← old_setting;
    if tracing_lost_chars > 2 then
      begin help0; error;
      end
    else end_diagnostic(false);
    end; { of tracing_lost_chars > 0 }
  end; { of procedure }

```

609* Here is a function that returns a pointer to a character node for a given character in a given font. If that character doesn't exist, *null* is returned instead.

This allows a character node to be used if there is an equivalent in the *char_sub_code* list.

```

function new_character(f : internal_font_number; c : eight_bits): pointer;
  label exit;
  var p: pointer; { newly allocated node }
      ec: quarterword; { effective character of c }
  begin ec ← effective_char(false, f, qi(c));
  if font_bc[f] ≤ qo(ec) then
    if font_ec[f] ≥ qo(ec) then
      if char_exists(orig_char_info(f)(ec)) then { N.B.: not char_info }
        begin p ← get_avail; font(p) ← f; character(p) ← qi(c); new_character ← p; return;
        end;
    char_warning(f, c); new_character ← null;
  exit: end;

```


619* **Shipping pages out.** After considering TEX’s eyes and stomach, we come now to the bowels.

The *ship_out* procedure is given a pointer to a box; its mission is to describe that box in DVI form, outputting a “page” to *dvi_file*. The DVI coordinates $(h, v) = (0, 0)$ should correspond to the upper left corner of the box being shipped.

Since boxes can be inside of boxes inside of boxes, the main work of *ship_out* is done by two mutually recursive routines, *hlist_out* and *vlist_out*, which traverse the hlists and vlists inside of horizontal and vertical boxes.

As individual pages are being processed, we need to accumulate information about the entire set of pages, since such statistics must be reported in the postamble. The global variables *total_pages*, *max_v*, *max_h*, *max_push*, and *last_bop* are used to record this information.

The variable *doing_leaders* is *true* while leaders are being output. The variable *dead_cycles* contains the number of times an output routine has been initiated since the last *ship_out*.

A few additional global variables are also defined here for use in *vlist_out* and *hlist_out*. They could have been local variables, but that would waste stack space when boxes are deeply nested, since the values of these variables are not needed during recursive calls.

```

⟨ Global variables 13 ⟩ +≡
total_pages: integer; { the number of pages that have been shipped out }
max_v: scaled; { maximum height-plus-depth of pages shipped so far }
max_h: scaled; { maximum width of pages shipped so far }
max_push: integer; { deepest nesting of push commands encountered so far }
last_bop: integer; { location of previous bop in the DVI output }
dead_cycles: integer; { recent outputs that didn't ship anything out }
doing_leaders: boolean; { are we inside a leader box? }

{ character and font in current char_node }
c: quarterword;
f: internal_font_number;
rule_ht, rule_dp, rule_wd: scaled; { size of current rule being output }
g: pointer; { current glue specification }
lq, lr: integer; { quantities used in calculations for leaders }

```

622* Some systems may find it more efficient to make *dvi_buf* a **packed** array, since output of four bytes at once may be facilitated.

```

⟨ Global variables 13 ⟩ +≡
dvi_buf: ↑eight_bits; { buffer for DVI output }
half_buf: integer; { half of dvi_buf_size }
dvi_limit: integer; { end of the current half buffer }
dvi_ptr: integer; { the next available buffer address }
dvi_offset: integer; { dvi_buf_size times the number of times the output buffer has been fully emptied }
dvi_gone: integer; { the number of bytes already output to dvi_file }

```

624* The actual output of *dvi_buf*[*a* .. *b*] to *dvi_file* is performed by calling *write_dvi*(*a*, *b*). For best results, this procedure should be optimized to run as fast as possible on each particular system, since it is part of TEX’s inner loop. It is safe to assume that *a* and *b* + 1 will both be multiples of 4 when *write_dvi*(*a*, *b*) is called; therefore it is possible on many machines to use efficient methods to pack four bytes per word and to output an array of words with one system call.

In C, we use a macro to call *fwrite* or *write* directly, writing all the bytes in one shot. Much better even than writing four bytes at a time.

625* To put a byte in the buffer without paying the cost of invoking a procedure each time, we use the macro *dvi_out*.

The length of *dvi_file* should not exceed "7FFFFFFF"; we set *cur_s* \leftarrow -2 to prevent further DVI output causing infinite recursion.

```

define dvi_out(#)  $\equiv$  begin dvi_buf[dvi_ptr]  $\leftarrow$  #; incr(dvi_ptr);
    if dvi_ptr = dvi_limit then dvi_swap;
    end
procedure dvi_swap; { outputs half of the buffer }
begin if dvi_ptr > ("7FFFFFFF - dvi_offset) then
    begin cur_s  $\leftarrow$   $-2$ ; fatal_error("dvi_length_exceeds_" "7FFFFFFF");
    end;
    if dvi_limit = dvi_buf_size then
    begin write_dvi(0, half_buf - 1); dvi_limit  $\leftarrow$  half_buf; dvi_offset  $\leftarrow$  dvi_offset + dvi_buf_size;
    dvi_ptr  $\leftarrow$  0;
    end
    else begin write_dvi(half_buf, dvi_buf_size - 1); dvi_limit  $\leftarrow$  dvi_buf_size;
    end;
    dvi_gone  $\leftarrow$  dvi_gone + half_buf;
end;

```

626* Here is how we clean out the buffer when TEX is all through; *dvi_ptr* will be a multiple of 4.

```

< Empty the last bytes out of dvi_buf 626*  $\equiv$ 
if dvi_limit = half_buf then write_dvi(half_buf, dvi_buf_size - 1);
if dvi_ptr > ("7FFFFFFF - dvi_offset) then
    begin cur_s  $\leftarrow$   $-2$ ; fatal_error("dvi_length_exceeds_" "7FFFFFFF");
    end;
if dvi_ptr > 0 then write_dvi(0, dvi_ptr - 1)

```

This code is used in section 670*.

629* Here's a procedure that outputs a font definition. Since TEX82 uses at most 256 different fonts per job, *font_def1* is always used as the command code.

```

procedure dvi_font_def(f : internal_font_number);
    var k: pool_pointer; { index into str_pool }
    begin if f  $\leq$  256 + font_base then
        begin dvi_out(font_def1); dvi_out(f - font_base - 1);
        end
    else begin dvi_out(font_def1 + 1); dvi_out((f - font_base - 1) div '400);
        dvi_out((f - font_base - 1) mod '400);
        end;
    dvi_out(qo(font_check[f].b0)); dvi_out(qo(font_check[f].b1)); dvi_out(qo(font_check[f].b2));
    dvi_out(qo(font_check[f].b3));
    dvi_four(font_size[f]); dvi_four(font_dsize[f]);
    dvi_out(length(font_area[f])); dvi_out(length(font_name[f]));
    < Output the font name whose internal number is f 630 >;
end;

```

```

645* ⟨ Initialize variables as ship_out begins 645* ⟩ ≡
  dvi_h ← 0; dvi_v ← 0; cur_h ← h_offset; dvi_f ← null_font;
  ⟨ Calculate DVI page dimensions and margins 644 ⟩;
  ensure_dvi_open;
  if total_pages = 0 then
    begin dvi_out(pre); dvi_out(id_byte); { output the preamble }
    dvi_four(25400000); dvi_four(473628672); { conversion ratio for sp }
    prepare_mag; dvi_four(mag); { magnification factor is frozen }
    if output_comment then
      begin l ← strlen(output_comment); dvi_out(l);
      for s ← 0 to l - 1 do dvi_out(output_comment[s]);
      end
    else begin { the default code is unchanged }
      old_setting ← selector; selector ← new_string; print("□TeX□output□"); print_int(year);
      print_char("."); print_two(month); print_char("."); print_two(day); print_char(":");
      print_two(time div 60); print_two(time mod 60); selector ← old_setting; dvi_out(cur_length);
      for s ← str_start[str_ptr] to pool_ptr - 1 do dvi_out(so(str_pool[s]));
      pool_ptr ← str_start[str_ptr]; { flush the current string }
      end;
    end
  end

```

This code is used in section 668*.

647* The recursive procedures *hlist_out* and *vlist_out* each have local variables *save_h* and *save_v* to hold the values of *dvi_h* and *dvi_v* just before entering a new level of recursion. In effect, the values of *save_h* and *save_v* on T_EX's run-time stack correspond to the values of *h* and *v* that a DVI-reading program will push onto its coordinate stack.

```

define move_past = 13 { go to this label when advancing past glue or a rule }
define fin_rule = 14 { go to this label to finish processing a rule }
define next_p = 15 { go to this label when finished with node p }

⟨Declare procedures needed in hlist_out, vlist_out 1616*⟩
procedure hlist_out; { output an hlist_node box }
label reswitch, move_past, fin_rule, next_p, continue, found;
var base_line: scaled; { the baseline coordinate for this box }
    left_edge: scaled; { the left coordinate for this box }
    save_h, save_v: scaled; { what dvi_h and dvi_v should pop to }
    this_box: pointer; { pointer to containing box }
    g_order: glue_ord; { applicable order of infinity for glue }
    g_sign: normal .. shrinking; { selects type of glue }
    p: pointer; { current position in the hlist }
    save_loc: integer; { DVI byte location upon entry }
    leader_box: pointer; { the leader box being replicated }
    leader_wd: scaled; { width of leader box being replicated }
    lx: scaled; { extra space between leader boxes }
    outer_doing_leaders: boolean; { were we doing leaders? }
    edge: scaled; { right edge of sub-box or leader space }
    prev_p: pointer; { one step behind p }
    glue_temp: real; { glue value before rounding }
    cur_glue: real; { glue seen so far }
    cur_g: scaled; { rounded equivalent of cur_glue times the glue ratio }
begin cur_g ← 0; cur_glue ← float_constant(0); this_box ← temp_ptr; g_order ← glue_order(this_box);
g_sign ← glue_sign(this_box); p ← list_ptr(this_box); incr(cur_s);
if cur_s > 0 then dvi_out(push);
if cur_s > max_push then max_push ← cur_s;
save_loc ← dvi_offset + dvi_ptr; base_line ← cur_v; prev_p ← this_box + list_offset;
⟨Initialize hlist_out for mixed direction typesetting 1715⟩;
left_edge ← cur_h; ⟨Start hlist SyncTEX information record 1928*⟩;
while p ≠ null do ⟨Output node p for hlist_out and move to the next node, maintaining the condition
    cur_v = base_line 648*⟩;
⟨Finish hlist SyncTEX information record 1929*⟩;
⟨Finish hlist_out for mixed direction typesetting 1716⟩;
prune_movements(save_loc);
if cur_s > 0 then dvi_pop(save_loc);
decr(cur_s);
end;

```

648* We ought to give special care to the efficiency of one part of *hlist_out*, since it belongs to $\text{T}_{\text{E}}\text{X}$'s inner loop. When a *char_node* is encountered, we save a little time by processing several nodes in succession until reaching a non-*char_node*. The program uses the fact that $\text{set_char_0} = 0$.

In $\text{M}_{\text{L}}\text{T}_{\text{E}}\text{X}$ this part looks for the existence of a substitution definition for a character *c*, if *c* does not exist in the font, and create appropriate DVI commands. Former versions of $\text{M}_{\text{L}}\text{T}_{\text{E}}\text{X}$ have spliced appropriate character, kern, and box nodes into the horizontal list. Because the user can change character substitutions or $\backslash\text{charsubdefmax}$ on the fly, we have to test a again for valid substitutions. (Additional it is necessary to be careful—if leaders are used the current hlist is normally traversed more than once!)

⟨Output node *p* for *hlist_out* and move to the next node, maintaining the condition $\text{cur_v} = \text{base_line}$ 648*⟩ ≡

```
reswitch: if is_char_node(p) then
  begin synch_h; synch_v;
  repeat f ← font(p); c ← character(p);
    if f ≠ dvi_f then ⟨Change font dvi_f to f 649*⟩;
    if font_ec[f] ≥ qo(c) then
      if font_bc[f] ≤ qo(c) then
        if char_exists(orig_char_info(f)(c)) then {N.B.: not char_info }
          begin if c ≥ qi(128) then dvi_out(set1);
            dvi_out(qo(c));
            cur_h ← cur_h + char_width(f)(orig_char_info(f)(c)); goto continue;
          end;
        if mltex_enabled_p then ⟨Output a substitution, goto continue if not possible 1887*⟩;
      continue: prev_p ← link(prev_p); {N.B.: not prev_p ← p, p might be lig_trick }
      p ← link(p);
    until ¬is_char_node(p);
    ⟨Record current point SyncTEX information 1931*⟩;
    dvi_h ← cur_h;
  end
else ⟨Output the non-char_node p for hlist_out and move to the next node 650*⟩
```

This code is used in section 647*.

```
649* ⟨Change font dvi_f to f 649*⟩ ≡
  begin if ¬font_used[f] then
    begin dvi_font_def(f); font_used[f] ← true;
    end;
  if f ≤ 64 + font_base then dvi_out(f − font_base − 1 + fnt_num_0)
  else if f ≤ 256 + font_base then
    begin dvi_out(fnt1); dvi_out(f − font_base − 1);
    end
  else begin dvi_out(fnt1 + 1); dvi_out((f − font_base − 1) div '400);
    dvi_out((f − font_base − 1) mod '400);
  end;
  dvi_f ← f;
end
```

This code is used in section 648*.

```

650* ⟨Output the non-char_node p for hlist_out and move to the next node 650*⟩ ≡
begin case type(p) of
  hlist_node, vlist_node: ⟨Output a box in an hlist 651*⟩;
  rule_node: begin rule_ht ← height(p); rule_dp ← depth(p); rule_wd ← width(p); goto fin_rule;
  end;
  whatsit_node: ⟨Output the whatsit node p in an hlist 1615⟩;
  glue_node: ⟨Move right or output leaders 653⟩;
  margin_kern_node: cur_h ← cur_h + width(p); { separate the margin_kern_node case in hlist_out }
  kern_node: begin ⟨Record kern_node SyncTeX information 1933*⟩;
    cur_h ← cur_h + width(p);
  end;
  math_node: begin ⟨Record math_node SyncTeX information 1934*⟩;
    ⟨Handle a math node in hlist_out 1717⟩;
  end;
  ligature_node: ⟨Make node p look like a char_node and goto reswitch 826⟩;
    ⟨Cases of hlist_out that arise in mixed direction text only 1721⟩
othercases do_nothing
endcases;
goto next_p;
fin_rule: ⟨Output a rule in an hlist 652⟩;
move_past: begin cur_h ← cur_h + rule_wd;
  ⟨Record horizontal rule_node or glue_node SyncTeX information 1932*⟩;
end;
next_p: prev_p ← p; p ← link(p);
end

```

This code is used in section **648***.

```

651* ⟨Output a box in an hlist 651*⟩ ≡
if list_ptr(p) = null then
  begin ⟨Record void list SyncTeX information 1930*⟩;
  cur_h ← cur_h + width(p);
  end
else begin save_h ← dvi_h; save_v ← dvi_v; cur_v ← base_line + shift_amount(p);
  { shift the box down }
  temp_ptr ← p; edge ← cur_h + width(p);
  if cur_dir = right_to_left then cur_h ← edge;
  if type(p) = vlist_node then vlist_out else hlist_out;
  dvi_h ← save_h; dvi_v ← save_v; cur_h ← edge; cur_v ← base_line;
end

```

This code is used in section **650***.

657* The *vlist_out* routine is similar to *hlist_out*, but a bit simpler.

```

procedure vlist_out; { output a vlist_node box }
  label move_past, fin_rule, next_p;
  var left_edge: scaled; { the left coordinate for this box }
      top_edge: scaled; { the top coordinate for this box }
      save_h, save_v: scaled; { what dvi_h and dvi_v should pop to }
      this_box: pointer; { pointer to containing box }
      g_order: glue_ord; { applicable order of infinity for glue }
      g_sign: normal .. shrinking; { selects type of glue }
      p: pointer; { current position in the vlist }
      save_loc: integer; { DVI byte location upon entry }
      leader_box: pointer; { the leader box being replicated }
      leader_ht: scaled; { height of leader box being replicated }
      lx: scaled; { extra space between leader boxes }
      outer_doing_leaders: boolean; { were we doing leaders? }
      edge: scaled; { bottom boundary of leader space }
      glue_temp: real; { glue value before rounding }
      cur_glue: real; { glue seen so far }
      cur_g: scaled; { rounded equivalent of cur_glue times the glue ratio }
  begin cur_g  $\leftarrow$  0; cur_glue  $\leftarrow$  float_constant(0); this_box  $\leftarrow$  temp_ptr; g_order  $\leftarrow$  glue_order(this_box);
  g_sign  $\leftarrow$  glue_sign(this_box); p  $\leftarrow$  list_ptr(this_box); incr(cur_s);
  if cur_s > 0 then dvi_out(push);
  if cur_s > max_push then max_push  $\leftarrow$  cur_s;
  save_loc  $\leftarrow$  dvi_offset + dvi_ptr; left_edge  $\leftarrow$  cur_h; { Start vlist SyncTEX information record 1926* };
  cur_v  $\leftarrow$  cur_v - height(this_box); top_edge  $\leftarrow$  cur_v;
  while p  $\neq$  null do { Output node p for vlist_out and move to the next node, maintaining the condition
      cur_h = left_edge 658 };
  { Finish vlist SyncTEX information record 1927* };
  prune_movements(save_loc);
  if cur_s > 0 then dvi_pop(save_loc);
  decr(cur_s);
  end;

```

660* The *synch_v* here allows the DVI output to use one-byte commands for adjusting *v* in most cases, since the baselineskip distance will usually be constant.

```

{ Output a box in a vlist 660* }  $\equiv$ 
  if list_ptr(p) = null then
    begin cur_v  $\leftarrow$  cur_v + height(p); { Record void list SyncTEX information 1930* };
    cur_v  $\leftarrow$  cur_v + depth(p);
    end
  else begin cur_v  $\leftarrow$  cur_v + height(p); synch_v; save_h  $\leftarrow$  dvi_h; save_v  $\leftarrow$  dvi_v;
  if cur_dir = right_to_left then cur_h  $\leftarrow$  left_edge - shift_amount(p)
  else cur_h  $\leftarrow$  left_edge + shift_amount(p); { shift the box right }
  temp_ptr  $\leftarrow$  p;
  if type(p) = vlist_node then vlist_out else hlist_out;
  dvi_h  $\leftarrow$  save_h; dvi_v  $\leftarrow$  save_v; cur_v  $\leftarrow$  save_v + depth(p); cur_h  $\leftarrow$  left_edge;
  end

```

This code is used in section 659.

666* The *hlist_out* and *vlist_out* procedures are now complete, so we are ready for the *dvi_ship_out* routine that gets them started in the first place.

```

procedure dvi_ship_out(p: pointer); { output the box p }
  label done;
  var page_loc: integer; { location of the current bop }
      j, k: 0 .. 9; { indices to first ten count registers }
      s: pool_pointer; { index into str_pool }
      old_setting: 0 .. max_selector; { saved selector setting }
  begin ⟨Start sheet SyncTeX information record 1924*⟩;
  begin if tracing_output > 0 then
    begin print_nl(""); print_ln; print("Completed□box□being□shipped□out");
    end;
  if term_offset > max_print_line - 9 then print_ln
  else if (term_offset > 0) ∨ (file_offset > 0) then print_char("□");
  print_char("["); j ← 9;
  while (count(j) = 0) ∧ (j > 0) do decr(j);
  for k ← 0 to j do
    begin print_int(count(k));
    if k < j then print_char(".");
    end;
  update_terminal;
  if tracing_output > 0 then
    begin print_char("]"); begin_diagnostic; show_box(p); end_diagnostic(true);
    end;
  ⟨Ship box p out 668*⟩;
  if eTeX_ex then ⟨Check for LR anomalies at the end of ship_out 1731⟩;
  if tracing_output ≤ 0 then print_char("]");
  dead_cycles ← 0; update_terminal; { progress report }
  ⟨Flush the box from memory, showing statistics if requested 667⟩;
  end; ⟨Finish sheet SyncTeX information record 1925*⟩;
  end;

```



```

668* ⟨Ship box p out 668*⟩ ≡
  ⟨Update the values of max_h and max_v; but if the page is too large, goto done 669⟩;
  ⟨Initialize variables as ship_out begins 645*⟩;
  page_loc ← dvi_offset + dvi_ptr; dvi_out(bop);
  for k ← 0 to 9 do dvi_four(count(k));
  dvi_four(last_bop); last_bop ← page_loc; cur_v ← height(p) + v_offset; temp_ptr ← p;
  if type(p) = vlist_node then vlist_out else hlist_out;
  dvi_out(eop); incr(total_pages); cur_s ← -1; ifdef(`IPC`)
  if ipc_on > 0 then
    begin if dvi_limit = half_buf then
      begin write_dvi(half_buf, dvi_buf_size - 1); flush_dvi; dvi_gone ← dvi_gone + half_buf;
      end;
    if dvi_ptr > ("7FFFFFFF" - dvi_offset) then
      begin cur_s ← -2; fatal_error("dvi_□length_□exceeds_□" "7FFFFFFF");
      end;
    if dvi_ptr > 0 then
      begin write_dvi(0, dvi_ptr - 1); flush_dvi; dvi_offset ← dvi_offset + dvi_ptr;
      dvi_gone ← dvi_gone + dvi_ptr;
      end;
      dvi_ptr ← 0; dvi_limit ← dvi_buf_size; ipc_page(dvi_gone);
    end;
  endif(`IPC`);
done:

```

This code is used in section 666*.

670* At the end of the program, we must finish things off by writing the postamble. If $total_pages = 0$, the DVI file was never opened. If $total_pages \geq 65536$, the DVI file will lie. And if $max_push \geq 65536$, the user deserves whatever chaos might ensue.

An integer variable k will be declared for use by this routine.

```

⟨ Finish the DVI file 670* ⟩ ≡
  while cur_s > -1 do
    begin if cur_s > 0 then dvi_out(pop)
    else begin dvi_out(eop); incr(total_pages);
    end;
    decr(cur_s);
  end;
  if total_pages = 0 then print_nl("No_pages_of_output.")
  else if cur_s ≠ -2 then
    begin dvi_out(post); { beginning of the postamble }
    dvi_four(last_bop); last_bop ← dvi_offset + dvi_ptr - 5; { post location }
    dvi_four(25400000); dvi_four(473628672); { conversion ratio for sp }
    prepare_mag; dvi_four(mag); { magnification factor }
    dvi_four(max.v); dvi_four(max.h);
    dvi_out(max_push div 256); dvi_out(max_push mod 256);
    dvi_out((total_pages div 256) mod 256); dvi_out(total_pages mod 256);
    ⟨ Output the font definitions for all fonts that were used 671 ⟩;
    dvi_out(post_post); dvi_four(last_bop); dvi_out(id_byte);
    ifdef(`IPC`)k ← 7 - ((3 + dvi_offset + dvi_ptr) mod 4); { the number of 223's }
    endif(`IPC`)ifndef(`IPC`)k ← 4 + ((dvi_buf_size - dvi_ptr) mod 4); { the number of 223's }
    endifn(`IPC`)
    while k > 0 do
      begin dvi_out(223); decr(k);
      end;
    ⟨ Empty the last bytes out of dvi_buf 626* ⟩;
    print_nl("Output_written_on"); print_file_name(0, output_file_name, 0); print(",");
    print_int(total_pages);
    if total_pages ≠ 1 then print(",pages")
    else print(",page");
    print(","); print_int(dvi_offset + dvi_ptr); print(",bytes)."); b_close(dvi_file);
  end

```

This code is used in section 1514*.

673* The subroutines define the corresponding macros so we can use them in C.

```

define flushable(#)  $\equiv$  (# = str_ptr - 1)
define is_valid_char(#)  $\equiv$  ((font_bc[f]  $\leq$  #)  $\wedge$  (#  $\leq$  font_ec[f])  $\wedge$  char_exists(orig_char_info(f)(#)))

function get_pdf_compress_level: integer;
  begin get_pdf_compress_level  $\leftarrow$  pdf_compress_level;
  end;

function get_pdf_suppress_warning_dup_map: integer;
  begin get_pdf_suppress_warning_dup_map  $\leftarrow$  pdf_suppress_warning_dup_map;
  end;

function get_pdf_suppress_warning_page_group: integer;
  begin get_pdf_suppress_warning_page_group  $\leftarrow$  pdf_suppress_warning_page_group;
  end;

function get_pdf_suppress_ptex_info: integer;
  begin get_pdf_suppress_ptex_info  $\leftarrow$  pdf_suppress_ptex_info;
  end;

function get_pdf_omit_charset: integer;
  begin get_pdf_omit_charset  $\leftarrow$  pdf_omit_charset;
  end;

function get_nullfont: internal_font_number;
  begin get_nullfont  $\leftarrow$  null_font;
  end;

function get_fontbase: internal_font_number;
  begin get_fontbase  $\leftarrow$  font_base;
  end;

function get_nullcs: pointer;
  begin get_nullcs  $\leftarrow$  null_cs;
  end;

function get_nullptr: pointer;
  begin get_nullptr  $\leftarrow$  null;
  end;

function get_tex_int(code : integer): integer;
  begin get_tex_int  $\leftarrow$  int_par(code);
  end;

function get_tex_dimen(code : integer): scaled;
  begin get_tex_dimen  $\leftarrow$  dimen_par(code);
  end;

function get_x_height(f : internal_font_number): scaled;
  begin get_x_height  $\leftarrow$  x_height(f);
  end;

function get_charwidth(f : internal_font_number; c : eight_bits): scaled;
  begin if is_valid_char(c) then get_charwidth  $\leftarrow$  char_width(f)(orig_char_info(f)(c))
  else get_charwidth  $\leftarrow$  0;
  end;

function get_charheight(f : internal_font_number; c : eight_bits): scaled;
  begin if is_valid_char(c) then get_charheight  $\leftarrow$  char_height(f)(height_depth(orig_char_info(f)(c)))
  else get_charheight  $\leftarrow$  0;
  end;

function get_chardepth(f : internal_font_number; c : eight_bits): scaled;
  begin if is_valid_char(c) then get_chardepth  $\leftarrow$  char_depth(f)(height_depth(orig_char_info(f)(c)))
  else get_chardepth  $\leftarrow$  0;
  end;

function get_quad(f : internal_font_number): scaled;

```

```
begin get_quad ← quad(f);  
end;  
function get_slant(f : internal_font_number): scaled;  
begin get_slant ← slant(f);  
end;
```

729* The implementation of procedure *pdf_hlist_out* is similar to *hlist_out*.

⟨Declare procedures needed in *pdf_hlist_out*, *pdf_vlist_out* 727⟩

```
procedure pdf_hlist_out; {output an hlist_node box}
  label reswitch, move_past, fin_rule, next_p, found, continue;
  var base_line: scaled; {the baseline coordinate for this box}
      left_edge: scaled; {the left coordinate for this box}
      save_h: scaled; {what cur_h should pop to}
      this_box: pointer; {pointer to containing box}
      g_order: glue_ord; {applicable order of infinity for glue}
      g_sign: normal .. shrinking; {selects type of glue}
      p: pointer; {current position in the hlist}
      leader_box: pointer; {the leader box being replicated}
      leader_wd: scaled; {width of leader box being replicated}
      lx: scaled; {extra space between leader boxes}
      outer_doing_leaders: boolean; {were we doing leaders?}
      edge: scaled; {right edge of sub-box or leader space}
      prev_p: pointer; {one step behind p}
      glue_temp: real; {glue value before rounding}
      cur_glue: real; {glue seen so far}
      cur_g: scaled; {rounded equivalent of cur_glue times the glue ratio}
      i: small_number; {index to scan pdf_link_stack}
  begin cur_g ← 0; cur_glue ← float_constant(0); this_box ← temp_ptr; g_order ← glue_order(this_box);
  g_sign ← glue_sign(this_box); p ← list_ptr(this_box); incr(cur_s); base_line ← cur_v;
  prev_p ← this_box + list_offset; ⟨Initialize hlist_out for mixed direction typesetting 1715⟩;
  left_edge ← cur_h; ⟨Create link annotations for the current hbox if needed 730⟩;
  ⟨Start hlist SyncTEX information record 1928*⟩;
  while p ≠ null do ⟨Output node p for pdf_hlist_out and move to the next node, maintaining the
    condition cur_v = base_line 731*⟩;
  ⟨Finish hlist SyncTEX information record 1929*⟩;
  ⟨Finish hlist_out for mixed direction typesetting 1716⟩;
  decr(cur_s);
end;
```

731* ⟨Output node *p* for *pdf_hlist_out* and move to the next node, maintaining the condition *cur_v = base_line* 731*⟩ ≡

```
reswitch: if is_char_node(p) then
  begin repeat f ← font(p); c ← character(p);
    if is_valid_char(c) then
      begin output_one_char(c); cur_h ← cur_h + char_width(f)(char_info(f)(c)); goto continue;
    end;
    if mltex_enabled_p then ⟨(pdfTEX) Output a substitution, goto continue if not possible 1888*⟩;
  continue: prev_p ← link(prev_p); {N.B.: not prev_p ← p, p might be lig_trick}
  p ← link(p);
  until ¬is_char_node(p);
  ⟨Record current point SyncTEX information 1931*⟩;
end
else ⟨Output the non-char_node p for pdf_hlist_out and move to the next node 732*⟩
```

This code is used in section 729*.

```

732* ⟨Output the non-char_node p for pdf_hlist_out and move to the next node 732*⟩ ≡
  begin case type(p) of
    hlist_node, vlist_node: ⟨(pdfTeX) Output a box in an hlist 733*⟩;
    rule_node: begin rule_ht ← height(p); rule_dp ← depth(p); rule_wd ← width(p); goto fin_rule;
    end;
    whatsit_node: ⟨Output the whatsit node p in pdf_hlist_out 1646⟩;
    glue_node: ⟨(pdfTeX) Move right or output leaders 735⟩;
    margin_kern_node: cur_h ← cur_h + width(p);
    kern_node: begin ⟨Record kern_node SyncTeX information 1933*⟩;
      cur_h ← cur_h + width(p);
    end;
    math_node: begin ⟨Record math_node SyncTeX information 1934*⟩;
      ⟨Handle a math node in hlist_out 1717⟩;
    end;
    ligature_node: ⟨Make node p look like a char_node and goto reswitch 826⟩;
      ⟨Cases of hlist_out that arise in mixed direction text only 1721⟩
    othercases do_nothing
  endcases;
  goto next_p;
fin_rule: ⟨(pdfTeX) Output a rule in an hlist 734⟩;
move_past: begin cur_h ← cur_h + rule_wd;
  ⟨Record horizontal rule_node or glue_node SyncTeX information 1932*⟩;
end;
next_p: prev_p ← p; p ← link(p);
end

```

This code is used in section 731*.

```

733* ⟨(pdfTeX) Output a box in an hlist 733*⟩ ≡
  if list_ptr(p) = null then
    begin ⟨Record void list SyncTeX information 1930*⟩;
      cur_h ← cur_h + width(p);
    end
  else begin cur_v ← base_line + shift_amount(p); { shift the box down }
    temp_ptr ← p; edge ← cur_h + width(p);
    if cur_dir = right_to_left then cur_h ← edge;
    if type(p) = vlist_node then pdf_vlist_out else pdf_hlist_out;
    cur_h ← edge; cur_v ← base_line;
  end

```

This code is used in section 732*.

738* The *pdf_vlist_out* routine is similar to *pdf_hlist_out*, but a bit simpler.

```

procedure pdf_vlist_out; { output a pdf_vlist_node box }
  label move_past, fin_rule, next_p;
  var left_edge: scaled; { the left coordinate for this box }
      top_edge: scaled; { the top coordinate for this box }
      save_v: scaled; { what cur_v should pop to }
      this_box: pointer; { pointer to containing box }
      g_order: glue_ord; { applicable order of infinity for glue }
      g_sign: normal .. shrinking; { selects type of glue }
      p: pointer; { current position in the vlist }
      leader_box: pointer; { the leader box being replicated }
      leader_ht: scaled; { height of leader box being replicated }
      lx: scaled; { extra space between leader boxes }
      outer_doing_leaders: boolean; { were we doing leaders? }
      edge: scaled; { bottom boundary of leader space }
      glue_temp: real; { glue value before rounding }
      cur_glue: real; { glue seen so far }
      cur_g: scaled; { rounded equivalent of cur_glue times the glue ratio }
  begin cur_g ← 0; cur_glue ← float_constant(0); this_box ← temp_ptr; g_order ← glue_order(this_box);
  g_sign ← glue_sign(this_box); p ← list_ptr(this_box); incr(cur_s); left_edge ← cur_h;
  ⟨Start vlist SyncTEX information record 1926*⟩;
  cur_v ← cur_v - height(this_box); top_edge ← cur_v; ⟨Create thread for the current vbox if needed 739⟩;
  while p ≠ null do ⟨Output node p for pdf_vlist_out and move to the next node, maintaining the
    condition cur_h = left_edge 740⟩;
  ⟨Finish vlist SyncTEX information record 1927*⟩;
  decr(cur_s);
  end;

```

742* ⟨(pdfTEX) Output a box in a vlist 742*⟩ ≡

```

if list_ptr(p) = null then
  begin cur_v ← cur_v + height(p); ⟨Record void list SyncTEX information 1930*⟩;
  cur_v ← cur_v + depth(p);
  end
else begin cur_v ← cur_v + height(p); save_v ← cur_v;
  if cur_dir = right_to_left then cur_h ← left_edge - shift_amount(p)
  else cur_h ← left_edge + shift_amount(p); { shift the box right }
  temp_ptr ← p;
  if type(p) = vlist_node then pdf_vlist_out else pdf_hlist_out;
  cur_v ← save_v + depth(p); cur_h ← left_edge;
  end

```

This code is used in section 741.

750* *pdf_ship_out* is used instead of *ship_out* to shipout a box to PDF output. If *shipping_page* is not set then the output will be a Form object, otherwise it will be a Page object.

```

procedure pdf_ship_out(p : pointer; shipping_page : boolean); { output the box p }
  label done, done1;
  var i, j, k: integer; { general purpose accumulators }
    s: pool_pointer; { index into str_pool }
    mediabox_given: boolean; save_font_list: pointer;
      { to save pdf_font_list during flushing pending forms }
    save_obj_list: pointer; { to save pdf_obj_list }
    save_ximage_list: pointer; { to save pdf_ximage_list }
    save_xform_list: pointer; { to save pdf_xform_list }
    save_image_procset: integer; { to save pdf_image_procset }
    save_text_procset: integer; { to save pdf_text_procset }
    pdf_last_resources: integer; { pointer to most recently generated Resources object }
  begin if tracing_output > 0 then
    begin print_nl(""); print_ln; print("Completed_box_being_shipped_out");
    end;
  if  $\neg$ init_pdf_output then
    begin  $\langle$  Initialize variables for PDF output 792  $\rangle$ ;
    init_pdf_output  $\leftarrow$  true;
    end;
  is_shipping_page  $\leftarrow$  shipping_page;
  if shipping_page then
    begin if term_offset > max_print_line - 9 then print_ln
    else if (term_offset > 0)  $\vee$  (file_offset > 0) then print_char(" ");
    print_char("["); j  $\leftarrow$  9;
    while (count(j) = 0)  $\wedge$  (j > 0) do decr(j);
    for k  $\leftarrow$  0 to j do
      begin print_int(count(k));
      if k < j then print_char(".");
      end;
    update_terminal;
    end;
  if tracing_output > 0 then
    begin if shipping_page then print_char("]");
    begin_diagnostic; show_box(p); end_diagnostic(true);
    end;
  pdf_output_value  $\leftarrow$  pdf_output; { SyncTeX: we assume that pdf_output is properly set up }
  if shipping_page then synctex_sheet(mag) else synctex_pdfxform(p);
   $\langle$  (pdfTeX) Ship box p out 751  $\rangle$ ;
  if shipping_page then synctex_teehs else synctex_mroxfdp;
  if eTeX_ex then  $\langle$  Check for LR anomalies at the end of ship_out 1731  $\rangle$ ;
  if (tracing_output  $\leq$  0)  $\wedge$  shipping_page then print_char("]");
  dead_cycles  $\leftarrow$  0; update_terminal; { progress report }
   $\langle$  Flush the box from memory, showing statistics if requested 667  $\rangle$ ;
  end;

```


884* \langle Look at the list of characters starting with x in font g ; set f and c whenever a better character is found; **goto** $found$ as soon as a large enough variant is encountered **884*** $\rangle \equiv$

```

begin  $y \leftarrow x$ ;
if  $(qo(y) \geq font\_bc[g]) \wedge (qo(y) \leq font\_ec[g])$  then
  begin  $continue: q \leftarrow orig\_char\_info(g)(y)$ ;
  if  $char\_exists(q)$  then
    begin if  $char\_tag(q) = ext\_tag$  then
      begin  $f \leftarrow g; c \leftarrow y; \mathbf{goto} found$ ;
      end;
       $hd \leftarrow height\_depth(q); u \leftarrow char\_height(g)(hd) + char\_depth(g)(hd)$ ;
    if  $u > w$  then
      begin  $f \leftarrow g; c \leftarrow y; w \leftarrow u$ ;
      if  $u \geq v$  then goto  $found$ ;
      end;
    if  $char\_tag(q) = list\_tag$  then
      begin  $y \leftarrow rem\_byte(q); \mathbf{goto} continue$ ;
      end;
    end;
  end;
end

```

This code is used in section [883](#).

897* Here we save memory space in a common case.

⟨Simplify a trivial box 897*⟩ ≡

```

q ← list_ptr(x);
if is_char_node(q) then
  begin r ← link(q);
  if r ≠ null then
    if link(r) = null then
      if ¬is_char_node(r) then
        if type(r) = kern_node then { unneeded italic correction }
          begin free_node(r, medium_node_size); link(q) ← null;
          end;
      end;
  end

```

This code is used in section 896.

898* It is convenient to have a procedure that converts a *math_char* field to an “unpacked” form. The *fetch* routine sets *cur_f*, *cur_c*, and *cur_i* to the font code, character code, and character information bytes of a given noad field. It also takes care of issuing error messages for nonexistent characters; in such cases, *char_exists*(*cur_i*) will be *false* after *fetch* has acted, and the field will also have been reset to *empty*.

```

procedure fetch(a : pointer); { unpack the math_char field a }
begin cur_c ← character(a); cur_f ← fam_fnt(fam(a) + cur_size);
if cur_f = null_font then ⟨Complain about an undefined family and set cur_i null 899⟩
else begin if (qo(cur_c) ≥ font_bc[cur_f]) ∧ (qo(cur_c) ≤ font_ec[cur_f]) then
  cur_i ← orig_char_info(cur_f)(cur_c)
else cur_i ← null_character;
if ¬(char_exists(cur_i)) then
  begin char_warning(cur_f, qo(cur_c)); math_type(a) ← empty; cur_i ← null_character;
  end;
end;
end;

```

916* ⟨Switch to a larger accent if available and appropriate 916*⟩ ≡

```

loop begin if char_tag(i) ≠ list_tag then goto done;
  y ← rem_byte(i); i ← orig_char_info(f)(y);
  if ¬char_exists(i) then goto done;
  if char_width(f)(i) > w then goto done;
  c ← y;
end;

```

done:

This code is used in section 914.

925* If the nucleus of an *op_noad* is a single character, it is to be centered vertically with respect to the axis, after first being enlarged (via a character list in the font) if we are in display style. The normal convention for placing displayed limits is to put them above and below the operator in display style.

The italic correction is removed from the character if there is a subscript and the limits are not being displayed. The *make_op* routine returns the value that should be used as an offset between subscript and superscript.

After *make_op* has acted, *subtype(q)* will be *limits* if and only if the limits have been set above and below the operator. In that case, *new_hlist(q)* will already contain the desired final box.

⟨Declare math construction procedures 910⟩ +≡

```

function make_op(q : pointer): scaled;
  var delta: scaled; { offset between subscript and superscript }
      p, v, x, y, z: pointer; { temporary registers for box construction }
      c: quarterword; i: four_quarters; { registers for character examination }
      shift_up, shift_down: scaled; { dimensions for box calculation }
  begin if (subtype(q) = normal) ∧ (cur_style < text_style) then subtype(q) ← limits;
  if math_type(nucleus(q)) = math_char then
    begin fetch(nucleus(q));
    if (cur_style < text_style) ∧ (char_tag(cur_i) = list_tag) then { make it larger }
      begin c ← rem_byte(cur_i); i ← orig_char_info(cur_f)(c);
      if char_exists(i) then
        begin cur_c ← c; cur_i ← i; character(nucleus(q)) ← c;
        end;
      end;
    delta ← char_italic(cur_f)(cur_i); x ← clean_box(nucleus(q), cur_style);
    if (math_type(subscr(q)) ≠ empty) ∧ (subtype(q) ≠ limits) then width(x) ← width(x) − delta;
      { remove italic correction }
    shift_amount(x) ← half(height(x) − depth(x)) − axis_height(cur_size); { center vertically }
    math_type(nucleus(q)) ← sub_box; info(nucleus(q)) ← x;
    end
  else delta ← 0;
  if subtype(q) = limits then ⟨Construct a box with limits above and below it, skewed by delta 926⟩;
  make_op ← delta;
  end;

```

```

1087* define wrap_lig(#) ≡
    if ligature_present then
        begin p ← new_ligature(hf, cur_l, link(cur_q));
        if lft_hit then
            begin subtype(p) ← 2; lft_hit ← false;
            end;
        if # then
            if lig_stack = null then
                begin incr(subtype(p)); rt_hit ← false;
                end;
            link(cur_q) ← p; t ← p; ligature_present ← false;
            end
define pop_lig_stack ≡
    begin if lig_ptr(lig_stack) > null then
        begin link(t) ← lig_ptr(lig_stack); { this is a charnode for hu[j + 1] }
        t ← link(t); incr(j);
        end;
        p ← lig_stack; lig_stack ← link(p); free_node(p, small_node_size);
        if lig_stack = null then set_cur_r else cur_r ← character(lig_stack);
        end { if lig_stack isn't null we have cur_rh = non_char }
⟨ Append a ligature and/or kern to the translation; goto continue if the stack of inserted ligatures is
  nonempty 1087* ⟩ ≡
wrap_lig(rt_hit);
if w ≠ 0 then
    begin link(t) ← new_kern(w); t ← link(t); w ← 0; sync_tag(t + medium_node_size) ← 0;
    { SyncTeX: do nothing, it is too late }
    end;
if lig_stack > null then
    begin cur_q ← t; cur_l ← character(lig_stack); ligature_present ← true; pop_lig_stack;
    goto continue;
    end

```

This code is used in section 1083.

1097* The patterns are stored in a compact table that is also efficient for retrieval, using a variant of “trie memory” [cf. *The Art of Computer Programming* **3** (1973), 481–505]. We can find each pattern $p_1 \dots p_k$ by letting z_0 be one greater than the relevant language index and then, for $1 \leq i \leq k$, setting $z_i \leftarrow \text{trie_link}(z_{i-1}) + p_i$; the pattern will be identified by the number z_k . Since all the pattern information is packed together into a single *trie_link* array, it is necessary to prevent confusion between the data from inequivalent patterns, so another table is provided such that $\text{trie_char}(z_i) = p_i$ for all i . There is also a table $\text{trie_op}(z_k)$ to identify the numbers $n_0 \dots n_k$ associated with $p_1 \dots p_k$.

The theory that comparatively few different number sequences $n_0 \dots n_k$ actually occur, since most of the n 's are generally zero, seems to fail at least for the large German hyphenation patterns. Therefore the number sequences cannot any longer be encoded in such a way that $\text{trie_op}(z_k)$ is only one byte long. We have introduced a new constant *max_trie_op* for the maximum allowable hyphenation operation code value; *max_trie_op* might be different for TeX and INITEX and must not exceed *max_halfword*. An opcode will occupy a halfword if *max_trie_op* exceeds *max_quarterword* or a quarterword otherwise. If $\text{trie_op}(z_k) \neq \text{min_trie_op}$, when $p_1 \dots p_k$ has matched the letters in $hc[(l - k + 1) \dots l]$ of language t , we perform all of the required operations for this pattern by carrying out the following little program: Set $v \leftarrow \text{trie_op}(z_k)$. Then set $v \leftarrow v + \text{op_start}[t]$, $\text{hyf}[l - \text{hyf_distance}[v]] \leftarrow \max(\text{hyf}[l - \text{hyf_distance}[v]], \text{hyf_num}[v])$, and $v \leftarrow \text{hyf_next}[v]$; repeat, if necessary, until $v = \text{min_trie_op}$.

```
<Types in the outer block 18> +≡
  trie_pointer = 0 .. ssup_trie_size; { an index into trie }
  trie_opcode = 0 .. ssup_trie_opcode; { a trie opcode }
```

1098* For more than 255 trie op codes, the three fields *trie_link*, *trie_char*, and *trie_op* will no longer fit into one memory word; thus using web2c we define *trie* as three array instead of an array of records. The variant will be implemented by reusing the opcode field later on with another macro.

```
define trie_link(#) ≡ trie_trl[#] { “downward” link in a trie }
define trie_char(#) ≡ trie_trc[#] { character matched at this trie location }
define trie_op(#) ≡ trie_tro[#] { program for hyphenation at this trie location }
```

```
<Global variables 13> +≡
  { We will dynamically allocate these arrays. }
trie_trl: ↑trie_pointer; { trie_link }
trie_tro: ↑trie_pointer; { trie_op }
trie_trc: ↑quarterword; { trie_char }
hyf_distance: array [1 .. trie_op_size] of small_number; { position k - j of n_j }
hyf_num: array [1 .. trie_op_size] of small_number; { value of n_j }
hyf_next: array [1 .. trie_op_size] of trie_opcode; { continuation code }
op_start: array [ASCII_code] of 0 .. trie_op_size; { offset for current language }
```

1100* Assuming that these auxiliary tables have been set up properly, the hyphenation algorithm is quite short. In the following code we set $hc[hn + 2]$ to the impossible value 256, in order to guarantee that $hc[hn + 3]$ will never be fetched.

```

⟨Find hyphen locations for the word in hc, or return 1100*⟩ ≡
  for j ← 0 to hn do hyf[j] ← 0;
  ⟨Look for the word hc[1 .. hn] in the exception table, and goto found (with hyf containing the hyphens)
  if an entry is found 1107*⟩;
  if trie_char(cur_lang + 1) ≠ qi(cur_lang) then return; { no patterns for cur_lang }
  hc[0] ← 0; hc[hn + 1] ← 0; hc[hn + 2] ← 256; { insert delimiters }
  for j ← 0 to hn - r_hyf + 1 do
    begin z ← trie_link(cur_lang + 1) + hc[j]; l ← j;
    while hc[l] = qo(trie_char(z)) do
      begin if trie_op(z) ≠ min_trie_op then ⟨Store maximum values in the hyf table 1101*⟩;
        incr(l); z ← trie_link(z) + hc[l];
      end;
    end;
  end;
found: for j ← 0 to l_hyf - 1 do hyf[j] ← 0;
  for j ← 0 to r_hyf - 1 do hyf[hn - j] ← 0

```

This code is used in section 1072.

```

1101* ⟨Store maximum values in the hyf table 1101*⟩ ≡
  begin v ← trie_op(z);
  repeat v ← v + op_start[cur_lang]; i ← l - hyf_distance[v];
    if hyf_num[v] > hyf[i] then hyf[i] ← hyf_num[v];
    v ← hyf_next[v];
  until v = min_trie_op;
  end

```

This code is used in section 1100*.

1102* The exception table that is built by TeX's `\hyphenation` primitive is organized as an ordered hash table [cf. Amble and Knuth, *The Computer Journal* **17** (1974), 135–142] using linear probing. If α and β are words, we will say that $\alpha < \beta$ if $|\alpha| < |\beta|$ or if $|\alpha| = |\beta|$ and α is lexicographically smaller than β . (The notation $|\alpha|$ stands for the length of α .) The idea of ordered hashing is to arrange the table so that a given word α can be sought by computing a hash address $h = h(\alpha)$ and then looking in table positions $h, h - 1, \dots$, until encountering the first word $\leq \alpha$. If this word is different from α , we can conclude that α is not in the table. This is a clever scheme which saves the need for a hash link array. However, it is difficult to increase the size of the hyphen exception arrays. To make this easier, the ordered hash has been replaced by a simple hash, using an additional array *hyph_link*. The value 0 in *hyph_link*[*k*] means that there are no more entries corresponding to the specific hash chain. When *hyph_link*[*k*] > 0, the next entry in the hash chain is *hyph_link*[*k*] - 1. This value is used because the arrays start at 0.

The words in the table point to lists in *mem* that specify hyphen positions in their *info* fields. The list for $c_1 \dots c_n$ contains the number k if the word $c_1 \dots c_n$ has a discretionary hyphen between c_k and c_{k+1} .

```

⟨Types in the outer block 18⟩ +≡
  hyph_pointer = 0 .. ssup_hyph_size;
  { index into hyphen exceptions hash table; enlarging this requires changing (un)dump code }

```

1103* \langle Global variables 13 $\rangle + \equiv$

hyph_word: $\uparrow str_number$; {exception words}
hyph_list: $\uparrow pointer$; {lists of hyphen positions}
hyph_link: $\uparrow hyph_pointer$; {link array for hyphen exceptions hash table}
hyph_count: *integer*; {the number of words in the exception dictionary}
hyph_next: *integer*; {next free slot in hyphen exceptions hash table}

1105* \langle Set initial values of key variables 21 $\rangle + \equiv$

```

for z  $\leftarrow$  0 to hyph_size do
  begin hyph_word[z]  $\leftarrow$  0; hyph_list[z]  $\leftarrow$  null; hyph_link[z]  $\leftarrow$  0;
  end;
hyph_count  $\leftarrow$  0; hyph_next  $\leftarrow$  hyph_prime + 1;
if hyph_next > hyph_size then hyph_next  $\leftarrow$  hyph_prime;

```

1107* First we compute the hash code *h*, then we search until we either find the word or we don't. Words from different languages are kept separate by appending the language code to the string.

\langle Look for the word *hc*[1 .. *hn*] in the exception table, and **goto** *found* (with *hyf* containing the hyphens) if an entry is found 1107* $\rangle \equiv$

```

h  $\leftarrow$  hc[1]; incr(hn); hc[hn]  $\leftarrow$  cur_lang;
for j  $\leftarrow$  2 to hn do h  $\leftarrow$  (h + h + hc[j]) mod hyph_prime;
loop begin  $\langle$  If the string hyph_word[h] is less than hc[1 .. hn], goto not_found; but if the two strings
  are equal, set hyf to the hyphen positions and goto found 1108*  $\rangle$ ;
  h  $\leftarrow$  hyph_link[h];
  if h = 0 then goto not_found;
  decr(h);
end;
not_found: decr(hn)

```

This code is used in section 1100*.

1108* \langle If the string *hyph_word*[*h*] is less than *hc*[1 .. *hn*], **goto** *not_found*; but if the two strings are equal, set *hyf* to the hyphen positions and **goto** *found* 1108* $\rangle \equiv$

{ This is now a simple hash list, not an ordered one, so the module title is no longer descriptive. }

```

k  $\leftarrow$  hyph_word[h];
if k = 0 then goto not_found;
if length(k) = hn then
  begin j  $\leftarrow$  1; u  $\leftarrow$  str_start[k];
  repeat if so(str_pool[u])  $\neq$  hc[j] then goto done;
    incr(j); incr(u);
  until j > hn;
   $\langle$  Insert hyphens as specified in hyph_list[h] 1109  $\rangle$ ;
  decr(hn); goto found;
end;

```

done:

This code is used in section 1107*.

1111* We have now completed the hyphenation routine, so the *line_break* procedure is finished at last. Since the hyphenation exception table is fresh in our minds, it's a good time to deal with the routine that adds new entries to it.

When \TeX has scanned ' \backslash hyphenation', it calls on a procedure named *new_hyph_exceptions* to do the right thing.

```

define set_cur_lang  $\equiv$ 
    if language  $\leq$  0 then cur_lang  $\leftarrow$  0
    else if language  $>$  255 then cur_lang  $\leftarrow$  0
    else cur_lang  $\leftarrow$  language

procedure new_hyph_exceptions; { enters new exceptions }
label reswitch, exit, found, not_found, not_found1;
var n: 0 .. 64; { length of current word; not always a small_number }
    j: 0 .. 64; { an index into hc }
    h: hyph_pointer; { an index into hyph_word and hyph_list }
    k: str_number; { an index into str_start }
    p: pointer; { head of a list of hyphen positions }
    q: pointer; { used when creating a new node for list p }
    s: str_number; { strings being compared or stored }
    u, v: pool_pointer; { indices into str_pool }
begin scan_left_brace; { a left brace must follow  $\backslash$ hyphenation }
set_cur_lang;
init if trie_not_ready then
    begin hyph_index  $\leftarrow$  0; goto not_found1;
    end;
tini
    set_hyph_index;
not_found1:  $\langle$  Enter as many hyphenation exceptions as are listed, until coming to a right brace; then
    return 1112;
exit: end;

1116*  $\langle$  Enter a hyphenation exception 1116*  $\rangle \equiv$ 
begin incr(n); hc[n]  $\leftarrow$  cur_lang; str_room(n); h  $\leftarrow$  0;
for j  $\leftarrow$  1 to n do
    begin h  $\leftarrow$  (h + h + hc[j]) mod hyph_prime; append_char(hc[j]);
    end;
s  $\leftarrow$  make_string;  $\langle$  Insert the pair (s, p) into the exception table 1117*  $\rangle$ ;
end

This code is used in section 1112.

```



```

1117* ⟨Insert the pair  $(s, p)$  into the exception table 1117*⟩ ≡
  if hyph_next ≤ hyph_prime then
    while (hyph_next > 0) ∧ (hyph_word[hyph_next - 1] > 0) do decr(hyph_next);
  if (hyph_count = hyph_size) ∨ (hyph_next = 0) then overflow("exception_dictionary", hyph_size);
  incr(hyph_count);
  while hyph_word[h] ≠ 0 do
    begin ⟨If the string hyph_word[h] is less than or equal to s, interchange (hyph_word[h], hyph_list[h])
      with  $(s, p)$  1118*⟩;
    if hyph_link[h] = 0 then
      begin hyph_link[h] ← hyph_next;
      if hyph_next ≥ hyph_size then hyph_next ← hyph_prime;
      if hyph_next > hyph_prime then incr(hyph_next);
      end;
    h ← hyph_link[h] - 1;
  end;
found: hyph_word[h] ← s; hyph_list[h] ← p
This code is used in section 1116*.

```

```

1118* ⟨If the string hyph_word[h] is less than or equal to s, interchange (hyph_word[h], hyph_list[h]) with
   $(s, p)$  1118*⟩ ≡
  { This is now a simple hash list, not an ordered one, so the module title is no longer descriptive. }
  k ← hyph_word[h];
  if length(k) ≠ length(s) then goto not_found;
  u ← str_start[k]; v ← str_start[s];
  repeat if str_pool[u] ≠ str_pool[v] then goto not_found;
    incr(u); incr(v);
  until u = str_start[k + 1]; { repeat hyphenation exception; flushing old data }
  flush_string; s ← hyph_word[h]; { avoid slow_make_string! }
  decr(hyph_count); { We could also flush_list(hyph_list[h]);, but it interferes with trip.log. }
  goto found;
not_found:
This code is used in section 1117*.

```

1120* Before we discuss trie building in detail, let's consider the simpler problem of creating the *hyf_distance*, *hyf_num*, and *hyf_next* arrays.

Suppose, for example, that TeX reads the pattern 'ab2cde1'. This is a pattern of length 5, with $n_0 \dots n_5 = 002001$ in the notation above. We want the corresponding *trie_op* code v to have $hyf_distance[v] = 3$, $hyf_num[v] = 2$, and $hyf_next[v] = v'$, where the auxiliary *trie_op* code v' has $hyf_distance[v'] = 0$, $hyf_num[v'] = 1$, and $hyf_next[v'] = min_trie_op$.

TeX computes an appropriate value v with the *new_trie_op* subroutine below, by setting

$$v' \leftarrow new_trie_op(0, 1, min_trie_op), \quad v \leftarrow new_trie_op(3, 2, v').$$

This subroutine looks up its three parameters in a special hash table, assigning a new value only if these three have not appeared before for the current language.

The hash table is called *trie_op_hash*, and the number of entries it contains is *trie_op_ptr*.

<Global variables 13> +≡

```

init trie_op_hash: array [neg_trie_op_size .. trie_op_size] of 0 .. trie_op_size;
    { trie op codes for quadruples }
trie_used: array [ASCII_code] of trie_opcode; { largest opcode used so far for this language }
trie_op_lang: array [1 .. trie_op_size] of ASCII_code; { language part of a hashed quadruple }
trie_op_val: array [1 .. trie_op_size] of trie_opcode; { opcode corresponding to a hashed quadruple }
trie_op_ptr: 0 .. trie_op_size; { number of stored ops so far }
tini
max_op_used: trie_opcode; { largest opcode used for any language }
small_op: boolean; { flag used while dumping or undumping }

```

1121* It's tempting to remove the *overflow* stops in the following procedure; *new_trie_op* could return *min_trie_op* (thereby simply ignoring part of a hyphenation pattern) instead of aborting the job. However, that would lead to different hyphenation results on different installations of TeX using the same patterns. The *overflow* stops are necessary for portability of patterns.

(Declare procedures for preprocessing hyphenation patterns 1121*) \equiv

```
function new_trie_op(d, n : small_number; v : trie_opcode): trie_opcode;
  label exit;
  var h: neg_trie_op_size .. trie_op_size; { trial hash location }
      u: trie_opcode; { trial op code }
      l: 0 .. trie_op_size; { pointer to stored data }
  begin h  $\leftarrow$  abs(n+313*d+361*v+1009*cur_lang) mod (trie_op_size - neg_trie_op_size) + neg_trie_op_size;
  loop begin l  $\leftarrow$  trie_op_hash[h];
    if l = 0 then { empty position found for a new op }
      begin if trie_op_ptr = trie_op_size then overflow("pattern_memory_ops", trie_op_size);
        u  $\leftarrow$  trie_used[cur_lang];
        if u = max_trie_op then
          overflow("pattern_memory_ops_per_language", max_trie_op - min_trie_op);
          incr(trie_op_ptr); incr(u); trie_used[cur_lang]  $\leftarrow$  u;
          if u > max_op_used then max_op_used  $\leftarrow$  u;
          hyf_distance[trie_op_ptr]  $\leftarrow$  d; hyf_num[trie_op_ptr]  $\leftarrow$  n; hyf_next[trie_op_ptr]  $\leftarrow$  v;
          trie_op_lang[trie_op_ptr]  $\leftarrow$  cur_lang; trie_op_hash[h]  $\leftarrow$  trie_op_ptr; trie_op_val[trie_op_ptr]  $\leftarrow$  u;
          new_trie_op  $\leftarrow$  u; return;
        end;
      if (hyf_distance[l] = d)  $\wedge$  (hyf_num[l] = n)  $\wedge$  (hyf_next[l] = v)  $\wedge$  (trie_op_lang[l] = cur_lang) then
        begin new_trie_op  $\leftarrow$  trie_op_val[l]; return;
        end;
      if h > -trie_op_size then decr(h) else h  $\leftarrow$  trie_op_size;
    end;
  exit: end;
```

See also sections 1125, 1126, 1130, 1134, 1136, 1137*, and 1143*.

This code is used in section 1119.

1122* After *new_trie_op* has compressed the necessary opcode information, plenty of information is available to unscramble the data into the final form needed by our hyphenation algorithm.

(Sort the hyphenation op tables into proper order 1122*) \equiv

```
op_start[0]  $\leftarrow$  -min_trie_op;
for j  $\leftarrow$  1 to 255 do op_start[j]  $\leftarrow$  op_start[j - 1] + qo(trie_used[j - 1]);
for j  $\leftarrow$  1 to trie_op_ptr do trie_op_hash[j]  $\leftarrow$  op_start[trie_op_lang[j]] + trie_op_val[j]; { destination }
for j  $\leftarrow$  1 to trie_op_ptr do
  while trie_op_hash[j] > j do
    begin k  $\leftarrow$  trie_op_hash[j];
      t  $\leftarrow$  hyf_distance[k]; hyf_distance[k]  $\leftarrow$  hyf_distance[j]; hyf_distance[j]  $\leftarrow$  t;
      t  $\leftarrow$  hyf_num[k]; hyf_num[k]  $\leftarrow$  hyf_num[j]; hyf_num[j]  $\leftarrow$  t;
      t  $\leftarrow$  hyf_next[k]; hyf_next[k]  $\leftarrow$  hyf_next[j]; hyf_next[j]  $\leftarrow$  t;
      trie_op_hash[j]  $\leftarrow$  trie_op_hash[k]; trie_op_hash[k]  $\leftarrow$  j;
    end
```

This code is used in section 1129.

1123* Before we forget how to initialize the data structures that have been mentioned so far, let's write down the code that gets them started.

```

⟨ Initialize table entries (done by INITEX only) 182 ⟩ +≡
  for  $k \leftarrow -trie\_op\_size$  to  $trie\_op\_size$  do  $trie\_op\_hash[k] \leftarrow 0$ ;
  for  $k \leftarrow 0$  to 255 do  $trie\_used[k] \leftarrow min\_trie\_op$ ;
   $max\_op\_used \leftarrow min\_trie\_op$ ;  $trie\_op\_ptr \leftarrow 0$ ;

```

1124* The linked trie that is used to preprocess hyphenation patterns appears in several global arrays. Each node represents an instruction of the form “if you see character c , then perform operation o , move to the next character, and go to node l ; otherwise go to node r .” The four quantities c , o , l , and r are stored in four arrays $trie_c$, $trie_o$, $trie_l$, and $trie_r$. The root of the trie is $trie_l[0]$, and the number of nodes is $trie_ptr$. Null trie pointers are represented by zero. To initialize the trie, we simply set $trie_l[0]$ and $trie_ptr$ to zero. We also set $trie_c[0]$ to some arbitrary value, since the algorithm may access it.

The algorithms maintain the condition

$$trie_c[trie_r[z]] > trie_c[z] \quad \text{whenever } z \neq 0 \text{ and } trie_r[z] \neq 0;$$

in other words, sibling nodes are ordered by their c fields.

define $trie_root \equiv trie_l[0]$ { root of the linked trie }

⟨ Global variables 13 ⟩ +≡

```

init  $trie\_c$ :  $\uparrow packed\_ASCII\_code$ ; { characters to match }
 $trie\_o$ :  $\uparrow trie\_opcode$ ; { operations to perform }
 $trie\_l$ :  $\uparrow trie\_pointer$ ; { left subtrie links }
 $trie\_r$ :  $\uparrow trie\_pointer$ ; { right subtrie links }
 $trie\_ptr$ :  $trie\_pointer$ ; { the number of nodes in the trie }
 $trie\_hash$ :  $\uparrow trie\_pointer$ ; { used to identify equivalent subtrees }
tini

```

1127* The compressed trie will be packed into the $trie$ array using a “top-down first-fit” procedure. This is a little tricky, so the reader should pay close attention: The $trie_hash$ array is cleared to zero again and renamed $trie_ref$ for this phase of the operation; later on, $trie_ref[p]$ will be nonzero only if the linked trie node p is the smallest character in a family and if the characters c of that family have been allocated to locations $trie_ref[p] + c$ in the $trie$ array. Locations of $trie$ that are in use will have $trie_link = 0$, while the unused holes in $trie$ will be doubly linked with $trie_link$ pointing to the next larger vacant location and $trie_back$ pointing to the next smaller one. This double linking will have been carried out only as far as $trie_max$, where $trie_max$ is the largest index of $trie$ that will be needed. To save time at the low end of the trie, we maintain array entries $trie_min[c]$ pointing to the smallest hole that is greater than c . Another array $trie_taken$ tells whether or not a given location is equal to $trie_ref[p]$ for some p ; this array is used to ensure that distinct nodes in the compressed trie will have distinct $trie_ref$ entries.

define $trie_ref \equiv trie_hash$ { where linked trie families go into $trie$ }

define $trie_back(\#) \equiv trie_tro[\#]$ { use the opcode field now for backward links }

⟨ Global variables 13 ⟩ +≡

```

init  $trie\_taken$ :  $\uparrow boolean$ ; { does a family start here? }
 $trie\_min$ : array [ $ASCII\_code$ ] of  $trie\_pointer$ ; { the first possible slot for each character }
 $trie\_max$ :  $trie\_pointer$ ; { largest location used in  $trie$  }
 $trie\_not\_ready$ :  $boolean$ ; { is the trie still in linked form? }
tini

```

1128* Each time `\patterns` appears, it contributes further patterns to the future trie, which will be built only when hyphenation is attempted or when a format file is dumped. The boolean variable `trie_not_ready` will change to `false` when the trie is compressed; this will disable further patterns.

```
⟨Initialize table entries (done by INITEX only) 182⟩ +≡
  trie_not_ready ← true;
```

1135* When the whole trie has been allocated into the sequential table, we must go through it once again so that `trie` contains the correct information. Null pointers in the linked trie will be represented by the value 0, which properly implements an “empty” family.

```
define clear_trie ≡ { clear trie[r] }
  begin trie_link(r) ← 0; trie_op(r) ← min_trie_op; trie_char(r) ← min_quarterword;
    { trie_char ← qi(0) }
  end
```

```
⟨Move the data into trie 1135*⟩ ≡
```

```
  if trie_max = 0 then { no patterns were given }
    begin for r ← 0 to 256 do clear_trie;
      trie_max ← 256;
    end
  else begin if hyph_root > 0 then trie_fix(hyph_root);
    if trie_root > 0 then trie_fix(trie_root); { this fixes the non-holes in trie }
    r ← 0; { now we will zero out all the holes }
    repeat s ← trie_link(r); clear_trie; r ← s;
    until r > trie_max;
  end;
  trie_char(0) ← qi("?"); { make trie_char(c) ≠ c for all c }
```

This code is used in section 1143*.

1137* Now let’s go back to the easier problem, of building the linked trie. When INITEX has scanned the ‘`\patterns`’ control sequence, it calls on `new_patterns` to do the right thing.

```
⟨Declare procedures for preprocessing hyphenation patterns 1121*⟩ +≡
```

```
procedure new_patterns; { initializes the hyphenation pattern data }
  label done, done1;
  var k, l: 0 .. 64; { indices into hc and hyf; not always in small_number range }
    digit_sensed: boolean; { should the next digit be treated as a letter? }
    v: trie_opcode; { trie op code }
    p, q: trie_pointer; { nodes of trie traversed during insertion }
    first_child: boolean; { is p = trie_l[q]? }
    c: ASCII_code; { character being inserted }
  begin if trie_not_ready then
    begin set_cur_lang; scan_left_brace; { a left brace must follow \patterns }
    ⟨Enter all of the patterns into a linked trie, until coming to a right brace 1138⟩;
    if saving_hyph_codes > 0 then ⟨Store hyphenation codes for current language 1856⟩;
    end
  else begin print_err("Too_late_for_"); print_esc("patterns");
    help1("All_patterns_must_be_given_before_typesetting_begins."); error;
    link(garbage) ← scan_toks(false, false); flush_list(def_ref);
    end;
  end;
```

1140* When the following code comes into play, the pattern $p_1 \dots p_k$ appears in $hc[1 \dots k]$, and the corresponding sequence of numbers $n_0 \dots n_k$ appears in $hyf[0 \dots k]$.

⟨Insert a new pattern into the linked trie **1140***⟩ \equiv

```

begin ⟨Compute the trie op code,  $v$ , and set  $l \leftarrow 0$  1142*⟩;
 $q \leftarrow 0$ ;  $hc[0] \leftarrow cur\_lang$ ;
while  $l \leq k$  do
  begin  $c \leftarrow hc[l]$ ;  $incr(l)$ ;  $p \leftarrow trie\_l[q]$ ;  $first\_child \leftarrow true$ ;
  while  $(p > 0) \wedge (c > so(trie\_c[p]))$  do
    begin  $q \leftarrow p$ ;  $p \leftarrow trie\_r[q]$ ;  $first\_child \leftarrow false$ ;
    end;
  if  $(p = 0) \vee (c < so(trie\_c[p]))$  then
    ⟨Insert a new trie node between  $q$  and  $p$ , and make  $p$  point to it 1141*⟩;
     $q \leftarrow p$ ; { now node  $q$  represents  $p_1 \dots p_{l-1}$  }
  end;
if  $trie\_o[q] \neq min\_trie\_op$  then
  begin  $print\_err("Duplicate\_pattern")$ ;  $help1("See\_Appendix\_H.")$ ;  $error$ ;
  end;
 $trie\_o[q] \leftarrow v$ ;
end

```

This code is used in section **1138**.

1141* ⟨Insert a new trie node between q and p , and make p point to it **1141***⟩ \equiv

```

begin if  $trie\_ptr = trie\_size$  then  $overflow("pattern\_memory", trie\_size)$ ;
 $incr(trie\_ptr)$ ;  $trie\_r[trie\_ptr] \leftarrow p$ ;  $p \leftarrow trie\_ptr$ ;  $trie\_l[p] \leftarrow 0$ ;
if  $first\_child$  then  $trie\_l[q] \leftarrow p$  else  $trie\_r[q] \leftarrow p$ ;
 $trie\_c[p] \leftarrow si(c)$ ;  $trie\_o[p] \leftarrow min\_trie\_op$ ;
end

```

This code is used in sections **1140***, **1856**, and **1857**.

1142* ⟨Compute the trie op code, v , and set $l \leftarrow 0$ **1142***⟩ \equiv

```

if  $hc[1] = 0$  then  $hyf[0] \leftarrow 0$ ;
if  $hc[k] = 0$  then  $hyf[k] \leftarrow 0$ ;
 $l \leftarrow k$ ;  $v \leftarrow min\_trie\_op$ ;
loop begin if  $hyf[l] \neq 0$  then  $v \leftarrow new\_trie\_op(k - l, hyf[l], v)$ ;
  if  $l > 0$  then  $decr(l)$  else goto  $done1$ ;
end;

```

$done1$:

This code is used in section **1140***.

1143* Finally we put everything together: Here is how the trie gets to its final, efficient form. The following packing routine is rigged so that the root of the linked tree gets mapped into location 1 of *trie*, as required by the hyphenation algorithm. This happens because the first call of *first_fit* will “take” location 1.

⟨Declare procedures for preprocessing hyphenation patterns 1121*⟩ +≡

```

procedure init_trie;
  var p: trie_pointer; { pointer for initialization }
      j, k, t: integer; { all-purpose registers for initialization }
      r, s: trie_pointer; { used to clean up the packed trie }
  begin ⟨Get ready to compress the trie 1129⟩;
  if trie_root ≠ 0 then
    begin first_fit(trie_root); trie_pack(trie_root);
    end;
  if hyph_root ≠ 0 then ⟨Pack all stored hyph_codes 1858⟩;
  ⟨Move the data into trie 1135*⟩;
  trie_not_ready ← false;
  end;

```

1165* Pages are built by appending nodes to the current list in TeX’s vertical mode, which is at the outermost level of the semantic nest. This vlist is split into two parts; the “current page” that we have been talking so much about already, and the “contribution list” that receives new nodes as they are created. The current page contains everything that the page builder has accounted for in its data structures, as described above, while the contribution list contains other things that have been generated by other parts of TeX but have not yet been seen by the page builder. The contribution list starts at *link(contrib.head)*, and it ends at the current node in TeX’s vertical mode.

When TeX has appended new material in vertical mode, it calls the procedure *build_page*, which tries to catch up by moving nodes from the contribution list to the current page. This procedure will succeed in its goal of emptying the contribution list, unless a page break is discovered, i.e., unless the current page has grown to the point where the optimum next page break has been determined. In the latter case, the nodes after the optimum break will go back onto the contribution list, and control will effectively pass to the user’s output routine.

We make *type(page.head) = glue_node*, so that an initial glue node on the current page will not be considered a valid breakpoint.

```

⟨ Initialize the special list heads and constant nodes 966 ⟩ +≡
  type(page.head) ← glue_node; subtype(page.head) ← normal;
  { SyncTeX watch point: box(page.head) size  $\dot{=}$  glue_node size }

```

1203* When the user’s output routine finishes, it has constructed a vlist in internal vertical mode, and TeX will do the following:

```

⟨ Resume the page builder after an output routine has come to an end 1203* ⟩ ≡
  begin while (state = token_list) ∧ (loc = null) ∧ (token_type = backed_up) do end_token_list;
    { output-ending brace may have been backed-up }
  if (state ≠ token_list) ∨ (loc ≠ null) ∨ (token_type ≠ output_text) then
    ⟨ Recover from an unbalanced output routine 1204 ⟩;
    end_graf; unsave; output_active ← false; insert_penalties ← 0;
    end_token_list; { conserve stack space in case more outputs are triggered }
    ⟨ Ensure that box 255 is empty after output 1205 ⟩;
    if tail ≠ head then { current list goes after heldover insertions }
      begin link(page_tail) ← link(head); page_tail ← tail;
      end;
    if link(page_head) ≠ null then { and both go before heldover contributions }
      begin if link(contrib_head) = null then contrib_tail ← page_tail;
      link(page_tail) ← link(contrib_head); link(contrib_head) ← link(page_head); link(page_head) ← null;
      page_tail ← page_head;
      end;
    flush_node_list(page_disc); page_disc ← null; pop_nest; build_page;
  end

```

This code is used in section 1278*.

1211* We leave the *space_factor* unchanged if *sf_code(cur_chr)* = 0; otherwise we set it equal to *sf_code(cur_chr)*, except that it should never change from a value less than 1000 to a value exceeding 1000. The most common case is *sf_code(cur_chr)* = 1000, so we want that case to be fast.

The overall structure of the main loop is presented here. Some program labels are inside the individual sections.

```
define adjust_space_factor ≡
  main_s ← sf_code(cur_chr);
  if main_s = 1000 then space_factor ← 1000
  else if main_s < 1000 then
    begin if main_s > 0 then space_factor ← main_s;
    end
    else if space_factor < 1000 then space_factor ← 1000
    else space_factor ← main_s
```

⟨Append character *cur_chr* and the following characters (if any) to the current hlist in the current font;

goto *reswitch* when a non-character has been fetched 1211*) ≡

```
if ((head = tail) ∧ (mode > 0)) then
```

```
  begin if (insert_src_special_auto) then append_src_special;
```

```
  end;
```

```
adjust_space_factor;
```

```
save_tail ← null; main_f ← cur_font; bchar ← font_bchar[main_f];
```

```
false_bchar ← font_false_bchar[main_f];
```

```
if mode > 0 then
```

```
  if language ≠ clang then fix_language;
```

```
fast_get_avail(lig_stack); font(lig_stack) ← main_f; cur_l ← qi(cur_chr); character(lig_stack) ← cur_l;
```

```
cur_q ← tail; tmp_k1 ← get_auto_kern(main_f, non_char, cur_l);
```

⟨If *tmp_k1* is not null then append that kern 1217);

```
if cancel_boundary then
```

```
  begin cancel_boundary ← false; main_k ← non_address;
```

```
  end
```

```
else main_k ← bchar_label[main_f];
```

```
if main_k = non_address then goto main_loop_move + 2; {no left boundary processing }
```

```
cur_r ← cur_l; cur_l ← non_char; goto main_lig_loop + 1; {begin with cursor after left boundary }
```

main_loop_wrapup: ⟨Make a ligature node, if *ligature_present*; insert a null discretionary, if appropriate 1212);

main_loop_move: ⟨If the cursor is immediately followed by the right boundary, **goto** *reswitch*; if it's followed by an invalid character, **goto** *big_switch*; otherwise move the cursor one step to the right and **goto** *main_lig_loop* 1213*);

main_loop_lookahead: ⟨Look ahead for another character, or leave *lig_stack* empty if there's none there 1215);

main_lig_loop: ⟨If there's a ligature/kern command relevant to *cur_l* and *cur_r*, adjust the text appropriately; exit to *main_loop_wrapup* 1216);

main_loop_move_lig: ⟨Move the cursor past a pseudo-ligature, then **goto** *main_loop_lookahead* or *main_lig_loop* 1214*)

This code is used in section 1207.

1213* \langle If the cursor is immediately followed by the right boundary, **goto** *reswitch*; if it's followed by an invalid character, **goto** *big_switch*; otherwise move the cursor one step to the right and **goto** *main_lig_loop* 1213* $\rangle \equiv$

```

if lig_stack = null then goto reswitch;
cur_q  $\leftarrow$  tail; cur_l  $\leftarrow$  character(lig_stack);
main_loop_move + 1: if  $\neg$ is_char_node(lig_stack) then goto main_loop_move_lig;
main_loop_move + 2: if (qo(effective_char(false, main_f,
    qi(cur_chr))) > font_ec[main_f])  $\vee$  (qo(effective_char(false, main_f, qi(cur_chr))) < font_bc[main_f])
then
    begin char_warning(main_f, cur_chr); free_avail(lig_stack); goto big_switch;
end;
main_i  $\leftarrow$  effective_char_info(main_f, cur_l);
if  $\neg$ char_exists(main_i) then
    begin char_warning(main_f, cur_chr); free_avail(lig_stack); goto big_switch;
end;
link(tail)  $\leftarrow$  lig_stack; tail  $\leftarrow$  lig_stack { main_loop_lookahead is next }

```

This code is used in section 1211*.

1214* Here we are at *main_loop_move_lig*. When we begin this code we have *cur_q* = *tail* and *cur_l* = *character*(*lig_stack*).

\langle Move the cursor past a pseudo-ligature, then **goto** *main_loop_lookahead* or *main_lig_loop* 1214* $\rangle \equiv$

```

main_p  $\leftarrow$  lig_ptr(lig_stack);
if main_p > null then tail_append(main_p); { append a single character }
temp_ptr  $\leftarrow$  lig_stack; lig_stack  $\leftarrow$  link(temp_ptr); free_node(temp_ptr, small_node_size);
    { SyncTEX watch point: proper size! }
main_i  $\leftarrow$  char_info(main_f)(cur_l); ligature_present  $\leftarrow$  true;
if lig_stack = null then
    if main_p > null then goto main_loop_lookahead
    else cur_r  $\leftarrow$  bchar
else cur_r  $\leftarrow$  character(lig_stack);
goto main_lig_loop

```

This code is used in section 1211*.

1227* The ‘*you_cant*’ procedure prints a line saying that the current command is illegal in the current mode; it identifies these things symbolically.

\langle Declare action procedures for use by *main_control* 1221 $\rangle + \equiv$

```

procedure you_cant;
    begin print_err("You can't use `"); print_cmd_chr(cur_cmd, cur_chr); print_in_mode(mode);
end;

```

1263* When the right brace occurs at the end of an `\hbox` or `\vbox` or `\vtop` construction, the *package* routine comes into action. We might also have to finish a paragraph that hasn't ended.

⟨Cases of *handle_right_brace* where a *right_brace* triggers a delayed action 1263*⟩ ≡

```

hbox_group: package(0);
adjusted_hbox_group: begin adjust_tail ← adjust_head; pre_adjust_tail ← pre_adjust_head; package(0);
end;
vbox_group: if (partoken_context > 0) ∧ (mode = hmode) then
  begin back_input; cur_tok ← par_token; back_input; token_type ← inserted;
end
else begin end_graf; package(0);
end;
vtop_group: if (partoken_context > 0) ∧ (mode = hmode) then
  begin back_input; cur_tok ← par_token; back_input; token_type ← inserted;
end
else begin end_graf; package(vtop_code);
end;

```

See also sections 1278*, 1296, 1310, 1311*, 1346*, 1351, and 1364.

This code is used in section 1246.

1269* ⟨Declare action procedures for use by *main_control* 1221⟩ +≡

```

function norm_min(h : integer): small_number;
  begin if h ≤ 0 then norm_min ← 1 else if h ≥ 63 then norm_min ← 63 else norm_min ← h;
end;

procedure new_graf(indented : boolean);
  begin prev_graf ← 0;
  if (mode = vmode) ∨ (head ≠ tail) then tail_append(new_param_glue(par_skip_code));
  push_nest; mode ← hmode; space_factor ← 1000; set_cur_lang; clang ← cur_lang;
  prev_graf ← (norm_min(left_hyphen_min) * '100 + norm_min(right_hyphen_min)) * '200000 + cur_lang;
  if indented then
    begin tail ← new_null_box; link(head) ← tail; width(tail) ← par_indent;
    if (insert_src_special_every_par) then insert_src_special;
    end;
  if every_par ≠ null then begin_token_list(every_par, every_par_text);
  if nest_ptr = 1 then build_page; { put par_skip glue on current page }
end;

```

1278* \langle Cases of *handle_right_brace* where a *right_brace* triggers a delayed action 1263* $\rangle +\equiv$
insert_group: **if** (*partoken_context* > 1) \wedge (*mode* = *hmode*) **then**
 begin *back_input*; *cur_tok* \leftarrow *par_token*; *back_input*; *token_type* \leftarrow *inserted*;
 end
 else begin *end_graf*; *q* \leftarrow *split_top_skip*; *add_glue_ref*(*q*); *d* \leftarrow *split_max_depth*; *f* \leftarrow *floating_penalty*;
 unsave; *save_ptr* \leftarrow *save_ptr* - 2; { now *saved*(0) is the insertion number, or 255 for *vadjust* }
 p \leftarrow *vpack*(*link*(*head*), *natural*); *pop_nest*;
 if *saved*(0) < 255 **then**
 begin *tail_append*(*get_node*(*ins_node_size*)); *type*(*tail*) \leftarrow *ins_node*; *subtype*(*tail*) \leftarrow *qi*(*saved*(0));
 height(*tail*) \leftarrow *height*(*p*) + *depth*(*p*); *ins_ptr*(*tail*) \leftarrow *list_ptr*(*p*); *split_top_ptr*(*tail*) \leftarrow *q*;
 depth(*tail*) \leftarrow *d*; *float_cost*(*tail*) \leftarrow *f*;
 end
 else begin *tail_append*(*get_node*(*small_node_size*)); *type*(*tail*) \leftarrow *adjust_node*;
 adjust_pre(*tail*) \leftarrow *saved*(1); { the *subtype* is used for *adjust_pre* }
 adjust_ptr(*tail*) \leftarrow *list_ptr*(*p*); *delete_glue_ref*(*q*);
 end;
 free_node(*p*, *box_node_size*);
 if *nest_ptr* = 0 **then** *build_page*;
 end;
output_group: **if** (*partoken_context* > 1) \wedge (*mode* = *hmode*) **then**
 begin *back_input*; *cur_tok* \leftarrow *par_token*; *back_input*; *token_type* \leftarrow *inserted*;
 end
 else \langle Resume the page builder after an output routine has come to an end 1203* \rangle ;

1308* We've now covered most of the abuses of `\halign` and `\valign`. Let's take a look at what happens when they are used correctly.

\langle Cases of *main_control* that build boxes and lists 1234 $\rangle +\equiv$
vmode + *halign*: *init_align*;
hmode + *valign*: \langle Cases of *main_control* for *hmode* + *valign* 1704 \rangle
 init_align;
mmode + *halign*: **if** *privileged* **then**
 if *cur_group* = *math_shift_group* **then** *init_align*
 else *off_save*;
vmode + *endv*, *hmode* + *endv*: **if** (*partoken_context* > 1) \wedge (*mode* = *hmode*) **then**
 begin *back_input*; *cur_tok* \leftarrow *par_token*; *back_input*; *token_type* \leftarrow *inserted*;
 end
 else *do_endv*;

1311* \langle Cases of *handle_right_brace* where a *right_brace* triggers a delayed action 1263* $\rangle +\equiv$
no_align_group: **if** (*partoken_context* > 1) \wedge (*mode* = *hmode*) **then**
 begin *back_input*; *cur_tok* \leftarrow *par_token*; *back_input*; *token_type* \leftarrow *inserted*;
 end
 else begin *end_graf*; *unsave*; *align_peek*;
 end;

1313* <Declare action procedures for use by *main_control* 1221> +≡

```
procedure cs_error;
  begin if cur_chr = 10 then
    begin print_err("Extra_"); print_esc("endmubyte");
      help1("I`m_ignoring_this,_since_I_wasn't_doing_a_\mubyte.");
    end
  else begin print_err("Extra_"); print_esc("endcsname");
    help1("I`m_ignoring_this,_since_I_wasn't_doing_a_\csname.");
    end;
  error;
end;
```

```

1317* ⟨Go into ordinary math mode 1317*⟩ ≡
  begin push_math(math_shift_group); eq_word_define(int_base + cur_fam_code, -1);
  if (insert_src_special_every_math) then insert_src_special;
  if every_math ≠ null then begin_token_list(every_math, every_math_text);
  end

```

This code is used in sections 1316 and 1320.

```

1345* ⟨Cases of main_control that build boxes and lists 1234⟩ +≡
mmode + vcenter: begin scan_spec(vcenter_group, false); normal_paragraph; push_nest; mode ← -vmode;
  prev_depth ← pdf_ignored_dimen;
  if (insert_src_special_every_vbox) then insert_src_special;
  if every_vbox ≠ null then begin_token_list(every_vbox, every_vbox_text);
  end;

```

```

1346* ⟨Cases of handle_right_brace where a right_brace triggers a delayed action 1263*⟩ +≡
vcenter_group: if (partoken_context > 0) ∧ (mode = hmode) then
  begin back_input; cur_tok ← par_token; back_input; token_type ← inserted;
  end
else begin end_graf; unsave; save_ptr ← save_ptr - 2; p ← vpack(link(head), saved(1), saved(0));
  pop_nest; tail_append(new_noad); type(tail) ← vcenter_noad; math_type(nucleus(tail)) ← sub_box;
  info(nucleus(tail)) ← p;
  end;

```

1389* If the user says, e.g., ‘\global\global’, the redundancy is silently accepted.

```

⟨Declare action procedures for use by main_control 1221⟩ +≡
⟨Declare subprocedures for prefixed_command 1393*⟩
procedure prefixed_command;
  label done, exit;
  var a: small_number; { accumulated prefix codes so far }
      f: internal_font_number; { identifies a font }
      j: halfword; { index into a \parshape specification }
      k: font_index; { index into font_info }
      p, q, r: pointer; { for temporary short-term use }
      n: integer; { ditto }
      e: boolean; { should a definition be expanded? or was \let not done? }
  begin a ← 0;
  while cur_cmd = prefix do
    begin if ¬odd(a div cur_chr) then a ← a + cur_chr;
    ⟨Get the next non-blank non-relax non-call token 430⟩;
    if cur_cmd ≤ max_non_prefixed_command then ⟨Discard erroneous prefixes and return 1390⟩;
    if tracing_commands > 2 then
      if eTeX_ex then show_cur_cmd_chr;
    end;
    ⟨Discard the prefixes \long and \outer if they are irrelevant 1391⟩;
    ⟨Adjust for the setting of \globaldefs 1392⟩;
    case cur_cmd of
      ⟨Assignments 1395⟩
    othercases confusion("prefix")
    endcases;
  done: ⟨Insert a token saved by \afterassignment, if any 1447⟩;
  exit: end;

```

1393* When a control sequence is to be defined, by \def or \let or something similar, the *get_r_token* routine will substitute a special control sequence for a token that is not redefinable.

```

⟨Declare subprocedures for prefixed_command 1393*⟩ ≡
procedure get_r_token;
  label restart;
  begin restart: repeat get_token;
  until cur_tok ≠ space_token;
  if (cur_cs = 0) ∨ (cur_cs > eqtb_top) ∨ ((cur_cs > frozen_control_sequence) ∧ (cur_cs ≤ eqtb_size)) then
    begin print_err("Missing_control_sequence_inserted");
    help5("Please_don't_say_`\\def{...}`,_say_`\\def\\cs{...}`.")
    ("I've_inserted_an_inaccessible_control_sequence_so_that_your")
    ("definition_will_be_completed_without_mixing_me_up_too_badly.")
    ("You_can_recover_graciously_from_this_error,_if_you're")
    ("careful;_see_exercise_27.2_in_The_TeX_book.");
    if cur_cs = 0 then back_input;
    cur_tok ← cs_token_flag + frozen_protection; ins_error; goto restart;
    end;
  end;

```

See also sections 1407, 1414, 1421, 1422, 1423, 1424, 1425, 1435*, and 1443*.

This code is used in section 1389*.

1397* Both `\let` and `\futurelet` share the command code *let*.

⟨Put each of TeX's primitives into the hash table 244⟩ +≡

```
primitive("let", let, normal);
primitive("futurelet", let, normal + 1);
if enctex-p then
  begin primitive("mubyte", let, normal + 10);
  primitive("noconvert", let, normal + 11);
  end;
```

1398* ⟨Cases of *print_cmd_chr* for symbolic printing of primitives 245⟩ +≡

```
let: if chr_code ≠ normal then
  if chr_code = normal + 10 then print_esc("mubyte")
  else if chr_code = normal + 11 then print_esc("noconvert")
  else print_esc("futurelet")
else print_esc("let");
```


1399* (Assignments 1395) +≡

```

let: if cur_chr = normal + 11 then do_nothing { noconvert primitive }
     else if cur_chr = normal + 10 then { mubyte primitive }
       begin selector ← term_and_log; get_token; mubyte_token ← cur_tok;
       if cur_tok ≤ cs_token_flag then mubyte_token ← cur_tok mod 256;
       mubyte_prefix ← 60; mubyte_relax ← false; mubyte_tablein ← true; mubyte_tableout ← true;
       get_x_token;
       if cur_cmd = spacer then get_x_token;
       if cur_cmd = sub_mark then
         begin mubyte_tableout ← false; get_x_token;
         if cur_cmd = sub_mark then
           begin mubyte_tableout ← true; mubyte_tablein ← false; get_x_token;
           end;
         end
       else if (mubyte_token > cs_token_flag) ∧ (cur_cmd = mac_param) then
         begin mubyte_tableout ← false; scan_int; mubyte_prefix ← cur_val; get_x_token;
         if mubyte_prefix > 50 then mubyte_prefix ← 52;
         if mubyte_prefix ≤ 0 then mubyte_prefix ← 51;
         end
       else if (mubyte_token > cs_token_flag) ∧ (cur_cmd = relax) then
         begin mubyte_tableout ← true; mubyte_tablein ← false; mubyte_relax ← true; get_x_token;
         end;
r ← get_avail; p ← r;
while cur_cs = 0 do
  begin store_new_token(cur_tok); get_x_token;
  end;
if (cur_cmd ≠ end_cs_name) ∨ (cur_chr ≠ 10) then
  begin print_err("Missing_"); print_esc("endmubyte"); print("_inserted");
  help2("The_control_sequence_marked_to_be_read_again_should")
  ("not_appear_in_byte_sequence_between_\mubyte_and_\endmubyte."); back_error;
  end;
p ← link(r);
if (p = null) ∧ mubyte_tablein then
  begin print_err("The_empty_byte_sequence_,"); print_esc("mubyte"); print("_ignored");
  help2("The_byte_sequence_in")
  ("_\mubyte_token>_byte_sequence>\endmubyte_should_not_be_empty."); error;
  end
else begin while p ≠ null do
  begin append_char(info(p) mod 256); p ← link(p);
  end;
flush_list(r);
if (str_start[str_ptr] + 1 = pool_ptr) ∧ (str_pool[pool_ptr - 1] = mubyte_token) then
  begin if mubyte_read[mubyte_token] ≠ null ∧ mubyte_tablein then { clearing data }
    dispose_munode(mubyte_read[mubyte_token]);
  if mubyte_tablein then mubyte_read[mubyte_token] ← null;
  if mubyte_tableout then mubyte_write[mubyte_token] ← 0;
  pool_ptr ← str_start[str_ptr];
  end
else begin if mubyte_tablein then mubyte_update; { updating input side }
  if mubyte_tableout then { updating output side }
    begin if mubyte_token > cs_token_flag then { control sequence }
      begin dispose_mutableout(mubyte_token - cs_token_flag);

```

```

    if (str_start[str_ptr] < pool_ptr) ∨ mubyte_relax then
      begin { store data }
        r ← mubyte_cswrite[(mubyte_stoken − cs_token_flag) mod 128]; p ← get_aval;
        mubyte_cswrite[(mubyte_stoken − cs_token_flag) mod 128] ← p;
        info(p) ← mubyte_stoken − cs_token_flag; link(p) ← get_aval; p ← link(p);
        if mubyte_relax then
          begin info(p) ← 0; pool_ptr ← str_start[str_ptr];
          end
        else info(p) ← slow_make_string;
          link(p) ← r;
          end;
        end
      else begin { single character }
        if str_start[str_ptr] = pool_ptr then mubyte_write[mubyte_stoken] ← 0
        else mubyte_write[mubyte_stoken] ← slow_make_string;
        end;
      end
    else pool_ptr ← str_start[str_ptr];
    end;
  end;
end
else begin { let primitive }
  n ← cur_chr; get_r_token; p ← cur_cs;
  if n = normal then
    begin repeat get_token;
      until cur_cmd ≠ spacer;
      if cur_tok = other_token + "=" then
        begin get_token;
          if cur_cmd = spacer then get_token;
          end;
        end
      else begin get_token; q ← cur_tok; get_token; back_input; cur_tok ← q; back_input;
        { look ahead, then back up }
        end; { note that back_input doesn't affect cur_cmd, cur_chr }
      if cur_cmd ≥ call then add_token_ref(cur_chr)
      else if (cur_cmd = register) ∨ (cur_cmd = toks_register) then
        if (cur_chr < mem_bot) ∨ (cur_chr > lo_mem_stat_max) then add_sa_ref(cur_chr);
        define(p, cur_cmd, cur_chr);
      end;
    end;
  end;
end;

```

1400* A `\chardef` creates a control sequence whose *cmd* is *char-given*; a `\mathchardef` creates a control sequence whose *cmd* is *math-given*; and the corresponding *chr* is the character code or math code. A `\countdef` or `\dimendef` or `\skipdef` or `\muskipdef` creates a control sequence whose *cmd* is *assign-int* or ... or *assign-mu-glue*, and the corresponding *chr* is the *eqtb* location of the internal register in question.

```

define char_def_code = 0 {shorthand_def for \chardef }
define math_char_def_code = 1 {shorthand_def for \mathchardef }
define count_def_code = 2 {shorthand_def for \countdef }
define dimen_def_code = 3 {shorthand_def for \dimendef }
define skip_def_code = 4 {shorthand_def for \skipdef }
define mu_skip_def_code = 5 {shorthand_def for \muskipdef }
define toks_def_code = 6 {shorthand_def for \toksdef }
define char_sub_def_code = 7 {shorthand_def for \charsubdef }

```

⟨Put each of TEX's primitives into the hash table 244⟩ +≡

```

primitive("chardef", shorthand_def, char_def_code);
primitive("mathchardef", shorthand_def, math_char_def_code);
primitive("countdef", shorthand_def, count_def_code);
primitive("dimendef", shorthand_def, dimen_def_code);
primitive("skipdef", shorthand_def, skip_def_code);
primitive("muskipdef", shorthand_def, mu_skip_def_code);
primitive("toksdef", shorthand_def, toks_def_code);
if mltex_p then
  begin primitive("charsubdef", shorthand_def, char_sub_def_code);
  end;

```

1401* ⟨Cases of *print_cmd_chr* for symbolic printing of primitives 245⟩ +≡

```

shorthand_def: case chr_code of
  char_def_code: print_esc("chardef");
  math_char_def_code: print_esc("mathchardef");
  count_def_code: print_esc("countdef");
  dimen_def_code: print_esc("dimendef");
  skip_def_code: print_esc("skipdef");
  mu_skip_def_code: print_esc("muskipdef");
  char_sub_def_code: print_esc("charsubdef");
  othercases print_esc("toksdef")
endcases;
char-given: begin print_esc("char"); print_hex(chr_code);
end;
math-given: begin print_esc("mathchar"); print_hex(chr_code);
end;

```

1402* We temporarily define p to be *relax*, so that an occurrence of p while scanning the definition will simply stop the scanning instead of producing an “undefined control sequence” error or expanding the previous meaning. This allows, for instance, ‘`\chardef\foo=123\foo`’.

(Assignments 1395) +≡

```
shorthand_def: if cur_chr = char_sub_def_code then
  begin scan_char_num; p ← char_sub_code_base + cur_val; scan_optional_equals; scan_char_num;
  n ← cur_val; { accent character in substitution }
  scan_char_num;
  if (tracing_char_sub_def > 0) then
    begin begin_diagnostic; print_nl("New character substitution:");
    print_ASCII(p - char_sub_code_base); print("_="); print_ASCII(n); print_char("_");
    print_ASCII(cur_val); end_diagnostic(false);
    end;
  n ← n * 256 + cur_val; define(p, data, hi(n));
  if (p - char_sub_code_base) < char_sub_def_min then
    word_define(int_base + char_sub_def_min_code, p - char_sub_code_base);
  if (p - char_sub_code_base) > char_sub_def_max then
    word_define(int_base + char_sub_def_max_code, p - char_sub_code_base);
  end
else begin n ← cur_chr; get_r_token; p ← cur_cs; define(p, relax, 256); scan_optional_equals;
  case n of
    char_def_code: begin scan_char_num; define(p, char_given, cur_val);
    end;
    math_char_def_code: begin scan_fifteen_bit_int; define(p, math_given, cur_val);
    end;
  othercases begin scan_register_num;
  if cur_val > 255 then
    begin j ← n - count_def_code; { int_val .. box_val }
    if j > mu_val then j ← tok_val; { int_val .. mu_val or tok_val }
    find_sa_element(j, cur_val, true); add_sa_ref(cur_ptr);
    if j = tok_val then j ← toks_register else j ← register;
    define(p, j, cur_ptr);
    end
  else case n of
    count_def_code: define(p, assign_int, count_base + cur_val);
    dimen_def_code: define(p, assign_dimen, scaled_base + cur_val);
    skip_def_code: define(p, assign_glue, skip_base + cur_val);
    mu_skip_def_code: define(p, assign_mu_glue, mu_skip_base + cur_val);
    toks_def_code: define(p, assign_toks, toks_base + cur_val);
    end; { there are no other cases }
  end
endcases;
end;
```

1408* The various character code tables are changed by the *def_code* commands, and the font families are declared by *def_family*.

⟨Put each of TEX's primitives into the hash table 244⟩ +≡

```
primitive("catcode", def_code, cat_code_base);
if enctex_p then
  begin primitive("xordcode", def_code, xord_code_base);
    primitive("xchrcode", def_code, xchr_code_base); primitive("xprncode", def_code, xprn_code_base);
  end;
primitive("mathcode", def_code, math_code_base); primitive("lccode", def_code, lc_code_base);
primitive("uccode", def_code, uc_code_base); primitive("sfcode", def_code, sf_code_base);
primitive("delcode", def_code, del_code_base); primitive("textfont", def_family, math_font_base);
primitive("scriptfont", def_family, math_font_base + script_size);
primitive("scriptscriptfont", def_family, math_font_base + script_script_size);
```

1409* ⟨Cases of *print_cmd_chr* for symbolic printing of primitives 245⟩ +≡

```
def_code: if chr_code = xord_code_base then print_esc("xordcode")
  else if chr_code = xchr_code_base then print_esc("xchrcode")
    else if chr_code = xprn_code_base then print_esc("xprncode")
      else if chr_code = cat_code_base then print_esc("catcode")
        else if chr_code = math_code_base then print_esc("mathcode")
          else if chr_code = lc_code_base then print_esc("lccode")
            else if chr_code = uc_code_base then print_esc("uccode")
              else if chr_code = sf_code_base then print_esc("sfcode")
                else print_esc("delcode");
```

```
def_family: print_size(chr_code - math_font_base);
```

1410* The different types of code values have different legal ranges; the following program is careful to check each case properly.

⟨Assignments 1395⟩ +≡

```
def_code: begin ⟨Let n be the largest legal code value, based on cur_chr 1411⟩;
  p ← cur_chr; scan_char_num;
  if p = xord_code_base then p ← cur_val
  else if p = xchr_code_base then p ← cur_val + 256
  else if p = xprn_code_base then p ← cur_val + 512
  else p ← p + cur_val;
  scan_optional_equals; scan_int;
  if ((cur_val < 0) ∧ (p < del_code_base)) ∨ (cur_val > n) then
    begin print_err("Invalid_code_"); print_int(cur_val);
      if p < del_code_base then print(")_should_be_in_the_range_0..")
      else print(")_should_be_at_most_");
      print_int(n); help1("I'm_going_to_use_0_instead_of_that_illegal_code_value.");
      error; cur_val ← 0;
    end;
  if p < 256 then xord[p] ← cur_val
  else if p < 512 then xchr[p - 256] ← cur_val
  else if p < 768 then xprn[p - 512] ← cur_val
  else if p < math_code_base then define(p, data, cur_val)
  else if p < del_code_base then define(p, data, hi(cur_val))
  else word_define(p, cur_val);
end;
```

1430* \langle Assignments 1395 \rangle \equiv

```
hyph_data: if cur_chr = 1 then
  begin Init new_patterns; goto done; Tini
  print_err("Patterns can be loaded only by INITEX"); help0; error;
  repeat get_token;
  until cur_cmd = right_brace; { flush the patterns }
  return;
  end
else begin new_hyph_exceptions; goto done;
end;
```

1435* \langle Declare subprocedures for *prefixed_command* 1393* \rangle \equiv

```
procedure new_font(a : small_number);
  label common_ending;
  var u: pointer; { user's font identifier }
  s: scaled; { stated "at" size, or negative of scaled magnification }
  f: internal_font_number; { runs through existing fonts }
  t: str_number; { name for the frozen font identifier }
  old_setting: 0 .. max_selector; { holds selector setting }
  begin if job_name = 0 then open_log_file; { avoid confusing texpout with the font name }
  get_r_token; u  $\leftarrow$  cur_cs;
  if u  $\geq$  hash_base then t  $\leftarrow$  text(u)
  else if u  $\geq$  single_base then
    if u = null_cs then t  $\leftarrow$  "FONT" else t  $\leftarrow$  u - single_base
    else begin old_setting  $\leftarrow$  selector; selector  $\leftarrow$  new_string; print("FONT"); print(u - active_base);
    selector  $\leftarrow$  old_setting; str_room(1); t  $\leftarrow$  make_string;
    end;
    define(u, set_font, null_font); scan_optional_equality; scan_file_name;
   $\langle$  Scan the font size specification 1436  $\rangle$ ;
   $\langle$  If this font has already been loaded, set f to the internal font number and goto common_ending 1438*  $\rangle$ ;
  f  $\leftarrow$  read_font_info(u, cur_name, cur_area, s);
  common_ending: define(u, set_font, f); eqtb[font_id_base + f]  $\leftarrow$  eqtb[u]; font_id_text(f)  $\leftarrow$  t;
  end;
```

1438* When the user gives a new identifier to a font that was previously loaded, the new name becomes the font identifier of record. Font names 'xyz' and 'XYZ' are considered to be different.

\langle If this font has already been loaded, set f to the internal font number and **goto** common_ending 1438* \rangle \equiv

```
for f  $\leftarrow$  font_base + 1 to font_ptr do
  if str_eq_str(font_name[f], cur_name)  $\wedge$  str_eq_str(font_area[f], cur_area) then
    begin if pdf_font_step[f] = 0 then
      begin if s > 0 then
        begin if s = font_size[f] then goto common_ending;
        end
      else if font_size[f] = xn_over_d(font_dsize[f], -s, 1000) then goto common_ending;
      end
    end
```

This code is used in section 1435*.

1443* <Declare subprocedures for *prefixed_command* 1393* > +≡

```

procedure new_interaction;
  begin print_ln; interaction ← cur_chr;
  if interaction = batch_mode then kpse_make_tex_discard_errors ← 1
  else kpse_make_tex_discard_errors ← 0;
  <Initialize the print selector based on interaction 75>;
  if log_opened then selector ← selector + 2;
  end;

```

1449* <Cases of *main_control* that don't depend on *mode* 1388 > +≡

```

any_mode(after_group): begin get_token; save_for_after(cur_tok);
  end;
any_mode(partoken_name): begin get_token;
  if cur_cs > 0 then
    begin par_loc ← cur_cs; par_token ← cur_tok;
    end;
  end;

```

1453* <Declare action procedures for use by *main_control* 1221 > +≡

```

procedure open_or_close_in;
  var c: 0 .. 1; { 1 for \openin, 0 for \closein }
  n: 0 .. 15; { stream number }
  begin c ← cur_chr; scan_four_bit_int; n ← cur_val;
  if read_open[n] ≠ closed then
    begin a_close(read_file[n]); read_open[n] ← closed;
    end;
  if c ≠ 0 then
    begin scan_optional_equals; scan_file_name; pack_cur_name; tex_input_type ← 0;
      { Tell open_input we are \openin. }
    if kpse_in_name_ok(stringcast(name_of_file + 1)) ∧ a_open_in(read_file[n], kpse_tex_format) then
      read_open[n] ← just_open;
    end;
  end;

```

1457* <Declare action procedures for use by *main_control* 1221 > +≡

```

procedure issue_message;
  var old_setting: 0 .. max_selector; { holds selector setting }
  c: 0 .. 1; { identifies \message and \errmessage }
  s: str_number; { the message }
  begin c ← cur_chr; link(garbage) ← scan_toks(false, true); old_setting ← selector;
  selector ← new_string; message_printing ← true; active_noconvert ← true; token_show(def_ref);
  message_printing ← false; active_noconvert ← false; selector ← old_setting; flush_list(def_ref);
  str_room(1); s ← make_string;
  if c = 0 then <Print string s on the terminal 1458* >
  else <Print string s as an error message 1461* >;
  flush_string;
  end;

```

```

1458* ⟨Print string s on the terminal 1458*⟩ ≡
  begin if term_offset + length(s) > max_print_line - 2 then print_ln
  else if (term_offset > 0) ∨ (file_offset > 0) then print_char("␣");
  print(s); update_terminal;
  end

```

This code is used in section 1457*.

```

1461* ⟨Print string s as an error message 1461*⟩ ≡
  begin print_err(""); print(s);
  if err_help ≠ null then use_err_help ← true
  else if long_help_seen then help1("(That␣was␣another␣\errmessage.)")
    else begin if interaction < error_stop_mode then long_help_seen ← true;
      help4("This␣error␣message␣was␣generated␣by␣an␣\errmessage")
      ("command,␣so␣I␣can't␣give␣any␣explicit␣help.")
      ("Pretend␣that␣you're␣Hercule␣Poirot:␣Examine␣all␣clues,")
      ("and␣deduce␣the␣truth␣by␣order␣and␣method.");
    end;
  error; use_err_help ← false;
  end

```

This code is used in section 1457*.

1471* \langle Declare action procedures for use by *main_control* 1221 $\rangle + \equiv$

```

procedure show_whatever;
  label common_ending;
  var p: pointer; { tail of a token list to show }
      t: small_number; { type of conditional being shown }
      m: normal .. or_code; { upper bound on fi_or_else codes }
      l: integer; { line where that conditional began }
      n: integer; { level of \if... \fi nesting }
  begin case cur_chr of
    show_lists_code: begin  $\langle$  Adjust selector based on show_stream 1472*  $\rangle$  begin_diagnostic; show_activities;
      end;
    show_box_code:  $\langle$  Show the current contents of a box 1475*  $\rangle$ ;
    show_code:  $\langle$  Show the current meaning of a token, then goto common_ending 1473*  $\rangle$ ;
       $\langle$  Cases for show_whatever 1678*  $\rangle$ 
    othercases  $\langle$  Show the current value of some parameter or register, then goto common_ending 1476*  $\rangle$ 
    endcases;
     $\langle$  Complete a potentially long \show command 1477  $\rangle$ ;
  common_ending: if selector < no_print then
    begin print_ln;  $\langle$  Initialize the print selector based on interaction 75  $\rangle$ ;
    if log_opened then selector  $\leftarrow$  selector + 2;
    end
  else begin if interaction < error_stop_mode then
    begin help0; decr(error_count);
    end
  else if tracing_online > 0 then
    begin
      help3("This isn't an error message; I'm just showing something.")
      ("Type `I\show...` to show more (e.g., \show\cs,")
      ("\showthe\count10, \showbox255, \showlists).");
    end
  else begin
    help5("This isn't an error message; I'm just showing something.")
    ("Type `I\show...` to show more (e.g., \show\cs,")
    ("\showthe\count10, \showbox255, \showlists).")
    ("And type `I\tracingonline=1\show...` to show boxes and")
    ("lists on your terminal as well as in the transcript file.");
    end;
  error;
  end;
end;

```

1472* \langle Adjust *selector* based on *show_stream* 1472* $\rangle \equiv$

```

if (show_stream  $\geq$  0)  $\wedge$  (show_stream < no_print)  $\wedge$  write_open[show_stream] then
  selector  $\leftarrow$  show_stream;

```

This code is used in sections 1471*, 1473*, 1475*, 1476*, 1678*, and 1692*.

```

1473* ⟨Show the current meaning of a token, then goto common_ending 1473*⟩ ≡
  begin get_token; ⟨Adjust selector based on show_stream 1472*⟩
  if interaction = error_stop_mode then wake_up_terminal;
  print_nl(">␣");
  if cur_cs ≠ 0 then
    begin sprint_cs(cur_cs); print_char("=");
    end;
  print_meaning; goto common_ending;
end

```

This code is used in section 1471*.

```

1475* ⟨Show the current contents of a box 1475*⟩ ≡
  begin scan_register_num; fetch_box(p); ⟨Adjust selector based on show_stream 1472*⟩begin_diagnostic;
  print_nl(">␣\box"); print_int(cur_val); print_char("=");
  if p = null then print("void") else show_box(p);
end

```

This code is used in section 1471*.

```

1476* ⟨Show the current value of some parameter or register, then goto common_ending 1476*⟩ ≡
  begin p ← the_toks; ⟨Adjust selector based on show_stream 1472*⟩
  if interaction = error_stop_mode then wake_up_terminal;
  print_nl(">␣"); token_show(temp_head); flush_list(link(temp_head)); goto common_ending;
end

```

This code is used in section 1471*.

```

1480* <Initialize table entries (done by INITEX only) 182> +≡
  if ini_version then format_ident ← "␣(INITEX)";

1481* <Declare action procedures for use by main_control 1221> +≡
  init procedure store_fmt_file;
  label found1, found2, done1, done2;
  var j, k, l: integer; { all-purpose indices }
     p, q: pointer; { all-purpose pointers }
     x: integer; { something to dump }
     format_engine: ↑text_char;
  begin <If dumping is not allowed, abort 1483>;
  <Create the format_ident, open the format file, and inform the user that dumping has begun 1509>;
  <Dump constants for consistency check 1486*>;
  <Dump MLTeX-specific data 1894*>;
  <Dump encTeX-specific data 1903*>;
  <Dump the string pool 1488*>;
  <Dump the dynamic memory 1490*>;
  <Dump the table of equivalents 1492>;
  <Dump the font information 1499*>;
  <Dump the hyphenation tables 1503*>;
  <Dump pdftex data 1505>;
  <Dump a couple more things and the closing check word 1507>;
  <Close the format file 1510>;
  end;
tini

```

1482* Corresponding to the procedure that dumps a format file, we have a function that reads one in. The function returns *false* if the dumped format is incompatible with the present TeX table sizes, etc.

```

define bad_fmt = 6666 { go here if the format file is unacceptable }
define too_small(#) ≡
    begin wake_up_terminal; wterm_ln(`---!_Must_increase_the_`,#); goto bad_fmt;
    end
⟨ Declare the function called open_fmt_file 550* ⟩
function load_fmt_file: boolean;
    label bad_fmt, exit;
    var j, k: integer; { all-purpose indices }
        p, q: pointer; { all-purpose pointers }
        x: integer; { something undumped }
        format_engine: ↑text_char; dummy_xord: ASCII_code; dummy_xchr: text_char;
        dummy_xprn: ASCII_code;
    begin ⟨ Undump constants for consistency check 1487* ⟩;
    ⟨ Undump MLTeX-specific data 1895* ⟩;
    ⟨ Undump encTeX-specific data 1904* ⟩;
    ⟨ Undump the string pool 1489* ⟩;
    ⟨ Undump the dynamic memory 1491* ⟩;
    ⟨ Undump the table of equivalents 1493* ⟩;
    ⟨ Undump the font information 1500* ⟩;
    ⟨ Undump the hyphenation tables 1504* ⟩;
    ⟨ Undump pdftex data 1506 ⟩;
    ⟨ Undump a couple more things and the closing check word 1508* ⟩;
    prev_depth ← pdf_ignored_dimen; load_fmt_file ← true; return; { it worked! }
bad_fmt: wake_up_terminal; wterm_ln(`(Fatal_format_file_error;_I_`m_stymied)`);
    load_fmt_file ← false;
exit: end;

```

1484* Format files consist of *memory_word* items, and we use the following macros to dump words of different types:

```

⟨ Global variables 13 ⟩ +≡
fmt_file: word_file; { for input or output of format information }

```

1485* The inverse macros are slightly more complicated, since we need to check the range of the values we are reading in. We say ‘*undump(a)(b)(x)*’ to read an integer value x that is supposed to be in the range $a \leq x \leq b$. System error messages should be suppressed when undumping.

```

define undump_end_end(#)  $\equiv$  #  $\leftarrow$  x; end
define undump_end(#)  $\equiv$  (x > #) then goto bad_fmt else undump_end_end
define undump(#)  $\equiv$ 
  begin undump_int(x);
  if (x < #)  $\vee$  undump_end
define format_debug_end(#)  $\equiv$  write_ln(stderr, ‘_=_’, #);
  end ;
define format_debug(#)  $\equiv$ 
  if debug_format_file then
    begin write(stderr, ‘fmtdebug:’, #); format_debug_end
define undump_size_end_end(#)  $\equiv$  too_small(#) else format_debug(#)(x); undump_end_end
define undump_size_end(#)  $\equiv$ 
  if x > # then undump_size_end_end
define undump_size(#)  $\equiv$ 
  begin undump_int(x);
  if x < # then goto bad_fmt;
  undump_size_end

```

1486* The next few sections of the program should make it clear how we use the dump/undump macros.

```

< Dump constants for consistency check 1486*  $\equiv$ 
  dump_int("57325458); { Web2C TeX's magic constant: "W2TX" }
  { Align engine to 4 bytes with one or more trailing NUL }
  x  $\leftarrow$  strlen(engine_name); format_engine  $\leftarrow$  xmalloc_array(text_char, x + 4);
  strcpy(stringcast(format_engine), engine_name);
  for k  $\leftarrow$  x to x + 3 do format_engine[k]  $\leftarrow$  0;
  x  $\leftarrow$  x + 4 - (x mod 4); dump_int(x); dump_things(format_engine[0], x); libc_free(format_engine);
  dump_int(@$);
  < Dump xord, xchr, and xprn 1875* >;
  dump_int(max_halfword);
  dump_int(hash_high); < Dump the  $\epsilon$ -TeX state 1655 >
  dump_int(mem_bot);
  dump_int(mem_top);
  dump_int(eqb_size);
  dump_int(hash_prime);
  dump_int(hyph_prime)

```

This code is used in section 1481*.

1487* Sections of a WEB program that are “commented out” still contribute strings to the string pool; therefore INITEX and T_EX will have the same strings. (And it is, of course, a good thing that they do.)

```

⟨Undump constants for consistency check 1487*⟩ ≡ Init libc_free(font_info); libc_free(str_pool);
libc_free(str_start); libc_free(yhash); libc_free(zeqtb); libc_free(yzmem); Tini undump_int(x);
format_debug(ˆformat_magic_numberˆ)(x);
if x ≠ "57325458 then goto bad_fmt; { not a format file }
undump_int(x); format_debug(ˆengine_name_sizeˆ)(x);
if (x < 0) ∨ (x > 256) then goto bad_fmt; { corrupted format file }
format_engine ← xmalloc_array(text_char, x); undump_things(format_engine[0], x);
format_engine[x - 1] ← 0; { force string termination, just in case }
if stcmp(engine_name, stringcast(format_engine)) then
  begin wake_up_terminal;
  wterm.ln(ˆ---!ˆ, stringcast(name_of_file + 1), ˆwas_written_byˆ, format_engine);
  libc_free(format_engine); goto bad_fmt;
  end;
libc_free(format_engine); undump_int(x); format_debug(ˆstring_pool_checksumˆ)(x);
if x ≠ 0$ then
  begin { check that strings are the same }
  wake_up_terminal; wterm.ln(ˆ---!ˆ, stringcast(name_of_file + 1),
  ˆmade_by_different_executable_version, strings_are_differentˆ); goto bad_fmt;
  end;
⟨Undump xord, xchr, and xprn 1876*⟩;
undump_int(x);
if x ≠ max_halfword then goto bad_fmt; { check max_halfword }
undump_int(hash_high);
if (hash_high < 0) ∨ (hash_high > sup_hash_extra) then goto bad_fmt;
if hash_extra < hash_high then hash_extra ← hash_high;
eqtb_top ← eqtb_size + hash_extra;
if hash_extra = 0 then hash_top ← undefined_control_sequence
else hash_top ← eqtb_top;
yhash ← xmalloc_array(two_halves, 1 + hash_top - hash_offset); hash ← yhash - hash_offset;
next(hash_base) ← 0; text(hash_base) ← 0;
for x ← hash_base + 1 to hash_top do hash[x] ← hash[hash_base];
zeqtb ← xmalloc_array(memory_word, eqtb_top + 1); eqtb ← zeqtb;
eq_type(undefined_control_sequence) ← undefined_cs; equiv(undefined_control_sequence) ← null;
eq_level(undefined_control_sequence) ← level_zero;
for x ← eqtb_size + 1 to eqtb_top do eqtb[x] ← eqtb[undefined_control_sequence];
⟨Undump the ε-TEX state 1656⟩
undump_int(x); format_debug(ˆmem_botˆ)(x);
if x ≠ mem_bot then goto bad_fmt;
undump_int(mem_top); format_debug(ˆmem_topˆ)(mem_top);
if mem_bot + 1100 > mem_top then goto bad_fmt;
head ← contrib_head; tail ← contrib_head; page.tail ← page.head; { page initialization }
mem_min ← mem_bot - extra_mem_bot; mem_max ← mem_top + extra_mem_top;
yzmem ← xmalloc_array(memory_word, mem_max - mem_min + 1); zmem ← yzmem - mem_min;
  { this pointer arithmetic fails with some compilers }
mem ← zmem; undump_int(x);
if x ≠ eqtb_size then goto bad_fmt;
undump_int(x);
if x ≠ hash_prime then goto bad_fmt;
undump_int(x);
if x ≠ hyph_prime then goto bad_fmt

```

This code is used in section 1482*.

```
1488* define dump_four_ASCII  $\equiv w.b0 \leftarrow qi(so(str\_pool[k])); w.b1 \leftarrow qi(so(str\_pool[k + 1]));$   

 $w.b2 \leftarrow qi(so(str\_pool[k + 2])); w.b3 \leftarrow qi(so(str\_pool[k + 3])); dump\_qqqq(w)$ 
```

```
(Dump the string pool 1488*)  $\equiv$   

dump_int(pool_ptr); dump_int(str_ptr); dump_things(str_start[0], str_ptr + 1);  

dump_things(str_pool[0], pool_ptr); print_ln; print_int(str_ptr); print("_strings_of_total_length");  

print_int(pool_ptr)
```

This code is used in section 1481*.

```
1489* define undump_four_ASCII  $\equiv undump\_qqqq(w); str\_pool[k] \leftarrow si(qo(w.b0));$   

 $str\_pool[k + 1] \leftarrow si(qo(w.b1)); str\_pool[k + 2] \leftarrow si(qo(w.b2)); str\_pool[k + 3] \leftarrow si(qo(w.b3))$ 
```

```
(Undump the string pool 1489*)  $\equiv$   

undump_size(0)(sup_pool_size - pool_free)('string_pool_size')(pool_ptr);  

if pool_size < pool_ptr + pool_free then pool_size  $\leftarrow$  pool_ptr + pool_free;  

undump_size(0)(sup_max_strings - strings_free)('sup_strings')(str_ptr);  

if max_strings < str_ptr + strings_free then max_strings  $\leftarrow$  str_ptr + strings_free;  

str_start  $\leftarrow$  xmalloc_array(pool_pointer, max_strings);  

undump_checked_things(0, pool_ptr, str_start[0], str_ptr + 1);  

str_pool  $\leftarrow$  xmalloc_array(packed_ASCII_code, pool_size); undump_things(str_pool[0], pool_ptr);  

init_str_ptr  $\leftarrow$  str_ptr; init_pool_ptr  $\leftarrow$  pool_ptr
```

This code is used in section 1482*.

1490* By sorting the list of available spaces in the variable-size portion of *mem*, we are usually able to get by without having to dump very much of the dynamic memory.

We recompute *var_used* and *dyn_used*, so that INITEX dumps valid information even when it has not been gathering statistics.

```
(Dump the dynamic memory 1490*)  $\equiv$   

sort_avail; var_used  $\leftarrow$  0; dump_int(lo_mem_max); dump_int(rover);  

if eTeX_ex then  

  for k  $\leftarrow$  int_val to tok_val do dump_int(sa_root[k]);  

p  $\leftarrow$  mem_bot; q  $\leftarrow$  rover; x  $\leftarrow$  0;  

repeat dump_things(mem[p], q + 2 - p); x  $\leftarrow$  x + q + 2 - p; var_used  $\leftarrow$  var_used + q - p;  

  p  $\leftarrow$  q + node_size(q); q  $\leftarrow$  rlink(q);  

until q = rover;  

var_used  $\leftarrow$  var_used + lo_mem_max - p; dyn_used  $\leftarrow$  mem_end + 1 - hi_mem_min;  

dump_things(mem[p], lo_mem_max + 1 - p); x  $\leftarrow$  x + lo_mem_max + 1 - p; dump_int(hi_mem_min);  

dump_int(avail); dump_things(mem[hi_mem_min], mem_end + 1 - hi_mem_min);  

x  $\leftarrow$  x + mem_end + 1 - hi_mem_min; p  $\leftarrow$  avail;  

while p  $\neq$  null do  

  begin decr(dyn_used); p  $\leftarrow$  link(p);  

  end;  

dump_int(var_used); dump_int(dyn_used); print_ln; print_int(x);  

print("_memory_locations_dumped;_current_usage_is"); print_int(var_used); print_char("&");  

print_int(dyn_used)
```

This code is used in section 1481*.

```

1491* ⟨Undump the dynamic memory 1491*⟩ ≡
  undump(lo_mem_stat_max + 1000)(hi_mem_stat_min - 1)(lo_mem_max);
  undump(lo_mem_stat_max + 1)(lo_mem_max)(rover);
  if eTeX_ex then
    for k ← int_val to tok_val do undump(null)(lo_mem_max)(sa_root[k]);
  p ← mem_bot; q ← rover;
  repeat undump_things(mem[p], q + 2 - p); { If the format file is messed up, that addition to p might
    cause it to become garbage. Report from Gregory James DUCK to Karl, 14 Sep 2023. Also
    changed in METAFONT. Fix from DRF, who explains: we test before doing the addition to avoid
    assuming silent wrap-around overflow, and also to catch cases where node_size was, say, bogusly
    the equivalent of -1 and thus p + node_size would still look valid. }
    if (node_size(q) > lo_mem_max - q) ∨ (rlink(q) > lo_mem_max) ∨ ((q ≥ rlink(q)) ∧ (rlink(q) ≠ rover))
      then goto bad_fmt;
    p ← q + node_size(q); q ← rlink(q);
  until q = rover;
  undump_things(mem[p], lo_mem_max + 1 - p);
  if mem_min < mem_bot - 2 then { make more low memory available }
    begin p ← llink(rover); q ← mem_min + 1; link(mem_min) ← null; info(mem_min) ← null;
      { we don't use the bottom word }
    rlink(p) ← q; llink(rover) ← q;
    rlink(q) ← rover; llink(q) ← p; link(q) ← empty_flag; node_size(q) ← mem_bot - q;
  end;
  undump(lo_mem_max + 1)(hi_mem_stat_min)(hi_mem_min); undump(null)(mem_top)(avail);
  mem_end ← mem_top; undump_things(mem[hi_mem_min], mem_end + 1 - hi_mem_min);
  undump_int(var_used); undump_int(dyn_used)

```

This code is used in section 1482*.

```

1493* ⟨Undump the table of equivalents 1493*⟩ ≡
  ⟨Undump regions 1 to 6 of eqtb 1496*⟩;
  undump_int(par_loc); par_token ← cs_token_flag + par_loc;
  undump(hash_base)(hash_top)(write_loc);
  ⟨Undump the hash table 1498*⟩

```

This code is used in section 1482*.

1494* The table of equivalents usually contains repeated information, so we dump it in compressed form: The sequence of $n + 2$ values (n, x_1, \dots, x_n, m) in the format file represents $n + m$ consecutive entries of *eqtb*, with m extra copies of x_n , namely $(x_1, \dots, x_n, x_n, \dots, x_n)$.

```

⟨Dump regions 1 to 4 of eqtb 1494*⟩ ≡
  k ← active_base;
  repeat j ← k;
    while j < int_base - 1 do
      begin if (equiv(j) = equiv(j + 1)) ∧ (eq_type(j) = eq_type(j + 1)) ∧ (eq_level(j) = eq_level(j + 1))
        then goto found1;
        incr(j);
      end;
      l ← int_base; goto done1; {j = int_base - 1}
    found1: incr(j); l ← j;
    while j < int_base - 1 do
      begin if (equiv(j) ≠ equiv(j + 1)) ∨ (eq_type(j) ≠ eq_type(j + 1)) ∨ (eq_level(j) ≠ eq_level(j + 1))
        then goto done1;
        incr(j);
      end;
    done1: dump_int(l - k); dump_things(eqtb[k], l - k); k ← j + 1; dump_int(k - l);
  until k = int_base

```

This code is used in section 1492.

```

1495* ⟨Dump regions 5 and 6 of eqtb 1495*⟩ ≡
  repeat j ← k;
    while j < eqtb_size do
      begin if eqtb[j].int = eqtb[j + 1].int then goto found2;
        incr(j);
      end;
      l ← eqtb_size + 1; goto done2; {j = eqtb_size}
    found2: incr(j); l ← j;
    while j < eqtb_size do
      begin if eqtb[j].int ≠ eqtb[j + 1].int then goto done2;
        incr(j);
      end;
    done2: dump_int(l - k); dump_things(eqtb[k], l - k); k ← j + 1; dump_int(k - l);
  until k > eqtb_size;
  if hash_high > 0 then dump_things(eqtb[eqtb_size + 1], hash_high); {dump hash_extra part}

```

This code is used in section 1492.

```

1496* ⟨Undump regions 1 to 6 of eqtb 1496*⟩ ≡
  k ← active_base;
  repeat undump_int(x);
    if (x < 1) ∨ (k + x > eqtb_size + 1) then goto bad_fmt;
    undump_things(eqtb[k], x); k ← k + x; undump_int(x);
    if (x < 0) ∨ (k + x > eqtb_size + 1) then goto bad_fmt;
    for j ← k to k + x - 1 do eqtb[j] ← eqtb[k - 1];
    k ← k + x;
  until k > eqtb_size;
  if hash_high > 0 then undump_things(eqtb[eqtb_size + 1], hash_high); {undump hash_extra part}

```

This code is used in section 1493*.

1497* A different scheme is used to compress the hash table, since its lower region is usually sparse. When $text(p) \neq 0$ for $p \leq hash_used$, we output two words, p and $hash[p]$. The hash table is, of course, densely packed for $p \geq hash_used$, so the remaining entries are output in a block.

```

⟨Dump the hash table 1497*⟩ ≡
  for p ← 0 to prim_size do dump_hh(prim[p]);
  dump_int(hash_used); cs_count ← frozen_control_sequence - 1 - hash_used + hash_high;
  for p ← hash_base to hash_used do
    if text(p) ≠ 0 then
      begin dump_int(p); dump_hh(hash[p]); incr(cs_count);
      end;
  dump_things(hash[hash_used + 1], undefined_control_sequence - 1 - hash_used);
  if hash_high > 0 then dump_things(hash[eqtb_size + 1], hash_high);
  dump_int(cs_count);
  print_ln; print_int(cs_count); print("multiletter_control_sequences")

```

This code is used in section 1492.

```

1498* ⟨Undump the hash table 1498*⟩ ≡
  for p ← 0 to prim_size do undump_hh(prim[p]);
  undump(hash_base)(frozen_control_sequence)(hash_used); p ← hash_base - 1;
  repeat undump(p + 1)(hash_used)(p); undump_hh(hash[p]);
  until p = hash_used;
  undump_things(hash[hash_used + 1], undefined_control_sequence - 1 - hash_used);
  if debug_format_file then
    begin print_csnames(hash_base, undefined_control_sequence - 1);
    end;
  if hash_high > 0 then
    begin undump_things(hash[eqtb_size + 1], hash_high);
    if debug_format_file then
      begin print_csnames(eqtb_size + 1, hash_high - (eqtb_size + 1));
      end;
    end;
  undump_int(cs_count)

```

This code is used in section 1493*.

```

1499* ⟨Dump the font information 1499*⟩ ≡
  dump_int(fmем_ptr); dump_things(font_info[0], fmем_ptr); dump_int(font_ptr);
  ⟨Dump the array info for internal font number k 1501*⟩;
  print_ln; print_int(fmем_ptr - 7); print("words_of_font_info_for");
  print_int(font_ptr - font_base);
  if font_ptr ≠ font_base + 1 then print("preloaded_fonts")
  else print("preloaded_font")

```

This code is used in section 1481*.

```

1500* ⟨Undump the font information 1500*⟩ ≡
  undump_size(7)(sup_font_mem_size)(font_mem_size)(fmем_ptr);
  if fmем_ptr > font_mem_size then font_mem_size ← fmем_ptr;
  font_info ← xmalloc_array(fmemory_word, font_mem_size); undump_things(font_info[0], fmем_ptr);
  undump_size(font_base)(font_base + max_font_max)(font_max)(font_ptr);
  { This undumps all of the font info, despite the name. }
  ⟨Undump the array info for internal font number k 1502*⟩;

```

This code is used in section 1482*.

```

1501* ⟨Dump the array info for internal font number k 1501*⟩ ≡
begin dump_things(font_check[null_font], font_ptr + 1 - null_font);
dump_things(font_size[null_font], font_ptr + 1 - null_font);
dump_things(font_dsize[null_font], font_ptr + 1 - null_font);
dump_things(font_params[null_font], font_ptr + 1 - null_font);
dump_things(hyphen_char[null_font], font_ptr + 1 - null_font);
dump_things(skew_char[null_font], font_ptr + 1 - null_font);
dump_things(font_name[null_font], font_ptr + 1 - null_font);
dump_things(font_area[null_font], font_ptr + 1 - null_font);
dump_things(font_bc[null_font], font_ptr + 1 - null_font);
dump_things(font_ec[null_font], font_ptr + 1 - null_font);
dump_things(char_base[null_font], font_ptr + 1 - null_font);
dump_things(width_base[null_font], font_ptr + 1 - null_font);
dump_things(height_base[null_font], font_ptr + 1 - null_font);
dump_things(depth_base[null_font], font_ptr + 1 - null_font);
dump_things(italic_base[null_font], font_ptr + 1 - null_font);
dump_things(lig_kern_base[null_font], font_ptr + 1 - null_font);
dump_things(kern_base[null_font], font_ptr + 1 - null_font);
dump_things(exten_base[null_font], font_ptr + 1 - null_font);
dump_things(param_base[null_font], font_ptr + 1 - null_font);
dump_things(font_glue[null_font], font_ptr + 1 - null_font);
dump_things(bchar_label[null_font], font_ptr + 1 - null_font);
dump_things(font_bchar[null_font], font_ptr + 1 - null_font);
dump_things(font_false_bchar[null_font], font_ptr + 1 - null_font);
for k ← null_font to font_ptr do
  begin print_nl("\font"); print_esc(font_id_text(k)); print_char("=");
  print_file_name(font_name[k], font_area[k], "");
  if font_size[k] ≠ font_dsize[k] then
    begin print("␣at␣"); print_scaled(font_size[k]); print("pt");
    end;
  end;
end

```

This code is used in section 1499*.

1502* This module should now be named ‘Undump all the font arrays’.

(Undump the array info for internal font number k 1502*) \equiv

```

begin { Allocate the font arrays }
font_check  $\leftarrow$  xmalloc_array(four_quarters, font_max); font_size  $\leftarrow$  xmalloc_array(scaled, font_max);
font_dsize  $\leftarrow$  xmalloc_array(scaled, font_max); font_params  $\leftarrow$  xmalloc_array(font_index, font_max);
font_name  $\leftarrow$  xmalloc_array(str_number, font_max); font_area  $\leftarrow$  xmalloc_array(str_number, font_max);
font_bc  $\leftarrow$  xmalloc_array(eight_bits, font_max); font_ec  $\leftarrow$  xmalloc_array(eight_bits, font_max);
font_glue  $\leftarrow$  xmalloc_array(halfword, font_max); hyphen_char  $\leftarrow$  xmalloc_array(integer, font_max);
skew_char  $\leftarrow$  xmalloc_array(integer, font_max); bchar_label  $\leftarrow$  xmalloc_array(font_index, font_max);
font_bchar  $\leftarrow$  xmalloc_array(nine_bits, font_max); font_false_bchar  $\leftarrow$  xmalloc_array(nine_bits, font_max);
char_base  $\leftarrow$  xmalloc_array(integer, font_max); width_base  $\leftarrow$  xmalloc_array(integer, font_max);
height_base  $\leftarrow$  xmalloc_array(integer, font_max); depth_base  $\leftarrow$  xmalloc_array(integer, font_max);
italic_base  $\leftarrow$  xmalloc_array(integer, font_max); lig_kern_base  $\leftarrow$  xmalloc_array(integer, font_max);
kern_base  $\leftarrow$  xmalloc_array(integer, font_max); exten_base  $\leftarrow$  xmalloc_array(integer, font_max);
param_base  $\leftarrow$  xmalloc_array(integer, font_max);
pdf_char_used  $\leftarrow$  xmalloc_array(char_used_array, font_max);
pdf_font_size  $\leftarrow$  xmalloc_array(scaled, font_max); pdf_font_num  $\leftarrow$  xmalloc_array(integer, font_max);
pdf_font_map  $\leftarrow$  xmalloc_array(fm_entry_ptr, font_max);
pdf_font_type  $\leftarrow$  xmalloc_array(eight_bits, font_max);
pdf_font_attr  $\leftarrow$  xmalloc_array(str_number, font_max);
pdf_font_blink  $\leftarrow$  xmalloc_array(internal_font_number, font_max);
pdf_font_elinek  $\leftarrow$  xmalloc_array(internal_font_number, font_max);
pdf_font_has_space_char  $\leftarrow$  xmalloc_array(internal_font_number, font_max);
pdf_font_stretch  $\leftarrow$  xmalloc_array(integer, font_max);
pdf_font_shrink  $\leftarrow$  xmalloc_array(integer, font_max); pdf_font_step  $\leftarrow$  xmalloc_array(integer, font_max);
pdf_font_expand_ratio  $\leftarrow$  xmalloc_array(integer, font_max);
pdf_font_auto_expand  $\leftarrow$  xmalloc_array(boolean, font_max);
pdf_font_lp_base  $\leftarrow$  xmalloc_array(integer, font_max);
pdf_font_rp_base  $\leftarrow$  xmalloc_array(integer, font_max);
pdf_font_ef_base  $\leftarrow$  xmalloc_array(integer, font_max);
pdf_font_kn_bs_base  $\leftarrow$  xmalloc_array(integer, font_max);
pdf_font_st_bs_base  $\leftarrow$  xmalloc_array(integer, font_max);
pdf_font_sh_bs_base  $\leftarrow$  xmalloc_array(integer, font_max);
pdf_font_kn_bc_base  $\leftarrow$  xmalloc_array(integer, font_max);
pdf_font_kn_ac_base  $\leftarrow$  xmalloc_array(integer, font_max);
vf_packet_base  $\leftarrow$  xmalloc_array(integer, font_max);
vf_default_font  $\leftarrow$  xmalloc_array(internal_font_number, font_max);
vf_local_font_num  $\leftarrow$  xmalloc_array(internal_font_number, font_max);
vf_e_fnts  $\leftarrow$  xmalloc_array(integer, font_max);
vf_i_fnts  $\leftarrow$  xmalloc_array(internal_font_number, font_max);
pdf_font_nobuiltin_tounicode  $\leftarrow$  xmalloc_array(boolean, font_max);
for font_k  $\leftarrow$  font_base to font_max do
  begin for k  $\leftarrow$  0 to 31 do pdf_char_used[font_k, k]  $\leftarrow$  0;
  pdf_font_size[font_k]  $\leftarrow$  0; pdf_font_num[font_k]  $\leftarrow$  0; pdf_font_map[font_k]  $\leftarrow$  0;
  pdf_font_type[font_k]  $\leftarrow$  new_font_type; pdf_font_attr[font_k]  $\leftarrow$  ""; pdf_font_blink[font_k]  $\leftarrow$  null_font;
  pdf_font_elinek[font_k]  $\leftarrow$  null_font; pdf_font_has_space_char[font_k]  $\leftarrow$  false;
  pdf_font_stretch[font_k]  $\leftarrow$  null_font; pdf_font_shrink[font_k]  $\leftarrow$  null_font; pdf_font_step[font_k]  $\leftarrow$  0;
  pdf_font_expand_ratio[font_k]  $\leftarrow$  0; pdf_font_auto_expand[font_k]  $\leftarrow$  false; pdf_font_lp_base[font_k]  $\leftarrow$  0;
  pdf_font_rp_base[font_k]  $\leftarrow$  0; pdf_font_ef_base[font_k]  $\leftarrow$  0; pdf_font_kn_bs_base[font_k]  $\leftarrow$  0;
  pdf_font_st_bs_base[font_k]  $\leftarrow$  0; pdf_font_sh_bs_base[font_k]  $\leftarrow$  0; pdf_font_kn_bc_base[font_k]  $\leftarrow$  0;
  pdf_font_kn_ac_base[font_k]  $\leftarrow$  0; pdf_font_nobuiltin_tounicode[font_k]  $\leftarrow$  false;
  end;
end;

```

```

make_pdftex_banner; undump_things(font_check[null_font], font_ptr + 1 - null_font);
undump_things(font_size[null_font], font_ptr + 1 - null_font);
undump_things(font_dsize[null_font], font_ptr + 1 - null_font);
undump_checked_things(min_halfword, max_halfword, font_params[null_font], font_ptr + 1 - null_font);
undump_things(hyphen_char[null_font], font_ptr + 1 - null_font);
undump_things(skew_char[null_font], font_ptr + 1 - null_font);
undump_upper_check_things(str_ptr, font_name[null_font], font_ptr + 1 - null_font);
undump_upper_check_things(str_ptr, font_area[null_font], font_ptr + 1 - null_font); { There's no point in
checking these values against the range [0, 255], since the data type is unsigned char, and all values
of that type are in that range by definition. }
undump_things(font_bc[null_font], font_ptr + 1 - null_font);
undump_things(font_ec[null_font], font_ptr + 1 - null_font);
undump_things(char_base[null_font], font_ptr + 1 - null_font);
undump_things(width_base[null_font], font_ptr + 1 - null_font);
undump_things(height_base[null_font], font_ptr + 1 - null_font);
undump_things(depth_base[null_font], font_ptr + 1 - null_font);
undump_things(italic_base[null_font], font_ptr + 1 - null_font);
undump_things(lig_kern_base[null_font], font_ptr + 1 - null_font);
undump_things(kern_base[null_font], font_ptr + 1 - null_font);
undump_things(exten_base[null_font], font_ptr + 1 - null_font);
undump_things(param_base[null_font], font_ptr + 1 - null_font);
undump_checked_things(min_halfword, lo_mem_max, font_glue[null_font], font_ptr + 1 - null_font);
undump_checked_things(0, fmem_ptr - 1, bchar_label[null_font], font_ptr + 1 - null_font);
undump_checked_things(min_quarterword, non_char, font_bchar[null_font], font_ptr + 1 - null_font);
undump_checked_things(min_quarterword, non_char, font_false_bchar[null_font], font_ptr + 1 - null_font);
end

```

This code is used in section 1500*.

```

1503* ⟨Dump the hyphenation tables 1503*⟩ ≡
  dump_int(hyph_count);
  if hyph_next ≤ hyph_prime then hyph_next ← hyph_size;
  dump_int(hyph_next); { minimum value of hyphen_size needed }
  for k ← 0 to hyph_size do
    if hyph_word[k] ≠ 0 then
      begin dump_int(k + 65536 * hyph_link[k]);
        { assumes number of hyphen exceptions does not exceed 65535 }
        dump_int(hyph_word[k]); dump_int(hyph_list[k]);
      end;
  print_ln; print_int(hyph_count);
  if hyph_count ≠ 1 then print("␣hyphenation␣exceptions")
  else print("␣hyphenation␣exception");
  if trie_not_ready then init_trie;
  dump_int(trie_max); dump_int(hyph_start); dump_things(trie_trl[0], trie_max + 1);
  dump_things(trie_tro[0], trie_max + 1); dump_things(trie_trc[0], trie_max + 1); dump_int(trie_op_ptr);
  dump_things(hyf_distance[1], trie_op_ptr); dump_things(hyf_num[1], trie_op_ptr);
  dump_things(hyf_next[1], trie_op_ptr); print_nl("Hyphenation␣trie␣of␣length␣"); print_int(trie_max);
  print("␣has␣"); print_int(trie_op_ptr);
  if trie_op_ptr ≠ 1 then print("␣ops")
  else print("␣op");
  print("␣out␣of␣"); print_int(trie_op_size);
  for k ← 255 downto 0 do
    if trie_used[k] > min_quarterword then
      begin print_nl("␣␣"); print_int(qo(trie_used[k])); print("␣for␣language␣"); print_int(k);
        dump_int(k); dump_int(qo(trie_used[k]));
      end
  end

```

This code is used in section 1481*.

1504* Only “nonempty” parts of *op_start* need to be restored.

```

⟨Undump the hyphenation tables 1504*⟩ ≡
  undump_size(0)(hyph_size)(`hyph_size`)(hyph_count);
  undump_size(hyph_prime)(hyph_size)(`hyph_size`)(hyph_next); j ← 0;
  for k ← 1 to hyph_count do
    begin undump_int(j);
    if j < 0 then goto bad_fmt;
    if j > 65535 then
      begin hyph_next ← j div 65536; j ← j - hyph_next * 65536;
      end
    else hyph_next ← 0;
    if (j ≥ hyph_size) ∨ (hyph_next > hyph_size) then goto bad_fmt;
    hyph_link[j] ← hyph_next; undump(0)(str_ptr)(hyph_word[j]);
    undump(min_halfword)(max_halfword)(hyph_list[j]);
    end; { j is now the largest occupied location in hyph_word }
  incr(j);
  if j < hyph_prime then j ← hyph_prime;
  hyph_next ← j;
  if hyph_next ≥ hyph_size then hyph_next ← hyph_prime
  else if hyph_next ≥ hyph_prime then incr(hyph_next);
  undump_size(0)(trie_size)(`trie_size`)(j); init trie_max ← j; tini undump(0)(j)(hyph_start);
  { These first three haven't been allocated yet unless we're INITEX; we do that precisely so we don't
  allocate more space than necessary. }
  if ¬trie_trl then trie_trl ← xmalloc_array(trie_pointer, j + 1);
  undump_things(trie_trl[0], j + 1);
  if ¬trie_tro then trie_tro ← xmalloc_array(trie_pointer, j + 1);
  undump_things(trie_tro[0], j + 1);
  if ¬trie_trc then trie_trc ← xmalloc_array(quarterword, j + 1);
  undump_things(trie_trc[0], j + 1);
  undump_size(0)(trie_op_size)(`trie_op_size`)(j); init trie_op_ptr ← j; tini
  { I'm not sure we have such a strict limitation (64) on these values, so let's leave them unchecked. }
  undump_things(hyf_distance[1], j); undump_things(hyf_num[1], j);
  undump_upper_check_things(max_trie_op, hyf_next[1], j);
  init for k ← 0 to 255 do trie_used[k] ← min_quarterword;
  tini
  k ← 256;
  while j > 0 do
    begin undump(0)(k - 1)(k); undump(1)(j)(x); init trie_used[k] ← qi(x); tini
    j ← j - x; op_start[k] ← qo(j);
    end;
  init trie_not_ready ← false tini

```

This code is used in section 1482*.

```

1508* ⟨Undump a couple more things and the closing check word 1508*⟩ ≡
  undump(batch_mode)(error_stop_mode)(interaction);
  if interaction_option ≠ unspecified_mode then interaction ← interaction_option;
  undump(0)(str_ptr)(format_ident); undump_int(x);
  if x ≠ 69069 then goto bad_fmt

```

This code is used in section 1482*.

1513* Now this is really it: TeX starts and ends here.

The initial test involving *ready_already* should be deleted if the Pascal runtime system is smart enough to detect such a “mistake.”

```

define const_chk(#) ≡
    begin if # < inf@&# then # ← inf@&#
    else if # > sup@&# then # ← sup@&#
    end { setup_bound_var stuff duplicated in mf.ch. }
define setup_bound_var(#) ≡ bound_default ← #; setup_bound_var_end
define setup_bound_var_end(#) ≡ bound_name ← #; setup_bound_var_end_end
define setup_bound_var_end_end(#) ≡ setup_bound_variable(addressof(#), bound_name, bound_default)
procedure main_body;
begin { start_here }
    { Bounds that may be set from the configuration file. We want the user to be able to specify the names
      with underscores, but TANGLE removes underscores, so we're stuck giving the names twice, once as a
      string, once as the identifier. How ugly. }
    setup_bound_var(0)(`mem_bot`)(mem_bot); setup_bound_var(250000)(`main_memory`)(main_memory);
    { memory_words for mem in INITEX }
    setup_bound_var(0)(`extra_mem_top`)(extra_mem_top); { increase high mem in VIRTEX }
    setup_bound_var(0)(`extra_mem_bot`)(extra_mem_bot); { increase low mem in VIRTEX }
    setup_bound_var(200000)(`pool_size`)(pool_size);
    setup_bound_var(75000)(`string_vacancies`)(string_vacancies);
    setup_bound_var(5000)(`pool_free`)(pool_free); { min pool avail after fmt }
    setup_bound_var(15000)(`max_strings`)(max_strings);
    setup_bound_var(100)(`strings_free`)(strings_free);
    setup_bound_var(100000)(`font_mem_size`)(font_mem_size);
    setup_bound_var(500)(`font_max`)(font_max); setup_bound_var(20000)(`trie_size`)(trie_size);
    { if ssup.trie_size increases, recompile }
    setup_bound_var(659)(`hyph_size`)(hyph_size); setup_bound_var(3000)(`buf_size`)(buf_size);
    setup_bound_var(50)(`nest_size`)(nest_size); setup_bound_var(15)(`max_in_open`)(max_in_open);
    setup_bound_var(60)(`param_size`)(param_size); setup_bound_var(4000)(`save_size`)(save_size);
    setup_bound_var(300)(`stack_size`)(stack_size);
    setup_bound_var(16384)(`dvi_buf_size`)(dvi_buf_size); setup_bound_var(79)(`error_line`)(error_line);
    setup_bound_var(50)(`half_error_line`)(half_error_line);
    setup_bound_var(79)(`max_print_line`)(max_print_line);
    setup_bound_var(0)(`hash_extra`)(hash_extra);
    setup_bound_var(10000)(`expand_depth`)(expand_depth); setup_bound_var(72)(`pk_dpi`)(pk_dpi);
    const_chk(mem_bot); const_chk(main_memory); Init extra_mem_top ← 0; extra_mem_bot ← 0; Tini
if extra_mem_bot > sup_main_memory then extra_mem_bot ← sup_main_memory;
if extra_mem_top > sup_main_memory then extra_mem_top ← sup_main_memory;
    { mem_top is an index, main_memory a size }
    mem_top ← mem_bot + main_memory - 1; mem_min ← mem_bot; mem_max ← mem_top;
    { Check other constants against their sup and inf. }
    const_chk(trie_size); const_chk(hyph_size); const_chk(buf_size); const_chk(nest_size);
    const_chk(max_in_open); const_chk(param_size); const_chk(save_size); const_chk(stack_size);
    const_chk(dvi_buf_size); const_chk(pool_size); const_chk(string_vacancies); const_chk(pool_free);
    const_chk(max_strings); const_chk(strings_free); const_chk(font_mem_size); const_chk(font_max);
    const_chk(hash_extra); const_chk(obj_tab_size); const_chk(pdf_mem_size); const_chk(dest_names_size);
    const_chk(pk_dpi);
if error_line > ssup_error_line then error_line ← ssup_error_line; { array memory allocation }
    buffer ← xmalloc_array(ASCII_code, buf_size); nest ← xmalloc_array(list_state_record, nest_size);
    save_stack ← xmalloc_array(memory_word, save_size);
    input_stack ← xmalloc_array(in_state_record, stack_size);

```



```

input_file ← xmalloc_array(alpha_file, max_in_open); line_stack ← xmalloc_array(integer, max_in_open);
eof_seen ← xmalloc_array(boolean, max_in_open); grp_stack ← xmalloc_array(save_pointer, max_in_open);
if_stack ← xmalloc_array(pointer, max_in_open);
source_filename_stack ← xmalloc_array(str_number, max_in_open);
full_source_filename_stack ← xmalloc_array(str_number, max_in_open);
param_stack ← xmalloc_array(halfword, param_size); dvi_buf ← xmalloc_array(eight_bits, dvi_buf_size);
hyph_word ← xmalloc_array(str_number, hyph_size); hyph_list ← xmalloc_array(halfword, hyph_size);
hyph_link ← xmalloc_array(hyph_pointer, hyph_size);
obj_tab ← xmalloc_array(obj_entry, inf_obj_tab_size); { will grow dynamically }
pdf_mem ← xmalloc_array(integer, inf_pdf_mem_size); { will grow dynamically }
dest_names ← xmalloc_array(dest_name_entry, inf_dest_names_size); { will grow dynamically }
pdf_op_buf ← xmalloc_array(eight_bits, pdf_op_buf_size);
pdf_os_buf ← xmalloc_array(eight_bits, inf_pdf_os_buf_size); { will grow dynamically }
pdf_os_objnum ← xmalloc_array(integer, pdf_os_max_objs);
pdf_os_objoff ← xmalloc_array(integer, pdf_os_max_objs); Init
    yzmem ← xmalloc_array(memory_word, mem_top - mem_bot + 1); zmem ← yzmem - mem_bot;
    { Some compilers require mem_bot = 0 }
eqtb_top ← eqtb_size + hash_extra;
if hash_extra = 0 then hash_top ← undefined_control_sequence
else hash_top ← eqtb_top;
yhash ← xmalloc_array(two_halves, 1 + hash_top - hash_offset); hash ← yhash - hash_offset;
    { Some compilers require hash_offset = 0 }
next(hash_base) ← 0; text(hash_base) ← 0;
for hash_used ← hash_base + 1 to hash_top do hash[hash_used] ← hash[hash_base];
zeqtb ← xmalloc_array(memory_word, eqtb_top); eqtb ← zeqtb;
str_start ← xmalloc_array(pool_pointer, max_strings);
str_pool ← xmalloc_array(packed_ASCII_code, pool_size);
font_info ← xmalloc_array(fm_memory_word, font_mem_size); Tinihistory ← fatal_error_stop;
    { in case we quit during initialization }
t_open_out; { open the terminal for output }
if ready_already = 314159 then goto start_of_TEX;
⟨ Check the “constant” values for consistency 14 ⟩
if bad > 0 then
    begin wterm_ln(ˆUuch---my_internal_constants_have_been_clobbered!ˆ, ˆ---caseˆ, bad : 1);
    goto final_end;
    end;
initialize; { set global variables to their starting values }
Init if ¬get_strings_started then goto final_end;
init_prim; { call primitive for each primitive }
init_str_ptr ← str_ptr; init_pool_ptr ← pool_ptr; fix_date_and_time;
Tini
ready_already ← 314159;
start_of_TEX: ⟨ Initialize the output routines 55 ⟩;
⟨ Get the first line of input and prepare to start 1518* ⟩;
history ← spotless; { ready to go! }
⟨ Initialize syntex primitive 1914* ⟩ main_control; { come to life }
final_cleanup; { prepare for death }
close_files_and_terminate;
final_end: do_final_end;
end { main_body }
;

```

1514* Here we do whatever is needed to complete TeX's job gracefully on the local operating system. The code here might come into play after a fatal error; it must therefore consist entirely of "safe" operations that cannot produce error messages. For example, it would be a mistake to call *str_room* or *make_string* at this time, because a call on *overflow* might lead to an infinite loop. (Actually there's one way to get error messages, via *prepare_mag*; but that can't cause infinite recursion.)

If *final_cleanup* is bypassed, this program doesn't bother to close the input files that may still be open.

⟨Last-minute procedures 1514*⟩ ≡

```

procedure close_files_and_terminate;
label done, done1;
var a, b, c, i, j, k, l: integer; { all-purpose index }
    is_root: boolean; { pdf_last_pages is root of Pages tree? }
    is_names: boolean; { flag for name tree output: is it Names or Kids? }
    root, outlines, threads, names_tree, dests: integer; xref_offset_width, names_head, names_tail: integer;
begin ⟨Finish the extensions 1627⟩;
new_line_char ← -1;
stat if tracing_stats > 0 then ⟨Output statistics about this job 1515*⟩; tats
wake_up_terminal;
if ¬fixed_pdfoutput_set then fix_pdfoutput;
if fixed_pdfoutput > 0 then
  begin if history = fatal_error_stop then
    begin remove_pdffile; synctex_abort(log_opened);
    print_err("=>Fatal error occurred, no output PDF file produced!")
    end
  else begin ⟨Finish the PDF file 794⟩;
    if log_opened then
      begin wlog_cr; wlog_ln("PDF statistics:"); wlog_ln(``, obj_ptr : 1,
        `PDF objects out of`, obj_tab_size : 1, `(max.`, sup_obj_tab_size : 1, `)`);
      if pdf_os_cntr > 0 then
        begin wlog(``, ((pdf_os_cntr - 1) * pdf_os_max_objs + pdf_os_objidx + 1) : 1,
          `compressed objects within`, pdf_os_cntr : 1, `object stream`);
        if pdf_os_cntr > 1 then wlog(`s`);
        wlog_cr;
        end;
      wlog_ln(``, pdf_dest_names_ptr : 1, `named destinations out of`, dest_names_size : 1,
        `max.`, sup_dest_names_size : 1, `)`);
      wlog_ln(``, pdf_mem_ptr : 1, `words of extra memory for PDF output out of`,
        pdf_mem_size : 1, `(max.`, sup_pdf_mem_size : 1, `)`);
      end;
    end;
  end
else begin ⟨Finish the DVI file 670*⟩;
  end;
⟨Close SyncTeX file and write status 1922*⟩;
if log_opened then
  begin wlog_cr; a_close(log_file); selector ← selector - 2;
  if selector = term_only then
    begin print_nl("Transcript written on"); print_file_name(0, log_name, 0); print_char(".");
    end;
  end;
print_ln;
if (edit_name_start ≠ 0) ∧ (interaction > batch_mode) then
  call_edit(str_pool, edit_name_start, edit_name_length, edit_line);

```

end;

See also sections 1516*, 1517, and 1519*.

This code is used in section 1511.

1515* The present section goes directly to the log file instead of using *print* commands, because there's no need for these strings to take up *str_pool* memory when a non-**stat** version of TeX is being used.

⟨Output statistics about this job 1515*⟩ ≡

```
if log_opened then
  begin wlog_ln(`␣`); wlog_ln(`Here␣is␣how␣much␣of␣TeX`'s␣memory`, `␣you␣used: `);
  wlog(`␣`, str_ptr - init_str_ptr : 1, `␣string`);
  if str_ptr ≠ init_str_ptr + 1 then wlog(`s`);
  wlog_ln(`␣out␣of␣`, max_strings - init_str_ptr : 1);
  wlog_ln(`␣`, pool_ptr - init_pool_ptr : 1, `␣string␣characters␣out␣of␣`, pool_size - init_pool_ptr : 1);
  wlog_ln(`␣`, lo_mem_max - mem_min + mem_end - hi_mem_min + 2 : 1,
    `␣words␣of␣memory␣out␣of␣`, mem_end + 1 - mem_min : 1);
  wlog_ln(`␣`, cs_count : 1, `␣multiletter␣control␣sequences␣out␣of␣`, hash_size : 1, `+`,
    hash_extra : 1);
  wlog(`␣`, fmem_ptr : 1, `␣words␣of␣font␣info␣for␣`, font_ptr - font_base : 1, `␣font`);
  if font_ptr ≠ font_base + 1 then wlog(`s`);
  wlog_ln(`␣out␣of␣`, font_mem_size : 1, `␣for␣`, font_max - font_base : 1);
  wlog(`␣`, hyph_count : 1, `␣hyphenation␣exception`);
  if hyph_count ≠ 1 then wlog(`s`);
  wlog_ln(`␣out␣of␣`, hyph_size : 1);
  wlog_ln(`␣`, max_in_stack : 1, `i`, `max_nest_stack` : 1, `n`, `max_param_stack` : 1, `p`,
    max_buf_stack + 1 : 1, `b`, `max_save_stack` + 6 : 1, `s␣stack␣positions␣out␣of␣`,
    stack_size : 1, `i`, `nest_size` : 1, `n`, `param_size` : 1, `p`, buf_size : 1, `b`, save_size : 1, `s`);
  end
```

This code is used in section 1514*.

1516* We get to the *final_cleanup* routine when `\end` or `\dump` has been scanned and *its_all_over*.

⟨Last-minute procedures 1514*⟩ +≡

```

procedure final_cleanup;
  label exit;
  var c: small_number; { 0 for \end, 1 for \dump }
  begin c ← cur_chr;
  if c ≠ 1 then new_line_char ← -1;
  if job_name = 0 then open_log_file;
  while input_ptr > 0 do
    if state = token_list then end_token_list else end_file_reading;
  while open_parens > 0 do
    begin print("␣"); decr(open_parens);
    end;
  if cur_level > level_one then
    begin print_nl("("); print_esc("end␣occurred␣"); print("inside␣a␣group␣at␣level␣");
    print_int(cur_level - level_one); print_char(")");
    if eTeX_ex then show_save_groups;
    end;
  while cond_ptr ≠ null do
    begin print_nl("("); print_esc("end␣occurred␣"); print("when␣"); print_cmd_chr(if_test, cur_if);
    if if_line ≠ 0 then
      begin print("␣on␣line␣"); print_int(if_line);
      end;
    print("␣was␣incomplete"); if_line ← if_line_field(cond_ptr); cur_if ← subtype(cond_ptr);
    temp_ptr ← cond_ptr; cond_ptr ← link(cond_ptr); free_node(temp_ptr, if_node_size);
    end;
  if history ≠ spotless then
    if ((history = warning_issued) ∨ (interaction < error_stop_mode)) then
      if selector = term_and_log then
        begin selector ← term_only;
        print_nl("(see␣the␣transcript␣file␣for␣additional␣information)");
        selector ← term_and_log;
        end;
  if c = 1 then
    begin Init for c ← top_mark_code to split_bot_mark_code do
      if cur_mark[c] ≠ null then delete_token_ref(cur_mark[c]);
    if sa_mark ≠ null then
      if do_marks(destroy_marks, 0, sa_mark) then sa_mark ← null;
    for c ← last_box_code to vsplit_code do flush_node_list(disc_ptr[c]);
    if last_glue ≠ max_halfword then delete_glue_ref(last_glue);
    store_fmt_file; return; Tini
    print_nl("(\dump␣is␣performed␣only␣by␣INITEX)"); return;
    end;
  exit: end;

```

1518* When we begin the following code, TeX's tables may still contain garbage; the strings might not even be present. Thus we must proceed cautiously to get bootstrapped in.

But when we finish this part of the program, TeX is ready to call on the *main_control* routine to do its work.

```

⟨Get the first line of input and prepare to start 1518*⟩ ≡
begin ⟨Initialize the input routines 353*⟩;
⟨Enable ε-TeX, if requested 1649*⟩
if (format_ident = 0) ∨ (buffer[loc] = "&") ∨ dump_line then
  begin if format_ident ≠ 0 then initialize; { erase preloaded format }
  if ¬open_fmt_file then goto final_end;
  if ¬load_fmt_file then
    begin w_close(fmt_file); goto final_end;
    end;
  w_close(fmt_file); eqtb ← zeqtb;
  while (loc < limit) ∧ (buffer[loc] = " ") do incr(loc);
  end;
if (pdf_output_option ≠ 0) then pdf_output ← pdf_output_value;
if (pdf_draftmode_option ≠ 0) then pdf_draftmode ← pdf_draftmode_value;
pdf_init_map_file(`pdftex.map`);
if eTeX_ex then wterm.ln(`entering_extended_mode`);
if end_line_char_inactive then decr(limit)
else buffer[limit] ← end_line_char;
if mltx_enabled_p then
  begin wterm.ln(`MLTeX_v2.2_enabled`);
  end;
if encTeX_enabled_p then
  begin wterm(encTeX_banner); wterm.ln(`,reencoding_enabled.`);
  if translate_filename then
    begin wterm.ln(`\xordcode,\xchrcode,\xprncode_overridden_by_TCX`);
    end;
  end;
fix_date_and_time;
init if trie_not_ready then
  begin { initex without format loaded }
  trie_trl ← xmalloc_array(trie_pointer, trie_size); trie_tro ← xmalloc_array(trie_pointer, trie_size);
  trie_trc ← xmalloc_array(quarterword, trie_size); trie_c ← xmalloc_array(packed_ASCII_code, trie_size);
  trie_o ← xmalloc_array(trie_opcode, trie_size); trie_l ← xmalloc_array(trie_pointer, trie_size);
  trie_r ← xmalloc_array(trie_pointer, trie_size); trie_hash ← xmalloc_array(trie_pointer, trie_size);
  trie_taken ← xmalloc_array(boolean, trie_size); trie_root ← 0; trie_c[0] ← si(0); trie_ptr ← 0;
  hyph_root ← 0; hyph_start ← 0; { Allocate and initialize font arrays }
  font_check ← xmalloc_array(four_quarters, font_max); font_size ← xmalloc_array(scaled, font_max);
  font_dsize ← xmalloc_array(scaled, font_max); font_params ← xmalloc_array(font_index, font_max);
  font_name ← xmalloc_array(str_number, font_max);
  font_area ← xmalloc_array(str_number, font_max); font_bc ← xmalloc_array(eight_bits, font_max);
  font_ec ← xmalloc_array(eight_bits, font_max); font_glue ← xmalloc_array(halfword, font_max);
  hyphen_char ← xmalloc_array(integer, font_max); skew_char ← xmalloc_array(integer, font_max);
  bchar_label ← xmalloc_array(font_index, font_max); font_bchar ← xmalloc_array(nine_bits, font_max);
  font_false_bchar ← xmalloc_array(nine_bits, font_max); char_base ← xmalloc_array(integer, font_max);
  width_base ← xmalloc_array(integer, font_max); height_base ← xmalloc_array(integer, font_max);
  depth_base ← xmalloc_array(integer, font_max); italic_base ← xmalloc_array(integer, font_max);
  lig_kern_base ← xmalloc_array(integer, font_max); kern_base ← xmalloc_array(integer, font_max);
  exten_base ← xmalloc_array(integer, font_max); param_base ← xmalloc_array(integer, font_max);

```

```

pdf_char_used ← xmalloc_array(char_used_array, font_max);
pdf_font_size ← xmalloc_array(scaled, font_max); pdf_font_num ← xmalloc_array(integer, font_max);
pdf_font_map ← xmalloc_array(fm_entry_ptr, font_max);
pdf_font_type ← xmalloc_array(eight_bits, font_max);
pdf_font_attr ← xmalloc_array(str_number, font_max);
pdf_font_blink ← xmalloc_array(internal_font_number, font_max);
pdf_font_elinek ← xmalloc_array(internal_font_number, font_max);
pdf_font_has_space_char ← xmalloc_array(internal_font_number, font_max);
pdf_font_stretch ← xmalloc_array(integer, font_max);
pdf_font_shrink ← xmalloc_array(integer, font_max); pdf_font_step ← xmalloc_array(integer, font_max);
pdf_font_expand_ratio ← xmalloc_array(integer, font_max);
pdf_font_auto_expand ← xmalloc_array(boolean, font_max);
pdf_font_lp_base ← xmalloc_array(integer, font_max);
pdf_font_rp_base ← xmalloc_array(integer, font_max);
pdf_font_ef_base ← xmalloc_array(integer, font_max);
pdf_font_kn_bs_base ← xmalloc_array(integer, font_max);
pdf_font_st_bs_base ← xmalloc_array(integer, font_max);
pdf_font_sh_bs_base ← xmalloc_array(integer, font_max);
pdf_font_kn_bc_base ← xmalloc_array(integer, font_max);
pdf_font_kn_ac_base ← xmalloc_array(integer, font_max);
vf_packet_base ← xmalloc_array(integer, font_max);
vf_default_font ← xmalloc_array(internal_font_number, font_max);
vf_local_font_num ← xmalloc_array(internal_font_number, font_max);
vf_e_fnts ← xmalloc_array(integer, font_max);
vf_i_fnts ← xmalloc_array(internal_font_number, font_max);
pdf_font_nobuiltin_tounicode ← xmalloc_array(boolean, font_max);
for font_k ← font_base to font_max do
  begin for k ← 0 to 31 do pdf_char_used[font_k, k] ← 0;
  pdf_font_size[font_k] ← 0; pdf_font_num[font_k] ← 0; pdf_font_map[font_k] ← 0;
  pdf_font_type[font_k] ← new_font_type; pdf_font_attr[font_k] ← "";
  pdf_font_blink[font_k] ← null_font; pdf_font_elinek[font_k] ← null_font;
  pdf_font_has_space_char[font_k] ← false; pdf_font_stretch[font_k] ← null_font;
  pdf_font_shrink[font_k] ← null_font; pdf_font_step[font_k] ← 0; pdf_font_expand_ratio[font_k] ← 0;
  pdf_font_auto_expand[font_k] ← false; pdf_font_lp_base[font_k] ← 0; pdf_font_rp_base[font_k] ← 0;
  pdf_font_ef_base[font_k] ← 0; pdf_font_kn_bs_base[font_k] ← 0; pdf_font_st_bs_base[font_k] ← 0;
  pdf_font_sh_bs_base[font_k] ← 0; pdf_font_kn_bc_base[font_k] ← 0; pdf_font_kn_ac_base[font_k] ← 0;
  pdf_font_nobuiltin_tounicode[font_k] ← false;
  end;
font_ptr ← null_font; fmem_ptr ← 7; make_pdftex_banner; font_name[null_font] ← "nullfont";
font_area[null_font] ← ""; hyphen_char[null_font] ← "-"; skew_char[null_font] ← -1;
bchar_label[null_font] ← non_address; font_bchar[null_font] ← non_char;
font_false_bchar[null_font] ← non_char; font_bc[null_font] ← 1; font_ec[null_font] ← 0;
font_size[null_font] ← 0; font_dsize[null_font] ← 0; char_base[null_font] ← 0;
width_base[null_font] ← 0; height_base[null_font] ← 0; depth_base[null_font] ← 0;
italic_base[null_font] ← 0; lig_kern_base[null_font] ← 0; kern_base[null_font] ← 0;
exten_base[null_font] ← 0; font_glue[null_font] ← null; font_params[null_font] ← 7;
param_base[null_font] ← -1;
for font_k ← 0 to 6 do font_info[font_k].sc ← 0;
end;
tini
font_used ← xmalloc_array(boolean, font_max);
for font_k ← font_base to font_max do font_used[font_k] ← false;

```

```
random_seed ← (microseconds * 1000) + (epochseconds mod 1000000);  
init_randoms(random_seed);  
⟨ Compute the magic offset 941 ⟩;  
⟨ Initialize the print selector based on interaction 75 ⟩;  
if (loc < limit) ∧ (cat_code(buffer[loc]) ≠ escape) then start_input; { \input assumed }  
end
```

This code is used in section 1513*.

1519* Debugging. Once TeX is working, you should be able to diagnose most errors with the `\show` commands and other diagnostic features. But for the initial stages of debugging, and for the revelation of really deep mysteries, you can compile TeX with a few more aids, including the Pascal runtime checks and its debugger. An additional routine called *debug_help* will also come into play when you type ‘D’ after an error message; *debug_help* also occurs just before a fatal error causes TeX to succumb.

The interface to *debug_help* is primitive, but it is good enough when used with a Pascal debugger that allows you to set breakpoints and to read variables and change their values. After getting the prompt ‘debug #’, you type either a negative number (this exits *debug_help*), or zero (this goes to a location where you can set a breakpoint, thereby entering into dialog with the Pascal debugger), or a positive number *m* followed by an argument *n*. The meaning of *m* and *n* will be clear from the program below. (If *m* = 13, there is an additional argument, *l*.)

```

define breakpoint = 888 { place where a breakpoint is desirable }
⟨Last-minute procedures 1514*⟩ +≡
debug procedure debug_help; { routine to display various things }
label breakpoint, exit;
var k, l, m, n: integer;
begin clear_terminal;
loop
  begin wake_up_terminal; print_nl("debug_#_(-1_to_exit):"); update_terminal; read(term_in, m);
  if m < 0 then return
  else if m = 0 then dump_core { do something to cause a core dump }
    else begin read(term_in, n);
      case m of
        ⟨Numbered cases for debug_help 1520*⟩
      othercases print("?")
      endcases;
    end;
  end;
exit: end;
gubed

```


1520* \langle Numbered cases for *debug_help* 1520* $\rangle \equiv$

- 1: *print_word(mem[n]);* { display *mem[n]* in all forms }
- 2: *print_int(info(n));*
- 3: *print_int(link(n));*
- 4: *print_word(eqtb[n]);*
- 5: **begin** *print_scaled(font_info[n].sc); print_char("_");*
print_int(font_info[n].qqqq.b0); print_char(":");
print_int(font_info[n].qqqq.b1); print_char(":");
print_int(font_info[n].qqqq.b2); print_char(":");
print_int(font_info[n].qqqq.b3);
end;
- 6: *print_word(save_stack[n]);*
- 7: *show_box(n);* { show a box, abbreviated by *show_box_depth* and *show_box_breadth* }
- 8: **begin** *breadth_max* \leftarrow 10000; *depth_threshold* \leftarrow *pool_size* - *pool_ptr* - 10; *show_node_list(n);*
{ show a box in its entirety }
end;
- 9: *show_token_list(n, null, 1000);*
- 10: *slow_print(n);*
- 11: *check_mem(n > 0);* { check wellformedness; print new busy locations if $n > 0$ }
- 12: *search_mem(n);* { look for pointers to n }
- 13: **begin** *read(term_in, l); print_cmd_chr(n, l);*
end;
- 14: **for** $k \leftarrow 0$ **to** n **do** *print(buffer[k]);*
- 15: **begin** *font_in_short_display* \leftarrow *null_font*; *short_display(n);*
end;
- 16: *panicking* \leftarrow \neg *panicking*;

This code is used in section 1519*.

1522* First let's consider the format of `whatsit` nodes that are used to represent the data associated with `\write` and its relatives. Recall that a `whatsit` has *type* = `whatsit_node`, and the *subtype* is supposed to distinguish different kinds of `whatsits`. Each node occupies two or more words; the exact number is immaterial, as long as it is readily determined from the *subtype* or other data.

We shall introduce five *subtype* values here, corresponding to the control sequences `\openout`, `\write`, `\closeout`, `\special`, and `\setlanguage`. The second word of I/O `whatsits` has a *write_stream* field that identifies the write-stream number (0 to 15, or 16 for out-of-range and positive, or 17 for out-of-range and negative). In the case of `\write` and `\special`, there is also a field that points to the reference count of a token list that should be sent. In the case of `\openout`, we need three words and three auxiliary subfields to hold the string numbers for name, area, and extension.

```

define write_node_size = 2 { number of words in a write/whatsit node }
define open_node_size = 3 { number of words in an open/whatsit node }
define open_node = 0 { subtype in whatsits that represent files to \openout }
define write_node = 1 { subtype in whatsits that represent things to \write }
define close_node = 2 { subtype in whatsits that represent streams to \closeout }
define special_node = 3 { subtype in whatsits that represent \special things }
define latespecial_node ≡ 4
      { subtype in whatsits that represent \special things expanded during output }
define language_node = 5 { subtype in whatsits that change the current language }
define what_lang(#) ≡ link(# + 1) { language number, in the range 0 .. 255 }
define what_lhm(#) ≡ type(# + 1) { minimum left fragment, in the range 1 .. 63 }
define what_rhm(#) ≡ subtype(# + 1) { minimum right fragment, in the range 1 .. 63 }
define write_tokens(#) ≡ link(# + 1) { reference count of token list to write }
define write_stream(#) ≡ type(# + 1) { stream number (0 to 17) }
define mubyte_zero ≡ 64
define write_mubyte(#) ≡ subtype(# + 1) { mubyte value + mubyte_zero }
define open_name(#) ≡ link(# + 1) { string number of file name to open }
define open_area(#) ≡ info(# + 2) { string number of file area for open_name }
define open_ext(#) ≡ link(# + 2) { string number of file extension for open_name }

```

1525* Extensions might introduce new command codes; but it's best to use *extension* with a modifier, whenever possible, so that *main_control* stays the same.

```

define immediate_code = 5 { command modifier for \immediate }
define set_language_code = 6 { command modifier for \setlanguage }
define pdftex_first_extension_code = 7
define pdf_literal_node ≡ pdftex_first_extension_code + 0
define pdf_lateliteral_node ≡ pdftex_first_extension_code + 1
define pdf_obj_code ≡ pdftex_first_extension_code + 2
define pdf_refobj_node ≡ pdftex_first_extension_code + 3
define pdf_xform_code ≡ pdftex_first_extension_code + 4
define pdf_refxform_node ≡ pdftex_first_extension_code + 5
define pdf_ximage_code ≡ pdftex_first_extension_code + 6
define pdf_refximage_node ≡ pdftex_first_extension_code + 7
define pdf_annot_node ≡ pdftex_first_extension_code + 8
define pdf_start_link_node ≡ pdftex_first_extension_code + 9
define pdf_end_link_node ≡ pdftex_first_extension_code + 10
define pdf_outline_code ≡ pdftex_first_extension_code + 11
define pdf_dest_node ≡ pdftex_first_extension_code + 12
define pdf_thread_node ≡ pdftex_first_extension_code + 13
define pdf_start_thread_node ≡ pdftex_first_extension_code + 14
define pdf_end_thread_node ≡ pdftex_first_extension_code + 15
define pdf_save_pos_node ≡ pdftex_first_extension_code + 16
define pdf_info_code ≡ pdftex_first_extension_code + 17
define pdf_catalog_code ≡ pdftex_first_extension_code + 18
define pdf_names_code ≡ pdftex_first_extension_code + 19
define pdf_font_attr_code ≡ pdftex_first_extension_code + 20
define pdf_include_chars_code ≡ pdftex_first_extension_code + 21
define pdf_map_file_code ≡ pdftex_first_extension_code + 22
define pdf_map_line_code ≡ pdftex_first_extension_code + 23
define pdf_trailer_code ≡ pdftex_first_extension_code + 24
define pdf_trailer_id_code ≡ pdftex_first_extension_code + 25
define reset_timer_code ≡ pdftex_first_extension_code + 26
define pdf_font_expand_code ≡ pdftex_first_extension_code + 27
define set_random_seed_code ≡ pdftex_first_extension_code + 28
define pdf_snap_ref_point_node ≡ pdftex_first_extension_code + 29
define pdf_snap_node ≡ pdftex_first_extension_code + 30
define pdf_snap_node_comp_node ≡ pdftex_first_extension_code + 31
define pdf_glyph_to_unicode_code ≡ pdftex_first_extension_code + 32
define pdf_colorstack_node ≡ pdftex_first_extension_code + 33
define pdf_setmatrix_node ≡ pdftex_first_extension_code + 34
define pdf_save_node ≡ pdftex_first_extension_code + 35
define pdf_restore_node ≡ pdftex_first_extension_code + 36
define pdf_nobuiltin_tounicode_code ≡ pdftex_first_extension_code + 37
define pdf_interword_space_on_node ≡ pdftex_first_extension_code + 38
define pdf_interword_space_off_node ≡ pdftex_first_extension_code + 39
define pdf_fake_space_node ≡ pdftex_first_extension_code + 40
define pdf_running_link_off_node ≡ pdftex_first_extension_code + 41
define pdf_running_link_on_node ≡ pdftex_first_extension_code + 42
define pdf_space_font_code ≡ pdftex_first_extension_code + 43
define pdftex_last_extension_code ≡ pdftex_first_extension_code + 43

```

(Put each of TeX's primitives into the hash table 244) +=
primitive("openout", extension, open_node);

```

primitive("write", extension, write_node); write_loc ← cur_val;
primitive("closeout", extension, close_node);
primitive("special", extension, special_node);
text(frozen_special) ← "special"; eqtb[frozen_special] ← eqtb[cur_val];
primitive("immediate", extension, immediate_code);
primitive("setlanguage", extension, set_language_code);
primitive("pdfliteral", extension, pdf_literal_node);
primitive("pdfcolorstack", extension, pdf_colorstack_node);
primitive("pdfsetmatrix", extension, pdf_setmatrix_node);
primitive("pdfsave", extension, pdf_save_node);
primitive("pdfrestore", extension, pdf_restore_node);
primitive("pdfobj", extension, pdf_obj_code);
primitive("pdfrefobj", extension, pdf_refobj_node);
primitive("pdfxform", extension, pdf_xform_code);
primitive("pdfrefxform", extension, pdf_refxform_node);
primitive("pdfximage", extension, pdf_ximage_code);
primitive("pdfrefximage", extension, pdf_refximage_node);
primitive("pdfannot", extension, pdf_annot_node);
primitive("pdfstartlink", extension, pdf_start_link_node);
primitive("pdfendlink", extension, pdf_end_link_node);
primitive("pdfoutline", extension, pdf_outline_code);
primitive("pdfdest", extension, pdf_dest_node);
primitive("pdfthread", extension, pdf_thread_node);
primitive("pdfstartthread", extension, pdf_start_thread_node);
primitive("pdfendthread", extension, pdf_end_thread_node);
primitive("pdfsavepos", extension, pdf_save_pos_node);
primitive("pdfsnaprefpoint", extension, pdf_snap_ref_point_node);
primitive("pdfsnapy", extension, pdf_snapy_node);
primitive("pdfsnapycomp", extension, pdf_snapy_comp_node);
primitive("pdfinfo", extension, pdf_info_code);
primitive("pdfcatalog", extension, pdf_catalog_code);
primitive("pdfnames", extension, pdf_names_code);
primitive("pdfincludechars", extension, pdf_include_chars_code);
primitive("pdffontattr", extension, pdf_font_attr_code);
primitive("pdfmapfile", extension, pdf_map_file_code);
primitive("pdfmapline", extension, pdf_map_line_code);
primitive("pdftrailer", extension, pdf_trailer_code);
primitive("pdftrailerid", extension, pdf_trailer_id_code);
primitive("pdfresettimer", extension, reset_timer_code);
primitive("pdfsetrandomseed", extension, set_random_seed_code);
primitive("pdffontexpand", extension, pdf_font_expand_code);
primitive("pdfglyphtounicode", extension, pdf_glyph_to_unicode_code);
primitive("pdfnobuiltintounicode", extension, pdf_nobuiltin_tounicode_code);
primitive("pdfinterwordspaceon", extension, pdf_interword_space_on_node);
primitive("pdfinterwordspaceoff", extension, pdf_interword_space_off_node);
primitive("pdffakespace", extension, pdf_fake_space_node);
primitive("pdfrunninglinkoff", extension, pdf_running_link_off_node);
primitive("pdfrunninglinkon", extension, pdf_running_link_on_node);
primitive("pdfspacefont", extension, pdf_space_font_code);

```

1529* \langle Declare action procedures for use by *main_control* 1221 $\rangle + \equiv$
 \langle Declare procedures needed in *do_extension* 1530 \rangle

procedure *do_extension*;

var *i, j, k*: *integer*; { all-purpose integers }

p, q, r: *pointer*; { all-purpose pointers }

begin case *cur_chr* **of**

open_node: \langle Implement \backslash openout 1532 \rangle ;

write_node: \langle Implement \backslash write 1533 \rangle ;

close_node: \langle Implement \backslash closeout 1534 \rangle ;

special_node: \langle Implement \backslash special 1535* \rangle ;

immediate_code: \langle Implement \backslash immediate 1624 \rangle ;

set_language_code: \langle Implement \backslash setlanguage 1626 \rangle ;

pdf_annot_node: \langle Implement \backslash pdfannot 1559 \rangle ;

pdf_catalog_code: \langle Implement \backslash pdfcatalog 1580 \rangle ;

pdf_dest_node: \langle Implement \backslash pdfdest 1566 \rangle ;

pdf_end_link_node: \langle Implement \backslash pdfendlink 1562 \rangle ;

pdf_end_thread_node: \langle Implement \backslash pdfendthread 1570 \rangle ;

pdf_font_attr_code: \langle Implement \backslash pdffontattr 1590 \rangle ;

pdf_font_expand_code: \langle Implement \backslash pdffontexpand 1536 \rangle ;

pdf_include_chars_code: \langle Implement \backslash pdfincludechars 1589 \rangle ;

pdf_info_code: \langle Implement \backslash pdfinfo 1579 \rangle ;

pdf_literal_node: \langle Implement \backslash pdfliteral 1539 \rangle ;

pdf_colorstack_node: \langle Implement \backslash pdfcolorstack 1540 \rangle ;

pdf_setmatrix_node: \langle Implement \backslash pdfsetmatrix 1541 \rangle ;

pdf_save_node: \langle Implement \backslash pdfsave 1542 \rangle ;

pdf_restore_node: \langle Implement \backslash pdfrestore 1543 \rangle ;

pdf_map_file_code: \langle Implement \backslash pdfmapfile 1591 \rangle ;

pdf_map_line_code: \langle Implement \backslash pdfmapline 1592 \rangle ;

pdf_names_code: \langle Implement \backslash pdfnames 1581 \rangle ;

pdf_obj_code: \langle Implement \backslash pdfobj 1545 \rangle ;

pdf_outline_code: \langle Implement \backslash pdfoutline 1564 \rangle ;

pdf_refobj_node: \langle Implement \backslash pdfrefobj 1547 \rangle ;

pdf_refxform_node: \langle Implement \backslash pdfrefxform 1550 \rangle ;

pdf_refximage_node: \langle Implement \backslash pdfrefximage 1555 \rangle ;

pdf_save_pos_node: \langle Implement \backslash pdfsavepos 1577 \rangle ;

pdf_snap_ref_point_node: \langle Implement \backslash pdfsnaprefpoint 1573 \rangle ;

pdf_snapy_comp_node: \langle Implement \backslash pdfsnapycomp 1576 \rangle ;

pdf_snapy_node: \langle Implement \backslash pdfsnapy 1575 \rangle ;

pdf_start_link_node: \langle Implement \backslash pdfstartlink 1561 \rangle ;

pdf_start_thread_node: \langle Implement \backslash pdfstartthread 1569 \rangle ;

pdf_thread_node: \langle Implement \backslash pdfthread 1568 \rangle ;

pdf_trailer_code: \langle Implement \backslash pdftrailer 1582 \rangle ;

pdf_trailer_id_code: \langle Implement \backslash pdftrailerid 1583 \rangle ;

pdf_xform_code: \langle Implement \backslash pdfxform 1549 \rangle ;

pdf_ximage_code: \langle Implement \backslash pdfximage 1554 \rangle ;

reset_timer_code: \langle Implement \backslash pdfresettimer 1587 \rangle ;

set_random_seed_code: \langle Implement \backslash pdfsetrandomseed 1586 \rangle ;

pdf_glyph_to_unicode_code: \langle Implement \backslash pdfglyphtounicode 1593 \rangle ;

pdf_nobuiltintounicode_code: \langle Implement \backslash pdfnobuiltintounicode 1594 \rangle ;

pdf_interword_space_on_node: \langle Implement \backslash pdfinterwordspaceon 1595 \rangle ;

pdf_interword_space_off_node: \langle Implement \backslash pdfinterwordspaceoff 1596 \rangle ;

pdf_fake_space_node: \langle Implement \backslash pdffakespace 1597 \rangle ;

```

pdf_running_link_off_node: <Implement \pdfrunninglinkoff 1598>;
pdf_running_link_on_node: <Implement \pdfrunninglinkon 1599>;
pdf_space_font_code: <Implement \pdfspacefont 1600>;
othercases confusion("ext1")
endcases;
end;

```

1531* The next subroutine uses *cur_chr* to decide what sort of whatsit is involved, and also inserts a *write_stream* number.

<Declare procedures needed in *do_extension 1530*> +≡

```

procedure new_write_whatshit(w : small_number);

```

```

  begin new_whatshit(cur_chr, w);

```

```

  if w ≠ write_node_size then scan_four_bit_int

```

```

  else begin scan_int;

```

```

    if cur_val < 0 then cur_val ← 17

```

```

    else if (cur_val > 15) ∧ (cur_val ≠ 18) then cur_val ← 16;

```

```

    end;

```

```

  write_stream(tail) ← cur_val;

```

```

  if mubyte_out + mubyte_zero < 0 then write_mubyte(tail) ← 0

```

```

  else if mubyte_out + mubyte_zero ≥ 2 * mubyte_zero then write_mubyte(tail) ← 2 * mubyte_zero - 1

```

```

    else write_mubyte(tail) ← mubyte_out + mubyte_zero;

```

```

  end;

```

1535* When `\special{...}` appears, we expand the macros in the token list as in `\xdef` and `\mark`. When marked with `shipout`, we keep tokens unexpanded for now.

Unfortunately, the `write_stream(tail) ← null` done here is not a valid assignment in Web2C, because `null` (a.k.a. `min_halfword`) is a large negative number ($-268435455 = -\text{"FFFFFFF}$, set in `tex.ch`); too large to fit in the `short` structure element that's being assigned. The warning from gcc 8.5.0 was:

```
pdftex0.c: In function 'doextension':
pdftex0.c:37849:40: warning: overflow in conversion from 'long int' to 'short int'
  changes value from '-268435455' to '1' [-Woverflow]
mem [curlist .tailfield + 1 ].hh.b0 = -268435455L ;
```

The correct thing to do is not immediately evident. However, for Web2C, it does not matter, because these lines are changed for `encTeX`, in `enctex2.ch`, and now zero is assigned, instead of `null`.

⟨Implement `\special 1535*`⟩ ≡

```
begin if scan_keyword("shipout") then
  begin new_whatsit(latespecial_node, write_node_size);
  if spec_out + mubyte_zero < 0 then write_stream(tail) ← 0
  else if spec_out + mubyte_zero ≥ 2 * mubyte_zero then write_stream(tail) ← 2 * mubyte_zero - 1
    else write_stream(tail) ← spec_out + mubyte_zero;
  if mubyte_out + mubyte_zero < 0 then write_mubyte(tail) ← 0
  else if mubyte_out + mubyte_zero ≥ 2 * mubyte_zero then write_mubyte(tail) ← 2 * mubyte_zero - 1
    else write_mubyte(tail) ← mubyte_out + mubyte_zero;
  if (spec_out = 2) ∨ (spec_out = 3) then
    if (mubyte_out > 2) ∨ (mubyte_out = -1) ∨ (mubyte_out = -2) then write_noexpanding ← true;
  p ← scan_toks(false, false); write_tokens(tail) ← def_ref; write_noexpanding ← false;
  end
else begin new_whatsit(special_node, write_node_size);
  if spec_out + mubyte_zero < 0 then write_stream(tail) ← 0
  else if spec_out + mubyte_zero ≥ 2 * mubyte_zero then write_stream(tail) ← 2 * mubyte_zero - 1
    else write_stream(tail) ← spec_out + mubyte_zero;
  if mubyte_out + mubyte_zero < 0 then write_mubyte(tail) ← 0
  else if mubyte_out + mubyte_zero ≥ 2 * mubyte_zero then write_mubyte(tail) ← 2 * mubyte_zero - 1
    else write_mubyte(tail) ← mubyte_out + mubyte_zero;
  if (spec_out = 2) ∨ (spec_out = 3) then
    if (mubyte_out > 2) ∨ (mubyte_out = -1) ∨ (mubyte_out = -2) then write_noexpanding ← true;
  p ← scan_toks(false, true); write_tokens(tail) ← def_ref; write_noexpanding ← false;
  end;
end
```

This code is used in section [1529*](#).

1603* Each new type of node that appears in our data structure must be capable of being displayed, copied, destroyed, and so on. The routines that we need for write-oriented whatsits are somewhat like those for mark nodes; other extensions might, of course, involve more subtlety here.

⟨Basic printing procedures [57](#)⟩ +≡

```
procedure print_write_whatsit(s : str_number; p : pointer);
  begin print_esc(s);
  if write_stream(p) < 16 then print_int(write_stream(p))
  else if write_stream(p) = 16 then print_char("*")
    else print_char("-");
  if (s = "write") ∧ (write_mubyte(p) ≠ mubyte_zero) then
    begin print_char("<"); print_int(write_mubyte(p) - mubyte_zero); print_char(">");
    end;
  end;
```

1604* \langle Display the whatsit node *p* 1604* $\rangle \equiv$

```

case subtype(p) of
  open_node: begin print_write_whatsit("openout",p); print_char("=");
    print_file_name(open_name(p), open_area(p), open_ext(p));
  end;
  write_node: begin print_write_whatsit("write",p); print_mark(write_tokens(p));
  end;
  close_node: print_write_whatsit("closeout",p);
  special_node: begin print_esc("special");
    if write_stream(p)  $\neq$  mubyte_zero then
      begin print_char("<"); print_int(write_stream(p) - mubyte_zero);
      if (write_stream(p) - mubyte_zero = 2)  $\vee$  (write_stream(p) - mubyte_zero = 3) then
        begin print_char(":"); print_int(write_mubyte(p) - mubyte_zero);
        end;
      print_char(">");
      end;
    print_mark(write_tokens(p));
  end;
  latespecial_node: begin print_esc("special"); print("␣shipout"); print_mark(write_tokens(p));
  end;
  language_node: begin print_esc("setlanguage"); print_int(what_lang(p)); print("␣(hyphenmin␣");
    print_int(what_lhm(p)); print_char(","); print_int(what_rhm(p)); print_char(")");
  end;
  pdf_literal_node, pdf_lateliteral_node: begin print_esc("pdfliteral");
    if subtype(p) = pdf_lateliteral_node then print("␣shipout");
    case pdf_literal_mode(p) of
      set_origin: do_nothing;
      direct_page: print("␣page");
      direct_always: print("␣direct");
      othercases confusion("literal2")
    endcases; print_mark(pdf_literal_data(p));
  end;
  pdf_colorstack_node: begin print_esc("pdfcolorstack␣"); print_int(pdf_colorstack_stack(p));
    case pdf_colorstack_cmd(p) of
      colorstack_set: print("␣set␣");
      colorstack_push: print("␣push␣");
      colorstack_pop: print("␣pop");
      colorstack_current: print("␣current");
      othercases confusion("pdfcolorstack")
    endcases;
    if pdf_colorstack_cmd(p)  $\leq$  colorstack_data then print_mark(pdf_colorstack_data(p));
  end;
  pdf_setmatrix_node: begin print_esc("pdfsetmatrix"); print_mark(pdf_setmatrix_data(p));
  end;
  pdf_save_node: begin print_esc("pdfsave");
  end;
  pdf_restore_node: begin print_esc("pdfrestore");
  end;
  pdf_refobj_node: begin print_esc("pdfrefobj");
    if obj_obj_is_stream(pdf_obj_objnum(p)) > 0 then
      begin if obj_obj_stream_attr(pdf_obj_objnum(p))  $\neq$  null then
        begin print("␣attr"); print_mark(obj_obj_stream_attr(pdf_obj_objnum(p)));
      end
    end
  end

```



```

    end;
    print("_stream");
  end;
  if obj_obj_is_file(pdf_obj_objnum(p)) > 0 then print("_file");
  print_mark(obj_obj_data(pdf_obj_objnum(p)));
  end;
pdf_refxform_node: begin print_esc("pdfrefxform"); print("(");
  print_scaled(obj_xform_height(pdf_xform_objnum(p))); print_char("+");
  print_scaled(obj_xform_depth(pdf_xform_objnum(p))); print(")x");
  print_scaled(obj_xform_width(pdf_xform_objnum(p)));
  end;
pdf_refximage_node: begin print_esc("pdfrefximage"); print("(");
  print_scaled(obj_ximage_height(pdf_ximage_objnum(p))); print_char("+");
  print_scaled(obj_ximage_depth(pdf_ximage_objnum(p))); print(")x");
  print_scaled(obj_ximage_width(pdf_ximage_objnum(p)));
  end;
pdf_annot_node: begin print_esc("pdfannot");
  ⟨Display rule specj for whatsit node created by pdfTeX 1602⟩;
  print_mark(pdf_annot_data(p));
  end;
pdf_start_link_node: begin print_esc("pdfstartlink");
  ⟨Display rule specj for whatsit node created by pdfTeX 1602⟩;
  if pdf_link_attr(p) ≠ null then
    begin print("_attr"); print_mark(pdf_link_attr(p));
    end;
  print("_action");
  if pdf_action_type(pdf_link_action(p)) = pdf_action_user then
    begin print("_user"); print_mark(pdf_action_user_tokens(pdf_link_action(p)));
    end
  else begin if pdf_action_file(pdf_link_action(p)) ≠ null then
    begin print("_file"); print_mark(pdf_action_file(pdf_link_action(p)));
    end;
    case pdf_action_type(pdf_link_action(p)) of
pdf_action_goto: begin if (pdf_action_named_id(pdf_link_action(p)) mod 2) = 1 then
  begin print("_goto_name"); print_mark(pdf_action_id(pdf_link_action(p)));
  end
  else begin print("_goto_num"); print_int(pdf_action_id(pdf_link_action(p)))
  end;
  end;
pdf_action_page: begin print("_page"); print_int(pdf_action_id(pdf_link_action(p)));
  print_mark(pdf_action_page_tokens(pdf_link_action(p)));
  end;
pdf_action_thread: begin if (pdf_action_named_id(pdf_link_action(p)) mod 2) = 1 then
  begin print("_thread_name"); print_mark(pdf_action_id(pdf_link_action(p)));
  end
  else begin print("_thread_num"); print_int(pdf_action_id(pdf_link_action(p)));
  end;
  end;
  othercases pdf_error("displaying", "unknown_action_type");
  endcases;
  end
end;
end;

```

```

pdf_end_link_node: print_esc("pdfendlink");
pdf_dest_node: begin print_esc("pdfdest");
  if pdf_dest_objnum(p) ≠ null then
    begin print("_struct"); print_int(pdf_dest_objnum(p));
    end;
  if pdf_dest_named_id(p) > 0 then
    begin print("_name"); print_mark(pdf_dest_id(p));
    end
  else begin print("_num"); print_int(pdf_dest_id(p));
    end;
  print("_");
  case pdf_dest_type(p) of
pdf_dest_xyz: begin print("xyz");
  if pdf_dest_xyz_zoom(p) ≠ null then
    begin print("_zoom"); print_int(pdf_dest_xyz_zoom(p));
    end;
  end;
pdf_dest_fitbh: print("fitbh");
pdf_dest_fitbv: print("fitbv");
pdf_dest_fitb: print("fitb");
pdf_dest_fit: print("fit");
pdf_dest_fitv: print("fitv");
pdf_dest_fitr: begin print("fitr"); < Display rule speci for whatsit node created by pdfTeX 1602 >;
  end;
pdf_dest_fit: print("fit");
  othercases print("unknown!");
  endcases;
end;
pdf_thread_node, pdf_start_thread_node: begin if subtype(p) = pdf_thread_node then
  print_esc("pdfthread")
  else print_esc("pdfstartthread");
  print("("); print_rule_dimen(pdf_height(p)); print_char("+"); print_rule_dimen(pdf_depth(p));
  print("x"); print_rule_dimen(pdf_width(p));
  if pdf_thread_attr(p) ≠ null then
    begin print("_attr"); print_mark(pdf_thread_attr(p));
    end;
  if pdf_thread_named_id(p) > 0 then
    begin print("_name"); print_mark(pdf_thread_id(p));
    end
  else begin print("_num"); print_int(pdf_thread_id(p));
    end;
  end;
pdf_end_thread_node: print_esc("pdfendthread");
pdf_save_pos_node: print_esc("pdfsavepos");
pdf_snap_ref_point_node: print_esc("pdfsnaprefpoint");
pdf_snap_node: begin print_esc("pdfsnap"); print_char("_"); print_spec(snap_glue_ptr(p), 0);
  print_char("_"); print_spec(final_skip(p), 0);
  end;
pdf_snap_comp_node: begin print_esc("pdfsnapcomp"); print_char("_");
  print_int(snap_comp_ratio(p));
  end;
pdf_interword_space_on_node: print_esc("pdfinterwordspaceon");

```

```

pdf_interword_space_off_node: print_esc("pdfinterwordspaceoff");
pdf_fake_space_node: print_esc("pdffakepace");
pdf_running_link_off_node: print_esc("pdfrunninglinkoff");
pdf_running_link_on_node: print_esc("pdfrunninglinkon");
othercases print("whatsit?")
endcases

```

This code is used in section 201.

1616* After all this preliminary shuffling, we come finally to the routines that actually send out the requested data. Let's do `\special` first (it's easier).

⟨Declare procedures needed in *hlist.out*, *vlist.out* 1616*⟩ ≡

```

procedure special_out(p: pointer);
  var old_setting: 0 .. max_selector; { holds print selector }
      k: pool_pointer; { index into str_pool }
      h: halfword; q,r: pointer; { temporary variables for list manipulation }
      old_mode: integer; { saved mode }
  begin synch_h; synch_v;
  old_setting ← selector; selector ← new_string; spec_sout ← spec_out;
  spec_out ← write_stream(p) − mubyte_zero; mubyte_sout ← mubyte_out;
  mubyte_out ← write_mubyte(p) − mubyte_zero; active_noconvert ← true; mubyte_slog ← mubyte_log;
  mubyte_log ← 0;
  if (mubyte_out > 0) ∨ (mubyte_out = −1) then mubyte_log ← 1;
  if (spec_out = 2) ∨ (spec_out = 3) then
    begin if (mubyte_out > 0) ∨ (mubyte_out = −1) then
      begin special_printing ← true; mubyte_log ← 1;
      end;
    if mubyte_out > 1 then cs_converting ← true;
    end;
  selector ← old_setting;
  if subtype(p) = latespecial_node then
    begin ⟨Expand macros in the token list and make link(def_ref) point to the result 1619*⟩;
    h ← def_ref;
    end
  else h ← write_tokens(p);
  selector ← new_string; show_token_list(link(h), null, pool_size − pool_ptr); selector ← old_setting;
  str_room(1);
  if cur_length < 256 then
    begin dvi_out(xxx1); dvi_out(cur_length);
    end
  else begin dvi_out(xxx4); dvi_four(cur_length);
  end;
  if (spec_out = 1) ∨ (spec_out = 3) then
    for k ← str_start[str_ptr] to pool_ptr − 1 do str_pool[k] ← si(xchr[so(str_pool[k])]);
  for k ← str_start[str_ptr] to pool_ptr − 1 do dvi_out(so(str_pool[k]));
  spec_out ← spec_sout; mubyte_out ← mubyte_sout; mubyte_log ← mubyte_slog; special_printing ← false;
  cs_converting ← false; active_noconvert ← false; pool_ptr ← str_start[str_ptr]; { erase the string }
  if subtype(p) = latespecial_node then flush_list(def_ref);
  end;

```

See also sections 1618*, 1621*, 1720, and 1724.

This code is used in section 647*.

```

1618* <Declare procedures needed in hlist_out, vlist_out 1616*> +≡
procedure write_out(p : pointer);
  var old_setting: 0 .. max_selector; { holds print selector }
    old_mode: integer; { saved mode }
    j: small_number; { write stream number }
    q, r: pointer; { temporary variables for list manipulation }
    d: integer; { number of characters in incomplete current string }
    clobbered: boolean; { system string is ok? }
    runsystem_ret: integer; { return value from runsystem }
begin mubyte_sout ← mubyte_out; mubyte_out ← write_mubyte(p) – mubyte_zero;
if (mubyte_out > 2) ∨ (mubyte_out = –1) ∨ (mubyte_out = –2) then write_noexpanding ← true;
<Expand macros in the token list and make link(def_ref) point to the result 1619*>;
old_setting ← selector; j ← write_stream(p);
if j = 18 then selector ← new_string
else if write_open[j] then selector ← j
  else begin { write to the terminal if file isn't open }
    if (j = 17) ∧ (selector = term_and_log) then selector ← log_only;
    print_nl("");
  end;
active_noconvert ← true;
if mubyte_out > 1 then cs_converting ← true;
mubyte_slog ← mubyte_log;
if (mubyte_out > 0) ∨ (mubyte_out = –1) then mubyte_log ← 1
else mubyte_log ← 0;
token_show(def_ref); print_ln; cs_converting ← false; write_noexpanding ← false;
active_noconvert ← false; mubyte_out ← mubyte_sout; mubyte_log ← mubyte_slog; flush_list(def_ref);
if j = 18 then
  begin if (tracing_online ≤ 0) then selector ← log_only { Show what we're doing in the log file. }
  else selector ← term_and_log; { Show what we're doing. }
  { If the log file isn't open yet, we can only send output to the terminal. Calling open_log_file from
  here seems to result in bad data in the log. }
  if ¬log_opened then selector ← term_only;
  print_nl("runsystem(");
  for d ← 0 to cur_length – 1 do
    begin { print gives up if passed str_ptr, so do it by hand. }
    print(so(str_pool[str_start[str_ptr] + d])); { N.B.: not print_char }
    end;
  print(")...");
  if shellenabledp then
    begin str_room(1); append_char(0); { Append a null byte to the expansion. }
    clobbered ← false;
    for d ← 0 to cur_length – 1 do { Convert to external character set. }
      begin str_pool[str_start[str_ptr] + d] ← xchr[str_pool[str_start[str_ptr] + d]];
      if (str_pool[str_start[str_ptr] + d] = null_code) ∧ (d < cur_length – 1) then clobbered ← true;
      { minimal checking: NUL not allowed in argument string of system() }
    end;
  if clobbered then print("clobbered")
  else begin { We have the command. See if we're allowed to execute it, and report in the log. We
  don't check the actual exit status of the command, or do anything with the output. }
    runsystem_ret ← runsystem(conststringcast(addressof(str_pool[str_start[str_ptr])))];
    if runsystem_ret = –1 then print("quotation_error_in_system_command")
    else if runsystem_ret = 0 then print("disabled(restricted)")

```

```

    else if runsystem_ret = 1 then print("executed")
    else if runsystem_ret = 2 then print("executed_safely_(allowed)")
  end;
end
else begin print("disabled"); { shellenabledp false }
end;
print_char("."); print_nl(""); print_ln; pool_ptr ← str_start[str_ptr]; { erase the string }
end;
selector ← old_setting;
end;

```

1619* The final line of this routine is slightly subtle; at least, the author didn't think about it until getting burnt! There is a used-up token list on the stack, namely the one that contained *end_write_token*. (We insert this artificial '\endwrite' to prevent runaways, as explained above.) If it were not removed, and if there were numerous writes on a single page, the stack would overflow.

```

define end_write_token ≡ cs_token_flag + end_write
⟨Expand macros in the token list and make link(def_ref) point to the result 1619*⟩ ≡
q ← get_avail; info(q) ← right_brace_token + "}";
r ← get_avail; link(q) ← r; info(r) ← end_write_token; ins_list(q);
begin_token_list(write_tokens(p), write_text);
q ← get_avail; info(q) ← left_brace_token + "{"; ins_list(q);
{ now we're ready to scan '{token list}' \endwrite }
old_mode ← mode; mode ← 0; { disable \prevdepth, \spacefactor, \lastskip, \prevgraf }
cur_cs ← write_loc; q ← scan_toks(false, true); { expand macros, etc. }
mode ← old_mode; get_token; if cur_tok ≠ end_write_token then
  ⟨Recover from an unbalanced write command 1620⟩;
end_token_list { conserve stack space }

```

This code is used in sections 727, 727, 1616*, and 1618*.

1621* The *out_what* procedure takes care of outputting whatsit nodes for *vlist_out* and *hlist_out*.

```

⟨Declare procedures needed in hlist_out, vlist_out 1616*⟩ +≡
procedure out_what(p : pointer);
var j : small_number; { write stream number }
old_setting : 0 .. max_selector;
begin case subtype(p) of
open_node, write_node, close_node : ⟨Do some work that has been queued up for \write 1623*⟩;
special_node, latespecial_node : special_out(p);
language_node : do_nothing;
pdf_save_pos_node : ⟨Save current position in DVI mode 1622⟩;
others : begin if (pdfTeX_first_extension_code ≤ subtype(p)) ∧ (subtype(p) ≤ pdfTeX_last_extension_code)
then pdf_error("ext4", "pdf_node_ended_up_in_DVI_mode")
else confusion("ext4")
end;
endcases;
end;

```

1623* We don't implement `\write` inside of leaders. (The reason is that the number of times a leader box appears might be different in different implementations, due to machine-dependent rounding in the glue calculations.)

⟨Do some work that has been queued up for `\write 1623*`⟩ ≡

```

if  $\neg$ doing_leaders then
  begin  $j \leftarrow$  write_stream( $p$ );
  if subtype( $p$ ) = write_node then write_out( $p$ )
  else begin if write_open[ $j$ ] then
    begin a_close(write_file[ $j$ ]); write_open[ $j$ ]  $\leftarrow$  false;
    end;
  if subtype( $p$ ) = close_node then do_nothing { already closed }
  else if  $j < 16$  then
    begin cur_name  $\leftarrow$  open_name( $p$ ); cur_area  $\leftarrow$  open_area( $p$ ); cur_ext  $\leftarrow$  open_ext( $p$ );
    if cur_ext = "" then cur_ext  $\leftarrow$  ".tex";
    pack_cur_name;
    while  $\neg$ kpse_out_name_ok(stringcast(name_of_file + 1))  $\vee$   $\neg$ a_open_out(write_file[ $j$ ]) do
      prompt_file_name("output_□file_□name", ".tex");
    write_open[ $j$ ]  $\leftarrow$  true; { If on first line of input, log file is not ready yet, so don't log. }
    if log_opened  $\wedge$  texmf_yesno( $\text{\textasciitilde}$ log_openout $\text{\textasciitilde}$ ) then
      begin old_setting  $\leftarrow$  selector;
      if (tracing_online  $\leq$  0) then selector  $\leftarrow$  log_only { Show what we're doing in the log file. }
      else selector  $\leftarrow$  term_and_log; { Show what we're doing. }
      print_nl( $\text{\textasciitilde}$ openout); print_int( $j$ ); print("_□=");
      print_file_name(cur_name, cur_area, cur_ext); print("^."); print_nl(""); print_ln;
      selector  $\leftarrow$  old_setting;
      end;
    end;
  end;
end;
end

```

This code is used in section 1621*.

1638* Threads are handled in similar way as link annotations.

(Declare procedures needed in *pdf_hlist_out*, *pdf_vlist_out* 727) +≡

```

procedure append_bead(p : pointer);
  var a, b, c, t: integer;
  begin if  $\neg$ is_shipping_page then pdf_error("ext4", "threads_cannot_be_inside_an_XForm");
  t  $\leftarrow$  get_obj(obj_type_thread, pdf_thread_id(p), pdf_thread_named_id(p)); b  $\leftarrow$  pdf_new_objnum;
  obj_bead_ptr(b)  $\leftarrow$  pdf_get_mem(pdfmem_bead_size); obj_bead_page(b)  $\leftarrow$  pdf_last_page;
  obj_bead_data(b)  $\leftarrow$  p;
  if pdf_thread_attr(p)  $\neq$  null then obj_bead_attr(b)  $\leftarrow$  tokens_to_string(pdf_thread_attr(p))
  else obj_bead_attr(b)  $\leftarrow$  0;
  if obj_thread_first(t) = 0 then
    begin obj_thread_first(t)  $\leftarrow$  b; obj_bead_next(b)  $\leftarrow$  b; obj_bead_prev(b)  $\leftarrow$  b;
    end
  else begin a  $\leftarrow$  obj_thread_first(t); c  $\leftarrow$  obj_bead_prev(a); obj_bead_prev(b)  $\leftarrow$  c; obj_bead_next(b)  $\leftarrow$  a;
    obj_bead_prev(a)  $\leftarrow$  b; obj_bead_next(c)  $\leftarrow$  b;
    end;
  pdf_append_list(b)(pdf_bead_list);
  end;
procedure do_thread(p, parent_box : pointer; x, y : scaled);
  begin if doing_leaders then return;
  if subtype(p) = pdf_start_thread_node then
    begin pdf_thread_wd  $\leftarrow$  pdf_width(p); pdf_thread_ht  $\leftarrow$  pdf_height(p); pdf_thread_dp  $\leftarrow$  pdf_depth(p);
    pdf_last_thread_id  $\leftarrow$  pdf_thread_id(p); pdf_last_thread_named_id  $\leftarrow$  (pdf_thread_named_id(p) > 0);
    if pdf_last_thread_named_id then add_token_ref(pdf_thread_id(p));
    pdf_thread_level  $\leftarrow$  cur_s;
    end;
  set_rect_dimens(p, parent_box, x, y, pdf_width(p), pdf_height(p), pdf_depth(p), pdf_thread_margin);
  append_bead(p); last_thread  $\leftarrow$  p;
  end;
procedure append_thread(parent_box : pointer; x, y : scaled);
  var p: pointer;
  begin p  $\leftarrow$  get_node(pdf_thread_node_size); info(p)  $\leftarrow$  max_halfword; { this is not a whatsit node }
  link(p)  $\leftarrow$  null; { this node will be destroyed separately }
  pdf_width(p)  $\leftarrow$  pdf_thread_wd; pdf_height(p)  $\leftarrow$  pdf_thread_ht; pdf_depth(p)  $\leftarrow$  pdf_thread_dp;
  pdf_thread_attr(p)  $\leftarrow$  null; pdf_thread_id(p)  $\leftarrow$  pdf_last_thread_id;
  if pdf_last_thread_named_id then
    begin add_token_ref(pdf_thread_id(p)); pdf_thread_named_id(p)  $\leftarrow$  1;
    end
  else pdf_thread_named_id(p)  $\leftarrow$  0;
  set_rect_dimens(p, parent_box, x, y, pdf_width(p), pdf_height(p), pdf_depth(p), pdf_thread_margin);
  append_bead(p); last_thread  $\leftarrow$  p;
  end;
procedure end_thread;
  begin if pdf_thread_level  $\neq$  cur_s then pdf_error("ext4",
    "\pdfendthread_ended_up_in_different_nesting_level_than_\pdfstartthread");
  if is_running(pdf_thread_dp)  $\wedge$  (last_thread  $\neq$  null) then
    pdf_bottom(last_thread)  $\leftarrow$  cur_v + pdf_thread_margin;
  if pdf_last_thread_named_id then delete_token_ref(pdf_last_thread_id);
  last_thread  $\leftarrow$  null;
  end;
function open_subentries(p : pointer): integer;
  var k, c: integer; l, r: integer;

```

```

begin  $k \leftarrow 0$ ;
if  $obj\_outline\_first(p) \neq 0$  then
  begin  $l \leftarrow obj\_outline\_first(p)$ ;
  repeat  $incr(k)$ ;  $c \leftarrow open\_subentries(l)$ ;
    if  $obj\_outline\_count(l) > 0$  then  $k \leftarrow k + c$ ;
     $obj\_outline\_parent(l) \leftarrow p$ ;  $r \leftarrow obj\_outline\_next(l)$ ;
    if  $r = 0$  then  $obj\_outline\_last(p) \leftarrow l$ ;
     $l \leftarrow r$ ;
  until  $l = 0$ ;
  end;
if  $obj\_outline\_count(p) > 0$  then  $obj\_outline\_count(p) \leftarrow k$ 
else  $obj\_outline\_count(p) \leftarrow -k$ ;
 $open\_subentries \leftarrow k$ ;
end;
procedure  $do\_dest(p, parent\_box : pointer; x, y : scaled)$ ;
  var  $k$ : integer;
  begin if  $\neg is\_shipping\_page$  then  $pdf\_error("ext4", "destinations\_cannot\_be\_inside\_an\_XForm")$ ;
  if  $doing\_leaders$  then return;
  if  $pdf\_dest\_objnum(p) = null$  then  $k \leftarrow get\_obj(obj\_type\_dest, pdf\_dest\_id(p), pdf\_dest\_named\_id(p))$ 
  else  $k \leftarrow get\_obj(obj\_type\_struct\_dest, pdf\_dest\_id(p), pdf\_dest\_named\_id(p))$ ;
  if  $obj\_dest\_ptr(k) \neq null$  then
    begin  $warn\_dest\_dup(pdf\_dest\_id(p), pdf\_dest\_named\_id(p), "ext4",$ 
       $"has\_been\_already\_used, \_duplicate\_ignored")$ ; return;
    end;
   $obj\_dest\_ptr(k) \leftarrow p$ ;  $pdf\_append\_list(k)(pdf\_dest\_list)$ ;
  case  $pdf\_dest\_type(p)$  of
   $pdf\_dest\_xyz$ : if  $matrixused$  then
     $set\_rect\_dimens(p, parent\_box, x, y, pdf\_width(p), pdf\_height(p), pdf\_depth(p), pdf\_dest\_margin)$ 
  else begin  $pdf\_left(p) \leftarrow cur\_h$ ;  $pdf\_top(p) \leftarrow cur\_v$ ;
  end;
   $pdf\_dest\_fith, pdf\_dest\_fitbh$ : if  $matrixused$  then
     $set\_rect\_dimens(p, parent\_box, x, y, pdf\_width(p), pdf\_height(p), pdf\_depth(p), pdf\_dest\_margin)$ 
  else  $pdf\_top(p) \leftarrow cur\_v$ ;
   $pdf\_dest\_fitv, pdf\_dest\_fitbv$ : if  $matrixused$  then
     $set\_rect\_dimens(p, parent\_box, x, y, pdf\_width(p), pdf\_height(p), pdf\_depth(p), pdf\_dest\_margin)$ 
  else  $pdf\_left(p) \leftarrow cur\_h$ ;
   $pdf\_dest\_fit, pdf\_dest\_fitb$ :  $do\_nothing$ ;
   $pdf\_dest\_fitr$ :  $set\_rect\_dimens(p, parent\_box, x, y, pdf\_width(p), pdf\_height(p), pdf\_depth(p), pdf\_dest\_margin)$ ;
  endcases;
end;
procedure  $out\_form(p : pointer)$ ;
  begin  $synctexpdfrefxform(pdf\_xform\_objnum(p))$ ;  $pdf\_end\_text$ ;  $pdf\_print\_ln("q")$ ;
  if  $pdf\_lookup\_list(pdf\_xform\_list, pdf\_xform\_objnum(p)) = null$  then
     $pdf\_append\_list(pdf\_xform\_objnum(p))(pdf\_xform\_list)$ ;
   $cur\_v \leftarrow cur\_v + obj\_xform\_depth(pdf\_xform\_objnum(p))$ ;  $pdf\_print("1\_0\_0\_1")$ ;
   $pdf\_print\_bp(pdf\_x(cur\_h))$ ;  $pdf\_out("_")$ ;  $pdf\_print\_bp(pdf\_y(cur\_v))$ ;  $pdf\_print\_ln("_cm")$ ;
   $pdf\_print("/Fm")$ ;  $pdf\_print\_int(obj\_info(pdf\_xform\_objnum(p)))$ ;  $pdf\_print\_resname\_prefix$ ;
   $pdf\_print\_ln("_Do")$ ;  $pdf\_print\_ln("Q")$ ;
  end;
procedure  $out\_image(p : pointer)$ ;
  var  $image, groupref$ : integer;  $img\_w, img\_h$ : integer;
  begin  $image \leftarrow obj\_ximage\_data(pdf\_ximage\_objnum(p))$ ;

```



```

if (image_rotate(image) = 90)  $\vee$  (image_rotate(image) = 270) then
  begin img_h  $\leftarrow$  image_width(image); img_w  $\leftarrow$  image_height(image);
  end
else begin img_w  $\leftarrow$  image_width(image); img_h  $\leftarrow$  image_height(image);
  end;
pdf_end_text; pdf_print_ln("q");
if pdf_lookup_list(pdf_ximage_list, pdf_ximage_objnum(p)) = null then
  pdf_append_list(pdf_ximage_objnum(p))(pdf_ximage_list);
if  $\neg$ is_pdf_image(image) then
  begin if is_png_image(image) then
    begin groupref  $\leftarrow$  get_image_group_ref(image);
    if (groupref > 0)  $\wedge$  (pdf_page_group_val = 0) then pdf_page_group_val  $\leftarrow$  groupref;
    end;
    pdf_print_real(ext_xn_over_d(pdf_width(p), ten_pow[6], one_hundred_bp), 4); pdf_print("_0_0_");
    pdf_print_real(ext_xn_over_d(pdf_height(p) + pdf_depth(p), ten_pow[6], one_hundred_bp), 4);
    pdf_out("_"); pdf_print_bp(pdf_x(cur_h)); pdf_out("_"); pdf_print_bp(pdf_y(cur_v));
    end
  else begin { for pdf images we generate the page group object number here }
    groupref  $\leftarrow$  get_image_group_ref(image); { 0: no group, -1: to be generated;  $\neq$ 0: already written }
    if (groupref  $\neq$  0)  $\wedge$  (pdf_page_group_val = 0) then
      begin if groupref = -1 then
        begin pdf_page_group_val  $\leftarrow$  pdf_new_objnum; set_image_group_ref(image, pdf_page_group_val);
        end
      else { groupref  $\neq$  0 }
        pdf_page_group_val  $\leftarrow$  groupref;
      end;
      pdf_print_real(ext_xn_over_d(pdf_width(p), ten_pow[6], img_w), 6); pdf_print("_0_0_");
      pdf_print_real(ext_xn_over_d(pdf_height(p) + pdf_depth(p), ten_pow[6], img_h), 6); pdf_out("_");
      pdf_print_bp(pdf_x(cur_h) - ext_xn_over_d(pdf_width(p), epdf_orig_x(image), img_w)); pdf_out("_");
      pdf_print_bp(pdf_y(cur_v) - ext_xn_over_d(pdf_height(p) + pdf_depth(p), epdf_orig_y(image), img_h));
      end;
      pdf_print_ln("_cm"); pdf_print("/Im"); pdf_print_int(obj_info(pdf_ximage_objnum(p)));
      pdf_print_rename_prefix; pdf_print_ln("_Do"); pdf_print_ln("Q");
    end;
function gap_amount(p : pointer; cur_pos : scaled): scaled;
  { find the gap between the position of the current snap node p and the nearest point on the grid }
  var snap_unit, stretch_amount, shrink_amount: scaled; last_pos, next_pos, g, g2: scaled;
  begin snap_unit  $\leftarrow$  width(snap_glue_ptr(p));
  if stretch_order(snap_glue_ptr(p)) > normal then stretch_amount  $\leftarrow$  max_dimen
  else stretch_amount  $\leftarrow$  stretch(snap_glue_ptr(p));
  if shrink_order(snap_glue_ptr(p)) > normal then shrink_amount  $\leftarrow$  max_dimen
  else shrink_amount  $\leftarrow$  shrink(snap_glue_ptr(p));
  if subtype(p) = pdf_snap_node then
    last_pos  $\leftarrow$  pdf_snap_y_refpos + snap_unit * ((cur_pos - pdf_snap_y_refpos) div snap_unit)
  else pdf_error("snapping", "invalid_parameter_value_for_gap_amount");
  next_pos  $\leftarrow$  last_pos + snap_unit; @{print_nl("snap_ref_pos="); print_scaled(pdf_snap_y_refpos);
  print_nl("snap_glue="); print_spec(snap_glue_ptr(p), 0); print_nl("gap_amount=");
  print_scaled(snap_unit); print_nl("stretch_amount="); print_scaled(stretch_amount);
  print_nl("shrink_amount="); print_scaled(shrink_amount); print_nl("last_point=");
  print_scaled(last_pos); print_nl("cur_point="); print_scaled(cur_pos); print_nl("next_point=");
  print_scaled(next_pos); @} g  $\leftarrow$  max_dimen; g2  $\leftarrow$  max_dimen; gap_amount  $\leftarrow$  0;
  if cur_pos - last_pos < shrink_amount then g  $\leftarrow$  cur_pos - last_pos;

```

```

if ( $next\_pos - cur\_pos < stretch\_amount$ ) then  $g2 \leftarrow next\_pos - cur\_pos$ ;
if ( $g = max\_dimen$ )  $\wedge$  ( $g2 = max\_dimen$ ) then return; {unable to snap}
if  $g2 \leq g$  then  $gap\_amount \leftarrow g2$  {skip forward}
else  $gap\_amount \leftarrow -g$ ; {skip backward}
end;

function  $get\_vpos(p, q, b : pointer)$ :  $pointer$ ;
  {find the vertical position of node  $q$  in the output PDF page; this functions is called when the
  current node is  $p$  and current position is  $cur\_v$  (global variable);  $b$  is the parent box;}
var  $tmp\_v$ :  $scaled$ ;  $g\_order$ :  $glue\_ord$ ; {applicable order of infinity for glue}
   $g\_sign$ :  $normal \dots shrinking$ ; {selects type of glue}
   $glue\_temp$ :  $real$ ; {glue value before rounding}
   $cur\_glue$ :  $real$ ; {glue seen so far}
   $cur\_g$ :  $scaled$ ; {rounded equivalent of  $cur\_glue$  times the glue ratio}
   $this\_box$ :  $pointer$ ; {pointer to containing box}
begin  $tmp\_v \leftarrow cur\_v$ ;  $this\_box \leftarrow b$ ;  $cur\_g \leftarrow 0$ ;  $cur\_glue \leftarrow float\_constant(0)$ ;
 $g\_order \leftarrow glue\_order(this\_box)$ ;  $g\_sign \leftarrow glue\_sign(this\_box)$ ;
while ( $p \neq q$ )  $\wedge$  ( $p \neq null$ ) do
  begin if  $is\_char\_node(p)$  then  $confusion("get\_vpos")$ 
  else begin case  $type(p)$  of
     $hlist\_node, vlist\_node, rule\_node$ :  $tmp\_v \leftarrow tmp\_v + height(p) + depth(p)$ ;
     $whatsit\_node$ : if ( $subtype(p) = pdf\_refxform\_node$ )  $\vee$  ( $subtype(p) = pdf\_refximage\_node$ ) then
       $tmp\_v \leftarrow tmp\_v + pdf\_height(p) + pdf\_depth(p)$ ;
     $glue\_node$ : begin {Move down without outputting leaders 1639};
       $tmp\_v \leftarrow tmp\_v + rule\_ht$ ;
    end;
     $kern\_node$ :  $tmp\_v \leftarrow tmp\_v + width(p)$ ;
    othercases  $do\_nothing$ ;
    endcases;
  end;
   $p \leftarrow link(p)$ ;
end;
 $get\_vpos \leftarrow tmp\_v$ ;
end;

procedure  $do\_snapy\_comp(p, b : pointer)$ ; {do snapping compensation in vertical direction; search for
the next snap node and do the compensation if found}
var  $q$ :  $pointer$ ;  $tmp\_v, g, g2$ :  $scaled$ ;
begin if  $\neg(\neg is\_char\_node(p) \wedge (type(p) = whatsit\_node) \wedge (subtype(p) = pdf\_snapy\_comp\_node))$  then
   $pdf\_error("snapping", "invalid\_parameter\_value\_for\_do\_snapy\_comp")$ ;
 $q \leftarrow p$ ;
while ( $q \neq null$ ) do
  begin if  $\neg is\_char\_node(q) \wedge (type(q) = whatsit\_node) \wedge (subtype(q) = pdf\_snapy\_node)$  then
    begin  $tmp\_v \leftarrow get\_vpos(p, q, b)$ ; {get the position of  $q$ }
     $g \leftarrow gap\_amount(q, tmp\_v)$ ; {get the gap to the grid}
     $g2 \leftarrow round\_xn\_over\_d(g, snapy\_comp\_ratio(p), 1000)$ ; {adjustment for  $p$ }
    @{ $print\_nl("do\_snapy\_comp: \_tmp\_v\_=\_")$ ;  $print\_scaled(tmp\_v)$ ;
     $print\_nl("do\_snapy\_comp: \_cur\_v\_=\_")$ ;  $print\_scaled(cur\_v)$ ;  $print\_nl("do\_snapy\_comp: \_g\_=\_")$ ;
     $print\_scaled(g)$ ;  $print\_nl("do\_snapy\_comp: \_g2\_=\_")$ ;  $print\_scaled(g2)$ ; @}  $cur\_v \leftarrow cur\_v + g2$ ;
     $final\_skip(q) \leftarrow g - g2$ ; {adjustment for  $q$ }
    if  $final\_skip(q) = 0$  then  $final\_skip(q) \leftarrow 1$ ;
    {use  $1sp$  as the magic value to record that  $final\_skip$  has been set here}
    return;
  end;

```

```
    q ← link(q);  
  end;  
end;  
procedure do_snap(p : pointer);  
begin incr(count_do_snap); @{print_nl("do_snap: count="); print_int(count_do_snap);  
  print_nl("do_snap: cur_v="); print_scaled(cur_v); print_nl("do_snap: final_skip=");  
  print_scaled(final_skip(p)); @}  
  if final_skip(p) ≠ 0 then cur_v ← cur_v + final_skip(p)  
  else cur_v ← cur_v + gap_amount(p, cur_v);  
  @{print_nl("do_snap: cur_v after snap="); print_scaled(cur_v); @}  
end;
```

1649* **The extended features of ε -TEX.** The program has two modes of operation: (1) In TEX compatibility mode it fully deserves the name TEX and there are neither extended features nor additional primitive commands. There are, however, a few modifications that would be legitimate in any implementation of TEX such as, e.g., preventing inadequate results of the glue to DVI unit conversion during *ship_out*. (2) In extended mode there are additional primitive commands and the extended features of ε -TEX are available.

The distinction between these two modes of operation initially takes place when a ‘virgin’ eINITEX starts without reading a format file. Later on the values of all ε -TEX state variables are inherited when eVIRTEX (or eINITEX) reads a format file.

The code below is designed to work for cases where ‘init ... tini’ is a run-time switch.

```

⟨ Enable  $\varepsilon$ -TEX, if requested 1649* ⟩ ≡
init if (etex_p  $\vee$  (buffer[loc] = "*" ))  $\wedge$  (format_ident = "_(INITEX)") then
  begin no_new_control_sequence  $\leftarrow$  false; ⟨ Generate all  $\varepsilon$ -TEX primitives 1650 ⟩
  if (buffer[loc] = "*" ) then incr(loc);
  eTeX_mode  $\leftarrow$  1; { enter extended mode }
  ⟨ Initialize variables for  $\varepsilon$ -TEX extended mode 1814 ⟩
  end;
tini
if  $\neg$ no_new_control_sequence then { just entered extended mode ? }
  no_new_control_sequence  $\leftarrow$  true else

```

This code is used in section 1518*.

1653* **define** *eTeX_ex* \equiv (*eTeX_mode* = 1) { is this extended mode? }

```

⟨ Global variables 13 ⟩ +≡
eTeX_mode: 0 .. 1; { identifies compatibility and extended mode }
etex_p: boolean; { was the -etex option specified }

```

1661* In order to handle `\everyeof` we need an array *eof_seen* of boolean variables.

```

⟨ Global variables 13 ⟩ +≡
eof_seen:  $\uparrow$ boolean; { has eof been seen? }

```

1678* ⟨ Cases for *show_whatever* 1678* ⟩ \equiv

```

show_groups: begin ⟨ Adjust selector based on show_stream 1472* ⟩ begin_diagnostic; show_save_groups;
  end;

```

See also section 1692*.

This code is used in section 1471*.

1692*

```

define print_if_line(#)  $\equiv$ 
  if #  $\neq$  0 then
    begin print("_entered_on_line_"); print_int(#);
    end

```

\langle Cases for *show_whatever* 1678* $\rangle \equiv$

```

show_ifs: begin  $\langle$  Adjust selector based on show_stream 1472*  $\rangle$  begin_diagnostic; print_nl(""); print_ln;
if cond_ptr = null then
  begin print_nl("###_"); print("no_active_conditionals");
  end
else begin p  $\leftarrow$  cond_ptr; n  $\leftarrow$  0;
  repeat incr(n); p  $\leftarrow$  link(p); until p = null;
  p  $\leftarrow$  cond_ptr; t  $\leftarrow$  cur_if; l  $\leftarrow$  if_line; m  $\leftarrow$  if_limit;
  repeat print_nl("###_level_"); print_int(n); print(":_"); print_cmd_chr(if_test, t);
  if m = fi_code then print_esc("else");
  print_if_line(l); decr(n); t  $\leftarrow$  subtype(p); l  $\leftarrow$  if_line_field(p); m  $\leftarrow$  type(p); p  $\leftarrow$  link(p);
until p = null;
end;
end;

```

1722* We detach the hlist, start a new one consisting of just one kern node, append the reversed list, and set the width of the kern node.

\langle Reverse the complete hlist and set the subtype to *reversed* 1722* $\rangle \equiv$

```

begin save_h  $\leftarrow$  cur_h; temp_ptr  $\leftarrow$  p; p  $\leftarrow$  new_kern(0); sync_tag(p + medium_node_size)  $\leftarrow$  0;
  { SyncTEX: do nothing, it is too late }
  link(prev_p)  $\leftarrow$  p; cur_h  $\leftarrow$  0; link(p)  $\leftarrow$  reverse(this_box, null, cur_g, cur_glue); width(p)  $\leftarrow$   $-cur_h$ ;
  cur_h  $\leftarrow$  save_h; set_box_lr(this_box)(reversed);
end

```

This code is used in section 1715.

1723* We detach the remainder of the hlist, replace the math node by an edge node, and append the reversed hlist segment to it; the tail of the reversed segment is another edge node and the remainder of the original list is attached to it.

\langle Reverse an hlist segment and **goto** *reswitch* 1723* $\rangle \equiv$

```

begin save_h  $\leftarrow$  cur_h; temp_ptr  $\leftarrow$  link(p); rule_wd  $\leftarrow$  width(p); free_node(p, medium_node_size);
  { SyncTEX: p is a math_node }
  cur_dir  $\leftarrow$  reflected; p  $\leftarrow$  new_edge(cur_dir, rule_wd); link(prev_p)  $\leftarrow$  p;
  cur_h  $\leftarrow$  cur_h - left_edge + rule_wd; link(p)  $\leftarrow$  reverse(this_box, new_edge(reflected, 0), cur_g, cur_glue);
  edge_dist(p)  $\leftarrow$  cur_h; cur_dir  $\leftarrow$  reflected; cur_h  $\leftarrow$  save_h; goto reswitch;
end

```

This code is used in section 1718.

```

1726*  $\langle$  Move the non-char_node  $p$  to the new list 1726*  $\rangle \equiv$ 
  begin  $q \leftarrow \text{link}(p)$ ;
  case  $\text{type}(p)$  of
    hlist_node, vlist_node, rule_node, kern_node:  $\text{rule\_wd} \leftarrow \text{width}(p)$ ;
     $\langle$  Cases of reverse that need special treatment 1727  $\rangle$ 
    edge_node:  $\text{confusion}(\text{"LR2"})$ ;
  othercases goto next_p
endcases;
   $\text{cur\_h} \leftarrow \text{cur\_h} + \text{rule\_wd}$ ;
 $\text{next\_p}$ :  $\text{link}(p) \leftarrow l$ ;
  if  $\text{type}(p) = \text{kern\_node}$  then
    if  $(\text{rule\_wd} = 0) \vee (l = \text{null})$  then
      begin  $\text{free\_node}(p, \text{medium\_node\_size})$ ;  $p \leftarrow l$ ;
      end;
     $l \leftarrow p$ ;  $p \leftarrow q$ ;
  end

```

This code is used in section **1725**.

1730* Finally we have found the end of the *hlist* segment to be reversed; the final math node is released and the remaining list attached to the edge node terminating the reversed segment.

```

 $\langle$  Finish the reversed hlist segment and goto done 1730*  $\rangle \equiv$ 
  begin  $\text{free\_node}(p, \text{medium\_node\_size})$ ; { SyncTEX:  $p$  is a kern_node }
   $\text{link}(t) \leftarrow q$ ;  $\text{width}(t) \leftarrow \text{rule\_wd}$ ;  $\text{edge\_dist}(t) \leftarrow -\text{cur\_h} - \text{rule\_wd}$ ; goto done;
end

```

This code is used in section **1729**.

1734* When calculating the natural width, w , of the final line preceding the display, we may have to copy all or part of its hlist. We copy, however, only those parts of the original list that are relevant for the computation of *pre_display_size*.

⟨Declare subprocedures for *init_math* 1734*⟩ ≡

```

procedure just_copy(p, h, t : pointer);
  label found, not_found;
  var r: pointer; { current node being fabricated for new list }
      words: 0 .. 5; { number of words remaining to be copied }
  begin while p ≠ null do
    begin words ← 1; { this setting occurs in more branches than any other }
    if is_char_node(p) then r ← get_avail
    else case type(p) of
      hlist_node, vlist_node: begin r ← get_node(box_node_size);
        ⟨Copy the box SyncTEX information 1936*⟩;
        mem[r + 6] ← mem[p + 6]; mem[r + 5] ← mem[p + 5]; { copy the last two words }
        words ← 5; list_ptr(r) ← null; { this affects mem[r + 5] }
        end;
      rule_node: begin r ← get_node(rule_node_size); words ← rule_node_size;
        end;
      ligature_node: begin r ← get_avail; { only font and character are needed }
        mem[r] ← mem[lig_char(p)]; goto found;
        end;
      kern_node, math_node: begin words ← medium_node_size;
        { SyncTEX: proper size for math and kern }
        r ← get_node(words);
        end;
      glue_node: begin r ← get_node(medium_node_size); add_glue_ref(glue_ptr(p));
        { SyncTEX: proper size for glue }
        ⟨Copy the medium sized node SyncTEX information 1938*⟩;
        glue_ptr(r) ← glue_ptr(p); leader_ptr(r) ← null;
        end;
      whatsit_node: ⟨Make a partial copy of the whatsit node p and make r point to it; set words to the
        number of initial words not yet copied 1605⟩;
    othercases goto not_found
  endcases;
  while words > 0 do
    begin decr(words); mem[r + words] ← mem[p + words];
    end;
  found: link(h) ← r; h ← r;
  not_found: p ← link(p);
  end;
  link(h) ← t;
end;

```

See also section 1739*.

This code is used in section 1316.

1739* \langle Declare subprocedures for *init_math* 1734* \rangle \equiv

```

procedure just_reverse(p : pointer);
  label done;
  var l : pointer; { the new list }
      t : pointer; { tail of reversed segment }
      q : pointer; { the next node }
      m, n : halfword; { count of unmatched math nodes }
  begin m  $\leftarrow$  min_halfword; n  $\leftarrow$  min_halfword;
  if link(temp_head) = null then
    begin just_copy(link(p), temp_head, null); q  $\leftarrow$  link(temp_head);
    end
  else begin q  $\leftarrow$  link(p); link(p)  $\leftarrow$  null; flush_node_list(link(temp_head));
  end;
  t  $\leftarrow$  new_edge(cur_dir, 0); l  $\leftarrow$  t; cur_dir  $\leftarrow$  reflected;
  while q  $\neq$  null do
    if is_char_node(q) then
      repeat p  $\leftarrow$  q; q  $\leftarrow$  link(p); link(p)  $\leftarrow$  l; l  $\leftarrow$  p;
      until  $\neg$ is_char_node(q)
    else begin p  $\leftarrow$  q; q  $\leftarrow$  link(p);
      if type(p) = math_node then  $\langle$  Adjust the LR stack for the just_reverse routine 1740*  $\rangle$ ;
      link(p)  $\leftarrow$  l; l  $\leftarrow$  p;
      end;
    goto done; width(t)  $\leftarrow$  width(p); link(t)  $\leftarrow$  q; free_node(p, small_node_size);
  done : link(temp_head)  $\leftarrow$  l;
  end;

```

1740* \langle Adjust the LR stack for the *just_reverse* routine 1740* \rangle \equiv

```

if end_LR(p) then
  if info(LR_ptr)  $\neq$  end_LR_type(p) then
    begin type(p)  $\leftarrow$  kern_node; incr(LR_problems);
      { SyncTeX node size watch point: math_node size == kern_node size }
    end
  else begin pop_LR;
    if n > min_halfword then
      begin decr(n); decr(subtype(p)); { change after into before }
      end
    else begin if m > min_halfword then decr(m) else begin width(t)  $\leftarrow$  width(p); link(t)  $\leftarrow$  q;
      free_node(p, medium_node_size); { SyncTeX: no more "goto found", and proper node size }
      goto done;
      end;
      type(p)  $\leftarrow$  kern_node; { SyncTeX node size watch point: math_node size == kern_node size }
      end;
    end
  else begin push_LR(p);
    if (n > min_halfword)  $\vee$  (LR_dir(p)  $\neq$  cur_dir) then
      begin incr(n); incr(subtype(p)); { change before into after }
      end
    else begin type(p)  $\leftarrow$  kern_node; incr(m);
      { SyncTeX node size watch point: math_node size == kern_node size }
      end;
    end
  end

```

This code is used in section 1739*.


```

1756*  $\langle$  Initiate input from new pseudo file 1756\*  $\rangle \equiv$ 
  begin_file_reading; { set up cur_file and new level of input }
  line  $\leftarrow$  0; limit  $\leftarrow$  start; loc  $\leftarrow$  limit + 1; { force line read }
  if tracing_scan_tokens > 0 then
    begin if term_offset > max_print_line - 3 then print_ln
    else if (term_offset > 0)  $\vee$  (file_offset > 0) then print_char("□");
    name  $\leftarrow$  19; print("□"); incr(open_parens); update_terminal;
    end
  else begin name  $\leftarrow$  18;  $\langle$  Prepare pseudo file SyncTEX information 1921\*  $\rangle$ ;
  end

```

This code is used in section [1754](#).

1774* A group entered (or a conditional started) in one file may end in a different file. Such slight anomalies, although perfectly legitimate, may cause errors that are difficult to locate. In order to be able to give a warning message when such anomalies occur, ε -TEX uses the *grp_stack* and *if_stack* arrays to record the initial *cur_boundary* and *cond_ptr* values for each input file.

```

 $\langle$  Global variables 13  $\rangle + \equiv$ 
grp_stack:  $\uparrow$ save_pointer; { initial cur_boundary }
if_stack:  $\uparrow$ pointer; { initial cond_ptr }

```

1855* When reading \backslash patterns while \backslash savinghyphcodes is positive the current *lc_code* values are stored together with the hyphenation patterns for the current language. They will later be used instead of the *lc_code* values for hyphenation purposes.

The *lc_code* values are stored in the linked trie analogous to patterns p_1 of length 1, with *hyph_root* = *trie_r*[0] replacing *trie_root* and *lc_code*(p_1) replacing the *trie_op* code. This allows to compress and pack them together with the patterns with minimal changes to the existing code.

```

define hyph_root  $\equiv$  trie_r[0] { root of the linked trie for hyph_codes }
 $\langle$  Initialize table entries (done by INITEX only) 182  $\rangle + \equiv$ 

```

1868* **System-dependent changes for Web2c.** Here are extra variables for Web2c. (This numbering of the system-dependent section allows easy integration of Web2c and e-T_EX, etc.)

⟨Global variables 13⟩ +≡

edit_name_start: *pool_pointer*; { where the filename to switch to starts }

edit_name_length, *edit_line*: *integer*; { what line to start editing at }

ipc_on: *cinttype*; { level of IPC action, 0 for none [default] }

stop_at_space: *boolean*; { whether *more_name* returns false for space }

1869* The *edit_name_start* will be set to point into *str_pool* somewhere after its beginning if T_EX is supposed to switch to an editor on exit.

Initialize the *stop_at_space* variable for filename parsing.

Initialize the *halting_on_error_p* variable to avoid infloop with `--halt-on-error`.

⟨Set initial values of key variables 21⟩ +≡

edit_name_start ← 0; *stop_at_space* ← *true*; *halting_on_error_p* ← *false*;

1870* These are used when we regenerate the representation of the first 256 strings.

⟨Global variables 13⟩ +≡

save_str_ptr: *str_number*;

save_pool_ptr: *pool_pointer*;

shellenabledp: *cinttype*;

restrictedshell: *cinttype*;

output_comment: ↑*char*;

k, *l*: 0 .. 255; { used by ‘Make the first 256 strings’, etc. }

1871* When debugging a macro package, it can be useful to see the exact control sequence names in the format file. For example, if ten new csnames appear, it’s nice to know what they are, to help pinpoint where they came from. (This isn’t a truly “basic” printing procedure, but that’s a convenient module in which to put it.)

⟨Basic printing procedures 57⟩ +≡

procedure *print_csnames*(*hstart* : *integer*; *hfinish* : *integer*);

var *c*, *h*: *integer*;

begin *write_ln*(*stderr*, ^*fmtdebug*:*csnames*□*from*□^, *hstart*, ^□*to*□^, *hfinish*, ^: ^);

for *h* ← *hstart* **to** *hfinish* **do**

begin if *text*(*h*) > 0 **then**

begin { if have anything at this position }

for *c* ← *str_start*[*text*(*h*)] **to** *str_start*[*text*(*h*) + 1] − 1 **do**

begin *put_byte*(*str_pool*[*c*], *stderr*); { print the characters }

end;

write_ln(*stderr*, ^| ^);

end;

end;

end;

1872* Are we printing extra info as we read the format file?

⟨Global variables 13⟩ +≡

debug_format_file: *boolean*;

1873* A helper for printing file:line:error style messages. Look for a filename in *full_source_filename_stack*, and if we fail to find one fall back on the non-file:line:error style.

⟨Basic printing procedures 57⟩ +≡

```

procedure print_file_line;
  var level: 0 .. max_in_open;
  begin level ← in_open;
  while (level > 0) ∧ (full_source_filename_stack[level] = 0) do decr(level);
  if level = 0 then print_nl("!␣")
  else begin print_nl(""); print(full_source_filename_stack[level]); print(":");
    if level = in_open then print_int(line)
    else print_int(line_stack[level + 1]);
    print(":␣");
  end;
end;

```

1874* To be able to determine whether `\write18` is enabled from within TeX we also implement `\eof18`. We sort of cheat by having an additional route *scan_four_bit_int_or_18* which is the same as *scan_four_bit_int* except it also accepts the value 18.

⟨Declare procedures that scan restricted classes of integers 459⟩ +≡

```

procedure scan_four_bit_int_or_18;
  begin scan_int;
  if (cur_val < 0) ∨ ((cur_val > 15) ∧ (cur_val ≠ 18)) then
    begin print_err("Bad␣number");
    help2("Since␣I␣expected␣to␣read␣a␣number␣between␣0␣and␣15,")
    ("I␣changed␣this␣one␣to␣zero."); int_error(cur_val); cur_val ← 0;
    end;
  end;

```

1875* Dumping the *xord*, *xchr*, and *xprn* arrays. We dump these always in the format, so a TCX file loaded during format creation can set a default for users of the format.

⟨Dump *xord*, *xchr*, and *xprn* 1875*⟩ ≡

```

  dump_things(xord[0], 256); dump_things(xchr[0], 256); dump_things(xprn[0], 256);

```

This code is used in section 1486*.

1876* Undumping the *xord*, *xchr*, and *xprn* arrays. This code is more complicated, because we want to ensure that a TCX file specified on the command line will override whatever is in the format. Since the tcx file has already been loaded, that implies throwing away the data in the format. Also, if no *translate_filename* is given, but *eight_bit_p* is set we have to make all characters printable.

⟨Undump *xord*, *xchr*, and *xprn* 1876*⟩ ≡

```

if translate_filename then
  begin for k ← 0 to 255 do undump_things(dummy_xord, 1);
  for k ← 0 to 255 do undump_things(dummy_xchr, 1);
  for k ← 0 to 255 do undump_things(dummy_xprn, 1);
  end
else begin undump_things(xord[0], 256); undump_things(xchr[0], 256); undump_things(xprn[0], 256);
  if eight_bit_p then
    for k ← 0 to 255 do xprn[k] ← 1;
  end;

```

This code is used in section 1487*.

1877* **The string recycling routines.** T_EX uses 2 upto 4 *new* strings when scanning a filename in an `\input`, `\openin`, or `\openout` operation. These strings are normally lost because the reference to them are not saved after finishing the operation. `search_string` searches through the string pool for the given string and returns either 0 or the found string number.

```

⟨Declare additional routines for string recycling 1877*⟩ ≡
function search_string(search : str_number): str_number;
  label found;
  var result: str_number; s: str_number; { running index }
      len: integer; { length of searched string }
  begin result ← 0; len ← length(search);
  if len = 0 then { trivial case }
    begin result ← ""; goto found;
    end
  else begin s ← search - 1; { start search with newest string below s; search > 1! }
    while s > 255 do { first 256 strings depend on implementation!! }
      begin if length(s) = len then
        if str_eq_str(s, search) then
          begin result ← s; goto found;
          end;
        decr(s);
      end;
    end;
  found: search_string ← result;
  end;

```

See also section 1878*.

This code is used in section 47*.

1878* The following routine is a variant of `make_string`. It searches the whole string pool for a string equal to the string currently built and returns a found string. Otherwise a new string is created and returned. Be cautious, you can not apply `flush_string` to a replaced string!

```

⟨Declare additional routines for string recycling 1877*⟩ +≡
function slow_make_string: str_number;
  label exit;
  var s: str_number; { result of search_string }
      t: str_number; { new string }
  begin t ← make_string; s ← search_string(t);
  if s > 0 then
    begin flush_string; slow_make_string ← s; return;
    end;
  slow_make_string ← t;
  exit: end;

```

1879* **More changes for Web2c.** Sometimes, recursive calls to the *expand* routine may cause exhaustion of the run-time calling stack, resulting in forced execution stops by the operating system. To diminish the chance of this happening, a counter is used to keep track of the recursion depth, in conjunction with a constant called *expand_depth*.

This does not catch all possible infinite recursion loops, just the ones that exhaust the application calling stack. The actual maximum value of *expand_depth* is outside of our control, but the initial setting of 10000 should be enough to prevent problems.

```
<Global variables 13> +≡
expand_depth_count: integer;
```

```
1880* <Set initial values of key variables 21> +≡
expand_depth_count ← 0;
```

1881* When *scan_file_name* starts it looks for a *left_brace* (skipping *\relaxes*, as other *\toks*-like primitives). If a *left_brace* is found, then the procedure scans a file name contained in a balanced token list, expanding tokens as it goes. When the scanner finds the balanced token list, it is converted into a string and fed character-by-character to *more_name* to do its job the same as in the “normal” file name scanning.

```
procedure scan_file_name_braced;
```

```
var save_scanner_status: small_number; { scanner_status upon entry }
    save_def_ref: pointer; { def_ref upon entry, important if inside '\message }
    save_cur_cs: pointer; s: str_number; { temp string }
    p: pointer; { temp pointer }
    i: integer; { loop tally }
    save_stop_at_space: boolean; { this should be in tex.ch }
    dummy: boolean; { Initializing }
```

```
begin save_scanner_status ← scanner_status; { scan_toks sets scanner_status to absorbing }
```

```
save_def_ref ← def_ref; { scan_toks uses def_ref to point to the token list just read }
```

```
save_cur_cs ← cur_cs; { we set cur_cs back a few tokens to use in runaway errors }
```

```
{ Scanning a token list }
```

```
cur_cs ← warning_index; { for possible runaway error }
```

```
{ mimick call_func from pdfTeX }
```

```
if scan_toks(false, true) ≠ 0 then do_nothing; { actually do the scanning }
```

```
{ s ← tokens_to_string(def_ref); }
```

```
old_setting ← selector; selector ← new_string; show_token_list(link(def_ref), null, pool_size - pool_ptr);
```

```
selector ← old_setting; s ← make_string; { turns the token list read in a string to input }
```

```
{ Restoring some variables }
```

```
delete_token_ref(def_ref); { remove the token list from memory }
```

```
def_ref ← save_def_ref; { and restore def_ref }
```

```
cur_cs ← save_cur_cs; { restore cur_cs }
```

```
scanner_status ← save_scanner_status; { restore scanner_status }
```

```
{ Passing the read string to the input machinery }
```

```
save_stop_at_space ← stop_at_space; { save stop_at_space }
```

```
stop_at_space ← false; { set stop_at_space to false to allow spaces in file names }
```

```
begin_name;
```

```
for i ← str_start[s] to str_start[s + 1] - 1 do dummy ← more_name(str_pool[i]);
```

```
{ add each read character to the current file name }
```

```
stop_at_space ← save_stop_at_space; { restore stop_at_space }
```

```
end;
```

1882* **System-dependent changes for ML_TE_X.** The boolean variable *mltex_p* is set by web2c according to the given command line option (or an entry in the configuration file) before any _TE_X function is called.

⟨Global variables 13⟩ +≡
mltex_p: *boolean*;

1883* The boolean variable *mltex_enabled_p* is used to enable ML_TE_X's character substitution. It is initialized to *false*. When loading a **FMT** it is set to the value of the boolean *mltex_p* saved in the **FMT** file. Additionally it is set to the value of *mltex_p* in **Ini_TE_X**.

⟨Global variables 13⟩ +≡
mltex_enabled_p: *boolean*; {enable character substitution}

1884* ⟨Set initial values of key variables 21⟩ +≡
mltex_enabled_p ← *false*;

1885* The function *effective_char* computes the effective character with respect to font information. The effective character is either the base character part of a character substitution definition, if the character does not exist in the font or the character itself.

Inside *effective_char* we can not use *char_info* because the macro *char_info* uses *effective_char* calling this function a second time with the same arguments.

If neither the character *c* exists in font *f* nor a character substitution for *c* was defined, you can not use the function value as a character offset in *char_info* because it will access an undefined or invalid *font_info* entry! Therefore inside *char_info* and in other places, *effective_char*'s boolean parameter *err_p* is set to *true* to issue a warning and return the incorrect replacement, but always existing character *font_bc[f]*.

⟨Declare ε -TEX procedures for scanning 1683⟩ +≡

```

function effective_char(err_p : boolean; f : internal_font_number; c : quarterword): integer;
  label found;
  var base_c: integer; { or eightbits: replacement base character }
      result: integer; { or quarterword }
  begin result ← c; { return c unless it does not exist in the font }
  if  $\neg$ mltex_enabled_p then goto found;
  if font_ec[f] ≥ qo(c) then
    if font_bc[f] ≤ qo(c) then
      if char_exists(orig_char_info(f)(c)) then { N.B.: not char_info(f)(c) }
        goto found;
  if qo(c) ≥ char_sub_def_min then
    if qo(c) ≤ char_sub_def_max then
      if char_list_exists(qo(c)) then
        begin base_c ← char_list_char(qo(c)); result ← qi(base_c); { return base_c }
        if  $\neg$ err_p then goto found;
        if font_ec[f] ≥ base_c then
          if font_bc[f] ≤ base_c then
            if char_exists(orig_char_info(f)(qi(base_c))) then goto found;
          end;
  if err_p then { print error and return existing character? }
    begin begin_diagnostic; print_nl("Missing_character:_There_is_no_");
    print("substitution_for_"); print_ASCII(qo(c)); print("_in_font_"); slow_print(font_name[f]);
    print_char("!"); end_diagnostic(false); result ← qi(font_bc[f]);
    { N.B.: not non-existing character c! }
    end;
  found: effective_char ← result;
  end;

```

1886* The function *effective_char_info* is equivalent to *char_info*, except it will return *null_character* if neither the character *c* exists in font *f* nor is there a substitution definition for *c*. (For these cases *char_info* using *effective_char* will access an undefined or invalid *font_info* entry. See the documentation of *effective_char* for more information.)

⟨Declare additional functions for MLT_EX 1886*⟩ ≡

```

function effective_char_info(f : internal_font_number; c : quarterword): four_quarters;
  label exit;
  var ci: four_quarters; { character information bytes for c }
    base_c: integer; { or eightbits: replacement base character }
  begin if  $\neg$ mltex_enabled_p then
    begin effective_char_info  $\leftarrow$  orig_char_info(f)(c); return;
    end;
  if font_ec[f]  $\geq$  qo(c) then
    if font_bc[f]  $\leq$  qo(c) then
      begin ci  $\leftarrow$  orig_char_info(f)(c); { N.B.: not char_info(f)(c) }
      if char_exists(ci) then
        begin effective_char_info  $\leftarrow$  ci; return;
        end;
      end;
    if qo(c)  $\geq$  char_sub_def_min then
      if qo(c)  $\leq$  char_sub_def_max then
        if char_list_exists(qo(c)) then
          begin { effective_char_info  $\leftarrow$  char_info(f)(qi(char_list_char(qo(c))); }
          base_c  $\leftarrow$  char_list_char(qo(c));
          if font_ec[f]  $\geq$  base_c then
            if font_bc[f]  $\leq$  base_c then
              begin ci  $\leftarrow$  orig_char_info(f)(qi(base_c)); { N.B.: not char_info(f)(c) }
              if char_exists(ci) then
                begin effective_char_info  $\leftarrow$  ci; return;
                end;
              end;
            end;
          end;
        end;
      end;
    end;
  effective_char_info  $\leftarrow$  null_character;
  exit: end;

```

This code is used in section 586*.

1887* This code is called for a virtual character c in *hlist_out* during *ship_out*. It tries to build a character substitution construct for c generating appropriate DVI code using the character substitution definition for this character. If a valid character substitution exists DVI code is created as if *make_accent* was used. In all other cases the status of the substitution for this character has been changed between the creation of the character node in the *hlist* and the output of the page—the created DVI code will be correct but the visual result will be undefined.

Former MLTeX versions have replaced the character node by a sequence of character, box, and accent kern nodes splicing them into the original horizontal list. This version does not do this to avoid a) a memory overflow at this processing stage, b) additional code to add a pointer to the previous node needed for the replacement, and c) to avoid wrong code resulting in anomalies because of the use within a `\leaders` box.

```

⟨ Output a substitution, goto continue if not possible 1887* ⟩ ≡
begin ⟨ Get substitution information, check it, goto found if all is ok, otherwise goto continue 1890* ⟩;
found: ⟨ Print character substitution tracing log 1891* ⟩;
⟨ Rebuild character using substitution information 1892* ⟩;
end

```

This code is used in section 648*.

1888* pdfTeX's *pdf_hlist_out* uses a similar, but slightly modified code section of the (almost) same name.

```

⟨ (pdfTeX) Output a substitution, goto continue if not possible 1888* ⟩ ≡
begin ⟨ Get substitution information, check it, goto found if all is ok, otherwise goto continue 1890* ⟩;
found: ⟨ Print character substitution tracing log 1891* ⟩;
⟨ (pdfTeX) Rebuild character using substitution information 1893* ⟩;
end

```

This code is used in section 731*.

1889* The global variables for the code to substitute a virtual character can be declared as local. Nonetheless we declare them as global to avoid stack overflows because *hlist_out* can be called recursively.

```

⟨ Global variables 13 ⟩ +≡
accent_c, base_c, replace_c: integer;
ia_c, ib_c: four_quarters; { accent and base character information }
base_slant, accent_slant: real; { amount of slant }
base_x_height: scaled; { accent is designed for characters of this height }
base_width, base_height: scaled; { height and width for base character }
accent_width, accent_height: scaled; { height and width for accent }
delta: scaled; { amount of right shift }

```

1890* Get the character substitution information in *char_sub_code* for the character *c*. The current code checks that the substitution exists and is valid and all substitution characters exist in the font, so we can *not* substitute a character used in a substitution. This simplifies the code because we have not to check for cycles in all character substitution definitions.

⟨ Get substitution information, check it, goto *found* if all is ok, otherwise goto *continue* 1890* ⟩ ≡

```

if qo(c) ≥ char_sub_def_min then
  if qo(c) ≤ char_sub_def_max then
    if char_list_exists(qo(c)) then
      begin base_c ← char_list_char(qo(c)); accent_c ← char_list_accent(qo(c));
      if (font_ec[f] ≥ base_c) then
        if (font_bc[f] ≤ base_c) then
          if (font_ec[f] ≥ accent_c) then
            if (font_bc[f] ≤ accent_c) then
              begin ia_c ← char_info(f)(qi(accent_c)); ib_c ← char_info(f)(qi(base_c));
              if char_exists(ib_c) then
                if char_exists(ia_c) then goto found;
              end;
              begin_diagnostic; print_nl("Missing_character: Incomplete_substitution");
              print_ASCII(qo(c)); print("_="); print_ASCII(accent_c); print("_"); print_ASCII(base_c);
              print("_in_font"); slow_print(font_name[f]); print_char("!"); end_diagnostic(false);
              goto continue;
            end;
            begin_diagnostic; print_nl("Missing_character: There_is_no"); print("substitution_for");
            print_ASCII(qo(c)); print("_in_font"); slow_print(font_name[f]); print_char("!");
            end_diagnostic(false); goto continue
          end;

```

This code is used in sections 1887* and 1888*.

1891* For *tracinglostchars > 99* the substitution is shown in the log file.

⟨ Print character substitution tracing log 1891* ⟩ ≡

```

if tracing_lost_chars > 99 then
  begin begin_diagnostic; print_nl("Using_character_substitution:"); print_ASCII(qo(c));
  print("_="); print_ASCII(accent_c); print("_"); print_ASCII(base_c); print("_in_font");
  slow_print(font_name[f]); print_char("."); end_diagnostic(false);
  end

```

This code is used in sections 1887* and 1888*.

1892* This outputs the accent and the base character given in the substitution. It uses code virtually identical to the *make_accent* procedure, but without the node creation steps.

Additionally if the accent character has to be shifted vertically it does *not* create the same code. The original routine in *make_accent* and former versions of MLTeX creates a box node resulting in *push* and *pop* operations, whereas this code simply produces vertical positioning operations. This can influence the pixel rounding algorithm in some DVI drivers—and therefore will probably be changed in one of the next MLTeX versions.

```

⟨Rebuild character using substitution information 1892*⟩ ≡
  base_x_height ← x_height(f); base_slant ← slant(f)/float_constant(65536); accent_slant ← base_slant;
    { slant of accent character font }
  base_width ← char_width(f)(ib_c); base_height ← char_height(f)(height_depth(ib_c));
  accent_width ← char_width(f)(ia_c); accent_height ← char_height(f)(height_depth(ia_c));
    { compute necessary horizontal shift (don't forget slant) }
  delta ← round((base_width - accent_width)/float_constant(2) + base_height * base_slant - base_x_height *
    accent_slant); dvi_h ← cur_h; { update dvi_h, similar to the last statement in module 620 }
    { 1. For centering/horizontal shifting insert a kern node. }
  cur_h ← cur_h + delta; synch_h;
    { 2. Then insert the accent character possibly shifted up or down. }
  if ((base_height ≠ base_x_height) ∧ (accent_height > 0)) then
    begin { the accent must be shifted up or down }
      cur_v ← base_line + (base_x_height - base_height); synch_v;
      if accent_c ≥ 128 then dvi_out(set1);
      dvi_out(accent_c);
      cur_v ← base_line;
    end
  else begin synch_v;
    if accent_c ≥ 128 then dvi_out(set1);
    dvi_out(accent_c);
    end;
  cur_h ← cur_h + accent_width; dvi_h ← cur_h;
    { 3. For centering/horizontal shifting insert another kern node. }
  cur_h ← cur_h + (-accent_width - delta);
    { 4. Output the base character. }
  synch_h; synch_v;
  if base_c ≥ 128 then dvi_out(set1);
  dvi_out(base_c);
  cur_h ← cur_h + base_width; dvi_h ← cur_h { update of dvi_h is unnecessary, will be set in module 620 }

```

This code is used in section 1887*.

1893* pdfT_EX's *pdf_hlist_out* uses a similar, but slightly modified code section of the (almost) same name.

```

⟨(pdfTEX) Rebuild character using substitution information 1893*⟩ ≡
  base_x_height ← x_height(f); base_slant ← slant(f)/float_constant(65536); accent_slant ← base_slant;
  { slant of accent character font }
  base_width ← char_width(f)(ib_c); base_height ← char_height(f)(height_depth(ib_c));
  accent_width ← char_width(f)(ia_c); accent_height ← char_height(f)(height_depth(ia_c));
  { compute necessary horizontal shift (don't forget slant) }
  delta ← round(((base_width - accent_width)/float_constant(2) + base_height * base_slant - base_x_height *
  accent_slant);
  { 1. For centering/horizontal shifting insert a kern node. }
  cur_h ← cur_h + delta;
  { 2. Then insert the accent character possibly shifted up or down. }
  if ((base_height ≠ base_x_height) ∧ (accent_height > 0)) then
    begin { the accent must be shifted up or down }
      cur_v ← base_line + (base_x_height - base_height); output_one_char(accent_c); cur_v ← base_line;
    end
  else begin output_one_char(accent_c);
    end;
  cur_h ← cur_h + accent_width;
  { 3. For centering/horizontal shifting insert another kern node. }
  cur_h ← cur_h + (-accent_width - delta);
  { 4. Output the base character. }
  output_one_char(base_c); cur_h ← cur_h + base_width;

```

This code is used in section 1888*.

1894* Dumping MLT_EX-related material. This is just the flag in the format that tells us whether MLT_EX is enabled.

```

⟨Dump MLTEX-specific data 1894*⟩ ≡
  dump_int("4D4C5458); { MLTEX's magic constant: "MLTX" }
  if mltx_p then dump_int(1)
  else dump_int(0);

```

This code is used in section 1481*.

1895* Undump MLT_EX-related material, which is just a flag in the format that tells us whether MLT_EX is enabled.

```

⟨Undump MLTEX-specific data 1895*⟩ ≡
  undump_int(x); { check magic constant of MLTEX }
  if x ≠ "4D4C5458 then goto bad_fmt;
  undump_int(x); { undump mltx_p flag into mltx_enabled_p }
  if x = 1 then mltx_enabled_p ← true
  else if x ≠ 0 then goto bad_fmt;

```

This code is used in section 1482*.

1896* System-dependent changes for encTeX.

```
define encTeX_banner ≡ `␣encTeX␣v.␣Jun.␣2004`
```

1897* The boolean variable *enctex_p* is set by web2c according to the given command line option (or an entry in the configuration file) before any TeX function is called.

⟨Global variables 13⟩ +≡

```
enctex_p: boolean;
```

1898* The boolean variable *enctex_enabled_p* is used to enable encTeX's primitives. It is initialised to *false*. When loading a FMT it is set to the value of the boolean *enctex_p* saved in the FMT file. Additionally it is set to the value of *enctex_p* in IniTeX.

⟨Global variables 13⟩ +≡

```
enctex_enabled_p: boolean; { enable encTeX }
```

1899* ⟨Set initial values of key variables 21⟩ +≡

```
enctex_enabled_p ← false;
```

1900* Auxiliary functions/procedures for encT_EX (by Petr Olsak) follow. These functions implement the `\mubyte` code to convert the multibytes in *buffer* to one byte or to one control sequence. These functions manipulate a mubyte tree: each node of this tree is token list with $n+1$ tokens (first token consist the byte from the byte sequence itself and the other tokens point to the branches). If you travel from root of the tree to a leaf then you find exactly one byte sequence which we have to convert to one byte or control sequence. There are two variants of the leaf: the “definitive end” or the “middle leaf” if a longer byte sequence exists and the mubyte tree continues under this leaf. First variant is implemented as one memory word where the link part includes the token to which we have to convert and type part includes the number 60 (normal conversion) or 1.52 (insert the control sequence). The second variant of “middle leaf” is implemented as two memory words: first one has a type advanced by 64 and link points to the second word where info part includes the token to which we have to convert and link points to the next token list with the branches of the subtree.

The inverse: one byte to multi byte (for log printing and `\write` printing) is implemented via a pool. Each multibyte sequence is stored in a pool as a string and *mubyte_write*[*printed char*] points to this string.

```
define new_mubyte_node  $\equiv$  link(p)  $\leftarrow$  get_avail; p  $\leftarrow$  link(p); info(p)  $\leftarrow$  get_avail; p  $\leftarrow$  info(p)
define subinfo(#)  $\equiv$  subtype(#)
```

\langle Basic printing procedures 57 \rangle \equiv

```
{ read buffer[i] and convert multibyte. i should have been of type 0..buf_size, but web2c doesn't like
that construct in argument lists. }
```

```
function read_buffer(var i : integer): ASCII_code;
```

```
var p: pointer; last_found: integer; last_type: integer;
```

```
begin mubyte_skip  $\leftarrow$  0; mubyte_token  $\leftarrow$  0; read_buffer  $\leftarrow$  buffer[i];
```

```
if mubyte_in = 0 then
```

```
  begin if mubyte_keep > 0 then mubyte_keep  $\leftarrow$  0;
```

```
  return;
```

```
  end;
```

```
last_found  $\leftarrow$  -2;
```

```
if (i = start)  $\wedge$  ( $\neg$ mubyte_start) then
```

```
  begin mubyte_keep  $\leftarrow$  0;
```

```
  if (end_line_char  $\geq$  0)  $\wedge$  (end_line_char < 256) then
```

```
    if mubyte_read[end_line_char]  $\neq$  null then
```

```
      begin mubyte_start  $\leftarrow$  true; mubyte_skip  $\leftarrow$  -1; p  $\leftarrow$  mubyte_read[end_line_char]; goto continue;
```

```
      end;
```

```
    end;
```

```
restart: mubyte_start  $\leftarrow$  false;
```

```
if (mubyte_read[buffer[i]] = null)  $\vee$  (mubyte_keep > 0) then
```

```
  begin if mubyte_keep > 0 then decr(mubyte_keep);
```

```
  return;
```

```
  end;
```

```
p  $\leftarrow$  mubyte_read[buffer[i]];
```

```
continue: if type(p)  $\geq$  64 then
```

```
  begin last_type  $\leftarrow$  type(p) - 64; p  $\leftarrow$  link(p); mubyte_token  $\leftarrow$  info(p); last_found  $\leftarrow$  mubyte_skip;
```

```
  end
```

```
else if type(p) > 0 then
```

```
  begin last_type  $\leftarrow$  type(p); mubyte_token  $\leftarrow$  link(p); goto found;
```

```
  end;
```

```
incr(mubyte_skip);
```

```
if i + mubyte_skip > limit then
```

```
  begin mubyte_skip  $\leftarrow$  0;
```

```
  if mubyte_start then goto restart;
```

```
  return;
```

```
  end;
```

```

repeat  $p \leftarrow link(p)$ ;
  if  $subinfo(info(p)) = buffer[i + mubyte\_skip]$  then
    begin  $p \leftarrow info(p)$ ; goto continue;
    end;
until  $link(p) = null$ ;
 $mubyte\_skip \leftarrow 0$ ;
if  $mubyte\_start$  then goto restart;
if  $last\_found = -2$  then return; { no found }
 $mubyte\_skip \leftarrow last\_found$ ;
found: if  $mubyte\_token < 256$  then { multibyte to one byte }
  begin  $read\_buffer \leftarrow mubyte\_token$ ;  $mubyte\_token \leftarrow 0$ ;  $i \leftarrow i + mubyte\_skip$ ;
  if  $mubyte\_start \wedge (i \geq start)$  then  $mubyte\_start \leftarrow false$ ;
  return;
  end
else begin { multibyte to control sequence }
   $read\_buffer \leftarrow 0$ ;
  if  $last\_type = 60$  then { normal conversion }
     $i \leftarrow i + mubyte\_skip$ 
  else begin { insert control sequence }
     $decr(i)$ ;  $mubyte\_keep \leftarrow last\_type$ ;
    if  $i < start$  then  $mubyte\_start \leftarrow true$ ;
    if  $last\_type = 52$  then  $mubyte\_keep \leftarrow 10000$ ;
    if  $last\_type = 51$  then  $mubyte\_keep \leftarrow mubyte\_skip + 1$ ;
     $mubyte\_skip \leftarrow -1$ ;
    end;
  if  $mubyte\_start \wedge (i \geq start)$  then  $mubyte\_start \leftarrow false$ ;
  return;
  end;
exit: end;

```

```

1901* ⟨Declare additional routines for encTEX 1901*⟩ ≡
procedure mubyte_update; { saves new string to mubyte tree }
  var j: pool_pointer; p: pointer; q: pointer; in_mutree: integer;
  begin j ← str_start[str_ptr];
  if mubyte_read[so(str_pool[j])] = null then
    begin in_mutree ← 0; p ← get_avail; mubyte_read[so(str_pool[j])] ← p; subinfo(p) ← so(str_pool[j]);
    type(p) ← 0;
    end
  else begin in_mutree ← 1; p ← mubyte_read[so(str_pool[j])];
    end;
  incr(j);
  while j < pool_ptr do
    begin if in_mutree = 0 then
      begin new_mubyte_node; subinfo(p) ← so(str_pool[j]); type(p) ← 0;
      end
    else { in_mutree = 1 }
    if (type(p) > 0) ∧ (type(p) < 64) then
      begin type(p) ← type(p) + 64; q ← link(p); link(p) ← get_avail; p ← link(p); info(p) ← q;
      new_mubyte_node; subinfo(p) ← so(str_pool[j]); type(p) ← 0; in_mutree ← 0;
      end
    else begin if type(p) ≥ 64 then p ← link(p);
      repeat p ← link(p);
        if subinfo(info(p)) = so(str_pool[j]) then
          begin p ← info(p); goto continue;
          end;
        until link(p) = null;
        new_mubyte_node; subinfo(p) ← so(str_pool[j]); type(p) ← 0; in_mutree ← 0;
        end;
      continue: incr(j);
      end;
    if in_mutree = 1 then
      begin if type(p) = 0 then
        begin type(p) ← mubyte_prefix + 64; q ← link(p); link(p) ← get_avail; p ← link(p); link(p) ← q;
        info(p) ← mubyte_stoken; return;
        end;
      if type(p) ≥ 64 then
        begin type(p) ← mubyte_prefix + 64; p ← link(p); info(p) ← mubyte_stoken; return;
        end;
      end;
      type(p) ← mubyte_prefix; link(p) ← mubyte_stoken;
    exit: end;

procedure dispose_munode(p: pointer); { frees a mu subtree recursively }
  var q: pointer;
  begin if (type(p) > 0) ∧ (type(p) < 64) then free_avail(p)
  else begin if type(p) ≥ 64 then
    begin q ← link(p); free_avail(p); p ← q;
    end;
    q ← link(p); free_avail(p); p ← q;
    while p ≠ null do
      begin dispose_munode(info(p)); q ← link(p); free_avail(p); p ← q;
      end;
    end;
  end;

```



```

end;
procedure dispose_mutableout(cs : pointer); { frees record from out table }
  var p, q, r: pointer;
  begin p ← mubyte_cswrite[cs mod 128]; r ← null;
  while p ≠ null do
    if info(p) = cs then
      begin if r ≠ null then link(r) ← link(link(p))
      else mubyte_cswrite[cs mod 128] ← link(link(p));
      q ← link(link(p)); free_avail(link(p)); free_avail(p); p ← q;
      end
    else begin r ← link(p); p ← link(r);
    end;
  end;

```

This code is used in section 354*.

1902* The *print_buffer* procedure prints one character from *buffer*[*i*]. It also increases *i* to the next character in the buffer.

⟨ Basic printing procedures 57 ⟩ +≡

{ print one char from *buffer*[*i*]. *i* should have been of type *0..buf_size*, but web2c doesn't like that construct in argument lists. }

```

procedure print_buffer(var i : integer);
  var c: ASCII_code;
  begin if mubyte_in = 0 then print(buffer[i]) { normal TeX }
  else if mubyte_log > 0 then print_char(buffer[i])
    else begin c ← read_buffer(i);
      if mubyte_token > 0 then print_cs(mubyte_token − cs_token_flag)
      else print(c);
    end;
  incr(i);
  end;

```

1903* Additional material to dump for encTeX. This includes whether encTeX is enabled, and if it is we also have to dump the `\mubyte` arrays.

⟨ Dump encTeX-specific data 1903* ⟩ ≡

```

  dump_int("45435458); { encTeX's magic constant: "ECTX" }
  if ¬enctex_p then dump_int(0)
  else begin dump_int(1); dump_things(mubyte_read[0], 256); dump_things(mubyte_write[0], 256);
  dump_things(mubyte_cswrite[0], 128);
  end;

```

This code is used in section 1481*.

1904* Undumping the additional material we dumped for encTEX. This includes conditionally undumping the `\mubyte` arrays.

```

⟨ Undump encTEX-specific data 1904* ⟩ ≡
  undump_int(x); { check magic constant of encTEX }
  if x ≠ "45435458 then goto bad_fmt;
  undump_int(x); { undump encTex_p flag into encTex_enabled_p }
  if x = 0 then encTex_enabled_p ← false
  else if x ≠ 1 then goto bad_fmt
    else begin encTex_enabled_p ← true; undump_things(mubyte_read[0], 256);
      undump_things(mubyte_write[0], 256); undump_things(mubyte_cswrite[0], 128);
    end;

```

This code is used in section 1482*.

1905* **The Synchronize TEXnology.** This section is devoted to the *Synchronize TEXnology* - or simply *SyncTEX* - used to synchronize between input and output. This section explains how synchronization basics are implemented. Before we enter into more technical details, let us recall in a few words what is synchronization.

TEX typesetting system clearly separates the input and the output material, and synchronization will provide a new link between both that can help text editors and viewers to work together. More precisely, forwards synchronization is the ability, given a location in the input source file, to find what is the corresponding place in the output. Backwards synchronization just performs the opposite: given a location in the output, retrieve the corresponding material in the input source file.

For better code management and maintainance, we adopt a naming convention. Throughout this program, code related to the *Synchronize TEXnology* is tagged with the “*synctex*” key word. Any code extract where *SyncTEX* plays its part, either explicitly or implicitly, (should) contain the string “*synctex*”. This naming convention also holds for external files. Moreover, all the code related to *SyncTEX* is gathered in this section, except the definitions.

1906* Enabling synchronization should be performed from the command line, *synctexoption* is used for that purpose. This global integer variable is declared here but it is not used here. This is just a placeholder where the command line controller will put the *SyncTEX* related options, and the *SyncTEX* controller will read them.

1907* \langle Global variables 13 $\rangle + \equiv$
synctexoption: integer;

1908* A convenient primitive is provided: `\synctex=1` in the input source file enables synchronization whereas `\synctex=0` disables it. Its memory address is *synctex_code*. It is initialized by the *SyncTEX* controller to the command-line option if given. The controller may filter some reserved bits.

1909* \langle Put each of TEX’s primitives into the hash table 244 $\rangle + \equiv$
primitive("synctex", assign_int, int_base + synctex_code);

1910* \langle synctex case for *print_param* 1910* $\rangle \equiv$
synctex_code: print_esc("synctex");

This code is used in section 255*.

1911* In order to give the *SyncTEX* controller read and write access to the contents of the `\synctex` primitive, we declare *synctexoffset*, such that *mem[synctexoffset]* and `\synctex` correspond to the same memory storage. *synctexoffset* is initialized to the correct value when quite everything is initialized.

1912* \langle Global variables 13 $\rangle + \equiv$
synctexoffset: integer; { holds the true value of synctex_code }

1913* \langle Initialize whatever TEX might access 8* $\rangle + \equiv$
synctexoffset \leftarrow int_base + synctex_code;

1914* \langle Initialize synctex primitive 1914* $\rangle \equiv$
synctex_init_command;

This code is used in section 1513*.

1915* Synchronization is achieved with the help of an auxiliary file named ‘*jobname.synctex*’ (*jobname* is the contents of the `\jobname` macro), where a *SyncT_EX* controller implemented in the external *synctex.c* file will store geometrical information. This *SyncT_EX* controller will take care of every technical details concerning the *SyncT_EX* file, we will only focus on the messages the controller will receive from the T_EX program.

The most accurate synchronization information should allow to map any character of the input source file to the corresponding location in the output, if relevant. Ideally, the synchronization information of the input material consists of the file name, the line and column numbers of every character. The synchronization information in the output is simply the page number and either point coordinates, or box dimensions and position. The problem is that the mapping between these informations is only known at ship out time, which means that we must keep track of the input synchronization information until the pages ship out.

As T_EX only knows about file names and line numbers, but forgets the column numbers, we only consider a restricted input synchronization information called *SyncT_EX information*. It consists of a unique file name identifier, the *SyncT_EX file tag*, and the line number.

Keeping track of such information, should be different whether characters or nodes are involved. Actually, only certain nodes are involved in *SyncT_EX*, we call them *synchronized nodes*. Synchronized nodes store the *SyncT_EX* information in their last two words: the first one contains a *SyncT_EX file tag* uniquely identifying the input file, and the second one contains the current line number, as returned by the `\inputlineno` primitive. The *synctex.field.size* macro contains the necessary size to store the *SyncT_EX* information in a node.

When declaring the size of a new node, it is recommended to use the following convention: if the node is synchronized, use a definition similar to *my.synchronized.node.size=xxx+synctex.field.size*. Moreover, one should expect that the *SyncT_EX* information is always stored in the last two words of a synchronized node.

1916* By default, every node with a sufficiently big size is initialized at creation time in the *get.node* routine with the current *SyncT_EX* information, whether or not the node is synchronized. One purpose is to set this information very early in order to minimize code dependencies, including forthcoming extensions. Another purpose is to avoid the assumption that every node type has a dedicated getter, where initialization should take place. Actually, it appears that some nodes are created using directly the *get.node* routine and not the dedicated constructor. And finally, initializing the node at only one place is less error prone.

```
1917* ⟨Initialize bigger nodes with SyncTEX information 1917*⟩ ≡
  if  $s \geq \textit{medium\_node\_size}$  then
    begin sync.tag( $r + s$ ) ← synctex.tag; sync.line( $r + s$ ) ← line;
    end;
```

This code is used in section 143*.

1918* Instead of storing the input file name, it is better to store just an identifier. Each time T_EX opens a new file, it notifies the *SyncT_EX* controller with a *synctex.start.input* message. This controller will create a new *SyncT_EX* file tag and will update the current input state record accordingly. If the input comes from the terminal or a pseudo file, the *synctex.tag* is set to 0. It results in automatically disabling synchronization for material input from the terminal or pseudo files.

```
1919* ⟨Prepare new file SyncTEX information 1919*⟩ ≡
  synctex.start.input; { Give control to the SyncTEX controller }
```

This code is used in section 563*.

```
1920* ⟨Prepare terminal input SyncTEX information 1920*⟩ ≡
  synctex.tag ← 0;
```

This code is used in section 350*.

1921* \langle Prepare pseudo file *SyncTEX* information 1921* $\rangle \equiv$
`synctex_tag \leftarrow 0;`

This code is used in section 1756*.

1922* \langle Close *SyncTEX* file and write status 1922* $\rangle \equiv$
`synctex_terminate(log_opened); { Let the SyncTEX controller close its files. }`

This code is used in section 1514*.

1923* Synchronized nodes are boxes, math, kern and glue nodes. Other nodes should be synchronized too, in particular math nodes. TEX assumes that math, kern and glue nodes have the same size, this is why both are synchronized. *In fine*, only horizontal lists are really used in *SyncTEX*, but all box nodes are considered the same with respect to synchronization, because a box node type is allowed to change at execution time.

The next sections are the various messages sent to the *SyncTEX* controller. The argument is either the box or the node currently shipped out. The vertical boxes are not recorded, but the code is available for clients.

1924* \langle Start sheet *SyncTEX* information record 1924* $\rangle \equiv$
`synctex_sheet(mag);`

This code is used in section 666*.

1925* \langle Finish sheet *SyncTEX* information record 1925* $\rangle \equiv$
`synctex_teehs;`

This code is used in section 666*.

1926* \langle Start vlist *SyncTEX* information record 1926* $\rangle \equiv$
`synctex_vlist(this_box);`

This code is used in sections 657* and 738*.

1927* \langle Finish vlist *SyncTEX* information record 1927* $\rangle \equiv$
`synctex_tsilv(this_box);`

This code is used in sections 657* and 738*.

1928* \langle Start hlist *SyncTEX* information record 1928* $\rangle \equiv$
`synctex_hlist(this_box);`

This code is used in sections 647* and 729*.

1929* \langle Finish hlist *SyncTEX* information record 1929* $\rangle \equiv$
`synctex_tsilh(this_box);`

This code is used in sections 647* and 729*.

1930* \langle Record void list *SyncTEX* information 1930* $\rangle \equiv$
`if type(p) = vlist_node then
 begin synctex_void_vlist(p, this_box);
 end
 else begin synctex_void_hlist(p, this_box);
 end;`

This code is used in sections 651*, 660*, 733*, and 742*.

1931* \langle Record current point *SyncTEX* information 1931* $\rangle \equiv$
`synctex_current;`

This code is used in sections 648* and 731*.

1932* \langle Record horizontal *rule_node* or *glue_node* SyncT_EX information 1932* $\rangle \equiv$
`synctex_horizontal_rule_or_glue(p, this_box);`

This code is used in sections 650* and 732*.

1933* \langle Record *kern_node* SyncT_EX information 1933* $\rangle \equiv$
`synctex_kern(p, this_box);`

This code is used in sections 650* and 732*.

1934* \langle Record *math_node* SyncT_EX information 1934* $\rangle \equiv$
`synctex_math(p, this_box);`

This code is used in sections 650* and 732*.

1935* When making a copy of a synchronized node, we might also have to duplicate the SyncT_EX information by copying the two last words. This is the case for a *box_node* and for a *glue_node*, but not for a *math_node* nor a *kern_node*. These last two nodes always keep the SyncT_EX information they received at creation time.

1936* \langle Copy the box SyncT_EX information 1936* $\rangle \equiv$
`sync_tag(r + box_node_size) \leftarrow sync_tag(p + box_node_size);`
`sync_line(r + box_node_size) \leftarrow sync_line(p + box_node_size);`

This code is used in sections 224* and 1734*.

1937* \langle Copy the rule SyncT_EX information 1937* $\rangle \equiv$

$$\{ \text{sync_tag}(r + \text{rule_node_size}) \leftarrow \text{sync_tag}(p + \text{rule_node_size});$$

$$\text{sync_line}(r + \text{rule_node_size}) \leftarrow \text{sync_line}(p + \text{rule_node_size}); \}$$

This code is used in section 224*.

1938* \langle Copy the medium sized node SyncT_EX information 1938* $\rangle \equiv$
`sync_tag(r + medium_node_size) \leftarrow sync_tag(p + medium_node_size);`
`sync_line(r + medium_node_size) \leftarrow sync_line(p + medium_node_size);`

This code is used in sections 224* and 1734*.

1939* *Nota Bene:* The SyncT_EX code is very close to the memory model. It is not connected to any other part of the code, except for memory management. It is possible to neutralize the SyncT_EX code rather simply. The first step is to define a null *synctex_field_size*. The second step is to comment out the code in “Initialize bigger nodes...” and every “Copy ... SyncT_EX information”. The last step will be to comment out the *synctex_tag_field* related code in the definition of *synctex_tag* and the various “Prepare ... SyncT_EX information”. Then all the remaining code should be just harmless. The resulting program would behave exactly the same as if absolutely no SyncT_EX related code was there, including memory management. Of course, all this assumes that SyncT_EX is turned off from the command line.

1940* System-dependent changes.

⟨ Declare action procedures for use by *main_control* 1221 ⟩ +≡

```

procedure insert_src_special;
  var toklist, p, q: pointer;
  begin if (source_filename_stack[in_open] > 0 ∧ is_new_source(source_filename_stack[in_open], line)) then
    begin toklist ← get_avail; p ← toklist; info(p) ← cs_token_flag + frozen_special; link(p) ← get_avail;
    p ← link(p); info(p) ← left_brace_token + "{";
    q ← str_toks(make_src_special(source_filename_stack[in_open], line)); link(p) ← link(temp_head);
    p ← q; link(p) ← get_avail; p ← link(p); info(p) ← right_brace_token + "}"; ins_list(toklist);
    remember_source_info(source_filename_stack[in_open], line);
    end;
  end;
procedure append_src_special;
  var q: pointer;
  begin if (source_filename_stack[in_open] > 0 ∧ is_new_source(source_filename_stack[in_open], line)) then
    begin new_whatsit(special_node, write_node_size); write_stream(tail) ← 0; def_ref ← get_avail;
    token_ref_count(def_ref) ← null; q ← str_toks(make_src_special(source_filename_stack[in_open], line));
    link(def_ref) ← link(temp_head); write_tokens(tail) ← def_ref;
    remember_source_info(source_filename_stack[in_open], line);
    end;
  end;

```

1941* This function used to be in pdftex, but is useful in tex too.

```

function get_nullstr: str_number;
  begin get_nullstr ← "";
  end;

```

1942* Index. Here is where you can find all uses of each identifier in the program, with underlined entries pointing to where the identifier was defined. If the identifier is only one letter long, however, you get to see only the underlined entries. *All references are to section numbers instead of page numbers.*

This index also lists error messages and other aspects of the program that you might want to look up some day. For example, the entry for “system dependencies” lists all sections that should receive special attention from people who are installing TeX in a new operating environment. A list of various things that can’t happen appears under “this can’t happen”. Approximately 40 sections are listed under “inner loop”; these account for about 60% of TeX’s running time, exclusive of input and output.

The following sections were changed by the change file: 2, 4, 6, 7, 8, 11, 12, 16, 19, 20, 23, 24, 26, 27, 28, 30, 31, 32, 33, 34, 35, 37, 38, 39, 47, 49, 51, 52, 53, 54, 59, 61, 62, 71, 73, 74, 81, 82, 84, 93, 94, 95, 104, 109, 128, 129, 130, 131, 134, 143, 153, 156, 159, 162, 165, 170, 171, 174, 176, 183, 192, 194, 204, 220, 224, 227, 229, 231, 233, 237, 238, 240, 248, 254, 255, 256, 258, 259, 270, 271, 274, 276, 277, 279, 284, 287, 288, 293, 305, 312, 322, 323, 324, 326, 328, 330, 340, 346, 347, 350, 353, 354, 360, 361, 363, 365, 376, 377, 378, 379, 385, 388, 393, 398, 416, 426, 427, 440, 510, 527, 539, 540, 541, 542, 543, 544, 545, 546, 547, 549, 550, 551, 552, 556, 558, 560, 562, 563, 574, 575, 576, 577, 578, 580, 586, 587, 589, 590, 596, 600, 602, 603, 604, 608, 609, 619, 622, 624, 625, 626, 629, 645, 647, 648, 649, 650, 651, 657, 660, 666, 668, 670, 673, 729, 731, 732, 733, 738, 742, 750, 884, 897, 898, 916, 925, 1087, 1097, 1098, 1100, 1101, 1102, 1103, 1105, 1107, 1108, 1111, 1116, 1117, 1118, 1120, 1121, 1122, 1123, 1124, 1127, 1128, 1135, 1137, 1140, 1141, 1142, 1143, 1165, 1203, 1211, 1213, 1214, 1227, 1263, 1269, 1278, 1308, 1311, 1313, 1317, 1345, 1346, 1389, 1393, 1397, 1398, 1399, 1400, 1401, 1402, 1408, 1409, 1410, 1430, 1435, 1438, 1443, 1449, 1453, 1457, 1458, 1461, 1471, 1472, 1473, 1475, 1476, 1480, 1481, 1482, 1484, 1485, 1486, 1487, 1488, 1489, 1490, 1491, 1493, 1494, 1495, 1496, 1497, 1498, 1499, 1500, 1501, 1502, 1503, 1504, 1508, 1513, 1514, 1515, 1516, 1518, 1519, 1520, 1522, 1525, 1529, 1531, 1535, 1603, 1604, 1616, 1618, 1619, 1621, 1623, 1638, 1649, 1653, 1661, 1678, 1692, 1722, 1723, 1726, 1730, 1734, 1739, 1740, 1756, 1774, 1855, 1868, 1869, 1870, 1871, 1872, 1873, 1874, 1875, 1876, 1877, 1878, 1879, 1880, 1881, 1882, 1883, 1884, 1885, 1886, 1887, 1888, 1889, 1890, 1891, 1892, 1893, 1894, 1895, 1896, 1897, 1898, 1899, 1900, 1901, 1902, 1903, 1904, 1905, 1906, 1907, 1908, 1909, 1910, 1911, 1912, 1913, 1914, 1915, 1916, 1917, 1918, 1919, 1920, 1921, 1922, 1923, 1924, 1925, 1926, 1927, 1928, 1929, 1930, 1931, 1932, 1933, 1934, 1935, 1936, 1937, 1938, 1939, 1940, 1941, 1942.

** : 37* 560*
* : 192* 194* 196, 335, 382, 674, 1032, 1183, 1603*
-> : 316.
=> : 385*
??? : 59*
? : 83.
@ : 1032.
@@ : 1022.
a : 102, 122, 236, 303, 544* 545* 549* 586* 597,
678, 686, 698, 867, 898* 914, 928, 1253, 1301,
1372, 1389* 1414, 1435* 1514* 1601, 1638* 1680,
1783, 1794, 1798, 1800, 1826.
A <box> was supposed to... : 1262.
a_close : 351, 511, 512, 1453* 1514* 1623* 1627.
a_leaders : 167, 207, 653, 655, 662, 664, 735,
744, 832, 847, 1249, 1250, 1251, 1256, 1326,
1682, 1700.
a_make_name_string : 551* 560* 563*
a_open_in : 563* 1453*
a_open_out : 560* 1623*
A_token : 471.
ab_vs_cd : 122, 127.
abort : 586* 589* 590* 591, 594, 595, 596* 597,
598, 600* 602*
above : 226, 1224, 1356, 1357, 1358.
\above primitive : 1356.
above_code : 1356, 1357, 1360, 1361.
above_display_short_skip : 242, 990.
\abovedisplayshortskip primitive : 244.
above_display_short_skip_code : 242, 243, 244, 1381.
above_display_skip : 242, 990.
\abovedisplayskip primitive : 244.
above_display_skip_code : 242, 243, 244, 1381, 1384.
\abovewithdelims primitive : 1356.
abs : 66, 125, 126, 127, 204* 229* 236, 237* 444,
448, 474, 527* 637, 686, 690, 692, 693, 705, 706,
839, 851, 894, 913, 933, 934, 935, 1007, 1012,
1025, 1035, 1121* 1125, 1206, 1207, 1234, 1254,
1256, 1258, 1261, 1271, 1288, 1298, 1305, 1327,
1421, 1422, 1561, 1562, 1564, 1626, 1682, 1791.
absorbing : 327, 328* 361* 499, 1684, 1881*
acc_kern : 173, 209, 1303.
accent : 226, 287* 288* 1268, 1300, 1342, 1343.
\accent primitive : 287*
accent_c : 1889* 1890* 1891* 1892* 1893*
accent_chr : 863, 872, 914, 1343.
accent_height : 1889* 1892* 1893*
accent_noad : 863, 866, 872, 874, 909, 937,
1343, 1364.
accent_noad_size : 863, 874, 937, 1343.
accent_slant : 1889* 1892* 1893*
accent_width : 1889* 1892* 1893*
act_width : 1042, 1043, 1044, 1047, 1610.
action procedure : 1206.
active : 180, 995, 1005, 1019, 1030, 1036, 1037,
1039, 1040, 1041, 1049, 1050, 1051.

- active_base*: [238*](#), [240*](#), [270*](#), [273](#), [284*](#), [285](#), [375](#), [468](#),
[532](#), [706](#), [1330](#), [1435*](#), [1467](#), [1494*](#), [1496*](#)
active_char: [225](#), [366](#), [532](#).
active_glue: [1843](#), [1846](#), [1847](#), [1852](#), [1853](#), [1854](#).
active_height: [1147](#), [1152](#), [1153](#).
active_noconvert: [20*](#), [23*](#), [284*](#), [1457*](#), [1616*](#), [1618*](#)
active_node_size: [1021](#), [1036](#), [1040](#), [1041](#), [1843](#),
[1844](#).
active_node_size_extended: [1843](#), [1844](#).
active_node_size_normal: [995](#), [1844](#).
active_short: [1843](#), [1846](#), [1847](#), [1852](#), [1853](#), [1854](#).
active_width: [999](#), [1000](#), [1005](#), [1015](#), [1019](#), [1037](#),
[1040](#), [1042](#), [1043](#), [1044](#), [1047](#), [1147](#).
actual_looseness: [1048](#), [1049](#), [1051](#).
add_action_ref: [1537](#), [1605](#).
add_char_shrink: [828](#), [1015](#), [1018](#), [1042](#), [1043](#),
[1046](#), [1047](#).
add_char_shrink_end: [1015](#).
add_char_stretch: [828](#), [1015](#), [1018](#), [1042](#), [1043](#),
[1046](#), [1047](#).
add_char_stretch_end: [1015](#).
add_delims_to: [369](#).
add_disc_width_to_active_width: [1015](#), [1045](#).
add_disc_width_to_break_width: [1015](#), [1016](#).
add_glue_ref: [221](#), [224*](#), [456](#), [978](#), [1057](#), [1173](#), [1278*](#),
[1407](#), [1605](#), [1734*](#), [1783](#), [1821](#).
add_kern_shrink: [1015](#), [1018](#), [1042](#), [1046](#), [1047](#).
add_kern_shrink_end: [1015](#).
add_kern_stretch: [1015](#), [1018](#), [1042](#), [1046](#), [1047](#).
add_kern_stretch_end: [1015](#).
add_or_sub: [1793](#), [1794](#).
add_sa_ptr: [1820](#).
add_sa_ref: [1399*](#), [1402*](#), [1822](#), [1838](#), [1840](#), [1841](#).
add_token_ref: [221](#), [224*](#), [345](#), [1156](#), [1189](#), [1193](#),
[1399*](#), [1405](#), [1605](#), [1638*](#), [1828](#), [1829](#), [1830](#), [1831](#).
additional: [816](#), [817](#), [833](#), [848](#).
addressof: [1513*](#), [1618*](#)
adj_demerits: [254*](#), [1012](#), [1035](#).
\adjdemerits primitive: [256*](#)
adj_demerits_code: [254*](#), [255*](#), [256*](#)
adjust: [603*](#)
adjust_head: [180](#), [1065](#), [1066](#), [1254](#), [1263*](#), [1377](#),
[1383](#).
adjust_interword_glue: [705](#), [1219](#).
adjust_node: [160](#), [166](#), [193](#), [201](#), [220*](#), [224*](#), [819](#),
[825](#), [831](#), [906](#), [937](#), [1005](#), [1042](#), [1076](#), [1278*](#)
adjust_pre: [160](#), [215](#), [831](#), [1278*](#)
adjust_ptr: [160](#), [215](#), [220*](#), [224*](#), [831](#), [1278*](#)
adjust_space_factor: [1211*](#), [1215](#).
adjust_tail: [819](#), [820](#), [823](#), [825](#), [831](#), [972](#), [1065](#),
[1066](#), [1254](#), [1263*](#), [1377](#).
adjusted_hbox_group: [291](#), [1240](#), [1261](#), [1263*](#),
[1662](#), [1680](#).
adv_char_width: [687](#), [690](#), [693](#), [726](#).
adv_char_width_s: [687](#), [690](#), [693](#).
adv_char_width_s_out: [687](#), [690](#), [693](#).
adv_past: [1610](#).
advance: [227*](#), [287*](#), [288*](#), [1388](#), [1413](#), [1414](#), [1416](#).
\advance primitive: [287*](#)
advance_major_tail: [1091](#), [1094](#).
after: [165*](#), [210](#), [1374](#), [1729](#), [1740*](#)
after_assignment: [226](#), [287*](#), [288*](#), [1446](#).
\afterassignment primitive: [287*](#)
after_group: [226](#), [287*](#), [288*](#), [1449*](#)
\aftergroup primitive: [287*](#)
after_math: [1371](#), [1372](#).
after_token: [1444](#), [1445](#), [1446](#), [1447](#).
aire: [586*](#), [587*](#), [589*](#), [603*](#)
align_error: [1304](#), [1305](#).
align_group: [291](#), [944](#), [950](#), [967](#), [976](#), [1309](#), [1310](#),
[1662](#), [1680](#).
align_head: [180](#), [946](#), [953](#).
align_peek: [949](#), [950](#), [961](#), [975](#), [1226](#), [1311*](#)
align_ptr: [946](#), [947](#), [948](#).
align_stack_node_size: [946](#), [948](#).
align_state: [88](#), [331](#), [346*](#), [347*](#), [348](#), [353*](#), [361*](#), [364](#),
[369](#), [379*](#), [420](#), [421](#), [422](#), [429](#), [468](#), [501](#), [508](#), [509](#),
[512](#), [946](#), [947](#), [948](#), [950](#), [953](#), [959](#), [960](#), [961](#),
[964](#), [965](#), [967](#), [1247](#), [1272](#), [1304](#), [1305](#).
aligning: [327](#), [328*](#), [361*](#), [953](#), [965](#).
alignment of rules with characters: [616](#).
allocffnts: [706](#), [715](#), [720](#).
alpha: [586*](#), [597](#), [599](#).
alpha_file: [25](#), [50](#), [54*](#), [326*](#), [506](#), [551*](#), [1513*](#), [1523](#).
alpha_token: [464](#), [466](#).
alt_rule: [1551](#), [1552](#), [1553](#), [1557](#), [1566](#).
alter_aux: [1420](#), [1421](#).
alter_box_dimen: [1420](#), [1425](#).
alter_integer: [1420](#), [1424](#).
alter_page_so_far: [1420](#), [1423](#).
alter_prev_graf: [1420](#), [1422](#).
Ambiguous...: [1361](#).
Amble, Ole: [1102*](#)
AmSTeX: [1512](#).
any_mode: [1223](#), [1226](#), [1235](#), [1241](#), [1245](#), [1251](#),
[1275](#), [1280](#), [1282](#), [1304](#), [1312](#), [1388](#), [1446](#), [1449*](#),
[1452](#), [1454](#), [1463](#), [1468](#), [1528](#).
any_state_plus: [366](#), [367](#), [369](#).
app_display: [1381](#), [1382](#), [1383](#), [1745](#).
app_kern: [1295](#).
app_lc_hex: [48](#).
app_space: [1207](#), [1221](#).
append_bead: [1638*](#)

- append_char*: [42](#), [48](#), [58](#), [198](#), [213](#), [279*](#), [542*](#),
[551*](#), [706](#), [712](#), [717](#), [719](#), [726](#), [727](#), [868](#), [871](#),
[1116*](#), [1399*](#), [1618*](#)
append_charnode_to_t: [1085](#), [1088](#).
append_choices: [1349](#), [1350](#).
append_dest_name: [698](#).
append_discretionary: [1294](#), [1295](#).
append_glue: [1235](#), [1238](#), [1256](#).
append_italic_correction: [1290](#), [1291](#).
append_kern: [1235](#), [1239](#).
append_link: [730](#), [783](#), [1633](#), [1636](#), [1637](#).
append_list: [160](#), [975](#), [1065](#), [1254](#).
append_list_end: [160](#).
append_nl: [686](#).
append_normal_space: [1207](#).
append_penalty: [1280](#), [1281](#).
append_ptr: [698](#), [700](#).
append_src_special: [1211*](#), [1940*](#).
append_thread: [739](#), [1638*](#).
append_to_name: [545*](#), [549*](#).
append_to_vlist: [855](#), [975](#), [1065](#), [1254](#), [1745](#).
area_delimiter: [539*](#), [541*](#), [542*](#), [543*](#), [551*](#).
Argument of `\x` has...: [421](#).
arith_error: [104*](#), [105](#), [106](#), [107](#), [112](#), [114](#), [474](#), [479](#),
[486](#), [689](#), [1414](#), [1783](#), [1784](#), [1791](#), [1847](#).
Arithmetic overflow: [1414](#), [1783](#).
artificial_demerits: [1006](#), [1027](#), [1030](#), [1031](#), [1032](#).
ASCII code: [17](#), [529](#).
ASCII_code: [18](#), [19*](#), [20*](#), [29](#), [30*](#), [31*](#), [38*](#), [42](#), [54*](#),
[58](#), [60](#), [82*](#), [314](#), [363*](#), [415](#), [542*](#), [545*](#), [549*](#), [868](#),
[1069](#), [1089](#), [1098*](#), [1120*](#), [1127*](#), [1130](#), [1136](#), [1137*](#),
[1482*](#), [1513*](#), [1625](#), [1900*](#), [1902*](#).
assign_dimen: [227*](#), [266](#), [267](#), [439](#), [1388](#), [1402*](#),
[1406](#).
assign_font_dimen: [227*](#), [287*](#), [288*](#), [439](#), [1388](#), [1431](#).
assign_font_int: [227*](#), [439](#), [1388](#), [1431](#), [1432](#), [1433](#).
assign_glue: [227*](#), [244](#), [245](#), [439](#), [958](#), [1388](#),
[1402*](#), [1406](#).
assign_int: [227*](#), [256*](#), [257](#), [439](#), [1388](#), [1400*](#), [1402*](#),
[1406](#), [1415](#), [1658](#), [1702](#), [1909*](#).
assign_mu_glue: [227*](#), [244](#), [245](#), [439](#), [1388](#), [1400*](#),
[1402*](#), [1406](#), [1415](#).
assign_toks: [227*](#), [248*](#), [249](#), [251](#), [345](#), [439](#), [441](#),
[1388](#), [1402*](#), [1404](#), [1405](#), [1658](#).
assign_trace: [299](#), [300](#), [301](#).
at: [1436](#).
`\atop` primitive: [1356](#).
atop_code: [1356](#), [1357](#), [1360](#).
`\atopwithdelims` primitive: [1356](#).
attach_fraction: [474](#), [479](#), [480](#), [482](#).
attach_sign: [474](#), [475](#), [481](#).
auto_breaking: [999](#), [1038](#), [1039](#), [1042](#), [1044](#).
auto_expand: [705](#).
auto_expand_font: [705](#), [720](#).
auto_expand_vf: [712](#), [720](#).
auto_kern: [173](#), [209](#), [705](#), [1005](#).
aux: [230](#), [231*](#), [234](#), [976](#), [988](#).
aux_field: [230](#), [231*](#), [236](#), [951](#).
aux_save: [976](#), [988](#), [1384](#).
avail: [136](#), [138](#), [139](#), [140](#), [141](#), [182](#), [186](#), [1490*](#), [1491*](#).
AVAIL list clobbered...: [186](#).
avl_find_obj: [1556](#).
avl_put_obj: [698](#).
awful_bad: [1009](#), [1010](#), [1011](#), [1012](#), [1030](#), [1050](#),
[1147](#), [1151](#), [1152](#), [1164](#), [1182](#), [1183](#), [1184](#).
axis_height: [876](#), [882](#), [912](#), [922](#), [923](#), [925*](#), [938](#).
b: [388*](#), [490](#), [491](#), [496](#), [524](#), [549*](#), [586*](#), [855](#), [881](#),
[882](#), [885](#), [887](#), [891](#), [1006](#), [1147](#), [1171](#), [1376](#),
[1425](#), [1466](#), [1657](#), [1745](#), [1783](#).
b_close: [586*](#), [670*](#), [712](#), [772](#), [794](#).
b_make_name_string: [551*](#), [558*](#), [684](#).
b_open_in: [589*](#).
b_open_out: [558*](#), [684](#).
back_error: [349](#), [399](#), [422](#), [429](#), [441](#), [468](#), [472](#), [502](#),
[505](#), [529](#), [604*](#), [959](#), [1256](#), [1262](#), [1339](#), [1375](#),
[1385](#), [1390](#), [1399*](#), [1766](#), [1770](#), [1785](#).
back_input: [286](#), [303](#), [347*](#), [348](#), [349](#), [392](#), [393*](#), [394](#),
[398*](#), [401](#), [405](#), [421](#), [431](#), [433](#), [441](#), [469](#), [470](#),
[474](#), [478](#), [481](#), [487](#), [552*](#), [964](#), [1208](#), [1225](#), [1232](#),
[1242](#), [1263*](#), [1268](#), [1273](#), [1278*](#), [1302](#), [1305](#), [1308*](#),
[1310](#), [1311*](#), [1316](#), [1328](#), [1330](#), [1331](#), [1346*](#), [1393*](#),
[1399*](#), [1404](#), [1447](#), [1624](#), [1785](#), [1786](#).
back_list: [345](#), [347*](#), [359](#), [433](#), [1466](#).
backed_up: [329](#), [333](#), [334](#), [336](#), [345](#), [346*](#), [347*](#), [1203*](#).
background: [999](#), [1000](#), [1003](#), [1013](#), [1039](#), [1040](#),
[1844](#).
backup_backup: [388*](#).
backup_head: [180](#), [388*](#), [433](#).
BAD: [315](#), [316](#).
bad: [13](#), [14](#), [129*](#), [312*](#), [548](#), [1427](#), [1513*](#).
Bad `\patterns`: [1138](#).
Bad `\prevgraf`: [1422](#).
Bad character code: [460](#).
Bad delimiter code: [463](#).
Bad dump length: [497](#).
Bad file offset: [497](#).
Bad flag...: [188](#).
Bad interaction mode: [1697](#).
Bad link...: [200](#).
Bad match number: [497](#).
Bad mathchar: [462](#).
Bad number: [461](#), [1874*](#).
Bad register code: [459](#), [1812](#).
Bad space factor: [1421](#).

- bad_fmt*: [1482*](#), [1485*](#), [1487*](#), [1491*](#), [1496*](#), [1504*](#),
[1508*](#), [1895*](#), [1904*](#).
bad_tfm: [586*](#).
bad_vf: [710](#), [712](#), [714](#), [717](#), [719](#), [725](#).
badness: [108](#), [836](#), [843](#), [850](#), [854](#), [1004](#), [1028](#), [1029](#),
[1152](#), [1184](#), [1848](#), [1849](#).
\badness primitive: [442](#).
badness_code: [442](#), [450](#).
banner: [2*](#), [61*](#), [562*](#), [1478](#).
banner.k: [2*](#), [61*](#), [562*](#).
base_c: [1885*](#), [1886*](#), [1889*](#), [1890*](#), [1891*](#), [1892*](#), [1893*](#).
base_height: [1889*](#), [1892*](#), [1893*](#).
base_line: [647*](#), [651*](#), [652](#), [656](#), [729*](#), [730](#), [733*](#), [734](#),
[737](#), [1646](#), [1647](#), [1648](#), [1892*](#), [1893*](#).
base_ptr: [84*](#), [85](#), [332](#), [333](#), [334](#), [335](#), [1309](#), [1775](#),
[1776](#), [1777](#).
base_slant: [1889*](#), [1892*](#), [1893*](#).
base_width: [1889*](#), [1892*](#), [1893*](#).
base_x_height: [1889*](#), [1892*](#), [1893*](#).
baseline_skip: [242](#), [265](#), [855](#).
\baselineskip primitive: [244](#).
baseline_skip_code: [167](#), [242](#), [243](#), [244](#), [855](#).
batch_mode: [73*](#), [75](#), [86](#), [90](#), [92](#), [93*](#), [561](#), [1440](#),
[1441](#), [1443*](#), [1508*](#), [1509](#), [1514*](#), [1697](#).
\batchmode primitive: [1440](#).
bc: [566](#), [567](#), [569](#), [571](#), [586*](#), [591](#), [592](#), [596*](#), [603*](#), [706](#).
bch_label: [586*](#), [600*](#), [603*](#).
bchar: [586*](#), [600*](#), [603*](#), [1078](#), [1080](#), [1082](#), [1083](#),
[1085](#), [1088](#), [1090](#), [1093](#), [1094](#), [1209](#), [1211*](#),
[1214*](#), [1215](#), [1218](#).
bchar_label: [575*](#), [603*](#), [705](#), [706](#), [1086](#), [1093](#), [1211*](#),
[1218](#), [1501*](#), [1502*](#), [1518*](#).
be_careful: [112](#), [113](#), [114](#).
before: [165*](#), [210](#), [1374](#), [1711](#), [1713](#), [1719](#), [1729](#),
[1740*](#).
before_rejected_cur_p: [999](#), [1039](#).
begin: [7*](#), [8*](#).
begin_box: [1251](#), [1257](#), [1262](#).
begin_diagnostic: [76](#), [263](#), [306](#), [321](#), [345](#), [426*](#),
[427*](#), [528](#), [535](#), [563*](#), [608*](#), [666*](#), [669](#), [750*](#), [839](#),
[851](#), [1002](#), [1039](#), [1164](#), [1169](#), [1183](#), [1188](#), [1299](#),
[1402*](#), [1471*](#), [1475*](#), [1663](#), [1678*](#), [1692*](#), [1824](#),
[1885*](#), [1890*](#), [1891*](#).
begin_file_reading: [78](#), [87](#), [350*](#), [509](#), [563*](#), [1756*](#).
begin_group: [226](#), [287*](#), [288*](#), [1241](#).
\begingroup primitive: [287*](#).
begin_insert_or_adjust: [1275](#), [1277](#).
begin_L_code: [165*](#), [1702](#), [1703](#), [1735](#).
begin_LR_type: [165*](#), [1708](#).
begin_M: [1258](#).
begin_M_code: [165*](#), [1258](#), [1747](#).
begin_name: [538](#), [541*](#), [551*](#), [552*](#), [553](#), [557](#), [1881*](#).
begin_pseudoprint: [338](#), [340*](#), [341](#).
begin_R_code: [165*](#), [1702](#), [1703](#).
begin_reflect: [1701](#).
begin_token_list: [345](#), [381](#), [384](#), [412](#), [416*](#), [950](#),
[964](#), [965](#), [975](#), [1202](#), [1207](#), [1261](#), [1269*](#), [1317*](#),
[1323](#), [1345*](#), [1619*](#).
\beginL primitive: [1702](#).
Beginning to dump...: [1509](#).
\beginR primitive: [1702](#).
below_display_short_skip: [242](#).
\belowdisplayshortskip primitive: [244](#).
below_display_short_skip_code: [242](#), [243](#), [244](#), [1381](#).
below_display_skip: [242](#).
\belowdisplayskip primitive: [244](#).
below_display_skip_code: [242](#), [243](#), [244](#), [1381](#), [1384](#).
best_bet: [1048](#), [1050](#), [1051](#), [1053](#), [1054](#), [1854](#).
best_height_plus_depth: [1148](#), [1151](#), [1187](#), [1188](#).
best_ins_ptr: [1158](#), [1182](#), [1186](#), [1195](#), [1197](#), [1198](#).
best_line: [1048](#), [1050](#), [1051](#), [1053](#), [1065](#), [1067](#).
best_page_break: [1157](#), [1182](#), [1190](#), [1191](#).
best_pl_glue: [1843](#), [1851](#), [1852](#).
best_pl_line: [1009](#), [1021](#), [1031](#).
best_pl_short: [1843](#), [1851](#), [1852](#).
best_place: [1009](#), [1021](#), [1031](#), [1147](#), [1151](#), [1157](#).
best_size: [1157](#), [1182](#), [1194](#).
beta: [586*](#), [597](#), [599](#).
bf: [720](#).
big_op_spacing1: [877](#), [927](#).
big_op_spacing2: [877](#), [927](#).
big_op_spacing3: [877](#), [927](#).
big_op_spacing4: [877](#), [927](#).
big_op_spacing5: [877](#), [927](#).
big_switch: [227*](#), [254*](#), [1171](#), [1206](#), [1207](#), [1208](#),
[1213*](#), [1219](#).
BigEndian order: [566](#).
biggest_char: [275](#), [281](#).
billion: [653](#).
bin_noad: [858](#), [866](#), [872](#), [874](#), [904](#), [905](#), [937](#),
[1334](#), [1335](#).
bin_op_penalty: [254*](#), [937](#).
\binoppenalty primitive: [256*](#).
bin_op_penalty_code: [254*](#), [255*](#), [256*](#).
blank_line: [263](#).
bool: [496](#), [497](#).
boolean: [20*](#), [32*](#), [37*](#), [45](#), [46](#), [47*](#), [76](#), [79](#), [96](#), [104*](#),
[106](#), [107](#), [112](#), [114](#), [183*](#), [185](#), [263](#), [274*](#), [303](#), [333](#),
[363*](#), [383](#), [388*](#), [389](#), [433](#), [439](#), [466](#), [474](#), [487](#), [496](#),
[499](#), [524](#), [542*](#), [543*](#), [544*](#), [550*](#), [551*](#), [553](#), [575*](#), [586*](#),
[605](#), [619*](#), [647*](#), [657*](#), [680](#), [686](#), [687](#), [689](#), [691](#), [693](#),
[696](#), [698](#), [701](#), [702](#), [704](#), [705](#), [706](#), [720](#), [725](#), [729*](#),
[738*](#), [749](#), [750*](#), [793](#), [807](#), [817](#), [821](#), [823](#), [882](#),
[895](#), [902](#), [967](#), [991](#), [999](#), [1001](#), [1004](#), [1005](#), [1006](#),

- 1053, 1077, 1084, 1120*1127*1137*1145, 1166,
1189, 1209, 1229, 1232, 1257, 1269*1283, 1338,
1372, 1389*1414, 1459, 1482*1502*1513*1514*
1518*1523, 1538, 1551, 1556, 1618*1629, 1641,
1653*1657, 1661*1662, 1663, 1757, 1775, 1777,
1783, 1794, 1798, 1800, 1820, 1826, 1843, 1868*
1872*1881*1882*1883*1885*1897*1898*
bp: 610, 612, 613, 615, 617, 619*666*668*
Bosshard, Hans Rudolf: 484.
bot: 572.
bot_mark: 408, 409, 1189, 1193, 1810, 1829.
`\botmark` primitive: 410.
bot_mark_code: 408, 410, 411, 1810.
`\botmarks` primitive: 1810.
bottom: 693.
bottom_level: 291, 294, 303, 1242, 1246, 1662,
1680.
bottom_line: 333.
bound_default: 32*1513*
bound_name: 32*1513*
bowels: 619*
box: 248*250, 1169, 1170, 1186, 1192, 1194, 1195,
1198, 1200, 1205, 1821, 1822, 1840.
`\box` primitive: 1249.
box_base: 248*250, 251, 273, 1255.
box_code: 1249, 1250, 1257, 1285, 1288, 1862.
box_context: 1253, 1254, 1255, 1256, 1257, 1261,
1262.
box_end: 1253, 1257, 1262, 1264.
box_error: 1169, 1170, 1192, 1205.
box_flag: 1249, 1253, 1255, 1261, 1419, 1682.
box_lr: 153*643, 1705, 1715, 1716, 1746.
box_max_depth: 265, 1264.
`\boxmaxdepth` primitive: 266.
box_max_depth_code: 265, 266.
box_node: 1935*
box_node_size: 153*154, 220*224*823, 844, 891,
903, 927, 932, 1154, 1198, 1278*1288, 1379,
1734*1746, 1936*
box_ref: 228, 250, 297, 1255.
box_there: 1157, 1164, 1177, 1178.
box_val: 1402*1816, 1821, 1822, 1824, 1840.
box_val_limit: 1816, 1839.
`\box255` is not void: 1192.
bp: 484.
bp: 690.
brain: 1206.
breadth_max: 199, 200, 216, 251, 254*1005,
1520*1824.
break_node: 995, 1005, 1021, 1027, 1031, 1032,
1039, 1040, 1053, 1054.
break_penalty: 226, 287*288*1280.
break_type: 1005, 1013, 1021, 1022, 1035.
break_width: 999, 1000, 1013, 1014, 1015, 1017,
1018, 1019, 1020, 1055.
breakpoint: 1519*
broken_ins: 1158, 1163, 1187, 1198.
broken_penalty: 254*1067.
`\brokenpenalty` primitive: 256*
broken_penalty_code: 254*255*256*
broken_ptr: 1158, 1187, 1198.
buf_size: 30*31*32*35*71*129*286, 337, 350*
359*363*378*385*388*400, 550*556*560*
1513*1515*1757, 1769, 1900*1902*
buffer: 20*30*31*36, 37*45, 71*83, 87, 88, 278,
279*280, 286, 324*325, 337, 340*353*363*374,
376*377*378*382, 384, 385*388*400, 509, 510*
549*550*556*557, 560*564, 1513*1518*1520*
1649*1757, 1762, 1769, 1900*1902*
build_choices: 1351, 1352.
build_discretionary: 1296, 1297.
build_page: 976, 988, 1165*1171, 1203*1232, 1238,
1254, 1269*1272, 1278*1281, 1323, 1378.
by: 1414.
byname: 1556, 1565.
bypass_eoln: 31*
byte: 702.
byte_file: 25, 551*558*565, 680, 710, 772.
b0: 128*132, 151, 239, 275, 290, 571, 572, 576*
580*582, 590*629*710, 712, 714, 859, 861,
1488*1489*1520*1755, 1757.
b1: 128*132, 151, 239, 275, 290, 571, 572, 580*
582, 590*629*710, 712, 714, 859, 861, 1488*
1489*1520*1755, 1757.
b2: 128*132, 571, 572, 580*582, 590*629*710, 712,
714, 859, 861, 1488*1489*1520*1755, 1757.
b3: 128*132, 571, 572, 582, 590*629*710, 712,
714, 859, 861, 1488*1489*1520*1755, 1757.
c: 63, 82*162*286, 296, 314, 363*491, 496, 542*
549*549*586*604*608*609*619*705, 817,
868, 870, 882, 885, 887, 888, 914, 925*1070,
1089, 1130, 1136, 1137*1171, 1189, 1264, 1279,
1288, 1295, 1314, 1329, 1333, 1359, 1421, 1423,
1424, 1425, 1453*1457*1466, 1516*1680, 1778,
1871*1885*1886*1902*
c_leaders: 167, 208, 655, 664, 1249, 1250.
`\cleaders` primitive: 1249.
c_loc: 1089, 1093.
c_node: 1295.
cal_expand_ratio: 823, 825, 828, 834, 840, 1066.
cal_margin_kern_var: 822.
call: 228, 241, 297, 318, 388*406, 413, 421,
422, 504, 533, 1396, 1399*1403, 1404, 1405,
1474, 1773.

- call_edit*: [84*](#), [1514*](#)
- call_func*: [687](#), [692](#), [712](#), [714](#), [1538](#), [1881*](#)
- cancel_boundary*: [1207](#), [1209](#), [1210](#), [1211*](#)
- cancel_glue*: [1747](#).
- cancel_glue_cont*: [1747](#).
- cancel_glue_cont_cont*: [1747](#).
- cancel_glue_end*: [1747](#).
- cancel_glue_end_end*: [1747](#).
- cannot \read**: [510*](#)
- car_ret*: [225](#), [250](#), [364](#), [369](#), [953](#), [956](#), [957](#), [959](#), [960](#), [961](#), [964](#), [1304](#).
- carriage_return*: [22](#), [49*](#), [225](#), [250](#), [258*](#), [385*](#)
- case_shift*: [226](#), [1463](#), [1464](#), [1465](#).
- cat*: [363*](#), [376*](#), [377*](#), [378*](#)
- cat_code*: [245*](#), [250](#), [254*](#), [284*](#), [363*](#), [365*](#), [376*](#), [377*](#), [378*](#), [1518*](#)
- \catcode primitive**: [1408*](#)
- cat_code_base*: [248*](#), [250](#), [251](#), [253](#), [1408*](#), [1409*](#), [1411](#).
- cc*: [363*](#), [374](#), [377*](#), [712](#), [717](#), [718](#).
- cc*: [484](#).
- change_box*: [1154](#), [1257](#), [1288](#), [1549](#), [1822](#).
- change_if_limit*: [523](#), [524](#), [535](#).
- char*: [19*](#), [1502*](#), [1870*](#)
- \char primitive**: [287*](#)
- char_base*: [576*](#), [580*](#), [592](#), [596*](#), [603*](#), [705](#), [706](#), [1501*](#), [1502*](#), [1518*](#)
- char_box*: [885](#), [886](#), [887](#), [914](#).
- \chardef primitive**: [1400*](#)
- char_def_code*: [1400*](#), [1401*](#), [1402*](#)
- char_depth*: [580*](#), [673*](#), [828](#), [884*](#), [885](#), [888](#), [1672](#).
- char_depth_end*: [580*](#)
- char_exists*: [580*](#), [600*](#), [603*](#), [604*](#), [609*](#), [648*](#), [673*](#), [705](#), [884*](#), [898*](#), [914](#), [916*](#), [925*](#), [931](#), [1213*](#), [1770](#), [1885*](#), [1886*](#), [1890*](#)
- char_given*: [226](#), [439](#), [1112](#), [1207](#), [1215](#), [1268](#), [1302](#), [1329](#), [1332](#), [1400*](#), [1401*](#), [1402*](#)
- char_height*: [580*](#), [673*](#), [828](#), [884*](#), [885](#), [888](#), [1303](#), [1672](#), [1892*](#), [1893*](#)
- char_height_end*: [580*](#)
- char_info*: [569](#), [576*](#), [580*](#), [581](#), [583](#), [609*](#), [648*](#), [690](#), [705](#), [717](#), [726](#), [731*](#), [823](#), [828](#), [885](#), [888](#), [890](#), [891](#), [900](#), [914](#), [1017](#), [1018](#), [1042](#), [1043](#), [1046](#), [1047](#), [1086](#), [1214*](#), [1216](#), [1218](#), [1291](#), [1301](#), [1303](#), [1325](#), [1672](#), [1725](#), [1770](#), [1885*](#), [1886*](#), [1890*](#)
- char_info_end*: [580*](#)
- char_info_word*: [567](#), [569](#), [570](#).
- char_italic*: [580*](#), [885](#), [890](#), [925*](#), [931](#), [1291](#), [1672](#).
- char_italic_end*: [580*](#)
- char_kern*: [583](#), [823](#), [917](#), [929](#), [1086](#), [1218](#).
- char_kern_end*: [583](#).
- char_list_accent*: [580*](#), [1890*](#)
- char_list_char*: [580*](#), [1885*](#), [1886*](#), [1890*](#)
- char_list_exists*: [580*](#), [1885*](#), [1886*](#), [1890*](#)
- char_map_array*: [707](#).
- char_move*: [725](#), [726](#).
- char_node*: [152](#), [161](#), [163](#), [180](#), [194*](#), [574*](#), [619*](#), [648*](#), [823](#), [928](#), [1057](#), [1084](#), [1206](#), [1291](#), [1316](#).
- char_num*: [226](#), [287*](#), [288*](#), [1112](#), [1207](#), [1215](#), [1268](#), [1302](#), [1329](#), [1332](#).
- char_pw*: [823](#), [825](#).
- char_shrink*: [823](#), [1015](#).
- char_stretch*: [823](#), [1015](#).
- char_sub_code*: [248*](#), [580*](#), [609*](#), [1890*](#)
- char_sub_code_base*: [248*](#), [1402*](#)
- \charsubdef primitive**: [1400*](#)
- char_sub_def_code*: [1400*](#), [1401*](#), [1402*](#)
- char_sub_def_max*: [254*](#), [258*](#), [1402*](#), [1885*](#), [1886*](#), [1890*](#)
- \charsubdefmax primitive**: [256*](#)
- char_sub_def_max_code*: [254*](#), [255*](#), [256*](#), [1402*](#)
- char_sub_def_min*: [254*](#), [258*](#), [1402*](#), [1885*](#), [1886*](#), [1890*](#)
- \charsubdefmin primitive**: [256*](#)
- char_sub_def_min_code*: [254*](#), [255*](#), [256*](#), [1402*](#)
- char_tag*: [580*](#), [596*](#), [604*](#), [705](#), [823](#), [884*](#), [886](#), [916*](#), [917](#), [925*](#), [928](#), [1086](#), [1216](#).
- char_used_array*: [707](#), [708](#), [1502*](#), [1518*](#)
- char_warning*: [608*](#), [609*](#), [726](#), [898*](#), [1213*](#)
- char_width*: [580*](#), [648*](#), [673*](#), [690](#), [717](#), [726](#), [731*](#), [823](#), [828](#), [885](#), [890](#), [891](#), [916*](#), [1017](#), [1018](#), [1042](#), [1043](#), [1046](#), [1047](#), [1301](#), [1303](#), [1325](#), [1672](#), [1725](#), [1892*](#), [1893*](#)
- char_width_end*: [580*](#)
- character*: [152](#), [161](#), [162*](#), [192*](#), [194*](#), [224*](#), [609*](#), [648*](#), [674](#), [705](#), [731*](#), [822](#), [823](#), [825](#), [828](#), [857](#), [858](#), [859](#), [863](#), [867](#), [885](#), [891](#), [898*](#), [900](#), [925*](#), [928](#), [929](#), [1017](#), [1018](#), [1042](#), [1043](#), [1046](#), [1047](#), [1073](#), [1074](#), [1075](#), [1080](#), [1084](#), [1085](#), [1087*](#), [1088](#), [1209](#), [1211*](#), [1212](#), [1213*](#), [1214*](#), [1215](#), [1218](#), [1291](#), [1301](#), [1303](#), [1325](#), [1329](#), [1333](#), [1343](#), [1725](#), [1734*](#)
- character set dependencies: [23*](#), [49*](#)
- check sum: [568](#), [615](#).
- check_byte_range*: [596*](#), [600*](#)
- check_dimensions*: [902](#), [903](#), [909](#), [930](#).
- check_effective_tail*: [1258](#), [1283](#).
- check_existence*: [600*](#), [601](#).
- check_expand_pars*: [823](#), [1017](#), [1018](#), [1042](#), [1043](#), [1046](#), [1047](#).
- check_full_save_stack*: [295](#), [296](#), [298](#), [302](#), [1838](#).
- check_image_b*: [768](#).
- check_image_c*: [768](#).
- check_image_i*: [768](#).
- check_interrupt*: [96](#), [346*](#), [365*](#), [929](#), [1088](#), [1208](#), [1218](#).

- check_mem*: [183*](#), [185](#), [1208](#), [1520*](#)
check_outer_validity: [358](#), [373](#), [375](#), [376*](#), [379*](#),
[384](#), [401](#).
check_pdfoutput: [1538](#), [1539](#), [1540](#), [1541](#), [1542](#),
[1543](#), [1545](#), [1547](#), [1549](#), [1550](#), [1554](#), [1555](#),
[1559](#), [1561](#), [1562](#), [1564](#), [1566](#), [1568](#), [1569](#),
[1570](#), [1573](#), [1575](#), [1576](#), [1579](#), [1580](#), [1581](#), [1582](#),
[1583](#), [1589](#), [1590](#), [1591](#), [1592](#), [1594](#), [1595](#), [1596](#),
[1597](#), [1598](#), [1599](#), [1600](#).
check_pdfversion: [683](#), [698](#), [792](#), [1554](#).
check_quoted: [544*](#).
check_shrinkage: [1001](#), [1003](#), [1044](#).
checkpdfrestore: [727](#).
checkpdfsave: [727](#).
Chinese characters: [152](#), [612](#).
choice_node: [864](#), [865](#), [866](#), [874](#), [906](#).
choose_mlist: [907](#).
chr: [19*](#), [20*](#), [23*](#), [24*](#), [1400*](#)
chr_cmd: [320](#), [957](#).
chr_code: [245](#), [249](#), [257](#), [267](#), [288*](#), [320](#), [403](#), [411](#),
[437](#), [439](#), [443](#), [495](#), [514](#), [518](#), [957](#), [1161](#), [1231](#),
[1237](#), [1249](#), [1250](#), [1267](#), [1286](#), [1293](#), [1321](#), [1335](#),
[1348](#), [1357](#), [1367](#), [1387](#), [1398*](#), [1401*](#), [1409*](#), [1429](#),
[1433](#), [1439](#), [1441](#), [1451](#), [1456](#), [1465](#), [1467](#), [1470](#),
[1474](#), [1527](#), [1688](#), [1694](#), [1699](#), [1703](#), [1749](#), [1772](#),
[1833](#), [1834](#), [1862](#), [1863](#).
ci: [1886*](#).
cinttype: [32*](#), [1868*](#), [1870*](#).
clang: [230](#), [231*](#), [988](#), [1211*](#), [1269*](#), [1378](#), [1625](#), [1626](#).
clean_box: [896](#), [910](#), [911](#), [913](#), [914](#), [918](#), [920](#), [925*](#),
[926](#), [933](#), [934](#), [935](#).
clear_for_error_prompt: [78](#), [83](#), [352](#), [368](#).
clear_terminal: [34*](#), [352](#), [556*](#), [1519*](#).
clear_trie: [1135*](#).
clobbered: [185](#), [186](#), [187](#), [1618*](#).
CLOBBERED: [315](#).
close_files_and_terminate: [78](#), [81*](#), [82*](#), [1513*](#), [1514*](#).
\closein primitive: [1450](#).
close_noad: [858](#), [866](#), [872](#), [874](#), [904](#), [937](#), [938](#),
[1334](#), [1335](#).
close_node: [1522*](#), [1525*](#), [1527](#), [1529*](#), [1604*](#), [1605](#),
[1606](#), [1621*](#), [1623*](#), [1624](#).
\closeout primitive: [1525*](#).
closed: [506](#), [507](#), [509](#), [511](#), [512](#), [527*](#), [1453*](#).
clr: [913](#), [919](#), [921](#), [922](#), [932](#), [933](#), [934](#), [935](#).
\clubpenalties primitive: [1865](#).
club_penalties_loc: [248*](#), [1865](#), [1866](#).
club_penalties_ptr: [1067](#), [1865](#).
club_penalty: [254*](#), [1067](#).
\clubpenalty primitive: [256*](#).
club_penalty_code: [254*](#), [255*](#), [256*](#).
cm: [484](#).
cmd: [320](#), [712](#), [715](#), [717](#), [719](#), [725](#), [726](#), [727](#),
[1400*](#), [1467](#), [1474](#), [1833](#).
cmd_length: [712](#), [714](#), [717](#), [719](#).
co_backup: [388*](#).
code: [673*](#).
Color stack action is missing: [1540](#).
colorspace: [1553](#).
colorstack_current: [695](#), [727](#), [1540](#), [1604*](#).
colorstack_data: [695](#), [1540](#), [1604*](#), [1605](#), [1606](#).
colorstack_pop: [695](#), [727](#), [1540](#), [1604*](#).
colorstack_push: [695](#), [727](#), [1540](#), [1604*](#).
colorstack_set: [695](#), [727](#), [1540](#), [1604*](#).
colorstackcurrent: [727](#).
colorstackpop: [727](#).
colorstackpush: [727](#).
colorstackset: [727](#).
colorstackskippagestart: [727](#).
colorstackused: [727](#), [1540](#).
combine_two_deltas: [1036](#).
comment: [225](#), [250](#), [369](#).
common_ending: [15](#), [524](#), [526](#), [535](#), [823](#), [836](#), [842](#),
[843](#), [844](#), [850](#), [853](#), [854](#), [1072](#), [1080](#), [1435*](#), [1438*](#),
[1471*](#), [1473*](#), [1476*](#), [1713](#).
compare_strings: [497](#), [1538](#).
Completed box...: [666*](#), [750*](#).
compress_trie: [1126](#), [1129](#).
concat_tokens: [1578](#), [1579](#), [1580](#), [1581](#), [1582](#), [1583](#).
cond_math_glue: [167](#), [207](#), [908](#), [1349](#).
cond_ptr: [321](#), [350*](#), [384](#), [515](#), [516](#), [521](#), [522](#),
[523](#), [524](#), [526](#), [535](#), [1516*](#), [1669](#), [1692*](#), [1774*](#),
[1777](#), [1778](#).
conditional: [388*](#), [391](#), [524](#).
confusion: [95*](#), [112](#), [220*](#), [224*](#), [303](#), [523](#), [658](#), [693](#),
[727](#), [740](#), [831](#), [845](#), [904](#), [912](#), [930](#), [937](#), [942](#),
[967](#), [974](#), [976](#), [1017](#), [1018](#), [1042](#), [1046](#), [1047](#),
[1053](#), [1145](#), [1150](#), [1177](#), [1246](#), [1258](#), [1363](#),
[1378](#), [1389*](#), [1529*](#), [1604*](#), [1605](#), [1606](#), [1621*](#), [1638*](#),
[1713](#), [1726*](#), [1731](#), [1746](#).
const_chk: [1513*](#).
const_cstring: [32*](#), [560*](#).
conststringcast: [1618*](#).
continental_point_token: [464](#), [474](#).
continue: [15](#), [82*](#), [83](#), [84*](#), [88](#), [89](#), [415](#), [418](#), [419](#),
[420](#), [421](#), [423](#), [499](#), [500](#), [502](#), [647*](#), [648*](#), [725](#), [726](#),
[729*](#), [731*](#), [749](#), [823](#), [882](#), [884*](#), [950](#), [960](#), [991](#),
[1005](#), [1008](#), [1027](#), [1073](#), [1083](#), [1086](#), [1087*](#), [1088](#),
[1171](#), [1178](#), [1783](#), [1784](#), [1890*](#), [1900*](#), [1901*](#).
contrib_head: [180](#), [233*](#), [236](#), [1165*](#), [1171](#), [1172](#),
[1175](#), [1176](#), [1178](#), [1194](#), [1200](#), [1203*](#), [1487*](#).
contrib_tail: [1172](#), [1194](#), [1200](#), [1203*](#).
contribute: [1171](#), [1174](#), [1177](#), [1179](#), [1185](#), [1612](#).
conv_toks: [388*](#), [391](#), [496](#).

- conventions for representing stacks: 322*
- convert*: 228, 388*, 391, 494, 495, 496, 1650.
- convert_to_break_width*: 1019.
- `\copy` primitive: 1249.
- copy_code*: 1249, 1250, 1257, 1285, 1286, 1288, 1860, 1862.
- copy_expand_params*: 705, 720.
- copy_font_info*: 706.
- copy_node_list*: 179, 221, 222, 224*, 1257, 1288, 1636, 1637, 1746.
- copy_to_cur_active*: 1005, 1037.
- count*: 254*, 453, 666*, 668*, 750*, 1163, 1185, 1186, 1187.
- `\count` primitive: 437.
- count_base*: 254*, 257, 260, 1402*, 1415.
- `\countdef` primitive: 1400*.
- count_def_code*: 1400*, 1401*, 1402*.
- count_do_snap*: 1571, 1572, 1638*.
- cp*: 822, 1005.
- cp_skipable*: 498, 1005.
- `\cr` primitive: 956.
- cr_code*: 956, 957, 965, 967, 968.
- `\crr` primitive: 956.
- cr_cr_code*: 956, 961, 965.
- cramped*: 864, 878.
- cramped_style*: 878, 910, 913, 914.
- creationdate_given*: 807.
- Creator*: 807.
- creator_given*: 807.
- cs*: 712, 1901*.
- cs_converting*: 20*, 23*, 284*, 1616*, 1618*.
- cs_count*: 274*, 277*, 279*, 1497*, 1498*, 1515*.
- cs_error*: 1312, 1313*.
- cs_name*: 228, 287*, 288*, 388*, 391.
- `\csname` primitive: 287*.
- cs_token_flag*: 286, 311, 312*, 315, 356, 358, 359, 361*, 365*, 376*, 379*, 380, 387, 393*, 394, 395, 398*, 401, 405, 406, 407, 466, 468, 492, 532, 956, 1223, 1243, 1310, 1393*, 1399*, 1467, 1493*, 1619*, 1902*, 1940*.
- cstring*: 546*.
- cur_active_width*: 999, 1000, 1005, 1008, 1013, 1019, 1020, 1027, 1028, 1029, 1036, 1847, 1848, 1849, 1850.
- cur_align*: 946, 947, 948, 953, 954, 955, 959, 962, 964, 965, 967, 968, 971, 972, 974.
- cur_area*: 538, 543*, 551*, 555, 556*, 772, 1435*, 1438*, 1532, 1623*.
- cur_boundary*: 292, 293*, 294, 296, 304, 350*, 384, 1680, 1774*, 1775, 1778.
- cur_box*: 1252, 1253, 1254, 1255, 1256, 1257, 1258, 1259, 1260, 1262, 1264, 1265, 1840.
- cur_break*: 997, 1005, 1021, 1027, 1055, 1056, 1057, 1708.
- cur_c*: 898*, 899, 900, 914, 925*, 928, 929, 931.
- cur_chr*: 88, 286, 318, 319, 321, 354*, 359, 363*, 365*, 370, 371, 373, 374, 375, 376*, 377*, 378*, 379*, 380, 381, 382, 386, 387, 391, 394, 395, 398*, 404, 406, 407, 412, 413, 415, 429, 433, 439, 450, 454, 468, 491, 496, 498, 500, 502, 504, 505, 509, 520, 521, 524, 526, 527*, 532, 533, 534, 535, 536, 552*, 604*, 958, 961, 965, 1112, 1114, 1139, 1207, 1211*, 1213*, 1215, 1223, 1227*, 1236, 1238, 1239, 1244, 1251, 1257, 1261, 1268, 1270, 1271, 1279, 1283, 1284, 1288, 1295, 1302, 1306, 1313*, 1318, 1320, 1329, 1330, 1332, 1333, 1336, 1337, 1338, 1349, 1359, 1369, 1389*, 1390, 1391, 1395, 1396, 1399*, 1402*, 1403, 1404, 1405, 1406, 1410*, 1411, 1412, 1415, 1421, 1423, 1424, 1425, 1426, 1430*, 1431, 1443*, 1453*, 1457*, 1466, 1471*, 1516*, 1529*, 1531*, 1624, 1675, 1689, 1697, 1704, 1750, 1762, 1766, 1773, 1864.
- cur_cmd*: 88, 229*, 286, 318, 319, 321, 354*, 359, 363*, 364, 365*, 366, 370, 371, 373, 375, 376*, 379*, 380, 382, 386, 387, 388*, 391, 392, 394, 395, 398*, 406, 407, 412, 413, 429, 430, 432, 433, 439, 441, 454, 466, 468, 469, 470, 474, 478, 481, 487, 489, 500, 503, 504, 505, 509, 520, 527*, 532, 533, 552*, 604*, 953, 958, 959, 960, 961, 964, 965, 967, 1112, 1138, 1206, 1207, 1215, 1223, 1227*, 1244, 1256, 1257, 1262, 1273, 1277, 1302, 1306, 1316, 1329, 1330, 1338, 1343, 1354, 1355, 1375, 1384, 1389*, 1390, 1391, 1399*, 1404, 1405, 1406, 1414, 1415, 1430*, 1448, 1624, 1684, 1704, 1766, 1767, 1768, 1773, 1785.
- cur_cs*: 319, 354*, 355, 358, 359, 360*, 363*, 365*, 373, 375, 376*, 378*, 379*, 380, 387, 394, 395, 398*, 400, 405, 406, 407, 415, 417, 433, 498, 499, 527*, 533, 552*, 706, 950, 1223, 1330, 1393*, 1396, 1399*, 1402*, 1403, 1404, 1435*, 1449*, 1473*, 1533, 1538, 1619*, 1684, 1768, 1769, 1881*.
- cur_delta_h*: 691.
- cur_dir*: 643, 651*, 654, 656, 660*, 661, 665, 733*, 736, 737, 742*, 743, 746, 1706, 1707, 1715, 1716, 1718, 1721, 1723*, 1729, 1731, 1735, 1736, 1737, 1738, 1739*, 1740*.
- cur_ext*: 538, 543*, 551*, 555, 556*, 563*, 772, 1532, 1623*.
- cur_f*: 898*, 900, 914, 917, 925*, 928, 929, 931.
- cur_fam*: 254*, 1329, 1333, 1343.
- cur_fam_code*: 254*, 255*, 256*, 1317*, 1323.
- cur_file*: 326*, 351, 384, 563*, 564, 1756*.
- cur_font*: 248*, 250, 584, 585, 604*, 1209, 1211*, 1220, 1222, 1295, 1301, 1302, 1735.

- cur_font_loc*: [248](#)*, [250](#), [251](#), [252](#), [1395](#).
cur_font_step: [823](#), [999](#), [1003](#), [1027](#).
cur_g: [647](#)*, [653](#), [657](#)*, [662](#), [729](#)*, [735](#), [738](#)*, [744](#), [1638](#)*,
[1639](#), [1700](#), [1722](#)*, [1723](#)*, [1724](#).
cur_glue: [647](#)*, [653](#), [657](#)*, [662](#), [729](#)*, [735](#), [738](#)*, [744](#),
[1638](#)*, [1639](#), [1700](#), [1722](#)*, [1723](#)*, [1724](#).
cur_group: [292](#), [293](#)*, [294](#), [296](#), [303](#), [304](#), [976](#),
[1240](#), [1241](#), [1242](#), [1243](#), [1245](#), [1246](#), [1247](#), [1308](#)*,
[1309](#), [1318](#), [1320](#), [1369](#), [1370](#), [1371](#), [1372](#), [1378](#),
[1662](#), [1666](#), [1680](#), [1778](#).
cur_h: [643](#), [645](#)*, [646](#), [647](#)*, [648](#)*, [650](#)*, [651](#)*, [654](#), [655](#),
[656](#), [657](#)*, [660](#)*, [661](#), [665](#), [691](#), [692](#), [693](#), [725](#), [726](#),
[727](#), [729](#)*, [731](#)*, [732](#)*, [733](#)*, [734](#), [736](#), [737](#), [738](#)*, [742](#)*,
[743](#), [746](#), [752](#), [1622](#), [1631](#), [1636](#), [1638](#)*, [1642](#),
[1643](#), [1644](#), [1645](#), [1647](#), [1648](#), [1715](#), [1717](#), [1720](#),
[1721](#), [1722](#)*, [1723](#)*, [1725](#), [1726](#)*, [1730](#)*, [1892](#)*, [1893](#)*.
cur_h_offset: [644](#), [752](#), [755](#), [1629](#).
cur_head: [946](#), [947](#), [948](#), [962](#), [975](#).
cur_height: [1147](#), [1149](#), [1150](#), [1151](#), [1152](#), [1153](#),
[1613](#).
cur_i: [898](#)*, [899](#), [900](#), [914](#), [917](#), [925](#)*, [928](#), [929](#), [931](#).
cur_if: [321](#), [358](#), [515](#), [516](#), [521](#), [522](#), [1516](#)*, [1669](#),
[1692](#)*, [1777](#), [1778](#).
cur_indent: [1053](#), [1066](#).
cur_input: [35](#)*, [36](#), [87](#), [323](#)*, [324](#)*, [333](#), [343](#), [344](#),
[560](#)*, [1309](#), [1775](#), [1777](#).
cur_l: [1084](#), [1085](#), [1086](#), [1087](#)*, [1088](#), [1209](#), [1211](#)*,
[1212](#), [1213](#)*, [1214](#)*, [1216](#), [1218](#).
cur_lang: [1068](#), [1069](#), [1100](#)*, [1101](#)*, [1107](#)*, [1111](#)*, [1116](#)*,
[1121](#)*, [1140](#)*, [1269](#)*, [1378](#), [1610](#), [1611](#), [1856](#), [1859](#).
cur_length: [41](#), [198](#), [200](#), [279](#)*, [281](#), [542](#)*, [551](#)*, [645](#)*,
[727](#), [868](#), [1616](#)*, [1618](#)*.
cur_level: [292](#), [293](#)*, [294](#), [296](#), [299](#), [300](#), [302](#), [303](#),
[1483](#), [1516](#)*, [1662](#), [1666](#), [1680](#), [1778](#), [1838](#), [1840](#).
cur_line: [1053](#), [1065](#), [1066](#), [1067](#).
cur_list: [231](#)*, [234](#), [235](#), [236](#), [448](#), [1422](#), [1680](#).
cur_loop: [946](#), [947](#), [948](#), [953](#), [959](#), [968](#), [969](#), [970](#).
cur_mark: [318](#), [408](#), [412](#), [1516](#)*, [1810](#).
cur_mlist: [895](#), [896](#), [902](#), [930](#), [1372](#), [1374](#), [1377](#).
cur_mu: [879](#), [895](#), [906](#), [908](#), [942](#).
cur_name: [538](#), [543](#)*, [551](#)*, [555](#), [556](#)*, [563](#)*, [772](#), [1435](#)*,
[1436](#), [1438](#)*, [1532](#), [1623](#)*.
cur_order: [388](#)*, [465](#), [473](#), [474](#), [480](#), [488](#).
cur_p: [999](#), [1004](#), [1005](#), [1006](#), [1009](#), [1013](#), [1015](#),
[1016](#), [1021](#), [1027](#), [1028](#), [1029](#), [1031](#), [1032](#), [1033](#),
[1034](#), [1035](#), [1036](#), [1038](#), [1039](#), [1041](#), [1042](#), [1043](#),
[1044](#), [1045](#), [1048](#), [1053](#), [1054](#), [1055](#), [1056](#), [1057](#),
[1071](#), [1080](#), [1610](#), [1708](#), [1850](#), [1853](#).
cur_page_height: [644](#), [693](#), [727](#), [752](#), [755](#), [769](#), [780](#),
[1622](#), [1629](#), [1631](#), [1636](#), [1642](#).
cur_page_width: [644](#), [755](#), [769](#), [1629](#).
cur_pos: [1638](#)*,
cur_pre_head: [946](#), [947](#), [948](#), [962](#), [975](#).
cur_pre_tail: [946](#), [947](#), [948](#), [962](#), [972](#), [975](#).
cur_ptr: [412](#), [441](#), [453](#), [1402](#)*, [1404](#), [1405](#), [1415](#),
[1816](#), [1817](#), [1820](#), [1821](#), [1822](#), [1825](#), [1826](#),
[1828](#), [1831](#), [1832](#), [1840](#).
cur_q: [1084](#), [1085](#), [1087](#)*, [1088](#), [1211](#)*, [1212](#), [1213](#)*,
[1214](#)*, [1218](#).
cur_r: [1084](#), [1085](#), [1086](#), [1087](#)*, [1088](#), [1209](#), [1211](#)*,
[1214](#)*, [1215](#), [1216](#), [1218](#).
cur_rh: [1083](#), [1085](#), [1086](#), [1087](#)*.
cur_s: [620](#), [625](#)*, [626](#)*, [643](#), [647](#)*, [657](#)*, [668](#)*, [670](#)*, [729](#)*,
[730](#), [738](#)*, [739](#), [751](#), [1636](#), [1638](#)*.
cur_size: [876](#), [877](#), [879](#), [895](#), [898](#)*, [899](#), [908](#), [912](#),
[913](#), [920](#), [922](#), [923](#), [924](#), [925](#)*, [933](#), [934](#), [935](#), [938](#).
cur_span: [946](#), [947](#), [948](#), [963](#), [972](#), [974](#).
cur_style: [879](#), [895](#), [896](#), [902](#), [903](#), [906](#), [907](#), [910](#),
[911](#), [913](#), [914](#), [918](#), [920](#), [921](#), [922](#), [924](#), [925](#)*,
[926](#), [930](#), [932](#), [933](#), [934](#), [935](#), [936](#), [938](#), [939](#),
[942](#), [1372](#), [1374](#), [1377](#).
cur_tail: [946](#), [947](#), [948](#), [962](#), [972](#), [975](#).
cur_tok: [88](#), [286](#), [303](#), [319](#), [347](#)*, [348](#), [349](#), [358](#), [386](#),
[387](#), [388](#)*, [392](#), [393](#)*, [394](#), [395](#), [398](#)*, [401](#), [405](#), [406](#),
[407](#), [418](#), [419](#), [420](#), [421](#), [423](#), [425](#), [429](#), [431](#), [433](#),
[466](#), [467](#), [468](#), [470](#), [471](#), [474](#), [478](#), [500](#), [502](#), [503](#),
[505](#), [509](#), [520](#), [529](#), [532](#), [959](#), [960](#), [1215](#), [1223](#),
[1225](#), [1263](#)*, [1273](#), [1278](#)*, [1305](#), [1306](#), [1308](#)*, [1310](#),
[1311](#)*, [1346](#)*, [1393](#)*, [1399](#)*, [1446](#), [1447](#), [1449](#)*, [1619](#)*,
[1620](#), [1684](#), [1762](#), [1768](#), [1770](#), [1773](#), [1785](#), [1786](#).
cur_v: [643](#), [646](#), [647](#)*, [651](#)*, [652](#), [656](#), [657](#)*, [659](#), [660](#)*,
[661](#), [663](#), [664](#), [665](#), [668](#)*, [692](#), [693](#), [725](#), [726](#),
[727](#), [729](#)*, [733](#)*, [734](#), [737](#), [738](#)*, [741](#), [742](#)*, [743](#),
[745](#), [746](#), [752](#), [1622](#), [1631](#), [1638](#)*, [1642](#), [1643](#),
[1644](#), [1645](#), [1647](#), [1648](#), [1892](#)*, [1893](#)*.
cur_v_offset: [644](#), [752](#), [755](#), [1629](#).
cur_val: [286](#), [287](#)*, [356](#), [388](#)*, [412](#), [436](#), [439](#), [440](#)*,
[441](#), [445](#), [446](#), [447](#), [449](#), [450](#), [451](#), [452](#), [453](#),
[455](#), [456](#), [457](#), [459](#), [460](#), [461](#), [462](#), [463](#), [464](#),
[465](#), [466](#), [468](#), [470](#), [471](#), [473](#), [474](#), [476](#), [477](#),
[479](#), [481](#), [483](#), [484](#), [486](#), [487](#), [488](#), [489](#), [491](#),
[492](#), [497](#), [498](#), [508](#), [517](#), [527](#)*, [529](#), [530](#), [535](#),
[579](#), [604](#)*, [605](#), [606](#), [607](#), [693](#), [705](#), [706](#), [720](#),
[817](#), [956](#), [958](#), [1112](#), [1154](#), [1207](#), [1215](#), [1238](#),
[1239](#), [1251](#), [1255](#), [1260](#), [1277](#), [1279](#), [1281](#), [1301](#),
[1302](#), [1329](#), [1332](#), [1338](#), [1339](#), [1343](#), [1360](#), [1366](#),
[1399](#)*, [1402](#)*, [1403](#), [1404](#), [1405](#), [1406](#), [1407](#), [1410](#)*,
[1412](#), [1414](#), [1415](#), [1416](#), [1417](#), [1418](#), [1419](#), [1421](#),
[1422](#), [1423](#), [1424](#), [1425](#), [1426](#), [1431](#), [1436](#), [1437](#),
[1453](#)*, [1475](#)*, [1525](#)*, [1531](#)*, [1538](#), [1540](#), [1545](#), [1547](#),
[1550](#), [1553](#), [1555](#), [1557](#), [1559](#), [1564](#), [1566](#), [1567](#),
[1574](#), [1576](#), [1586](#), [1588](#), [1590](#), [1594](#), [1626](#), [1652](#),
[1666](#), [1669](#), [1672](#), [1675](#), [1684](#), [1689](#), [1695](#), [1697](#),
[1770](#), [1781](#), [1783](#), [1786](#), [1804](#), [1805](#), [1812](#), [1820](#),

- 1821, 1822, 1825, 1840, 1867, 1874*
cur_val_level: 388* [436](#), [439](#), [441](#), [445](#), [446](#), [447](#),
[449](#), [450](#), [453](#), [455](#), [456](#), [465](#), [475](#), [477](#), [481](#), [487](#),
[491](#), [492](#), [497](#), [1538](#), [1675](#), [1781](#), [1783](#).
cur_width: [1053](#), [1066](#).
current page: [1157](#).
current_character_being_worked_on: [596](#)*
\currentgrouplevel primitive: [1664](#).
current_group_level_code: [1664](#), [1665](#), [1666](#).
\currentgroupstype primitive: [1664](#).
current_group_type_code: [1664](#), [1665](#), [1666](#).
\currentifbranch primitive: [1667](#).
current_if_branch_code: [1667](#), [1668](#), [1669](#).
\currentiflevel primitive: [1667](#).
current_if_level_code: [1667](#), [1668](#), [1669](#).
\currentifttype primitive: [1667](#).
current_if_type_code: [1667](#), [1668](#), [1669](#).
cv_backup: [388](#)*
cvl_backup: [388](#)*
c1: [793](#).
c2: [793](#).
d: [107](#), [194](#)* [195](#), [278](#), [363](#)* [466](#), [586](#)* [689](#), [823](#), [844](#),
[855](#), [882](#), [991](#), [1006](#), [1053](#), [1121](#)* [1147](#), [1246](#),
[1264](#), [1316](#), [1376](#), [1618](#)* [1684](#), [1745](#), [1798](#), [1800](#).
d_fixed: [635](#), [636](#).
danger: [1372](#), [1373](#), [1377](#).
data: [228](#), [250](#), [1395](#), [1402](#)* [1410](#)* [1412](#).
data structure assumptions: [179](#), [182](#), [222](#), [643](#),
[992](#), [1145](#), [1158](#), [1467](#), [1734](#)*
date_and_time: [259](#)*
dateandtime: [259](#)*
day: [254](#)* [259](#)* [645](#)* [792](#), [1509](#).
\day primitive: [256](#)*
day_code: [254](#)* [255](#)* [256](#)*
dd: [484](#).
dd: [689](#), [690](#).
deactivate: [1005](#), [1027](#), [1030](#).
dead_cycles: [445](#), [619](#)* [620](#), [666](#)* [750](#)* [1189](#), [1201](#),
[1202](#), [1232](#), [1420](#), [1424](#).
\deadcycles primitive: [442](#).
debug: [7](#)* [9](#), [78](#), [84](#)* [93](#)* [132](#), [183](#)* [184](#), [185](#),
[190](#), [1208](#), [1519](#)*
debug #: [1519](#)*
debug_format_file: [1485](#)* [1498](#)* [1872](#)*
debug_help: [78](#), [84](#)* [93](#)* [1519](#)*
debugging: [7](#)* [84](#)* [96](#), [132](#), [183](#)* [200](#), [1208](#), [1519](#)*
decent_fit: [993](#), [1010](#), [1028](#), [1029](#), [1040](#), [1848](#), [1849](#).
decr: [42](#), [44](#), [64](#), [71](#)* [86](#), [88](#), [89](#), [90](#), [92](#), [102](#), [124](#),
[138](#), [139](#), [141](#), [193](#), [195](#), [218](#), [219](#), [223](#), [235](#), [263](#),
[279](#)* [282](#), [303](#), [304](#), [333](#), [344](#), [346](#)* [347](#)* [348](#), [351](#),
[353](#)* [369](#), [378](#)* [379](#)* [382](#), [384](#), [388](#)* [420](#), [425](#), [427](#)*
[448](#), [455](#), [468](#), [496](#), [503](#), [509](#), [520](#), [535](#), [543](#)* [560](#)*
[563](#)* [564](#), [594](#), [603](#)* [628](#), [647](#)* [657](#)* [666](#)* [670](#)* [671](#),
[674](#), [686](#), [690](#), [698](#), [702](#), [712](#), [717](#), [719](#), [725](#), [726](#),
[729](#)* [738](#)* [750](#)* [793](#), [892](#), [893](#), [979](#), [984](#), [1005](#),
[1016](#), [1034](#), [1045](#), [1059](#), [1092](#), [1093](#), [1107](#)* [1108](#)*
[1117](#)* [1118](#)* [1121](#)* [1125](#), [1142](#)* [1238](#), [1298](#), [1305](#),
[1309](#), [1352](#), [1364](#), [1372](#), [1422](#), [1471](#)* [1490](#)* [1516](#)*
[1518](#)* [1537](#), [1636](#), [1680](#), [1684](#), [1692](#)* [1729](#), [1734](#)*
[1740](#)* [1755](#), [1757](#), [1775](#), [1776](#), [1777](#), [1778](#), [1781](#),
[1783](#), [1820](#), [1822](#), [1873](#)* [1877](#)* [1900](#)*
def: [227](#)* [1386](#), [1387](#), [1388](#), [1391](#), [1396](#).
\def primitive: [1386](#).
def_code: [227](#)* [439](#), [1388](#), [1408](#)* [1409](#)* [1410](#)*
def_family: [227](#)* [439](#), [604](#)* [1388](#), [1408](#)* [1409](#)* [1412](#).
def_font: [227](#)* [287](#)* [288](#)* [439](#), [604](#)* [1388](#), [1434](#).
def_ref: [327](#), [328](#)* [496](#), [497](#), [499](#), [508](#), [727](#), [1137](#)*
[1279](#), [1396](#), [1404](#), [1457](#)* [1466](#), [1533](#), [1535](#)*
[1538](#), [1539](#), [1540](#), [1541](#), [1545](#), [1549](#), [1553](#),
[1557](#), [1559](#), [1564](#), [1566](#), [1567](#), [1579](#), [1580](#), [1581](#),
[1582](#), [1583](#), [1588](#), [1590](#), [1591](#), [1592](#), [1600](#), [1616](#)*
[1618](#)* [1684](#), [1881](#)* [1940](#)*
def_tounicode: [1588](#).
default_code: [859](#), [873](#), [919](#), [1360](#).
default_hyphen_char: [254](#)* [603](#)*
\defaulthyphenchar primitive: [256](#)*
default_hyphen_char_code: [254](#)* [255](#)* [256](#)*
default_res: [1553](#).
default_rule: [489](#).
default_rule_thickness: [859](#), [877](#), [910](#), [911](#), [913](#),
[919](#), [921](#), [935](#).
default_skew_char: [254](#)* [603](#)*
\defaultskewchar primitive: [256](#)*
default_skew_char_code: [254](#)* [255](#)* [256](#)*
defecation: [624](#)*
define: [706](#), [1255](#), [1392](#), [1395](#), [1396](#), [1399](#)* [1402](#)*
[1403](#), [1406](#), [1410](#)* [1412](#), [1426](#), [1435](#)* [1840](#).
defining: [327](#), [328](#)* [361](#)* [499](#), [508](#).
del_code: [254](#)* [258](#)* [1338](#).
\delcode primitive: [1408](#)*
del_code_base: [254](#)* [258](#)* [260](#), [1408](#)* [1410](#)* [1411](#).
delete_action_ref: [1537](#), [1564](#), [1580](#), [1606](#).
delete_glue_ref: [219](#), [220](#)* [297](#), [477](#), [491](#), [605](#), [705](#),
[908](#), [978](#), [992](#), [1002](#), [1057](#), [1153](#), [1173](#), [1181](#),
[1194](#), [1199](#), [1278](#)* [1407](#), [1414](#), [1417](#), [1516](#)*
[1606](#), [1781](#), [1783](#), [1791](#), [1792](#), [1795](#), [1804](#),
[1805](#), [1822](#), [1839](#), [1854](#).
delete_image: [778](#).
delete_last: [1282](#), [1283](#).
delete_q: [902](#), [936](#), [939](#).
delete_sa_ptr: [1820](#), [1822](#), [1826](#).
delete_sa_ref: [1822](#), [1835](#), [1840](#), [1841](#), [1842](#).
delete_token_ref: [218](#), [220](#)* [297](#), [346](#)* [497](#), [764](#),
[1154](#), [1156](#), [1189](#), [1193](#), [1516](#)* [1537](#), [1538](#), [1553](#),

- 1564, 1588, 1591, 1592, 1600, 1606, 1638*, 1827, 1828, 1829, 1831, 1832, 1839, 1881*.
- delete_toks*: 756, 763, 764, 772, 778, 789, 804, 806, 807, 814, 815.
- deletions_allowed*: 76, 77, 84*, 85, 98, 358, 368.
- delim_num*: 225, 287*, 288*, 1224, 1329, 1332, 1338.
- delim_ptr*: 230, 231*, 1363, 1369.
- delimited_code*: 1356, 1357, 1360, 1361.
- delimiter*: 863, 872, 938, 1369.
- \delimiter* primitive: 287*.
- delimiter_factor*: 254*, 938.
- \delimiterfactor* primitive: 256*.
- delimiter_factor_code*: 254*, 255*, 256*.
- delimiter_shortfall*: 265, 938.
- \delimitershortfall* primitive: 266.
- delimiter_shortfall_code*: 265, 266.
- delim1*: 876, 924.
- delim2*: 876, 924.
- delta*: 103, 902, 904, 909, 911, 912, 913, 914, 918, 919, 921, 922, 923, 924, 925*, 926, 930, 931, 932, 935, 938, 1171, 1185, 1187, 1301, 1303, 1889*, 1892*, 1893*.
- delta_node*: 998, 1006, 1008, 1019, 1020, 1036, 1037, 1041, 1050, 1051.
- delta_node_size*: 998, 1019, 1020, 1036, 1037, 1041.
- delta1*: 919, 922, 938.
- delta2*: 919, 922, 938.
- den*: 612, 614, 617.
- denom*: 476, 484.
- denom_style*: 878, 920.
- denominator*: 859, 866, 873, 874, 920, 1359, 1363.
- denom1*: 876, 920.
- denom2*: 876, 920.
- deplorable*: 1151, 1182.
- depth*: 489.
- depth*: 153*, 154, 156*, 157, 158, 202, 205, 206, 489, 580*, 644, 650*, 652, 654, 659, 660*, 663, 669, 732*, 734, 736, 741, 742*, 745, 752, 755, 823, 827, 832, 844, 846, 855, 864, 880, 882, 885, 889, 903, 906, 907, 911, 912, 913, 921, 922, 923, 925*, 926, 927, 932, 934, 935, 944, 945, 977, 982, 986, 1005, 1065, 1150, 1179, 1186, 1187, 1198, 1265, 1278*, 1549, 1553, 1557, 1566, 1631, 1638*, 1720, 1746.
- depth_base*: 576*, 580*, 592, 598, 705, 706, 1501*, 1502*, 1518*.
- depth_index*: 569, 580*.
- depth_offset*: 153*, 442, 945, 1425.
- depth_threshold*: 199, 200, 216, 251, 254*, 868, 1005, 1520*, 1824.
- dest_name_entry*: 698, 793, 1513*, 1628, 1629.
- dest_names*: 697, 698, 793, 804, 805, 1513*, 1629.
- dest_names_size*: 697, 698, 1513*, 1514*, 1629.
- destroy_marks*: 1516*, 1826, 1832.
- dests*: 804, 1514*.
- destrxyz*: 695.
- \detokenize* primitive: 1687.
- dig*: 54*, 64, 65, 67, 102, 478, 686, 702.
- digit_sensed*: 1137*, 1138, 1139.
- \dimexpr* primitive: 1779.
- dimen*: 265, 453, 1185, 1187.
- \dimen* primitive: 437.
- dimen_base*: 238*, 254*, 265, 266, 267, 268, 269, 270*, 1248, 1323.
- \dimendef* primitive: 1400*.
- dimen_def_code*: 1400*, 1401*, 1402*.
- dimen_par*: 265, 673*.
- dimen_pars*: 265.
- dimen_val*: 436, 437, 439, 441, 442, 443, 444, 446, 447, 450, 451, 453, 454, 455, 475, 481, 491, 1415, 1675, 1779, 1780, 1786, 1791, 1793, 1796, 1799, 1816, 1821, 1824, 1833.
- dimen_val_limit*: 1816, 1822, 1823, 1838, 1842.
- Dimension too large: 486.
- direct_always*: 497, 693, 695, 1539, 1604*.
- direct_page*: 497, 693, 695, 1539, 1604*.
- dirty Pascal: 3, 132, 190, 200, 204*, 307, 988, 1512.
- disc_break*: 1053, 1056, 1057, 1058, 1067.
- disc_group*: 291, 1295, 1296, 1297, 1662, 1680.
- disc_node*: 163, 166, 193, 201, 220*, 224*, 674, 823, 825, 906, 937, 993, 995, 1005, 1032, 1034, 1042, 1057, 1091, 1217, 1258.
- disc_ptr*: 1516*, 1860, 1864.
- disc_width*: 1015, 1046.
- discard_or_move*: 1145.
- discretionary*: 226, 1268, 1292, 1293, 1294.
- Discretionary list is too long: 1298.
- \discretionary* primitive: 1292.
- Display math...with \$\$: 1375.
- display_indent*: 265, 976, 1316, 1323, 1377, 1745.
- \displayindent* primitive: 266.
- display_indent_code*: 265, 266, 1323.
- \displaylimits* primitive: 1334.
- display_mlist*: 865, 871, 874, 907, 1352.
- display_style*: 864, 870, 907, 1347, 1377.
- \displaystyle* primitive: 1347.
- \displaywidowpenalties* primitive: 1865.
- display_widow_penalties_loc*: 248*, 1865, 1866.
- display_widow_penalties_ptr*: 1067, 1865.
- display_widow_penalty*: 254*, 990, 1067.
- \displaywidowpenalty* primitive: 256*.
- display_widow_penalty_code*: 254*, 255*, 256*.
- display_width*: 265, 1316, 1323, 1377, 1745.
- \displaywidth* primitive: 266.
- display_width_code*: 265, 266, 1323.

- dispose_munode*: [1399*](#), [1901*](#)
dispose_mutableout: [1399*](#), [1901*](#)
div: [100](#), [655](#), [664](#).
divide: [227*](#), [287*](#), [288*](#), [1388](#), [1413](#), [1414](#).
`\divide` primitive: [287*](#)
divide_scaled: [687](#), [689](#), [690](#), [692](#), [693](#), [792](#),
[834](#), [840](#).
dlist: [643](#), [983](#), [1372](#), [1380](#), [1705](#), [1715](#), [1716](#), [1746](#).
do_all_eight: [999](#), [1005](#), [1008](#), [1013](#), [1019](#), [1020](#),
[1036](#), [1037](#), [1040](#).
do_all_six: [999](#), [1147](#), [1164](#).
do_annot: [1631](#), [1640](#), [1646](#).
do_assignments: [976](#), [1301](#), [1384](#), [1448](#).
do_char: [710](#), [725](#), [726](#).
do_dest: [1638*](#), [1640](#), [1646](#).
do_endv: [1308*](#), [1309](#).
do_extension: [1528](#), [1529*](#), [1624](#).
do_final_end: [81*](#), [82*](#), [1513*](#)
do_last_line_fit: [1021](#), [1022](#), [1027](#), [1028](#), [1031](#),
[1039](#), [1040](#), [1843](#), [1844](#), [1854](#).
do_link: [1561](#), [1636](#), [1646](#).
do_marks: [1154](#), [1189](#), [1516*](#), [1826](#).
do_nothing: [16*](#), [34*](#), [57](#), [58](#), [84*](#), [193](#), [297](#), [366](#), [379*](#)
[497](#), [564](#), [595](#), [636](#), [638](#), [639](#), [650*](#), [659](#), [687](#),
[732*](#), [741](#), [793](#), [825](#), [845](#), [868](#), [904](#), [909](#), [937](#),
[1013](#), [1042](#), [1076](#), [1223](#), [1399*](#), [1414](#), [1553](#), [1604*](#),
[1621*](#), [1623*](#), [1638*](#), [1646](#), [1881*](#)
do_one_seven_eight: [999](#), [1016](#), [1045](#).
do_pdf_font: [801](#).
do_register_command: [1413](#), [1414](#).
do_seven_eight: [999](#).
do_snapv: [1638*](#), [1640](#).
do_snapv_comp: [1638*](#), [1640](#).
do_subst_font: [822](#), [823](#), [825](#), [828](#).
do_thread: [1638*](#), [1640](#), [1646](#).
do_vf: [712](#), [720](#), [726](#).
do_vf_packet: [721](#), [725](#), [726](#).
doing_leaders: [619*](#), [620](#), [656](#), [665](#), [737](#), [746](#),
[1623*](#), [1631](#), [1638*](#)
done: [15](#), [47*](#), [220*](#), [303](#), [304](#), [333](#), [406](#), [415](#), [423](#),
[466](#), [471](#), [474](#), [479](#), [484](#), [499](#), [500](#), [502](#), [508](#),
[509](#), [520](#), [552*](#), [556*](#), [557](#), [563*](#), [586*](#), [593](#), [603*](#),
[642](#), [666*](#), [668*](#), [669](#), [698](#), [702](#), [706](#), [750*](#), [751](#),
[802](#), [874](#), [902](#), [914](#), [916*](#), [936](#), [937](#), [950](#), [953](#),
[991](#), [1005](#), [1013](#), [1039](#), [1049](#), [1053](#), [1057](#), [1072](#),
[1083](#), [1086](#), [1088](#), [1108*](#), [1137*](#), [1138](#), [1147](#), [1151](#),
[1154](#), [1156](#), [1171](#), [1174](#), [1175](#), [1182](#), [1257](#), [1258](#),
[1259](#), [1288](#), [1297](#), [1299](#), [1316](#), [1324](#), [1389*](#), [1405](#),
[1430*](#), [1514*](#), [1538](#), [1606](#), [1680](#), [1724](#), [1730*](#), [1737](#),
[1738](#), [1739*](#), [1740*](#), [1762](#), [1800](#), [1864](#).
done_with_noad: [902](#), [903](#), [904](#), [909](#), [930](#).
done_with_node: [902](#), [903](#), [906](#), [907](#), [930](#).
done1: [15](#), [185](#), [186](#), [415](#), [425](#), [474](#), [478](#), [499](#), [500](#),
[750*](#), [804](#), [914](#), [917](#), [950](#), [959](#), [991](#), [1005](#), [1028](#),
[1053](#), [1055](#), [1071](#), [1073](#), [1076](#), [1137*](#), [1142*](#), [1171](#),
[1174](#), [1177](#), [1481*](#), [1494*](#), [1514*](#).
done2: [15](#), [185](#), [187](#), [474](#), [484](#), [485](#), [499](#), [504](#), [950](#),
[960](#), [991](#), [1073](#), [1481*](#), [1495*](#).
done3: [15](#), [991](#), [1074](#), [1075](#).
done4: [15](#), [991](#), [1076](#).
done5: [15](#), [991](#), [1042](#), [1045](#).
done6: [15](#).
dont_expand: [228](#), [277*](#), [379*](#), [393*](#)
double: [111](#), [113](#), [119](#).
Double subscript: [1355](#).
Double superscript: [1355](#).
double_hyphen_demerits: [254*](#), [1035](#).
`\doublehyphendemerits` primitive: [256*](#)
double_hyphen_demerits_code: [254*](#), [255*](#), [256*](#)
Doubly free location...: [187](#).
down_ptr: [632](#), [633](#), [634](#), [642](#).
downdate_width: [1036](#).
down1: [612](#), [613](#), [634](#), [636](#), [637](#), [640](#), [641](#), [643](#),
[719](#), [726](#).
down2: [612](#), [621](#), [637](#).
down3: [612](#), [637](#).
down4: [612](#), [637](#).
`\dp` primitive: [442](#).
dry rot: [95*](#)
ds: [712](#).
dummy: [1881*](#)
dummy_xchr: [1482*](#), [1876*](#)
dummy_xord: [1482*](#), [1876*](#)
dummy_xprn: [1482*](#), [1876*](#)
`\dump...only` by INITEX: [1516*](#)
`\dump` primitive: [1230](#).
dump_core: [1519*](#)
dump_four_ASCII: [1488*](#)
dump_hh: [1497*](#)
dump_int: [1486*](#), [1488*](#), [1490*](#), [1492](#), [1494*](#), [1495*](#),
[1497*](#), [1499*](#), [1503*](#), [1505](#), [1507](#), [1655](#), [1894*](#), [1903*](#)
dump_line: [32*](#), [1518*](#)
dump_name: [32*](#), [61*](#)
dump_option: [32*](#)
dump_qqqq: [1488*](#)
dump_things: [1486*](#), [1488*](#), [1490*](#), [1494*](#), [1495*](#), [1497*](#),
[1499*](#), [1501*](#), [1503*](#), [1875*](#), [1903*](#)
dumpimagemeta: [1505](#).
dumpunicode: [1505](#).
Duplicate pattern: [1140*](#)
dvi length exceeds...: [625*](#), [626*](#), [668*](#)
dvi_buf: [621](#), [622*](#), [624*](#), [625*](#), [634](#), [640](#), [641](#), [1513*](#)
dvi_buf_size: [14](#), [32*](#), [621](#), [622*](#), [623](#), [625*](#), [626*](#), [634](#),
[640](#), [641](#), [668*](#), [670*](#), [1513*](#)

- dvi_f*: [643](#), [645*](#), [648*](#), [649*](#)
dvi_file: [558*](#), [619*](#), [622*](#), [624*](#), [625*](#), [670*](#)
DVI files: [610](#).
dvi_font_def: [629*](#), [649*](#), [671](#).
dvi_four: [627](#), [629*](#), [637](#), [645*](#), [652](#), [661](#), [668*](#), [670*](#), [1616*](#)
dvi_gone: [621](#), [622*](#), [623](#), [625*](#), [639](#), [668*](#)
dvi_h: [643](#), [645*](#), [647*](#), [648*](#), [651*](#), [652](#), [656](#), [657*](#), [660*](#), [665](#), [1892*](#)
dvi_index: [621](#).
dvi_limit: [621](#), [622*](#), [623](#), [625*](#), [626*](#), [668*](#)
dvi_offset: [621](#), [622*](#), [623](#), [625*](#), [626*](#), [628](#), [632](#), [634](#), [640](#), [641](#), [647*](#), [657*](#), [668*](#), [670*](#)
dvi_out: [625*](#), [627](#), [628](#), [629*](#), [630](#), [636](#), [637](#), [645*](#), [647*](#), [648*](#), [649*](#), [652](#), [657*](#), [661](#), [668*](#), [670*](#), [1616*](#), [1892*](#)
dvi_pop: [628](#), [647*](#), [657*](#)
dvi_ptr: [621](#), [622*](#), [623](#), [625*](#), [626*](#), [628](#), [634](#), [647*](#), [657*](#), [668*](#), [670*](#)
dvi_ship_out: [666*](#), [791](#).
dvi_swap: [625*](#)
dvi_v: [643](#), [645*](#), [647*](#), [651*](#), [656](#), [657*](#), [660*](#), [665](#).
dvi_x: [691](#).
dvi_y: [691](#).
dw: [823](#).
dyn_used: [135](#), [138](#), [139](#), [140](#), [141](#), [182](#), [667](#), [1490*](#), [1491*](#)
e: [299](#), [301](#), [524](#), [544*](#), [545*](#), [556*](#), [1376](#), [1389*](#), [1414](#), [1662](#), [1663](#), [1745](#), [1783](#), [1840](#), [1841](#).
easy_line: [995](#), [1011](#), [1023](#), [1024](#), [1026](#).
ec: [566](#), [567](#), [569](#), [571](#), [586*](#), [591](#), [592](#), [596*](#), [603*](#), [609*](#), [706](#).
\edef primitive: [1386](#).
edge: [647*](#), [651*](#), [654](#), [657*](#), [663](#), [729*](#), [733*](#), [736](#), [738*](#), [745](#), [1647](#), [1648](#).
edge_dist: [1720](#), [1721](#), [1723*](#), [1730*](#)
edge_node: [643](#), [1720](#), [1721](#), [1726*](#), [1737](#).
edge_node_size: [1720](#).
edit_file: [84*](#)
edit_line: [84*](#), [1514*](#), [1868*](#)
edit_name_length: [84*](#), [1514*](#), [1868*](#)
edit_name_start: [84*](#), [1514*](#), [1868*](#), [1869*](#)
ef: [823](#).
\efcode primitive: [1432](#).
ef_code_base: [173](#), [452](#), [1431](#), [1432](#), [1433](#).
effective_char: [580*](#), [609*](#), [1213*](#), [1885*](#), [1886*](#)
effective_char_info: [1213*](#), [1886*](#)
eight_bit_p: [24*](#), [32*](#), [1876*](#)
eight_bits: [25](#), [64](#), [130*](#), [319](#), [575*](#), [586*](#), [597](#), [604*](#), [608*](#), [609*](#), [622*](#), [634](#), [673*](#), [680](#), [686](#), [690](#), [696](#), [704](#), [705](#), [707](#), [712](#), [725](#), [823](#), [882](#), [885](#), [888](#), [1169](#), [1170](#), [1466](#), [1502*](#), [1513*](#), [1518*](#)
eightbits: [1885*](#), [1886*](#)
eject_penalty: [175](#), [1005](#), [1007](#), [1027](#), [1035](#), [1049](#), [1147](#), [1149](#), [1151](#), [1182](#), [1187](#), [1188](#).
el_gordo: [111](#), [112](#), [114](#).
\pdfelapsedtime primitive: [442](#).
elapsed_time_code: [442](#), [443](#), [450](#).
else: [10](#).
\else primitive: [517](#).
else_code: [515](#), [517](#), [524](#), [1669](#).
em: [481](#).
Emergency stop: [93*](#)
emergency_stretch: [265](#), [1004](#), [1039](#).
\emergencystretch primitive: [266](#).
emergency_stretch_code: [265](#), [266](#).
empty: [16*](#), [233*](#), [447](#), [857](#), [861](#), [863](#), [868](#), [898*](#), [899](#), [914](#), [925*](#), [927](#), [928](#), [930](#), [931](#), [932](#), [1157](#), [1163](#), [1164](#), [1168](#), [1178](#), [1185](#), [1354](#), [1355](#), [1364](#).
empty line at end of file: [512](#), [564](#).
empty_field: [860](#), [861](#), [862](#), [918](#), [1341](#), [1343](#), [1359](#).
empty_flag: [142](#), [144](#), [148](#), [168](#), [182](#), [1491*](#)
encTeX_banner: [560*](#), [1518*](#), [1896*](#)
encTeX_enabled_p: [256*](#), [560*](#), [1518*](#), [1898*](#), [1899*](#), [1904*](#)
encTeX_p: [256*](#), [287*](#), [1397*](#), [1408*](#), [1897*](#), [1898*](#), [1903*](#), [1904*](#)
end: [7*](#), [8*](#), [10](#).
End of file on the terminal: [37*](#), [71*](#)
(\end occurred...): [1516*](#)
\end primitive: [1230](#).
end_cs_name: [226](#), [287*](#), [288*](#), [398*](#), [1312](#), [1399*](#), [1768](#).
\endcsname primitive: [287*](#)
end_diagnostic: [263](#), [306](#), [321](#), [345](#), [426*](#), [427*](#), [528](#), [535](#), [563*](#), [608*](#), [666*](#), [669](#), [750*](#), [839](#), [851](#), [1002](#), [1039](#), [1164](#), [1169](#), [1183](#), [1188](#), [1299](#), [1402*](#), [1477](#), [1663](#), [1824](#), [1885*](#), [1890*](#), [1891*](#)
end_file_reading: [351](#), [352](#), [382](#), [384](#), [509](#), [563*](#), [1516*](#)
end_graf: [1203*](#), [1263*](#), [1272](#), [1274](#), [1278*](#), [1309](#), [1311*](#), [1346*](#)
end_group: [226](#), [287*](#), [288*](#), [1241](#).
\endgroup primitive: [287*](#)
\endinput primitive: [402](#).
end_L_code: [165*](#), [1702](#), [1703](#), [1706](#), [1735](#).
end_line_char: [87](#), [254*](#), [258*](#), [325](#), [340*](#), [354*](#), [382](#), [384](#), [509](#), [560*](#), [564](#), [1518*](#), [1900*](#)
\endlinechar primitive: [256*](#)
end_line_char_code: [254*](#), [255*](#), [256*](#)
end_line_char_inactive: [382](#), [384](#), [509](#), [564](#), [1518*](#)
end_link: [1636](#), [1646](#).
end_LR: [165*](#), [210](#), [1709](#), [1712](#), [1718](#), [1729](#), [1738](#), [1740*](#)
end_LR_type: [165*](#), [1706](#), [1709](#), [1712](#), [1718](#), [1729](#), [1738](#), [1740*](#)
end_M: [1258](#).

end_M_code: [165*](#), [450](#), [1706](#), [1747](#).
end_match: [225](#), [311](#), [313](#), [316](#), [417](#), [418](#), [420](#).
end_match_token: [311](#), [415](#), [417](#), [418](#), [419](#), [420](#),
[500](#), [502](#), [508](#).
\endmubyte primitive: [287*](#)
end_name: [538](#), [543*](#), [551*](#), [552*](#), [557](#).
end_R_code: [165*](#), [1702](#), [1706](#).
end_reflect: [1701](#).
end_span: [180](#), [944](#), [955](#), [969](#), [973](#), [977](#), [979](#).
end_template: [228](#), [388*](#), [401](#), [406](#), [956](#), [1474](#), [1773](#).
end_template_token: [956](#), [960](#), [966](#).
end_thread: [1638*](#), [1640](#).
end_token_list: [346*](#), [347*](#), [379*](#), [416*](#), [1203*](#), [1516*](#),
[1619*](#)
end_write: [240*](#), [379*](#), [1617](#), [1619*](#)
\endwrite: [1617](#).
end_write_token: [393*](#), [1619*](#), [1620](#).
endcases: [10](#).
endif: [7*](#), [8*](#), [668*](#), [670*](#)
endifn: [670*](#)
\endL primitive: [1702](#).
\endR primitive: [1702](#).
endtemplate: [956](#).
endv: [225](#), [320](#), [401](#), [406](#), [944](#), [956](#), [958](#), [967](#),
[1224](#), [1308*](#), [1309](#).
engine_name: [11*](#), [1486*](#), [1487*](#)
ensure_dvi_open: [558*](#), [645*](#)
ensure_pdf_open: [683](#), [684](#).
ensure_vbox: [1170](#), [1186](#), [1195](#).
eof: [26*](#), [31*](#), [590*](#), [772](#).
eof_seen: [350*](#), [384](#), [1513*](#), [1661*](#)
eoln: [31*](#)
eop: [610](#), [612](#), [613](#), [615](#), [668*](#), [670*](#)
epdf_orig_x: [498](#), [1638*](#)
epdf_orig_y: [498](#), [1638*](#)
epochseconds: [680](#), [1518*](#), [1556](#), [1585](#), [1587](#).
eq_define: [299](#), [300](#), [301](#), [398*](#), [958](#), [1248](#), [1392](#).
eq_destroy: [297](#), [299](#), [301](#), [305*](#)
eq_level: [239](#), [240*](#), [246](#), [250](#), [254*](#), [271*](#), [277*](#), [286](#),
[299](#), [301](#), [305*](#), [956](#), [1154](#), [1487*](#), [1494*](#), [1617](#),
[1821](#), [1822](#).
eq_level_field: [239](#).
eq_no: [226](#), [1318](#), [1319](#), [1321](#), [1322](#), [1680](#).
\eqno primitive: [1319](#).
eq_save: [298](#), [299](#), [300](#).
eq_type: [228](#), [239](#), [240*](#), [241](#), [246](#), [250](#), [271*](#), [277*](#),
[284*](#), [286](#), [287*](#), [289](#), [299](#), [301](#), [373](#), [375](#), [376*](#),
[379*](#), [380](#), [398*](#), [415](#), [417](#), [956](#), [1330](#), [1487*](#),
[1494*](#), [1617](#), [1768](#).
eq_type_field: [239](#), [297](#).
eq_word_define: [300](#), [301](#), [1248](#), [1317*](#), [1323](#), [1392](#).
eqtb: [2*](#), [133](#), [181](#), [238*](#), [239](#), [240*](#), [241](#), [242](#), [246](#),
[248*](#), [250](#), [254*](#), [258*](#), [260](#), [265](#), [268](#), [269](#), [270*](#), [271*](#),
[273](#), [274*](#), [275](#), [284*](#), [286](#), [287*](#), [288*](#), [289](#), [290](#),
[292](#), [294](#), [296](#), [297](#), [298](#), [299](#), [300](#), [301](#), [303](#),
[304](#), [305*](#), [306](#), [307](#), [308](#), [311](#), [313](#), [319](#), [320](#),
[327](#), [329](#), [354*](#), [355](#), [376*](#), [415](#), [439](#), [440*](#), [499](#),
[517](#), [574*](#), [579](#), [706](#), [956](#), [990](#), [1366](#), [1386](#), [1400*](#),
[1415](#), [1431](#), [1435*](#), [1487*](#), [1494*](#), [1495*](#), [1496*](#), [1513*](#),
[1518*](#), [1520*](#), [1525*](#), [1526](#), [1650](#), [1824](#), [1836](#).
eqtb_size: [238*](#), [265](#), [268](#), [270*](#), [271*](#), [272](#), [274*](#), [279*](#),
[284*](#), [305*](#), [312*](#), [1393*](#), [1486*](#), [1487*](#), [1495*](#), [1496*](#),
[1497*](#), [1498*](#), [1513*](#).
eqtb_top: [240*](#), [270*](#), [274*](#), [284*](#), [1393*](#), [1487*](#), [1513*](#)
equiv: [239](#), [240*](#), [241](#), [242](#), [246](#), [247](#), [248*](#), [250](#), [251](#),
[252](#), [253](#), [271*](#), [273](#), [277*](#), [284*](#), [286](#), [287*](#), [289](#),
[297](#), [299](#), [301](#), [373](#), [375](#), [376*](#), [379*](#), [380](#), [439](#),
[440*](#), [441](#), [534](#), [604*](#), [706](#), [956](#), [1330](#), [1405](#), [1415](#),
[1467](#), [1487*](#), [1494*](#), [1617](#), [1659](#), [1865](#), [1867](#).
equiv_field: [239](#), [297](#), [307](#), [1835](#).
err_help: [79](#), [248*](#), [1461*](#), [1462](#).
\errhelp primitive: [248*](#)
err_help_loc: [248*](#)
\errmessage primitive: [1455](#).
err_p: [1885*](#)
error: [72](#), [75](#), [76](#), [78](#), [79](#), [82*](#), [88](#), [91](#), [93*](#), [98](#), [121](#),
[349](#), [360*](#), [368](#), [396](#), [424](#), [434](#), [444](#), [454](#), [471](#), [480](#),
[482](#), [485](#), [486](#), [497](#), [501](#), [502](#), [512](#), [526](#), [536](#),
[549*](#), [561](#), [587*](#), [593](#), [606](#), [608*](#), [669](#), [899](#), [952](#),
[960](#), [968](#), [1002](#), [1113](#), [1114](#), [1137*](#), [1138](#), [1139](#),
[1140*](#), [1153](#), [1155](#), [1169](#), [1181](#), [1186](#), [1201](#), [1204](#),
[1228](#), [1242](#), [1244](#), [1246](#), [1247](#), [1258](#), [1260](#), [1273](#),
[1277](#), [1284](#), [1288](#), [1298](#), [1299](#), [1306](#), [1307](#), [1313*](#),
[1337](#), [1344](#), [1355](#), [1361](#), [1370](#), [1373](#), [1391](#), [1399*](#),
[1403](#), [1410*](#), [1414](#), [1415](#), [1419](#), [1430*](#), [1437](#), [1461*](#),
[1462](#), [1471*](#), [1540](#), [1620](#), [1657](#), [1783](#).
error_context_lines: [254*](#), [333](#).
\errorcontextlines primitive: [256*](#)
error_context_lines_code: [254*](#), [255*](#), [256*](#)
error_count: [76](#), [77](#), [82*](#), [86](#), [1274](#), [1471*](#)
error_line: [14](#), [32*](#), [58](#), [328*](#), [333](#), [337](#), [338](#), [339](#),
[1513*](#)
error_message_issued: [76](#), [82*](#), [95*](#)
error_stop_mode: [72](#), [73*](#), [74*](#), [82*](#), [83](#), [93*](#), [98](#), [686](#),
[1440](#), [1461*](#), [1471*](#), [1473*](#), [1476*](#), [1508*](#), [1516*](#), [1697](#).
\errorstopmode primitive: [1440](#).
escape: [225](#), [250](#), [366](#), [378*](#), [1518*](#)
escape_char: [254*](#), [258*](#), [261](#).
\escapechar primitive: [256*](#)
escape_char_code: [254*](#), [255*](#), [256*](#)
escapehex: [497](#).
escapename: [497](#).
escapestring: [497](#).

- ETC: 314.
 etc: 200.
eTeX_aux: 230, [231](#)*, [233](#)*, [234](#).
eTeX_aux_field: [230](#), [231](#)*, [1680](#).
eTeX_banner: [2](#)*
etex_convert_base: [494](#).
etex_convert_codes: [494](#).
eTeX_dim: [442](#), [450](#), [1670](#), [1673](#), [1802](#).
eTeX_enabled: [1657](#), [1704](#).
eTeX_ex: 202, 296, 299, 300, 304, 348, [562](#)*, [608](#)*,
[653](#), [666](#)*, [735](#), [750](#)*, [1323](#), [1389](#)*, [1390](#), [1391](#),
[1490](#)*, [1491](#)*, [1516](#)*, [1518](#)*, [1653](#)*, [1656](#), [1715](#),
[1716](#), [1717](#), [1735](#).
eTeX_expr: [442](#), [1779](#), [1780](#), [1781](#).
eTeX_glue: [442](#), [450](#), [1806](#).
eTeX_int: [442](#), [1650](#), [1664](#), [1667](#), [1802](#).
etex_int_base: [254](#)*
etex_int_pars: [254](#)*
eTeX_mode: [1649](#)*, [1653](#)*, [1654](#), [1655](#), [1656](#).
eTeX_mu: [442](#), [1781](#), [1806](#).
etex_p: [1649](#)*, [1653](#)*
etex_pen_base: [248](#)*, [250](#), [251](#).
etex_pens: [248](#)*, [250](#), [251](#).
eTeX_revision: [2](#)*, [498](#).
`\eTeXrevision` primitive: [1650](#).
eTeX_revision_code: [494](#), [495](#), [497](#), [498](#), [1650](#).
eTeX_state: [1650](#), [1655](#), [1701](#).
eTeX_state_base: [1650](#), [1702](#).
eTeX_state_code: [254](#)*, [1650](#), [1701](#).
eTeX_states: [2](#)*, [254](#)*, [1655](#).
eTeX_text_offset: [329](#).
etex_toks: [248](#)*
etex_toks_base: [248](#)*
eTeX_version: [2](#)*, [1652](#).
`\eTeXversion` primitive: [1650](#).
eTeX_version_code: [442](#), [1650](#), [1651](#), [1652](#).
eTeX_version_string: [2](#)*
every_cr: [248](#)*, [950](#), [975](#).
`\everycr` primitive: [248](#)*
every_cr_loc: [248](#)*, [249](#).
every_cr_text: [329](#), [336](#), [950](#), [975](#).
every_display: [248](#)*, [1323](#).
`\everydisplay` primitive: [248](#)*
every_display_loc: [248](#)*, [249](#).
every_display_text: [329](#), [336](#), [1323](#).
every_eof: [384](#), [1659](#).
`\everyeof` primitive: [1658](#).
every_eof_loc: [248](#)*, [329](#), [1658](#), [1659](#).
every_eof_text: [329](#), [336](#), [384](#).
every_hbox: [248](#)*, [1261](#).
`\everyhbox` primitive: [248](#)*
every_hbox_loc: [248](#)*, [249](#).
every_hbox_text: [329](#), [336](#), [1261](#).
every_job: [248](#)*, [1207](#).
`\everyjob` primitive: [248](#)*
every_job_loc: [248](#)*, [249](#).
every_job_text: [329](#), [336](#), [1207](#).
every_math: [248](#)*, [1317](#)*
`\everymath` primitive: [248](#)*
every_math_loc: [248](#)*, [249](#).
every_math_text: [329](#), [336](#), [1317](#)*
every_par: [248](#)*, [1269](#)*
`\everypar` primitive: [248](#)*
every_par_loc: [248](#)*, [249](#), [329](#), [1404](#).
every_par_text: [329](#), [336](#), [1269](#)*
every_vbox: [248](#)*, [1261](#), [1345](#)*
`\everyvbox` primitive: [248](#)*
every_vbox_loc: [248](#)*, [249](#).
every_vbox_text: [329](#), [336](#), [1261](#), [1345](#)*
 ex: 481.
ex_hyphen_penalty: 163, [254](#)*, [1045](#).
`\exhyphenpenalty` primitive: [256](#)*
ex_hyphen_penalty_code: [254](#)*, [255](#)*, [256](#)*
ex_ratio: 823.
ex_space: [226](#), [287](#)*, [288](#)*, [1207](#), [1268](#).
exactly: [816](#), [817](#), [891](#), [1066](#), [1154](#), [1194](#), [1240](#),
[1379](#), [1681](#).
exit: [15](#), [16](#)*, [37](#)*, [47](#)*, [58](#), [59](#)*, [69](#), [82](#)*, [122](#), [143](#)*, [200](#),
[284](#)*, [299](#), [300](#), [314](#), [363](#)*, [415](#), [433](#), [439](#), [487](#),
[491](#), [496](#), [523](#), [524](#), [550](#)*, [604](#)*, [609](#)*, [634](#), [642](#),
[749](#), [793](#), [823](#), [844](#), [928](#), [967](#), [1005](#), [1072](#), [1111](#)*,
[1121](#)*, [1125](#), [1154](#), [1171](#), [1189](#), [1207](#), [1232](#), [1257](#),
[1283](#), [1288](#), [1291](#), [1297](#), [1329](#), [1337](#), [1352](#), [1389](#)*,
[1414](#), [1448](#), [1482](#)*, [1516](#)*, [1519](#)*, [1662](#), [1773](#), [1820](#),
[1822](#), [1878](#)*, [1886](#)*, [1900](#)*, [1901](#)*
expand: [32](#)*, [380](#), [388](#)*, [392](#), [394](#), [397](#), [406](#), [407](#), [465](#),
[493](#), [504](#), [524](#), [536](#), [958](#), [1683](#), [1773](#), [1879](#)*
expand_after: [228](#), [287](#)*, [288](#)*, [388](#)*, [391](#), [1763](#).
`\expandafter` primitive: [287](#)*
expand_depth: [32](#)*, [388](#)*, [1513](#)*, [1783](#), [1879](#)*
expand_depth_count: [388](#)*, [1783](#), [1879](#)*, [1880](#)*
expand_font: [705](#), [823](#).
expand_font_name: [705](#).
expand_ratio: [705](#).
`\expanded` primitive: [494](#).
expanded_code: [494](#), [495](#), [497](#).
explicit: [173](#), [674](#), [893](#), [1013](#), [1042](#), [1044](#), [1055](#),
[1236](#), [1291](#), [1712](#).
expr_a: [1793](#), [1795](#).
expr_add: [1784](#), [1785](#).
expr_add_sub: [1793](#).
expr_d: [1797](#).
expr_div: [1784](#), [1785](#), [1796](#), [1797](#).
expr_e_field: [1789](#), [1790](#).

- expr_m*: [1796](#).
expr_mult: [1784](#), [1785](#), [1796](#).
expr_n_field: [1789](#), [1790](#).
expr_node_size: [1789](#), [1790](#).
expr_none: [1784](#), [1785](#), [1792](#), [1793](#).
expr_s: [1799](#).
expr_scale: [1784](#), [1796](#), [1799](#).
expr_sub: [1784](#), [1785](#), [1791](#), [1793](#).
expr_t_field: [1789](#), [1790](#).
ext_bot: [572](#), [889](#), [890](#).
ext_delimiter: [539](#)*, [541](#)*, [542](#)*, [543](#)*, [551](#)*
ext_mid: [572](#), [889](#), [890](#).
ext_rep: [572](#), [889](#), [890](#).
ext_tag: [570](#), [595](#), [604](#)*, [705](#), [884](#)*, [886](#).
ext_top: [572](#), [889](#), [890](#).
ext_xn_over_d: [823](#), [1553](#), [1638](#)*
exten: [570](#).
exten_base: [576](#)*, [592](#), [600](#)*, [601](#), [603](#)*, [705](#), [706](#),
[889](#), [1501](#)*, [1502](#)*, [1518](#)*
extensible_recipe: [567](#), [572](#).
extension: [226](#), [1525](#)*, [1527](#), [1528](#), [1624](#).
 extensions to TeX: [2](#)*, [164](#), [1521](#).
 Extra \else: [536](#).
 Extra \endcsname: [1313](#)*
 Extra \endmubyte: [1313](#)*
 Extra \fi: [536](#).
 Extra \middle.: [1370](#).
 Extra \or: [526](#), [536](#).
 Extra \right.: [1370](#).
 Extra }, or forgotten x: [1247](#).
 Extra alignment tab...: [968](#).
 Extra x: [1244](#).
extra_info: [945](#), [964](#), [965](#), [967](#), [968](#).
extra_mem_bot: [32](#)*, [1487](#)*, [1513](#)*
extra_mem_top: [32](#)*, [1487](#)*, [1513](#)*
extra_right_brace: [1246](#), [1247](#).
extra_space: [573](#), [584](#), [1222](#).
extra_space_code: [573](#), [584](#).
 eyes and mouth: [354](#)*
e1: [793](#).
e2: [793](#).
f: [112](#), [114](#), [162](#)*, [474](#), [551](#)*, [586](#)*, [604](#)*, [605](#), [608](#)*, [609](#)*
[619](#)*, [629](#)*, [706](#), [720](#), [725](#), [823](#), [882](#), [885](#), [887](#),
[888](#), [891](#), [892](#), [893](#), [914](#), [1006](#), [1038](#), [1246](#), [1291](#),
[1301](#), [1316](#), [1389](#)*, [1435](#)*, [1783](#), [1800](#), [1885](#)*, [1886](#)*
fabs: [204](#)*
false: [23](#)*, [31](#)*, [37](#)*, [45](#), [46](#), [47](#)*, [51](#)*, [59](#)*, [76](#), [80](#), [88](#), [89](#),
[98](#), [106](#), [107](#), [112](#), [115](#), [184](#), [185](#), [186](#), [187](#), [256](#)*,
[284](#)*, [286](#), [296](#), [303](#), [306](#), [321](#), [333](#), [340](#)*, [345](#), [349](#),
[350](#)*, [353](#)*, [358](#), [368](#), [376](#)*, [383](#), [384](#), [387](#), [390](#), [400](#),
[426](#)*, [427](#)*, [433](#), [441](#), [451](#), [453](#), [466](#), [467](#), [471](#), [473](#),
[474](#), [475](#), [481](#), [486](#), [487](#), [488](#), [491](#), [498](#), [511](#), [527](#)*
[528](#), [531](#), [533](#), [535](#), [538](#), [541](#)*, [542](#)*, [543](#)*, [544](#)*, [550](#)*
[551](#)*, [552](#)*, [554](#), [563](#)*, [564](#), [589](#)*, [608](#)*, [609](#)*, [620](#), [681](#),
[683](#), [685](#), [686](#), [688](#), [689](#), [692](#), [693](#), [698](#), [702](#),
[705](#), [706](#), [720](#), [726](#), [727](#), [749](#), [753](#), [769](#), [775](#),
[793](#), [794](#), [795](#), [797](#), [799](#), [801](#), [802](#), [804](#), [805](#),
[807](#), [823](#), [882](#), [896](#), [898](#)*, [930](#), [950](#), [967](#), [1002](#),
[1004](#), [1005](#), [1013](#), [1027](#), [1030](#), [1039](#), [1057](#), [1063](#),
[1080](#), [1083](#), [1087](#)*, [1088](#), [1128](#)*, [1131](#), [1137](#)*, [1138](#),
[1139](#), [1140](#)*, [1143](#)*, [1145](#), [1164](#), [1167](#), [1183](#), [1188](#),
[1197](#), [1198](#), [1203](#)*, [1208](#), [1210](#), [1211](#)*, [1212](#), [1213](#)*
[1218](#), [1229](#), [1232](#), [1239](#), [1258](#), [1274](#), [1279](#), [1345](#)*
[1360](#), [1361](#), [1369](#), [1370](#), [1372](#), [1377](#), [1399](#)*, [1402](#)*
[1404](#), [1405](#), [1414](#), [1436](#), [1448](#), [1457](#)*, [1460](#), [1461](#)*
[1466](#), [1482](#)*, [1502](#)*, [1504](#)*, [1517](#), [1518](#)*, [1523](#), [1524](#),
[1533](#), [1535](#)*, [1538](#), [1553](#), [1556](#), [1565](#), [1566](#), [1579](#),
[1580](#), [1582](#), [1583](#), [1601](#), [1616](#)*, [1618](#)*, [1619](#)*, [1623](#)*
[1624](#), [1630](#), [1631](#), [1640](#), [1646](#), [1649](#)*, [1657](#), [1663](#),
[1683](#), [1757](#), [1770](#), [1775](#), [1777](#), [1783](#), [1794](#), [1798](#),
[1800](#), [1821](#), [1822](#), [1824](#), [1825](#), [1844](#), [1847](#), [1854](#),
[1856](#), [1857](#), [1869](#)*, [1881](#)*, [1883](#)*, [1884](#)*, [1885](#)*, [1890](#)*
[1891](#)*, [1898](#)*, [1899](#)*, [1900](#)*, [1904](#)*
false_bchar: [1209](#), [1211](#)*, [1215](#).
fam: [857](#), [858](#), [859](#), [863](#), [867](#), [898](#)*, [899](#), [928](#), [929](#),
[1329](#), [1333](#), [1343](#).
 \fam primitive: [256](#)*
fam_fnt: [248](#)*, [876](#), [877](#), [883](#), [898](#)*, [1373](#).
fam_in_range: [1329](#), [1333](#), [1343](#).
fast_delete_glue_ref: [219](#), [220](#)*, [1700](#).
fast_get_avail: [140](#), [224](#)*, [397](#), [700](#), [822](#), [823](#),
[1211](#)*, [1215](#).
fast_store_new_token: [397](#), [425](#), [490](#), [492](#).
 Fatal format file error: [1482](#)*
fatal_error: [71](#)*, [93](#)*, [346](#)*, [379](#)*, [382](#), [510](#)*, [556](#)*, [561](#),
[625](#)*, [626](#)*, [668](#)*, [958](#), [965](#), [967](#), [1309](#).
fatal_error_stop: [76](#), [77](#), [82](#)*, [93](#)*, [1513](#)*, [1514](#)*
fbyte: [590](#)*, [594](#), [597](#), [602](#)*
feof: [602](#)*
 Ferguson, Michael John: [2](#)*
fetch: [898](#)*, [900](#), [914](#), [917](#), [925](#)*, [928](#), [931](#).
fetch_box: [446](#), [497](#), [531](#), [1154](#), [1257](#), [1288](#), [1425](#),
[1475](#)*, [1549](#), [1821](#).
fetch_effective_tail: [1258](#), [1259](#), [1283](#).
fetch_effective_tail_eTeX: [1258](#).
fewest_demerits: [1048](#), [1050](#), [1051](#).
ff: [498](#), [693](#), [696](#), [698](#), [766](#).
fflush: [34](#)*
fget: [590](#)*, [591](#), [594](#), [597](#), [602](#)*
 \fi primitive: [517](#).
fi_code: [515](#), [517](#), [518](#), [520](#), [524](#), [526](#), [535](#), [536](#),
[1669](#), [1692](#)*, [1778](#).
fi_or_else: [228](#), [321](#), [388](#)*, [391](#), [515](#), [517](#), [518](#),
[520](#), [536](#), [1471](#)*

- fil*: 480.
- fil*: [153*](#), [168](#), 182, 195, 480, 824, 835, 841, 1379.
- fil_code*: [1236](#), 1237, 1238.
- fil_glue*: [180](#), 182, 1238.
- fil_neg_code*: [1236](#), 1238.
- fil_neg_glue*: [180](#), 182, 1238.
- File ended while scanning...: [360*](#)
- File ended within \read: [512](#).
- file_line_error_style_p*: [32*](#), [61*](#), [73*](#), [562*](#)
- file_name_size*: [11*](#), [26*](#), [545*](#), [548](#), [549*](#), [551*](#)
- file_offset*: [54*](#), [55](#), [57](#), [58](#), [62*](#), [563*](#), [666*](#), [750*](#), [1458*](#), [1756*](#)
- file_opened*: [586*](#), [587*](#), [589*](#)
- file_warning*: [384](#), [1778](#).
- filename*: [712](#).
- fill*: [153*](#), [168](#), 182, 824, 835, 841, 1379.
- fill_code*: [1236](#), 1237, 1238.
- fill_glue*: [180](#), 182, 1232, 1238.
- fill_width*: [1843](#), 1844, 1847.
- filll*: [153*](#), [168](#), 195, 480, 824, 835, 841, 1379, 1700.
- fin_align*: 949, 961, [976](#), 1309.
- fin_col*: 949, [967](#), 1309.
- fin_mlist*: 1352, [1362](#), 1364, 1369, 1372.
- fin_row*: 949, [975](#), 1309.
- fin_rule*: [647*](#), [650*](#), [654](#), [657*](#), [659](#), 663, [729*](#), [732*](#), [736](#), [738*](#), [741](#), [745](#).
- final_cleanup*: [1513*](#), [1514*](#), [1516*](#), 1826.
- final_end*: [0*](#), [35*](#), [353*](#), [1513*](#), [1518*](#)
- final_hyphen_demerits*: [254*](#), 1035.
- \finalhyphendemerits primitive: [256*](#)
- final_hyphen_demerits_code*: [254*](#), [255*](#), [256*](#)
- final_pass*: [1004](#), 1030, 1039, 1049.
- final_skip*: [695](#), 1574, [1604*](#), [1638*](#)
- find_effective_tail*: [450](#).
- find_effective_tail_eTeX*: [450](#), 1258.
- find_font_dimen*: 451, [605](#), 1220, 1431.
- find_obj*: [1556](#), 1566.
- find_protchar_left*: 821, [1005](#), 1063.
- find_protchar_right*: 821, [1005](#), 1057.
- find_sa_element*: 441, 453, [1402*](#), [1404](#), [1405](#), [1415](#), [1817](#), [1820](#), 1821, 1822, 1825, 1828, 1831, 1840.
- fingers: [537](#).
- finite_shrink*: [1001](#), [1002](#).
- fire_up*: 1182, [1189](#), 1810, 1826, 1829.
- fire_up_done*: 1189, [1826](#), 1830.
- fire_up_init*: 1189, [1826](#), 1829.
- firm_up_the_line*: 362, 384, [385*](#), 564.
- first*: [30*](#), [31*](#), [35*](#), [36](#), [37*](#), [71*](#), 83, 87, 88, 286, [350*](#), [351](#), [353*](#), [377*](#), [378*](#), [382](#), 384, [385*](#), 400, 509, [557](#), [564](#), 1517, 1757, 1769.
- first_child*: [1137*](#), [1140*](#), [1141*](#), 1856, 1857.
- first_count*: [54*](#), 337, 338, 339.
- first_fit*: [1130](#), 1134, [1143*](#), 1858.
- first_indent*: [1023](#), 1025, 1066.
- first_mark*: [408](#), 409, 1189, 1193, 1810, 1829.
- \firstmark primitive: [410](#).
- first_mark_code*: [408](#), 410, 411, 1810.
- \firstmarks primitive: [1810](#).
- first_p*: [999](#), 1005, 1039.
- first_text_char*: [19*](#), [24*](#)
- first_width*: [1023](#), 1025, 1026, 1066.
- fit_class*: [1006](#), 1012, 1021, 1022, 1028, 1029, 1031, 1035, 1848, 1849, 1851, 1852.
- fitness*: [995](#), 1021, 1035, 1040.
- fix_date_and_time*: [259*](#), [1513*](#), [1518*](#)
- fix_expand_value*: [705](#).
- fix_int*: [682](#), 683, 705, 706, 792, 823, 1553, 1576.
- fix_language*: 1211*, [1625](#).
- fix_pdf_draftmode*: [747](#), [748](#).
- fix_pdfoutput*: 683, [747](#), 752, 791, 1514*
- fix_word*: [567](#), 568, 573, [574*](#), 597.
- fixed_decimal_digits*: 690, [691](#), 692, 693, 792.
- fixed_gamma*: [680](#), 683.
- fixed_gen_tounicode*: [691](#), 801.
- fixed_image_apply_gamma*: [680](#), 683.
- fixed_image_gamma*: [680](#), 683.
- fixed_image_hicolor*: [680](#), 683.
- fixed_inclusion_copy_font*: 683, [691](#).
- fixed_pdf_draftmode*: [680](#), 683, 684, 685, 748, 778, 794.
- fixed_pdf_draftmode_set*: [680](#), 681, 748.
- fixed_pdf_major_version*: [680](#), 683.
- fixed_pdf_minor_version*: [680](#), 683.
- fixed_pdf_objcompresslevel*: [680](#), 683, 698, 748.
- fixed_pdfoutput*: [680](#), [747](#), 1514*
- fixed_pdfoutput_set*: [680](#), 681, [747](#), 1514*
- fixed_pk_resolution*: [691](#), 792.
- fixedi*: [705](#).
- float*: [109*](#), 132, 204*, 653, 662, 735, 744, 985, 1639.
- float_constant*: [109*](#), [204*](#), [647*](#), 653, 657*, [729*](#), [738*](#), 1301, 1303, [1638*](#), [1892*](#), [1893*](#)
- float_cost*: [158](#), 206, 1185, 1278*
- floating_penalty*: 158, [254*](#), 1246, 1278*
- \floatingpenalty primitive: [256*](#)
- floating_penalty_code*: [254*](#), [255*](#), [256*](#)
- flush_char*: 42, 198, 213, 868, 871.
- flush_dvi*: 668*
- flush_jbig2_page0_objects*: 794.
- flush_list*: [141](#), 218, [346*](#), [398*](#), 422, 433, 727, 764, 765, 977, 1080, 1118*, [1137*](#), 1274, 1399*, [1457*](#), [1476*](#), [1616*](#), [1618*](#), 1689, 1754, 1768.
- flush_math*: [894](#), 952, 1373.
- flush_node_list*: 217, [220*](#), 297, 667, 772, 874, 894, 907, 908, 918, 976, 992, 1055, 1059, 1080, 1095,

- 1145, 1154, 1169, 1176, 1200, 1203*, 1256, 1258, 1283, 1298, 1299, 1384, 1516*, 1566, 1624, 1636, 1637, 1728, 1736, 1739*, 1744, 1839.
- flush_str*: 497, 705, 706, 718, 726, 727, 769, 772, 807, 1538, 1553, 1556, 1564, 1566, 1588, 1631.
- flush_string*: 44, 286, 543*, 563*, 792, 1118*, 1457*, 1509, 1556, 1754, 1878*.
- flush_whatsit_node*: 772, 783, 786.
- flushable*: 673*, 1556.
- fm*: 1257, 1258, 1283.
- fm_entry_ptr*: 707, 708, 1502*, 1518*.
- fmem_ptr*: 451, 575*, 592, 595, 596*, 603*, 605, 606, 607, 705, 706, 1499*, 1500*, 1502*, 1515*, 1518*.
- fmemory_word*: 575*, 1500*, 1513*.
- fnt_file*: 550*, 1484*, 1509, 1510, 1518*.
- fnt_def1*: 612, 613, 629*, 715.
- fnt_def2*: 612.
- fnt_def3*: 612.
- fnt_def4*: 612.
- fnt_num_0*: 612, 613, 649*, 719, 726.
- fnt1*: 612, 613, 649*, 719, 726.
- fnt2*: 612.
- fnt3*: 612.
- fnt4*: 612.
- font*: 152, 161, 162*, 192*, 194*, 211, 224*, 574*, 609*, 648*, 674, 705, 731*, 822, 823, 825, 828, 857, 885, 891, 900, 1017, 1018, 1042, 1043, 1046, 1047, 1073, 1074, 1075, 1080, 1085, 1088, 1211*, 1215, 1291, 1325, 1725, 1734*.
- font metric files: 565.
- font parameters: 876, 877.
- Font x has only...: 606.
- Font x=xx not loadable...: 587*.
- Font x=xx not loaded...: 593.
- `\font` primitive: 287*.
- font_area*: 575*, 603*, 629*, 630, 705, 706, 1438*, 1501*, 1502*, 1518*.
- font_base*: 11*, 32*, 129*, 152, 240*, 250, 629*, 649*, 671, 673*, 674, 705, 801, 1438*, 1499*, 1500*, 1502*, 1515*, 1518*.
- font_bc*: 575*, 580*, 603*, 604*, 609*, 648*, 673*, 705, 706, 884*, 898*, 1213*, 1501*, 1502*, 1518*, 1672, 1770, 1885*, 1886*, 1890*.
- font_bchar*: 575*, 603*, 705, 706, 1074, 1075, 1092, 1209, 1211*, 1501*, 1502*, 1518*.
- `\fontchardp` primitive: 1670.
- font_char_dp_code*: 1670, 1671, 1672.
- `\fontcharht` primitive: 1670.
- font_char_ht_code*: 1670, 1671, 1672.
- `\fontcharic` primitive: 1670.
- font_char_ic_code*: 1670, 1671, 1672.
- `\fontcharwd` primitive: 1670.
- font_char_wd_code*: 1670, 1671, 1672.
- font_check*: 575*, 594, 629*, 712, 714, 1501*, 1502*, 1518*.
- `\fontdimen` primitive: 287*.
- font_dsize*: 192*, 498, 575*, 594, 629*, 705, 706, 712, 714, 1438*, 1439, 1501*, 1502*, 1518*.
- font_ec*: 575*, 603*, 604*, 609*, 648*, 673*, 705, 706, 884*, 898*, 1213*, 1501*, 1502*, 1518*, 1672, 1770, 1885*, 1886*, 1890*.
- font_expand_ratio*: 821, 823, 825, 828, 834, 840.
- font_false_bchar*: 575*, 603*, 705, 706, 1209, 1211*, 1501*, 1502*, 1518*.
- font_glue*: 575*, 603*, 605, 705, 706, 1220, 1501*, 1502*, 1518*.
- font_id_base*: 240*, 252, 274*, 441, 574*, 706, 1435*.
- font_id_text*: 192*, 252, 274*, 606, 705, 706, 1435*, 1501*.
- font_in_short_display*: 191, 192*, 211, 674, 839, 1040, 1520*.
- font_index*: 574*, 575*, 586*, 823, 1083, 1209, 1389*, 1502*, 1518*.
- font_info*: 32*, 451, 574*, 575*, 576*, 580*, 583, 584, 586*, 592, 595, 598, 600*, 601, 602*, 605, 607, 705, 706, 823, 876, 877, 889, 917, 928, 1086, 1209, 1216, 1220, 1389*, 1431, 1487*, 1499*, 1500*, 1513*, 1518*, 1520*, 1885*, 1886*.
- font_k*: 32*, 1502*, 1518*.
- font_max*: 12*, 32*, 129*, 192*, 194*, 592, 674, 705, 706, 1502*, 1513*, 1515*, 1518*.
- font_mem_size*: 32*, 592, 607, 705, 706, 1500*, 1513*, 1515*.
- font_name*: 192*, 498, 575*, 603*, 608*, 629*, 630, 693, 705, 706, 710, 712, 713, 714, 717, 1438*, 1439, 1501*, 1502*, 1518*, 1885*, 1890*, 1891*.
- `\fontname` primitive: 494.
- font_name_code*: 494, 495, 497, 498.
- font_params*: 575*, 603*, 605, 606, 607, 705, 706, 1373, 1501*, 1502*, 1518*.
- font_ptr*: 575*, 592, 603*, 605, 671, 705, 706, 801, 1438*, 1499*, 1500*, 1501*, 1502*, 1515*, 1518*.
- font_shrink*: 823, 825, 828, 840.
- font_size*: 192*, 498, 575*, 594, 629*, 692, 693, 705, 706, 712, 717, 726, 1438*, 1439, 1501*, 1502*, 1518*.
- font_step*: 705.
- font_stretch*: 823, 825, 828, 834.
- font_used*: 497, 575*, 649*, 671, 692, 693, 801, 1518*, 1588.
- fontnum*: 692.
- FONTx: 706, 1435*.
- for accent: 209.
- Forbidden control sequence...: 360*.
- force_eof*: 353*, 383, 384, 404.

- format_area_length*: [546](#)*
format_debug: [1485](#)*, [1487](#)*
format_debug_end: [1485](#)*
format_default_length: [546](#)*, [548](#), [549](#)*, [550](#)*
format_engine: [1481](#)*, [1482](#)*, [1486](#)*, [1487](#)*
format_ext_length: [546](#)*, [549](#)*, [550](#)*
format_extension: [546](#)*, [555](#), [1509](#).
format_ident: [61](#)*, [562](#)*, [1478](#), [1479](#), [1480](#)*, [1507](#),
[1508](#)*, [1509](#), [1518](#)*, [1649](#)*
forward: [78](#), [236](#), [303](#), [362](#), [388](#)*, [435](#), [646](#), [703](#),
[728](#), [868](#), [869](#), [896](#), [950](#), [976](#), [1683](#), [1696](#), [1753](#),
[1782](#), [1787](#), [1811](#).
found: [15](#), [143](#)*, [146](#), [147](#), [278](#), [281](#), [363](#)*, [365](#)*, [376](#)*,
[378](#)*, [415](#), [418](#), [420](#), [474](#), [481](#), [499](#), [501](#), [503](#),
[550](#)*, [634](#), [636](#), [639](#), [640](#), [641](#), [647](#)*, [693](#), [705](#),
[729](#)*, [817](#), [882](#), [884](#)*, [896](#), [1005](#), [1027](#), [1072](#),
[1100](#)*, [1108](#)*, [1111](#)*, [1117](#)*, [1118](#)*, [1130](#), [1132](#), [1316](#),
[1324](#), [1325](#), [1326](#), [1414](#), [1415](#), [1680](#), [1684](#), [1734](#)*,
[1783](#), [1784](#), [1790](#), [1800](#), [1848](#), [1849](#), [1877](#)*, [1885](#)*,
[1887](#)*, [1888](#)*, [1890](#)*, [1900](#)*
found1: [15](#), [693](#), [1072](#), [1079](#), [1481](#)*, [1494](#)*, [1680](#),
[1800](#), [1801](#).
found2: [15](#), [1072](#), [1080](#), [1481](#)*, [1495](#)*, [1680](#).
four_cases: [710](#), [719](#), [726](#).
four_choices: [131](#)*
four_quarters: [439](#), [574](#)*, [575](#)*, [580](#)*, [581](#), [586](#)*, [712](#),
[823](#), [859](#), [860](#), [882](#), [885](#), [888](#), [900](#), [914](#), [925](#)*, [1083](#),
[1209](#), [1301](#), [1502](#)*, [1518](#)*, [1754](#), [1757](#), [1886](#)*, [1889](#)*
fputs: [61](#)*, [550](#)*, [562](#)*
fract: [1799](#), [1800](#), [1847](#).
fraction: [110](#), [112](#).
fraction_four: [110](#), [111](#), [116](#), [119](#), [120](#).
fraction_half: [111](#), [116](#), [127](#).
fraction_noad: [110](#), [859](#), [863](#), [866](#), [874](#), [909](#),
[937](#), [1356](#), [1359](#).
fraction_noad_size: [859](#), [874](#), [937](#), [1359](#).
fraction_one: [110](#), [111](#), [112](#), [113](#), [114](#), [124](#), [125](#).
fraction_rule: [880](#), [881](#), [911](#), [923](#).
free: [183](#)*, [185](#), [186](#), [187](#), [188](#), [189](#).
free_arr: [183](#)*
free_avail: [139](#), [220](#)*, [222](#), [235](#), [426](#)*, [478](#), [497](#),
[822](#), [948](#), [1092](#), [1213](#)*, [1288](#), [1404](#), [1466](#), [1578](#),
[1684](#), [1706](#), [1758](#), [1901](#)*
free_node: [148](#), [219](#), [220](#)*, [297](#), [522](#), [642](#), [823](#), [831](#),
[874](#), [891](#), [897](#)*, [903](#), [927](#), [929](#), [932](#), [936](#), [948](#), [979](#),
[1036](#), [1037](#), [1041](#), [1080](#), [1087](#)*, [1154](#), [1196](#), [1198](#),
[1199](#), [1214](#)*, [1278](#)*, [1288](#), [1364](#), [1365](#), [1379](#), [1516](#)*,
[1537](#), [1606](#), [1723](#)*, [1726](#)*, [1728](#), [1730](#)*, [1739](#)*, [1740](#)*,
[1746](#), [1757](#), [1758](#), [1790](#), [1822](#), [1826](#), [1842](#).
freeze_page_specs: [1164](#), [1178](#), [1185](#).
frozen_control_sequence: [240](#)*, [277](#)*, [1393](#)*, [1497](#)*,
[1498](#)*
frozen_cr: [240](#)*, [361](#)*, [956](#), [1310](#).
frozen_dont_expand: [240](#)*, [277](#)*, [393](#)*
frozen_end_group: [240](#)*, [287](#)*, [1243](#).
frozen_end_template: [240](#)*, [401](#), [956](#).
frozen_endv: [240](#)*, [401](#), [406](#), [956](#).
frozen_fi: [240](#)*, [358](#), [517](#).
frozen_null_font: [240](#)*, [284](#)*, [285](#), [579](#).
frozen_primitive: [240](#)*, [277](#)*, [394](#), [466](#).
frozen_protection: [240](#)*, [1393](#)*, [1394](#).
frozen_relax: [240](#)*, [287](#)*, [395](#), [405](#).
frozen_right: [240](#)*, [1243](#), [1366](#).
frozen_special: [240](#)*, [1525](#)*, [1940](#)*
fs: [705](#), [712](#), [725](#).
Fuchs, David Raymond: [2](#)*, [610](#), [618](#).
full_source_filename_stack: [326](#)*, [350](#)*, [353](#)*, [563](#)*,
[1513](#)*, [1873](#)*
\futurelet primitive: [1397](#)*
fwrite: [624](#)*
g: [47](#)*, [200](#), [586](#)*, [619](#)*, [823](#), [844](#), [882](#), [892](#), [1845](#).
g_order: [647](#)*, [653](#), [657](#)*, [662](#), [729](#)*, [735](#), [738](#)*, [744](#),
[1638](#)*, [1639](#), [1700](#), [1724](#).
g_sign: [647](#)*, [653](#), [657](#)*, [662](#), [729](#)*, [735](#), [738](#)*, [744](#),
[1638](#)*, [1639](#), [1700](#), [1724](#).
gap_amount: [1638](#)*
garbage: [180](#), [493](#), [496](#), [497](#), [1137](#)*, [1361](#), [1370](#),
[1457](#)*
garbage_warning: [794](#).
\gdef primitive: [1386](#).
gen_faked_interword_space: [693](#), [1629](#), [1630](#),
[1640](#), [1646](#).
gen_running_link: [730](#), [1629](#), [1630](#), [1640](#), [1646](#).
geq_define: [301](#), [958](#), [1392](#).
geq_word_define: [301](#), [310](#), [1190](#), [1392](#).
get: [26](#)*, [29](#), [31](#)*, [511](#), [564](#), [590](#)*
get_auto_kern: [173](#), [705](#), [1211](#)*, [1212](#), [1216](#), [1295](#).
get_avail: [138](#), [140](#), [222](#), [223](#), [234](#), [347](#)*, [348](#), [359](#),
[361](#)*, [393](#)*, [394](#), [397](#), [398](#)*, [478](#), [499](#), [508](#), [609](#)*,
[885](#), [948](#), [959](#), [960](#), [970](#), [1085](#), [1088](#), [1115](#), [1242](#),
[1243](#), [1396](#), [1399](#)*, [1404](#), [1619](#)*, [1684](#), [1689](#), [1706](#),
[1728](#), [1734](#)*, [1755](#), [1768](#), [1900](#)*, [1901](#)*, [1940](#)*
get_chardepth: [673](#)*
get_charheight: [673](#)*
get_charwidth: [673](#)*
get_date_and_time: [259](#)*
get_ef_code: [452](#), [823](#).
get_expand_font: [705](#).
get_fontbase: [673](#)*
get_image_group_ref: [1638](#)*
get_job_name: [560](#)*, [563](#)*
get_kern: [823](#), [825](#).
get_kn_ac_code: [452](#), [705](#).
get_kn_bc_code: [452](#), [705](#).

- get_kn_bs_code*: 452, 705.
get_lp_code: 452, 823.
get_microinterval: 450, [1556](#).
get_next: 76, 319, 354*, 358, 362, [363](#)*, 379*, 382, 386, 387, 388*, 393*, 406, 407, 413, 415, 504, 520, 527*, 533, 816, 1215, 1223, 1304, 1767.
get_next_char: [793](#).
get_node: [143](#)*, 149, 154, 157, 162*, 163, 165*, 169, 170*, 171*, 174*, 176*, 224*, 521, 634, 823, 844, 862, 864, 865, 892, 948, 974, 1019, 1020, 1021, 1040, 1091, 1186, 1278*, 1279, 1341, 1343, 1359, 1426, 1427, 1530, 1557, 1574, 1605, 1638*, 1700, 1720, 1734*, 1755, 1789, 1816, 1821, 1838, 1916*.
get_nullcs: [673](#)*.
get_nullfont: [673](#)*.
get_nullptr: [673](#)*.
get_nullstr: [1941](#)*.
get_obj: 498, 752, [1556](#), 1631, 1638*.
get_pdf_compress_level: [673](#)*.
get_pdf_omit_charset: [673](#)*.
get_pdf_suppress_ptex_info: [673](#)*.
get_pdf_suppress_warning_dup_map: [673](#)*.
get_pdf_suppress_warning_page_group: [673](#)*.
get_pk_char_width: 690.
get_preamble_token: [958](#), 959, 960.
get_quad: [673](#)*.
get_r_token: 706, [1393](#)*, 1396, 1399*, 1402*, 1403, 1435*.
get_rename_prefix: 792.
get_rp_code: 452, 823.
get_sa_ptr: [1820](#), 1826, 1832.
get_sh_bs_code: 452, 705.
get_slant: [673](#)*.
get_st_bs_code: 452, 705.
get_strings_started: [47](#)*, 51*, 1513*.
get_tag_code: 452, [604](#)*.
get_tex_dimen: [673](#)*.
get_tex_int: [673](#)*.
get_token: 76, 78, 88, 386, [387](#), 392, 393*, 394, 395, 418, 425, 468, 478, 497, 499, 500, 502, 503, 505, 509, 958, 1204, 1316, 1393*, 1399*, 1430*, 1446, 1449*, 1473*, 1619*, 1620, 1684, 1766, 1773.
get_vpos: [1638](#)*.
get_x_height: [673](#)*.
get_x_or_protected: 961, 967, [1773](#).
get_x_token: 386, 388*, 398*, [406](#), 407, 428, 430, 432, 433, 469, 470, 471, 478, 491, 505, 532, 552*, 956, 1112, 1138, 1206, 1207, 1316, 1375, 1399*, 1415, 1624, 1768, 1773.
get_x_token_or_active_char: [532](#).
getc: 590*, 712, 772.
getcreationdate: 497.
getfiledump: 497.
getfilemoddate: 497.
getfilesize: 497.
getllx: 1631, 1636.
getlly: 1631, 1636.
getmatch: 497.
getmd5sum: 497.
geturx: 1631, 1636.
getury: 1631, 1636.
give_err_help: 78, 89, 90, [1462](#).
global: [1392](#), 1396, 1419, 1840.
global definitions: 239, 301, 305*, 1841.
\global primitive: [1386](#).
global_box_flag: [1249](#), 1255, 1419, 1682.
global_defs: [254](#)*, 958, 1392, 1396.
\globaldefs primitive: [250](#)*.
global_defs_code: [254](#)*, 255*, 256*.
glue_base: 238*, [240](#)*, 242, 244, 245, 246, 247, 270*, 958.
glue_break: 1053, 1057.
glue_error: [1791](#).
\glueexpr primitive: [1779](#).
glue_node: [167](#), 170*, 171*, 193, 201, 220*, 224*, 450, 498, 650*, 659, 674, 705, 732*, 741, 825, 845, 906, 908, 937, 992, 993, 1005, 1013, 1032, 1038, 1042, 1055, 1057, 1076, 1080, 1145, 1149, 1150, 1165*, 1173, 1174, 1177, 1284, 1285, 1286, 1325, 1380, 1638*, 1727, 1734*, 1747, 1935*.
glue_offset: [153](#)*, 177, 204*.
glue_ord: [168](#), 473, 647*, 657*, 729*, 738*, 818, 823, 844, 967, 1638*, 1724.
glue_order: [153](#)*, 154, 177, 203, 204*, 647*, 657*, 729*, 738*, 833, 834, 840, 848, 849, 852, 945, 972, 977, 983, 985, 986, 987, 1326, 1638*, 1724, 1741.
glue_par: [242](#), 942.
glue_pars: [242](#).
glue_ptr: [167](#), 170*, 171*, 193, 207, 208, 220*, 224*, 450, 653, 662, 705, 735, 744, 832, 847, 855, 908, 962, 969, 971, 978, 979, 985, 992, 1005, 1014, 1044, 1057, 1146, 1153, 1173, 1178, 1181, 1326, 1639, 1700, 1734*, 1747, 1844, 1854.
glue_ratio: 109*, 128*, 153*, 204*.
glue_ref: [228](#), 246, 297, 958, 1406, 1414.
glue_ref_count: [168](#), 169, 170*, 171*, 172, 182, 219, 221, 246, 942, 1221, 1238.
glue_set: [153](#)*, 154, 177, 204*, 653, 662, 735, 744, 833, 834, 840, 848, 849, 852, 983, 985, 986, 987, 1326, 1639, 1700, 1741.
glue_shrink: [177](#), 203, 972, 975, 977, 986, 987.
\glueshrink primitive: [1802](#).
glue_shrink_code: [1802](#), 1803, 1805.
\glueshrinkorder primitive: [1802](#).

- glue_shrink_order_code*: [1802](#), [1803](#), [1804](#).
glue_sign: [153](#)*, [154](#), [177](#), [203](#), [204](#)*, [647](#)*, [657](#)*, [729](#)*,
[738](#)*, [833](#), [834](#), [840](#), [848](#), [849](#), [852](#), [945](#), [972](#), [977](#),
[983](#), [985](#), [986](#), [987](#), [1326](#), [1638](#)*, [1724](#), [1741](#).
glue_spec_size: [168](#), [169](#), [180](#), [182](#), [219](#), [892](#), [1700](#).
glue_stretch: [177](#), [203](#), [972](#), [975](#), [977](#), [986](#), [987](#).
\gluestretch primitive: [1802](#).
glue_stretch_code: [1802](#), [1803](#), [1805](#).
\gluestretchorder primitive: [1802](#).
glue_stretch_order_code: [1802](#), [1803](#), [1804](#).
glue_temp: [647](#)*, [653](#), [657](#)*, [662](#), [729](#)*, [735](#), [738](#)*,
[744](#), [1638](#)*, [1639](#), [1724](#).
\gluetomu primitive: [1806](#).
glue_to_mu_code: [1806](#), [1807](#), [1809](#).
glue_val: [436](#), [437](#), [439](#), [442](#), [443](#), [450](#), [453](#), [455](#),
[456](#), [477](#), [487](#), [491](#), [958](#), [1238](#), [1406](#), [1414](#), [1415](#),
[1416](#), [1418](#), [1574](#), [1779](#), [1780](#), [1781](#), [1783](#), [1786](#),
[1788](#), [1792](#), [1797](#), [1816](#), [1824](#), [1833](#).
glyph_to_unicode: [1588](#), [1593](#).
goal height: [1163](#), [1164](#).
goto: [35](#)*.
gr: [128](#)*, [132](#), [153](#)*.
group_code: [291](#), [293](#)*, [296](#), [817](#), [1314](#), [1680](#).
group_trace: [296](#), [304](#), [1663](#).
group_warning: [304](#), [1775](#).
groupref: [1638](#)*.
grp_stack: [304](#), [350](#)*, [353](#)*, [384](#), [1513](#)*, [1774](#)*, [1775](#),
[1778](#).
gsa_def: [1840](#), [1841](#).
gsa_w_def: [1840](#), [1841](#).
gubed: [7](#)*.
Guibas, Leonidas Ioannis: [2](#)*.
gzFile: [131](#)*.
g1: [1376](#), [1381](#).
g2: [1376](#), [1381](#), [1383](#), [1638](#)*.
h: [222](#), [278](#), [281](#), [823](#), [844](#), [914](#), [1106](#), [1111](#)*, [1121](#)*,
[1125](#), [1130](#), [1147](#), [1154](#), [1171](#), [1264](#), [1269](#)*,
[1301](#), [1616](#)*, [1734](#)*, [1800](#).
h_offset: [265](#), [644](#), [645](#)*, [669](#), [755](#).
\hoffset primitive: [266](#).
h_offset_code: [265](#), [266](#).
ha: [1069](#), [1073](#), [1077](#), [1080](#), [1089](#).
half: [100](#), [882](#), [912](#), [913](#), [914](#), [921](#), [922](#), [925](#)*,
[926](#), [1380](#).
half_buf: [621](#), [622](#)*, [623](#), [625](#)*, [626](#)*, [668](#)*.
half_error_line: [14](#), [32](#)*, [333](#), [337](#), [338](#), [339](#), [1513](#)*.
halfp: [111](#), [116](#), [120](#), [125](#).
halfword: [108](#), [128](#)*, [131](#)*, [133](#), [148](#), [286](#), [299](#), [301](#),
[302](#), [303](#), [319](#), [320](#), [322](#)*, [355](#), [363](#)*, [388](#)*, [415](#),
[439](#), [490](#), [499](#), [508](#), [575](#)*, [586](#)*, [604](#)*, [705](#), [706](#),
[727](#), [857](#), [967](#), [976](#), [997](#), [1005](#), [1006](#), [1009](#), [1023](#),
[1048](#), [1053](#), [1069](#), [1078](#), [1083](#), [1084](#), [1154](#), [1209](#),
[1257](#), [1279](#), [1389](#)*, [1421](#), [1444](#), [1466](#), [1502](#)*, [1513](#)*,
[1518](#)*, [1616](#)*, [1629](#), [1657](#), [1684](#), [1724](#), [1739](#)*, [1815](#),
[1820](#), [1823](#), [1840](#), [1841](#).
halign: [226](#), [287](#)*, [288](#)*, [1272](#), [1308](#)*.
\halign primitive: [287](#)*.
halt_on_error_p: [32](#)*, [82](#)*.
halting_on_error_p: [32](#)*, [82](#)*, [1869](#)*.
handle_right_brace: [1245](#), [1246](#).
hang_after: [254](#)*, [258](#)*, [1023](#), [1025](#), [1248](#), [1327](#).
\hangafter primitive: [256](#)*.
hang_after_code: [254](#)*, [255](#)*, [256](#)*, [1248](#).
hang_indent: [265](#), [1023](#), [1024](#), [1025](#), [1248](#), [1327](#).
\hangindent primitive: [266](#).
hang_indent_code: [265](#), [266](#), [1248](#).
hanging indentation: [1023](#).
hasfmentry: [801](#).
hash: [252](#), [274](#)*, [278](#), [279](#)*, [281](#), [1487](#)*, [1497](#)*,
[1498](#)*, [1513](#)*.
hash_base: [11](#)*, [238](#)*, [240](#)*, [274](#)*, [278](#), [284](#)*, [285](#), [312](#)*,
[394](#), [395](#), [527](#)*, [706](#), [1223](#), [1435](#)*, [1487](#)*, [1493](#)*,
[1497](#)*, [1498](#)*, [1513](#)*.
hash_brace: [499](#), [502](#).
hash_extra: [274](#)*, [279](#)*, [312](#)*, [1487](#)*, [1495](#)*, [1496](#)*,
[1513](#)*, [1515](#)*.
hash_high: [274](#)*, [277](#)*, [279](#)*, [1486](#)*, [1487](#)*, [1495](#)*, [1496](#)*,
[1497](#)*, [1498](#)*.
hash_is_full: [274](#)*, [279](#)*.
hash_offset: [11](#)*, [312](#)*, [1487](#)*, [1513](#)*.
hash_prime: [12](#)*, [14](#), [278](#), [280](#), [1486](#)*, [1487](#)*.
hash_size: [11](#)*, [12](#)*, [14](#), [240](#)*, [279](#)*, [280](#), [284](#)*, [1515](#)*.
hash_top: [274](#)*, [1487](#)*, [1493](#)*, [1513](#)*.
hash_used: [274](#)*, [277](#)*, [279](#)*, [1497](#)*, [1498](#)*, [1513](#)*.
hasspacechar: [693](#).
hb: [1069](#), [1074](#), [1075](#), [1077](#), [1080](#).
hbadness: [254](#)*, [836](#), [842](#), [843](#).
\hbadness primitive: [256](#)*.
hbadness_code: [254](#)*, [255](#)*, [256](#)*.
\hbox primitive: [1249](#).
hbox_group: [291](#), [296](#), [1261](#), [1263](#)*, [1662](#), [1680](#).
hc: [1069](#), [1070](#), [1073](#), [1074](#), [1075](#), [1077](#), [1078](#),
[1096](#), [1097](#)*, [1100](#)*, [1107](#)*, [1108](#)*, [1111](#)*, [1114](#), [1116](#)*,
[1137](#)*, [1139](#), [1140](#)*, [1142](#)*, [1859](#).
hchar: [1082](#), [1083](#), [1085](#), [1086](#).
hd: [823](#), [828](#), [882](#), [884](#)*, [885](#), [888](#).
head: [230](#), [231](#)*, [233](#)*, [234](#), [235](#), [450](#), [894](#), [952](#), [972](#),
[975](#), [981](#), [988](#), [990](#), [992](#), [1203](#)*, [1211](#)*, [1232](#),
[1258](#), [1264](#), [1269](#)*, [1274](#), [1278](#)*, [1283](#), [1291](#),
[1297](#), [1299](#), [1323](#), [1337](#), [1346](#)*, [1354](#), [1359](#), [1362](#),
[1363](#), [1365](#), [1369](#), [1487](#)*.
head_field: [230](#), [231](#)*, [236](#).
head_for_vmode: [1272](#), [1273](#).

- head_tab*: 693, 695, 696, 697, 698, 789, 790, 795, 796, 797, 798, 799, 800, 801, 802, 803, 1505, 1506, 1546, 1601.
- head_tab_max*: 695, 696, 697.
- header*: 568.
- Hedrick, Charles Locke: 3.
- height*: 153*, 154, 156*, 157, 158, 202, 205, 206, 489, 498, 580*, 644, 650*, 652, 654, 657*, 659, 660*, 663, 665, 668*, 669, 732*, 734, 736, 738*, 739, 741, 742*, 745, 746, 752, 755, 823, 827, 832, 846, 848, 855, 880, 882, 885, 887, 889, 903, 906, 911, 912, 913, 914, 915, 918, 921, 922, 923, 925*, 926, 927, 932, 933, 935, 944, 945, 972, 977, 980, 982, 983, 985, 986, 987, 1005, 1065, 1146, 1150, 1158, 1163, 1178, 1179, 1185, 1186, 1187, 1198, 1265, 1278*, 1549, 1553, 1557, 1566, 1631, 1638*, 1640, 1746.
- height*: 489.
- height_base*: 576*, 580*, 592, 598, 705, 706, 1501*, 1502*, 1518*.
- height_depth*: 580*, 673*, 828, 884*, 885, 888, 1303, 1672, 1892*, 1893*.
- height_index*: 569, 580*.
- height_offset*: 153*, 442, 443, 945, 1425.
- height_plus_depth*: 888, 890.
- held over for next output**: 1163.
- help_line*: 79, 89, 90, 358, 1284, 1390, 1391.
- help_ptr*: 79, 80, 89, 90.
- help0*: 79, 608*, 1430*, 1471*.
- help1*: 79, 93*, 95*, 310, 434, 454, 480, 512, 526, 529, 536, 1137*, 1138, 1139, 1140*, 1244, 1258, 1277, 1299, 1310, 1313*, 1337, 1355, 1370, 1390, 1391, 1410*, 1415, 1421, 1422, 1436, 1461*, 1483, 1657, 1766, 1770, 1785.
- help2*: 72, 79, 88, 89, 94*, 95*, 121, 310, 368, 399, 459, 460, 461, 462, 463, 468, 471, 486, 497, 501, 502, 604*, 606, 669, 683, 1113, 1114, 1155, 1192, 1204, 1225, 1246, 1258, 1260, 1273, 1284, 1298, 1307, 1344, 1375, 1385, 1399*, 1403, 1414, 1419, 1437, 1540, 1620, 1697, 1783, 1812, 1874*.
- help3*: 72, 79, 98, 358, 422, 441, 472, 505, 952, 959, 960, 968, 1170, 1186, 1201, 1205, 1256, 1262, 1288, 1305, 1361, 1373, 1471*, 1540.
- help4*: 79, 89, 360*, 424, 429, 444, 482, 593, 899, 1153, 1181, 1228, 1461*.
- help5*: 79, 396, 587*, 1002, 1242, 1247, 1306, 1393*, 1471*.
- help6*: 79, 421, 485, 1306, 1339.
- Here is how much...**: 1515*.
- hex_dig1*: 1820.
- hex_dig2*: 1820.
- hex_dig3*: 1820.
- hex_dig4*: 1820, 1822, 1823.
- hex_to_cur_chr*: 374, 377*.
- hex_token*: 464, 470.
- hf*: 1069, 1073, 1074, 1075, 1080, 1085, 1086, 1087*, 1088, 1092, 1093.
- \hf** primitive: 1236.
- \hfilneg** primitive: 1236.
- \hfill** primitive: 1236.
- hfinish*: 1871*.
- hfuzz*: 265, 842.
- \hfuzz** primitive: 266.
- hfuzz_code*: 265, 266.
- hh*: 128*, 132, 136, 151, 200, 231*, 237*, 239, 275, 290, 862, 918, 1341, 1343, 1359, 1364, 1818.
- hi*: 130*, 250, 580*, 1402*, 1410*, 1755.
- hi_mem_min*: 134*, 136, 138, 143*, 144, 152, 182, 183*, 185, 186, 189, 190, 194*, 315, 667, 1490*, 1491*, 1515*.
- hi_mem_stat_min*: 180, 182, 1491*.
- hi_mem_stat_usage*: 180, 182.
- history*: 76, 77, 81*, 82*, 93*, 95*, 263, 686, 1513*, 1514*, 1516*, 1775, 1777, 1778.
- hlist_node*: 153*, 154, 155, 156*, 166, 177, 193, 201, 202, 220*, 224*, 497, 531, 643, 646, 647*, 650*, 659, 729*, 732*, 741, 816, 823, 825, 845, 857, 983, 986, 990, 1005, 1017, 1018, 1042, 1046, 1047, 1145, 1150, 1170, 1177, 1252, 1258, 1265, 1288, 1325, 1381, 1636, 1637, 1638*, 1705, 1726*, 1734*.
- hlist_out*: 619*, 642, 643, 646, 647*, 648*, 650*, 651*, 656, 657*, 660*, 665, 666*, 668*, 727, 729*, 869, 1621*, 1700, 1727, 1887*, 1889*.
- hlist_stack*: 173, 821, 1005.
- hlist_stack_level*: 821, 1005.
- hlp1*: 79.
- hlp2*: 79.
- hlp3*: 79.
- hlp4*: 79.
- hlp5*: 79.
- hlp6*: 79.
- hmode*: 229*, 236, 442, 527*, 962, 963, 972, 975, 1207, 1223, 1224, 1226, 1234, 1235, 1249, 1251, 1254, 1257, 1261, 1263*, 1264, 1269*, 1270, 1271, 1272, 1274, 1275, 1278*, 1287, 1288, 1290, 1294, 1295, 1297, 1300, 1308*, 1311*, 1315, 1346*, 1378, 1421, 1626, 1680.
- hmove*: 226, 1226, 1249, 1250, 1251, 1682.
- hn*: 1069, 1074, 1075, 1076, 1079, 1089, 1090, 1092, 1093, 1094, 1096, 1100*, 1107*, 1108*.
- ho*: 130*, 253, 440*, 580*, 1329, 1332, 1757, 1758.
- hold_head*: 180, 328*, 955, 959, 960, 970, 984, 1082, 1083, 1090, 1091, 1092, 1093, 1094, 1191, 1194.
- holding_inserts*: 254*, 1191.
- \holdinginserts** primitive: 256*.

- holding_inserts_code*: [254*](#), [255*](#), [256*](#)
hpack: [180](#), [254*](#), [816](#), [817](#), [818](#), [819](#), [823](#), [834](#), [837](#),
[885](#), [891](#), [896](#), [903](#), [913](#), [924](#), [930](#), [932](#), [972](#),
[975](#), [980](#), [982](#), [1066](#), [1240](#), [1264](#), [1303](#), [1372](#),
[1377](#), [1379](#), [1382](#), [1706](#), [1737](#), [1747](#).
hrule: [226](#), [287*](#), [288*](#), [489](#), [1224](#), [1234](#), [1262](#),
[1272](#), [1273](#).
\hrule primitive: [287*](#)
hsize: [265](#), [1023](#), [1024](#), [1025](#), [1232](#), [1327](#).
\hsize primitive: [266](#).
hsize_code: [265](#), [266](#).
hskip: [226](#), [1235](#), [1236](#), [1237](#), [1256](#), [1268](#).
\hskip primitive: [1236](#).
\hss primitive: [1236](#).
hstart: [1871*](#).
\ht primitive: [442](#).
hu: [1069](#), [1070](#), [1074](#), [1075](#), [1078](#), [1080](#), [1082](#),
[1084](#), [1085](#), [1087*](#), [1088](#), [1089](#), [1092](#), [1093](#).
Huge page...: [669](#).
hyf: [1077](#), [1079](#), [1082](#), [1085](#), [1086](#), [1090](#), [1091](#),
[1096](#), [1097*](#), [1100*](#), [1101*](#), [1109](#), [1137*](#), [1138](#),
[1139](#), [1140*](#), [1142*](#).
hyf_bchar: [1069](#), [1074](#), [1075](#), [1080](#).
hyf_char: [1069](#), [1073](#), [1090](#), [1092](#).
hyf_distance: [1097*](#), [1098*](#), [1099](#), [1101*](#), [1120*](#), [1121*](#),
[1122*](#), [1503*](#), [1504*](#).
hyf_next: [1097*](#), [1098*](#), [1101*](#), [1120*](#), [1121*](#), [1122*](#),
[1503*](#), [1504*](#).
hyf_node: [1089](#), [1092](#).
hyf_num: [1097*](#), [1098*](#), [1101*](#), [1120*](#), [1121*](#), [1122*](#),
[1503*](#), [1504*](#).
hyph_codes: [1855*](#), [1859](#).
hyph_count: [1103*](#), [1105*](#), [1117*](#), [1118*](#), [1503*](#), [1504*](#),
[1515*](#).
hyph_data: [227*](#), [1388](#), [1428](#), [1429](#), [1430*](#).
hyph_index: [1111*](#), [1857](#), [1859](#).
hyph_link: [1102*](#), [1103*](#), [1105*](#), [1107*](#), [1117*](#), [1503*](#),
[1504*](#), [1513*](#).
hyph_list: [1103*](#), [1105*](#), [1106](#), [1109](#), [1110](#), [1111*](#),
[1117*](#), [1118*](#), [1503*](#), [1504*](#), [1513*](#).
hyph_next: [1103*](#), [1105*](#), [1117*](#), [1503*](#), [1504*](#).
hyph_pointer: [1102*](#), [1103*](#), [1104](#), [1106](#), [1111*](#), [1513*](#).
hyph_prime: [11*](#), [12*](#), [1105*](#), [1107*](#), [1116*](#), [1117*](#), [1486*](#),
[1487*](#), [1503*](#), [1504*](#).
hyph_root: [1129](#), [1135*](#), [1143*](#), [1518*](#), [1855*](#), [1858](#).
hyph_size: [32*](#), [1105*](#), [1110](#), [1117*](#), [1503*](#), [1504*](#),
[1513*](#), [1515*](#).
hyph_start: [1503*](#), [1504*](#), [1518*](#), [1858](#), [1859](#).
hyph_word: [1103*](#), [1105*](#), [1106](#), [1108*](#), [1111*](#), [1117*](#),
[1118*](#), [1503*](#), [1504*](#), [1513*](#).
hyphen_char: [173](#), [452](#), [575*](#), [603*](#), [705](#), [706](#), [1068](#),
[1073](#), [1212](#), [1295](#), [1431](#), [1501*](#), [1502*](#), [1518*](#).
\hyphenchar primitive: [1432](#).
hyphen_passed: [1082](#), [1083](#), [1086](#), [1090](#), [1091](#).
hyphen_penalty: [163](#), [254*](#), [1045](#).
\hyphenpenalty primitive: [256*](#).
hyphen_penalty_code: [254*](#), [255*](#), [256*](#).
hyphen_size: [1503*](#).
hyphenate: [1071](#), [1072](#).
hyphenated: [995](#), [996](#), [1005](#), [1022](#), [1035](#), [1045](#),
[1049](#).
Hyphenation trie...: [1503*](#).
\hyphenation primitive: [1428](#).
i: [19*](#), [125](#), [337](#), [363*](#), [439](#), [496](#), [604*](#), [614](#), [699](#), [702](#),
[705](#), [706](#), [712](#), [725](#), [727](#), [729*](#), [750*](#), [793](#), [823](#), [914](#),
[925*](#), [1078](#), [1301](#), [1529*](#), [1680](#), [1775](#), [1777](#), [1778](#),
[1816](#), [1820](#), [1822](#), [1826](#), [1838](#), [1881*](#), [1900*](#), [1902*](#).
I can't find file x: [556*](#).
I can't find the format...: [550*](#).
I can't go on...: [95*](#).
I can't write on file x: [556*](#).
ia_c: [1889*](#), [1890*](#), [1892*](#), [1893*](#).
ib_c: [1889*](#), [1890*](#), [1892*](#), [1893*](#).
id: [1565](#).
id_byte: [614](#), [645*](#), [670*](#).
id_lookup: [278](#), [286](#), [378*](#), [400](#), [1769](#).
ident_val: [436](#), [441](#), [491](#), [492](#).
\ifcase primitive: [513](#).
if_case_code: [513](#), [514](#), [527*](#), [1766](#).
if_cat_code: [513](#), [514](#), [527*](#).
\ifcat primitive: [513](#).
\if primitive: [513](#).
if_char_code: [513](#), [527*](#), [532](#).
if_code: [515](#), [521](#), [536](#).
if_cs_code: [1763](#), [1765](#), [1768](#).
\ifcsname primitive: [1763](#).
if_cur_ptr_is_null_then_return_or_goto: [1820](#).
if_def_code: [1763](#), [1765](#), [1767](#).
\ifdefined primitive: [1763](#).
\ifdim primitive: [513](#).
if_dim_code: [513](#), [514](#), [527*](#).
\ifeof primitive: [513](#).
if_eof_code: [513](#), [514](#), [527*](#).
\iffalse primitive: [513](#).
if_false_code: [513](#), [514](#), [527*](#).
\iffontchar primitive: [1763](#).
if_font_char_code: [1763](#), [1765](#), [1770](#).
\ifhbox primitive: [513](#).
if_hbox_code: [513](#), [514](#), [527*](#), [531](#).
\ifhmode primitive: [513](#).
if_hmode_code: [513](#), [514](#), [527*](#).
\ifincsname primitive: [1763](#).
if_in_csname_code: [1763](#), [1765](#), [1770](#).
\ifinner primitive: [513](#).

- if_inner_code*: [513](#), [514](#), [527](#)*
- `\ifnum` primitive: [513](#).
- if_int_code*: [513](#), [514](#), [527](#)*, [529](#).
- if_limit*: [515](#), [516](#), [521](#), [522](#), [523](#), [524](#), [536](#), [1669](#), [1692](#)*, [1778](#).
- if_line*: [321](#), [515](#), [516](#), [521](#), [522](#), [1516](#)*, [1692](#)*, [1777](#), [1778](#).
- if_line_field*: [515](#), [521](#), [522](#), [1516](#)*, [1692](#)*, [1778](#).
- `\ifmmode` primitive: [513](#).
- if_mmode_code*: [513](#), [514](#), [527](#)*
- if_node_size*: [515](#), [521](#), [522](#), [1516](#)*
- `\ifodd` primitive: [513](#).
- if_odd_code*: [513](#), [514](#), [527](#)*
- `\ifpdfabsdim` primitive: [1763](#).
- if_pdfabs_dim_code*: [1763](#), [1765](#), [1770](#).
- `\ifpdfabsnum` primitive: [1763](#).
- if_pdfabs_num_code*: [1763](#), [1765](#), [1770](#).
- if_pdfprimitive*: [1763](#).
- `\ifpdfprimitive` primitive: [513](#).
- if_pdfprimitive_code*: [513](#), [514](#), [527](#)*
- if_stack*: [350](#)*, [353](#)*, [384](#), [522](#), [1513](#)*, [1774](#)*, [1777](#), [1778](#).
- if_test*: [228](#), [321](#), [358](#), [388](#)*, [391](#), [513](#), [514](#), [520](#), [524](#), [529](#), [1516](#)*, [1692](#)*, [1763](#), [1766](#), [1770](#), [1777](#), [1778](#).
- `\iftrue` primitive: [513](#).
- if_true_code*: [513](#), [514](#), [527](#)*
- `\ifvbox` primitive: [513](#).
- if_vbox_code*: [513](#), [514](#), [527](#)*
- `\ifvmode` primitive: [513](#).
- if_vmode_code*: [513](#), [514](#), [527](#)*
- `\ifvoid` primitive: [513](#).
- if_void_code*: [513](#), [514](#), [527](#)*, [531](#).
- if_warning*: [522](#), [1777](#).
- ifdef*: [7](#)*, [8](#)*, [668](#)*, [670](#)*
- ifndef*: [670](#)*
- `\ifx` primitive: [513](#).
- ifx_code*: [513](#), [514](#), [527](#)*
- ignore*: [225](#), [250](#), [354](#)*, [367](#).
- ignore_depth*: [230](#), [233](#)*, [1064](#).
- ignore_spaces*: [226](#), [277](#)*, [287](#)*, [288](#)*, [394](#), [439](#), [1223](#).
- `\ignorespaces` primitive: [287](#)*
- infn_hyphen_size*: [11](#)*, [12](#)*
- Illegal magnification...: [310](#), [1436](#).
- Illegal math `\disc`...: [1298](#).
- Illegal parameter number...: [505](#).
- Illegal unit of measure: [480](#), [482](#), [485](#).
- image*: [1553](#), [1638](#)*
- image_colordepth*: [1553](#).
- image_height*: [498](#), [1553](#), [1638](#)*
- image_orig_x*: [1629](#).
- image_orig_y*: [1629](#).
- image_pages*: [1553](#).
- image_rotate*: [1553](#), [1638](#)*
- image_width*: [498](#), [1553](#), [1638](#)*
- image_x_res*: [1553](#).
- image_y_res*: [1553](#).
- img_h*: [1638](#)*
- img_w*: [1638](#)*
- `\immediate` primitive: [1525](#)*
- immediate_code*: [1525](#)*, [1527](#), [1529](#)*
- IMPOSSIBLE: [284](#)*
- Improper `\beginL`: [1704](#).
- Improper `\beginR`: [1704](#).
- Improper `\endL`: [1704](#).
- Improper `\endR`: [1704](#).
- Improper `\halign`...: [952](#).
- Improper `\hyphenation`...: [1113](#).
- Improper `\prevdepth`: [444](#).
- Improper `\setbox`: [1419](#).
- Improper `\spacefactor`: [444](#).
- Improper ‘at’ size...: [1437](#).
- Improper alphabetic constant: [468](#).
- Improper discretionary list: [1299](#).
- in*: [484](#).
- in_mutree*: [1901](#)*
- in_open*: [304](#), [326](#)*, [335](#), [350](#)*, [351](#), [353](#)*, [384](#), [522](#), [563](#)*, [1775](#), [1777](#), [1778](#), [1873](#)*, [1940](#)*
- in_state_record*: [322](#)*, [323](#)*, [1513](#)*
- in_stream*: [226](#), [1450](#), [1451](#), [1452](#).
- inaccessible*: [1394](#).
- Incompatible glue units: [434](#).
- Incompatible list...: [1288](#).
- Incompatible magnification: [310](#).
- incompleat_noad*: [230](#), [231](#)*, [894](#), [952](#), [1314](#), [1356](#), [1359](#), [1360](#), [1362](#), [1363](#).
- Incomplete `\if`...: [358](#).
- incr*: [37](#)*, [42](#), [43](#), [45](#), [46](#), [58](#), [59](#)*, [60](#), [65](#), [67](#), [70](#), [71](#)*, [82](#)*, [90](#), [98](#), [113](#), [138](#), [140](#), [170](#)*, [171](#)*, [188](#), [200](#), [221](#), [234](#), [279](#)*, [296](#), [298](#), [302](#), [316](#), [321](#), [333](#), [334](#), [343](#), [347](#)*, [348](#), [350](#)*, [365](#)*, [369](#), [374](#), [376](#)*, [377](#)*, [378](#)*, [379](#)*, [382](#), [384](#), [388](#)*, [400](#), [418](#), [421](#), [423](#), [425](#), [426](#)*, [429](#), [433](#), [468](#), [478](#), [480](#), [490](#), [501](#), [502](#), [503](#), [520](#), [543](#)*, [544](#)*, [545](#)*, [550](#)*, [551](#)*, [557](#), [563](#)*, [607](#), [625](#)*, [647](#)*, [657](#)*, [668](#)*, [670](#)*, [674](#), [680](#), [686](#), [689](#), [693](#), [698](#), [699](#), [702](#), [705](#), [706](#), [715](#), [719](#), [720](#), [725](#), [726](#), [727](#), [729](#)*, [738](#)*, [749](#), [751](#), [788](#), [793](#), [802](#), [803](#), [805](#), [817](#), [823](#), [890](#), [974](#), [1021](#), [1053](#), [1074](#), [1075](#), [1087](#)*, [1088](#), [1091](#), [1092](#), [1100](#)*, [1107](#)*, [1108](#)*, [1114](#), [1116](#)*, [1117](#)*, [1118](#)*, [1121](#)*, [1131](#), [1133](#), [1139](#), [1140](#)*, [1141](#)*, [1163](#), [1199](#), [1202](#), [1212](#), [1216](#), [1247](#), [1295](#), [1297](#), [1299](#), [1305](#), [1320](#), [1331](#), [1350](#), [1352](#), [1494](#)*, [1495](#)*, [1497](#)*, [1504](#)*, [1518](#)*, [1537](#), [1538](#), [1545](#), [1549](#), [1553](#), [1563](#), [1588](#), [1636](#), [1638](#)*, [1649](#)*, [1669](#), [1680](#), [1684](#), [1692](#)*, [1712](#), [1718](#), [1729](#),

- 1740*1755, 1756*1762, 1769, 1783, 1798, 1801,
1820, 1822, 1838, 1900*1901*1902*
- \indent primitive: [1266](#).
- indent_in_hmode*: [1266](#), [1270](#), [1271](#).
- indented*: [1269](#)*
- index*: [322](#)*[324](#)*[325](#), [326](#)*[329](#), [335](#), [350](#)*[351](#),
[353](#)*[384](#).
- index_field*: [322](#)*[324](#)*[1309](#), [1776](#).
- index_node_size*: [1816](#), [1822](#), [1826](#).
- inf*: [473](#), [474](#), [479](#), [1513](#)*
- inf_bad*: [108](#), [175](#), [1027](#), [1028](#), [1029](#), [1032](#), [1039](#),
[1151](#), [1182](#), [1194](#), [1848](#).
- inf_buf_size*: [11](#)*
- inf_dest_names_size*: [695](#), [697](#), [1513](#)*
- inf_dvi_buf_size*: [11](#)*
- inf_expand_depth*: [11](#)*
- inf_font_max*: [11](#)*
- inf_font_mem_size*: [11](#)*
- inf_hash_extra*: [11](#)*
- inf_hyph_size*: [11](#)*
- inf_main_memory*: [11](#)*
- inf_max_in_open*: [11](#)*
- inf_max_strings*: [11](#)*
- inf_mem_bot*: [11](#)*
- inf_nest_size*: [11](#)*
- inf_obj_tab_size*: [695](#), [697](#), [1513](#)*
- inf_param_size*: [11](#)*
- inf_pdf_mem_size*: [675](#), [677](#), [1513](#)*
- inf_pdf_os_buf_size*: [679](#), [681](#), [1513](#)*
- inf_penalty*: [175](#), [937](#), [943](#), [992](#), [1005](#), [1007](#), [1151](#),
[1182](#), [1190](#), [1381](#), [1383](#).
- inf_pk_dpi*: [695](#).
- inf_pool_free*: [11](#)*
- inf_pool_size*: [11](#)*
- inf_save_size*: [11](#)*
- inf_stack_size*: [11](#)*
- inf_string_vacancies*: [11](#)*
- inf_strings_free*: [11](#)*
- inf_trie_size*: [11](#)*
- Infinite glue shrinkage...: [1002](#), [1153](#),
[1181](#), [1186](#).
- infinity*: [471](#), [1791](#), [1793](#), [1799](#).
- info*: [136](#), [142](#), [144](#), [158](#), [159](#)*[173](#), [182](#), [190](#), [218](#),
[251](#), [284](#)*[297](#), [313](#), [315](#), [347](#)*[348](#), [359](#), [361](#)*[376](#)*
[379](#)*[380](#), [393](#)*[394](#), [397](#), [400](#), [415](#), [417](#), [418](#),
[419](#), [420](#), [423](#), [426](#)*[449](#), [478](#), [492](#), [504](#), [534](#),
[632](#), [635](#), [636](#), [637](#), [638](#), [639](#), [640](#), [641](#), [642](#),
[693](#), [695](#), [700](#), [766](#), [767](#), [771](#), [773](#), [775](#), [779](#),
[781](#), [782](#), [783](#), [784](#), [786](#), [857](#), [865](#), [868](#), [869](#),
[874](#), [896](#), [910](#), [911](#), [912](#), [913](#), [914](#), [918](#), [925](#)*
[930](#), [944](#), [945](#), [948](#), [955](#), [959](#), [960](#), [966](#), [969](#),
[970](#), [973](#), [974](#), [977](#), [979](#), [997](#), [1023](#), [1024](#), [1102](#)*
- 1109, 1115, 1158, 1243, 1254, 1271, 1327, 1329,
1346*1359, 1363, 1364, 1369, 1396, 1399*1404,
1426, 1427, 1467, 1474, 1491*1520*1522*1619*
1637, 1638*1675, 1706, 1708, 1709, 1710, 1712,
1713, 1718, 1719, 1724, 1729, 1732, 1738, 1740*
1751, 1755, 1757, 1758, 1769, 1773, 1816, 1820,
1821, 1825, 1826, 1900*1901*1940*
- ini_version*: [8](#)*[32](#)*[1480](#)*
- init**: [8](#)*[32](#)*[47](#)*[50](#), [149](#), [286](#), [1068](#), [1111](#)*[1119](#),
[1120](#)*[1124](#)*[1127](#)*[1481](#)*[1504](#)*[1517](#), [1518](#)*
[1649](#)*[1832](#).
- Init**: [8](#)*[1430](#)*[1513](#)*[1516](#)*
- init_align*: [949](#), [950](#), [1308](#)*
- init_col*: [949](#), [961](#), [964](#), [967](#).
- init_cur_lang*: [992](#), [1068](#), [1069](#).
- init_font_base*: [705](#).
- init_l_hyf*: [992](#), [1068](#), [1069](#).
- init_lft*: [1077](#), [1080](#), [1082](#), [1085](#).
- init_lig*: [1077](#), [1080](#), [1082](#), [1085](#).
- init_list*: [1077](#), [1080](#), [1082](#), [1085](#).
- init_math*: [1315](#), [1316](#), [1706](#).
- init_pdf_output*: [687](#), [688](#), [750](#)*
- init_pool_ptr*: [39](#)*[42](#), [1489](#)*[1513](#)*[1515](#)*
- init_prim*: [1513](#)*[1517](#).
- init_r_hyf*: [992](#), [1068](#), [1069](#).
- init_randoms*: [125](#), [1518](#)*[1586](#).
- init_row*: [949](#), [961](#), [962](#).
- init_span*: [949](#), [962](#), [963](#), [967](#).
- init_start_time*: [1585](#).
- init_str_ptr*: [39](#)*[43](#), [543](#)*[1489](#)*[1513](#)*[1515](#)*
- init_terminal*: [37](#)*[353](#)*
- init_trie*: [1068](#), [1143](#)*[1503](#)*
- INITEX: [8](#)*[11](#)*[12](#)*[47](#)*[50](#), [134](#)*[1478](#), [1512](#),
[1826](#), [1832](#).
- initialize*: [4](#)*[1513](#)*[1518](#)*
- inner loop: [31](#)*[112](#), [113](#), [116](#), [130](#)*[138](#), [139](#), [140](#),
[141](#), [143](#)*[145](#), [146](#), [148](#), [220](#)*[346](#)*[347](#)*[363](#)*[364](#),
[365](#)*[379](#)*[387](#), [406](#), [425](#), [433](#), [580](#)*[624](#)*[638](#), [648](#)*
[825](#), [828](#), [829](#), [1008](#), [1011](#), [1027](#), [1028](#), [1043](#),
[1207](#), [1211](#)*[1212](#), [1213](#)*[1216](#), [1219](#), [1885](#)*[1886](#)*
- inner_noad*: [858](#), [859](#), [866](#), [872](#), [874](#), [909](#), [937](#),
[940](#), [1334](#), [1335](#), [1369](#).
- input*: [228](#), [388](#)*[391](#), [402](#), [403](#), [1748](#).
- \input primitive: [402](#).
- input_file*: [326](#)*[1513](#)*
- \inputlineno primitive: [442](#).
- input_line_no_code*: [442](#), [443](#), [450](#).
- input_ln*: [30](#)*[31](#)*[37](#)*[58](#), [71](#)*[384](#), [511](#), [512](#), [564](#).
- input_ptr*: [323](#)*[333](#), [334](#), [343](#), [344](#), [352](#), [353](#)*[382](#),
[426](#)*[427](#)*[560](#)*[563](#)*[1309](#), [1516](#)*[1775](#), [1777](#).
- input_stack*: [84](#)*[85](#), [254](#)*[323](#)*[333](#), [343](#), [344](#), [560](#)*
[1309](#), [1513](#)*[1775](#), [1776](#), [1777](#).

- ins_disc*: [1209](#), [1210](#), [1212](#).
- ins_error*: [349](#), [358](#), [421](#), [1225](#), [1305](#), [1310](#), [1393](#).*
- ins_list*: [345](#), [361](#)*, [493](#), [496](#), [497](#), [1242](#), [1619](#)*, [1940](#).*
- ins_node*: [158](#), [166](#), [193](#), [201](#), [220](#)*, [224](#)*, [819](#), [825](#),
[906](#), [937](#), [1005](#), [1042](#), [1076](#), [1145](#), [1150](#), [1158](#),
[1163](#), [1177](#), [1191](#), [1278](#).*
- ins_node_size*: [158](#), [220](#)*, [224](#)*, [1199](#), [1278](#).*
- ins_ptr*: [158](#), [206](#), [220](#)*, [224](#)*, [1187](#), [1197](#), [1198](#), [1278](#).*
- ins_the_toks*: [388](#)*, [391](#), [493](#).
- insert*: [226](#), [287](#)*, [288](#)*, [1275](#).
- insert*>: [87](#).
- \insert* primitive: [287](#).*
- insert_before_tail*: [232](#), [1217](#).
- insert_dollar_sign*: [1223](#), [1225](#).
- insert_group*: [291](#), [1246](#), [1277](#), [1278](#)*, [1662](#), [1680](#).
- insert_penalties*: [445](#), [1159](#), [1167](#), [1182](#), [1185](#),
[1187](#), [1191](#), [1199](#), [1203](#)*, [1420](#), [1424](#).
- \insertpenalties* primitive: [442](#).
- insert_relax*: [404](#), [405](#), [536](#).
- insert_src_special*: [1269](#)*, [1317](#)*, [1345](#)*, [1940](#).*
- insert_src_special_auto*: [32](#)*, [1211](#).*
- insert_src_special_every_cr*: [32](#).*
- insert_src_special_every_display*: [32](#).*
- insert_src_special_every_hbox*: [32](#).*
- insert_src_special_every_math*: [32](#)*, [1317](#).*
- insert_src_special_every_par*: [32](#)*, [1269](#).*
- insert_src_special_every_parend*: [32](#).*
- insert_src_special_every_vbox*: [32](#)*, [1345](#).*
- insert_token*: [290](#), [302](#), [304](#).
- inserted*: [329](#), [336](#), [345](#), [346](#)*, [349](#), [405](#), [1263](#)*, [1273](#),
[1278](#)*, [1308](#)*, [1311](#)*, [1346](#).*
- inserting*: [1158](#), [1186](#).
- Insertions can only...: [1170](#).
- inserts_only*: [1157](#), [1164](#), [1185](#).
- int*: [128](#)*, [131](#)*, [132](#), [153](#)*, [158](#), [160](#), [175](#), [204](#)*, [231](#)*,
[237](#)*, [254](#)*, [258](#)*, [260](#), [296](#), [300](#), [301](#), [439](#), [440](#)*,
[515](#), [632](#), [695](#), [710](#), [901](#), [945](#), [948](#), [995](#), [1415](#),
[1426](#), [1495](#)*, [1650](#), [1789](#), [1821](#).
- int_base*: [238](#)*, [248](#)*, [250](#), [254](#)*, [256](#)*, [257](#), [258](#)*, [260](#),
[270](#)*, [271](#)*, [272](#), [290](#), [305](#)*, [310](#), [1190](#), [1248](#), [1317](#)*,
[1323](#), [1402](#)*, [1494](#)*, [1650](#), [1658](#), [1909](#)*, [1913](#).*
- int_error*: [91](#), [310](#), [459](#), [460](#), [461](#), [462](#), [463](#), [497](#),
[683](#), [1421](#), [1422](#), [1436](#), [1697](#), [1812](#), [1874](#).*
- int_par*: [254](#)*, [673](#).*
- int_pars*: [254](#).*
- int_val*: [436](#), [437](#), [439](#), [440](#)*, [442](#), [443](#), [444](#), [445](#), [448](#),
[449](#), [450](#), [452](#), [453](#), [454](#), [455](#), [465](#), [466](#), [475](#), [487](#),
[491](#), [497](#), [1402](#)*, [1414](#), [1415](#), [1416](#), [1418](#), [1490](#)*,
[1491](#)*, [1538](#), [1779](#), [1780](#), [1781](#), [1784](#), [1786](#), [1791](#),
[1793](#), [1796](#), [1799](#), [1816](#), [1817](#), [1819](#), [1824](#), [1833](#).
- integer*: [3](#), [11](#)*, [13](#), [19](#)*, [20](#)*, [32](#)*, [38](#)*, [45](#), [54](#)*, [59](#)*, [60](#),
[63](#), [66](#), [67](#), [69](#), [82](#)*, [91](#), [94](#)*, [96](#), [100](#), [101](#), [102](#),
[105](#), [106](#), [107](#), [108](#), [109](#)*, [110](#), [112](#), [114](#), [117](#), [119](#),
[122](#), [124](#), [125](#), [126](#), [127](#), [128](#)*, [131](#)*, [135](#), [143](#)*, [176](#)*,
[181](#), [190](#), [191](#), [192](#)*, [194](#)*, [195](#), [196](#), [199](#), [200](#), [229](#)*,
[230](#), [236](#), [243](#), [255](#)*, [264](#), [265](#), [274](#)*, [278](#), [281](#), [284](#)*,
[286](#), [300](#), [301](#), [308](#), [314](#), [320](#), [321](#), [322](#)*, [326](#)*, [330](#)*,
[331](#), [333](#), [337](#), [388](#)*, [436](#), [439](#), [466](#), [474](#), [476](#), [496](#),
[508](#), [515](#), [519](#), [520](#), [524](#), [544](#)*, [545](#)*, [546](#)*, [549](#)*, [574](#)*,
[575](#)*, [576](#)*, [586](#)*, [597](#), [604](#)*, [605](#), [608](#)*, [619](#)*, [622](#)*, [627](#),
[628](#), [634](#), [642](#), [643](#), [647](#)*, [657](#)*, [666](#)*, [673](#)*, [674](#), [676](#),
[678](#), [680](#), [682](#), [686](#), [687](#), [689](#), [690](#), [691](#), [692](#), [693](#),
[694](#), [696](#), [698](#), [700](#), [701](#), [702](#), [705](#), [706](#), [707](#), [708](#),
[710](#), [712](#), [720](#), [725](#), [727](#), [750](#)*, [772](#), [774](#), [778](#), [793](#),
[795](#), [797](#), [817](#), [818](#), [821](#), [823](#), [837](#), [867](#), [870](#), [875](#),
[882](#), [892](#), [893](#), [902](#), [914](#), [928](#), [940](#), [999](#), [1004](#),
[1005](#), [1006](#), [1009](#), [1048](#), [1053](#), [1069](#), [1089](#), [1099](#),
[1103](#)*, [1143](#)*, [1147](#), [1157](#), [1159](#), [1171](#), [1189](#), [1207](#),
[1209](#), [1246](#), [1253](#), [1257](#), [1262](#), [1269](#)*, [1295](#), [1297](#),
[1316](#), [1329](#), [1333](#), [1372](#), [1389](#)*, [1414](#), [1471](#)*, [1481](#)*,
[1482](#)*, [1502](#)*, [1506](#), [1512](#), [1513](#)*, [1514](#)*, [1518](#)*, [1519](#)*,
[1529](#)*, [1544](#), [1546](#), [1548](#), [1551](#), [1553](#), [1556](#), [1557](#),
[1558](#), [1560](#), [1563](#), [1565](#), [1571](#), [1584](#), [1601](#), [1616](#)*,
[1618](#)*, [1628](#), [1629](#), [1631](#), [1633](#), [1638](#)*, [1680](#), [1706](#),
[1745](#), [1754](#), [1757](#), [1778](#), [1783](#), [1794](#), [1798](#), [1800](#),
[1840](#), [1841](#), [1868](#)*, [1871](#)*, [1877](#)*, [1879](#)*, [1881](#)*, [1885](#)*,
[1886](#)*, [1889](#)*, [1900](#)*, [1901](#)*, [1902](#)*, [1907](#)*, [1912](#).*
- \interlinepenalties* primitive: [1865](#).
- inter_line_penalties_loc*: [248](#)*, [1248](#), [1865](#), [1866](#).
- inter_line_penalties_ptr*: [1067](#), [1248](#), [1865](#).
- inter_line_penalty*: [254](#)*, [1067](#).
- \interlinepenalty* primitive: [256](#).*
- inter_line_penalty_code*: [254](#)*, [255](#)*, [256](#).*
- interaction*: [71](#)*, [72](#), [73](#)*, [74](#)*, [75](#), [82](#)*, [83](#), [84](#)*, [86](#),
[90](#), [92](#), [93](#)*, [98](#), [382](#), [385](#)*, [510](#)*, [556](#)*, [686](#), [1443](#)*,
[1461](#)*, [1471](#)*, [1473](#)*, [1476](#)*, [1507](#), [1508](#)*, [1509](#),
[1514](#)*, [1516](#)*, [1695](#).
- \interactionmode* primitive: [1693](#).
- interaction_option*: [73](#)*, [74](#)*, [1508](#).*
- internal_font_number*: [162](#)*, [192](#)*, [574](#)*, [575](#)*, [586](#)*,
[604](#)*, [605](#), [608](#)*, [609](#)*, [619](#)*, [629](#)*, [643](#), [673](#)*, [686](#), [690](#),
[691](#), [692](#), [693](#), [705](#), [706](#), [710](#), [712](#), [720](#), [725](#), [821](#),
[823](#), [882](#), [885](#), [887](#), [888](#), [891](#), [900](#), [914](#), [1006](#),
[1038](#), [1069](#), [1209](#), [1291](#), [1301](#), [1316](#), [1389](#)*, [1435](#)*,
[1502](#)*, [1518](#)*, [1588](#), [1885](#)*, [1886](#).*
- interrupt*: [96](#), [97](#), [98](#), [1208](#).
- Interruption: [98](#).
- interwoven alignment preambles...*: [346](#)*,
[958](#), [965](#), [967](#), [1309](#).
- int0*: [694](#), [695](#), [1505](#), [1506](#).
- int1*: [694](#), [695](#), [1505](#), [1506](#).
- int2*: [694](#), [695](#), [1506](#).
- int3*: [694](#), [695](#), [1505](#), [1506](#).
- int4*: [694](#), [695](#), [1505](#), [1506](#).

- Invalid code: [1410](#)*
- Invalid negative color stack number: [1540](#).
- invalid_char*: [225](#), [250](#), [366](#).
- invalid_code*: [22](#), [24](#)*, [250](#).
- ipc_on*: [668](#)*, [1868](#)*.
- ipc_page*: [668](#)*.
- is_char_node*: [152](#), [192](#)*, [201](#), [220](#)*, [223](#), [450](#), [498](#), [648](#)*, [658](#), [674](#), [705](#), [731](#)*, [740](#), [823](#), [825](#), [845](#), [891](#), [896](#), [897](#)*, [932](#), [981](#), [992](#), [1005](#), [1013](#), [1017](#), [1018](#), [1042](#), [1043](#), [1044](#), [1046](#), [1047](#), [1055](#), [1057](#), [1073](#), [1074](#), [1076](#), [1080](#), [1213](#)*, [1217](#), [1218](#), [1258](#), [1283](#), [1288](#), [1291](#), [1299](#), [1325](#), [1380](#), [1638](#)*, [1708](#), [1725](#), [1734](#)*, [1739](#)*.
- IS_DIR_SEP*: [542](#)*.
- is_empty*: [142](#), [145](#), [187](#), [188](#).
- is_error*: [1538](#).
- is_hex*: [374](#), [377](#)*.
- is_hex_char*: [702](#).
- is_hex_string*: [702](#).
- is_in_cname*: [389](#), [390](#), [398](#)*, [1768](#), [1770](#).
- is_letterspaced_font*: [706](#).
- is_names*: [804](#), [805](#), [1514](#)*.
- is_new_source*: [1940](#)*.
- is_obj_scheduled*: [695](#), [1631](#), [1636](#).
- is_obj_written*: [695](#), [773](#), [775](#), [779](#), [784](#), [812](#), [813](#), [814](#).
- is_pdf_image*: [498](#), [1553](#), [1638](#)*.
- is_png_image*: [1638](#)*.
- is_root*: [802](#), [803](#), [1514](#)*.
- is_running*: [156](#)*, [194](#)*, [652](#), [661](#), [730](#), [734](#), [739](#), [743](#), [982](#), [1553](#), [1631](#), [1636](#), [1638](#)*.
- is_shipping_page*: [750](#)*, [1631](#), [1636](#), [1638](#)*, [1641](#), [1642](#).
- is_unless*: [524](#).
- is_valid_char*: [604](#)*, [673](#)*, [705](#), [717](#), [726](#), [731](#)*.
- isscalable*: [690](#), [693](#).
- issue_message*: [1454](#), [1457](#)*.
- ital_corr*: [226](#), [287](#)*, [288](#)*, [1289](#), [1290](#).
- italic correction: [569](#).
- italic_base*: [576](#)*, [580](#)*, [592](#), [598](#), [705](#), [706](#), [1501](#)*, [1502](#)*, [1518](#)*.
- italic_index*: [569](#).
- its_all_over*: [1223](#), [1232](#), [1516](#)*.
- i1*: [1538](#).
- i2*: [1538](#).
- j*: [45](#), [46](#), [59](#)*, [60](#), [69](#), [70](#), [125](#), [278](#), [281](#), [286](#), [337](#), [363](#)*, [388](#)*, [496](#), [508](#), [543](#)*, [544](#)*, [545](#)*, [549](#)*, [550](#)*, [666](#)*, [686](#), [693](#), [749](#), [1070](#), [1078](#), [1083](#), [1111](#)*, [1143](#)*, [1316](#), [1389](#)*, [1481](#)*, [1482](#)*, [1529](#)*, [1618](#)*, [1621](#)*, [1657](#), [1680](#), [1742](#), [1745](#), [1901](#)*.
- j_random*: [110](#), [124](#), [126](#), [127](#).
- Japanese characters: [152](#), [612](#).
- Jensen, Kathleen: [10](#).
- jj*: [125](#).
- job aborted: [382](#).
- job aborted, file error...: [556](#)*.
- job_name*: [92](#), [497](#), [498](#), [553](#), [554](#), [555](#), [558](#)*, [560](#)*, [563](#)*, [684](#), [1435](#)*, [1509](#), [1516](#)*.
- \jobname* primitive: [494](#).
- job_name_code*: [494](#), [496](#), [497](#), [498](#).
- jump_out*: [81](#)*, [82](#)*, [84](#)*, [93](#)*.
- just_box*: [990](#), [1065](#), [1066](#), [1326](#), [1735](#), [1741](#).
- just_copy*: [1734](#)*, [1735](#), [1739](#)*.
- just_open*: [506](#), [509](#), [1453](#)*.
- just_reverse*: [1738](#), [1739](#)*.
- j1*: [793](#), [1538](#).
- j2*: [793](#), [1538](#).
- k*: [45](#), [46](#), [47](#)*, [64](#), [65](#), [67](#), [69](#), [71](#)*, [102](#), [119](#), [124](#), [125](#), [181](#), [278](#), [281](#), [286](#), [363](#)*, [385](#)*, [433](#), [476](#), [490](#), [545](#)*, [549](#)*, [551](#)*, [556](#)*, [560](#)*, [586](#)*, [614](#), [629](#)*, [634](#), [666](#)*, [686](#), [693](#), [702](#), [705](#), [706](#), [712](#), [823](#), [881](#), [1083](#), [1106](#), [1111](#)*, [1137](#)*, [1143](#)*, [1257](#), [1389](#)*, [1481](#)*, [1482](#)*, [1519](#)*, [1529](#)*, [1546](#), [1553](#), [1563](#), [1610](#)*, [1638](#)*, [1657](#), [1816](#), [1870](#)*.
- kern*: [226](#), [571](#), [1235](#), [1236](#), [1237](#).
- \kern* primitive: [1236](#).
- kern_base*: [576](#)*, [583](#), [592](#), [600](#)*, [603](#)*, [705](#), [706](#), [1501](#)*, [1502](#)*, [1518](#)*.
- kern_base_offset*: [583](#), [592](#), [600](#)*, [705](#).
- kern_break*: [1042](#).
- kern_flag*: [571](#), [823](#), [917](#), [929](#), [1086](#), [1218](#).
- kern_node*: [173](#), [174](#)*, [201](#), [220](#)*, [224](#)*, [450](#), [650](#)*, [659](#), [674](#), [705](#), [732](#)*, [741](#), [825](#), [845](#), [897](#)*, [906](#), [908](#), [937](#), [1005](#), [1013](#), [1017](#), [1018](#), [1032](#), [1042](#), [1044](#), [1046](#), [1047](#), [1055](#), [1057](#), [1073](#), [1074](#), [1076](#), [1145](#), [1149](#), [1150](#), [1153](#), [1173](#), [1174](#), [1177](#), [1181](#), [1284](#), [1285](#), [1286](#), [1299](#), [1325](#), [1638](#)*, [1700](#), [1712](#), [1718](#), [1726](#)*, [1729](#), [1730](#)*, [1734](#)*, [1740](#)*, [1935](#)*.
- kern_shrink*: [823](#), [825](#), [1015](#).
- kern_stretch*: [823](#), [825](#), [1015](#).
- kk*: [476](#), [478](#), [749](#).
- kn*: [705](#).
- \knaccode* primitive: [1432](#).
- kn_ac_code_base*: [173](#), [452](#), [1431](#), [1432](#), [1433](#).
- \knbccode* primitive: [1432](#).
- kn_bc_code_base*: [173](#), [452](#), [1431](#), [1432](#), [1433](#).
- \knbscode* primitive: [1432](#).
- kn_bs_code_base*: [173](#), [452](#), [1431](#), [1432](#), [1433](#).
- Knuth, Donald Ervin: [2](#)*, [86](#), [869](#), [989](#), [1068](#), [1102](#)*, [1174](#), [1332](#), [1619](#)*, [1680](#), [1701](#).
- kpse_find_file*: [589](#)*.
- kpse_in_name_ok*: [563](#)*, [1453](#)*.
- kpse_init_prog*: [792](#).
- kpse_make_tex_discard_errors*: [1443](#)*.

- kpse_out_name_ok*: 1623*
kpse_pk_format: 792.
kpse_set_program_enabled: 792.
kpse_src_compile: 792.
kpse_tex_format: 563*, 1453*
l: [47*](#), [127](#), [278](#), [281](#), [286](#), [298](#), [303](#), [314](#), [321](#),
[337](#), [520](#), [523](#), [560*](#), [628](#), [642](#), [823](#), [844](#), [1005](#),
[1006](#), [1078](#), [1121*](#), [1130](#), [1137*](#), [1316](#), [1372](#),
[1414](#), [1471*](#), [1481*](#), [1519*](#), [1625](#), [1680](#), [1724](#), [1739*](#),
[1754](#), [1778](#), [1783](#), [1826](#).
L_code: [165*](#), 193, 210, 1042, 1073, 1076, 1718,
1719, 1737, 1738.
l_hyf: 1068, [1069](#), 1071, 1076, 1079, 1100*,
1610, 1611.
language: [254*](#), 1111*, 1211*, 1625.
\language primitive: [256*](#)
language_code: [254*](#), 255*, 256*
language_node: [1522*](#), [1604*](#), 1605, 1606, 1610,
1611, 1621*, 1625, 1626.
large_attempt: [882](#).
large_char: [859](#), 867, 873, 882, 1338.
large_fam: [859](#), 867, 873, 882, 1338.
last: [30*](#), [31*](#), [35*](#), [36](#), [37*](#), [71*](#), 83, 87, 88, 353*, 382,
385*, 509, 550*, 557, 1757.
last_active: [995](#), 996, 1008, 1011, 1020, 1030, 1036,
1037, 1039, 1040, 1041, 1049, 1050, 1051.
last_attr: 1601.
last_badness: 450, [818](#), 820, 823, 836, 840, 843,
844, 850, 852, 854.
last_bop: [619*](#), 620, 668*, 670*
\lastbox primitive: [1249](#).
last_box_code: [1249](#), 1250, 1257, 1516*, 1860,
1862, 1863.
last_found: 1900*
last_glue: 233*, 450, [1159](#), 1168, 1173, 1194,
1284, 1516*
last_ins_ptr: [1158](#), 1182, 1185, 1195, 1197.
last_item: [226](#), 439, 442, 443, 1226, 1650, 1664,
1667, 1670, 1673, 1779, 1802, 1806.
last_kern: 233*, 450, [1159](#), 1168, 1173.
\lastkern primitive: [442](#).
last_leftmost_char: [821](#), 822, 823, 1063.
last_line_fill: 992, [1843](#), 1844, 1854.
last_line_fit: [254*](#), 1843, 1844, 1847.
\lastlinefit primitive: [1658](#).
last_line_fit_code: [254*](#), 1658, 1660.
last_node_type: 233*, 450, [1159](#), 1168, 1173.
\lastnodetype primitive: [1650](#).
last_node_type_code: [442](#), 450, 1650, 1651.
last_penalty: 233*, 450, [1159](#), 1168, 1173.
\lastpenalty primitive: [442](#).
last_pos: 1638*
last_rightmost_char: [821](#), 822, 823, 1057.
\lastskip primitive: [442](#).
last_special_line: [1023](#), 1024, 1025, 1026, 1066.
last_text_char: [19*](#), [24*](#)
last_thread: 739, 754, [1629](#), 1638*
last_tokens_string: 686, [708](#), 709, 1564, 1631.
last_type: 1900*
latespecial_node: 727, [1522*](#), 1535*, 1604*, 1605,
1606, 1616*, 1621*, 1640, 1646.
lc: 823.
lc_code: [248*](#), 250, 1068, 1139, 1855*, 1857, 1858,
1859.
\lccode primitive: [1408*](#)
lc_code_base: [248*](#), 253, 1408*, 1409*, 1464, 1465,
1466.
leader_box: [647*](#), 654, 656, [657*](#), 663, 665, [729*](#),
736, 737, [738*](#), 745, 746.
leader_flag: [1249](#), 1251, 1256, 1262, 1682.
leader_ht: [657*](#), 663, 664, 665, [738*](#), 745, 746.
leader_ptr: [167](#), 170*, 171*, 208, 220*, 224*, 654, 663,
736, 745, 832, 847, 992, 1256, 1734*
leader_ship: [226](#), 1249, 1250, 1251, 1682.
leader_wd: [647*](#), 654, 655, 656, [729*](#), 736, 737.
leaders: 1623*
Leaders not followed by...: 1256.
\leaders primitive: [1249](#).
least_cost: [1147](#), 1151, 1157.
least_page_cost: [1157](#), 1164, 1182, 1183.
left: 693.
\left primitive: [1366](#).
left_brace: [225](#), 311, 316, 320, 369, 379*, 429, 499,
552*, 953, 1241, 1328, 1404, 1881*
left_brace_limit: [311](#), 347*, 348, 418, 420, 425, 502.
left_brace_token: [311](#), 429, 1305, 1404, 1619*, 1940*
left_delimiter: [859](#), 872, 873, 913, 924, 1341,
1359, 1360.
left_edge: [647*](#), 655, [657*](#), 660*, 661, 665, [729*](#), 730,
[738*](#), 739, 742*, 743, 746, 1640, 1644, 1645,
1646, 1720, 1721, 1723*
left_hyphen_min: [254*](#), 1269*, 1378, 1625, 1626.
\lefthyphenmin primitive: [256*](#)
left_hyphen_min_code: [254*](#), 255*, 256*
\leftmarginkern primitive: [494](#).
left_margin_kern_code: [494](#), 495, 497, 498.
left_noad: 230, [863](#), 866, 872, 874, 901, 903, 904,
909, 936, 937, 938, 1363, 1366, 1367, 1369, 1680.
left_pw: 822, [823](#), 1005, 1063.
left_right: [226](#), 1224, 1366, 1367, 1368, 1698.
left_side: [173](#), 201, 498, 823, 1063.
left_skip: [242](#), 1003, 1056, 1063, 1741, 1844.
\leftskip primitive: [244](#).
left_skip_code: [242](#), 243, 244, 498, 1063, 1741, 1747.

- left_to_right*: [643](#), [1707](#), [1715](#), [1731](#), [1736](#).
len: [693](#), [1877](#)*.
length: [40](#), [46](#), [278](#), [281](#), [545](#)*, [556](#)*, [563](#)*, [589](#)*, [629](#)*,
[686](#), [693](#), [702](#), [706](#), [712](#), [727](#), [749](#), [793](#), [801](#),
[807](#), [1108](#)*, [1118](#)*, [1458](#)*, [1631](#), [1877](#)*.
length of lines: [1023](#).
`\leqno` primitive: [1319](#).
let: [227](#)*, [284](#)*, [1388](#), [1397](#)*, [1398](#)*, [1399](#)*.
`\let` primitive: [1397](#)*.
letter: [225](#), [250](#), [284](#)*, [311](#), [313](#), [316](#), [320](#), [369](#),
[376](#)*, [378](#)*, [1112](#), [1138](#), [1206](#), [1207](#), [1215](#), [1268](#),
[1302](#), [1329](#), [1332](#), [1338](#).
letter_space_font: [706](#).
letter_token: [311](#), [471](#).
letterspace_font: [227](#)*, [287](#)*, [288](#)*, [439](#), [604](#)*, [1388](#),
[1434](#).
`\letterspacefont` primitive: [287](#)*.
level: [436](#), [439](#), [441](#), [444](#), [454](#), [487](#), [1781](#), [1873](#)*.
level_boundary: [290](#), [292](#), [296](#), [304](#).
level_one: [239](#), [246](#), [250](#), [272](#), [277](#)*, [286](#), [294](#), [299](#),
[300](#), [301](#), [302](#), [303](#), [305](#)*, [956](#), [1483](#), [1516](#)*, [1617](#),
[1666](#), [1821](#), [1841](#), [1842](#).
level_zero: [239](#), [240](#)*, [294](#), [298](#), [302](#), [1487](#)*, [1837](#).
lf: [566](#), [586](#)*, [591](#), [592](#), [602](#)*, [603](#)*, [705](#), [706](#), [720](#).
lft_hit: [1083](#), [1084](#), [1085](#), [1087](#)*, [1088](#), [1210](#),
[1212](#), [1218](#).
lh: [128](#)*, [132](#), [136](#), [231](#)*, [237](#)*, [274](#)*, [275](#), [566](#), [567](#),
[586](#)*, [591](#), [592](#), [594](#), [861](#), [1818](#).
Liang, Franklin Mark: [2](#)*, [1096](#).
libc_free: [545](#)*, [549](#)*, [1486](#)*, [1487](#)*.
libpdf_finish: [794](#).
lig_char: [161](#), [162](#)*, [211](#), [224](#)*, [705](#), [823](#), [825](#), [826](#),
[1017](#), [1018](#), [1042](#), [1046](#), [1047](#), [1075](#), [1080](#),
[1291](#), [1728](#), [1734](#)*.
lig_kern: [570](#), [571](#), [575](#)*.
lig_kern_base: [576](#)*, [583](#), [592](#), [598](#), [600](#)*, [603](#)*, [705](#),
[706](#), [1501](#)*, [1502](#)*, [1518](#)*.
lig_kern_command: [567](#), [571](#).
lig_kern_restart: [583](#), [823](#), [917](#), [928](#), [1086](#), [1216](#).
lig_kern_restart_end: [583](#).
lig_kern_start: [583](#), [823](#), [917](#), [928](#), [1086](#), [1216](#).
lig_ptr: [161](#), [162](#)*, [193](#), [211](#), [220](#)*, [224](#)*, [823](#), [1073](#),
[1075](#), [1080](#), [1084](#), [1087](#)*, [1088](#), [1214](#)*, [1218](#), [1728](#).
lig_stack: [1084](#), [1085](#), [1087](#)*, [1088](#), [1209](#), [1211](#)*,
[1212](#), [1213](#)*, [1214](#)*, [1215](#), [1218](#).
lig_tag: [570](#), [595](#), [604](#)*, [705](#), [823](#), [917](#), [928](#), [1086](#),
[1216](#).
lig_trick: [180](#), [648](#)*, [731](#)*, [826](#).
ligature_node: [161](#), [162](#)*, [166](#), [193](#), [201](#), [220](#)*, [224](#)*,
[650](#)*, [705](#), [732](#)*, [823](#), [825](#), [928](#), [1017](#), [1018](#), [1042](#),
[1046](#), [1047](#), [1073](#), [1074](#), [1076](#), [1080](#), [1291](#),
[1299](#), [1325](#), [1728](#), [1734](#)*.
ligature_present: [1083](#), [1084](#), [1085](#), [1087](#)*, [1088](#),
[1210](#), [1212](#), [1214](#)*, [1218](#).
limit: [71](#)*, [322](#)*, [324](#)*, [325](#), [329](#), [340](#)*, [350](#)*, [352](#), [353](#)*,
[365](#)*, [370](#), [372](#), [373](#), [374](#), [376](#)*, [377](#)*, [378](#)*, [382](#),
[384](#), [385](#)*, [509](#), [510](#)*, [512](#), [552](#)*, [563](#)*, [564](#), [1518](#)*,
[1756](#)*, [1762](#), [1900](#)*.
Limit controls must follow...: [1337](#).
limit_field: [35](#)*, [87](#), [322](#)*, [324](#)*, [560](#)*.
limit_switch: [226](#), [1224](#), [1334](#), [1335](#), [1336](#).
limits: [858](#), [872](#), [909](#), [925](#)*, [1334](#), [1335](#).
`\limits` primitive: [1334](#).
line: [84](#)*, [234](#), [296](#), [321](#), [326](#)*, [335](#), [350](#)*, [351](#), [353](#)*,
[384](#), [450](#), [520](#), [521](#), [564](#), [839](#), [851](#), [1202](#), [1756](#)*,
[1873](#)*, [1917](#)*, [1940](#)*.
line_break: [180](#), [990](#), [991](#), [999](#), [1004](#), [1015](#), [1024](#),
[1038](#), [1039](#), [1042](#), [1052](#), [1071](#), [1111](#)*, [1144](#),
[1147](#), [1159](#), [1274](#), [1323](#).
line_diff: [1048](#), [1051](#).
line_number: [995](#), [996](#), [1009](#), [1011](#), [1021](#), [1022](#),
[1026](#), [1040](#), [1048](#), [1050](#), [1051](#).
line_penalty: [254](#)*, [1035](#).
`\linepenalty` primitive: [256](#)*.
line_penalty_code: [254](#)*, [255](#)*, [256](#)*.
line_skip: [242](#), [265](#).
`\lineskip` primitive: [244](#).
line_skip_code: [167](#), [170](#)*, [242](#), [243](#), [244](#), [855](#).
line_skip_limit: [265](#), [855](#).
`\lineskiplimit` primitive: [266](#).
line_skip_limit_code: [265](#), [266](#).
line_stack: [326](#)*, [335](#), [350](#)*, [351](#), [1513](#)*, [1873](#)*.
line_width: [1006](#), [1026](#), [1027](#).
link: [136](#), [138](#), [139](#), [140](#), [141](#), [142](#), [143](#)*, [144](#), [148](#),
[151](#), [152](#), [153](#)*, [158](#), [159](#)*, [160](#), [161](#), [168](#), [182](#), [186](#),
[190](#), [192](#)*, [193](#), [194](#)*, [200](#), [220](#)*, [222](#), [230](#), [232](#), [233](#)*,
[236](#), [241](#), [251](#), [284](#)*, [314](#), [317](#), [321](#), [328](#)*, [341](#), [345](#),
[348](#), [361](#)*, [376](#)*, [379](#)*, [380](#), [388](#)*, [393](#)*, [394](#), [397](#), [400](#),
[415](#), [416](#)*, [417](#), [420](#), [422](#), [423](#), [426](#)*, [433](#), [450](#), [478](#),
[490](#), [492](#), [493](#), [496](#), [497](#), [498](#), [504](#), [515](#), [521](#), [522](#),
[523](#), [534](#), [632](#), [634](#), [636](#), [638](#), [642](#), [648](#)*, [650](#)*, [658](#),
[674](#), [686](#), [693](#), [695](#), [700](#), [705](#), [727](#), [731](#)*, [732](#)*, [740](#),
[766](#), [767](#), [771](#), [772](#), [773](#), [775](#), [779](#), [781](#), [782](#), [783](#),
[784](#), [786](#), [823](#), [825](#), [826](#), [828](#), [831](#), [842](#), [845](#), [855](#),
[857](#), [865](#), [881](#), [887](#), [891](#), [894](#), [895](#), [896](#), [897](#)*, [903](#),
[907](#), [908](#), [911](#), [913](#), [914](#), [915](#), [923](#), [924](#), [927](#), [928](#),
[929](#), [930](#), [931](#), [932](#), [935](#), [936](#), [937](#), [942](#), [943](#), [946](#),
[948](#), [954](#), [955](#), [959](#), [960](#), [962](#), [966](#), [967](#), [969](#), [970](#),
[971](#), [972](#), [973](#), [974](#), [975](#), [977](#), [978](#), [979](#), [980](#),
[981](#), [982](#), [983](#), [984](#), [985](#), [988](#), [990](#), [992](#), [995](#),
[997](#), [998](#), [1005](#), [1006](#), [1013](#), [1016](#), [1019](#), [1020](#),
[1021](#), [1030](#), [1033](#), [1034](#), [1036](#), [1037](#), [1038](#), [1039](#),
[1040](#), [1041](#), [1042](#), [1043](#), [1045](#), [1049](#), [1050](#), [1051](#),
[1053](#), [1055](#), [1056](#), [1057](#), [1058](#), [1059](#), [1060](#), [1061](#),

- 1062, 1063, 1067, 1071, 1073, 1074, 1075, 1076, 1080, 1082, 1083, 1084, 1085, 1087*, 1088, 1090, 1091, 1092, 1093, 1094, 1095, 1109, 1115, 1137*, 1145, 1146, 1147, 1150, 1156, 1157, 1158, 1163, 1165*, 1168, 1171, 1175, 1176, 1177, 1178, 1182, 1185, 1186, 1191, 1194, 1195, 1196, 1197, 1198, 1199, 1200, 1203*, 1212, 1213*, 1214*, 1217, 1218, 1219, 1221, 1242, 1243, 1254, 1258, 1264, 1269*, 1278*, 1279, 1288, 1295, 1297, 1298, 1299, 1301, 1303, 1324, 1333, 1346*, 1359, 1362, 1363, 1364, 1365, 1369, 1372, 1374, 1377, 1382, 1383, 1384, 1396, 1399*, 1404, 1457*, 1466, 1474, 1476*, 1490*, 1491*, 1516*, 1520*, 1522*, 1530, 1546, 1566, 1574, 1578, 1616*, 1619*, 1624, 1637, 1638*, 1669, 1684, 1689, 1692*, 1706, 1708, 1710, 1713, 1722*, 1723*, 1725, 1726*, 1728, 1730*, 1734*, 1735, 1736, 1739*, 1740*, 1741, 1746, 1747, 1754, 1755, 1757, 1758, 1769, 1773, 1777, 1778, 1789, 1790, 1816, 1820, 1821, 1822, 1823, 1824, 1825, 1826, 1829, 1838, 1842, 1864, 1881*, 1900*, 1901*, 1940*.
- link_node*: 730, 1633, 1636, 1637.
- list_offset*: 153*, 647*, 729*, 823, 945, 1195.
- list_ptr*: 153*, 154, 202, 220*, 224*, 498, 647*, 651*, 657*, 660*, 729*, 733*, 738*, 742*, 823, 834, 839, 840, 844, 849, 852, 885, 887, 891, 897*, 915, 923, 927, 983, 1005, 1154, 1156, 1198, 1265, 1278*, 1288, 1377, 1734*, 1735, 1741, 1746, 1747.
- list_state_record*: 230, 231*, 1513*.
- list_tag*: 570, 595, 596*, 604*, 705, 884*, 916*, 925*.
- literal*: 693, 726, 727.
- literal_mode*: 693, 727.
- ll*: 1130, 1133.
- llink*: 142, 144, 145, 147, 148, 149, 163, 167, 182, 187, 948, 995, 997, 1491*.
- ln*: 686.
- lo_mem_max*: 134*, 138, 143*, 144, 182, 183*, 185, 187, 188, 189, 190, 196, 667, 1490*, 1491*, 1502*, 1515*.
- lo_mem_stat_max*: 180, 182, 453, 1399*, 1415, 1491*, 1833, 1835.
- load_expand_font*: 705.
- load_fmt_file*: 1482*, 1518*.
- loadpoolstrings*: 51*.
- loc*: 36, 37*, 87, 322*, 324*, 325, 329, 334, 336, 340*, 341, 345, 347*, 348, 350*, 352, 353*, 365*, 370, 372, 373, 374, 376*, 377*, 378*, 379*, 380, 382, 384, 393*, 394, 416*, 509, 550*, 552*, 563*, 564, 1203*, 1204, 1518*, 1649*, 1756*, 1762.
- loc_field*: 35*, 36, 322*, 324*, 1309.
- local_base*: 238*, 242, 246, 248*, 270*.
- location*: 632, 634, 639, 640, 641, 642.
- log_file*: 54*, 56, 75, 560*, 562*, 1514*.
- log_name*: 558*, 560*, 1514*.
- log_only*: 54*, 57, 58, 62*, 75, 98, 382, 560*, 1509, 1618*, 1623*.
- log_opened*: 92, 93*, 553, 554, 560*, 561, 1443*, 1471*, 1514*, 1515*, 1618*, 1623*, 1922*.
- Logarithm...replaced by 0: 121.
- \long primitive*: 1386.
- long_call*: 228, 297, 388*, 413, 415, 418, 425, 1474.
- long_char*: 710, 712, 717.
- long_help_seen*: 1459, 1460, 1461*.
- long_outer_call*: 228, 297, 388*, 413, 415, 1474.
- long_state*: 361*, 413, 417, 418, 421, 422, 425.
- longinteger*: 65, 680, 685, 686, 694, 696, 702.
- loop**: 15, 16*.
- Loose *\hbox*...: 836.
- Loose *\vbox*...: 850.
- loose_fit*: 993, 1010, 1028, 1848.
- looseness*: 254*, 1024, 1049, 1051, 1248.
- \looseness primitive*: 256*.
- looseness_code*: 254*, 255*, 256*, 1248.
- \lower primitive*: 1249.
- \lowercase primitive*: 1464.
- lp*: 822, 1005.
- \lpcode primitive*: 1432.
- lp_code_base*: 173, 452, 1431, 1432, 1433.
- lq*: 619*, 655, 664.
- lr*: 619*, 655, 664.
- LR_box*: 230, 231*, 1323, 1384, 1743.
- LR_dir*: 1718, 1729, 1738, 1740*.
- LR_problems*: 1706, 1707, 1712, 1713, 1714, 1718, 1719, 1724, 1729, 1731, 1736, 1740*.
- LR_ptr*: 1053, 1706, 1707, 1708, 1709, 1710, 1712, 1713, 1718, 1719, 1724, 1729, 1731, 1736, 1738, 1740*.
- LR_save*: 230, 231*, 1053, 1274, 1732.
- lx*: 647*, 654, 655, 656, 657*, 663, 664, 665, 729*, 736, 737, 738*, 745, 746.
- m*: 65, 176*, 229*, 236, 314, 337, 415, 439, 466, 508, 524, 604*, 823, 844, 882, 892, 893, 1257, 1283, 1372, 1471*, 1519*, 1556, 1680, 1724, 1739*, 1754.
- M_code*: 165*.
- m_exp*: 110.
- m_log*: 110, 119, 121, 127.
- mac_param*: 225, 313, 316, 320, 369, 500, 503, 505, 959, 960, 1223, 1399*.
- MacKay, Pierre: 1701.
- macro*: 329, 336, 341, 345, 346*, 416*.
- macro_call*: 313, 388*, 406, 408, 413, 414, 415, 417.
- macro_def*: 499, 503.
- mag*: 254*, 258*, 310, 483, 612, 614, 615, 617, 645*, 670*, 690, 750*, 758, 1924*.
- \mag primitive*: 256*.

- mag_code*: [254](#)*, [255](#)*, [256](#)*, [310](#).
mag_set: [308](#), [309](#), [310](#).
magic_offset: [940](#), [941](#), [942](#).
main_body: [1513](#)*.
main_control: [286](#), [1206](#), [1207](#), [1209](#), [1218](#), [1219](#),
[1230](#), [1232](#), [1233](#), [1234](#), [1235](#), [1304](#), [1312](#), [1386](#),
[1468](#), [1513](#)*, [1518](#)*, [1525](#)*, [1528](#).
main_f: [1209](#), [1211](#)*, [1212](#), [1213](#)*, [1214](#)*, [1215](#),
[1216](#), [1218](#).
main_i: [1209](#), [1213](#)*, [1214](#)*, [1216](#), [1218](#).
main_j: [1209](#), [1216](#), [1218](#).
main_k: [1209](#), [1211](#)*, [1216](#), [1218](#), [1220](#).
main_lig_loop: [1207](#), [1211](#)*, [1214](#)*, [1215](#), [1216](#), [1218](#).
main_loop: [1207](#).
main_loop_lookahead: [1207](#), [1211](#)*, [1213](#)*, [1214](#)*,
[1215](#).
main_loop_move: [1207](#), [1211](#)*, [1213](#)*, [1217](#), [1218](#).
main_loop_move_lig: [1207](#), [1211](#)*, [1213](#)*, [1214](#)*.
main_loop_wrapup: [1207](#), [1211](#)*, [1216](#), [1218](#).
main_memory: [32](#)*, [1513](#)*.
main_p: [1209](#), [1212](#), [1214](#)*, [1218](#), [1219](#), [1220](#),
[1221](#), [1222](#).
main_s: [1209](#), [1211](#)*.
major_tail: [1089](#), [1091](#), [1094](#), [1095](#).
make_accent: [1300](#), [1301](#), [1887](#)*, [1892](#)*.
make_box: [226](#), [1249](#), [1250](#), [1251](#), [1257](#), [1262](#).
make_cstring: [792](#).
make_font_copy: [706](#), [1434](#).
make_frac: [110](#), [112](#), [127](#).
make_fraction: [110](#), [909](#), [910](#), [919](#), [1800](#).
make_full_name_string: [563](#)*.
make_left_right: [937](#), [938](#).
make_mark: [1275](#), [1279](#).
make_math_accent: [909](#), [914](#).
make_name_string: [551](#)*.
make_op: [909](#), [925](#)*.
make_ord: [909](#), [928](#).
make_over: [909](#), [910](#).
make_pdftex_banner: [1502](#)*, [1518](#)*.
make_radical: [909](#), [910](#), [913](#).
make_scripts: [930](#), [932](#).
make_src_special: [1940](#)*.
make_string: [43](#), [48](#), [279](#)*, [496](#), [543](#)*, [551](#)*, [686](#), [705](#),
[706](#), [712](#), [718](#), [726](#), [727](#), [1116](#)*, [1435](#)*, [1457](#)*, [1509](#),
[1514](#)*, [1754](#), [1878](#)*, [1881](#)*.
make_under: [909](#), [911](#).
make_vcenter: [909](#), [912](#).
margin: [1631](#).
margin_char: [173](#), [220](#)*, [224](#)*, [823](#), [825](#), [1288](#).
margin_kern_node: [173](#), [201](#), [220](#)*, [224](#)*, [498](#), [650](#)*,
[732](#)*, [823](#), [825](#), [1288](#), [1325](#).
margin_kern_node_size: [173](#), [220](#)*, [224](#)*, [823](#), [1288](#).
margin_kern_shrink: [822](#), [1005](#), [1027](#).
margin_kern_stretch: [822](#), [1005](#), [1027](#).
mark: [226](#), [287](#)*, [288](#)*, [1275](#), [1810](#).
\mark primitive: [287](#)*.
mark_class: [159](#)*, [214](#), [1156](#), [1191](#), [1279](#), [1828](#), [1831](#).
mark_class_node_size: [1821](#), [1826](#).
mark_node: [159](#)*, [166](#), [193](#), [201](#), [220](#)*, [224](#)*, [819](#),
[825](#), [906](#), [937](#), [1005](#), [1042](#), [1076](#), [1145](#), [1150](#),
[1156](#), [1177](#), [1191](#), [1279](#).
mark_ptr: [159](#)*, [214](#), [220](#)*, [224](#)*, [1156](#), [1193](#), [1279](#),
[1828](#), [1831](#).
mark_text: [329](#), [336](#), [345](#), [412](#).
mark_val: [1816](#), [1817](#), [1821](#), [1825](#), [1828](#), [1831](#).
\marks primitive: [1810](#).
marks_code: [318](#), [408](#), [411](#), [412](#), [1810](#).
mastication: [363](#)*.
match: [225](#), [311](#), [313](#), [314](#), [316](#), [417](#), [418](#).
match_chr: [314](#), [316](#), [415](#), [417](#), [420](#)*.
match_token: [311](#), [417](#), [418](#), [419](#), [420](#), [502](#).
matching: [327](#), [328](#)*, [361](#)*, [417](#).
matchstrings: [497](#).
Math formula deleted...: [1373](#).
math_ac: [1342](#), [1343](#).
math_accent: [226](#), [287](#)*, [288](#)*, [1224](#), [1342](#).
\mathaccent primitive: [287](#)*.
\mathbin primitive: [1334](#).
math_char: [857](#), [868](#), [896](#), [898](#)*, [900](#), [914](#), [917](#), [925](#)*,
[928](#), [929](#), [930](#), [1329](#), [1333](#), [1343](#).
\mathchar primitive: [287](#)*.
\mathchardef primitive: [1400](#)*.
math_char_def_code: [1400](#)*, [1401](#)*, [1402](#)*.
math_char_num: [226](#), [287](#)*, [288](#)*, [1224](#), [1329](#), [1332](#).
math_choice: [226](#), [287](#)*, [288](#)*, [1224](#), [1349](#).
\mathchoice primitive: [287](#)*.
math_choice_group: [291](#), [1350](#), [1351](#), [1352](#), [1662](#),
[1680](#).
\mathclose primitive: [1334](#).
math_code: [248](#)*, [250](#), [254](#)*, [440](#)*, [1329](#), [1332](#).
\mathcode primitive: [1408](#)*.
math_code_base: [248](#)*, [253](#), [440](#)*, [1408](#)*, [1409](#)*,
[1410](#)*, [1411](#).
math_comp: [226](#), [1224](#), [1334](#), [1335](#), [1336](#).
math_font_base: [248](#)*, [250](#), [252](#), [1408](#)*, [1409](#)*.
math_fraction: [1358](#), [1359](#).
math_given: [226](#), [439](#), [1224](#), [1329](#), [1332](#), [1400](#)*,
[1401](#)*, [1402](#)*.
math_glue: [892](#), [908](#), [942](#).
math_group: [291](#), [1314](#), [1328](#), [1331](#), [1364](#), [1662](#),
[1680](#).
\mathinner primitive: [1334](#).
math_kern: [893](#), [906](#).

- `math_left_group`: [230](#), [291](#), [1243](#), [1246](#), [1247](#), [1328](#),
[1369](#), [1662](#), [1680](#).
`math_left_right`: [1368](#), [1369](#).
`math_limit_switch`: [1336](#), [1337](#).
`math_node`: [165](#)*[166](#), [193](#), [201](#), [220](#)*[224](#)*[450](#), [650](#)*
[732](#)*[825](#), [993](#), [1005](#), [1013](#), [1042](#), [1055](#), [1057](#),
[1073](#), [1076](#), [1258](#), [1701](#), [1708](#), [1723](#)*[1729](#), [1734](#)*
[1737](#), [1739](#)*[1740](#)*[1935](#)*
`\mathop` primitive: [1334](#).
`\mathopen` primitive: [1334](#).
`\mathord` primitive: [1334](#).
`\mathpunct` primitive: [1334](#).
`math_quad`: [876](#), [879](#), [1377](#).
`math_radical`: [1340](#), [1341](#).
`\mathrel` primitive: [1334](#).
`math_shift`: [225](#), [311](#), [316](#), [320](#), [369](#), [1268](#), [1315](#),
[1316](#), [1371](#), [1375](#), [1384](#).
`math_shift_group`: [291](#), [1243](#), [1246](#), [1247](#), [1308](#)*
[1317](#)*[1318](#), [1320](#), [1323](#), [1370](#), [1371](#), [1372](#),
[1378](#), [1662](#), [1680](#).
`math_shift_token`: [311](#), [1225](#), [1243](#).
`math_spacing`: [940](#), [941](#).
`math_style`: [226](#), [1224](#), [1347](#), [1348](#), [1349](#).
`math_surround`: [265](#), [1374](#).
`\mathsurround` primitive: [266](#).
`math_surround_code`: [265](#), [266](#).
`math_text_char`: [857](#), [928](#), [929](#), [930](#), [931](#).
`math_type`: [857](#), [859](#), [863](#), [868](#), [874](#), [896](#), [898](#)*[899](#),
[910](#), [911](#), [913](#), [914](#), [917](#), [918](#), [925](#)*[927](#), [928](#), [929](#),
[930](#), [931](#), [932](#), [1254](#), [1271](#), [1329](#), [1333](#), [1343](#),
[1346](#)*[1354](#), [1359](#), [1363](#), [1364](#), [1369](#).
`math_x_height`: [876](#), [913](#), [933](#), [934](#), [935](#).
`mathex`: [877](#).
`mathsy`: [876](#).
`mathsy_end`: [876](#).
`matrixrecalculate`: [1636](#).
`matrixtransformrect`: [1631](#).
`matrixused`: [1631](#), [1636](#), [1638](#)*
`max`: [682](#), [727](#).
`max_answer`: [105](#), [1794](#), [1800](#).
`max_buf_stack`: [30](#)*[31](#)*[353](#)*[378](#)*[400](#), [1515](#)*
[1757](#), [1769](#).
`max_char_code`: [225](#), [325](#), [363](#)*[366](#), [1411](#).
`max_command`: [227](#)*[228](#), [229](#)*[237](#)*[380](#), [388](#)*[392](#),
[394](#), [406](#), [407](#), [504](#), [958](#), [1773](#).
`max_d`: [902](#), [903](#), [906](#), [936](#), [937](#), [938](#).
`max_dead_cycles`: [254](#)*[258](#)*[1189](#).
`\maxdeadcycles` primitive: [256](#)*
`max_dead_cycles_code`: [254](#)*[255](#)*[256](#)*
`max_depth`: [265](#), [1157](#), [1164](#).
`\maxdepth` primitive: [266](#).
`max_depth_code`: [265](#), [266](#).
`max_dimen`: [447](#), [486](#), [669](#), [844](#), [1187](#), [1194](#), [1323](#),
[1324](#), [1326](#), [1638](#)*[1736](#), [1737](#), [1738](#), [1791](#),
[1793](#), [1799](#), [1847](#).
`max_expand`: [705](#).
`max_font_max`: [11](#)*[32](#)*[129](#)*[240](#)*[1500](#)*
`max_group_code`: [291](#).
`max_h`: [619](#)*[620](#), [669](#), [670](#)*[902](#), [903](#), [906](#), [936](#),
[937](#), [938](#).
`max_halfword`: [14](#), [32](#)*[128](#)*[129](#)*[130](#)*[131](#)*[142](#),
[143](#)*[144](#), [149](#), [150](#), [233](#)*[311](#), [312](#)*[450](#), [783](#),
[786](#), [996](#), [1024](#), [1026](#), [1097](#)*[1159](#), [1168](#), [1173](#),
[1194](#), [1284](#), [1427](#), [1486](#)*[1487](#)*[1502](#)*[1504](#)*[1516](#)*
[1566](#), [1567](#), [1637](#), [1638](#)*
`max_hlist_stack`: [173](#), [821](#), [1005](#).
`max_in_open`: [14](#), [32](#)*[326](#)*[350](#)*[1513](#)*[1775](#),
[1777](#), [1873](#)*
`max_in_stack`: [323](#)*[343](#), [353](#)*[1515](#)*
`max_integer`: [687](#), [689](#), [1556](#).
`max_internal`: [227](#)*[439](#), [466](#), [474](#), [481](#), [487](#).
`max_len`: [693](#).
`max_nest_stack`: [231](#)*[233](#)*[234](#), [1515](#)*
`max_non_prefixed_command`: [226](#), [1389](#)*[1448](#).
`max_op_used`: [1120](#)*[1121](#)*[1123](#)*
`max_param_stack`: [330](#)*[353](#)*[416](#)*[1515](#)*
`max_print_line`: [14](#), [32](#)*[54](#)*[58](#), [72](#), [194](#)*[563](#)*[666](#)*
[750](#)*[1458](#)*[1513](#)*[1756](#)*
`max_push`: [619](#)*[620](#), [647](#)*[657](#)*[670](#)*
`max_quarterword`: [32](#)*[128](#)*[129](#)*[131](#)*[173](#), [296](#),
[973](#), [974](#), [1097](#)*[1298](#).
`max_reg_help_line`: [1812](#), [1813](#), [1814](#), [1815](#).
`max_reg_num`: [1812](#), [1813](#), [1814](#), [1815](#).
`max_save_stack`: [293](#)*[294](#), [295](#), [1515](#)*
`max_selector`: [54](#)*[264](#), [333](#), [491](#), [496](#), [560](#)*[666](#)*
[705](#), [706](#), [712](#), [727](#), [1435](#)*[1457](#)*[1616](#)*[1618](#)*
[1621](#)*[1754](#).
`max_shrink_ratio`: [823](#), [999](#), [1003](#), [1027](#).
`max_stretch_ratio`: [823](#), [999](#), [1003](#), [1027](#).
`max_strings`: [32](#)*[43](#), [129](#)*[543](#)*[551](#)*[1489](#)*[1513](#)*
[1515](#)*
`max_trie_op`: [11](#)*[1097](#)*[1121](#)*[1504](#)*
`max_v`: [619](#)*[620](#), [669](#), [670](#)*
`maxdimen`: [110](#).
`maxint`: [11](#)*
`\meaning` primitive: [494](#).
`meaning_code`: [494](#), [495](#), [497](#), [498](#).
`med_mu_skip`: [242](#).
`\medmuskip` primitive: [244](#).
`med_mu_skip_code`: [242](#), [243](#), [244](#), [942](#).
`mediabox_gIVEN`: [750](#)*[769](#).
`medium_node_size`: [159](#)*[165](#)*[170](#)*[171](#)*[174](#)*[176](#)*
[220](#)*[224](#)*[897](#)*[1087](#)*[1722](#)*[1723](#)*[1726](#)*[1730](#)*
[1734](#)*[1740](#)*[1917](#)*[1938](#)*

- mem*: [32*](#), [133](#), [134*](#), [136](#), [142](#), [144](#), [149](#), [151](#), [152](#), [153*](#), [158](#), [160](#), [168](#), [169](#), [175](#), [177](#), [180](#), [181](#), [182](#), [183*](#), [185](#), [190](#), [200](#), [204*](#), [221](#), [223](#), [224*](#), [239](#), [242](#), [297](#), [313](#), [413](#), [446](#), [515](#), [632](#), [695](#), [826](#), [856](#), [857](#), [859](#), [862](#), [863](#), [896](#), [901](#), [918](#), [929](#), [945](#), [946](#), [948](#), [973](#), [992](#), [994](#), [995](#), [998](#), [999](#), [1008](#), [1019](#), [1020](#), [1023](#), [1024](#), [1026](#), [1036](#), [1037](#), [1066](#), [1102*](#), [1327](#), [1329](#), [1338](#), [1341](#), [1343](#), [1359](#), [1364](#), [1425](#), [1426](#), [1487*](#), [1490*](#), [1491*](#), [1513*](#), [1520*](#), [1675](#), [1728](#), [1734*](#), [1755](#), [1757](#), [1789](#), [1816](#), [1821](#), [1843](#), [1911*](#)
- mem_bot*: [14](#), [32*](#), [129*](#), [134*](#), [143*](#), [144](#), [180](#), [182](#), [287*](#), [437](#), [441](#), [453](#), [1399*](#), [1404](#), [1405](#), [1415](#), [1486*](#), [1487*](#), [1490*](#), [1491*](#), [1513*](#), [1833](#), [1834](#), [1835](#).
- mem_end*: [134*](#), [136](#), [138](#), [182](#), [183*](#), [185](#), [186](#), [189](#), [190](#), [192*](#), [194*](#), [200](#), [315](#), [674](#), [1490*](#), [1491*](#), [1515*](#)
- mem_max*: [12*](#), [14](#), [32*](#), [128*](#), [129*](#), [134*](#), [138](#), [142](#), [143*](#), [184](#), [1487*](#), [1513*](#)
- mem_min*: [12*](#), [32*](#), [129*](#), [134*](#), [138](#), [143*](#), [184](#), [185](#), [187](#), [188](#), [189](#), [190](#), [192*](#), [196](#), [200](#), [674](#), [1427](#), [1487*](#), [1491*](#), [1513*](#), [1515*](#)
- mem_top*: [14](#), [32*](#), [129*](#), [134*](#), [180](#), [182](#), [1427](#), [1486*](#), [1487*](#), [1491*](#), [1513*](#)
- Memory usage...: [667](#).
- memory_word*: [128*](#), [132](#), [134*](#), [200](#), [230](#), [236](#), [239](#), [271*](#), [290](#), [293*](#), [297](#), [574*](#), [710](#), [976](#), [1484*](#), [1487*](#), [1513*](#), [1817](#).
- message*: [226](#), [1454](#), [1455](#), [1456](#).
- `\message` primitive: [1455](#).
- message_printing*: [20*](#), [23*](#), [59*](#), [1457*](#)
- METAFONT: [616](#).
- microseconds*: [680](#), [1518*](#), [1556](#), [1585](#), [1587](#).
- mid*: [572](#).
- mid_line*: [87](#), [325](#), [350*](#), [365*](#), [366](#), [369](#), [374](#), [375](#), [376*](#)
- middle*: [1698](#).
- `\middle` primitive: [1698](#).
- middle_noad*: [230](#), [863](#), [1369](#), [1370](#), [1698](#), [1699](#).
- min*: [682](#).
- min_bp_val*: [691](#), [692](#), [693](#), [792](#).
- min_font_val*: [691](#).
- min_halfword*: [32*](#), [128*](#), [129*](#), [130*](#), [131*](#), [133](#), [248*](#), [1204](#), [1502*](#), [1504*](#), [1535*](#), [1724](#), [1729](#), [1739*](#), [1740*](#)
- min_internal*: [226](#), [439](#), [466](#), [474](#), [481](#), [487](#).
- min_quarterword*: [11*](#), [128*](#), [129*](#), [130*](#), [131*](#), [152](#), [154](#), [158](#), [203](#), [239](#), [296](#), [574*](#), [576*](#), [580*](#), [582](#), [583](#), [592](#), [603*](#), [823](#), [844](#), [861](#), [873](#), [883](#), [889](#), [890](#), [972](#), [977](#), [979](#), [984](#), [1135*](#), [1171](#), [1189](#), [1502*](#), [1503*](#), [1504*](#)
- min_trie_op*: [11*](#), [1097*](#), [1100*](#), [1101*](#), [1120*](#), [1121*](#), [1122*](#), [1123*](#), [1135*](#), [1140*](#), [1141*](#), [1142*](#)
- minimal_demerits*: [1009](#), [1010](#), [1012](#), [1021](#), [1031](#), [1843](#).
- minimum_demerits*: [1009](#), [1010](#), [1011](#), [1012](#), [1030](#), [1031](#).
- minor_tail*: [1089](#), [1092](#), [1093](#).
- minus: [488](#).
- Misplaced &: [1306](#).
- Misplaced \cr: [1306](#).
- Misplaced \noalign: [1307](#).
- Misplaced \omit: [1307](#).
- Misplaced \span: [1306](#).
- Missing) inserted: [1785](#).
- Missing = inserted: [529](#), [1770](#).
- Missing # inserted...: [959](#).
- Missing \$ inserted: [1225](#), [1243](#).
- Missing \cr inserted: [1310](#).
- Missing \endcsname...: [399](#).
- Missing \endgroup inserted: [1243](#).
- Missing \right. inserted: [1243](#).
- Missing { inserted: [429](#), [501](#), [1305](#).
- Missing } inserted: [1243](#), [1305](#).
- Missing 'to' inserted: [1260](#).
- Missing 'to'...: [1403](#).
- Missing \$\$ inserted: [1385](#).
- Missing character: [608*](#), [1885*](#), [1890*](#)
- Missing control...: [1393*](#)
- Missing delimiter...: [1339](#).
- Missing font identifier: [604*](#)
- Missing number...: [441](#), [472](#).
- mkern*: [226](#), [1224](#), [1235](#), [1236](#), [1237](#).
- `\mkern` primitive: [1236](#).
- ml_field*: [230](#), [231*](#), [236](#).
- mlist*: [902](#), [936](#).
- mlist_penalties*: [895](#), [896](#), [902](#), [930](#), [1372](#), [1374](#), [1377](#).
- mlist_to_hlist*: [869](#), [895](#), [896](#), [901](#), [902](#), [910](#), [930](#), [936](#), [1372](#), [1374](#), [1377](#).
- mltex_enabled_p*: [256*](#), [560*](#), [648*](#), [731*](#), [1518*](#), [1883*](#), [1884*](#), [1885*](#), [1886*](#), [1895*](#)
- mltex_p*: [256*](#), [1400*](#), [1882*](#), [1883*](#), [1894*](#), [1895*](#)
- mm: [484](#).
- mmode*: [229*](#), [230](#), [231*](#), [236](#), [527*](#), [894](#), [951](#), [952](#), [976](#), [983](#), [988](#), [1207](#), [1223](#), [1224](#), [1226](#), [1234](#), [1235](#), [1251](#), [1258](#), [1270](#), [1275](#), [1287](#), [1288](#), [1290](#), [1294](#), [1298](#), [1308*](#), [1314](#), [1318](#), [1323](#), [1328](#), [1332](#), [1336](#), [1340](#), [1342](#), [1345*](#), [1349](#), [1353](#), [1358](#), [1368](#), [1371](#), [1372](#), [1680](#), [1743](#).
- moddate_given*: [807](#).
- mode*: [229*](#), [230](#), [231*](#), [233*](#), [234](#), [321](#), [379*](#), [444](#), [448](#), [450](#), [527*](#), [727](#), [894](#), [951](#), [952](#), [961](#), [962](#), [963](#), [972](#), [975](#), [980](#), [983](#), [984](#), [985](#), [988](#), [1202](#), [1206](#), [1207](#), [1211*](#), [1212](#), [1227*](#), [1229](#), [1234](#), [1254](#), [1256](#), [1258](#), [1261](#), [1263*](#), [1264](#), [1269*](#), [1271](#), [1272](#), [1273](#), [1274](#), [1277](#), [1278*](#), [1281](#), [1283](#), [1288](#), [1295](#), [1297](#), [1298](#), [1308*](#), [1311*](#), [1314](#), [1316](#), [1323](#), [1345*](#)

- 1346*, 1372, 1374, 1378, 1421, 1561, 1562, 1616*, 1618*, 1619*, 1626, 1743.
- mode_field*: [230](#), [231*](#), [236](#), [448](#), [976](#), [983](#), [1422](#), [1680](#), [1682](#).
- mode_line*: [230](#), [231*](#), [233*](#), [234](#), [326*](#), [980](#), [991](#), [1202](#).
- month*: [254*](#), [259*](#), [645*](#), [792](#), [1509](#).
- \month* primitive: [256*](#).
- month_code*: [254*](#), [255*](#), [256*](#).
- months*: [560*](#), [562*](#).
- more_name*: [538](#), [542*](#), [551*](#), [552*](#), [557](#), [1868*](#), [1881*](#).
- \moveleft* primitive: [1249](#).
- move_past*: [647*](#), [650*](#), [653](#), [657*](#), [659](#), [662](#), [729*](#), [732*](#), [735](#), [738*](#), [741](#), [744](#).
- \moveright* primitive: [1249](#).
- movement*: [634](#), [636](#), [643](#).
- movement_node_size*: [632](#), [634](#), [642](#).
- msg*: [712](#).
- mskip*: [226](#), [1224](#), [1235](#), [1236](#), [1237](#).
- \mskip* primitive: [1236](#).
- mskip_code*: [1236](#), [1238](#).
- mstate*: [634](#), [638](#), [639](#).
- mtype**: [4*](#).
- mu*: [473](#), [474](#), [475](#), [479](#), [481](#), [487](#), [488](#).
- mu*: [482](#).
- mu_error*: [434](#), [455](#), [475](#), [481](#), [487](#), [1781](#).
- \muexpr* primitive: [1779](#).
- mu_glue*: [167](#), [173](#), [209](#), [450](#), [893](#), [908](#), [1236](#), [1238](#), [1239](#).
- mu_mult*: [892](#), [893](#).
- mu_skip*: [242](#), [453](#).
- \muskip* primitive: [437](#).
- mu_skip_base*: [242](#), [245](#), [247](#), [1402*](#), [1415](#).
- \muskipdef* primitive: [1400*](#).
- mu_skip_def_code*: [1400*](#), [1401*](#), [1402*](#).
- \mutoglu* primitive: [1806](#).
- mu_to_glue_code*: [1806](#), [1807](#), [1808](#).
- mu_val*: [436](#), [437](#), [439](#), [450](#), [453](#), [455](#), [456](#), [475](#), [477](#), [481](#), [487](#), [491](#), [1238](#), [1402*](#), [1406](#), [1414](#), [1415](#), [1779](#), [1780](#), [1781](#), [1788](#), [1816](#), [1821](#), [1824](#).
- mu_val_limit*: [1816](#), [1822](#), [1839](#).
- \mubyte* primitive: [1397*](#).
- mubyte_cswrite*: [20*](#), [23*](#), [284*](#), [376*](#), [379*](#), [1399*](#), [1901*](#), [1903*](#), [1904*](#).
- mubyte_in*: [254*](#), [376*](#), [377*](#), [378*](#), [1900*](#), [1902*](#).
- \mubytein* primitive: [256*](#).
- mubyte_in_code*: [254*](#), [255*](#), [256*](#).
- mubyte_incs*: [363*](#), [376*](#), [378*](#).
- mubyte_keep*: [20*](#), [23*](#), [340*](#), [376*](#), [377*](#), [378*](#), [1900*](#).
- mubyte_log*: [20*](#), [59*](#), [254*](#), [1616*](#), [1618*](#), [1902*](#).
- \mbytelog* primitive: [256*](#).
- mubyte_log_code*: [254*](#), [255*](#), [256*](#).
- mubyte_out*: [20*](#), [254*](#), [1531*](#), [1535*](#), [1616*](#), [1618*](#).
- \mubyteout* primitive: [256*](#).
- mubyte_out_code*: [254*](#), [255*](#), [256*](#).
- mubyte_prefix*: [20*](#), [1399*](#), [1901*](#).
- mubyte_read*: [20*](#), [23*](#), [1399*](#), [1900*](#), [1901*](#), [1903*](#), [1904*](#).
- mubyte_relax*: [20*](#), [1399*](#).
- mubyte_skeep*: [20*](#), [340*](#), [376*](#), [378*](#).
- mubyte_skip*: [20*](#), [376*](#), [378*](#), [1900*](#).
- mubyte_slog*: [20*](#), [1616*](#), [1618*](#).
- mubyte_sout*: [20*](#), [1616*](#), [1618*](#).
- mubyte_sstart*: [20*](#), [340*](#).
- mubyte_start*: [20*](#), [23*](#), [340*](#), [1900*](#).
- mubyte_stoken*: [20*](#), [1399*](#), [1901*](#).
- mubyte_tablein*: [20*](#), [1399*](#).
- mubyte_tableout*: [20*](#), [1399*](#).
- mubyte_token*: [20*](#), [365*](#), [376*](#), [378*](#), [1900*](#), [1902*](#).
- mubyte_update*: [1399*](#), [1901*](#).
- mubyte_write*: [20*](#), [23*](#), [59*](#), [1399*](#), [1900*](#), [1903*](#), [1904*](#).
- mubyte_zero*: [1522*](#), [1531*](#), [1535*](#), [1603*](#), [1604*](#), [1616*](#), [1618*](#).
- mult_and_add*: [105](#).
- mult_integers*: [105](#), [1418](#), [1796](#).
- multiply*: [227*](#), [287*](#), [288*](#), [1388](#), [1413](#), [1414](#), [1418](#).
- \multiply* primitive: [287*](#).
- Must increase the x: [1482*](#).
- must_end_string*: [693](#).
- must_insert_space*: [693](#).
- must_quote*: [543*](#), [544*](#).
- my_synchronized_node_size*: [1915*](#).
- n*: [65](#), [66](#), [67](#), [69](#), [91](#), [94*](#), [105](#), [106](#), [107](#), [112](#), [114](#), [170*](#), [172](#), [192*](#), [200](#), [243](#), [255*](#), [265](#), [270*](#), [314](#), [320](#), [321](#), [337](#), [415](#), [508](#), [524](#), [544*](#), [545*](#), [549*](#), [605](#), [674](#), [689](#), [882](#), [892](#), [893](#), [967](#), [976](#), [1083](#), [1111*](#), [1121*](#), [1154](#), [1169](#), [1170](#), [1171](#), [1189](#), [1257](#), [1297](#), [1316](#), [1389*](#), [1453*](#), [1471*](#), [1519*](#), [1724](#), [1739*](#), [1783](#), [1798](#), [1800](#), [1820](#), [1823](#).
- name*: [322*](#), [324*](#), [325](#), [326*](#), [329](#), [333](#), [335](#), [336](#), [345](#), [350*](#), [351](#), [353*](#), [359](#), [382](#), [384](#), [416*](#), [509](#), [563*](#), [1756*](#).
- name_field*: [84*](#), [85](#), [322*](#), [324*](#), [1775](#), [1776](#).
- name_in_progress*: [404](#), [551*](#), [552*](#), [553](#), [554](#), [1436](#).
- name_length*: [26*](#), [545*](#), [549*](#), [551*](#).
- name_of_file*: [26*](#), [545*](#), [549*](#), [550*](#), [551*](#), [556*](#), [560*](#), [563*](#), [1453*](#), [1487*](#), [1623*](#).
- name_too_long*: [586*](#), [587*](#), [589*](#).
- name_tree_kids_max*: [695](#), [805](#).
- named*: [1553](#).
- names_head*: [804](#), [805](#), [1514*](#).
- names_tail*: [804](#), [1514*](#).
- names_tree*: [804](#), [806](#), [1514*](#).
- natural*: [816](#), [881](#), [891](#), [896](#), [903](#), [911](#), [913](#), [914](#), [924](#), [930](#), [932](#), [935](#), [972](#), [975](#), [982](#), [1154](#), [1198](#), [1278*](#), [1303](#), [1372](#), [1377](#), [1382](#), [1747](#).
- nc*: [484](#).

- nd*: 484.
nd: 566, 567, 586*, 591, 592, 595.
ne: 566, 567, 586*, 591, 592, 595.
neg: 705.
neg_trie_op_size: 11*, 1120* 1121*
negate: 16*, 65, 103, 105, 106, 107, 112, 115, 123,
 456, 457, 466, 474, 487, 686, 689, 951, 1586,
 1770, 1781, 1794, 1798, 1800.
negative: 106, 112, 114, 115, 439, 456, 466, 467,
474, 487, 1781, 1794, 1798, 1800.
nest: 230, 231*, 234, 235, 236, 237* 439, 448, 951,
 976, 983, 1172, 1422, 1513* 1680, 1682.
nest_ptr: 231*, 233* 234, 235, 236, 448, 951, 976,
 983, 1172, 1194, 1200, 1269* 1278* 1323,
 1378, 1422, 1680.
nest_size: 32* 231* 234, 236, 439, 1422, 1513*
1515* 1680.
nesting_level: 730, 1633, 1636.
new_annot_whatsit: 1557, 1559, 1561, 1568, 1569.
new_character: 609* 931, 1092, 1295, 1301, 1302.
new_choice: 865, 1350.
new_delta_from_break_width: 1020.
new_delta_to_break_width: 1019.
new_disc: 163, 1212, 1295.
new_edge: 1720, 1723* 1739*
new_font: 706, 1434, 1435*
new_font_type: 703, 705, 720, 726, 1502* 1518*
new_glue: 171* 172, 891, 942, 962, 969, 971, 985,
 1219, 1221, 1232, 1238, 1349.
new_graf: 1268, 1269*
new_hlist: 901, 903, 919, 924, 925* 926, 930,
 932, 938, 943.
new_hyph_exceptions: 1111* 1430*
new_index: 1816, 1817, 1820.
new_interaction: 1442, 1443* 1696, 1697.
new_kern: 174* 705, 881, 891, 911, 914, 915, 923,
 927, 929, 931, 935, 1087* 1218, 1239, 1290,
 1291, 1303, 1382, 1722* 1741, 1747.
new_letterspaced_font: 706, 1434.
new_lig_item: 162* 1088, 1218.
new_ligature: 162* 1087* 1212.
new_line: 325, 353* 365* 366, 367, 369, 509, 563*
new_line_char: 59*, 254* 262, 1514* 1516* 1755.
 \newlinechar primitive: 256*
new_line_char_code: 254* 255* 256*
new_margin_kern: 823, 1057, 1063.
new_math: 165* 1374, 1704, 1708, 1710, 1713,
 1724, 1735, 1747.
new_mubyte_node: 1900* 1901*
new_noad: 862, 896, 918, 929, 1254, 1271, 1328,
 1333, 1336, 1346* 1355, 1369.
new_null_box: 154, 882, 885, 889, 896, 923, 926,
 955, 969, 985, 1195, 1232, 1269* 1271, 1741.
new_param_glue: 170* 172, 855, 954, 992, 1062,
 1063, 1219, 1221, 1269* 1381, 1383, 1384, 1741.
new_patterns: 1137* 1430*
new_penalty: 176* 943, 992, 1067, 1232, 1281,
 1381, 1383, 1384.
new_randoms: 110, 124, 125.
new_rule: 157, 489, 842, 880, 1553.
new_save_level: 296, 817, 950, 961, 967, 1202,
 1241, 1277, 1295, 1297, 1314.
new_skip_param: 172, 855, 1146, 1178, 1747.
new_snap_node: 1574, 1575.
new_spec: 169, 172, 456, 488, 705, 1002, 1153,
 1181, 1220, 1221, 1417, 1418, 1781, 1791,
 1792, 1854.
new_string: 54* 57, 58, 491, 496, 645* 686, 705,
 706, 712, 727, 1435* 1457* 1509, 1616* 1618*
1689, 1754, 1881*
new_style: 864, 1349.
new_trie_op: 1120* 1121* 1122* 1142*
new_vf_packet: 706, 716.
new_whatsit: 1530, 1531* 1535* 1539, 1540, 1541,
 1542, 1543, 1547, 1550, 1555, 1557, 1562, 1566,
 1570, 1573, 1576, 1577, 1595, 1596, 1597, 1598,
 1599, 1625, 1626, 1940*
new_write_whatsit: 1531* 1532, 1533, 1534.
newcolorstack: 497.
next: 274* 278, 279* 1487* 1513*
next_break: 1053, 1054.
next_char: 571, 823, 917, 929, 1086, 1216.
next_char_p: 999.
next_p: 647* 650* 654, 657* 658, 659, 661, 663, 729*
732* 736, 738* 740, 741, 743, 745, 1724, 1726*
next_pos: 1638*
next_random: 124, 126, 127.
nh: 566, 567, 586* 591, 592, 595.
ni: 566, 567, 586* 591, 592, 595, 705.
nil: 16*
nine_bits: 574* 575* 1502* 1518*
nk: 566, 567, 586* 591, 592, 600* 705.
nl: 59* 566, 567, 571, 586* 591, 592, 595, 600*
603* 1754, 1755.
nn: 333, 334.
 No pages of output: 670* 794.
no_align: 226, 287* 288* 961, 1304.
 \noalign primitive: 287*
no_align_error: 1304, 1307.
no_align_group: 291, 944, 961, 1311* 1662, 1680.
no_boundary: 226, 287* 288* 1207, 1215, 1223,
 1268.
 \noboundary primitive: 287*

- no_break_yet*: [1005](#), [1012](#), [1013](#).
no_convert: [20*](#), [23*](#), [59*](#), [284*](#).
no_expand: [228](#), [287*](#), [288*](#), [388*](#), [391](#).
`\noexpand` primitive: [287*](#).
no_expand_flag: [380](#), [504](#), [532](#).
`\noindent` primitive: [1266](#).
no_lig_code: [173](#), [452](#), [1431](#), [1432](#), [1433](#).
`\pdfnoligatures` primitive: [1432](#).
no_limits: [858](#), [1334](#), [1335](#).
`\nolimits` primitive: [1334](#).
no_new_control_sequence: [274*](#), [276*](#), [278](#), [281](#), [286](#),
[387](#), [400](#), [1517](#), [1649*](#), [1769](#).
no_print: [54*](#), [57](#), [58](#), [62*](#), [75](#), [98](#), [1471*](#), [1472*](#).
no_shrink_error_yet: [1001](#), [1002](#), [1003](#).
no_tag: [570](#), [595](#).
no_zip: [680](#), [681](#), [685](#).
noad_size: [857](#), [862](#), [874](#), [929](#), [937](#), [1364](#), [1365](#).
`\noconvert` primitive: [1397*](#).
node_list_display: [198](#), [202](#), [206](#), [208](#), [213](#), [215](#).
node_r_stays_active: [1006](#), [1027](#), [1030](#).
node_size: [142](#), [144](#), [145](#), [146](#), [148](#), [182](#), [187](#),
[1490*](#), [1491*](#).
nom: [586*](#), [587*](#), [589*](#), [603*](#).
non_address: [575*](#), [603*](#), [1086](#), [1093](#), [1211*](#), [1518*](#).
non_char: [574*](#), [575*](#), [603*](#), [705](#), [1074](#), [1075](#), [1078](#),
[1085](#), [1086](#), [1087*](#), [1088](#), [1092](#), [1093](#), [1094](#), [1209](#),
[1211*](#), [1212](#), [1215](#), [1216](#), [1218](#), [1295](#), [1502*](#), [1518*](#).
non_discardable: [166](#), [1005](#), [1055](#).
non_existent_path: [705](#), [706](#).
non_math: [1224](#), [1241](#), [1322](#).
non_script: [226](#), [287*](#), [288*](#), [1224](#), [1349](#).
`\nonscript` primitive: [287*](#), [908](#).
none_seen: [638](#), [639](#).
NONEXISTENT: [284*](#).
Nonletter: [1139](#).
nonnegative_integer: [69](#), [101](#), [107](#), [689](#).
nonstop_mode: [73*](#), [86](#), [382](#), [385*](#), [510*](#), [1440](#), [1441](#).
`\nonstopmode` primitive: [1440](#).
nop: [610](#), [612](#), [613](#), [615](#), [617](#), [717](#), [719](#).
noreturn: [81*](#).
norm_min: [1269*](#), [1378](#), [1625](#), [1626](#).
norm_rand: [110](#), [127](#), [498](#).
normal: [153*](#), [154](#), [167](#), [168](#), [171*](#), [173](#), [174*](#), [182](#),
[195](#), [204*](#), [207](#), [209](#), [284*](#), [327](#), [353*](#), [358](#), [393*](#), [394](#),
[465](#), [474](#), [497](#), [499](#), [506](#), [508](#), [511](#), [515](#), [516](#), [527*](#),
[533](#), [647*](#), [653](#), [657*](#), [662](#), [729*](#), [735](#), [738*](#), [744](#), [824](#),
[825](#), [833](#), [834](#), [835](#), [836](#), [840](#), [841](#), [842](#), [843](#), [848](#),
[849](#), [850](#), [852](#), [853](#), [854](#), [858](#), [862](#), [872](#), [892](#),
[908](#), [925*](#), [953](#), [977](#), [986](#), [987](#), [1001](#), [1002](#), [1005](#),
[1017](#), [1018](#), [1042](#), [1046](#), [1047](#), [1073](#), [1074](#), [1076](#),
[1153](#), [1165*](#), [1181](#), [1186](#), [1223](#), [1334](#), [1341](#), [1343](#),
[1359](#), [1379](#), [1397*](#), [1398*](#), [1399*](#), [1417](#), [1471*](#), [1638*](#),
[1639](#), [1684](#), [1724](#), [1767](#), [1792](#), [1795](#), [1844](#).
`\pdfnormaldeviate` primitive: [494](#).
normal_deviate_code: [494](#), [495](#), [497](#), [498](#).
normal_paragraph: [950](#), [961](#), [963](#), [1202](#), [1248](#),
[1261](#), [1272](#), [1274](#), [1277](#), [1345*](#).
normalize_glue: [1792](#), [1795](#).
normalize_selector: [78](#), [92](#), [93*](#), [94*](#), [95*](#), [686](#), [1039](#).
Not a letter: [1114](#).
not_found: [15](#), [45](#), [46](#), [474](#), [481](#), [586*](#), [596*](#), [634](#),
[638](#), [639](#), [686](#), [1005](#), [1072](#), [1107*](#), [1108*](#), [1111*](#),
[1118*](#), [1130](#), [1132](#), [1147](#), [1149](#), [1150](#), [1316](#), [1324](#),
[1613](#), [1734*](#), [1820](#), [1847](#).
not_found1: [15](#), [1111*](#), [1820](#).
not_found2: [15](#), [1820](#).
not_found3: [15](#), [1820](#).
not_found4: [15](#), [1820](#).
notexpanded:: [277*](#).
np: [566](#), [567](#), [586*](#), [591](#), [592](#), [602*](#), [603*](#).
nucleus: [857](#), [858](#), [859](#), [862](#), [863](#), [866](#), [872](#), [874](#),
[896](#), [901](#), [910](#), [911](#), [912](#), [913](#), [914](#), [917](#), [918](#), [925*](#),
[926](#), [928](#), [929](#), [930](#), [931](#), [1254](#), [1271](#), [1328](#), [1329](#),
[1333](#), [1336](#), [1341](#), [1343](#), [1346*](#), [1364](#), [1369](#).
null: [23*](#), [133](#), [134*](#), [136](#), [138](#), [140](#), [141](#), [143*](#), [144](#),
[153*](#), [154](#), [162*](#), [163](#), [167](#), [168](#), [169](#), [170*](#), [171*](#), [172](#),
[182](#), [186](#), [187](#), [193](#), [194*](#), [200](#), [218](#), [219](#), [220*](#), [222](#),
[228](#), [230](#), [233*](#), [234](#), [236](#), [237*](#), [240*](#), [241](#), [250](#), [251](#),
[284*](#), [297](#), [314](#), [317](#), [321](#), [328*](#), [329](#), [334](#), [336](#), [347*](#),
[353*](#), [376*](#), [379*](#), [380](#), [384](#), [397](#), [400](#), [408](#), [409](#), [412](#),
[416*](#), [417](#), [418](#), [423](#), [426*](#), [433](#), [436](#), [441](#), [446](#), [449](#),
[453](#), [478](#), [490](#), [492](#), [497](#), [498](#), [499](#), [504](#), [508](#), [515](#),
[516](#), [523](#), [531](#), [534](#), [575*](#), [603*](#), [605](#), [609*](#), [633](#), [638](#),
[642](#), [647*](#), [651*](#), [657*](#), [660*](#), [673*](#), [674](#), [686](#), [693](#), [700](#),
[705](#), [727](#), [729*](#), [733*](#), [738*](#), [739](#), [742*](#), [753](#), [754](#), [756](#),
[763](#), [764](#), [766](#), [767](#), [769](#), [771](#), [772](#), [773](#), [775](#), [778](#),
[779](#), [781](#), [782](#), [783](#), [784](#), [786](#), [792](#), [795](#), [797](#), [803](#),
[804](#), [806](#), [807](#), [814](#), [815](#), [820](#), [822](#), [823](#), [825](#), [830](#),
[831](#), [834](#), [840](#), [842](#), [844](#), [849](#), [852](#), [857](#), [861](#), [865](#),
[868](#), [891](#), [894](#), [895](#), [896](#), [897*](#), [902](#), [907](#), [908](#), [928](#),
[930](#), [931](#), [932](#), [936](#), [937](#), [942](#), [943](#), [947](#), [950](#), [952](#),
[953](#), [959](#), [960](#), [965](#), [966](#), [967](#), [968](#), [970](#), [972](#), [973](#),
[975](#), [977](#), [980](#), [981](#), [982](#), [983](#), [988](#), [997](#), [1003](#),
[1005](#), [1013](#), [1016](#), [1022](#), [1023](#), [1024](#), [1026](#), [1027](#),
[1028](#), [1032](#), [1033](#), [1034](#), [1035](#), [1039](#), [1040](#), [1041](#),
[1043](#), [1045](#), [1048](#), [1053](#), [1054](#), [1055](#), [1057](#), [1058](#),
[1059](#), [1060](#), [1061](#), [1063](#), [1065](#), [1066](#), [1067](#), [1071](#),
[1073](#), [1075](#), [1080](#), [1083](#), [1084](#), [1085](#), [1087*](#), [1088](#),
[1090](#), [1091](#), [1092](#), [1093](#), [1094](#), [1095](#), [1105*](#), [1109](#),
[1112](#), [1145](#), [1146](#), [1147](#), [1149](#), [1150](#), [1154](#), [1155](#),
[1156](#), [1158](#), [1168](#), [1169](#), [1170](#), [1171](#), [1175](#), [1176](#),
[1177](#), [1186](#), [1187](#), [1188](#), [1189](#), [1191](#), [1192](#), [1193](#),
[1194](#), [1195](#), [1197](#), [1198](#), [1199](#), [1200](#), [1203*](#), [1204](#),

- 1205, 1207, 1209, 1211*, 1212, 1213*, 1214*, 1215, 1217, 1218, 1220, 1221, 1248, 1252, 1253, 1254, 1257, 1258, 1261, 1265, 1269*, 1274, 1288, 1295, 1299, 1301, 1302, 1309, 1314, 1317*, 1323, 1324, 1327, 1345*, 1352, 1354, 1359, 1362, 1363, 1364, 1372, 1374, 1377, 1380, 1383, 1384, 1399*, 1404, 1405, 1425, 1426, 1461*, 1466, 1475*, 1487*, 1490*, 1491*, 1516*, 1518*, 1520*, 1534, 1535*, 1537, 1545, 1546, 1549, 1552, 1553, 1556, 1557, 1566, 1574, 1578, 1604*, 1605, 1606, 1616*, 1617, 1624, 1630, 1631, 1637, 1638*, 1669, 1675, 1684, 1692*, 1707, 1708, 1709, 1710, 1713, 1722*, 1724, 1726*, 1731, 1732, 1734*, 1735, 1736, 1739*, 1746, 1747, 1752, 1757, 1758, 1759, 1769, 1783, 1784, 1785, 1810, 1816, 1817, 1818, 1819, 1820, 1821, 1822, 1824, 1825, 1826, 1827, 1828, 1829, 1830, 1831, 1832, 1833, 1837, 1838, 1839, 1842, 1850, 1853, 1861, 1864, 1867, 1881*, 1900*, 1901*, 1940*.
- null delimiter: 258*, 1243.
- null_character: 581, 582, 898*, 899, 1886*.
- null_code: 22, 250, 1618*.
- null_cs: 240*, 284*, 285, 376*, 400, 673*, 693, 705, 706, 712, 1435*, 1769.
- null_delimiter: 860, 861, 1359.
- null_delimiter_space: 265, 882.
- \nulldelimiterspace primitive: 266.
- null_delimiter_space_code: 265, 266.
- null_flag: 156*, 157, 489, 827, 955, 969, 977, 1553.
- null_font: 192*, 250, 497, 579, 586*, 604*, 645*, 673*, 674, 693, 697, 705, 706, 712, 720, 823, 839, 882, 883, 898*, 1040, 1435*, 1501*, 1502*, 1518*, 1520*, 1588, 1590, 1594.
- \nullfont primitive: 579.
- null_list: 14, 180, 406, 956.
- num: 476, 484, 612, 614, 617.
- num_error: 1791, 1794, 1798, 1800.
- \numexpr primitive: 1779.
- num_style: 878, 920.
- Number too big: 471.
- \number primitive: 494.
- number_code: 494, 495, 496, 497, 498.
- numerator: 859, 866, 873, 874, 920, 1359, 1363.
- num1: 876, 920.
- num2: 876, 920.
- num3: 876, 920.
- nw: 566, 567, 586*, 591, 592, 595, 705, 706.
- nx_plus_y: 105, 481, 892, 1418, 1796.
- o: 286, 634, 823, 844, 967, 976, 1783.
- obj_annot_ptr: 695, 781, 782, 783, 1559, 1561, 1631, 1636, 1637.
- obj_aux: 695, 698, 752, 799, 805.
- obj_bead_attr: 695, 1601, 1638*.
- obj_bead_data: 695, 786, 1638*.
- obj_bead_next: 695, 1601, 1638*.
- obj_bead_page: 695, 1601, 1638*.
- obj_bead_prev: 695, 1601, 1638*.
- obj_bead_ptr: 695, 1638*.
- obj_bead_rect: 695, 786, 1601.
- obj_data_ptr: 695, 1545, 1549, 1553, 1624.
- obj_dest_ptr: 695, 784, 795, 797, 1556, 1566, 1638*.
- obj_entry: 694, 695, 696, 698, 1513*.
- obj_info: 498, 693, 695, 698, 767, 794, 795, 797, 799, 801, 802, 803, 804, 805, 1601, 1638*.
- obj_link: 693, 695, 698, 789, 790, 796, 798, 799, 800, 801, 802, 803, 804, 805, 812, 813, 814, 1546.
- obj_obj_data: 695, 772, 1545, 1604*.
- obj_obj_is_file: 695, 772, 1545, 1604*.
- obj_obj_is_stream: 695, 772, 1545, 1604*.
- obj_obj_stream_attr: 695, 772, 1545, 1604*.
- obj_offset: 695, 698, 813, 814, 815.
- obj_os_idx: 695, 698, 814.
- obj_outline_action_objnum: 695, 789, 1564.
- obj_outline_attr: 695, 789, 1564.
- obj_outline_count: 695, 788, 789, 1564, 1638*.
- obj_outline_first: 695, 789, 1564, 1638*.
- obj_outline_last: 695, 789, 1564, 1638*.
- obj_outline_next: 695, 788, 789, 1564, 1638*.
- obj_outline_parent: 695, 788, 789, 1564, 1638*.
- obj_outline_prev: 695, 789, 1563, 1564.
- obj_outline_ptr: 695, 1564.
- obj_outline_title: 695, 789, 1564.
- obj_ptr: 693, 696, 697, 698, 752, 770, 786, 788, 790, 804, 806, 813, 814, 1505, 1506, 1514*, 1545, 1549, 1553, 1556, 1559, 1564, 1580, 1601, 1637.
- obj_tab: 694, 695, 696, 697, 698, 804, 1505, 1506, 1513*.
- obj_tab_size: 694, 696, 697, 698, 1505, 1506, 1513*, 1514*.
- obj_thread_first: 695, 1601, 1638*.
- obj_type_dest: 695, 698, 796, 1556, 1566, 1631, 1638*.
- obj_type_font: 693, 695, 801.
- obj_type_obj: 695, 1505, 1506, 1545, 1547.
- obj_type_others: 695, 698, 752, 786, 788, 790, 804, 806, 807, 814, 1564, 1580, 1601, 1637.
- obj_type_outline: 695, 789, 1564.
- obj_type_page: 498, 695, 698, 752, 795, 797, 799, 800, 802, 1601, 1631.
- obj_type_pages: 695, 770, 800, 802, 803.
- obj_type_struct_dest: 695, 798, 1556, 1566, 1631, 1638*.
- obj_type_thread: 695, 790, 1631, 1638*.
- obj_type_xform: 497, 695, 1505, 1506, 1549, 1550.
- obj_type_ximage: 497, 695, 1505, 1506, 1553, 1555.

- obj_xform_attr*: [695](#), [756](#), [1549](#).
obj_xform_box: [695](#), [775](#), [1549](#), [1624](#).
obj_xform_depth: [695](#), [1549](#), [1550](#), [1604](#)*, [1638](#)*.
obj_xform_height: [695](#), [1549](#), [1550](#), [1604](#)*.
obj_xform_resources: [695](#), [763](#), [1549](#).
obj_xform_width: [695](#), [1549](#), [1550](#), [1604](#)*.
obj_ximage_attr: [695](#), [778](#), [1553](#).
obj_ximage_data: [497](#), [695](#), [767](#), [778](#), [1553](#), [1638](#)*.
obj_ximage_depth: [695](#), [1553](#), [1555](#), [1604](#)*.
obj_ximage_height: [695](#), [1553](#), [1555](#), [1604](#)*.
obj_ximage_width: [695](#), [1553](#), [1555](#), [1604](#)*.
objname: [698](#), [793](#), [805](#), [1628](#).
objnum: [698](#), [805](#), [1628](#).
octal_token: [464](#), [470](#).
odd: [62](#)*, [100](#), [116](#), [165](#)*, [211](#), [530](#), [604](#)*, [702](#), [934](#),
[1042](#), [1075](#), [1079](#), [1085](#), [1086](#), [1090](#), [1091](#), [1389](#)*,
[1396](#), [1426](#), [1474](#), [1689](#), [1801](#), [1820](#), [1825](#).
off_save: [1241](#), [1242](#), [1272](#), [1273](#), [1308](#)*, [1309](#),
[1318](#), [1370](#), [1371](#).
OK: [1477](#).
OK_so_far: [466](#), [471](#).
OK_to_interrupt: [88](#), [96](#), [97](#), [98](#), [349](#), [1208](#).
old_l: [1005](#), [1011](#), [1026](#).
old_mode: [727](#), [1616](#)*, [1618](#)*, [1619](#)*.
old_rover: [149](#).
old_setting: [263](#), [264](#), [333](#), [334](#), [491](#), [496](#), [560](#)*, [608](#)*,
[645](#)*, [666](#)*, [686](#), [705](#), [706](#), [712](#), [727](#), [1435](#)*, [1457](#)*,
[1616](#)*, [1618](#)*, [1621](#)*, [1623](#)*, [1689](#), [1754](#), [1881](#)*.
omit: [226](#), [287](#)*, [288](#)*, [964](#), [965](#), [1304](#).
\omit primitive: [287](#)*.
omit_error: [1304](#), [1307](#).
omit_template: [180](#), [965](#), [966](#).
one_bp: [672](#), [687](#), [688](#), [693](#).
one_hundred_bp: [687](#), [688](#), [690](#), [692](#), [693](#), [792](#), [1638](#)*.
one_hundred_inch: [672](#), [687](#), [688](#), [1553](#).
Only one # is allowed...: [960](#).
op_byte: [571](#), [583](#), [705](#), [823](#), [917](#), [929](#), [1086](#),
[1088](#), [1218](#).
op_noad: [858](#), [866](#), [872](#), [874](#), [902](#), [904](#), [909](#), [925](#)*,
[937](#), [1334](#), [1335](#), [1337](#).
op_start: [1097](#)*, [1098](#)*, [1101](#)*, [1122](#)*, [1504](#)*.
open_area: [1522](#)*, [1532](#), [1604](#)*, [1623](#)*.
open_ext: [1522](#)*, [1532](#), [1604](#)*, [1623](#)*.
open_fmt_file: [550](#)*, [1518](#)*.
\openin primitive: [1450](#).
open_input: [563](#)*, [1453](#)*.
open_log_file: [78](#), [92](#), [382](#), [497](#), [558](#)*, [560](#)*, [561](#), [563](#)*,
[684](#), [1435](#)*, [1516](#)*, [1618](#)*.
open_name: [1522](#)*, [1532](#), [1604](#)*, [1623](#)*.
open_noad: [858](#), [866](#), [872](#), [874](#), [904](#), [909](#), [936](#),
[937](#), [938](#), [1334](#), [1335](#).
open_node: [1522](#)*, [1525](#)*, [1527](#), [1529](#)*, [1604](#)*, [1605](#),
[1606](#), [1621](#)*.
open_node_size: [1522](#)*, [1532](#), [1605](#), [1606](#).
open_or_close_in: [1452](#), [1453](#)*.
\openout primitive: [1525](#)*.
open_parens: [326](#)*, [353](#)*, [384](#), [563](#)*, [1516](#)*, [1756](#)*.
open_subentries: [788](#), [1638](#)*.
\or primitive: [517](#).
or_code: [515](#), [517](#), [518](#), [526](#), [535](#), [1471](#)*, [1669](#).
ord: [20](#)*.
ord_noad: [857](#), [858](#), [862](#), [863](#), [866](#), [872](#), [874](#), [904](#),
[905](#), [909](#), [928](#), [929](#), [937](#), [940](#), [941](#), [1253](#), [1333](#),
[1334](#), [1335](#), [1364](#).
order: [195](#).
oriental characters: [152](#), [612](#).
orig_char_info: [580](#)*, [596](#)*, [600](#)*, [603](#)*, [604](#)*, [609](#)*, [648](#)*,
[673](#)*, [705](#), [884](#)*, [898](#)*, [916](#)*, [925](#)*, [1885](#)*, [1886](#)*.
orig_char_info_end: [580](#)*.
other_A_token: [471](#).
other_char: [225](#), [250](#), [311](#), [313](#), [316](#), [320](#), [369](#),
[471](#), [490](#), [552](#)*, [1112](#), [1138](#), [1207](#), [1215](#), [1268](#),
[1302](#), [1329](#), [1332](#), [1338](#).
other_token: [311](#), [431](#), [464](#), [467](#), [471](#), [490](#), [529](#),
[1243](#), [1399](#)*, [1762](#), [1770](#), [1785](#), [1786](#).
othercases: [10](#).
others: [10](#), [1621](#)*.
Uch...clobbered: [1513](#)*.
out_form: [1638](#)*, [1645](#), [1648](#).
out_image: [1638](#)*, [1644](#), [1647](#).
out_param: [225](#), [311](#), [313](#), [316](#), [379](#)*.
out_param_token: [311](#), [505](#).
out_thread: [790](#), [1601](#).
out_what: [1614](#), [1615](#), [1621](#)*, [1624](#), [1640](#), [1646](#).
\outer primitive: [1386](#).
outer_call: [228](#), [297](#), [361](#)*, [373](#), [375](#), [376](#)*, [379](#)*, [388](#)*,
[413](#), [417](#), [422](#), [956](#), [1330](#), [1474](#), [1617](#).
outer_doing_leaders: [647](#)*, [656](#), [657](#)*, [665](#), [729](#)*,
[737](#), [738](#)*, [746](#).
outline_list_count: [1563](#), [1564](#).
outlines: [788](#), [806](#), [1514](#)*.
Output loop...: [1201](#).
Output routine didn't use...: [1205](#).
Output written on x: [670](#)*, [794](#).
\output primitive: [248](#)*.
output_active: [346](#)*, [447](#), [839](#), [851](#), [1163](#), [1166](#),
[1167](#), [1171](#), [1182](#), [1202](#), [1203](#)*.
output_comment: [645](#)*, [1870](#)*.
output_file_name: [558](#)*, [559](#), [670](#)*, [684](#), [794](#), [814](#), [815](#).
output_group: [291](#), [1202](#), [1278](#)*, [1662](#), [1680](#).
output_one_char: [726](#), [731](#)*, [1893](#)*.
output_penalty: [254](#)*.
\outputpenalty primitive: [256](#)*.

- output_penalty_code*: [254*](#), [255*](#), [256*](#), [1190](#).
output_routine: [248*](#), [1189](#), [1202](#).
output_routine_loc: [248*](#), [249](#), [250](#), [329](#), [345](#), [1404](#).
output_text: [329](#), [336](#), [345](#), [346*](#), [347*](#), [416*](#), [1202](#),
[1203*](#).
`\over` primitive: [1356](#).
over_code: [1356](#), [1357](#), [1360](#).
over_noad: [863](#), [866](#), [872](#), [874](#), [909](#), [937](#), [1334](#).
`\overwithdelims` primitive: [1356](#).
overbar: [881](#), [910](#), [913](#).
overflow: [35*](#), [42](#), [43](#), [94*](#), [138](#), [143*](#), [234](#), [279*](#), [282](#),
[286](#), [295](#), [296](#), [343](#), [350*](#), [378*](#), [388*](#), [400](#), [416*](#), [543*](#),
[607](#), [678](#), [680](#), [686](#), [698](#), [705](#), [706](#), [719](#), [725](#),
[1117*](#), [1121*](#), [1131](#), [1141*](#), [1514*](#), [1636](#), [1769](#), [1783](#).
overflow in arithmetic: [9](#), [104*](#).
Overfull `\hbox...`: [842](#).
Overfull `\vbox...`: [853](#).
overfull boxes: [1030](#).
overflow_rule: [265](#), [842](#), [976](#), [980](#).
`\overflowrule` primitive: [266](#).
overflow_rule_code: [265](#), [266](#).
`\overline` primitive: [1334](#).
p: [112](#), [114](#), [138](#), [141](#), [143*](#), [148](#), [149](#), [154](#), [157](#), [162*](#),
[163](#), [165*](#), [169](#), [170*](#), [171*](#), [172](#), [174*](#), [176*](#), [185](#), [190](#),
[192*](#), [194*](#), [196](#), [200](#), [216](#), [218](#), [219](#), [220*](#), [222](#), [236](#),
[278](#), [281](#), [284*](#), [285](#), [298](#), [299](#), [300](#), [301](#), [303](#), [306](#),
[314](#), [317](#), [321](#), [328*](#), [337](#), [345](#), [347*](#), [358](#), [363*](#), [388*](#),
[415](#), [433](#), [439](#), [476](#), [490](#), [491](#), [499](#), [508](#), [523](#), [524](#),
[609*](#), [634](#), [642](#), [647*](#), [657*](#), [666*](#), [674](#), [693](#), [729*](#), [738*](#),
[823](#), [844](#), [855](#), [862](#), [864](#), [865](#), [867](#), [868](#), [880](#), [881](#),
[885](#), [887](#), [891](#), [892](#), [893](#), [896](#), [902](#), [911](#), [914](#), [919](#),
[925*](#), [928](#), [932](#), [948](#), [950](#), [963](#), [967](#), [975](#), [976](#),
[1002](#), [1083](#), [1111*](#), [1125](#), [1126](#), [1130](#), [1134](#), [1136](#),
[1137*](#), [1143*](#), [1145](#), [1147](#), [1170](#), [1171](#), [1189](#), [1242](#),
[1246](#), [1253](#), [1257](#), [1264](#), [1271](#), [1279](#), [1283](#), [1288](#),
[1291](#), [1297](#), [1301](#), [1316](#), [1329](#), [1333](#), [1338](#), [1352](#),
[1354](#), [1362](#), [1369](#), [1372](#), [1389*](#), [1414](#), [1422](#), [1466](#),
[1471*](#), [1481*](#), [1482*](#), [1529*](#), [1530](#), [1546](#), [1557](#), [1574](#),
[1578](#), [1603*](#), [1616*](#), [1618*](#), [1621*](#), [1636](#), [1637](#), [1638*](#),
[1680](#), [1684](#), [1720](#), [1724](#), [1734*](#), [1739*](#), [1745](#), [1754](#),
[1757](#), [1758](#), [1778](#), [1783](#), [1822](#), [1824](#), [1838](#), [1839](#),
[1840](#), [1841](#), [1842](#), [1881*](#), [1900*](#), [1901*](#).
p_1: [1855*](#).
pack_begin_line: [837](#), [838](#), [839](#), [851](#), [980](#), [991](#).
pack_buffered_name: [549*](#), [550*](#).
pack_cur_name: [555](#), [556*](#), [563*](#), [772](#), [1453*](#), [1623*](#).
pack_file_name: [545*](#), [555](#), [589*](#), [713](#).
pack_job_name: [555](#), [558*](#), [560*](#), [684](#), [1509](#).
pack_lig: [1212](#).
package: [1263*](#), [1264](#).
packed_ASCII_code: [38*](#), [39*](#), [793](#), [1124*](#), [1489*](#),
[1513*](#), [1518*](#).
packet_byte: [725](#), [726](#).
packet_length: [712](#), [717](#), [719](#).
packet_read_signed: [725](#).
packet_read_unsigned: [725](#), [726](#).
packet_scaled: [725](#), [726](#).
page: [326*](#), [1553](#).
page_contents: [233*](#), [447](#), [1157](#), [1163](#), [1164](#), [1168](#),
[1177](#), [1178](#), [1185](#).
page_depth: [233*](#), [1159](#), [1164](#), [1168](#), [1179](#), [1180](#),
[1181](#), [1185](#), [1187](#), [1612](#).
`\pagedepth` primitive: [1160](#).
page_disc: [1176](#), [1200](#), [1203*](#), [1860](#), [1861](#).
`\pagediscards` primitive: [1862](#).
`\pagefilstretch` primitive: [1160](#).
`\pagefillstretch` primitive: [1160](#).
`\pagefilllstretch` primitive: [1160](#).
page_goal: [1157](#), [1159](#), [1163](#), [1164](#), [1182](#), [1183](#),
[1184](#), [1185](#), [1186](#), [1187](#).
`\pagegoal` primitive: [1160](#).
page_head: [180](#), [233*](#), [1157](#), [1163](#), [1165*](#), [1168](#), [1191](#),
[1194](#), [1200](#), [1203*](#), [1232](#), [1487*](#).
page_ins_head: [180](#), [498](#), [1158](#), [1163](#), [1182](#), [1185](#),
[1195](#), [1196](#), [1197](#).
page_ins_node_size: [1158](#), [1186](#), [1196](#).
page_loc: [666*](#), [668*](#).
page_max_depth: [233*](#), [1157](#), [1159](#), [1164](#), [1168](#),
[1180](#), [1194](#).
page_shrink: [1159](#), [1162](#), [1181](#), [1184](#), [1185](#), [1186](#).
`\pageshrink` primitive: [1160](#).
page_so_far: [447](#), [1159](#), [1162](#), [1164](#), [1181](#), [1184](#),
[1186](#), [1423](#).
page_stack: [326*](#).
`\pagestretch` primitive: [1160](#).
page_tail: [233*](#), [1157](#), [1163](#), [1168](#), [1175](#), [1177](#), [1194](#),
[1200](#), [1203*](#), [1232](#), [1487*](#).
page_total: [1159](#), [1162](#), [1179](#), [1180](#), [1181](#), [1184](#),
[1185](#), [1187](#), [1612](#).
`\pagetotal` primitive: [1160](#).
pagebox: [1553](#).
pages_tail: [696](#), [800](#), [802](#).
pages_tree_kids_max: [695](#), [770](#), [794](#), [802](#), [803](#).
panicking: [183*](#), [184](#), [1208](#), [1520*](#).
`\par` primitive: [356](#).
par_end: [225](#), [356](#), [357](#), [1224](#), [1272](#).
par_fill_skip: [242](#), [992](#), [1843](#), [1844](#), [1847](#), [1854](#).
`\parfillskip` primitive: [244](#).
par_fill_skip_code: [242](#), [243](#), [244](#), [992](#).
par_indent: [265](#), [1269*](#), [1271](#).
`\parindent` primitive: [266](#).
par_indent_code: [265](#), [266](#).
par_loc: [355](#), [356](#), [373](#), [1449*](#), [1492](#), [1493*](#).
`\parshape` primitive: [287*](#).

- `\parshapedimen` primitive: [1673](#).
- `par_shape_dimen_code`: [1673](#), [1674](#), [1675](#).
- `\parshapeindent` primitive: [1673](#).
- `par_shape_indent_code`: [1673](#), [1674](#), [1675](#).
- `\parshapelength` primitive: [1673](#).
- `par_shape_length_code`: [1673](#), [1674](#), [1675](#).
- `par_shape_loc`: [248](#)*, [250](#), [251](#), [287](#)*, [288](#)*, [449](#), [1248](#), [1426](#).
- `par_shape_ptr`: [248](#)*, [250](#), [251](#), [449](#), [990](#), [1023](#), [1024](#), [1026](#), [1066](#), [1248](#), [1327](#), [1427](#), [1675](#).
- `par_skip`: [242](#), [1269](#)*
- `\parskip` primitive: [244](#).
- `par_skip_code`: [242](#), [243](#), [244](#), [1269](#)*
- `par_token`: [227](#)*, [355](#), [356](#), [361](#)*, [418](#), [421](#), [425](#), [1263](#)*, [1273](#), [1278](#)*, [1308](#)*, [1311](#)*, [1346](#)*, [1449](#)*, [1493](#)*
- Paragraph ended before...: [422](#).
- `param`: [568](#), [573](#), [584](#).
- `param_base`: [576](#)*, [584](#), [592](#), [601](#), [602](#)*, [603](#)*, [605](#), [607](#), [705](#), [706](#), [876](#), [877](#), [1220](#), [1501](#)*, [1502](#)*, [1518](#)*
- `param_end`: [584](#).
- `param_ptr`: [330](#)*, [345](#), [346](#)*, [353](#)*, [416](#)*
- `param_size`: [32](#)*, [330](#)*, [416](#)*, [1513](#)*, [1515](#)*
- `param_stack`: [329](#), [330](#)*, [346](#)*, [381](#), [414](#), [415](#), [416](#)*, [1513](#)*
- `param_start`: [329](#), [345](#), [346](#)*, [381](#).
- `parameter`: [329](#), [336](#), [381](#).
- parameters for symbols: [876](#), [877](#).
- Parameters...consecutively: [502](#).
- `parent_box`: [1631](#), [1636](#), [1637](#), [1638](#)*
- `parse_first_line_p`: [32](#)*, [61](#)*, [562](#)*
- `partoken`: [254](#)*
- `partoken_context`: [254](#)*, [1263](#)*, [1278](#)*, [1308](#)*, [1311](#)*, [1346](#)*
- `\partokencontext` primitive: [256](#)*
- `partoken_context_code`: [254](#)*, [255](#)*, [256](#)*
- `partoken_name`: [227](#)*, [256](#)*, [288](#)*, [1449](#)*
- `\partokenname` primitive: [256](#)*
- Pascal-H: [3](#), [9](#), [10](#).
- Pascal: [1](#), [10](#), [869](#), [940](#).
- `pass_number`: [997](#), [1021](#), [1040](#).
- `pass_text`: [388](#)*, [520](#), [526](#), [535](#), [536](#).
- `passive`: [997](#), [1021](#), [1022](#), [1040](#), [1041](#).
- `passive_node_size`: [997](#), [1021](#), [1041](#).
- Patterns can be...: [1430](#)*
- `\patterns` primitive: [1428](#).
- `pause_for_instructions`: [96](#), [98](#).
- `pausing`: [254](#)*, [385](#)*
- `\pausing` primitive: [256](#)*
- `pausing_code`: [254](#)*, [255](#)*, [256](#)*
- `pc`: [204](#)*
- `pc`: [484](#).
- `pdf_action_file`: [695](#), [1537](#), [1557](#), [1604](#)*, [1631](#).
- `pdf_action_goto`: [695](#), [1557](#), [1604](#)*, [1631](#).
- `pdf_action_id`: [695](#), [1537](#), [1557](#), [1604](#)*, [1631](#).
- `pdf_action_named_id`: [695](#), [1537](#), [1557](#), [1604](#)*, [1631](#).
- `pdf_action_new_window`: [695](#), [1557](#), [1631](#).
- `pdf_action_page`: [695](#), [1537](#), [1557](#), [1604](#)*, [1631](#).
- `pdf_action_page_tokens`: [695](#), [1537](#), [1557](#), [1604](#)*, [1631](#).
- `pdf_action_refcount`: [695](#), [1537](#), [1557](#).
- `pdf_action_size`: [695](#), [1537](#), [1557](#).
- `pdf_action_struct_id`: [695](#), [1537](#), [1557](#), [1631](#).
- `pdf_action_thread`: [695](#), [1557](#), [1604](#)*, [1631](#).
- `pdf_action_type`: [695](#), [782](#), [1537](#), [1557](#), [1604](#)*, [1631](#).
- `pdf_action_user`: [695](#), [782](#), [1537](#), [1557](#), [1604](#)*, [1631](#).
- `pdf_action_user_tokens`: [695](#), [1537](#), [1557](#), [1604](#)*, [1631](#).
- `pdf_adjust_interword_glue`: [254](#)*, [1207](#), [1219](#).
- `\pdfadjustinterwordglue` primitive: [256](#)*
- `pdf_adjust_interword_glue_code`: [254](#)*, [255](#)*, [256](#)*
- `pdf_adjust_spacing`: [254](#)*, [999](#), [1003](#), [1017](#), [1018](#), [1027](#), [1042](#), [1043](#), [1046](#), [1047](#), [1066](#).
- `\pdfadjustspacing` primitive: [256](#)*
- `pdf_adjust_spacing_code`: [254](#)*, [255](#)*, [256](#)*
- `\pdfannot` primitive: [1525](#)*
- `pdf_annot_data`: [695](#), [781](#), [1559](#), [1604](#)*, [1605](#), [1606](#).
- `pdf_annot_list`: [754](#), [765](#), [771](#), [781](#), [1629](#), [1631](#).
- `pdf_annot_node`: [781](#), [1525](#)*, [1527](#), [1529](#)*, [1559](#), [1604](#)*, [1605](#), [1606](#), [1640](#), [1646](#).
- `pdf_annot_node_size`: [695](#), [1559](#), [1561](#), [1605](#), [1606](#).
- `pdf_annot_objnum`: [695](#), [1559](#), [1631](#).
- `pdf_append_kern`: [254](#)*, [705](#).
- `\pdfappendkern` primitive: [256](#)*
- `pdf_append_kern_code`: [254](#)*, [255](#)*, [256](#)*
- `pdf_append_list`: [693](#), [696](#), [698](#), [1631](#), [1636](#), [1637](#), [1638](#)*, [1640](#), [1646](#).
- `pdf_append_list_arg`: [696](#), [698](#).
- `pdf_append_list_end`: [698](#).
- `pdf_bead_list`: [754](#), [765](#), [771](#), [786](#), [1629](#), [1638](#)*
- `pdf_begin_dict`: [698](#), [699](#), [752](#), [762](#), [769](#), [772](#), [778](#), [781](#), [782](#), [784](#), [789](#), [803](#), [805](#), [1601](#).
- `pdf_begin_obj`: [698](#), [772](#), [784](#), [795](#), [797](#).
- `pdf_begin_stream`: [685](#), [699](#), [757](#), [772](#), [814](#).
- `pdf_begin_string`: [693](#), [726](#).
- `pdf_begin_text`: [693](#).
- `pdf_bottom`: [695](#), [781](#), [782](#), [785](#), [1631](#), [1636](#), [1638](#)*
- `pdf_box_spec_art`: [696](#), [697](#), [1553](#).
- `pdf_box_spec_bleed`: [696](#), [697](#), [1553](#).
- `pdf_box_spec_crop`: [696](#), [697](#), [1553](#).
- `pdf_box_spec_media`: [696](#), [697](#), [1553](#).
- `pdf_box_spec_trim`: [696](#), [697](#), [1553](#).
- `pdf_buf`: [680](#), [681](#), [685](#), [686](#), [698](#), [699](#), [772](#).
- `pdf_buf_size`: [680](#), [681](#), [686](#), [698](#), [699](#).
- `\pdfcatalog` primitive: [1525](#)*

- pdf_catalog_code*: [1525*](#), [1527](#), [1529*](#)
pdf_catalog_openaction: [806](#), [1580](#), [1629](#), [1630](#).
pdf_catalog_toks: [806](#), [1580](#), [1629](#), [1630](#).
pdf_char_marked: [801](#).
pdf_char_used: [708](#), [1502*](#), [1518*](#)
pdf_check_obj: [497](#), [1546](#), [1547](#), [1550](#), [1555](#).
pdf_check_vf_cur_val: [497](#), [703](#), [720](#), [1588](#).
\pdfcolorstack primitive: [1525*](#)
pdf_colorstack_cmd: [695](#), [727](#), [1540](#), [1604*](#), [1605](#), [1606](#).
pdf_colorstack_data: [695](#), [727](#), [1540](#), [1604*](#), [1605](#), [1606](#).
pdf_colorstack_getter_node_size: [695](#), [1540](#), [1605](#), [1606](#).
\pdfcolorstackinit primitive: [494](#).
pdf_colorstack_init_code: [494](#), [495](#), [497](#), [498](#).
pdf_colorstack_node: [1525*](#), [1527](#), [1529*](#), [1540](#), [1604*](#), [1605](#), [1606](#), [1640](#), [1646](#).
pdf_colorstack_node_size: [695](#).
pdf_colorstack_setter_node_size: [695](#), [1540](#), [1605](#), [1606](#).
pdf_colorstack_stack: [695](#), [727](#), [1540](#), [1604*](#)
pdf_compress_level: [254*](#), [672](#), [673*](#), [685](#), [698](#), [748](#).
\pdfcompresslevel primitive: [256*](#)
pdf_compress_level_code: [254*](#), [255*](#), [256*](#)
pdf_copy_font: [227*](#), [287*](#), [288*](#), [439](#), [604*](#), [1388](#), [1434](#).
\pdfcopyfont primitive: [287*](#)
pdf_create_obj: [693](#), [698](#), [770](#), [804](#), [1545](#), [1549](#), [1553](#), [1556](#), [1564](#), [1637](#).
\pdfcreationdate primitive: [494](#).
pdf_creation_date_code: [494](#), [495](#), [497](#).
pdf_cur_form: [752](#), [756](#), [763](#), [775](#), [1624](#), [1629](#).
pdf_cur_Tm_a: [690](#), [691](#), [692](#), [693](#).
pdf_decimal_digits: [254*](#), [672](#), [792](#).
\pdfdecimaldigits primitive: [256*](#)
pdf_decimal_digits_code: [254*](#), [255*](#), [256*](#)
pdf_delta_h: [690](#), [691](#), [692](#), [693](#).
pdf_depth: [695](#), [1550](#), [1555](#), [1557](#), [1566](#), [1602](#), [1604*](#), [1605](#), [1607](#), [1608](#), [1612](#), [1613](#), [1631](#), [1636](#), [1637](#), [1638*](#), [1644](#), [1645](#), [1647](#).
\pdfdest primitive: [1525*](#)
pdf_dest_fit: [695](#), [784](#), [1566](#), [1604*](#), [1638*](#)
pdf_dest_fitb: [695](#), [784](#), [1566](#), [1604*](#), [1638*](#)
pdf_dest_fitbh: [695](#), [784](#), [1566](#), [1604*](#), [1638*](#)
pdf_dest_fitbv: [695](#), [784](#), [1566](#), [1604*](#), [1638*](#)
pdf_dest_fith: [695](#), [784](#), [1566](#), [1604*](#), [1638*](#)
pdf_dest_fitr: [695](#), [784](#), [1566](#), [1604*](#), [1638*](#)
pdf_dest_fitv: [695](#), [784](#), [1566](#), [1604*](#), [1638*](#)
pdf_dest_id: [695](#), [1566](#), [1604*](#), [1605](#), [1606](#), [1638*](#)
pdf_dest_list: [754](#), [765](#), [784](#), [1629](#), [1638*](#)
pdf_dest_margin: [265](#), [1638*](#)
\pdfdestmargin primitive: [266](#).
pdf_dest_margin_code: [265](#), [266](#).
pdf_dest_named_id: [695](#), [784](#), [1566](#), [1604*](#), [1605](#), [1606](#), [1638*](#)
pdf_dest_names_ptr: [698](#), [804](#), [805](#), [1514*](#), [1629](#), [1630](#).
pdf_dest_node: [695](#), [1525*](#), [1527](#), [1529*](#), [1566](#), [1604*](#), [1605](#), [1606](#), [1640](#), [1646](#).
pdf_dest_node_size: [695](#), [1566](#), [1605](#), [1606](#).
pdf_dest_objnum: [695](#), [784](#), [1566](#), [1604*](#), [1638*](#)
pdf_dest_type: [695](#), [784](#), [1566](#), [1604*](#), [1638*](#)
pdf_dest_xyz: [695](#), [784](#), [1566](#), [1604*](#), [1638*](#)
pdf_dest_xyz_zoom: [695](#), [784](#), [1566](#), [1604*](#)
pdf_doing_string: [691](#), [692](#), [693](#).
pdf_doing_text: [691](#), [693](#).
pdf_draftmode: [254*](#), [672](#), [683](#), [748](#), [1518*](#)
\pdfdraftmode primitive: [256*](#)
pdf_draftmode_code: [254*](#), [255*](#), [256*](#)
pdf_draftmode_option: [691](#), [1518*](#)
pdf_draftmode_value: [691](#), [1518*](#)
pdf_dummy_font: [691](#), [693](#), [697](#).
pdf_each_line_depth: [265](#), [1064](#), [1065](#).
\pdfeachlinedepth primitive: [266](#).
pdf_each_line_depth_code: [265](#), [266](#).
pdf_each_line_height: [265](#), [1064](#), [1065](#).
\pdfeachlineheight primitive: [266](#).
pdf_each_line_height_code: [265](#), [266](#).
pdf_end_dict: [698](#), [762](#), [769](#), [781](#), [782](#), [784](#), [788](#), [789](#), [803](#), [804](#), [805](#), [806](#), [807](#), [1601](#).
\pdfendlink primitive: [1525*](#)
pdf_end_link_node: [1525*](#), [1527](#), [1529*](#), [1562](#), [1604*](#), [1605](#), [1606](#), [1640](#), [1646](#).
pdf_end_obj: [685](#), [698](#), [772](#), [784](#), [786](#), [790](#), [795](#), [797](#), [1564](#), [1580](#).
pdf_end_stream: [685](#), [699](#), [760](#), [772](#), [814](#).
pdf_end_string: [692](#), [693](#).
pdf_end_string_nl: [692](#), [693](#).
pdf_end_text: [693](#), [760](#), [1638*](#)
\pdfendthread primitive: [1525*](#)
pdf_end_thread_node: [1525*](#), [1527](#), [1529*](#), [1570](#), [1604*](#), [1605](#), [1606](#), [1640](#), [1646](#).
pdf_error: [497](#), [597](#), [599](#), [683](#), [685](#), [686](#), [689](#), [693](#), [705](#), [706](#), [712](#), [720](#), [726](#), [727](#), [747](#), [748](#), [772](#), [784](#), [823](#), [1005](#), [1538](#), [1546](#), [1549](#), [1553](#), [1557](#), [1559](#), [1561](#), [1562](#), [1566](#), [1567](#), [1574](#), [1580](#), [1588](#), [1590](#), [1594](#), [1604*](#), [1621*](#), [1624](#), [1631](#), [1636](#), [1638*](#), [1640](#), [1646](#).
\pdfescapehex primitive: [494](#).
pdf_escape_hex_code: [494](#), [495](#), [497](#).
\pdfescapename primitive: [494](#).
pdf_escape_name_code: [494](#), [495](#), [497](#).
\pdfescapestring primitive: [494](#).
pdf_escape_string_code: [494](#), [495](#), [497](#).

- pdf-f*: [691](#), [692](#), [693](#).
\pdffakespace primitive: [1525](#)*
pdf_fake_space_node: [1525](#)*, [1527](#), [1529](#)*, [1597](#), [1604](#)*,
[1605](#), [1606](#), [1640](#), [1646](#).
pdf_file: [680](#), [684](#), [794](#).
\pdffiledump primitive: [494](#).
pdf_file_dump_code: [494](#), [495](#), [497](#).
\pdffilemoddate primitive: [494](#).
pdf_file_mod_date_code: [494](#), [495](#), [497](#).
\pdffilesize primitive: [494](#).
pdf_file_size_code: [494](#), [495](#), [497](#).
pdf_first_line_height: [265](#), [1064](#), [1065](#).
\pdffirstlineheight primitive: [266](#).
pdf_first_line_height_code: [265](#), [266](#).
pdf_first_outline: [788](#), [789](#), [1564](#), [1629](#), [1630](#).
pdf_fix_dest: [795](#), [796](#).
pdf_fix_struct_dest: [797](#), [798](#).
pdf_fix_thread: [1601](#).
pdf_flush: [680](#), [685](#), [794](#).
pdf_font_attr: [704](#), [801](#), [1502](#)*, [1518](#)*, [1590](#).
\pdffontattr primitive: [1525](#)*
pdf_font_attr_code: [1525](#)*, [1527](#), [1529](#)*
pdf_font_auto_expand: [692](#), [693](#), [705](#), [712](#), [720](#),
[821](#), [1502](#)*, [1518](#)*
pdf_font_blink: [192](#)*, [693](#), [705](#), [720](#), [821](#), [1502](#)*, [1518](#)*
pdf_font_ef_base: [705](#), [821](#), [1502](#)*, [1518](#)*
pdf_font_elink: [703](#), [705](#), [821](#), [1502](#)*, [1518](#)*
\pdffontexpand primitive: [1525](#)*
pdf_font_expand_code: [1525](#)*, [1527](#), [1529](#)*
pdf_font_expand_ratio: [192](#)*, [692](#), [705](#), [706](#), [712](#),
[720](#), [821](#), [823](#), [1502](#)*, [1518](#)*
pdf_font_has_space_char: [693](#), [821](#), [1502](#)*, [1518](#)*
pdf_font_kn_ac_base: [705](#), [821](#), [1502](#)*, [1518](#)*
pdf_font_kn_bc_base: [705](#), [821](#), [1502](#)*, [1518](#)*
pdf_font_kn_bs_base: [705](#), [821](#), [1502](#)*, [1518](#)*
pdf_font_list: [693](#), [708](#), [750](#)*, [753](#), [764](#), [766](#), [775](#),
[776](#), [777](#).
pdf_font_lp_base: [705](#), [821](#), [1502](#)*, [1518](#)*
pdf_font_map: [693](#), [708](#), [1502](#)*, [1518](#)*
\pdffontname primitive: [494](#).
pdf_font_name_code: [494](#), [495](#), [497](#), [498](#).
pdf_font_nobuiltin_tounicode: [704](#), [1502](#)*, [1518](#)*
[1594](#).
pdf_font_num: [498](#), [692](#), [693](#), [698](#), [708](#), [766](#), [801](#),
[1502](#)*, [1518](#)*
\pdffontobjnum primitive: [494](#).
pdf_font_objnum_code: [494](#), [495](#), [497](#), [498](#).
pdf_font_rp_base: [705](#), [821](#), [1502](#)*, [1518](#)*
pdf_font_sh_bs_base: [705](#), [821](#), [1502](#)*, [1518](#)*
pdf_font_shrink: [705](#), [712](#), [821](#), [823](#), [1502](#)*, [1518](#)*
pdf_font_size: [690](#), [692](#), [693](#), [708](#), [1502](#)*, [1518](#)*
\pdffontsize primitive: [494](#).
pdf_font_size_code: [494](#), [495](#), [497](#), [498](#).
pdf_font_st_bs_base: [705](#), [821](#), [1502](#)*, [1518](#)*
pdf_font_step: [705](#), [706](#), [712](#), [821](#), [823](#), [1438](#)*,
[1502](#)*, [1518](#)*
pdf_font_stretch: [705](#), [712](#), [821](#), [823](#), [1502](#)*, [1518](#)*
pdf_font_type: [703](#), [704](#), [705](#), [706](#), [712](#), [720](#), [726](#),
[1502](#)*, [1518](#)*
pdf_force_pagebox: [254](#)*, [1553](#).
\pdfforcepagebox primitive: [256](#)*
pdf_force_pagebox_code: [254](#)*, [255](#)*, [256](#)*
pdf_gamma: [254](#)*, [672](#), [683](#).
\pdfgamma primitive: [256](#)*
pdf_gamma_code: [254](#)*, [255](#)*, [256](#)*
pdf_gen_tounicode: [254](#)*, [801](#).
\pdfgentounicode primitive: [256](#)*
pdf_gen_tounicode_code: [254](#)*, [255](#)*, [256](#)*
pdf_get_mem: [678](#), [705](#), [1545](#), [1549](#), [1553](#), [1564](#),
[1638](#)*
\pdfglyphtounicode primitive: [1525](#)*
pdf_glyph_to_unicode_code: [1525](#)*, [1527](#), [1529](#)*
pdf_gone: [680](#), [681](#), [685](#), [794](#).
pdf_h: [690](#), [691](#), [692](#).
pdf_h_origin: [265](#), [672](#), [755](#).
\pdfhorigin primitive: [266](#).
pdf_h_origin_code: [265](#), [266](#).
pdf_height: [695](#), [1550](#), [1555](#), [1557](#), [1566](#), [1602](#),
[1604](#)*, [1605](#), [1607](#), [1608](#), [1612](#), [1613](#), [1631](#), [1636](#),
[1637](#), [1638](#)*, [1644](#), [1645](#).
pdf_hlist_out: [727](#), [729](#)*, [733](#)*, [737](#), [738](#)*, [742](#)*, [746](#),
[751](#), [1556](#), [1888](#)*, [1893](#)*
pdf_ignored_dimen: [237](#)*, [265](#), [855](#), [963](#), [1064](#), [1065](#),
[1202](#), [1234](#), [1261](#), [1277](#), [1345](#)*, [1482](#)*
\pdfignoreddimen primitive: [266](#).
pdf_ignored_dimen_code: [265](#), [266](#).
pdf_image_apply_gamma: [254](#)*, [672](#), [683](#).
\pdfimageapplygamma primitive: [256](#)*
pdf_image_apply_gamma_code: [254](#)*, [255](#)*, [256](#)*
pdf_image_gamma: [254](#)*, [672](#), [683](#).
\pdfimagegamma primitive: [256](#)*
pdf_image_gamma_code: [254](#)*, [255](#)*, [256](#)*
pdf_image_hicolor: [254](#)*, [672](#), [683](#).
\pdfimagehicolor primitive: [256](#)*
pdf_image_hicolor_code: [254](#)*, [255](#)*, [256](#)*
pdf_image_procset: [701](#), [750](#)*, [753](#), [768](#), [776](#), [777](#).
pdf_image_resolution: [254](#)*, [672](#), [1553](#).
\pdfimageresolution primitive: [256](#)*
pdf_image_resolution_code: [254](#)*, [255](#)*, [256](#)*
pdf_include_chars: [1588](#), [1589](#).
\pdfincludechars primitive: [1525](#)*
pdf_include_chars_code: [1525](#)*, [1527](#), [1529](#)*
pdf_inclusion_copy_font: [254](#)*, [683](#).
\pdfinclusioncopyfonts primitive: [256](#)*

- pdf_inclusion_copy_font_code*: [254*](#), [255*](#), [256*](#)
pdf_inclusion_errorlevel: [254*](#), [1506](#), [1553](#).
`\pdfinclusionerrorlevel` primitive: [256*](#)
pdf_inclusion_errorlevel_code: [254*](#), [255*](#), [256*](#)
pdf_indirect: [702](#), [1631](#).
pdf_indirect_ln: [702](#), [756](#), [769](#), [770](#), [788](#), [789](#), [803](#),
[804](#), [806](#), [814](#), [815](#), [1601](#).
`\pdfinfo` primitive: [1525*](#)
pdf_info_code: [1525*](#), [1527](#), [1529*](#)
pdf_info_omit_date: [254*](#), [807](#).
`\pdfinfoomitdate` primitive: [256*](#)
pdf_info_omit_date_code: [254*](#), [255*](#), [256*](#)
pdf_info_toks: [807](#), [1579](#), [1629](#), [1630](#).
pdf_init_font: [693](#), [1588](#).
pdf_init_font_cur_val: [497](#), [693](#), [703](#).
pdf_init_map_file: [1518*](#)
pdf_insert_fake_space: [693](#), [1640](#), [1646](#).
`\pdfinsertht` primitive: [494](#).
pdf_insert_ht_code: [494](#), [495](#), [497](#), [498](#).
pdf_insert_interword_space: [693](#).
pdf_int_entry: [702](#), [1631](#).
pdf_int_entry_ln: [702](#), [788](#), [789](#), [803](#), [814](#), [815](#).
pdf_int_pars: [254*](#)
`\pdfinterwordspaceoff` primitive: [1525*](#)
pdf_interword_space_off_node: [1525*](#), [1527](#), [1529*](#),
[1596](#), [1604*](#), [1605](#), [1606](#), [1640](#), [1646](#).
`\pdfinterwordspaceon` primitive: [1525*](#)
pdf_interword_space_on_node: [1525*](#), [1527](#), [1529*](#),
[1595](#), [1604*](#), [1605](#), [1606](#), [1640](#), [1646](#).
pdf_last_annot: [450](#), [1558](#), [1559](#).
`\pdflastannot` primitive: [442](#).
pdf_last_annot_code: [442](#), [443](#), [450](#).
pdf_last_byte: [685](#), [696](#).
pdf_last_f: [691](#), [693](#).
pdf_last_fs: [691](#), [693](#).
pdf_last_line_depth: [265](#), [1064](#), [1065](#).
`\pdflastlinedepth` primitive: [266](#).
pdf_last_line_depth_code: [265](#), [266](#).
pdf_last_link: [450](#), [1560](#), [1561](#).
`\pdflastlink` primitive: [442](#).
pdf_last_link_code: [442](#), [443](#), [450](#).
`\pdflastmatch` primitive: [494](#).
pdf_last_match_code: [494](#), [495](#), [497](#).
pdf_last_obj: [450](#), [1505](#), [1506](#), [1544](#), [1545](#), [1624](#).
`\pdflastobj` primitive: [442](#).
pdf_last_obj_code: [442](#), [443](#), [450](#).
pdf_last_outline: [788](#), [789](#), [1564](#), [1629](#), [1630](#).
pdf_last_page: [696](#), [752](#), [769](#), [784](#), [1638*](#)
pdf_last_pages: [696](#), [770](#), [794](#), [802](#), [803](#), [806](#), [1514*](#)
pdf_last_resources: [750*](#), [752](#), [756](#), [762](#), [769](#).
pdf_last_stream: [696](#), [752](#), [769](#).
pdf_last_thread_id: [1629](#), [1638*](#)
pdf_last_thread_named_id: [1629](#), [1638*](#)
pdf_last_x_pos: [450](#), [1571](#), [1622](#), [1642](#).
`\pdflastxpos` primitive: [442](#).
pdf_last_x_pos_code: [442](#), [443](#), [450](#).
pdf_last_xform: [450](#), [1505](#), [1506](#), [1548](#), [1549](#), [1624](#).
`\pdflastxform` primitive: [442](#).
pdf_last_xform_code: [442](#), [443](#), [450](#).
pdf_last_ximage: [450](#), [1505](#), [1506](#), [1551](#), [1553](#), [1624](#).
`\pdflastximage` primitive: [442](#).
pdf_last_ximage_code: [442](#), [443](#), [450](#).
pdf_last_ximage_colordepth: [450](#), [1551](#), [1553](#).
`\pdflastximagecolordepth` primitive: [442](#).
pdf_last_ximage_colordepth_code: [442](#), [443](#), [450](#).
pdf_last_ximage_pages: [450](#), [1551](#), [1553](#).
`\pdflastximagepages` primitive: [442](#).
pdf_last_ximage_pages_code: [442](#), [443](#), [450](#).
pdf_last_y_pos: [450](#), [1571](#), [1622](#), [1642](#).
`\pdflastypos` primitive: [442](#).
pdf_last_y_pos_code: [442](#), [443](#), [450](#).
pdf_lateliteral_node: [727](#), [1525*](#), [1539](#), [1604*](#), [1605](#),
[1606](#), [1640](#), [1646](#).
pdf_left: [695](#), [781](#), [782](#), [784](#), [785](#), [1631](#), [1636](#), [1638*](#)
pdf_link_action: [695](#), [782](#), [1561](#), [1604*](#), [1605](#), [1606](#).
pdf_link_attr: [695](#), [782](#), [1557](#), [1604*](#), [1605](#), [1606](#).
pdf_link_list: [754](#), [765](#), [771](#), [782](#), [783](#), [1629](#),
[1636](#), [1637](#).
pdf_link_margin: [265](#), [1636](#), [1637](#).
`\pdflinkmargin` primitive: [266](#).
pdf_link_margin_code: [265](#), [266](#).
pdf_link_objnum: [695](#), [1561](#), [1605](#), [1636](#).
pdf_link_stack: [729*](#), [730](#), [1632](#), [1634](#), [1637](#).
pdf_link_stack_ptr: [730](#), [1632](#), [1634](#), [1635](#), [1636](#).
pdf_link_stack_record: [1633](#), [1634](#).
pdf_link_stack_top: [1632](#), [1636](#).
`\pdfliteral` primitive: [1525*](#)
pdf_literal_data: [695](#), [727](#), [1539](#), [1604*](#), [1605](#), [1606](#).
pdf_literal_mode: [695](#), [727](#), [1539](#), [1604*](#)
pdf_literal_node: [1525*](#), [1527](#), [1529*](#), [1539](#), [1604*](#),
[1605](#), [1606](#), [1640](#), [1646](#).
pdf_lookup_list: [700](#), [1638*](#)
pdf_major_version: [254*](#), [672](#), [683](#), [768](#), [1506](#), [1553](#).
`\pdfmajorversion` primitive: [256*](#)
pdf_major_version_code: [254*](#), [255*](#), [256*](#)
`\pdfmapfile` primitive: [1525*](#)
pdf_map_file_code: [1525*](#), [1527](#), [1529*](#)
`\pdfmapline` primitive: [1525*](#)
pdf_map_line_code: [1525*](#), [1527](#), [1529*](#)
pdf_mark_char: [686](#), [693](#), [801](#), [1588](#).
`\pdfmatch` primitive: [494](#).
pdf_match_code: [494](#), [495](#), [497](#).
pdf_max_link_level: [1632](#), [1634](#), [1636](#).
`\pdfmdfivesum` primitive: [494](#).

- pdf_mdfive_sum_code*: [494](#), [495](#), [497](#).
pdf_mem: [675](#), [676](#), [677](#), [678](#), [695](#), [705](#), [1505](#),
[1506](#), [1513](#)*.
pdf_mem_ptr: [676](#), [677](#), [678](#), [1505](#), [1506](#), [1514](#)*.
pdf_mem_size: [676](#), [677](#), [678](#), [1505](#), [1506](#), [1513](#)*,
[1514](#)*.
pdf_minor_version: [254](#)*, [672](#), [683](#), [1506](#), [1553](#).
\pdfminorversion primitive: [256](#)*.
\pdfoptionpdfminorversion primitive: [256](#)*.
pdf_minor_version_code: [254](#)*, [255](#)*, [256](#)*.
pdf_move_chars: [254](#)*, [692](#).
\pdfmovechars primitive: [256](#)*.
pdf_move_chars_code: [254](#)*, [255](#)*, [256](#)*.
\pdfnames primitive: [1525](#)*.
pdf_names_code: [1525](#)*, [1527](#), [1529](#)*.
pdf_names_toks: [804](#), [1581](#), [1629](#), [1630](#).
pdf_new_dict: [698](#), [752](#), [788](#), [804](#), [806](#), [807](#),
[814](#), [1601](#).
pdf_new_line_char: [685](#), [686](#), [699](#).
pdf_new_obj: [698](#), [786](#), [790](#), [1564](#), [1580](#).
pdf_new_objnum: [698](#), [752](#), [802](#), [1559](#), [1561](#), [1631](#),
[1636](#), [1638](#)*.
pdf_new_Tm_a: [692](#).
\pdfnombuiltintounicode primitive: [1525](#)*.
pdf_nombuiltin_tounicode_code: [1525](#)*, [1527](#), [1529](#)*.
\pdfobj primitive: [1525](#)*.
pdf_obj_code: [1525](#)*, [1527](#), [1529](#)*, [1624](#).
pdf_obj_count: [1505](#), [1506](#), [1545](#), [1629](#), [1630](#).
pdf_obj_list: [750](#)*, [753](#), [764](#), [773](#), [775](#), [776](#), [777](#),
[1544](#), [1629](#), [1640](#), [1646](#).
pdf_obj_objnum: [695](#), [1547](#), [1604](#)*, [1640](#), [1646](#).
pdf_objcompresslevel: [254](#)*, [672](#), [683](#).
\pdfobjcompresslevel primitive: [256](#)*.
pdf_objcompresslevel_code: [254](#)*, [255](#)*, [256](#)*.
pdf_objtype_max: [695](#).
pdf_offset: [680](#), [685](#), [698](#), [794](#), [813](#).
pdf_omit_charset: [254](#)*, [673](#)*.
\pdfomitcharset primitive: [256](#)*.
pdf_omit_charset_code: [254](#)*, [255](#)*, [256](#)*.
pdf_omit_info_dict: [254](#)*, [794](#), [814](#), [815](#).
\pdfomitinfodict primitive: [256](#)*.
pdf_omit_info_dict_code: [254](#)*, [255](#)*, [256](#)*.
pdf_omit_procset: [254](#)*, [768](#).
\pdfomitprocset primitive: [256](#)*.
pdf_omit_procset_code: [254](#)*, [255](#)*, [256](#)*.
pdf_op_buf: [680](#), [681](#), [698](#), [1513](#)*.
pdf_op_buf_size: [679](#), [680](#), [681](#), [698](#), [1513](#)*.
pdf_op_ptr: [680](#), [681](#), [698](#).
pdf_option_always_use_pdfpagebox: [254](#)*, [1553](#).
\pdfoptionalwaysusepdfpagebox
primitive: [256](#)*.
- pdf_option_always_use_pdfpagebox_code*: [254](#)*, [255](#)*,
[256](#)*.
pdf_option_pdf_inclusion_errorlevel: [254](#)*, [1553](#).
\pdfoptionpdfinclusionerrorlevel
primitive: [256](#)*.
pdf_option_pdf_inclusion_errorlevel_code: [254](#)*,
[255](#)*, [256](#)*.
pdf_origin_h: [691](#), [692](#), [752](#), [780](#).
pdf_origin_v: [691](#), [692](#), [752](#), [780](#).
pdf_os: [698](#).
pdf_os_buf: [680](#), [686](#), [698](#), [699](#), [1513](#)*.
pdf_os_buf_size: [679](#), [680](#), [681](#), [686](#), [698](#).
pdf_os_cntr: [680](#), [681](#), [698](#), [1514](#)*.
pdf_os_cur_objnum: [680](#), [681](#), [698](#), [699](#).
pdf_os_enable: [680](#), [683](#), [698](#), [794](#), [815](#).
pdf_os_get_os_buf: [680](#), [686](#).
pdf_os_level: [698](#).
pdf_os_max_objs: [679](#), [698](#), [1513](#)*, [1514](#)*.
pdf_os_mode: [680](#), [681](#), [685](#), [698](#), [699](#).
pdf_os_objidx: [680](#), [698](#), [699](#), [1514](#)*.
pdf_os_objnum: [680](#), [698](#), [699](#), [1513](#)*.
pdf_os_objoff: [680](#), [698](#), [699](#), [1513](#)*.
pdf_os_prepare_obj: [698](#).
pdf_os_ptr: [680](#), [681](#), [698](#).
pdf_os_switch: [698](#), [794](#).
pdf_os_write_objstream: [698](#), [699](#), [794](#).
pdf_out: [680](#), [683](#), [685](#), [686](#), [690](#), [692](#), [693](#), [699](#),
[702](#), [756](#), [766](#), [767](#), [769](#), [772](#), [784](#), [785](#), [786](#), [790](#),
[795](#), [797](#), [805](#), [808](#), [814](#), [1601](#), [1631](#), [1638](#)*.
pdf_out_bytes: [702](#), [814](#).
pdf_out_colorstack: [727](#), [1640](#), [1646](#).
pdf_out_colorstack_startpage: [727](#), [757](#).
pdf_out_literal: [727](#), [1640](#), [1646](#).
pdf_out_restore: [727](#), [1640](#), [1646](#).
pdf_out_save: [727](#), [1640](#), [1646](#).
pdf_out_setmatrix: [727](#), [1640](#), [1646](#).
\pdfoutline primitive: [1525](#)*.
pdf_outline_code: [1525](#)*, [1527](#), [1529](#)*.
pdf_output: [254](#)*, [747](#), [750](#)*, [791](#), [1027](#), [1518](#)*, [1538](#),
[1579](#), [1580](#), [1582](#), [1583](#).
\pdfoutput primitive: [256](#)*.
pdf_output_code: [254](#)*, [255](#)*, [256](#)*.
pdf_output_option: [691](#), [1518](#)*.
pdf_output_value: [691](#), [750](#)*, [1518](#)*.
pdf_page_attr: [248](#)*, [769](#).
\pdfpageattr primitive: [248](#)*.
pdf_page_attr_loc: [248](#)*, [249](#).
pdf_page_group_val: [680](#), [752](#), [769](#), [1638](#)*.
pdf_page_height: [265](#), [644](#), [755](#), [1601](#).
\pdfpageheight primitive: [266](#).
pdf_page_height_code: [265](#), [266](#).
\pdfpageref primitive: [494](#).

- pdf_page_ref_code*: [494](#), [495](#), [497](#), [498](#).
pdf_page_resources: [248](#)*, [763](#).
\pdfpagemresources primitive: [248](#)*.
pdf_page_resources_loc: [248](#)*, [249](#).
pdf_page_width: [265](#), [644](#), [755](#), [1601](#).
\pdfpagewidth primitive: [266](#).
pdf_page_width_code: [265](#), [266](#).
pdf_pagebox: [254](#)*, [1553](#).
\pdfpagebox primitive: [256](#)*.
pdf_pagebox_code: [254](#)*, [255](#)*, [256](#)*.
pdf_pages_attr: [248](#)*, [803](#).
\pdfpagesattr primitive: [248](#)*.
pdf_pages_attr_loc: [248](#)*, [249](#).
pdf_parent_outline: [789](#), [1564](#), [1629](#), [1630](#).
pdf_pk_mode: [248](#)*, [792](#).
\pdfpkmode primitive: [248](#)*.
pdf_pk_mode_loc: [248](#)*, [249](#).
pdf_pk_resolution: [254](#)*, [792](#).
\pdfpkresolution primitive: [256](#)*.
pdf_pk_resolution_code: [254](#)*, [255](#)*, [256](#)*.
pdf_prepend_kern: [254](#)*, [705](#), [1212](#).
\pdfprependkern primitive: [256](#)*.
pdf_prepend_kern_code: [254](#)*, [255](#)*, [256](#)*.
pdf_print: [683](#), [686](#), [692](#), [693](#), [698](#), [699](#), [702](#),
[727](#), [756](#), [758](#), [766](#), [767](#), [768](#), [769](#), [771](#), [772](#),
[782](#), [784](#), [790](#), [803](#), [805](#), [808](#), [813](#), [814](#), [815](#),
[1601](#), [1631](#), [1638](#)*.
pdf_print_bp: [690](#), [692](#), [693](#), [756](#), [1601](#), [1638](#)*.
pdf_print_char: [686](#), [726](#).
pdf_print_fw_int: [702](#), [813](#).
pdf_print_info: [749](#), [794](#), [807](#).
pdf_print_int: [683](#), [686](#), [690](#), [693](#), [698](#), [699](#), [702](#),
[766](#), [767](#), [769](#), [771](#), [784](#), [790](#), [795](#), [797](#), [803](#),
[805](#), [808](#), [814](#), [1601](#), [1631](#), [1638](#)*.
pdf_print_int_ln: [683](#), [686](#), [699](#), [813](#), [815](#).
pdf_print_ln: [685](#), [686](#), [692](#), [693](#), [698](#), [699](#), [727](#),
[756](#), [758](#), [766](#), [767](#), [768](#), [769](#), [771](#), [772](#), [781](#), [782](#),
[784](#), [786](#), [788](#), [790](#), [795](#), [797](#), [803](#), [805](#), [806](#), [807](#),
[808](#), [813](#), [814](#), [815](#), [1601](#), [1631](#), [1638](#)*.
pdf_print_mag_bp: [690](#), [693](#), [769](#), [784](#), [785](#).
pdf_print_nl: [683](#), [686](#), [693](#), [702](#), [814](#).
pdf_print_octal: [686](#).
pdf_print_real: [690](#), [692](#), [693](#), [758](#), [1638](#)*.
pdf_print_rect_spec: [784](#), [785](#), [786](#).
pdf_print_rename_prefix: [693](#), [766](#), [767](#), [1638](#)*.
pdf_print_str: [702](#), [805](#), [1631](#).
pdf_print_str_ln: [702](#), [1564](#).
pdf_print_toks: [727](#).
pdf_print_toks_ln: [727](#), [756](#), [763](#), [769](#), [772](#), [778](#),
[781](#), [782](#), [789](#), [803](#), [804](#), [806](#), [814](#), [815](#), [1631](#).
pdf_print_two: [686](#).
pdf_protrude_chars: [254](#)*, [1027](#), [1057](#), [1063](#).
\pdfprotrudechars primitive: [256](#)*.
pdf_protrude_chars_code: [254](#)*, [255](#)*, [256](#)*.
pdf_ptr: [680](#), [681](#), [685](#), [686](#), [698](#), [699](#), [772](#).
pdf_px_dimen: [265](#), [481](#), [672](#).
\pdfpxdimen primitive: [266](#).
pdf_px_dimen_code: [265](#), [266](#).
pdf_quick_out: [680](#), [686](#), [699](#), [702](#).
pdf_read_dummy_font: [693](#).
pdf_rectangle: [693](#), [781](#), [782](#).
\pdfrefobj primitive: [1525](#)*.
pdf_refobj_node: [1525](#)*, [1527](#), [1529](#)*, [1547](#), [1604](#)*,
[1605](#), [1606](#), [1640](#), [1646](#).
pdf_refobj_node_size: [695](#), [1547](#), [1605](#), [1606](#).
\pdfrefxform primitive: [1525](#)*.
pdf_refxform_node: [1005](#), [1525](#)*, [1527](#), [1529](#)*, [1550](#),
[1604](#)*, [1605](#), [1606](#), [1607](#), [1608](#), [1609](#), [1610](#), [1612](#),
[1613](#), [1638](#)*, [1640](#), [1646](#).
pdf_refxform_node_size: [695](#), [1550](#), [1605](#), [1606](#).
\pdfrefximage primitive: [1525](#)*.
pdf_refximage_node: [1005](#), [1525](#)*, [1527](#), [1529](#)*, [1555](#),
[1604](#)*, [1605](#), [1606](#), [1607](#), [1608](#), [1609](#), [1610](#), [1612](#),
[1613](#), [1638](#)*, [1640](#), [1646](#).
pdf_refximage_node_size: [695](#), [1555](#), [1605](#), [1606](#).
pdf_rename_prefix: [693](#), [708](#), [709](#), [792](#).
\pdfrestore primitive: [1525](#)*.
pdf_restore_node: [1525](#)*, [1527](#), [1529](#)*, [1543](#), [1604](#)*,
[1605](#), [1606](#), [1640](#), [1646](#).
pdf_restore_node_size: [695](#), [1543](#), [1605](#), [1606](#).
pdf_retval: [450](#), [1545](#), [1584](#).
\pdfretval primitive: [442](#).
pdf_retval_code: [442](#), [443](#), [450](#).
pdf_right: [695](#), [781](#), [782](#), [785](#), [1631](#), [1636](#).
pdf_room: [680](#), [686](#), [699](#), [702](#).
\pdfrunninglinkoff primitive: [1525](#)*.
pdf_running_link_off_node: [1525](#)*, [1527](#), [1529](#)*, [1598](#),
[1604](#)*, [1605](#), [1606](#), [1640](#), [1646](#).
\pdfrunninglinkon primitive: [1525](#)*.
pdf_running_link_on_node: [1525](#)*, [1527](#), [1529](#)*, [1599](#),
[1604](#)*, [1605](#), [1606](#), [1640](#), [1646](#).
\pdfsave primitive: [1525](#)*.
pdf_save_node: [1525](#)*, [1527](#), [1529](#)*, [1542](#), [1604](#)*, [1605](#),
[1606](#), [1640](#), [1646](#).
pdf_save_node_size: [695](#), [1542](#), [1605](#), [1606](#).
pdf_save_offset: [680](#), [685](#), [813](#), [815](#).
\pdfsavepos primitive: [1525](#)*.
pdf_save_pos_node: [1525](#)*, [1527](#), [1529](#)*, [1577](#), [1604](#)*,
[1605](#), [1606](#), [1621](#)*, [1640](#), [1646](#).
pdf_scan_ext_toks: [496](#).
pdf_seek_write_length: [681](#), [685](#), [696](#).
pdf_set_font: [693](#).
pdf_set_origin: [692](#), [693](#).
pdf_set_origin_temp: [692](#), [693](#).

- pdf_set_rule*: [693](#), [726](#), [734](#), [743](#).
pdf_set_textmatrix: [692](#), [693](#).
`\pdfsetmatrix` primitive: [1525](#)*
pdf_setmatrix_data: [695](#), [727](#), [1541](#), [1604](#)*, [1605](#), [1606](#).
pdf_setmatrix_node: [1525](#)*, [1527](#), [1529](#)*, [1541](#), [1604](#)*, [1605](#), [1606](#), [1640](#), [1646](#).
pdf_setmatrix_node_size: [695](#), [1541](#), [1605](#), [1606](#).
`\pdfshellescape` primitive: [442](#).
pdf_shell_escape_code: [442](#), [443](#), [450](#).
pdf_ship_out: [727](#), [749](#), [750](#)*, [775](#), [791](#), [1556](#), [1624](#), [1641](#).
`\pdfsnaprefpoint` primitive: [1525](#)*
pdf_snap_ref_point_node: [1525](#)*, [1527](#), [1529](#)*, [1573](#), [1604](#)*, [1605](#), [1606](#), [1640](#), [1646](#).
pdf_snapx_refpos: [1571](#), [1643](#).
`\pdfsnappy` primitive: [1525](#)*
`\pdfsnappycomp` primitive: [1525](#)*
pdf_snappy_comp_node: [1145](#), [1177](#), [1525](#)*, [1527](#), [1529](#)*, [1576](#), [1604](#)*, [1605](#), [1606](#), [1638](#)*, [1640](#), [1646](#).
pdf_snappy_node: [1145](#), [1177](#), [1525](#)*, [1527](#), [1529](#)*, [1575](#), [1604](#)*, [1605](#), [1606](#), [1638](#)*, [1640](#), [1646](#).
pdf_snappy_refpos: [1571](#), [1638](#)*, [1643](#).
`\pdfspacefont` primitive: [1525](#)*
pdf_space_font_code: [1525](#)*, [1527](#), [1529](#)*
pdf_space_font_name: [693](#), [1600](#), [1629](#), [1630](#).
pdf_special: [727](#), [1640](#), [1646](#).
`\pdfstartlink` primitive: [1525](#)*
pdf_start_link_node: [783](#), [1525](#)*, [1527](#), [1529](#)*, [1557](#), [1561](#), [1604](#)*, [1605](#), [1606](#), [1632](#), [1633](#), [1636](#), [1640](#), [1646](#).
`\pdfstartthread` primitive: [1525](#)*
pdf_start_thread_node: [786](#), [1525](#)*, [1527](#), [1529](#)*, [1557](#), [1569](#), [1604](#)*, [1605](#), [1606](#), [1638](#)*, [1640](#), [1646](#).
pdf_str_entry: [702](#), [1631](#).
pdf_str_entry_ln: [702](#), [807](#).
`\pdfstrcmp` primitive: [494](#).
pdf_strcmp_code: [494](#), [495](#), [497](#), [498](#).
pdf_stream_length: [685](#), [696](#).
pdf_stream_length_offset: [685](#), [696](#).
pdf_suppress_ptex_info: [254](#)*, [673](#)*, [807](#).
`\pdfsuppressptexinfo` primitive: [256](#)*
pdf_suppress_ptex_info_code: [254](#)*, [255](#)*, [256](#)*
pdf_suppress_warning_dup_dest: [254](#)*, [1565](#).
`\pdfsuppresswarningdupdest` primitive: [256](#)*
pdf_suppress_warning_dup_dest_code: [254](#)*, [255](#)*, [256](#)*
pdf_suppress_warning_dup_map: [254](#)*, [673](#)*
`\pdfsuppresswarningdupmap` primitive: [256](#)*
pdf_suppress_warning_dup_map_code: [254](#)*, [255](#)*, [256](#)*
pdf_suppress_warning_page_group: [254](#)*, [673](#)*
`\pdfsuppresswarningpagegroup` primitive: [256](#)*
pdf_suppress_warning_page_group_code: [254](#)*, [255](#)*, [256](#)*
pdf_text_procset: [701](#), [750](#)*, [753](#), [766](#), [768](#), [776](#), [777](#).
`\pdfthread` primitive: [1525](#)*
pdf_thread_attr: [695](#), [1557](#), [1604](#)*, [1605](#), [1606](#), [1638](#)*
pdf_thread_dp: [739](#), [1629](#), [1638](#)*
pdf_thread_ht: [1629](#), [1638](#)*
pdf_thread_id: [695](#), [1567](#), [1604](#)*, [1605](#), [1606](#), [1638](#)*
pdf_thread_level: [739](#), [1629](#), [1638](#)*
pdf_thread_margin: [265](#), [1638](#)*
`\pdfthreadmargin` primitive: [266](#).
pdf_thread_margin_code: [265](#), [266](#).
pdf_thread_named_id: [695](#), [1567](#), [1604](#)*, [1605](#), [1606](#), [1638](#)*
pdf_thread_node: [1525](#)*, [1527](#), [1529](#)*, [1557](#), [1568](#), [1604](#)*, [1605](#), [1606](#), [1640](#), [1646](#).
pdf_thread_node_size: [695](#), [1568](#), [1569](#), [1605](#), [1606](#), [1638](#)*
pdf_thread_wd: [1629](#), [1638](#)*
pdf_tj_start_h: [691](#), [692](#), [693](#).
pdf_toks: [248](#)*
pdf_top: [695](#), [781](#), [782](#), [784](#), [785](#), [1631](#), [1636](#), [1638](#)*
pdf_tracing_fonts: [192](#)*, [254](#)*
`\pdftracingfonts` primitive: [256](#)*
pdf_tracing_fonts_code: [254](#)*, [255](#)*, [256](#)*
`\pdftrailer` primitive: [1525](#)*
pdf_trailer_code: [1525](#)*, [1527](#), [1529](#)*
`\pdftrailerid` primitive: [1525](#)*
pdf_trailer_id_code: [1525](#)*, [1527](#), [1529](#)*
pdf_trailer_id_toks: [814](#), [815](#), [1583](#), [1629](#), [1630](#).
pdf_trailer_toks: [814](#), [815](#), [1582](#), [1629](#), [1630](#).
`\pdfunescapehex` primitive: [494](#).
pdf_unescape_hex_code: [494](#), [495](#), [497](#).
pdf_unique_resname: [254](#)*, [792](#).
`\pdfuniquerename` primitive: [256](#)*
pdf_unique_resname_code: [254](#)*, [255](#)*, [256](#)*
pdf_use_font: [692](#), [693](#).
pdf_v: [691](#), [692](#), [693](#).
pdf_v_origin: [265](#), [672](#), [755](#).
`\pdfvorigin` primitive: [266](#).
pdf_v_origin_code: [265](#), [266](#).
pdf_version_written: [680](#), [681](#), [683](#).
pdf_vlist_node: [738](#)*
pdf_vlist_out: [727](#), [728](#), [733](#)*, [737](#), [738](#)*, [742](#)*, [746](#), [751](#), [1556](#).
pdf_warning: [683](#), [686](#), [692](#), [705](#), [706](#), [794](#), [795](#), [797](#), [799](#), [801](#), [1538](#), [1545](#), [1553](#), [1565](#), [1601](#), [1636](#).
pdf_width: [695](#), [730](#), [1550](#), [1555](#), [1557](#), [1566](#), [1602](#), [1604](#)*, [1605](#), [1607](#), [1608](#), [1609](#), [1610](#), [1631](#), [1636](#), [1637](#), [1638](#)*, [1647](#), [1648](#).
pdf_write_image: [778](#), [779](#), [1624](#).

- pdf_write_obj*: [772](#), [773](#), [1624](#).
pdf_x: [691](#), [693](#), [784](#), [785](#), [1638](#)*
`\pdfxform` primitive: [1525](#)*
pdf_xform_code: [1525](#)*, [1527](#), [1529](#)*, [1624](#).
pdf_xform_count: [1505](#), [1506](#), [1549](#), [1629](#), [1630](#).
pdf_xform_depth: [752](#), [756](#), [1629](#), [1642](#).
pdf_xform_height: [752](#), [756](#), [1629](#), [1642](#).
pdf_xform_list: [750](#)*, [753](#), [764](#), [767](#), [775](#), [776](#),
[777](#), [1629](#), [1638](#)*
`\pdfxformname` primitive: [494](#).
pdf_xform_name_code: [494](#), [495](#), [497](#), [498](#).
pdf_xform_objnum: [695](#), [1550](#), [1604](#)*, [1638](#)*
pdf_xform_width: [752](#), [756](#), [1629](#).
`\pdfximage` primitive: [1525](#)*
`\pdfximagebbox` primitive: [494](#).
pdf_ximage_bbox_code: [494](#), [495](#), [497](#), [498](#).
pdf_ximage_code: [1525](#)*, [1527](#), [1529](#)*, [1624](#).
pdf_ximage_count: [1505](#), [1506](#), [1553](#), [1629](#), [1630](#).
pdf_ximage_list: [750](#)*, [753](#), [764](#), [767](#), [775](#), [776](#),
[777](#), [779](#), [1629](#), [1638](#)*
pdf_ximage_objnum: [695](#), [1555](#), [1604](#)*, [1638](#)*
pdf_y: [691](#), [693](#), [784](#), [785](#), [1638](#)*
pdfassert: [692](#), [693](#), [705](#), [712](#), [725](#), [730](#), [801](#),
[825](#), [1636](#), [1637](#).
pdfdraftmode: [748](#).
pdfmapfile: [1591](#).
pdfmapline: [1592](#).
pdfmaplinesp: [693](#).
pdfmem_bead_size: [695](#), [1638](#)*
pdfmem_obj_size: [695](#), [1545](#).
pdfmem_outline_size: [695](#), [1564](#).
pdfmem_xform_size: [695](#), [1549](#).
pdfmem_ximage_size: [695](#), [1553](#).
pdfoutput: [747](#).
pdfpagegroupval: [761](#).
`\pdfprimitive` primitive: [287](#)*
`\pdfprimitive` primitive (internalized): [394](#).
pdfsetmatrix: [727](#).
pdfshipoutbegin: [757](#).
pdfshipoutend: [760](#).
PDFTEX: [2](#)*
pdfTeX_banner: [2](#)*
pdftex_banner: [498](#), [807](#), [811](#).
`\pdftexbanner` primitive: [494](#).
pdftex_banner_code: [494](#), [495](#), [497](#), [498](#).
pdftex_convert_codes: [494](#).
pdftex_first_dimen_code: [265](#).
pdftex_first_expand_code: [494](#).
pdftex_first_extension_code: [1525](#)*, [1621](#)*
pdftex_first_integer_code: [254](#)*
pdftex_first_loc: [248](#)*
pdftex_first_rint_code: [442](#).
pdftex_last_dimen_code: [265](#).
pdftex_last_extension_code: [1525](#)*, [1621](#)*
pdftex_last_item_codes: [442](#).
pdftex_revision: [2](#)*, [498](#), [808](#).
`\pdftexrevision` primitive: [494](#).
pdftex_revision_code: [494](#), [495](#), [497](#), [498](#).
pdftex_version: [2](#)*, [450](#), [808](#).
`\pdftexversion` primitive: [442](#).
pdftex_version_code: [442](#), [443](#), [450](#).
pdftex_version_string: [2](#)*
pen: [902](#), [937](#), [943](#), [1053](#), [1067](#).
penalties: [1280](#).
penalties: [902](#), [943](#).
penalty: [175](#), [176](#)*, [212](#), [251](#), [450](#), [992](#), [1042](#), [1067](#),
[1150](#), [1173](#), [1177](#), [1187](#), [1188](#), [1190](#), [1867](#).
`\penalty` primitive: [287](#)*
penalty_node: [175](#), [176](#)*, [201](#), [220](#)*, [224](#)*, [450](#), [674](#),
[906](#), [937](#), [943](#), [992](#), [993](#), [1005](#), [1013](#), [1032](#),
[1042](#), [1055](#), [1076](#), [1145](#), [1150](#), [1173](#), [1177](#),
[1187](#), [1188](#), [1190](#), [1285](#).
pg_field: [230](#), [231](#)*, [236](#), [237](#)*, [448](#), [1422](#).
pi: [1005](#), [1007](#), [1027](#), [1032](#), [1035](#), [1147](#), [1149](#), [1150](#),
[1151](#), [1171](#), [1177](#), [1182](#), [1183](#).
pk_dpi: [792](#), [1513](#)*, [1629](#).
pk_scale_factor: [691](#), [792](#).
plain: [547](#)*, [550](#)*, [1512](#).
Plass, Michael Frederick: [2](#)*, [989](#).
Please type...: [382](#), [556](#)*
Please use `\mathaccent`...: [1344](#).
PLtoTF: [587](#)*
plus: [488](#).
point_token: [464](#), [466](#), [474](#), [478](#).
pointer: [20](#)*, [133](#), [134](#)*, [136](#), [138](#), [141](#), [142](#), [143](#)*, [148](#),
[149](#), [154](#), [157](#), [162](#)*, [163](#), [165](#)*, [169](#), [170](#)*, [171](#)*, [172](#),
[174](#)*, [176](#)*, [183](#)*, [185](#), [190](#), [216](#), [218](#), [219](#), [220](#)*, [222](#),
[230](#), [231](#)*, [236](#), [270](#)*, [274](#)*, [275](#), [278](#), [281](#), [284](#)*, [285](#),
[297](#), [298](#), [299](#), [300](#), [301](#), [303](#), [306](#), [317](#), [319](#), [321](#),
[327](#), [328](#)*, [330](#)*, [345](#), [347](#)*, [355](#), [358](#), [363](#)*, [388](#)*, [408](#),
[414](#), [415](#), [433](#), [439](#), [476](#), [487](#), [489](#), [490](#), [491](#), [496](#),
[499](#), [508](#), [515](#), [523](#), [524](#), [552](#)*, [563](#)*, [575](#)*, [586](#)*, [609](#)*,
[619](#)*, [632](#), [634](#), [642](#), [647](#)*, [657](#)*, [666](#)*, [673](#)*, [680](#), [686](#),
[693](#), [699](#), [700](#), [705](#), [706](#), [708](#), [727](#), [729](#)*, [738](#)*, [750](#)*,
[772](#), [785](#), [791](#), [819](#), [821](#), [823](#), [829](#), [844](#), [855](#), [862](#),
[864](#), [865](#), [867](#), [868](#), [880](#), [881](#), [882](#), [885](#), [887](#), [891](#),
[892](#), [893](#), [895](#), [896](#), [898](#)*, [902](#), [910](#), [911](#), [912](#), [913](#),
[914](#), [919](#), [925](#)*, [928](#), [932](#), [938](#), [946](#), [948](#), [950](#), [963](#),
[967](#), [975](#), [976](#), [990](#), [997](#), [999](#), [1002](#), [1004](#), [1005](#),
[1006](#), [1009](#), [1038](#), [1048](#), [1053](#), [1069](#), [1077](#), [1078](#),
[1083](#), [1084](#), [1089](#), [1103](#)*, [1111](#)*, [1145](#), [1147](#), [1154](#),
[1157](#), [1159](#), [1170](#), [1171](#), [1189](#), [1207](#), [1209](#), [1221](#),
[1242](#), [1246](#), [1252](#), [1253](#), [1257](#), [1264](#), [1271](#), [1279](#),
[1283](#), [1288](#), [1291](#), [1295](#), [1297](#), [1301](#), [1316](#), [1329](#),

- 1333, 1338, 1352, 1354, 1362, 1369, 1372, 1376, 1389* 1414, 1425, 1435* 1466, 1471* 1481* 1482* 1513* 1526, 1529* 1530, 1538, 1546, 1551, 1557, 1563, 1574, 1578, 1601, 1603* 1616* 1618* 1621* 1629, 1631, 1633, 1636, 1637, 1638* 1684, 1706, 1720, 1724, 1734* 1739* 1742, 1745, 1751, 1754, 1757, 1758, 1774* 1778, 1783, 1816, 1817, 1820, 1822, 1823, 1824, 1826, 1836, 1838, 1839, 1840, 1841, 1842, 1843, 1860, 1881* 1900* 1901* 1940*
pointer_node_size: [1821](#), 1822, 1838, 1842.
Poirot, Hercule: [1461](#)*
pool_file: [50](#).
pool_free: [32](#)* 1489* 1513*
pool_name: [11](#)*
pool_pointer: [38](#)* 39* 45, 46, 59* 60, 69, 70, 286, 433, 490, 491, 496, 539* 543* 544* 545* 551* 629* 666* 686, 693, 702, 706, 749, 750* 793, 1106, 1111* 1489* 1513* 1538, 1588, 1616* 1754, 1868* 1870* 1901*
pool_ptr: [38](#)* 39* 41, 42, 43, 44, 47* 58, 70, 216, 279* 490, 491, 496, 497, 542* 543* 551* 645* 686, 727, 1399* 1488* 1489* 1513* 1515* 1520* 1616* 1618* 1689, 1755, 1881* 1901*
pool_size: [32](#)* 42, 51* 58, 216, 551* 686, 727, 1489* 1513* 1515* 1520* 1616* 1881*
pop: [611](#), [612](#), [613](#), [617](#), [628](#), [635](#), [670](#)* 719, 726, 1892*
pop_alignment: [948](#), 976.
pop_input: [344](#), [346](#)* 351.
pop_lig_stack: [1087](#)* 1088.
pop_link_level: [1636](#).
pop_LR: [1706](#), 1709, 1712, 1713, 1718, 1719, 1729, 1736, 1738, 1740*
pop_nest: [235](#), 972, 975, 988, 992, 1203* 1264, 1274, 1278* 1297, 1346* 1362, 1384, 1733.
pop_node: [1005](#).
pop_packet_state: [725](#).
positive: [107](#), [689](#).
post: [610](#), [612](#), [613](#), [617](#), [618](#), [670](#)* 712.
post_break: [163](#), 193, 213, 220* 224* 674, 823, 1005, 1016, 1034, 1058, 1060, 1093, 1217, 1297.
post_disc_break: [1053](#), 1057, 1060.
post_display_penalty: [254](#)* 1383, 1384.
\postdisplaypenalty primitive: [256](#)*
post_display_penalty_code: [254](#)* 255* 256*
post_line_break: [1052](#), [1053](#), 1706.
post_post: [612](#), [613](#), [617](#), [618](#), [670](#)*
pre: [610](#), [612](#), [613](#), 645* 714.
pre_adjust_head: [180](#), 1065, 1066, 1254, 1263* 1377, 1383.
pre_adjust_tail: [823](#), [825](#), [829](#), 830, 831, 972, 1065, 1066, 1254, 1263* 1377.
pre_break: [163](#), 193, 213, 220* 224* 674, 823, 1005, 1034, 1045, 1057, 1058, 1061, 1092, 1217, 1295, 1297.
pre_display_direction: [254](#)* 1316, 1377, 1745.
\predisplaydirection primitive: [1658](#).
pre_display_direction_code: [254](#)* 1323, 1658, 1660.
pre_display_penalty: [254](#)* 1381, 1384.
\predisplaypenalty primitive: [256](#)*
pre_display_penalty_code: [254](#)* 255* 256*
pre_display_size: [265](#), 1316, 1323, 1326, 1381, 1734*
\preplaysize primitive: [266](#).
pre_display_size_code: [265](#), 266, 1323.
pre_kern: [1295](#).
pre_t: [1376](#), 1377, 1383.
preamble: [944](#), 950.
preamble: [946](#), 947, 948, 953, 962, 977, 980.
preamble of DVI file: [645](#)*
precedes_break: [166](#), 1044, 1150, 1177.
prefix: [227](#)* 1386, 1387, 1388, 1389* 1771.
prefixed_command: 1388, [1389](#)* 1448.
prepare_mag: [310](#), 483, 645* 670* 690, 693, 752, 758, 792, 1514*
prepend_nl: [686](#).
pretolerance: [254](#)* 1004, 1039.
\pretolerance primitive: [256](#)*
pretolerance_code: [254](#)* 255* 256*
prev_active_width: [999](#).
prev_auto_breaking: [999](#).
prev_break: [997](#), 1021, 1022, 1053, 1054.
prev_char_p: [823](#), [825](#), [828](#), [999](#), 1003, 1017, 1018, 1039, 1042, 1043, 1046, 1047.
prev_depth: [230](#), [231](#)* 233* 444, 855, 951, 962, 963, 1202, 1234, 1261, 1277, 1345* 1384, 1420, 1421, 1482*
\prevdepth primitive: [442](#).
prev_dp: [1147](#), 1149, 1150, 1151, 1153, 1613.
prev_graf: [230](#), [231](#)* 233* 234, 448, 990, 992, 1040, 1053, 1065, 1067, 1269* 1327, 1378, 1420.
\prevgraf primitive: [287](#)*
prev_legal: [999](#), 1039.
prev_p: [647](#)* 648* 650* 729* 731* 732* 999, 1005, 1038, 1039, 1042, 1043, 1044, 1045, [1145](#), 1146, [1147](#), 1150, [1189](#), 1191, 1194, 1199, 1722* 1723*
prev_prev_legal: [999](#).
prev_prev_r: [1006](#), 1008, 1019, 1020, 1036.
prev_r: [1005](#), 1006, 1008, 1019, 1020, 1021, 1027, 1030, 1036.
prev_rightmost: [498](#), 1005, 1057, [1546](#).
prev_s: [1038](#), 1071, 1073.
prev_tail: [231](#)* 232, 1217.
prim: [275](#), 276* 282, 1497* 1498*
prim_base: [275](#), 281.

- prim_eq_level*: [275](#), [286](#).
prim_eq_level_field: [275](#).
prim_eq_type: [275](#), [286](#), [394](#), [395](#), [527*](#), [1223](#).
prim_eq_type_field: [275](#).
prim_eqtb: [286](#).
prim_eqtb_base: [240*](#), [275](#), [284*](#), [285](#), [395](#), [1223](#).
prim_equiv: [275](#), [286](#), [394](#), [395](#), [527*](#), [1223](#).
prim_equiv_field: [275](#).
prim_is_full: [275](#), [282](#).
prim_lookup: [281](#), [286](#), [394](#), [395](#), [527*](#), [1223](#).
prim_next: [275](#), [276*](#), [281](#), [282](#).
prim_prime: [275](#), [281](#), [283](#).
prim_size: [240*](#), [275](#), [276*](#), [277*](#), [282](#), [283](#), [1497*](#), [1498*](#).
prim_text: [275](#), [276*](#), [281](#), [282](#), [284*](#), [285](#).
prim_used: [275](#), [277*](#), [282](#).
prim_val: [286](#).
primitive: [244](#), [248*](#), [256*](#), [266](#), [286](#), [287*](#), [288*](#), [320](#),
[356](#), [402](#), [410](#), [437](#), [442](#), [494](#), [513](#), [517](#), [579](#),
[956](#), [1160](#), [1230](#), [1236](#), [1249](#), [1266](#), [1285](#), [1292](#),
[1319](#), [1334](#), [1347](#), [1356](#), [1366](#), [1386](#), [1397*](#),
[1400*](#), [1408*](#), [1428](#), [1432](#), [1440](#), [1450](#), [1455](#), [1464](#),
[1469](#), [1512](#), [1513*](#), [1525*](#), [1650](#), [1658](#), [1664](#), [1667](#),
[1670](#), [1673](#), [1676](#), [1685](#), [1687](#), [1690](#), [1693](#), [1698](#),
[1702](#), [1748](#), [1760](#), [1763](#), [1771](#), [1779](#), [1802](#), [1806](#),
[1810](#), [1862](#), [1865](#), [1909*](#).
primitive_size: [275](#).
print: [54*](#), [59*](#), [60](#), [62*](#), [63](#), [68](#), [70](#), [71*](#), [73*](#), [85](#), [86](#), [89](#),
[91](#), [94*](#), [95*](#), [121](#), [192*](#), [193](#), [195](#), [196](#), [200](#), [201](#),
[202](#), [203](#), [204*](#), [205](#), [206](#), [208](#), [209](#), [210](#), [211](#), [213](#),
[215](#), [229*](#), [236](#), [237*](#), [243](#), [251](#), [252](#), [255*](#), [265](#), [269](#),
[284*](#), [285](#), [306](#), [310](#), [316](#), [320](#), [321](#), [339](#), [345](#), [358](#),
[360*](#), [361*](#), [399](#), [421](#), [422](#), [424](#), [426*](#), [454](#), [480](#), [482](#),
[485](#), [491](#), [498](#), [528](#), [535](#), [544*](#), [556*](#), [560*](#), [562*](#),
[587*](#), [593](#), [606](#), [608*](#), [645*](#), [666*](#), [667](#), [670*](#), [674](#),
[686](#), [693](#), [705](#), [706](#), [712](#), [714](#), [717](#), [727](#), [750*](#),
[772](#), [794](#), [795](#), [797](#), [799](#), [801](#), [836](#), [839](#), [842](#),
[850](#), [851](#), [853](#), [868](#), [870](#), [873](#), [899](#), [952](#), [1005](#),
[1022](#), [1032](#), [1113](#), [1145](#), [1155](#), [1162](#), [1163](#), [1164](#),
[1177](#), [1183](#), [1188](#), [1192](#), [1201](#), [1242](#), [1273](#), [1310](#),
[1344](#), [1391](#), [1399*](#), [1402*](#), [1410*](#), [1415](#), [1435*](#), [1437](#),
[1439](#), [1458*](#), [1461*](#), [1474](#), [1475*](#), [1477](#), [1488*](#), [1490*](#),
[1497*](#), [1499*](#), [1501*](#), [1503*](#), [1505](#), [1509](#), [1515*](#), [1516*](#),
[1519*](#), [1520*](#), [1527](#), [1565](#), [1601](#), [1602](#), [1604*](#), [1618*](#),
[1623*](#), [1662](#), [1663](#), [1680](#), [1681](#), [1682](#), [1692*](#), [1705](#),
[1714](#), [1756*](#), [1766](#), [1775](#), [1777](#), [1778](#), [1824](#), [1853](#),
[1873*](#), [1885*](#), [1890*](#), [1891*](#), [1902*](#).
print_ASCII: [68](#), [192*](#), [194*](#), [320](#), [608*](#), [674](#), [867](#),
[899](#), [1402*](#), [1885*](#), [1890*](#), [1891*](#).
print_buffer: [71*](#), [340*](#), [385*](#), [1902*](#).
print_c_string: [556*](#).
print_char: [58](#), [59*](#), [60](#), [64](#), [65](#), [66](#), [67](#), [69](#), [70](#), [82*](#),
[91](#), [94*](#), [95*](#), [103](#), [132](#), [189](#), [190](#), [192*](#), [193](#), [194*](#),
[195](#), [196](#), [202](#), [204*](#), [205](#), [206](#), [207](#), [208](#), [209](#), [210](#),
[211](#), [214](#), [236](#), [241](#), [247](#), [251](#), [252](#), [253](#), [260](#), [269](#),
[270*](#), [273](#), [284*](#), [288*](#), [306](#), [307](#), [316](#), [318](#), [321](#), [328*](#),
[335](#), [339](#), [384](#), [411](#), [427*](#), [498](#), [535](#), [544*](#), [562*](#), [563*](#),
[587*](#), [608*](#), [645*](#), [666*](#), [667](#), [674](#), [750*](#), [794](#), [867](#), [899](#),
[1022](#), [1032](#), [1110](#), [1183](#), [1188](#), [1243](#), [1247](#), [1390](#),
[1391](#), [1402*](#), [1458*](#), [1473*](#), [1474](#), [1475*](#), [1490*](#), [1501*](#),
[1509](#), [1514*](#), [1516*](#), [1520*](#), [1521](#), [1602](#), [1603*](#), [1604*](#),
[1618*](#), [1662](#), [1663](#), [1680](#), [1681](#), [1682](#), [1731](#), [1756*](#),
[1766](#), [1824](#), [1885*](#), [1890*](#), [1891*](#), [1902*](#).
print_cmd_chr: [241](#), [251](#), [288*](#), [318](#), [320](#), [321](#), [345](#),
[358](#), [444](#), [454](#), [529](#), [536](#), [1227*](#), [1244](#), [1306](#), [1390](#),
[1391](#), [1415](#), [1516*](#), [1520*](#), [1657](#), [1680](#), [1682](#), [1692*](#),
[1766](#), [1770](#), [1777](#), [1778](#), [1824](#).
print_creation_date: [809](#).
print_cs: [284*](#), [315](#), [336](#), [427*](#), [1902*](#).
print_csnames: [1498*](#), [1871*](#).
print_current_string: [70](#), [200](#), [868](#).
print_delimiter: [867](#), [872](#), [873](#).
print_err: [72](#), [73*](#), [93*](#), [94*](#), [95*](#), [98](#), [121](#), [310](#), [358](#),
[360*](#), [368](#), [396](#), [399](#), [421](#), [422](#), [424](#), [429](#), [434](#), [441](#),
[444](#), [454](#), [459](#), [460](#), [461](#), [462](#), [463](#), [468](#), [471](#), [472](#),
[480](#), [482](#), [485](#), [486](#), [497](#), [501](#), [502](#), [505](#), [512](#),
[526](#), [529](#), [536](#), [556*](#), [587*](#), [604*](#), [606](#), [608*](#), [669](#),
[683](#), [686](#), [899](#), [952](#), [959](#), [960](#), [968](#), [1002](#), [1113](#),
[1114](#), [1137*](#), [1138](#), [1139](#), [1140*](#), [1153](#), [1155](#), [1170](#),
[1181](#), [1186](#), [1192](#), [1201](#), [1204](#), [1205](#), [1225](#), [1227*](#),
[1242](#), [1244](#), [1246](#), [1247](#), [1256](#), [1260](#), [1262](#), [1273](#),
[1277](#), [1288](#), [1298](#), [1299](#), [1305](#), [1306](#), [1307](#), [1310](#),
[1313*](#), [1337](#), [1339](#), [1344](#), [1355](#), [1361](#), [1370](#), [1373](#),
[1375](#), [1385](#), [1390](#), [1391](#), [1393*](#), [1399*](#), [1403](#), [1410*](#),
[1414](#), [1415](#), [1419](#), [1421](#), [1422](#), [1430*](#), [1436](#), [1437](#),
[1461*](#), [1477](#), [1483](#), [1514*](#), [1540](#), [1620](#), [1657](#), [1697](#),
[1766](#), [1770](#), [1783](#), [1785](#), [1812](#), [1874*](#).
print_esc: [63](#), [86](#), [192*](#), [194*](#), [201](#), [202](#), [205](#), [206](#),
[207](#), [208](#), [209](#), [210](#), [212](#), [213](#), [214](#), [215](#), [243](#), [245](#),
[247](#), [249](#), [251](#), [252](#), [253](#), [255*](#), [257](#), [260](#), [265](#), [267](#),
[269](#), [284*](#), [285](#), [288*](#), [314](#), [315](#), [316](#), [345](#), [357](#), [399](#),
[403](#), [411](#), [443](#), [454](#), [495](#), [512](#), [514](#), [518](#), [526](#),
[606](#), [867](#), [870](#), [871](#), [872](#), [873](#), [875](#), [952](#), [957](#),
[968](#), [1032](#), [1113](#), [1137*](#), [1138](#), [1155](#), [1161](#), [1163](#),
[1186](#), [1192](#), [1205](#), [1231](#), [1237](#), [1243](#), [1247](#), [1250](#),
[1267](#), [1273](#), [1277](#), [1286](#), [1293](#), [1298](#), [1307](#), [1310](#),
[1313*](#), [1321](#), [1335](#), [1344](#), [1357](#), [1367](#), [1370](#), [1387](#),
[1391](#), [1398*](#), [1399*](#), [1401*](#), [1409*](#), [1419](#), [1422](#), [1429](#),
[1433](#), [1441](#), [1451](#), [1456](#), [1465](#), [1470](#), [1474](#), [1501*](#),
[1516*](#), [1527](#), [1603*](#), [1604*](#), [1651](#), [1659](#), [1660](#), [1665](#),
[1668](#), [1671](#), [1674](#), [1677](#), [1680](#), [1682](#), [1686](#), [1688](#),
[1691](#), [1692*](#), [1694](#), [1699](#), [1701](#), [1703](#), [1749](#), [1761](#),
[1764](#), [1765](#), [1766](#), [1772](#), [1778](#), [1780](#), [1803](#), [1807](#),
[1824](#), [1833](#), [1834](#), [1863](#), [1866](#), [1910*](#).
print_fam_and_char: [867](#), [868](#), [872](#).

- print_file_line*: [73](#)*, [1873](#)*
print_file_name: [544](#)*, [556](#)*, [587](#)*, [670](#)*, [794](#), [1501](#)*,
[1514](#)*, [1604](#)*, [1623](#)*
print_font_and_char: [194](#)*, [201](#), [211](#).
print_font_identifier: [192](#)*, [194](#)*, [674](#), [801](#).
print_glue: [195](#), [196](#), [203](#), [204](#)*
print_group: [1662](#), [1663](#), [1680](#), [1775](#), [1778](#).
print_hex: [67](#), [608](#)*, [867](#), [1401](#)*
print_ID: [814](#), [815](#).
print_ID_alt: [814](#), [815](#).
print_if_line: [321](#), [1692](#)*, [1777](#), [1778](#).
print_in_mode: [229](#)*, [1227](#)*
print_int: [65](#), [91](#), [94](#)*, [103](#), [132](#), [186](#), [187](#), [188](#), [189](#),
[190](#), [192](#)*, [203](#), [206](#), [212](#), [213](#), [214](#), [236](#), [237](#)*, [245](#),
[247](#), [249](#), [251](#), [252](#), [253](#), [257](#), [260](#), [267](#), [269](#), [273](#),
[307](#), [310](#), [321](#), [335](#), [358](#), [426](#)*, [491](#), [498](#), [535](#), [562](#)*,
[587](#)*, [606](#), [645](#)*, [666](#)*, [667](#), [670](#)*, [705](#), [706](#), [727](#), [750](#)*,
[794](#), [795](#), [797](#), [799](#), [836](#), [839](#), [843](#), [850](#), [851](#), [854](#),
[867](#), [899](#), [1022](#), [1032](#), [1110](#), [1163](#), [1183](#), [1186](#),
[1188](#), [1201](#), [1205](#), [1277](#), [1410](#)*, [1475](#)*, [1488](#)*, [1490](#)*,
[1497](#)*, [1499](#)*, [1503](#)*, [1505](#), [1509](#), [1516](#)*, [1520](#)*, [1540](#),
[1565](#), [1601](#), [1603](#)*, [1604](#)*, [1623](#)*, [1638](#)*, [1662](#), [1680](#),
[1682](#), [1692](#)*, [1714](#), [1823](#), [1824](#), [1873](#)*
print_length_param: [265](#), [267](#), [269](#).
print_ln: [57](#), [58](#), [59](#)*, [61](#)*, [62](#)*, [71](#)*, [86](#), [89](#), [90](#), [132](#),
[200](#), [216](#), [236](#), [254](#)*, [263](#), [318](#), [328](#)*, [336](#), [339](#),
[352](#), [382](#), [385](#)*, [427](#)*, [510](#)*, [556](#)*, [560](#)*, [563](#)*, [666](#)*,
[667](#), [683](#), [686](#), [693](#), [750](#)*, [795](#), [797](#), [799](#), [801](#),
[836](#), [839](#), [842](#), [843](#), [850](#), [851](#), [853](#), [854](#), [868](#),
[1005](#), [1027](#), [1057](#), [1145](#), [1163](#), [1443](#)*, [1458](#)*, [1471](#)*,
[1488](#)*, [1490](#)*, [1497](#)*, [1499](#)*, [1503](#)*, [1505](#), [1514](#)*, [1521](#),
[1565](#), [1601](#), [1618](#)*, [1623](#)*, [1680](#), [1692](#)*, [1714](#), [1731](#),
[1756](#)*, [1775](#), [1777](#), [1778](#).
print_locs: [185](#).
print_mark: [194](#)*, [214](#), [1565](#), [1604](#)*
print_meaning: [318](#), [498](#), [1473](#)*
print_mod_date: [810](#).
print_mode: [229](#)*, [236](#), [321](#).
print_nl: [62](#)*, [73](#)*, [82](#)*, [85](#), [90](#), [186](#), [187](#), [188](#), [189](#),
[190](#), [236](#), [237](#)*, [263](#), [273](#), [307](#), [310](#), [321](#), [328](#)*, [333](#),
[335](#), [336](#), [345](#), [382](#), [426](#)*, [556](#)*, [560](#)*, [608](#)*, [666](#)*, [667](#),
[669](#), [670](#)*, [693](#), [712](#), [714](#), [717](#), [727](#), [750](#)*, [772](#), [794](#),
[836](#), [842](#), [843](#), [850](#), [853](#), [854](#), [1022](#), [1032](#), [1033](#),
[1039](#), [1110](#), [1163](#), [1164](#), [1169](#), [1183](#), [1188](#), [1299](#),
[1402](#)*, [1473](#)*, [1475](#)*, [1476](#)*, [1501](#)*, [1503](#)*, [1509](#), [1514](#)*,
[1516](#)*, [1519](#)*, [1618](#)*, [1623](#)*, [1638](#)*, [1680](#), [1692](#)*, [1714](#),
[1775](#), [1777](#), [1778](#), [1873](#)*, [1885](#)*, [1890](#)*, [1891](#)*
print_param: [255](#)*, [257](#), [260](#).
print_plus: [1162](#).
print_plus_end: [1162](#).
print_quoted: [544](#)*
print_roman_int: [69](#), [498](#).
print_rule_dimen: [194](#)*, [205](#), [1602](#), [1604](#)*
print_sa_num: [1823](#), [1824](#), [1833](#), [1834](#).
print_scaled: [103](#), [121](#), [132](#), [192](#)*, [194](#)*, [195](#), [196](#),
[201](#), [202](#), [206](#), [209](#), [210](#), [237](#)*, [269](#), [491](#), [498](#),
[587](#)*, [842](#), [853](#), [873](#), [1162](#), [1163](#), [1164](#), [1183](#),
[1188](#), [1437](#), [1439](#), [1501](#)*, [1520](#)*, [1604](#)*, [1638](#)*,
[1681](#), [1682](#), [1824](#), [1853](#).
print_size: [875](#), [899](#), [1409](#)*
print_skip_param: [207](#), [243](#), [245](#), [247](#).
print_spec: [196](#), [206](#), [207](#), [208](#), [247](#), [491](#), [1604](#)*,
[1638](#)*, [1824](#).
print_style: [866](#), [870](#), [1348](#).
print_subsidary_data: [868](#), [872](#), [873](#).
print_the_digs: [64](#), [65](#), [67](#).
print_totals: [236](#), [1162](#), [1163](#), [1183](#).
print_two: [66](#), [562](#)*, [645](#)*
print_word: [132](#), [1520](#)*
print_write_whatsit: [1603](#)*, [1604](#)*
printed_node: [997](#), [1032](#), [1033](#), [1034](#), [1040](#).
privileged: [1229](#), [1232](#), [1308](#)*, [1318](#).
procedure: [81](#)*, [93](#)*, [94](#)*, [95](#)*
Producer: [807](#).
producer_given: [807](#).
prompt_file_name: [556](#)*, [558](#)*, [561](#), [563](#)*, [684](#),
[1509](#), [1623](#)*
prompt_file_name_help_msg: [556](#)*
prompt_input: [71](#)*, [83](#), [87](#), [382](#), [385](#)*, [510](#)*, [556](#)*
protected: [1771](#).
\protected primitive: [1771](#).
protected_token: [311](#), [415](#), [504](#), [1391](#), [1474](#), [1773](#).
prune_movements: [642](#), [647](#)*, [657](#)*
prune_page_top: [1145](#), [1154](#), [1198](#).
pseudo: [54](#)*, [57](#), [58](#), [59](#)*, [338](#).
pseudo_close: [351](#), [1758](#), [1759](#).
pseudo_files: [1751](#), [1752](#), [1755](#), [1757](#), [1758](#), [1759](#).
pseudo_input: [384](#), [1757](#).
pseudo_start: [1750](#), [1753](#), [1754](#).
pstack: [414](#), [416](#)*, [422](#), [426](#)*
pt: [479](#).
ptmp: [1053](#), [1057](#).
punct_noad: [858](#), [866](#), [872](#), [874](#), [904](#), [928](#), [937](#),
[1334](#), [1335](#).
push: [611](#), [612](#), [613](#), [617](#), [619](#)*, [628](#), [635](#), [643](#), [647](#)*,
[657](#)*, [719](#), [721](#), [726](#), [1892](#)*
push_alignment: [948](#), [950](#).
push_input: [343](#), [345](#), [347](#)*, [350](#)*
push_link_level: [1636](#).
push_LR: [1706](#), [1709](#), [1712](#), [1718](#), [1729](#), [1738](#), [1740](#)*
push_math: [1314](#), [1317](#)*, [1323](#), [1331](#), [1350](#), [1352](#),
[1369](#).
push_nest: [234](#), [950](#), [962](#), [963](#), [1202](#), [1261](#), [1269](#)*,
[1277](#), [1295](#), [1297](#), [1314](#), [1345](#)*, [1378](#).

- push_node*: [1005](#).
push_packet_state: [725](#).
put: [26](#)*, [29](#).
put_byte: [1871](#)*.
put_LR: [1706](#), [1711](#).
put_rule: [612](#), [613](#), [661](#), [719](#), [726](#).
put_sa_ptr: [1820](#), [1832](#).
put1: [612](#), [710](#), [719](#), [726](#).
put2: [612](#).
put3: [612](#).
put4: [612](#).
px: [481](#).
q: [112](#), [114](#), [122](#), [141](#), [143](#)*, [148](#), [149](#), [162](#)*, [169](#), [170](#)*,
[171](#)*, [185](#), [190](#), [220](#)*, [222](#), [236](#), [284](#)*, [297](#), [314](#), [337](#),
[358](#), [388](#)*, [415](#), [433](#), [439](#), [476](#), [487](#), [489](#), [490](#), [491](#),
[499](#), [508](#), [523](#), [524](#), [634](#), [689](#), [700](#), [727](#), [823](#), [881](#),
[882](#), [885](#), [888](#), [896](#), [902](#), [910](#), [911](#), [912](#), [913](#), [914](#),
[919](#), [925](#)*, [928](#), [932](#), [938](#), [967](#), [976](#), [1002](#), [1006](#),
[1038](#), [1053](#), [1078](#), [1083](#), [1111](#)*, [1125](#), [1130](#), [1134](#),
[1136](#), [1137](#)*, [1145](#), [1147](#), [1171](#), [1189](#), [1221](#), [1246](#),
[1257](#), [1271](#), [1283](#), [1297](#), [1301](#), [1316](#), [1362](#), [1369](#),
[1376](#), [1389](#)*, [1414](#), [1481](#)*, [1482](#)*, [1529](#)*, [1616](#)*, [1618](#)*,
[1638](#)*, [1684](#), [1724](#), [1739](#)*, [1745](#), [1754](#), [1758](#), [1783](#),
[1816](#), [1820](#), [1822](#), [1823](#), [1826](#), [1838](#), [1901](#)*, [1940](#)*.
qi: [130](#)*, [498](#), [571](#), [575](#)*, [590](#)*, [596](#)*, [600](#)*, [603](#)*, [609](#)*,
[643](#), [648](#)*, [823](#), [929](#), [1084](#), [1085](#), [1088](#), [1090](#),
[1100](#)*, [1135](#)*, [1136](#), [1158](#), [1185](#), [1186](#), [1211](#)*,
[1212](#), [1213](#)*, [1215](#), [1216](#), [1218](#), [1278](#)*, [1329](#), [1333](#),
[1338](#), [1343](#), [1488](#)*, [1504](#)*, [1672](#), [1755](#), [1770](#), [1857](#),
[1859](#), [1885](#)*, [1886](#)*, [1890](#)*.
qo: [130](#)*, [177](#), [192](#)*, [194](#)*, [203](#), [206](#), [580](#)*, [596](#)*, [603](#)*,
[609](#)*, [629](#)*, [643](#), [648](#)*, [674](#), [823](#), [867](#), [884](#)*, [898](#)*,
[899](#), [917](#), [928](#), [931](#), [1073](#), [1074](#), [1075](#), [1080](#),
[1086](#), [1100](#)*, [1122](#)*, [1158](#), [1163](#), [1185](#), [1195](#),
[1198](#), [1213](#)*, [1216](#), [1489](#)*, [1503](#)*, [1504](#)*, [1662](#), [1859](#),
[1885](#)*, [1886](#)*, [1890](#)*, [1891](#)*.
qqqq: [128](#)*, [132](#), [576](#)*, [580](#)*, [595](#), [600](#)*, [601](#), [710](#),
[823](#), [859](#), [889](#), [917](#), [928](#), [1086](#), [1216](#), [1359](#),
[1520](#)*, [1755](#), [1757](#).
quad: [573](#), [584](#), [673](#)*, [705](#), [706](#), [823](#), [1735](#).
quad_code: [573](#), [584](#).
quarterword: [128](#)*, [131](#)*, [162](#)*, [271](#)*, [286](#), [293](#)*, [298](#),
[299](#), [301](#), [303](#), [320](#), [322](#)*, [345](#), [609](#)*, [619](#)*, [857](#),
[882](#), [885](#), [887](#), [888](#), [900](#), [914](#), [925](#)*, [1053](#), [1098](#)*,
[1239](#), [1257](#), [1283](#), [1504](#)*, [1518](#)*, [1657](#), [1680](#), [1778](#),
[1816](#), [1836](#), [1838](#), [1885](#)*, [1886](#)*.
\quitvmode primitive: [1266](#).
quoted_filename: [32](#)*, [541](#)*, [542](#)*.
quotient: [1797](#), [1798](#).
qw: [586](#)*, [590](#)*, [596](#)*, [600](#)*, [603](#)*.
r: [108](#), [122](#), [141](#), [143](#)*, [149](#), [222](#), [236](#), [388](#)*, [415](#), [439](#),
[491](#), [508](#), [524](#), [727](#), [823](#), [844](#), [882](#), [896](#), [902](#),
[928](#), [967](#), [976](#), [1005](#), [1038](#), [1053](#), [1078](#), [1130](#),
[1143](#)*, [1145](#), [1147](#), [1171](#), [1189](#), [1257](#), [1283](#), [1301](#),
[1338](#), [1376](#), [1389](#)*, [1414](#), [1529](#)*, [1556](#), [1616](#)*, [1618](#)*,
[1734](#)*, [1745](#), [1754](#), [1757](#), [1783](#), [1800](#).
R_code: [165](#)*, [210](#), [1718](#), [1732](#).
r_count: [1089](#), [1091](#), [1095](#).
r_hyf: [1068](#), [1069](#), [1071](#), [1076](#), [1079](#), [1100](#)*,
[1610](#), [1611](#).
r_type: [902](#), [903](#), [904](#), [905](#), [936](#), [942](#), [943](#).
radical: [226](#), [287](#)*, [288](#)*, [1224](#), [1340](#).
\radical primitive: [287](#)*.
radical_noad: [859](#), [866](#), [872](#), [874](#), [909](#), [937](#), [1341](#).
radical_noad_size: [859](#), [874](#), [937](#), [1341](#).
radix: [388](#)*, [464](#), [465](#), [466](#), [470](#), [471](#), [474](#).
radix_backup: [388](#)*.
\raise primitive: [1249](#).
Ramshaw, Lyle Harold: [565](#).
random_seed: [110](#), [450](#), [1518](#)*, [1586](#).
\pdfandomseed primitive: [442](#).
random_seed_code: [442](#), [443](#), [450](#).
randoms: [110](#), [124](#), [125](#), [126](#), [127](#).
rbrace_ptr: [415](#), [425](#), [426](#)*.
rc: [823](#).
read: [1519](#)*, [1520](#)*.
\read primitive: [287](#)*.
read_buffer: [20](#)*, [365](#)*, [376](#)*, [378](#)*, [1900](#)*, [1902](#)*.
read_expand_font: [705](#), [1536](#).
read_file: [506](#), [511](#), [512](#), [1453](#)*.
read_font_info: [586](#)*, [590](#)*, [693](#), [705](#), [706](#), [712](#),
[1218](#), [1435](#)*.
read_image: [1553](#).
\readline primitive: [1760](#).
read_open: [506](#), [507](#), [509](#), [511](#), [512](#), [527](#)*, [1453](#)*.
read_sixteen: [590](#)*, [591](#), [594](#).
read_tcx_file: [24](#)*.
read_to_cs: [227](#)*, [287](#)*, [288](#)*, [1388](#), [1403](#), [1760](#).
read_toks: [325](#), [508](#), [1403](#).
ready_already: [81](#)*, [1512](#), [1513](#)*.
real: [3](#), [109](#)*, [128](#)*, [200](#), [204](#)*, [647](#)*, [657](#)*, [729](#)*, [738](#)*,
[1301](#), [1303](#), [1638](#)*, [1724](#), [1889](#)*.
real addition: [1303](#), [1892](#)*, [1893](#)*.
real division: [834](#), [840](#), [849](#), [852](#), [986](#), [987](#), [1301](#),
[1303](#), [1892](#)*, [1893](#)*.
real multiplication: [132](#), [204](#)*, [653](#), [662](#), [735](#), [744](#),
[985](#), [1303](#), [1639](#), [1892](#)*, [1893](#)*.
real_font_type: [703](#), [712](#).
rebox: [891](#), [920](#), [926](#).
reconstitute: [1082](#), [1083](#), [1090](#), [1092](#), [1093](#),
[1094](#), [1209](#).
recorder_change_filename: [560](#)*.
recursion: [76](#), [78](#), [191](#), [198](#), [216](#), [220](#)*, [221](#), [388](#)*,
[428](#), [433](#), [524](#), [553](#), [619](#)*, [646](#), [868](#), [895](#), [896](#), [901](#),

- 930, 1126, 1134, 1136, 1514*, 1624, 1683.
- ref_count*: [415](#), [416*](#), [427*](#)
- ref_link_node*: [1633](#), [1636](#), [1637](#).
- reference counts: [168](#), [218](#), [219](#), [221](#), [297](#), [313](#), [329](#), [1821](#), [1822](#).
- reflected*: [643](#), [1723*](#), [1739*](#)
- register*: [227*](#), [437](#), [438](#), [439](#), [1388](#), [1399*](#), [1402*](#), [1413](#), [1414](#), [1415](#), [1824](#), [1833](#), [1835](#).
- rejected_cur_p*: [999](#), [1039](#).
- rel_noad*: [858](#), [866](#), [872](#), [874](#), [904](#), [937](#), [943](#), [1334](#), [1335](#).
- rel_penalty*: [254*](#), [858](#), [937](#).
- `\relpenalty` primitive: [256*](#)
- rel_penalty_code*: [254*](#), [255*](#), [256*](#)
- relax*: [225](#), [287*](#), [288*](#), [376*](#), [379*](#), [380](#), [395](#), [398*](#), [430](#), [504](#), [532](#), [1223](#), [1399*](#), [1402*](#), [1785](#).
- `\relax` primitive: [287*](#)
- rem_byte*: [571](#), [580*](#), [583](#), [596*](#), [884*](#), [889](#), [916*](#), [925*](#), [929](#), [1088](#), [1218](#).
- remainder*: [104*](#), [106](#), [107](#), [483](#), [484](#), [569](#), [570](#), [571](#), [892](#), [893](#).
- remember_source_info*: [1940*](#)
- remove_item*: [226](#), [1282](#), [1285](#), [1286](#).
- remove_last_space*: [686](#), [790](#), [803](#), [805](#).
- remove_pdffile*: [1514*](#)
- rep*: [572](#).
- replace_c*: [1889*](#)
- replace_count*: [163](#), [193](#), [213](#), [674](#), [1005](#), [1016](#), [1034](#), [1045](#), [1058](#), [1059](#), [1095](#), [1217](#), [1258](#), [1298](#).
- report_illegal_case*: [1223](#), [1228](#), [1229](#), [1421](#), [1626](#).
- reset*: [26*](#)
- reset_disc_width*: [1015](#), [1045](#).
- `\pdfresettimer` primitive: [1525*](#)
- reset_timer_code*: [1525*](#), [1527](#), [1529*](#)
- restart*: [15](#), [143*](#), [144](#), [286](#), [363*](#), [368](#), [379*](#), [381](#), [382](#), [384](#), [395](#), [406](#), [439](#), [466](#), [928](#), [929](#), [958](#), [961](#), [965](#), [1329](#), [1393*](#), [1783](#), [1784](#), [1789](#), [1900*](#)
- restore_active_width*: [999](#).
- restore_cur_string*: [496](#), [497](#).
- restore_old_value*: [290](#), [298](#), [304](#).
- restore_sa*: [290](#), [304](#), [1838](#).
- restore_trace*: [299](#), [305*](#), [306](#), [1824](#).
- restore_zero*: [290](#), [298](#), [300](#).
- restrictedshell*: [61*](#), [450](#), [562*](#), [1870*](#)
- result*: [45](#), [46](#), [1877*](#), [1885*](#)
- resume_after_display*: [976](#), [1377](#), [1378](#), [1384](#).
- reswitch*: [15](#), [363*](#), [365*](#), [374](#), [388*](#), [394](#), [489](#), [647*](#), [648*](#), [729*](#), [731*](#), [823](#), [825](#), [826](#), [902](#), [904](#), [1111*](#), [1112](#), [1206](#), [1207](#), [1213*](#), [1223](#), [1316](#), [1325](#), [1329](#), [1553](#), [1723*](#), [1724](#), [1725](#), [1728](#), [1766](#).
- return**: [15](#), [16*](#)
- return_sign*: [122](#), [123](#).
- reverse*: [3](#), [1722*](#), [1723*](#), [1724](#).
- reversed*: [643](#), [1715](#), [1722*](#)
- rewrite*: [26*](#)
- rh*: [128*](#), [132](#), [136](#), [231*](#), [237*](#), [239](#), [252](#), [274*](#), [275](#), [290](#), [861](#), [1818](#).
- right*: [693](#).
- `\right` primitive: [1366](#).
- right_brace*: [225](#), [311](#), [316](#), [320](#), [369](#), [379*](#), [415](#), [468](#), [500](#), [503](#), [961](#), [1112](#), [1138](#), [1245](#), [1430*](#), [1684](#).
- right_brace_limit*: [311](#), [347*](#), [348](#), [418](#), [425](#), [426*](#), [500](#), [503](#), [1684](#).
- right_brace_token*: [311](#), [361*](#), [1243](#), [1305](#), [1404](#), [1619*](#), [1940*](#)
- right_delimiter*: [859](#), [873](#), [924](#), [1359](#), [1360](#).
- right_hyphen_min*: [254*](#), [1269*](#), [1378](#), [1625](#), [1626](#).
- `\righthyphenmin` primitive: [256*](#)
- right_hyphen_min_code*: [254*](#), [255*](#), [256*](#)
- `\rightmarginkern` primitive: [494](#).
- right_margin_kern_code*: [494](#), [495](#), [497](#), [498](#).
- right_noad*: [863](#), [866](#), [872](#), [874](#), [901](#), [903](#), [904](#), [936](#), [937](#), [938](#), [1362](#), [1366](#), [1369](#).
- right_ptr*: [632](#), [633](#), [634](#), [642](#).
- right_pw*: [823](#), [1005](#), [1057](#).
- right_side*: [173](#), [498](#), [823](#), [1057](#).
- right_skip*: [242](#), [1003](#), [1056](#), [1057](#), [1741](#), [1844](#).
- `\rightskip` primitive: [244](#).
- right_skip_code*: [242](#), [243](#), [244](#), [498](#), [1057](#), [1062](#), [1741](#), [1747](#).
- right_to_left*: [643](#), [651*](#), [654](#), [656](#), [660*](#), [661](#), [665](#), [733*](#), [736](#), [737](#), [742*](#), [743](#), [746](#), [1715](#), [1716](#), [1735](#).
- rightskip*: [1057](#).
- right1*: [612](#), [613](#), [634](#), [637](#), [643](#), [706](#), [719](#), [726](#).
- right2*: [612](#), [637](#).
- right3*: [612](#), [637](#).
- right4*: [612](#), [637](#).
- rlink*: [142](#), [143*](#), [144](#), [145](#), [147](#), [148](#), [149](#), [150](#), [163](#), [167](#), [182](#), [187](#), [948](#), [995](#), [997](#), [1490*](#), [1491*](#)
- `\romannumeral` primitive: [494](#).
- roman_numeral_code*: [494](#), [495](#), [497](#), [498](#).
- root*: [806](#), [814](#), [815](#), [1514*](#)
- round*: [3](#), [132](#), [204*](#), [653](#), [662](#), [735](#), [744](#), [985](#), [1303](#), [1639](#), [1892*](#), [1893*](#)
- round_decimals*: [102](#), [103](#), [478](#).
- round_glue*: [653](#), [1727](#).
- round_xn_over_d*: [689](#), [690](#), [693](#), [705](#), [706](#), [823](#), [1638*](#)
- rover*: [142](#), [143*](#), [144](#), [145](#), [146](#), [147](#), [148](#), [149](#), [150](#), [182](#), [187](#), [1490*](#), [1491*](#)
- rp*: [822](#), [1005](#).
- `\rpcode` primitive: [1432](#).
- rp_code_base*: [173](#), [452](#), [1431](#), [1432](#), [1433](#).

- rt_hit*: 1083, [1084](#), [1087*](#), 1088, 1210, 1212, 1217, 1218.
rule: 1551, 1553, 1557, 1566.
rule_dp: [619*](#), [650*](#), 652, 654, 659, 661, 663, [732*](#), 734, 736, 741, 743, 745.
rule_ht: [619*](#), [650*](#), 652, 654, 659, 661, 662, 663, 664, 726, [732*](#), 734, 736, 741, 743, 744, 745, [1638*](#), 1639.
rule_node: [156*](#), 157, 166, 193, 201, [220*](#), [224*](#), [650*](#), 654, 659, 663, [732*](#), 736, 741, 745, 825, 827, 845, 846, 906, 937, 981, 1017, 1018, 1042, 1046, 1047, 1145, 1150, 1177, 1252, 1265, 1299, 1325, [1551](#), [1638*](#), [1726*](#), [1734*](#).
rule_node_size: [156*](#), 157, [220*](#), [224*](#), [1734*](#), [1937*](#).
rule_save: [976](#), 980.
rule_wd: [619*](#), [650*](#), 652, 653, 654, 655, 659, 661, 663, 726, [732*](#), 734, 735, 736, 741, 743, 745, [1700](#), [1723*](#), [1726*](#), 1729, [1730*](#).
rules aligning with characters: 616.
run: 1005.
runaway: 138, [328*](#), [360*](#), 422, 512.
Runaway...: [328*](#).
runsystem: [1618*](#).
runsystem_ret: [1618*](#).
s: [45](#), [46](#), [58](#), [59*](#), [60](#), [62*](#), [63](#), [93*](#), [94*](#), [95*](#), [103](#), [108](#), [143*](#), [148](#), [165*](#), [195](#), [196](#), [281](#), [286](#), [306](#), [415](#), [433](#), [496](#), [499](#), [508](#), [543*](#), [555](#), [556*](#), [586*](#), [666*](#), [693](#), [705](#), [727](#), [772](#), [807](#), [817](#), [823](#), [844](#), [864](#), [875](#), [882](#), [896](#), [902](#), [914](#), [967](#), [976](#), [1006](#), [1038](#), [1053](#), [1078](#), [1111*](#), [1143*](#), [1145](#), [1164](#), [1189](#), [1238](#), [1239](#), [1301](#), [1316](#), [1376](#), [1414](#), [1435*](#), [1457*](#), [1530](#), [1556](#), [1588](#), [1603*](#), [1631](#), [1680](#), [1684](#), [1720](#), [1745](#), [1754](#), [1783](#), [1822](#), [1824](#), [1877*](#), [1878*](#), [1881*](#).
s_out: [690](#), [693](#).
sa_bot_mark: [1826](#), 1829, 1831.
sa_chain: 290, 304, [1836](#), 1837, 1838, 1842.
sa_def: [1840](#), 1841.
sa_def_box: 1255, [1840](#).
sa_define: 1404, 1405, 1414, [1840](#).
sa_destroy: [1839](#), 1840, 1841, 1842.
sa_dim: [1821](#), 1824.
sa_first_mark: [1826](#), 1829, 1830, 1831.
sa_index: [1816](#), 1821, 1822, 1823, 1838, 1839, 1842.
sa_int: 453, 1415, [1821](#), 1822, 1824, 1838, 1840, 1841, 1842.
sa_lev: [1821](#), 1838, 1840, 1841, 1842.
sa_level: 290, 304, [1836](#), 1837, 1838.
sa_loc: [1838](#), 1842.
sa_mark: 1154, 1189, [1516*](#), [1817](#), 1818.
sa_null: 1816, [1817](#), 1818, 1821.
sa_num: [1821](#), 1823.
sa_ptr: 441, 453, 1405, 1415, [1821](#), 1822, 1824, 1838, 1839, 1840, 1841, 1842.
sa_ref: [1821](#), 1822, 1838.
sa_restore: 304, [1842](#).
sa_root: [1490*](#), [1491*](#), [1817](#), 1819, 1820, 1822.
sa_save: [1838](#), 1840.
sa_split_bot_mark: [1826](#), 1827, 1828.
sa_split_first_mark: [1826](#), 1827, 1828.
sa_top_mark: [1826](#), 1829, 1830.
sa_type: 453, 1415, [1821](#), 1824, 1833.
sa_used: [1816](#), 1820, 1821, 1822, 1826.
sa_w_def: [1840](#), 1841.
sa_word_define: 1414, [1840](#).
save_active_width: [999](#).
save_area_delimiter: [551*](#).
save_cond_ptr: [524](#), 526, 535.
save_cs_ptr: [950](#), 953.
save_cur_cs: [433](#), 1538, [1881*](#).
save_cur_h: 725.
save_cur_string: [496](#), 497.
save_cur_v: 725.
save_cur_val: [476](#), 481.
save_def_ref: [496](#), 497, [1881*](#).
save_ext_delimiter: [551*](#).
save_font_list: [750*](#), 776, 777.
save_for_after: [302](#), 1449*.
save_h: [647*](#), [651*](#), 655, 656, [657*](#), [660*](#), 665, [729*](#), 737, 1722*, 1723*.
save_image_procset: [750*](#), 776, 777.
save_index: [290](#), 296, 298, 302, 304, 1680, 1775, 1778, 1838.
save_level: [290](#), 291, 296, 298, 302, 304, 1680, 1778, 1838.
save_link: [1006](#), 1033.
save_loc: [647*](#), [657*](#).
save_name_in_progress: [551*](#).
save_obj_list: [750*](#), 776, 777.
save_pdf_delta_h: 693.
save_pointer: [1513*](#), [1679](#), 1680, 1774*.
save_pool_ptr: [1870*](#).
save_ptr: [290](#), [293*](#), 294, 295, 296, 298, 302, 304, 305*, 307, 817, 980, 1264, 1277, 1278*, 1295, 1298, 1320, 1331, 1346*, 1350, 1352, 1364, 1372, 1483, 1680, 1775, 1778, 1838.
save_scanner_status: [388*](#), [393*](#), [394](#), [415](#), [496](#), 497, [520](#), [524](#), [527*](#), 533, 1767, [1881*](#).
save_size: [32*](#), [129*](#), [293*](#), 295, 1513*, 1515*, 1679.
save_split_top_skip: [1189](#), 1191.
save_stack: [221](#), 290, 292, [293*](#), 295, 296, 297, 298, 299, 303, 304, 305*, 307, 322*, 398*, 515, 817, 944, 1240, 1249, 1309, 1318, 1328, 1331, 1513*, 1520*, 1679.

- save_stop_at_space*: [551*](#), [1881*](#)
save_str_ptr: [1870*](#)
save_style: [896](#), [902](#), [930](#).
save_tail: [231*](#), [233*](#), [705](#), [1211*](#), [1217](#).
save_text_procset: [750*](#), [776](#), [777](#).
save_type: [290](#), [296](#), [298](#), [302](#), [304](#), [1838](#).
save_v: [647*](#), [651*](#), [656](#), [657*](#), [660*](#), [664](#), [665](#), [738*](#),
[742*](#), [746](#), [1644](#), [1645](#).
save_vbadness: [1189](#), [1194](#).
save_vf_nf: [712](#), [715](#).
save_vfuzz: [1189](#), [1194](#).
save_warning_index: [415](#), [496](#), [497](#), [552*](#)
save_xform_list: [750*](#), [776](#), [777](#).
save_ximage_list: [750*](#), [776](#), [777](#).
saved: [296](#), [817](#), [980](#), [1261](#), [1264](#), [1277](#), [1278*](#), [1295](#),
[1297](#), [1320](#), [1331](#), [1346*](#), [1350](#), [1352](#), [1364](#), [1372](#),
[1662](#), [1663](#), [1680](#), [1681](#), [1682](#).
saved_cur_area: [556*](#)
saved_cur_ext: [556*](#)
saved_cur_name: [556*](#)
saved_pdf_cur_form: [774](#), [775](#).
saved_pdf_gone: [685](#).
saving_hyph_codes: [254*](#), [1137*](#)
\savingshyphcodes primitive: [1658](#).
saving_hyph_codes_code: [254*](#), [1658](#), [1660](#).
saving_vdiscards: [254*](#), [1154](#), [1176](#), [1860](#).
\savingsvdiscards primitive: [1658](#).
saving_vdiscards_code: [254*](#), [1658](#), [1660](#).
sc: [128*](#), [131*](#), [132](#), [153*](#), [168](#), [177](#), [182](#), [231*](#), [237*](#),
[265](#), [268](#), [269](#), [439](#), [446](#), [451](#), [576*](#), [580*](#), [583](#), [584](#),
[598](#), [600*](#), [602*](#), [607](#), [695](#), [705](#), [706](#), [876](#), [877](#),
[951](#), [998](#), [999](#), [1008](#), [1019](#), [1020](#), [1024](#), [1026](#),
[1036](#), [1037](#), [1066](#), [1220](#), [1327](#), [1384](#), [1425](#), [1426](#),
[1431](#), [1518*](#), [1520*](#), [1675](#), [1821](#), [1843](#).
scale_image: [1553](#).
scaled: [101](#), [102](#), [103](#), [104*](#), [105](#), [106](#), [107](#), [108](#), [110](#),
[126](#), [128*](#), [131*](#), [165*](#), [168](#), [174*](#), [194*](#), [195](#), [473](#), [474](#),
[476](#), [479](#), [574*](#), [575*](#), [586*](#), [597](#), [611](#), [619*](#), [634](#),
[643](#), [647*](#), [657*](#), [673*](#), [687](#), [689](#), [690](#), [691](#), [692](#),
[693](#), [705](#), [706](#), [708](#), [712](#), [722](#), [725](#), [729*](#), [738*](#),
[818](#), [823](#), [844](#), [855](#), [880](#), [881](#), [882](#), [888](#), [891](#),
[892](#), [893](#), [895](#), [902](#), [911](#), [912](#), [913](#), [914](#), [919](#),
[925*](#), [932](#), [938](#), [967](#), [976](#), [999](#), [1005](#), [1006](#), [1015](#),
[1023](#), [1053](#), [1083](#), [1147](#), [1148](#), [1154](#), [1157](#), [1159](#),
[1171](#), [1189](#), [1246](#), [1264](#), [1301](#), [1316](#), [1376](#), [1435*](#),
[1502*](#), [1518*](#), [1553](#), [1629](#), [1631](#), [1636](#), [1637](#), [1638*](#),
[1720](#), [1724](#), [1745](#), [1843](#), [1845](#), [1889*](#)
scaled: [1436](#).
scaled_base: [265](#), [267](#), [269](#), [1402*](#), [1415](#).
scaled_out: [687](#), [689](#), [690](#), [692](#), [693](#).
scan_action: [1557](#), [1561](#), [1564](#), [1580](#).
scan_alt_rule: [1553](#), [1557](#), [1566](#).
scan_box: [1251](#), [1262](#), [1419](#).
scan_char_num: [440*](#), [452](#), [460](#), [1112](#), [1207](#), [1215](#),
[1301](#), [1302](#), [1329](#), [1332](#), [1402*](#), [1410*](#), [1431](#),
[1672](#), [1770](#).
scan_delimiter: [1338](#), [1341](#), [1360](#), [1361](#), [1369](#), [1370](#).
scan_dimen: [436](#), [466](#), [473](#), [474](#), [487](#), [488](#), [1239](#).
scan_eight_bit_int: [459](#), [1277](#).
scan_expr: [1781](#), [1782](#), [1783](#).
scan_fifteen_bit_int: [462](#), [1329](#), [1332](#), [1343](#), [1402*](#)
scan_file_name: [287*](#), [356](#), [552*](#), [553](#), [563*](#), [1435*](#),
[1453*](#), [1532](#), [1881*](#)
scan_file_name_braced: [552*](#), [1881*](#)
scan_font_ident: [441](#), [452](#), [497](#), [604*](#), [605](#), [705](#), [706](#),
[1412](#), [1431](#), [1588](#), [1590](#), [1594](#), [1672](#), [1770](#).
scan_four_bit_int: [461](#), [604*](#), [1412](#), [1453*](#), [1531*](#), [1874*](#)
scan_four_bit_int_or_18: [527*](#), [1874*](#)
scan_general_text: [1683](#), [1684](#), [1689](#), [1754](#).
scan_glue: [436](#), [487](#), [958](#), [1238](#), [1406](#), [1416](#),
[1574](#), [1788](#).
scan_image: [1553](#), [1554](#).
scan_int: [435](#), [436](#), [458](#), [459](#), [460](#), [461](#), [462](#), [463](#),
[464](#), [466](#), [473](#), [474](#), [487](#), [497](#), [529](#), [530](#), [535](#),
[605](#), [705](#), [706](#), [1281](#), [1399*](#), [1403](#), [1406](#), [1410*](#),
[1416](#), [1418](#), [1421](#), [1422](#), [1424](#), [1426](#), [1431](#), [1436](#),
[1531*](#), [1540](#), [1545](#), [1547](#), [1550](#), [1553](#), [1555](#), [1557](#),
[1559](#), [1564](#), [1566](#), [1567](#), [1576](#), [1586](#), [1626](#), [1675](#),
[1770](#), [1786](#), [1812](#), [1867](#), [1874*](#)
scan_keyword: [180](#), [433](#), [479](#), [480](#), [481](#), [482](#), [484](#),
[488](#), [489](#), [497](#), [705](#), [706](#), [817](#), [1260](#), [1277](#), [1403](#),
[1414](#), [1436](#), [1535*](#), [1539](#), [1540](#), [1545](#), [1549](#), [1553](#),
[1557](#), [1559](#), [1564](#), [1566](#), [1567](#), [1580](#).
scan_left_brace: [429](#), [499](#), [817](#), [961](#), [1111*](#), [1137*](#),
[1202](#), [1277](#), [1295](#), [1297](#), [1331](#), [1350](#), [1352](#), [1684](#).
scan_math: [1328](#), [1329](#), [1336](#), [1341](#), [1343](#), [1354](#).
scan_mu_glue: [1786](#), [1787](#), [1788](#), [1808](#).
scan_normal_dimen: [474](#), [489](#), [529](#), [817](#), [1251](#),
[1260](#), [1360](#), [1361](#), [1406](#), [1416](#), [1421](#), [1423](#), [1425](#),
[1426](#), [1431](#), [1437](#), [1553](#), [1770](#), [1786](#).
scan_normal_glue: [1786](#), [1787](#), [1788](#), [1804](#), [1805](#),
[1809](#).
scan_optional_equals: [431](#), [705](#), [706](#), [958](#), [1402*](#),
[1404](#), [1406](#), [1410*](#), [1412](#), [1414](#), [1419](#), [1421](#), [1422](#),
[1423](#), [1424](#), [1425](#), [1426](#), [1431](#), [1435*](#), [1453*](#), [1532](#).
scan_pdf_box_spec: [1553](#).
scan_pdf_ext_late_toks: [1538](#), [1539](#).
scan_pdf_ext_toks: [497](#), [703](#), [1538](#), [1539](#), [1540](#),
[1541](#), [1545](#), [1549](#), [1553](#), [1557](#), [1559](#), [1564](#),
[1566](#), [1567](#), [1579](#), [1580](#), [1581](#), [1582](#), [1583](#), [1588](#),
[1590](#), [1591](#), [1592](#), [1600](#).
scan_register_num: [412](#), [441](#), [446](#), [453](#), [497](#), [531](#),
[1257](#), [1260](#), [1279](#), [1288](#), [1402*](#), [1404](#), [1405](#), [1415](#),
[1419](#), [1425](#), [1475*](#), [1549](#), [1811](#), [1812](#).

- scan_rule_spec*: [489](#), [1234](#), [1262](#).
scan_something_internal: [435](#), [436](#), [439](#), [458](#), [466](#),
[475](#), [477](#), [481](#), [487](#), [491](#), [1781](#).
scan_spec: [817](#), [944](#), [950](#), [1249](#), [1261](#), [1345](#)*.
scan_special: [693](#), [695](#), [726](#), [727](#).
scan_thread_id: [1567](#), [1568](#), [1569](#).
scan_tokens: [1748](#).
\scantokens primitive: [1748](#).
scan_toks: [313](#), [490](#), [499](#), [1137](#)*, [1279](#), [1396](#), [1404](#),
[1457](#)*, [1466](#), [1533](#), [1535](#)*, [1538](#), [1619](#)*, [1683](#), [1881](#)*.
scan_twenty_seven_bit_int: [463](#), [1329](#), [1332](#), [1338](#).
scanned_result: [439](#), [440](#)*, [441](#), [444](#), [448](#), [451](#),
[452](#), [454](#).
scanned_result_end: [439](#).
scanner_status: [327](#), [328](#)*, [353](#)*, [358](#), [361](#)*, [388](#)*, [393](#)*,
[394](#), [415](#), [417](#), [496](#), [497](#), [499](#), [508](#), [520](#), [524](#), [527](#)*,
[533](#), [953](#), [965](#), [1223](#), [1684](#), [1767](#), [1881](#)*.
\scriptfont primitive: [1408](#)*.
script_mlist: [865](#), [871](#), [874](#), [907](#), [1352](#).
\scriptscriptfont primitive: [1408](#)*.
script_script_mlist: [865](#), [871](#), [874](#), [907](#), [1352](#).
script_script_size: [875](#), [932](#), [1373](#), [1408](#)*.
script_script_style: [864](#), [870](#), [907](#), [1347](#).
\scriptscriptstyle primitive: [1347](#).
script_size: [875](#), [932](#), [1373](#), [1408](#)*.
script_space: [265](#), [933](#), [934](#), [935](#).
\scriptspace primitive: [266](#).
script_space_code: [265](#), [266](#).
script_style: [864](#), [870](#), [878](#), [879](#), [907](#), [932](#), [942](#),
[1347](#).
\scriptstyle primitive: [1347](#).
scripts_allowed: [863](#), [1354](#).
scroll_mode: [71](#)*, [73](#)*, [84](#)*, [86](#), [93](#)*, [556](#)*, [1440](#),
[1441](#), [1459](#).
\scrollmode primitive: [1440](#).
search: [1877](#)*.
search_mem: [183](#)*, [190](#), [273](#), [1520](#)*.
search_string: [543](#)*, [563](#)*, [1877](#)*, [1878](#)*.
second_indent: [1023](#), [1024](#), [1025](#), [1066](#).
second_pass: [1004](#), [1039](#), [1042](#).
second_width: [1023](#), [1024](#), [1025](#), [1026](#), [1066](#).
seconds_and_micros: [1556](#), [1585](#), [1587](#).
Sedgewick, Robert: [2](#)*
see the transcript file...: [1516](#)*
seed: [125](#).
selector: [54](#)*, [55](#), [57](#), [58](#), [59](#)*, [62](#)*, [71](#)*, [75](#), [86](#), [90](#), [92](#),
[98](#), [263](#), [333](#), [334](#), [338](#), [382](#), [491](#), [496](#), [560](#)*, [561](#),
[645](#)*, [666](#)*, [686](#), [705](#), [706](#), [712](#), [727](#), [1399](#)*, [1435](#)*,
[1443](#)*, [1457](#)*, [1471](#)*, [1472](#)*, [1477](#), [1509](#), [1514](#)*, [1516](#)*,
[1616](#)*, [1618](#)*, [1623](#)*, [1689](#), [1754](#), [1881](#)*.
semi_simple_group: [291](#), [1241](#), [1243](#), [1246](#), [1247](#),
[1662](#), [1680](#).
serial: [997](#), [1021](#), [1022](#), [1032](#).
set_aux: [227](#)*, [439](#), [442](#), [443](#), [444](#), [1388](#), [1420](#).
set_box: [227](#)*, [287](#)*, [288](#)*, [1388](#), [1419](#).
\setbox primitive: [287](#)*.
set_box_allowed: [76](#), [77](#), [1419](#), [1448](#).
set_box_dimen: [227](#)*, [439](#), [442](#), [443](#), [1388](#), [1420](#).
set_box_lr: [643](#), [983](#), [984](#), [1372](#), [1380](#), [1715](#), [1722](#)*.
set_box_lr_end: [643](#).
set_break_width_to_background: [1013](#).
set_char_and_font: [705](#).
set_char_0: [612](#), [613](#), [648](#)*, [719](#), [726](#).
set_conversion: [484](#).
set_conversion_end: [484](#).
set_cur_lang: [1111](#)*, [1137](#)*, [1269](#)*, [1378](#).
set_cur_r: [1085](#), [1087](#)*, [1088](#).
set_ef_code: [705](#), [1431](#).
set_expand_params: [705](#), [712](#).
set_ff: [498](#), [693](#), [696](#), [698](#), [766](#).
set_font: [227](#)*, [439](#), [579](#), [604](#)*, [706](#), [1388](#), [1395](#),
[1435](#)*, [1439](#).
set_glue_ratio_one: [109](#)*, [840](#), [852](#), [986](#), [987](#).
set_glue_ratio_zero: [109](#)*, [154](#), [833](#), [834](#), [840](#), [848](#),
[849](#), [852](#), [986](#), [987](#).
set_height_zero: [1147](#).
set_hyph_index: [1068](#), [1111](#)*, [1611](#), [1859](#).
set_image_group_ref: [1638](#)*.
set_interaction: [227](#)*, [1388](#), [1440](#), [1441](#), [1442](#).
set_job_id: [792](#).
set_kn_ac_code: [705](#), [1431](#).
set_kn_bc_code: [705](#), [1431](#).
set_kn_bs_code: [705](#), [1431](#).
\setlanguage primitive: [1525](#)*.
set_language_code: [1525](#)*, [1527](#), [1529](#)*.
set_lc_code: [1073](#), [1074](#), [1075](#), [1114](#), [1859](#).
set_lp_code: [705](#), [1431](#).
set_math_char: [1332](#), [1333](#).
set_no_ligatures: [705](#), [706](#), [1431](#).
set_obj_fresh: [695](#), [698](#), [812](#).
set_obj_scheduled: [695](#), [1631](#), [1636](#).
set_origin: [497](#), [693](#), [695](#), [727](#), [1539](#), [1604](#)*.
set_page_dimen: [227](#)*, [439](#), [1159](#), [1160](#), [1161](#),
[1388](#), [1420](#).
set_page_int: [227](#)*, [439](#), [442](#), [443](#), [1388](#), [1420](#), [1693](#).
set_page_so_far_zero: [1164](#).
set_prev_graf: [227](#)*, [287](#)*, [288](#)*, [439](#), [1388](#), [1420](#).
set_random_seed_code: [1525](#)*, [1527](#), [1529](#)*.
\pdfsetrandomseed primitive: [1525](#)*.
set_rect_dimens: [1631](#), [1636](#), [1637](#), [1638](#)*.
set_rp_code: [705](#), [1431](#).
set_rule: [610](#), [612](#), [613](#), [652](#), [719](#), [726](#).
set_sa_box: [1822](#).
set_sh_bs_code: [705](#), [1431](#).

- set_shape*: [227*](#), [251](#), [287*](#), [288*](#), [439](#), [1388](#), [1426](#), [1865](#).
set_st_bs_code: [705](#), [1431](#).
set_tag_code: [705](#), [1431](#).
set_trick_count: [338](#), [339](#), [340*](#), [342](#).
setup_bound_var: [1513*](#).
setup_bound_var_end: [1513*](#).
setup_bound_var_end_end: [1513*](#).
setup_bound_variable: [1513*](#).
set1: [612](#), [613](#), [648*](#), [706](#), [719](#), [726](#), [1892*](#).
set2: [612](#).
set3: [612](#).
set4: [612](#).
sf_code: [248*](#), [250](#), [1211*](#).
\sfcode primitive: [1408*](#).
sf_code_base: [248*](#), [253](#), [1408*](#), [1409*](#), [1411](#).
sh: [705](#).
\shbscode primitive: [1432](#).
sh_bs_code_base: [173](#), [452](#), [1431](#), [1432](#), [1433](#).
shape_ref: [228](#), [250](#), [297](#), [1248](#), [1426](#).
shellenabledp: [61*](#), [450](#), [527*](#), [562*](#), [1618*](#), [1870*](#).
shift_amount: [153*](#), [154](#), [177](#), [202](#), [651*](#), [656](#), [660*](#), [665](#), [733*](#), [737](#), [742*](#), [746](#), [823](#), [827](#), [844](#), [846](#), [857](#), [882](#), [896](#), [913](#), [914](#), [925*](#), [926](#), [932](#), [933](#), [935](#), [975](#), [982](#), [983](#), [984](#), [1066](#), [1254](#), [1259](#), [1303](#), [1735](#), [1741](#), [1745](#), [1746](#), [1747](#).
shift_case: [1463](#), [1466](#).
shift_down: [919](#), [920](#), [921](#), [922](#), [923](#), [925*](#), [927](#), [932](#), [933](#), [935](#).
shift_up: [919](#), [920](#), [921](#), [922](#), [923](#), [925*](#), [927](#), [932](#), [934](#), [935](#).
ship_out: [619*](#), [727](#), [750*](#), [761](#), [791](#), [816](#), [983](#), [984](#), [1200](#), [1253](#), [1649*](#), [1701](#), [1706](#), [1887*](#).
\shipout primitive: [1249](#).
ship_out_flag: [1249](#), [1253](#), [1682](#).
shipping_page: [750*](#), [751](#), [752](#), [757](#), [759](#), [760](#), [763](#), [1641](#).
short_display: [191](#), [192*](#), [193](#), [211](#), [674](#), [839](#), [1033](#), [1520*](#).
short_display_n: [674](#), [823](#), [1005](#), [1027](#), [1057](#).
short_real: [109*](#), [128*](#).
shortcut: [473](#), [474](#).
shortfall: [1006](#), [1027](#), [1028](#), [1029](#), [1843](#), [1848](#), [1850](#), [1851](#).
shorthand_def: [227*](#), [1388](#), [1400*](#), [1401*](#), [1402*](#).
\show primitive: [1469](#).
show_activities: [236](#), [1471*](#).
show_box: [198](#), [200](#), [216](#), [236](#), [237*](#), [254*](#), [666*](#), [669](#), [750*](#), [839](#), [851](#), [1163](#), [1169](#), [1299](#), [1475*](#), [1520*](#).
\showbox primitive: [1469](#).
show_box_breadth: [254*](#), [1520*](#).
\showboxbreadth primitive: [256*](#).
show_box_breadth_code: [254*](#), [255*](#), [256*](#).
show_box_code: [1469](#), [1470](#), [1471*](#).
show_box_depth: [254*](#), [1520*](#).
\showboxdepth primitive: [256*](#).
show_box_depth_code: [254*](#), [255*](#), [256*](#).
show_code: [1469](#), [1471*](#).
show_context: [54*](#), [78](#), [82*](#), [88](#), [332](#), [333](#), [340*](#), [556*](#), [561](#), [563*](#), [1565](#), [1775](#), [1777](#), [1778](#).
show_cur_cmd_chr: [321](#), [391](#), [520](#), [524](#), [536](#), [1208](#), [1389*](#).
show_eqtb: [270*](#), [306](#), [1824](#).
show_groups: [1676](#), [1677](#), [1678*](#).
\showgroups primitive: [1676](#).
show_ifs: [1690](#), [1691](#), [1692*](#).
\showifs primitive: [1690](#).
show_info: [868](#), [869](#).
show_lists_code: [1469](#), [1470](#), [1471*](#).
\showlists primitive: [1469](#).
show_node_list: [191](#), [194*](#), [198](#), [199](#), [200](#), [213](#), [216](#), [251](#), [866](#), [868](#), [869](#), [871](#), [1005](#), [1145](#), [1520*](#), [1824](#).
show_sa: [1824](#), [1840](#), [1841](#), [1842](#).
show_save_groups: [1516*](#), [1678*](#), [1680](#).
show_stream: [254*](#), [258*](#), [1472*](#).
\showstream primitive: [256*](#).
show_stream_code: [254*](#), [255*](#), [256*](#).
\showthe primitive: [1469](#).
show_the_code: [1469](#), [1470](#).
show_token_list: [194*](#), [241](#), [251](#), [286](#), [314](#), [317](#), [328*](#), [341](#), [342](#), [426*](#), [686](#), [727](#), [1520*](#), [1616*](#), [1824](#), [1881*](#).
show_tokens: [1685](#), [1686](#), [1687](#).
\showtokens primitive: [1685](#).
show_whatever: [1468](#), [1471*](#).
shown_mode: [231*](#), [233*](#), [321](#).
shrink: [168](#), [169](#), [182](#), [196](#), [457](#), [488](#), [653](#), [662](#), [705](#), [735](#), [744](#), [832](#), [847](#), [892](#), [985](#), [1001](#), [1003](#), [1014](#), [1044](#), [1153](#), [1181](#), [1186](#), [1220](#), [1222](#), [1326](#), [1407](#), [1417](#), [1418](#), [1638*](#), [1639](#), [1700](#), [1747](#), [1791](#), [1792](#), [1795](#), [1796](#), [1797](#), [1799](#), [1805](#).
shrink_amount: [1638*](#).
shrink_limit: [705](#).
shrink_order: [168](#), [182](#), [196](#), [488](#), [653](#), [662](#), [735](#), [744](#), [832](#), [847](#), [892](#), [985](#), [1001](#), [1002](#), [1153](#), [1181](#), [1186](#), [1326](#), [1417](#), [1638*](#), [1639](#), [1700](#), [1747](#), [1792](#), [1795](#), [1804](#).
shrinking: [153*](#), [204*](#), [647*](#), [657*](#), [729*](#), [738*](#), [840](#), [852](#), [985](#), [986](#), [987](#), [1326](#), [1638*](#), [1700](#), [1724](#).
si: [38*](#), [42](#), [69](#), [1141*](#), [1489*](#), [1518*](#), [1616*](#), [1755](#), [1857](#).
side: [823](#).
sign: [689](#).
simple_group: [291](#), [1241](#), [1246](#), [1662](#), [1680](#).
Single-character primitives: [289](#).
\ -: [1292](#).

- \backslash : [287*](#)
- \sqcup : [287*](#)
- single_base*: [240*](#), [284*](#), [285](#), [286](#), [376*](#), [378*](#), [394](#), [395](#), [400](#), [468](#), [527*](#), [706](#), [1223](#), [1435*](#), [1467](#), [1769](#).
- skew_char*: [173](#), [452](#), [575*](#), [603*](#), [705](#), [706](#), [917](#), [1431](#), [1501*](#), [1502*](#), [1518*](#)
- \backslash skewchar primitive: [1432](#).
- skip*: [242](#), [453](#), [1186](#).
- \backslash skip primitive: [437](#).
- skip_base*: [242](#), [245](#), [247](#), [1402*](#), [1415](#).
- skip_blanks*: [325](#), [366](#), [367](#), [369](#), [371](#), [376*](#)
- skip_byte*: [571](#), [583](#), [823](#), [917](#), [928](#), [929](#), [1086](#), [1216](#).
- skip_code*: [1236](#), [1237](#), [1238](#).
- \backslash skipdef primitive: [1400*](#)
- skip_def_code*: [1400*](#), [1401*](#), [1402*](#)
- skip_line*: [358](#), [519](#), [520](#).
- skipping*: [327](#), [328*](#), [358](#), [520](#).
- slant*: [573](#), [584](#), [602*](#), [673*](#), [1301](#), [1303](#), [1892*](#), [1893*](#)
- slant_code*: [573](#), [584](#).
- slow_make_string*: [543*](#), [1118*](#), [1399*](#), [1878*](#)
- slow_print*: [60](#), [61*](#), [63](#), [562*](#), [563*](#), [608*](#), [1439](#), [1509](#), [1520*](#), [1885*](#), [1890*](#), [1891*](#)
- slow_print_substr*: [693](#).
- small_char*: [859](#), [867](#), [873](#), [882](#), [1338](#).
- small_fam*: [859](#), [867](#), [873](#), [882](#), [1338](#).
- small_node_size*: [159*](#), [162*](#), [163](#), [220*](#), [224*](#), [831](#), [1080](#), [1087*](#), [1091](#), [1214*](#), [1278*](#), [1279](#), [1562](#), [1570](#), [1573](#), [1576](#), [1577](#), [1595](#), [1596](#), [1597](#), [1598](#), [1599](#), [1605](#), [1606](#), [1625](#), [1626](#), [1728](#), [1739*](#)
- small_number*: [101](#), [102](#), [165*](#), [170*](#), [172](#), [286](#), [388*](#), [415](#), [439](#), [464](#), [466](#), [476](#), [487](#), [491](#), [496](#), [508](#), [515](#), [520](#), [523](#), [524](#), [549*](#), [604*](#), [634](#), [706](#), [729*](#), [772](#), [823](#), [844](#), [864](#), [882](#), [895](#), [896](#), [902](#), [932](#), [938](#), [1005](#), [1069](#), [1070](#), [1082](#), [1083](#), [1098*](#), [1111*](#), [1121*](#), [1137*](#), [1147](#), [1164](#), [1238](#), [1253](#), [1264](#), [1269*](#), [1354](#), [1359](#), [1369](#), [1376](#), [1389*](#), [1414](#), [1424](#), [1425](#), [1435*](#), [1471*](#), [1516*](#), [1530](#), [1531*](#), [1557](#), [1565](#), [1574](#), [1618*](#), [1621*](#), [1634](#), [1637](#), [1706](#), [1720](#), [1783](#), [1816](#), [1820](#), [1822](#), [1824](#), [1826](#), [1843](#), [1881*](#)
- small_op*: [1120*](#)
- snap_glue_ptr*: [695](#), [1574](#), [1604*](#), [1605](#), [1606](#), [1638*](#)
- snap_node_size*: [695](#), [1574](#), [1605](#), [1606](#).
- snap_unit*: [1638*](#)
- snappy_comp_ratio*: [695](#), [1576](#), [1604*](#), [1638*](#)
- so*: [38*](#), [45](#), [59*](#), [60](#), [69](#), [70](#), [286](#), [433](#), [490](#), [544*](#), [545*](#), [630](#), [645*](#), [693](#), [942](#), [1108*](#), [1130](#), [1132](#), [1133](#), [1136](#), [1140*](#), [1488*](#), [1616*](#), [1618*](#), [1755](#), [1856](#), [1901*](#)
- Sorry, I can't find...: [550*](#)
- sort_avail*: [149](#), [1490*](#)
- sort_dest_names*: [793](#), [804](#).
- source_filename_stack*: [326*](#), [350*](#), [353*](#), [563*](#), [1513*](#), [1940*](#)
- sp*: [104*](#), [614](#).
- sp*: [484](#).
- sp*: [1638*](#)
- space*: [573](#), [584](#), [693](#), [928](#), [931](#), [1220](#).
- space_code*: [573](#), [584](#), [605](#), [1220](#).
- space_factor*: [230](#), [231*](#), [444](#), [962](#), [963](#), [975](#), [1207](#), [1211*](#), [1221](#), [1222](#), [1234](#), [1254](#), [1261](#), [1269*](#), [1271](#), [1295](#), [1297](#), [1301](#), [1374](#), [1378](#), [1420](#), [1421](#).
- \backslash spacefactor primitive: [442](#).
- space_shrink*: [573](#), [584](#), [693](#), [1220](#).
- space_shrink_code*: [573](#), [584](#), [605](#).
- space_skip*: [242](#), [1219](#), [1221](#).
- \backslash spaceskip primitive: [244](#).
- space_skip_code*: [242](#), [243](#), [244](#), [1219](#).
- space_stretch*: [573](#), [584](#), [1220](#).
- space_stretch_code*: [573](#), [584](#).
- space_token*: [311](#), [419](#), [490](#), [1393*](#), [1762](#).
- spacer*: [225](#), [226](#), [250](#), [311](#), [313](#), [316](#), [320](#), [325](#), [359](#), [367](#), [369](#), [370](#), [371](#), [376*](#), [430](#), [432](#), [433](#), [469](#), [470](#), [478](#), [490](#), [959](#), [961](#), [967](#), [1112](#), [1138](#), [1207](#), [1223](#), [1399*](#)
- \backslash span primitive: [956](#).
- span_code*: [956](#), [957](#), [958](#), [965](#), [967](#).
- span_count*: [177](#), [203](#), [972](#), [977](#), [984](#).
- span_node_size*: [973](#), [974](#), [979](#).
- spec*: [1551](#), [1553](#), [1557](#), [1566](#).
- spec_code*: [817](#).
- spec_log*: [117](#), [118](#), [120](#).
- spec_out*: [20*](#), [254*](#), [1535*](#), [1616*](#)
- \backslash specialout primitive: [250*](#)
- spec_out_code*: [254*](#), [255*](#), [256*](#)
- spec_sout*: [20*](#), [1616*](#)
- \backslash special primitive: [1525*](#)
- special_node*: [1522*](#), [1525*](#), [1527](#), [1529*](#), [1535*](#), [1604*](#), [1605](#), [1606](#), [1621*](#), [1640](#), [1646](#), [1940*](#)
- special_out*: [1616*](#), [1621*](#)
- special_printing*: [20*](#), [23*](#), [59*](#), [1616*](#)
- split*: [1188](#).
- split_bot_mark*: [408](#), [409](#), [1154](#), [1156](#), [1810](#), [1827](#), [1828](#).
- \backslash splitbotmark primitive: [410](#).
- split_bot_mark_code*: [408](#), [410](#), [411](#), [1516*](#), [1810](#), [1832](#).
- \backslash splitbotmarks primitive: [1810](#).
- split_disc*: [1145](#), [1154](#), [1860](#), [1861](#).
- \backslash splitdiscards primitive: [1862](#).
- split_first_mark*: [408](#), [409](#), [1154](#), [1156](#), [1810](#), [1828](#).
- \backslash splitfirstmark primitive: [410](#).
- split_first_mark_code*: [408](#), [410](#), [411](#), [1810](#).
- \backslash splitfirstmarks primitive: [1810](#).
- split_fist_mark*: [1827](#).
- split_max_depth*: [158](#), [265](#), [1154](#), [1246](#), [1278*](#)

- `\splitmaxdepth` primitive: [266](#).
`split_max_depth_code`: [265](#), [266](#).
`split_top_ptr`: [158](#), [206](#), [220*](#), [224*](#), [1198](#), [1199](#), [1278*](#).
`split_top_skip`: [158](#), [242](#), [1145](#), [1154](#), [1189](#), [1191](#), [1198](#), [1278*](#).
`\splittopskip` primitive: [244](#).
`split_top_skip_code`: [242](#), [243](#), [244](#), [1146](#).
`split_up`: [1158](#), [1163](#), [1185](#), [1187](#), [1197](#), [1198](#).
`spotless`: [76](#), [77](#), [81*](#), [263](#), [686](#), [1513*](#), [1516*](#), [1775](#), [1777](#), [1778](#).
`spread`: [817](#).
`sprint_cs`: [241](#), [285](#), [360*](#), [421](#), [422](#), [424](#), [498](#), [505](#), [510*](#), [587*](#), [1473*](#).
`sq`: [597](#).
square roots: [913](#).
`src_specials`: [32*](#).
`src_specials_p`: [32*](#), [61*](#), [562*](#).
`ss_code`: [1236](#), [1237](#), [1238](#).
`ss_glue`: [180](#), [182](#), [891](#), [1238](#).
`ssup_error_line`: [11*](#), [54*](#), [1513*](#).
`ssup_hyph_size`: [11*](#), [1102*](#).
`ssup_max_strings`: [11*](#), [38*](#).
`ssup_trie_opcode`: [11*](#), [1097*](#).
`ssup_trie_size`: [11*](#), [1097*](#), [1513*](#).
`st`: [705](#).
`\stbscode` primitive: [1432](#).
`st_bs_code_base`: [173](#), [452](#), [1431](#), [1432](#), [1433](#).
stack conventions: [322*](#).
`stack_h`: [722](#), [726](#).
`stack_into_box`: [887](#), [889](#).
`stack_level`: [712](#), [717](#), [719](#).
`stack_no`: [727](#).
`stack_size`: [32*](#), [323*](#), [332](#), [343](#), [1513*](#), [1515*](#).
`stack_v`: [722](#), [726](#).
`stack_w`: [722](#), [726](#).
`stack_x`: [722](#), [726](#).
`stack_y`: [722](#), [726](#).
`stack_z`: [722](#), [726](#).
`start`: [322*](#), [324*](#), [325](#), [329](#), [340*](#), [341](#), [345](#), [346*](#), [347*](#), [348](#), [350*](#), [351](#), [353*](#), [382](#), [384](#), [385*](#), [393*](#), [394](#), [509](#), [564](#), [1756*](#), [1900*](#).
`start_cs`: [363*](#), [376*](#), [377*](#).
`start_eq_no`: [1318](#), [1320](#).
`start_field`: [322*](#), [324*](#).
`start_font_error_message`: [587*](#), [593](#).
`start_here`: [5](#), [1513*](#).
`start_input`: [388*](#), [402](#), [404](#), [563*](#), [1518*](#).
`start_of_TEX`: [6*](#), [1513*](#).
`start_packet`: [725](#).
`start_par`: [226](#), [1266](#), [1267](#), [1268](#), [1270](#).
`start_status`: [727](#).
`stat`: [7*](#), [135](#), [138](#), [139](#), [140](#), [141](#), [143*](#), [148](#), [270*](#), [279*](#), [296](#), [299](#), [304](#), [305*](#), [306](#), [667](#), [1002](#), [1005](#), [1021](#), [1031](#), [1039](#), [1164](#), [1182](#), [1187](#), [1514*](#), [1663](#), [1824](#), [1840](#), [1841](#), [1842](#).
`state`: [87](#), [322*](#), [324*](#), [325](#), [329](#), [333](#), [334](#), [345](#), [347*](#), [350*](#), [352](#), [353*](#), [359](#), [363*](#), [365*](#), [366](#), [368](#), [369](#), [371](#), [374](#), [375](#), [376*](#), [509](#), [552*](#), [563*](#), [1203*](#), [1516*](#).
`state_field`: [322*](#), [324*](#), [1309](#), [1776](#).
`stderr`: [1485*](#), [1871*](#).
`stdin`: [32*](#).
`stdout`: [32*](#), [61*](#), [550*](#).
`step`: [705](#).
stomach: [428](#).
`stop`: [225](#), [1223](#), [1224](#), [1230](#), [1231](#), [1232](#), [1272](#).
`stop_at_space`: [542*](#), [551*](#), [1868*](#), [1869*](#), [1881*](#).
`stop_flag`: [571](#), [583](#), [823](#), [917](#), [928](#), [929](#), [1086](#), [1216](#).
`store_background`: [1040](#).
`store_break_width`: [1019](#).
`store_fmt_file`: [1481*](#), [1516*](#).
`store_four_quarters`: [590*](#), [594](#), [595](#), [600*](#), [601](#).
`store_new_token`: [397](#), [398*](#), [419](#), [423](#), [425](#), [433](#), [490](#), [492](#), [499](#), [500](#), [502](#), [503](#), [508](#), [509](#), [1399*](#), [1684](#), [1762](#), [1768](#).
`store_scaled`: [597](#), [598](#), [600*](#), [602*](#).
`store_scaled_f`: [597](#), [712](#), [717](#), [725](#).
storepacket: [706](#), [718](#).
`str_eq_buf`: [45](#), [278](#).
`str_eq_str`: [46](#), [281](#), [693](#), [705](#), [801](#), [1438*](#), [1877*](#).
`str_in_str`: [686](#), [693](#).
`str_less_str`: [793](#).
`str_number`: [20*](#), [38*](#), [39*](#), [43](#), [45](#), [46](#), [47*](#), [62*](#), [63](#), [79](#), [93*](#), [94*](#), [95*](#), [195](#), [196](#), [281](#), [284*](#), [286](#), [306](#), [326*](#), [433](#), [496](#), [538](#), [543*](#), [545*](#), [551*](#), [553](#), [555](#), [556*](#), [558*](#), [563*](#), [575*](#), [586*](#), [686](#), [693](#), [698](#), [702](#), [704](#), [705](#), [706](#), [708](#), [712](#), [725](#), [727](#), [749](#), [772](#), [793](#), [807](#), [811](#), [1103*](#), [1106](#), [1111*](#), [1435*](#), [1457*](#), [1478](#), [1502*](#), [1513*](#), [1518*](#), [1538](#), [1553](#), [1556](#), [1565](#), [1588](#), [1603*](#), [1628](#), [1629](#), [1631](#), [1680](#), [1754](#), [1815](#), [1824](#), [1870*](#), [1877*](#), [1878*](#), [1881*](#), [1941*](#).
`str_pool`: [38*](#), [39*](#), [42](#), [43](#), [45](#), [46](#), [47*](#), [59*](#), [60](#), [69](#), [70](#), [274*](#), [279*](#), [283](#), [286](#), [325](#), [433](#), [490](#), [543*](#), [544*](#), [545*](#), [629*](#), [630](#), [645*](#), [666*](#), [686](#), [693](#), [702](#), [706](#), [727](#), [749](#), [750*](#), [793](#), [940](#), [942](#), [1106](#), [1108*](#), [1111*](#), [1118*](#), [1399*](#), [1487*](#), [1488*](#), [1489*](#), [1513*](#), [1514*](#), [1515*](#), [1538](#), [1588](#), [1616*](#), [1618*](#), [1631](#), [1754](#), [1755](#), [1869*](#), [1871*](#), [1881*](#), [1901*](#).
`str_ptr`: [38*](#), [39*](#), [41](#), [43](#), [44](#), [47*](#), [59*](#), [60](#), [70](#), [279*](#), [281](#), [284*](#), [496](#), [543*](#), [551*](#), [563*](#), [645*](#), [673*](#), [693](#), [727](#), [1399*](#), [1488*](#), [1489*](#), [1502*](#), [1504*](#), [1508*](#), [1513*](#), [1515*](#), [1616*](#), [1618*](#), [1901*](#).
`str_room`: [42](#), [198](#), [279*](#), [490](#), [542*](#), [543*](#), [551*](#), [706](#), [712](#), [717](#), [726](#), [727](#), [1116*](#), [1435*](#), [1457*](#), [1509](#),

- 1514*, 1616*, 1618*, 1754.
- str_start*: 38*, 39*, 40, 41, 43, 44, 45, 46, 47*, 59*, 60, 69, 70, 84*, 274*, 279*, 281, 286, 433, 496, 497, 543*, 544*, 545*, 630, 645*, 686, 693, 702, 706, 727, 749, 793, 941, 1106, 1108*, 1111*, 1118*, 1399*, 1487*, 1488*, 1489*, 1513*, 1538, 1588, 1616*, 1618*, 1631, 1755, 1871*, 1881*, 1901*.
- str_toks*: 490, 491, 496, 497, 1689, 1940*.
- strcmp*: 1487*.
- strcpy*: 1486*.
- stretch*: 168, 169, 182, 196, 457, 488, 653, 662, 705, 735, 744, 832, 847, 892, 985, 1003, 1014, 1044, 1153, 1181, 1186, 1220, 1222, 1326, 1407, 1417, 1418, 1638*, 1639, 1700, 1747, 1791, 1792, 1795, 1796, 1797, 1799, 1805, 1844, 1854.
- stretch_amount*: 1638*.
- stretch_limit*: 705.
- stretch_order*: 168, 182, 196, 488, 653, 662, 735, 744, 832, 847, 892, 985, 1003, 1014, 1044, 1153, 1181, 1186, 1326, 1417, 1638*, 1639, 1700, 1747, 1792, 1795, 1804, 1844.
- stretching*: 153*, 653, 662, 735, 744, 834, 849, 985, 986, 987, 1326, 1639, 1700.
- string pool: 47*, 1487*.
- `\string` primitive: 494.
- string_code*: 494, 495, 497, 498.
- string_vacancies*: 32*, 51*, 1513*.
- stringcast*: 550*, 560*, 563*, 1453*, 1486*, 1487*, 1623*.
- strings_free*: 32*, 1489*, 1513*.
- strlen*: 645*, 1486*.
- style*: 902, 903, 936, 937, 938.
- style_node*: 178, 864, 866, 874, 906, 907, 937, 1347, 1720.
- style_node_size*: 864, 865, 874, 939, 1720.
- sub_box*: 857, 863, 868, 874, 896, 910, 911, 913, 914, 925*, 930, 1254, 1271, 1346*.
- sub_char_shrink*: 1015, 1017.
- sub_char_shrink_end*: 1015.
- sub_char_stretch*: 1015, 1017.
- sub_char_stretch_end*: 1015.
- sub_disc_width_from_active_width*: 1015, 1045.
- sub_drop*: 876, 932.
- sub_kern_shrink*: 1015, 1017.
- sub_kern_shrink_end*: 1015.
- sub_kern_stretch*: 1015, 1017.
- sub_kern_stretch_end*: 1015.
- sub_mark*: 225, 316, 320, 369, 1224, 1353, 1399*.
- sub_mlist*: 857, 859, 868, 896, 918, 930, 1359, 1363, 1364, 1369.
- sub_style*: 878, 926, 933, 935.
- sub_sup*: 1353, 1354.
- subinfo*: 1900*, 1901*.
- subscr*: 857, 859, 862, 863, 866, 872, 874, 914, 918, 925*, 926, 927, 928, 929, 930, 931, 932, 933, 935, 1329, 1341, 1343, 1353, 1354, 1355, 1364.
- subscripts: 930, 1353.
- subst_ex_font*: 823, 825, 828.
- subst_font_type*: 703.
- substituted*: 823.
- substr_of_str*: 749, 769, 807.
- subtype*: 151, 152, 153*, 154, 157, 158, 160, 161, 162*, 163, 164, 165*, 167, 168, 170*, 171*, 172, 173, 174*, 176*, 177, 193, 201, 206, 207, 208, 209, 210, 211, 450, 498, 515, 521, 522, 643, 653, 655, 662, 664, 674, 695, 705, 727, 735, 744, 772, 823, 825, 832, 844, 847, 857, 858, 862, 863, 864, 865, 866, 872, 893, 906, 907, 908, 909, 925*, 939, 942, 944, 962, 969, 971, 985, 995, 996, 998, 1005, 1013, 1017, 1018, 1019, 1020, 1042, 1044, 1046, 1047, 1055, 1057, 1073, 1074, 1075, 1076, 1080, 1087*, 1145, 1158, 1163, 1165*, 1177, 1185, 1186, 1195, 1197, 1198, 1212, 1238, 1239, 1256, 1258, 1278*, 1279, 1291, 1303, 1326, 1337, 1341, 1343, 1349, 1359, 1369, 1516*, 1522*, 1530, 1574, 1604*, 1605, 1606, 1607, 1608, 1609, 1610, 1611, 1612, 1613, 1616*, 1621*, 1623*, 1636, 1638*, 1640, 1646, 1692*, 1700, 1712, 1718, 1720, 1721, 1729, 1737, 1738, 1740*, 1778, 1789, 1790, 1816, 1900*.
- sub1*: 876, 933.
- sub2*: 876, 935.
- succumb*: 93*, 94*, 95*, 686, 1483.
- sup*: 1513*.
- sup_buf_size*: 11*.
- sup_dest_names_size*: 695, 698, 1514*.
- sup_drop*: 876, 932.
- sup_dvi_buf_size*: 11*.
- sup_expand_depth*: 11*.
- sup_font_max*: 11*.
- sup_font_mem_size*: 11*, 1500*.
- sup_hash_extra*: 11*, 1487*.
- sup_hyph_size*: 11*.
- sup_main_memory*: 11*, 129*, 1513*.
- sup_mark*: 225, 316, 320, 366, 377*, 1224, 1353, 1354, 1355.
- sup_max_in_open*: 11*.
- sup_max_strings*: 11*, 1489*.
- sup_mem_bot*: 11*.
- sup_nest_size*: 11*.
- sup_obj_tab_size*: 695, 698, 1514*.
- sup_param_size*: 11*.
- sup_pdf_mem_size*: 675, 678, 1514*.
- sup_pdf_os_buf_size*: 679, 686.
- sup_pk_dpi*: 695.
- sup_pool_free*: 11*.

- sup_pool_size*: [11*](#), [1489*](#)
sup_save_size: [11*](#)
sup_stack_size: [11*](#)
sup_string_vacancies: [11*](#)
sup_strings_free: [11*](#)
sup_style: [878](#), [926](#), [934](#).
sup_trie_size: [11*](#)
superscripts: [930](#), [1353](#).
supscr: [857](#), [859](#), [862](#), [863](#), [866](#), [872](#), [874](#), [914](#),
[918](#), [926](#), [927](#), [928](#), [929](#), [930](#), [932](#), [934](#), [1329](#),
[1341](#), [1343](#), [1353](#), [1354](#), [1355](#), [1364](#).
sup1: [876](#), [934](#).
sup2: [876](#), [934](#).
sup3: [876](#), [934](#).
sw: [586*](#), [597](#), [602*](#)
switch: [363*](#), [365*](#), [366](#), [368](#), [372](#).
sync_line: [153*](#), [1917*](#), [1936*](#), [1937*](#), [1938*](#)
sync_tag: [153*](#), [1087*](#), [1722*](#), [1917*](#), [1936*](#), [1937*](#), [1938*](#)
synch_h: [643](#), [648*](#), [652](#), [656](#), [661](#), [665](#), [1616*](#), [1892*](#)
synch_v: [643](#), [648*](#), [652](#), [656](#), [660*](#), [661](#), [665](#),
[1616*](#), [1892*](#)
synchronization: [1939*](#)
synctex: [1939*](#)
synctex: [254*](#), [1915*](#)
\synctex primitive: [1909*](#)
synctex_abort: [1514*](#)
synctex_code: [254*](#), [1908*](#), [1909*](#), [1910*](#), [1912*](#), [1913*](#)
synctex_current: [1931*](#)
synctex_field_size: [153*](#), [156*](#), [159*](#), [224*](#), [1915*](#), [1939*](#)
synctex_hlist: [1928*](#)
synctex_horizontal_rule_or_glue: [1932*](#)
synctex_init_command: [1914*](#)
synctex_kern: [1933*](#)
synctex_math: [1934*](#)
synctex_mroxfdp: [750*](#)
synctex_pdfxform: [750*](#)
synctex_sheet: [750*](#), [1924*](#)
synctex_start_input: [1918*](#), [1919*](#)
synctex_tag: [324*](#), [1917*](#), [1918*](#), [1920*](#), [1921*](#), [1939*](#)
synctex_tag_field: [322*](#), [324*](#), [1939*](#)
synctex_teehs: [750*](#), [1925*](#)
synctex_terminate: [1922*](#)
synctex_tsilh: [1929*](#)
synctex_tsilv: [1927*](#)
synctex_vlist: [1926*](#)
synctex_void_hlist: [1930*](#)
synctex_void_vlist: [1930*](#)
synctexoffset: [1911*](#), [1912*](#), [1913*](#)
synctexoption: [1906*](#), [1907*](#)
synctexpdfxform: [1638*](#)
sys_: [259*](#)
sys_day: [259*](#), [264](#), [562*](#)
sys_month: [259*](#), [264](#), [562*](#)
sys_obj_ptr: [696](#), [697](#), [698](#), [802](#), [812](#), [814](#), [815](#),
[1505](#), [1506](#).
sys_time: [259*](#), [264](#), [562*](#)
sys_year: [259*](#), [264](#), [562*](#)
system: [1618*](#)
system dependencies: [2*](#), [3](#), [9](#), [10](#), [11*](#), [12*](#), [19*](#), [21](#),
[23*](#), [26*](#), [32*](#), [34*](#), [35*](#), [37*](#), [38*](#), [49*](#), [56](#), [59*](#), [61*](#), [72](#), [81*](#),
[84*](#), [96](#), [109*](#), [112](#), [128*](#), [130*](#), [131*](#), [179](#), [204*](#), [259*](#),
[326*](#), [335](#), [350*](#), [511](#), [537](#), [538](#), [539*](#), [540*](#), [541*](#), [542*](#),
[543*](#), [544*](#), [545*](#), [546*](#), [547*](#), [549*](#), [551*](#), [563*](#), [564](#), [583](#),
[590*](#), [618](#), [622*](#), [624*](#), [974](#), [1097*](#), [1485*](#), [1512](#), [1513*](#),
[1514*](#), [1519*](#), [1521](#), [1832](#), [1868*](#), [1879*](#), [1882*](#)
sz: [1754](#), [1755](#), [1757](#).
s1: [82*](#), [88](#), [793](#), [1538](#), [1565](#), [1588](#).
s2: [82*](#), [88](#), [793](#), [1538](#), [1565](#), [1588](#).
s3: [82*](#), [88](#).
s4: [82*](#), [88](#).
t: [46](#), [107](#), [108](#), [143*](#), [236](#), [299](#), [301](#), [302](#), [303](#), [345](#),
[363*](#), [388*](#), [415](#), [490](#), [496](#), [499](#), [543*](#), [689](#), [706](#),
[880](#), [881](#), [902](#), [932](#), [976](#), [1005](#), [1006](#), [1053](#),
[1083](#), [1143*](#), [1147](#), [1207](#), [1301](#), [1354](#), [1369](#), [1376](#),
[1435*](#), [1466](#), [1471*](#), [1724](#), [1734*](#), [1739*](#), [1745](#), [1783](#),
[1800](#), [1820](#), [1824](#), [1878*](#)
t_open_in: [33*](#), [37*](#)
t_open_out: [33*](#), [1513*](#)
tab_mark: [225](#), [311](#), [316](#), [364](#), [369](#), [956](#), [957](#), [958](#),
[959](#), [960](#), [964](#), [1304](#).
tab_skip: [242](#).
\tabskip primitive: [244](#).
tab_skip_code: [242](#), [243](#), [244](#), [954](#), [958](#), [962](#),
[969](#), [971](#), [985](#).
tab_token: [311](#), [1306](#).
tag: [569](#), [570](#), [580*](#)
tag_code: [173](#), [452](#), [1431](#), [1432](#), [1433](#).
\tagcode primitive: [1432](#).
tail: [160](#), [230](#), [231*](#), [232](#), [233*](#), [234](#), [450](#), [855](#), [894](#),
[952](#), [962](#), [971](#), [972](#), [975](#), [988](#), [992](#), [1067](#), [1172](#),
[1194](#), [1200](#), [1203*](#), [1211*](#), [1212](#), [1213*](#), [1214*](#),
[1217](#), [1218](#), [1219](#), [1221](#), [1232](#), [1238](#), [1239](#),
[1254](#), [1256](#), [1258](#), [1269*](#), [1274](#), [1278*](#), [1279](#),
[1283](#), [1288](#), [1291](#), [1295](#), [1297](#), [1298](#), [1301](#), [1303](#),
[1323](#), [1328](#), [1333](#), [1336](#), [1337](#), [1341](#), [1343](#), [1346*](#),
[1349](#), [1352](#), [1354](#), [1355](#), [1359](#), [1362](#), [1364](#), [1365](#),
[1369](#), [1374](#), [1383](#), [1384](#), [1487*](#), [1530](#), [1531*](#), [1532](#),
[1533](#), [1534](#), [1535*](#), [1539](#), [1540](#), [1541](#), [1547](#), [1550](#),
[1555](#), [1557](#), [1559](#), [1561](#), [1566](#), [1567](#), [1576](#), [1624](#),
[1625](#), [1626](#), [1864](#), [1940*](#)
tail_append: [231*](#), [232](#), [962](#), [971](#), [992](#), [1212](#), [1214*](#),
[1217](#), [1218](#), [1232](#), [1234](#), [1238](#), [1239](#), [1269*](#), [1271](#),
[1278*](#), [1281](#), [1290](#), [1291](#), [1295](#), [1328](#), [1336](#), [1341](#),
[1343](#), [1346*](#), [1349](#), [1350](#), [1355](#), [1369](#), [1374](#), [1381](#),

- 1383, 1384, 1575, 1704.
tail_field: [230](#), [231](#)*, [1172](#).
tail_page_disc: [1176](#), [1860](#).
take_frac: [114](#), [126](#), [127](#).
take_fraction: [1800](#).
tally: [54](#)*, [55](#), [57](#), [58](#), [314](#), [334](#), [337](#), [338](#), [339](#).
tats: [7](#)*.
temp_head: [180](#), [328](#)*, [417](#), [422](#), [426](#)*, [490](#), [492](#), [493](#),
[496](#), [497](#), [504](#), [895](#), [896](#), [930](#), [936](#), [992](#), [1038](#),
[1039](#), [1040](#), [1053](#), [1055](#), [1056](#), [1057](#), [1063](#), [1145](#),
[1242](#), [1243](#), [1372](#), [1374](#), [1377](#), [1476](#)*, [1684](#), [1689](#),
[1708](#), [1710](#), [1735](#), [1736](#), [1738](#), [1739](#)*, [1754](#), [1940](#)*.
temp_ptr: [133](#), [172](#), [646](#), [647](#)*, [651](#)*, [656](#), [657](#)*, [660](#)*
[665](#), [668](#)*, [729](#)*, [733](#)*, [737](#), [738](#)*, [742](#)*, [746](#), [752](#),
[855](#), [868](#), [869](#), [1146](#), [1178](#), [1198](#), [1214](#)*, [1219](#),
[1516](#)*, [1706](#), [1708](#), [1710](#), [1713](#), [1722](#)*, [1723](#)*,
[1724](#), [1728](#), [1747](#).
temp_str: [543](#)*, [563](#)*.
ten_pow: [687](#), [688](#), [689](#), [690](#), [792](#), [1638](#)*.
term_and_log: [54](#)*, [57](#), [58](#), [71](#)*, [75](#), [92](#), [263](#), [560](#)*
[1399](#)*, [1477](#), [1509](#), [1516](#)*, [1618](#)*, [1623](#)*.
term_in: [32](#)*, [36](#), [37](#)*, [71](#)*, [1519](#)*, [1520](#)*.
term_input: [71](#)*, [78](#).
term_offset: [54](#)*, [55](#), [57](#), [58](#), [61](#)*, [62](#)*, [71](#)*, [563](#)*, [666](#)*
[750](#)*, [1458](#)*, [1756](#)*.
term_only: [54](#)*, [55](#), [57](#), [58](#), [71](#)*, [75](#), [92](#), [561](#), [1477](#),
[1514](#)*, [1516](#)*, [1618](#)*.
term_out: [32](#)*, [34](#)*, [36](#), [37](#)*, [51](#)*, [56](#).
terminal_input: [326](#)*, [335](#), [350](#)*, [352](#), [382](#).
test_char: [1083](#), [1086](#).
test_no_ligatures: [452](#), [604](#)*.
TEX: [2](#)*, [4](#)*.
TeX capacity exceeded ...: [94](#)*
 buffer size: [35](#)*, [286](#), [350](#)*, [400](#), [1769](#).
 exception dictionary: [1117](#)*.
 font memory: [607](#).
 grouping levels: [296](#).
 hash size: [279](#)*.
 input stack size: [343](#).
 main memory size: [138](#), [143](#)*.
 number of strings: [43](#), [543](#)*.
 parameter stack size: [416](#)*.
 pattern memory: [1131](#), [1141](#)*.
 pool size: [42](#).
 primitive size: [282](#).
 save size: [295](#).
 semantic nest size: [234](#).
 text input levels: [350](#)*.
TEX_area: [540](#)*.
tex_b_openin: [772](#).
TeX_banner: [2](#)*.
TeX_banner_k: [2](#)*.
TEX_font_area: [540](#)*.
TEX_format_default: [546](#)*, [549](#)*, [550](#)*.
tex_input_type: [563](#)*, [1453](#)*.
tex_int_pars: [254](#)*.
tex_remainder: [104](#)*.
tex_toks: [248](#)*.
The T_EXbook: [1](#), [23](#)*, [49](#)*, [108](#), [225](#), [441](#), [472](#), [482](#),
[485](#), [859](#), [864](#), [940](#), [1393](#)*, [1512](#).
TeXformats: [11](#)*, [547](#)*.
TEXMF_ENGINE_NAME: [11](#)*.
termf_log_name: [558](#)*.
TEXMF_POOL_NAME: [11](#)*.
termf_yesno: [1623](#)*.
texput: [35](#)*, [560](#)*, [1435](#)*.
text: [274](#)*, [277](#)*, [278](#), [279](#)*, [284](#)*, [285](#), [286](#), [287](#)*, [394](#),
[395](#), [517](#), [527](#)*, [579](#), [706](#), [956](#), [1223](#), [1366](#), [1394](#),
[1435](#)*, [1487](#)*, [1497](#)*, [1513](#)*, [1525](#)*, [1617](#), [1871](#)*.
Text line contains...: [368](#).
text_char: [19](#)*, [20](#)*, [25](#), [26](#)*, [1481](#)*, [1482](#)*, [1486](#)*, [1487](#)*.
\textfont primitive: [1408](#)*.
text_mlist: [865](#), [871](#), [874](#), [907](#), [1352](#).
text_size: [875](#), [879](#), [908](#), [1373](#), [1377](#).
text_style: [864](#), [870](#), [879](#), [907](#), [913](#), [920](#), [921](#), [922](#),
[924](#), [925](#)*, [934](#), [1347](#), [1372](#), [1374](#).
\textstyle primitive: [1347](#).
TeXXeT: [1701](#).
TeXXeT_code: [2](#)*, [1701](#), [1702](#).
TeXXeT_en: [823](#), [825](#), [1055](#), [1056](#), [1057](#), [1701](#),
[1704](#), [1735](#), [1736](#), [1737](#).
TeXXeT_state: [1701](#).
\TeXXeT_state primitive: [1702](#).
T_EX82: [1](#), [99](#).
TFM files: [565](#).
tfm_file: [565](#), [586](#)*, [589](#)*, [590](#)*, [602](#)*.
tfm_lookup: [705](#), [706](#), [712](#).
tfm_temp: [590](#)*.
tfm_width: [712](#), [717](#).
TFtoPL: [587](#)*.
That makes 100 errors...: [82](#)*.
the: [228](#), [287](#)*, [288](#)*, [388](#)*, [391](#), [504](#), [1687](#).
The following...deleted: [669](#), [1169](#), [1299](#).
\the primitive: [287](#)*.
the_toks: [491](#), [492](#), [493](#), [504](#), [1476](#)*, [1689](#).
thick_mu_skip: [242](#).
\thickmuskip primitive: [244](#).
thick_mu_skip_code: [242](#), [243](#), [244](#), [942](#).
thickness: [859](#), [873](#), [901](#), [919](#), [920](#), [922](#), [923](#), [1360](#).
thin_mu_skip: [242](#).
\thinmuskip primitive: [244](#).
thin_mu_skip_code: [242](#), [243](#), [244](#), [247](#), [942](#).
This can't happen: [95](#)*
 /[112](#).

- align: 976.
- copying: 224*.
- curlevel: 303.
- disc1: 1017.
- disc2: 1018.
- disc3: 1046.
- disc4: 1047.
- display: 1378.
- endv: 967.
- ext1: 1529*.
- ext2: 1605.
- ext3: 1606.
- ext4: 1621*.
- flushing: 220*.
- if: 523.
- line breaking: 1053.
- LR1: 1713.
- LR2: 1726*.
- LR3: 1731.
- mlist1: 904.
- mlist2: 930.
- mlist3: 937.
- mlist4: 942.
- page: 1177.
- paragraph: 1042.
- pdfvlistout: 740.
- prefix: 1389*.
- pruning: 1145.
- right: 1363.
- rightbrace: 1246.
- tail1: 1258.
- vcenter: 912.
- vertbreak: 1150.
- vlistout: 658.
- vpack: 845.
- 256 spans: 974.
- this_box*: 647*, 652, 653, 657*, 661, 662, 729*, 730, 734, 735, 738*, 739, 743, 744, 1638*, 1639, 1640, 1646, 1715, 1716, 1722*, 1723*, 1724, 1926*, 1927*, 1928*, 1929*, 1930*, 1932*, 1933*, 1934*.
- this_if*: 524, 527*, 529, 531, 532, 1770.
- thread*: 1601.
- thread_title*: 1601.
- threads*: 790, 806, 1514*.
- three_codes*: 817.
- threshold*: 1004, 1027, 1030, 1039.
- Tight \hbox...: 843.
- Tight \vbox...: 854.
- tight_fit*: 993, 995, 1006, 1009, 1010, 1012, 1029, 1843, 1849.
- time*: 254*, 259*, 645*, 792.
- \time primitive: 256*.
- time_code*: 254*, 255*, 256*.
- tini**: 8*.
- Tini**: 8*.
- tmp_b0*: 706, 710, 712, 714.
- tmp_b1*: 706, 710, 712, 714.
- tmp_b2*: 706, 710, 714.
- tmp_b3*: 706, 710, 714.
- tmp_int*: 710, 726.
- tmp_k1*: 1207, 1211*, 1216, 1217.
- tmp_k2*: 1207, 1212.
- tmp_v*: 1638*.
- tmp_w*: 705, 710.
- to**: 817, 1260, 1403.
- tok_val*: 436, 441, 444, 454, 491, 1402*, 1404, 1405, 1490*, 1491*, 1816, 1819, 1824.
- tok_val_limit*: 1816, 1838.
- token**: 311.
- token_list*: 329, 333, 334, 345, 347*, 352, 359, 363*, 368, 552*, 1203*, 1309, 1516*, 1776.
- token_ref_count*: 218, 221, 313, 499, 508, 1156, 1684, 1940*.
- token_show*: 317, 318, 345, 427*, 1457*, 1462, 1476*, 1618*, 1689, 1754.
- token_type*: 329, 333, 334, 336, 341, 345, 346*, 347*, 349, 405, 416*, 1203*, 1263*, 1273, 1278*, 1308*, 1311*, 1346*.
- tokens_to_string*: 497, 686, 708, 727, 769, 772, 792, 807, 1538, 1553, 1556, 1564, 1566, 1588, 1590, 1600, 1631, 1638*, 1881*.
- toklist*: 1940*.
- toks*: 248*.
- \toks primitive: 287*.
- toks_base*: 248*, 249, 250, 251, 329, 441, 1402*, 1404, 1405.
- \toksdef primitive: 1400*.
- toks_def_code*: 1400*, 1402*.
- toks_register*: 227*, 287*, 288*, 439, 441, 1388, 1399*, 1402*, 1404, 1405, 1824, 1834, 1835.
- tolerance*: 254*, 258*, 1004, 1039.
- \tolerance primitive: 256*.
- tolerance_code*: 254*, 255*, 256*.
- Too many }'s: 1246.
- Too many color stacks: 497.
- too_big*: 1800.
- too_small*: 1482*, 1485*.
- top*: 572, 693.
- top_bot_mark*: 228, 318, 388*, 391, 410, 411, 412, 1810.
- top_edge*: 657*, 664, 738*, 739, 1640.
- top_mark*: 408, 409, 1189, 1810, 1829.
- \topmark primitive: 410.
- top_mark_code*: 408, 410, 412, 1516*, 1810, 1832.

- `\topmarks` primitive: [1810](#).
- `top_skip`: [242](#).
- `\topskip` primitive: [244](#).
- `top_skip_code`: [242](#), [243](#), [244](#), [1178](#).
- `total_demerits`: [995](#), [1021](#), [1022](#), [1031](#), [1040](#), [1050](#), [1051](#).
- `total_font_shrink`: [999](#), [1027](#).
- `total_font_stretch`: [999](#), [1027](#).
- `total height`: [1163](#).
- `total_mathex_params`: [877](#), [1373](#).
- `total_mathsy_params`: [876](#), [1373](#).
- `total_pages`: [619](#)*, [620](#), [645](#)*, [668](#)*, [670](#)*, [751](#), [752](#), [770](#), [794](#).
- `total_pw`: [1005](#), [1027](#).
- `total_shrink`: [818](#), [824](#), [832](#), [840](#), [841](#), [842](#), [843](#), [847](#), [852](#), [853](#), [854](#), [972](#), [1379](#).
- `total_stretch`: [818](#), [824](#), [832](#), [834](#), [835](#), [836](#), [847](#), [849](#), [850](#), [972](#).
- Trabb Pardo, Luis Isidoro: [2](#)*
- `tracing_assigns`: [254](#)*, [299](#), [1840](#), [1841](#).
- `\tracingassigns` primitive: [1658](#).
- `tracing_assigns_code`: [254](#)*, [1658](#), [1660](#).
- `tracing_char_sub_def`: [254](#)*, [258](#)*, [1402](#)*
- `\tracingcharsubdef` primitive: [256](#)*
- `tracing_char_sub_def_code`: [254](#)*, [255](#)*, [256](#)*
- `tracing_commands`: [254](#)*, [391](#), [524](#), [535](#), [536](#), [1208](#), [1389](#)*
- `\tracingcommands` primitive: [256](#)*
- `tracing_commands_code`: [254](#)*, [255](#)*, [256](#)*
- `tracing_groups`: [254](#)*, [296](#), [304](#).
- `\tracinggroups` primitive: [1658](#).
- `tracing_groups_code`: [254](#)*, [1658](#), [1660](#).
- `tracing_ifs`: [254](#)*, [321](#), [520](#), [524](#), [536](#).
- `\tracingifs` primitive: [1658](#).
- `tracing_ifs_code`: [254](#)*, [1658](#), [1660](#).
- `tracing_lost_chars`: [254](#)*, [608](#)*, [1891](#)*
- `\tracinglostchars` primitive: [256](#)*
- `tracing_lost_chars_code`: [254](#)*, [255](#)*, [256](#)*
- `tracing_macros`: [254](#)*, [345](#), [415](#), [426](#)*
- `\tracingmacros` primitive: [256](#)*
- `tracing_macros_code`: [254](#)*, [255](#)*, [256](#)*
- `tracing_nesting`: [254](#)*, [384](#), [1775](#), [1776](#), [1777](#), [1778](#).
- `\tracingnesting` primitive: [1658](#).
- `tracing_nesting_code`: [254](#)*, [1658](#), [1660](#).
- `tracing_online`: [254](#)*, [263](#), [608](#)*, [1471](#)*, [1477](#), [1618](#)*, [1623](#)*
- `\tracingonline` primitive: [256](#)*
- `tracing_online_code`: [254](#)*, [255](#)*, [256](#)*
- `tracing_output`: [254](#)*, [666](#)*, [669](#), [750](#)*
- `\tracingoutput` primitive: [256](#)*
- `tracing_output_code`: [254](#)*, [255](#)*, [256](#)*
- `tracing_pages`: [254](#)*, [1164](#), [1182](#), [1187](#).
- `\tracingpages` primitive: [256](#)*
- `tracing_pages_code`: [254](#)*, [255](#)*, [256](#)*
- `tracing_paragraphs`: [254](#)*, [1002](#), [1021](#), [1031](#), [1039](#).
- `\tracingparagraphs` primitive: [256](#)*
- `tracing_paragraphs_code`: [254](#)*, [255](#)*, [256](#)*
- `tracing_restores`: [254](#)*, [305](#)*, [1842](#).
- `\tracingrestores` primitive: [256](#)*
- `tracing_restores_code`: [254](#)*, [255](#)*, [256](#)*
- `tracing_scan_tokens`: [254](#)*, [1756](#)*
- `\tracingscantokens` primitive: [1658](#).
- `tracing_scan_tokens_code`: [254](#)*, [1658](#), [1660](#).
- `tracing_stack_levels`: [254](#)*, [426](#)*, [427](#)*, [563](#)*
- `\tracingstacklevels` primitive: [256](#)*
- `tracing_stack_levels_code`: [254](#)*, [255](#)*, [256](#)*
- `tracing_stats`: [135](#), [254](#)*, [667](#), [1507](#), [1514](#)*
- `\tracingstats` primitive: [256](#)*
- `tracing_stats_code`: [254](#)*, [255](#)*, [256](#)*
- `tracinglostchars`: [1891](#)*
- `tracingmacros`: [254](#)*
- Transcript written...: [1514](#)*
- `translate_filename`: [24](#)*, [61](#)*, [560](#)*, [562](#)*, [1518](#)*, [1876](#)*
- `trap_zero_glue`: [1406](#), [1407](#), [1414](#).
- `trapped_given`: [807](#).
- `trick_buf`: [54](#)*, [58](#), [337](#), [339](#).
- `trick_count`: [54](#)*, [58](#), [337](#), [338](#), [339](#).
- Trickey, Howard Wellington: [2](#)*
- `trie`: [1097](#)*, [1098](#)*, [1099](#), [1127](#)*, [1129](#), [1130](#), [1131](#), [1135](#)*, [1136](#), [1143](#)*
- `trie_back`: [1127](#)*, [1131](#), [1133](#).
- `trie_c`: [1124](#)*, [1125](#), [1130](#), [1132](#), [1133](#), [1136](#), [1140](#)*, [1141](#)*, [1518](#)*, [1856](#), [1857](#).
- `trie_char`: [1097](#)*, [1098](#)*, [1100](#)*, [1135](#)*, [1136](#), [1859](#).
- `trie_fix`: [1135](#)*, [1136](#).
- `trie_hash`: [1124](#)*, [1125](#), [1126](#), [1127](#)*, [1129](#), [1518](#)*
- `trie_l`: [1124](#)*, [1125](#), [1126](#), [1134](#), [1136](#), [1137](#)*, [1140](#)*, [1141](#)*, [1518](#)*, [1857](#).
- `trie_link`: [1097](#)*, [1098](#)*, [1100](#)*, [1127](#)*, [1129](#), [1130](#), [1131](#), [1132](#), [1133](#), [1135](#)*, [1136](#), [1859](#).
- `trie_max`: [1127](#)*, [1129](#), [1131](#), [1135](#)*, [1503](#)*, [1504](#)*
- `trie_min`: [1127](#)*, [1129](#), [1130](#), [1133](#), [1858](#).
- `trie_node`: [1125](#), [1126](#).
- `trie_not_ready`: [1068](#), [1111](#)*, [1127](#)*, [1128](#)*, [1137](#)*, [1143](#)*, [1503](#)*, [1504](#)*, [1518](#)*
- `trie_o`: [1124](#)*, [1125](#), [1136](#), [1140](#)*, [1141](#)*, [1518](#)*, [1857](#).
- `trie_op`: [1097](#)*, [1098](#)*, [1100](#)*, [1101](#)*, [1120](#)*, [1135](#)*, [1136](#), [1855](#)*, [1859](#).
- `trie_op_hash`: [11](#)*, [1120](#)*, [1121](#)*, [1122](#)*, [1123](#)*, [1125](#), [1129](#).
- `trie_op_lang`: [1120](#)*, [1121](#)*, [1122](#)*, [1129](#).
- `trie_op_ptr`: [1120](#)*, [1121](#)*, [1122](#)*, [1123](#)*, [1503](#)*, [1504](#)*
- `trie_op_size`: [11](#)*, [1098](#)*, [1120](#)*, [1121](#)*, [1123](#)*, [1503](#)*, [1504](#)*

- trie_op_val*: [1120](#)*, [1121](#)*, [1122](#)*, [1129](#).
trie_opcode: [1097](#)*, [1098](#)*, [1120](#)*, [1121](#)*, [1124](#)*, [1137](#)*,
[1518](#)*.
trie_pack: [1134](#), [1143](#)* [1858](#).
trie_pointer: [1097](#)*, [1098](#)*, [1099](#), [1124](#)*, [1125](#), [1126](#),
[1127](#)*, [1130](#), [1134](#), [1136](#), [1137](#)*, [1143](#)*, [1504](#)*,
[1518](#)*, [1859](#).
trie_ptr: [1124](#)*, [1129](#), [1141](#)*, [1518](#)*.
trie_r: [1124](#)*, [1125](#), [1126](#), [1132](#), [1133](#), [1134](#), [1136](#),
[1140](#)*, [1141](#)*, [1518](#)*, [1855](#)*, [1856](#), [1857](#).
trie_ref: [1127](#)*, [1129](#), [1130](#), [1133](#), [1134](#), [1136](#), [1858](#).
trie_root: [1124](#)*, [1126](#), [1129](#), [1135](#)*, [1143](#)*, [1518](#)*,
[1855](#)*, [1858](#).
trie_size: [32](#)*, [1125](#), [1129](#), [1131](#), [1141](#)*, [1504](#)*,
[1513](#)*, [1518](#)*.
trie_taken: [1127](#)*, [1129](#), [1130](#), [1131](#), [1133](#), [1518](#)*.
trie_trc: [1098](#)*, [1503](#)*, [1504](#)*, [1518](#)*.
trie_trl: [1098](#)*, [1503](#)*, [1504](#)*, [1518](#)*.
trie_tro: [1098](#)*, [1127](#)*, [1503](#)*, [1504](#)*, [1518](#)*.
trie_used: [1120](#)* [1121](#)* [1122](#)* [1123](#)* [1503](#)* [1504](#)*
true: [4](#)* [16](#)* [31](#)* [37](#)* [45](#), [46](#), [49](#)* [51](#)* [71](#)* [77](#), [82](#)* [88](#),
[97](#), [98](#), [104](#)* [105](#), [106](#), [107](#), [112](#), [114](#), [115](#), [186](#),
[187](#), [256](#)* [274](#)* [276](#)* [278](#), [284](#)* [304](#), [333](#), [349](#), [350](#)*
[358](#), [368](#), [376](#)* [378](#)* [383](#), [384](#), [387](#), [398](#)* [400](#), [404](#),
[433](#), [439](#), [456](#), [466](#), [470](#), [473](#), [479](#), [487](#), [488](#), [512](#),
[527](#)* [534](#), [538](#), [542](#)* [550](#)* [551](#)* [552](#)* [560](#)* [580](#)* [589](#)*
[605](#), [619](#)* [649](#)* [656](#), [665](#), [666](#)* [669](#), [683](#), [685](#),
[686](#), [689](#), [692](#), [693](#), [698](#), [699](#), [702](#), [705](#), [706](#),
[720](#), [726](#), [727](#), [737](#), [746](#), [747](#), [748](#), [749](#), [750](#)*
[766](#), [791](#), [793](#), [794](#), [795](#), [799](#), [801](#), [802](#), [804](#),
[823](#), [839](#), [851](#), [882](#), [895](#), [967](#), [1002](#), [1003](#), [1004](#),
[1005](#), [1027](#), [1030](#), [1039](#), [1056](#), [1057](#), [1058](#), [1060](#),
[1080](#), [1082](#), [1087](#)* [1088](#), [1128](#)* [1133](#), [1139](#), [1140](#)*
[1169](#), [1197](#), [1198](#), [1202](#), [1207](#), [1212](#), [1214](#)* [1218](#),
[1229](#), [1232](#), [1258](#), [1261](#), [1268](#), [1279](#), [1299](#), [1323](#),
[1341](#), [1372](#), [1373](#), [1396](#), [1399](#)* [1402](#)* [1404](#), [1414](#),
[1415](#), [1431](#), [1436](#), [1448](#), [1457](#)* [1461](#)* [1477](#), [1482](#)*
[1517](#), [1523](#), [1535](#)* [1538](#), [1539](#), [1540](#), [1541](#), [1542](#),
[1543](#), [1545](#), [1547](#), [1549](#), [1550](#), [1552](#), [1553](#), [1554](#),
[1555](#), [1556](#), [1559](#), [1561](#), [1562](#), [1564](#), [1565](#), [1566](#),
[1568](#), [1569](#), [1570](#), [1573](#), [1575](#), [1576](#), [1581](#), [1589](#),
[1590](#), [1591](#), [1592](#), [1594](#), [1595](#), [1596](#), [1597](#), [1598](#),
[1599](#), [1600](#), [1601](#), [1616](#)* [1618](#)* [1619](#)* [1623](#)* [1630](#),
[1636](#), [1640](#), [1646](#), [1649](#)* [1657](#), [1663](#), [1680](#), [1757](#),
[1768](#), [1769](#), [1775](#), [1776](#), [1778](#), [1791](#), [1794](#), [1798](#),
[1800](#), [1820](#), [1826](#), [1828](#), [1831](#), [1840](#), [1844](#), [1857](#),
[1869](#)* [1881](#)* [1885](#)* [1895](#)* [1900](#)* [1904](#)*
true: [479](#).
try_break: [1004](#), [1005](#), [1015](#), [1027](#), [1034](#), [1038](#),
[1042](#), [1044](#), [1045](#), [1049](#), [1055](#).
try_prev_break: [999](#), [1039](#).
two: [101](#), [102](#).
two_choices: [131](#)*.
two_halves: [136](#), [142](#), [190](#), [239](#), [274](#)* [275](#), [860](#),
[1487](#)* [1513](#)*.
two_to_the: [117](#), [118](#), [120](#).
tx: [439](#), [450](#), [1257](#), [1258](#), [1259](#), [1283](#).
type: [4](#)*, [151](#), [152](#), [153](#)* [154](#), [155](#), [156](#)* [157](#), [158](#),
[159](#)* [160](#), [161](#), [162](#)* [163](#), [164](#), [165](#)* [166](#), [167](#), [168](#),
[170](#)* [171](#)* [173](#), [174](#)* [175](#), [176](#)* [177](#), [178](#), [193](#), [201](#),
[202](#), [220](#)* [224](#)* [450](#), [497](#), [498](#), [515](#), [521](#), [522](#), [523](#),
[531](#), [650](#)* [651](#)* [654](#), [656](#), [659](#), [660](#)* [663](#), [665](#), [668](#)*
[674](#), [695](#), [705](#), [732](#)* [733](#)* [736](#), [737](#), [741](#), [742](#)* [745](#),
[746](#), [751](#), [772](#), [823](#), [825](#), [827](#), [831](#), [844](#), [845](#), [846](#),
[856](#), [857](#), [858](#), [859](#), [862](#), [863](#), [864](#), [865](#), [872](#), [874](#),
[889](#), [891](#), [896](#), [897](#)* [902](#), [903](#), [904](#), [905](#), [907](#), [908](#),
[912](#), [923](#), [926](#), [928](#), [936](#), [937](#), [938](#), [943](#), [944](#), [972](#),
[975](#), [977](#), [981](#), [983](#), [985](#), [986](#), [987](#), [992](#), [995](#), [996](#),
[998](#), [1005](#), [1006](#), [1008](#), [1013](#), [1017](#), [1018](#), [1019](#),
[1020](#), [1021](#), [1032](#), [1034](#), [1035](#), [1036](#), [1037](#), [1038](#),
[1040](#), [1041](#), [1042](#), [1044](#), [1046](#), [1047](#), [1050](#), [1051](#),
[1055](#), [1057](#), [1073](#), [1074](#), [1076](#), [1080](#), [1091](#), [1145](#),
[1147](#), [1149](#), [1150](#), [1153](#), [1155](#), [1156](#), [1158](#), [1163](#),
[1165](#)* [1170](#), [1173](#), [1174](#), [1177](#), [1181](#), [1185](#), [1186](#),
[1187](#), [1188](#), [1190](#), [1191](#), [1198](#), [1217](#), [1252](#), [1258](#),
[1265](#), [1278](#)* [1279](#), [1283](#), [1288](#), [1291](#), [1299](#), [1325](#),
[1333](#), [1336](#), [1337](#), [1341](#), [1343](#), [1346](#)* [1359](#), [1363](#),
[1364](#), [1369](#), [1380](#), [1381](#), [1522](#)* [1530](#), [1574](#), [1636](#),
[1637](#), [1638](#)* [1680](#), [1692](#)* [1700](#), [1705](#), [1708](#), [1712](#),
[1718](#), [1720](#), [1726](#)* [1729](#), [1734](#)* [1739](#)* [1740](#)* [1747](#),
[1778](#), [1789](#), [1790](#), [1816](#), [1900](#)* [1901](#)* [1930](#)*
Type <return> to proceed...: [85](#).
u: [69](#), [107](#), [127](#), [415](#), [496](#), [586](#)* [689](#), [706](#), [882](#), [967](#),
[976](#), [1106](#), [1111](#)* [1121](#)* [1435](#)* [1745](#).
u_part: [944](#), [945](#), [955](#), [964](#), [970](#), [977](#).
u_template: [329](#), [336](#), [346](#)* [964](#).
uc_code: [248](#)* [250](#), [433](#).
\uccode primitive: [1408](#)*.
uc_code_base: [248](#)* [253](#), [1408](#)* [1409](#)* [1464](#), [1466](#).
uc_hyph: [254](#)* [1068](#), [1073](#).
\uchyph primitive: [256](#)*.
uc_hyph_code: [254](#)* [255](#)* [256](#)*.
ucharcast: [549](#)*.
uexit: [81](#)*.
un_hbox: [226](#), [1268](#), [1285](#), [1286](#), [1287](#).
\unhbox primitive: [1285](#).
\unhcopy primitive: [1285](#).
\unkern primitive: [1285](#).
\unpenalty primitive: [1285](#).
\unskip primitive: [1285](#).
un_vbox: [226](#), [1224](#), [1272](#), [1285](#), [1286](#), [1287](#), [1862](#).
\unvbox primitive: [1285](#).
\unvcopy primitive: [1285](#).
unbalance: [415](#), [417](#), [422](#), [425](#), [499](#), [503](#), [1684](#).

- Unbalanced output routine: [346*](#), [1204](#).
- Unbalanced write...: [1620](#).
- Undefined control sequence: [396](#).
- undefined_control_sequence*: [240*](#), [250](#), [278](#), [284*](#), [290](#), [304](#), [1487*](#), [1497*](#), [1498*](#), [1513*](#).
- undefined_cs*: [228](#), [240*](#), [388*](#), [398*](#), [527*](#), [1404](#), [1405](#), [1474](#), [1487*](#), [1767](#), [1768](#).
- undefined_primitive*: [275](#), [281](#), [394](#), [395](#), [527*](#), [1223](#).
- under_noad*: [863](#), [866](#), [872](#), [874](#), [909](#), [937](#), [1334](#), [1335](#).
- Underfull \hbox...: [836](#).
- Underfull \vbox...: [850](#).
- \underline primitive: [1334](#).
- undump*: [1485*](#), [1491*](#), [1493*](#), [1498*](#), [1504*](#), [1508*](#), [1656](#).
- undump_checked_things*: [1489*](#), [1502*](#).
- undump_end*: [1485*](#).
- undump_end_end*: [1485*](#).
- undump_four_ASCII*: [1489*](#).
- undump_hh*: [1498*](#).
- undump_int*: [1485*](#), [1487*](#), [1491*](#), [1493*](#), [1496*](#), [1498*](#), [1504*](#), [1506](#), [1508*](#), [1895*](#), [1904*](#).
- undump_qqqq*: [1489*](#).
- undump_size*: [1485*](#), [1489*](#), [1500*](#), [1504*](#).
- undump_size_end*: [1485*](#).
- undump_size_end_end*: [1485*](#).
- undump_things*: [1487*](#), [1489*](#), [1491*](#), [1496*](#), [1498*](#), [1500*](#), [1502*](#), [1504*](#), [1876*](#), [1904*](#).
- undump_upper_check_things*: [1502*](#), [1504*](#).
- undumpimagemeta*: [1506](#).
- undumptonicode*: [1506](#).
- unescapehex*: [497](#).
- \unexpanded primitive: [1687](#).
- unfloat*: [109*](#), [834](#), [840](#), [849](#), [852](#), [986](#), [987](#).
- unhyphenated*: [995](#), [1005](#), [1013](#), [1040](#), [1042](#), [1044](#).
- unif_rand*: [126](#), [498](#).
- \pdfuniformdeviate primitive: [494](#).
- uniform_deviate_code*: [494](#), [495](#), [497](#), [498](#).
- unity*: [101](#), [103](#), [119](#), [132](#), [182](#), [204*](#), [479](#), [594](#), [1437](#).
- Unknown color stack: [1540](#).
- \unless primitive: [1763](#).
- unless_code*: [513](#), [514](#), [524](#), [1669](#), [1766](#).
- unpackage*: [1287](#), [1288](#).
- unsave*: [303](#), [305*](#), [967](#), [976](#), [1203*](#), [1241](#), [1246](#), [1264](#), [1278*](#), [1297](#), [1311*](#), [1346*](#), [1352](#), [1364](#), [1369](#), [1372](#), [1374](#), [1378](#).
- unset_node*: [177](#), [193](#), [201](#), [202](#), [220*](#), [224*](#), [450](#), [825](#), [845](#), [858](#), [864](#), [865](#), [944](#), [972](#), [975](#), [977](#), [981](#).
- unsigned*: [1502*](#).
- unspecified_mode*: [73*](#), [74*](#), [1508*](#).
- update_active*: [1037](#).
- update_adjust_list*: [831](#).
- update_heights*: [1147](#), [1149](#), [1150](#), [1171](#), [1174](#), [1177](#).
- update_image_procset*: [767](#).
- update_terminal*: [34*](#), [37*](#), [61*](#), [71*](#), [81*](#), [86](#), [384](#), [550*](#), [563*](#), [666*](#), [674](#), [714](#), [750*](#), [1458*](#), [1519*](#), [1756*](#).
- update_width*: [1008](#), [1036](#).
- \uppercase primitive: [1464](#).
- Use of x doesn't match...: [424](#).
- use_err_help*: [79](#), [80](#), [89](#), [90](#), [1461*](#).
- v*: [69](#), [107](#), [415](#), [476](#), [689](#), [882](#), [891](#), [912](#), [919](#), [925*](#), [976](#), [1006](#), [1099](#), [1111*](#), [1121*](#), [1137*](#), [1154](#), [1316](#), [1680](#).
- v_offset*: [265](#), [644](#), [668*](#), [669](#), [755](#).
- \voffset primitive: [266](#).
- v_offset_code*: [265](#), [266](#).
- v_out*: [692](#), [693](#).
- v_part*: [944](#), [945](#), [955](#), [965](#), [970](#), [977](#).
- v_template*: [329](#), [336](#), [347*](#), [416*](#), [965](#), [1309](#).
- vacuous*: [466](#), [470](#), [471](#).
- vadjust*: [226](#), [287*](#), [288*](#), [1275](#), [1276](#), [1277](#), [1278*](#).
- \vadjust primitive: [287*](#).
- val*: [682](#).
- valign*: [226](#), [287*](#), [288*](#), [1224](#), [1268](#), [1308*](#), [1701](#), [1702](#).
- \valign primitive: [287*](#).
- var_code*: [250](#), [1329](#), [1333](#), [1343](#).
- var_delimiter*: [882](#), [913](#), [924](#), [938](#).
- var_used*: [135](#), [143*](#), [148](#), [182](#), [667](#), [1490*](#), [1491*](#).
- vbadness*: [254*](#), [850](#), [853](#), [854](#), [1189](#), [1194](#).
- \vbadness primitive: [256*](#).
- vbadness_code*: [254*](#), [255*](#), [256*](#).
- \vbox primitive: [1249](#).
- vbox_group*: [291](#), [1261](#), [1263*](#), [1662](#), [1680](#).
- vcenter*: [226](#), [287*](#), [288*](#), [1224](#), [1345*](#).
- \vcenter primitive: [287*](#).
- vcenter_group*: [291](#), [1345*](#), [1346*](#), [1662](#), [1680](#).
- vcenter_noad*: [863](#), [866](#), [872](#), [874](#), [909](#), [937](#), [1346*](#).
- version_string*: [61*](#), [562*](#).
- vert_break*: [1147](#), [1148](#), [1153](#), [1154](#), [1157](#), [1159](#), [1187](#).
- very_loose_fit*: [993](#), [995](#), [1006](#), [1009](#), [1010](#), [1012](#), [1028](#), [1843](#), [1848](#).
- vet_glue*: [653](#), [662](#), [735](#), [744](#), [1639](#).
- vf_alpha*: [706](#).
- vf_b_open_in*: [713](#).
- vf_beta*: [706](#).
- vf_byte*: [712](#), [714](#), [715](#), [717](#).
- vf_cur_s*: [721](#), [723](#), [724](#), [725](#).
- vf_def_font*: [712](#), [715](#).
- vf_default_font*: [705](#), [706](#), [710](#), [715](#), [719](#), [720](#), [725](#), [726](#), [1502*](#), [1518*](#).
- vf_e_fnts*: [706](#), [710](#), [715](#), [719](#), [720](#), [726](#), [1502*](#), [1518*](#).
- vf_error*: [710](#), [712](#).
- vf_expand_local_fonts*: [705](#).
- vf_f*: [725](#), [726](#).

- vf_file*: [710](#), [712](#), [713](#).
vf_i_fnts: [705](#), [706](#), [710](#), [715](#), [720](#), [725](#), [726](#),
[1502*](#), [1518*](#).
vf_id: [710](#), [714](#).
vf_local_font_num: [705](#), [706](#), [710](#), [715](#), [719](#), [720](#),
[726](#), [1502*](#), [1518*](#).
vf_local_font_warning: [712](#).
vf_max_packet_length: [710](#), [717](#), [719](#).
vf_max_recursion: [721](#), [723](#), [725](#).
vf_nf: [706](#), [710](#), [711](#), [715](#), [720](#).
vf_packet_base: [706](#), [710](#), [716](#), [720](#), [1502*](#), [1518*](#).
vf_packet_length: [710](#), [725](#).
vf_read_signed: [712](#), [714](#), [717](#).
vf_read_unsigned: [712](#), [715](#), [717](#), [719](#).
vf_replace_z: [706](#).
vf_stack: [723](#), [726](#).
vf_stack_index: [712](#), [722](#), [723](#).
vf_stack_ptr: [723](#), [724](#), [726](#).
vf_stack_record: [722](#), [723](#).
vf_stack_size: [719](#), [721](#), [722](#).
vf_z: [706](#).
`\vfil` primitive: [1236](#).
`\vfilneg` primitive: [1236](#).
`\vfill` primitive: [1236](#).
vfuzz: [265](#), [853](#), [1189](#), [1194](#).
`\vfuzz` primitive: [266](#).
vfuzz_code: [265](#), [266](#).
VIRTEX: [1512](#).
virtual memory: [144](#).
virtual_font_type: [703](#), [705](#), [706](#), [712](#), [720](#), [726](#).
Vitter, Jeffrey Scott: [280](#).
vlist_node: [155](#), [166](#), [177](#), [193](#), [201](#), [202](#), [220*](#), [224*](#),
[531](#), [646](#), [650*](#), [651*](#), [656](#), [657*](#), [659](#), [660*](#), [665](#), [668*](#),
[732*](#), [733*](#), [737](#), [741](#), [742*](#), [746](#), [751](#), [816](#), [825](#),
[844](#), [845](#), [857](#), [889](#), [891](#), [896](#), [912](#), [923](#), [926](#),
[983](#), [985](#), [987](#), [1017](#), [1018](#), [1042](#), [1046](#), [1047](#),
[1145](#), [1150](#), [1155](#), [1177](#), [1252](#), [1258](#), [1265](#), [1288](#),
[1325](#), [1638*](#), [1726*](#), [1734*](#), [1930*](#).
vlist_out: [619*](#), [642](#), [643](#), [646](#), [647*](#), [651*](#), [656](#), [657*](#),
[660*](#), [665](#), [666*](#), [668*](#), [727](#), [728](#), [869](#), [1621*](#).
vmode: [229*](#), [233*](#), [442](#), [443](#), [444](#), [448](#), [450](#), [527*](#), [951](#),
[961](#), [962](#), [980](#), [983](#), [984](#), [985](#), [988](#), [1202](#), [1206](#),
[1223](#), [1224](#), [1226](#), [1234](#), [1235](#), [1249](#), [1250](#), [1251](#),
[1254](#), [1256](#), [1257](#), [1258](#), [1261](#), [1268](#), [1269*](#), [1272](#),
[1276](#), [1277](#), [1281](#), [1283](#), [1287](#), [1288](#), [1289](#), [1308*](#),
[1345*](#), [1421](#), [1422](#), [1561](#), [1562](#), [1680](#), [1682](#).
vmove: [226](#), [1226](#), [1249](#), [1250](#), [1251](#), [1682](#).
vpack: [254*](#), [816](#), [817](#), [818](#), [844](#), [881](#), [911](#), [914](#), [935](#),
[975](#), [980](#), [1154](#), [1198](#), [1278*](#), [1346*](#).
vpackage: [844](#), [972](#), [1154](#), [1194](#), [1264](#).
vrule: [226](#), [287*](#), [288*](#), [489](#), [1234](#), [1262](#), [1268](#).
`\vrule` primitive: [287*](#).
vsizer: [265](#), [1157](#), [1164](#).
`\vsizer` primitive: [266](#).
vsizer_code: [265](#), [266](#).
vskip: [226](#), [1224](#), [1235](#), [1236](#), [1237](#), [1256](#), [1272](#).
`\vskip` primitive: [1236](#).
vsplit: [1144](#), [1154](#), [1155](#), [1157](#), [1260](#), [1810](#),
[1826](#), [1827](#).
`\vsplit needs a \vbox`: [1155](#).
`\vsplit` primitive: [1249](#).
vsplit_code: [1249](#), [1250](#), [1257](#), [1516*](#), [1860](#), [1862](#),
[1863](#).
vsplit_init: [1154](#), [1826](#), [1827](#).
`\vss` primitive: [1236](#).
`\vtop` primitive: [1249](#).
vtop_code: [1249](#), [1250](#), [1261](#), [1263*](#), [1264](#).
vtop_group: [291](#), [1261](#), [1263*](#), [1662](#), [1680](#).
w: [132](#), [165*](#), [174*](#), [297](#), [300](#), [301](#), [634](#), [690](#), [823](#),
[844](#), [882](#), [891](#), [914](#), [967](#), [976](#), [1083](#), [1171](#), [1301](#),
[1316](#), [1376](#), [1414](#), [1530](#), [1531*](#), [1684](#), [1720](#), [1754](#),
[1757](#), [1775](#), [1777](#), [1820](#), [1840](#), [1841](#).
w_close: [1510](#), [1518*](#).
w_make_name_string: [551*](#), [1509](#).
w_open_in: [550*](#).
w_open_out: [1509](#).
wait: [1189](#), [1197](#), [1198](#), [1199](#).
wake_up_terminal: [34*](#), [37*](#), [51*](#), [71*](#), [73*](#), [385*](#), [510*](#), [550*](#),
[556*](#), [686](#), [1473*](#), [1476*](#), [1482*](#), [1487*](#), [1514*](#), [1519*](#).
warn: [693](#).
warn_dest_dup: [1565](#), [1566](#), [1638*](#).
warn_pdffpagebox: [1551](#), [1552](#), [1553](#).
Warning: end of file when...: [1778](#).
Warning: end of...: [1775](#), [1777](#).
warning_index: [327](#), [353*](#), [360*](#), [415](#), [416*](#), [421](#),
[422](#), [424](#), [427*](#), [497](#), [499](#), [505](#), [508](#), [552*](#), [950](#),
[953](#), [1684](#), [1881*](#).
warning_issued: [76](#), [81*](#), [263](#), [686](#), [1516*](#), [1775](#),
[1777](#), [1778](#).
was_free: [183*](#), [185](#), [189](#).
was_hi_min: [183*](#), [184](#), [185](#), [189](#).
was_lo_max: [183*](#), [184](#), [185](#), [189](#).
was_mem_end: [183*](#), [184](#), [185](#), [189](#).
`\wd` primitive: [442](#).
WEB: [1](#), [4*](#), [38*](#), [40](#), [50](#), [1487*](#).
web2c_int_base: [254*](#).
web2c_int_pars: [254*](#).
what_lang: [1522*](#), [1604*](#), [1610](#), [1611](#), [1625](#), [1626](#).
what_lhm: [1522*](#), [1604*](#), [1610](#), [1611](#), [1625](#), [1626](#).
what_rhm: [1522*](#), [1604*](#), [1610](#), [1611](#), [1625](#), [1626](#).
whatsit_node: [164](#), [166](#), [193](#), [201](#), [220*](#), [224*](#), [650*](#),
[659](#), [732*](#), [741](#), [772](#), [825](#), [845](#), [906](#), [937](#), [1005](#),
[1042](#), [1073](#), [1076](#), [1145](#), [1150](#), [1177](#), [1325](#), [1522*](#),
[1530](#), [1574](#), [1636](#), [1638*](#), [1701](#), [1734*](#).

- `\widowpenalties` primitive: [1865](#).
- `widow_penalties_loc`: [248*](#), [1865](#), [1866](#).
- `widow_penalties_ptr`: [1067](#), [1865](#).
- `widow_penalty`: [254*](#), [990](#), [1067](#).
- `\widowpenalty` primitive: [256*](#)
- `widow_penalty_code`: [254*](#), [255*](#), [256*](#)
- `width`: [489](#).
- `width`: [153*](#), [154](#), [156*](#), [157](#), [165*](#), [168](#), [169](#), [173](#), [174*](#), [196](#), [201](#), [202](#), [205](#), [209](#), [210](#), [450](#), [455](#), [457](#), [477](#), [488](#), [489](#), [498](#), [580*](#), [632](#), [634](#), [638](#), [644](#), [650*](#), [651*](#), [653](#), [654](#), [659](#), [661](#), [662](#), [663](#), [669](#), [705](#), [732*](#), [733*](#), [735](#), [736](#), [741](#), [743](#), [744](#), [745](#), [752](#), [755](#), [823](#), [825](#), [827](#), [832](#), [833](#), [842](#), [844](#), [845](#), [846](#), [847](#), [855](#), [859](#), [864](#), [882](#), [885](#), [890](#), [891](#), [892](#), [893](#), [907](#), [914](#), [920](#), [923](#), [925*](#), [926](#), [933](#), [934](#), [935](#), [944](#), [955](#), [969](#), [972](#), [973](#), [974](#), [977](#), [978](#), [979](#), [980](#), [982](#), [983](#), [984](#), [985](#), [986](#), [987](#), [1003](#), [1005](#), [1013](#), [1014](#), [1017](#), [1018](#), [1042](#), [1044](#), [1046](#), [1047](#), [1057](#), [1146](#), [1153](#), [1173](#), [1178](#), [1181](#), [1186](#), [1220](#), [1222](#), [1232](#), [1269*](#), [1271](#), [1325](#), [1326](#), [1377](#), [1379](#), [1383](#), [1407](#), [1417](#), [1418](#), [1549](#), [1553](#), [1557](#), [1566](#), [1574](#), [1631](#), [1638*](#), [1639](#), [1700](#), [1715](#), [1717](#), [1720](#), [1721](#), [1722*](#), [1723*](#), [1726*](#), [1729](#), [1730*](#), [1735](#), [1737](#), [1739*](#), [1740*](#), [1741](#), [1746](#), [1747](#), [1781](#), [1791](#), [1795](#), [1796](#), [1797](#), [1799](#), [1854](#).
- `width_base`: [576*](#), [580*](#), [592](#), [595](#), [598](#), [603*](#), [705](#), [706](#), [1501*](#), [1502*](#), [1518*](#)
- `width_index`: [569](#), [576*](#)
- `width_offset`: [153*](#), [442](#), [443](#), [1425](#).
- Wirth, Niklaus: [10](#).
- `wlog`: [56](#), [58](#), [560*](#), [562*](#), [1514*](#), [1515*](#)
- `wlog_cr`: [56](#), [57](#), [58](#), [560*](#), [562*](#), [1514*](#)
- `wlog_ln`: [56](#), [1514*](#), [1515*](#)
- `word_define`: [1392](#), [1402*](#), [1406](#), [1410*](#), [1840](#).
- `word_file`: [25](#), [131*](#), [551*](#), [1484*](#)
- `word_node_size`: [1821](#), [1822](#), [1838](#), [1842](#).
- `words`: [222](#), [223](#), [224*](#), [1605](#), [1734*](#)
- `wrap_lig`: [1087*](#), [1088](#).
- `wrapup`: [1212](#), [1217](#), [1218](#).
- `write`: [37*](#), [56](#), [58](#), [624*](#), [1485*](#)
- `\write` primitive: [1525*](#)
- `write_action`: [782](#), [1564](#), [1580](#), [1631](#).
- `write_dvi`: [624*](#), [625*](#), [626*](#), [668*](#)
- `write_file`: [57](#), [58](#), [1523](#), [1623*](#), [1627](#).
- `write_fontstuff`: [801](#).
- `write_image`: [778](#).
- `write_ln`: [37*](#), [51*](#), [56](#), [57](#), [1485*](#), [1871*](#)
- `write_loc`: [1492](#), [1493*](#), [1525*](#), [1526](#), [1619*](#)
- `write_mubyte`: [1522*](#), [1531*](#), [1535*](#), [1603*](#), [1604*](#), [1616*](#), [1618*](#)
- `write_node`: [1522*](#), [1525*](#), [1527](#), [1529*](#), [1604*](#), [1605](#), [1606](#), [1621*](#), [1623*](#)
- `write_node_size`: [1522*](#), [1531*](#), [1533](#), [1534](#), [1535*](#), [1539](#), [1605](#), [1606](#), [1940*](#)
- `write_noexpanding`: [20*](#), [23*](#), [376*](#), [379*](#), [1535*](#), [1618*](#)
- `write_open`: [1472*](#), [1523](#), [1524](#), [1618*](#), [1623*](#), [1627](#).
- `write_out`: [1618*](#), [1623*](#)
- `write_pdf`: [685](#).
- `write_stream`: [1522*](#), [1531*](#), [1535*](#), [1603*](#), [1604*](#), [1616*](#), [1618*](#), [1623*](#), [1940*](#)
- `write_stream_length`: [685](#).
- `write_text`: [329](#), [336](#), [345](#), [1521](#), [1619*](#)
- `write_tokens`: [727](#), [1522*](#), [1533](#), [1534](#), [1535*](#), [1604*](#), [1605](#), [1606](#), [1616*](#), [1619*](#), [1940*](#)
- `write_zip`: [685](#).
- `writing`: [605](#).
- `wterm`: [56](#), [58](#), [61*](#), [550*](#), [1518*](#)
- `wterm_cr`: [56](#), [57](#), [58](#).
- `wterm_ln`: [56](#), [61*](#), [550*](#), [1482*](#), [1487*](#), [1513*](#), [1518*](#)
- Wyatt, Douglas Kirk: [2*](#)
- `w0`: [612](#), [613](#), [631](#), [636](#), [719](#), [726](#).
- `w1`: [612](#), [613](#), [634](#), [719](#), [726](#).
- `w2`: [612](#).
- `w3`: [612](#).
- `w4`: [612](#).
- `x`: [100](#), [105](#), [106](#), [107](#), [119](#), [124](#), [126](#), [127](#), [614](#), [627](#), [689](#), [823](#), [844](#), [882](#), [896](#), [902](#), [911](#), [913](#), [914](#), [919](#), [925*](#), [932](#), [1301](#), [1316](#), [1481*](#), [1482*](#), [1553](#), [1745](#), [1794](#), [1800](#).
- `x_height`: [573](#), [584](#), [585](#), [673*](#), [914](#), [1301](#), [1892*](#), [1893*](#)
- `x_height_code`: [573](#), [584](#).
- `x_leaders`: [167](#), [208](#), [655](#), [1249](#), [1250](#).
- `\xleaders` primitive: [1249](#).
- `x_over_n`: [106](#), [879](#), [892](#), [893](#), [1163](#), [1185](#), [1186](#), [1187](#), [1418](#).
- `x_token`: [386](#), [407](#), [504](#), [1215](#), [1330](#).
- `xchr`: [20*](#), [21](#), [23*](#), [24*](#), [38*](#), [49*](#), [58](#), [440*](#), [545*](#), [1410*](#), [1616*](#), [1618*](#), [1875*](#), [1876*](#)
- `\xchr` primitive: [1408*](#)
- `xchr_code_base`: [248*](#), [440*](#), [1408*](#), [1409*](#), [1410*](#)
- `xclause`: [16*](#)
- `\xdef` primitive: [1386](#).
- `xreq_level`: [271*](#), [272](#), [290](#), [300](#), [301](#), [305*](#), [1483](#).
- `xmalloc_array`: [545*](#), [549*](#), [1486*](#), [1487*](#), [1489*](#), [1500*](#), [1502*](#), [1504*](#), [1513*](#), [1518*](#)
- `xn_over_d`: [107](#), [481](#), [483](#), [484](#), [594](#), [892](#), [1222](#), [1438*](#)
- `xord`: [20*](#), [24*](#), [440*](#), [549*](#), [551*](#), [1410*](#), [1875*](#), [1876*](#)
- `\xord` primitive: [1408*](#)
- `xord_code_base`: [248*](#), [440*](#), [1408*](#), [1409*](#), [1410*](#)
- `xpand`: [499](#), [503](#), [505](#).
- `xprn`: [20*](#), [24*](#), [59*](#), [440*](#), [1410*](#), [1875*](#), [1876*](#)
- `\xprn` primitive: [1408*](#)
- `xprn_code_base`: [248*](#), [440*](#), [1408*](#), [1409*](#), [1410*](#)

xr: 1553.
xray: [226](#), [1468](#), [1469](#), [1470](#), [1676](#), [1685](#), [1690](#).
xrealloc_array: [678](#), [686](#), [698](#), [1506](#).
xref_offset_width: [814](#), [1514](#)*.
xspace_skip: [242](#), [1221](#).
\xspaceskip primitive: [244](#).
xspace_skip_code: [242](#), [243](#), [244](#), [1221](#).
xxx1: [612](#), [613](#), [719](#), [726](#), [1616](#)*.
xxx2: [612](#).
xxx3: [612](#).
xxx4: [612](#), [613](#), [1616](#)*.
x0: [612](#), [613](#), [631](#), [636](#), [719](#), [726](#).
x1: [612](#), [613](#), [634](#), [719](#), [726](#).
x2: [612](#).
x3: [612](#).
x4: [612](#).
y: [105](#), [119](#), [126](#), [882](#), [902](#), [911](#), [913](#), [914](#), [919](#),
[925](#)*, [932](#), [1794](#).
y_here: [635](#), [636](#), [638](#), [639](#), [640](#).
y_OK: [635](#), [636](#), [639](#).
y_seen: [638](#), [639](#).
year: [254](#)*, [259](#)*, [645](#)*, [792](#), [1509](#).
\year primitive: [256](#)*.
year_code: [254](#)*, [255](#)*, [256](#)*.
yhash: [274](#)*, [1487](#)*, [1513](#)*.
You already have nine...: [502](#).
You can't `\insert255`: [1277](#).
You can't dump...: [1483](#).
You can't use `\hrule`...: [1273](#).
You can't use `\long`...: [1391](#).
You can't use `\unless`...: [1766](#).
You can't use a prefix with `x`: [1390](#).
You can't use `x` after ...: [454](#), [1415](#).
You can't use `x` in `y` mode: [1227](#)*.
you_cant: [1227](#)*, [1228](#), [1258](#), [1284](#).
yr: 1553.
yz_OK: [635](#), [636](#), [637](#), [639](#).
yzmem: [134](#)*, [1487](#)*, [1513](#)*.
y0: [612](#), [613](#), [621](#), [631](#), [636](#), [719](#), [726](#).
y1: [612](#), [613](#), [634](#), [640](#), [719](#), [726](#).
y2: [612](#), [621](#).
y3: [612](#).
y4: [612](#).
z: [119](#), [586](#)*, [882](#), [902](#), [919](#), [925](#)*, [932](#), [1099](#), [1104](#),
[1130](#), [1136](#), [1376](#), [1745](#).
z_here: [635](#), [636](#), [638](#), [639](#), [641](#).
z_OK: [635](#), [636](#), [639](#).
z_seen: [638](#), [639](#).
Zabala Salelles, Ignacio Andrés: [2](#)*.
zeqtb: [271](#)*, [1487](#)*, [1513](#)*, [1518](#)*.
zero_glue: [180](#), [193](#), [242](#), [246](#), [450](#), [453](#), [488](#), [908](#),
[978](#), [1005](#), [1063](#), [1219](#), [1220](#), [1221](#), [1349](#), [1407](#),
[1741](#), [1783](#), [1791](#), [1810](#), [1821](#), [1822](#).
zero_token: [471](#), [478](#), [499](#), [502](#), [505](#).
zip_finish: [680](#), [685](#).
zip_write_state: [679](#), [680](#), [681](#), [685](#).
zip_writing: [680](#), [685](#).
zmem: [134](#)*, [1487](#)*, [1513](#)*.
z0: [612](#), [613](#), [631](#), [636](#), [719](#), [726](#).
z1: [612](#), [613](#), [634](#), [641](#), [719](#), [726](#).
z2: [612](#).
z3: [612](#).
z4: [612](#).

- < (pdfTeX) Move down or output leaders 744 > Used in section 741.
- < (pdfTeX) Move right or output leaders 735 > Used in section 732*.
- < (pdfTeX) Output a box in a vlist 742* > Used in section 741.
- < (pdfTeX) Output a box in an hlist 733* > Used in section 732*.
- < (pdfTeX) Output a leader box at *cur_h*, then advance *cur_h* by *leader_wd + lx* 737 > Used in section 736.
- < (pdfTeX) Output a leader box at *cur_v*, then advance *cur_v* by *leader_ht + lx* 746 > Used in section 745.
- < (pdfTeX) Output a rule in a vlist, **goto** *next_p* 743 > Used in section 741.
- < (pdfTeX) Output a rule in an hlist 734 > Used in section 732*.
- < (pdfTeX) Output a substitution, **goto** *continue* if not possible 1888* > Used in section 731*.
- < (pdfTeX) Output leaders in a vlist, **goto** *fin_rule* if a rule or to *next_p* if done 745 > Used in section 744.
- < (pdfTeX) Output leaders in an hlist, **goto** *fin_rule* if a rule or to *next_p* if done 736 > Used in section 735.
- < (pdfTeX) Rebuild character using substitution information 1893* > Used in section 1888*.
- < (pdfTeX) Ship box *p* out 751 > Used in section 750*.
- < Accumulate the constant until *cur_tok* is not a suitable digit 471 > Used in section 470.
- < Add the width of node *s* to *act_width* 1047 > Used in section 1045.
- < Add the width of node *s* to *break_width* 1018 > Used in section 1016.
- < Add the width of node *s* to *disc_width* 1046 > Used in section 1045.
- < Adjust for the magnification ratio 483 > Used in section 479.
- < Adjust for the setting of `\globaldefs` 1392 > Used in section 1389*.
- < Adjust *shift_up* and *shift_down* for the case of a fraction line 922 > Used in section 919.
- < Adjust *shift_up* and *shift_down* for the case of no fraction line 921 > Used in section 919.
- < Adjust the LR stack for the *hlist_out* routine; if necessary reverse an hlist segment and **goto** *reswitch* 1718 >
Used in section 1717.
- < Adjust the LR stack for the *hpack* routine 1712 > Used in section 825.
- < Adjust the LR stack for the *init_math* routine 1738 > Used in section 1737.
- < Adjust the LR stack for the *just_reverse* routine 1740* > Used in section 1739*.
- < Adjust the LR stack for the *post_line_break* routine 1709 > Used in sections 1055, 1057, and 1708.
- < Adjust the additional data for last line 1850 > Used in section 1027.
- < Adjust the final line of the paragraph 1854 > Used in section 1039.
- < Adjust transformation matrix for the magnification ratio 758 > Used in section 757.
- < Adjust *selector* based on *show_stream* 1472* > Used in sections 1471*, 1473*, 1475*, 1476*, 1678*, and 1692*.
- < Advance *cur_p* to the node following the present string of characters 1043 > Used in section 1042.
- < Advance past a whatsit node in the *line_break* loop 1610 > Used in section 1042.
- < Advance past a whatsit node in the pre-hyphenation loop 1611 > Used in section 1073.
- < Advance *r*; **goto** *found* if the parameter delimiter has been fully matched, otherwise **goto** *continue* 420 >
Used in section 418.
- < Allocate entire node *p* and **goto** *found* 147 > Used in section 145.
- < Allocate from the top of node *p* and **goto** *found* 146 > Used in section 145.
- < Allocate memory for the new virtual font 716 > Used in section 712.
- < Apologize for inability to do the operation now, unless `\unskip` follows non-glue 1284 > Used in section 1283.
- < Apologize for not loading the font, **goto** *done* 593 > Used in section 592.
- < Append a ligature and/or kern to the translation; **goto** *continue* if the stack of inserted ligatures is nonempty 1087* > Used in section 1083.
- < Append a new leader node that uses *cur_box* 1256 > Used in section 1253.
- < Append a new letter or a hyphen level 1139 > Used in section 1138.
- < Append a new letter or hyphen 1114 > Used in section 1112.
- < Append a normal inter-word space to the current list, then **goto** *big_switch* 1219 > Used in section 1207.
- < Append a penalty node, if a nonzero penalty is appropriate 1067 > Used in section 1056.
- < Append an insertion to the current page and **goto** *contribute* 1185 > Used in section 1177.
- < Append any *new_hlist* entries for *q*, and any appropriate penalties 943 > Used in section 936.
- < Append box *cur_box* to the current list, shifted by *box_context* 1254 > Used in section 1253.

- < Append character *cur_chr* and the following characters (if any) to the current hlist in the current font; **goto** *reswitch* when a non-character has been fetched 1211* > Used in section 1207.
- < Append characters of *hu[j ..]* to *major_tail*, advancing *j* 1094 > Used in section 1093.
- < Append inter-element spacing based on *r_type* and *t* 942 > Used in section 936.
- < Append tabskip glue and an empty box to list *u*, and update *s* and *t* as the prototype nodes are passed 985 > Used in section 984.
- < Append the accent with appropriate kerns, then set $p \leftarrow q$ 1303 > Used in section 1301.
- < Append the current tabskip glue to the preamble list 954 > Used in section 953.
- < Append the display and perhaps also the equation number 1382 > Used in section 1377.
- < Append the glue or equation number following the display 1383 > Used in section 1377.
- < Append the glue or equation number preceding the display 1381 > Used in section 1377.
- < Append the new box to the current vertical list, followed by the list of special nodes taken out of the box by the packager 1065 > Used in section 1056.
- < Append the value *n* to list *p* 1115 > Used in section 1114.
- < Assign the values *depth_threshold* \leftarrow *show_box_depth* and *breadth_max* \leftarrow *show_box_breadth* 254* > Used in section 216.
- < Assignments 1395, 1396, 1399*, 1402*, 1403, 1404, 1406, 1410*, 1412, 1413, 1419, 1420, 1426, 1430*, 1431, 1434, 1442 > Used in section 1389*.
- < Attach list *p* to the current list, and record its length; then finish up and **return** 1298 > Used in section 1297.
- < Attach the limits to *y* and adjust *height(v)*, *depth(v)* to account for their presence 927 > Used in section 926.
- < Back up an outer control sequence so that it can be reread 359 > Used in section 358.
- < Basic printing procedures 57, 58, 59*, 60, 62*, 63, 64, 65, 284*, 285, 544*, 875, 1603*, 1823, 1871*, 1873*, 1900*, 1902* > Used in section 4*.
- < Break the current page at node *p*, put it in box 255, and put the remaining nodes on the contribution list 1194 > Used in section 1191.
- < Break the paragraph at the chosen breakpoints, justify the resulting lines to the correct widths, and append them to the current vertical list 1052 > Used in section 991.
- < Build a character packet 717 > Used in section 712.
- < Build a linked list of free objects 812 > Used in sections 813 and 814.
- < Calculate DVI page dimensions and margins 644 > Used in section 645*.
- < Calculate page dimensions and margins 755 > Used in section 752.
- < Calculate the length, *l*, and the shift amount, *s*, of the display lines 1327 > Used in section 1323.
- < Calculate the natural width, *w*, by which the characters of the final line extend to the right of the reference point, plus two ems; or set $w \leftarrow max_dimen$ if the non-blank information on that line is affected by stretching or shrinking 1324 > Used in section 1323.
- < Calculate variations of marginal kerns 822 > Used in section 1027.
- < Call the packaging subroutine, setting *just_box* to the justified box 1066 > Used in section 1056.
- < Call *try_break* if *cur_p* is a legal breakpoint; on the second pass, also try to hyphenate the next word, if *cur_p* is a glue node; then advance *cur_p* to the next node of the paragraph that could possibly be a legal breakpoint 1042 > Used in section 1039.
- < Carry out a ligature replacement, updating the cursor structure and possibly advancing *j*; **goto** *continue* if the cursor doesn't advance, otherwise **goto** *done* 1088 > Used in section 1086.
- < Case statement to copy different types and set *words* to the number of initial words not yet copied 224* > Used in section 223.
- < Cases for 'Fetch the *dead_cycles* or the *insert_penalties*' 1695 > Used in section 445.
- < Cases for evaluation of the current term 1792, 1796, 1797, 1799 > Used in section 1784.
- < Cases for fetching a dimension value 1672, 1675, 1805 > Used in section 450.
- < Cases for fetching a glue value 1808 > Used in section 1781.
- < Cases for fetching a mu value 1809 > Used in section 1781.
- < Cases for fetching an integer value 1652, 1666, 1669, 1804 > Used in section 450.
- < Cases for noads that can follow a *bin_noad* 909 > Used in section 904.
- < Cases for nodes that can appear in an mlist, after which we **goto** *done_with_node* 906 > Used in section 904.

- ⟨ Cases for *alter_integer* 1697 ⟩ Used in section 1424.
- ⟨ Cases for *conditional* 1767, 1768, 1770 ⟩ Used in section 527*.
- ⟨ Cases for *do_marks* 1827, 1829, 1830, 1832 ⟩ Used in section 1826.
- ⟨ Cases for *eq_destroy* 1835 ⟩ Used in section 297.
- ⟨ Cases for *input* 1750 ⟩ Used in section 404.
- ⟨ Cases for *print_param* 1660, 1701 ⟩ Used in section 255*.
- ⟨ Cases for *show_whatever* 1678*, 1692* ⟩ Used in section 1471*.
- ⟨ Cases of DVI commands that can appear in character packet 719 ⟩ Used in section 717.
- ⟨ Cases of ‘Let *d* be the natural width’ that need special treatment 1737 ⟩ Used in section 1325.
- ⟨ Cases of *assign_toks* for *print_cmd_chr* 1659 ⟩ Used in section 249.
- ⟨ Cases of *expandafter* for *print_cmd_chr* 1764 ⟩ Used in section 288*.
- ⟨ Cases of *flush_node_list* that arise in mlists only 874 ⟩ Used in section 220*.
- ⟨ Cases of *handle_right_brace* where a *right_brace* triggers a delayed action 1263*, 1278*, 1296, 1310, 1311*, 1346*, 1351, 1364 ⟩ Used in section 1246.
- ⟨ Cases of *hlist_out* that arise in mixed direction text only 1721 ⟩ Used in sections 650* and 732*.
- ⟨ Cases of *if_test* for *print_cmd_chr* 1765 ⟩ Used in section 514.
- ⟨ Cases of *input* for *print_cmd_chr* 1749 ⟩ Used in section 403.
- ⟨ Cases of *last_item* for *print_cmd_chr* 1651, 1665, 1668, 1671, 1674, 1780, 1803, 1807 ⟩ Used in section 443.
- ⟨ Cases of *left_right* for *print_cmd_chr* 1699 ⟩ Used in section 1367.
- ⟨ Cases of *main_control* for *hmode* + *valign* 1704 ⟩ Used in section 1308*.
- ⟨ Cases of *main_control* that are for extensions to T_EX 1528 ⟩ Used in section 1223.
- ⟨ Cases of *main_control* that are not part of the inner loop 1223 ⟩ Used in section 1207.
- ⟨ Cases of *main_control* that build boxes and lists 1234, 1235, 1241, 1245, 1251, 1268, 1270, 1272, 1275, 1280, 1282, 1287, 1290, 1294, 1300, 1304, 1308*, 1312, 1315, 1318, 1328, 1332, 1336, 1340, 1342, 1345*, 1349, 1353, 1358, 1368, 1371 ⟩ Used in section 1223.
- ⟨ Cases of *main_control* that don’t depend on *mode* 1388, 1446, 1449*, 1452, 1454, 1463, 1468 ⟩ Used in section 1223.
- ⟨ Cases of *prefix* for *print_cmd_chr* 1772 ⟩ Used in section 1387.
- ⟨ Cases of *print_cmd_chr* for symbolic printing of primitives 245, 249, 257, 267, 288*, 357, 403, 411, 438, 443, 495, 514, 518, 957, 1161, 1231, 1237, 1250, 1267, 1286, 1293, 1321, 1335, 1348, 1357, 1367, 1387, 1398*, 1401*, 1409*, 1429, 1433, 1439, 1441, 1451, 1456, 1465, 1470, 1474, 1527 ⟩ Used in section 320.
- ⟨ Cases of *read* for *print_cmd_chr* 1761 ⟩ Used in section 288*.
- ⟨ Cases of *register* for *print_cmd_chr* 1833 ⟩ Used in section 438.
- ⟨ Cases of *reverse* that need special treatment 1727, 1728, 1729 ⟩ Used in section 1726*.
- ⟨ Cases of *set_page_int* for *print_cmd_chr* 1694 ⟩ Used in section 443.
- ⟨ Cases of *set_shape* for *print_cmd_chr* 1866 ⟩ Used in section 288*.
- ⟨ Cases of *show_node_list* that arise in mlists only 866 ⟩ Used in section 201.
- ⟨ Cases of *the* for *print_cmd_chr* 1688 ⟩ Used in section 288*.
- ⟨ Cases of *toks_register* for *print_cmd_chr* 1834 ⟩ Used in section 288*.
- ⟨ Cases of *un_vbox* for *print_cmd_chr* 1863 ⟩ Used in section 1286.
- ⟨ Cases of *valign* for *print_cmd_chr* 1703 ⟩ Used in section 288*.
- ⟨ Cases of *xray* for *print_cmd_chr* 1677, 1686, 1691 ⟩ Used in section 1470.
- ⟨ Cases where character is ignored 367 ⟩ Used in section 366.
- ⟨ Change buffered instruction to *y* or *w* and **goto found** 640 ⟩ Used in section 639.
- ⟨ Change buffered instruction to *z* or *x* and **goto found** 641 ⟩ Used in section 639.
- ⟨ Change current mode to *-vmode* for **\halign**, *-hmode* for **\valign** 951 ⟩ Used in section 950.
- ⟨ Change discretionary to compulsory and set *disc_break* ← *true* 1058 ⟩ Used in section 1057.
- ⟨ Change font *dvi_f* to *f* 649* ⟩ Used in section 648*.
- ⟨ Change state if necessary, and **goto switch** if the current character should be ignored, or **goto reswitch** if the current character changes to another 366 ⟩ Used in section 365*.
- ⟨ Change the case of the token in *p*, if a change is appropriate 1467 ⟩ Used in section 1466.
- ⟨ Change the current style and **goto delete_q** 939 ⟩ Used in section 937.
- ⟨ Change the interaction level and **return** 86 ⟩ Used in section 84*.

- < Change this node to a style node followed by the correct choice, then **goto** *done_with_node* 907 > Used in section 906.
- < Character *k* cannot be printed 49* > Used in section 48.
- < Character *s* is the current new-line character 262 > Used in sections 58 and 59*.
- < Check flags of unavailable nodes 188 > Used in section 185.
- < Check for LR anomalies at the end of *hlist_out* 1719 > Used in section 1716.
- < Check for LR anomalies at the end of *hpack* 1713 > Used in section 823.
- < Check for LR anomalies at the end of *ship_out* 1731 > Used in sections 666* and 750*.
- < Check for charlist cycle 596* > Used in section 595.
- < Check for improper alignment in displayed math 952 > Used in section 950.
- < Check for non-existing destinations 796 > Used in section 794.
- < Check for non-existing pages 799 > Used in section 794.
- < Check for non-existing structure destinations 798 > Used in section 794.
- < Check for special treatment of last line of paragraph 1844 > Used in section 1003.
- < Check if node *p* is a new champion breakpoint; then **goto** *done* if *p* is a forced break or if the page-so-far is already too full 1151 > Used in section 1149.
- < Check if node *p* is a new champion breakpoint; then if it is time for a page break, prepare for output, and either fire up the user's output routine and **return** or ship out the page and **goto** *done* 1182 > Used in section 1174.
- < Check single-word *avail* list 186 > Used in section 185.
- < Check that another \$ follows 1375 > Used in sections 1372, 1372, and 1384.
- < Check that the necessary fonts for math symbols are present; if not, flush the current math lists and set *danger* \leftarrow *true* 1373 > Used in sections 1372 and 1372.
- < Check that the nodes following *hb* permit hyphenation and that at least $L_{hyf} + r_{hyf}$ letters have been found, otherwise **goto** *done1* 1076 > Used in section 1071.
- < Check the "constant" values for consistency 14, 129*, 312*, 548, 1427 > Used in section 1513*.
- < Check variable-size *avail* list 187 > Used in section 185.
- < Clean up the memory by removing the break nodes 1041 > Used in sections 991 and 1039.
- < Clear dimensions to zero 824 > Used in sections 823 and 844.
- < Clear off top level from *save_stack* 304 > Used in section 303.
- < Close the format file 1510 > Used in section 1481*.
- < Close *SyncTEX* file and write status 1922* > Used in section 1514*.
- < Coerce glue to a dimension 477 > Used in sections 475 and 481.
- < Compiler directives 9 > Used in section 4*.
- < Complain about an undefined family and set *cur_i* null 899 > Used in section 898*.
- < Complain about an undefined macro 396 > Used in section 391.
- < Complain about missing \backslash endcsname 399 > Used in sections 398* and 1768.
- < Complain about unknown unit and **goto** *done2* 485 > Used in section 484.
- < Complain that \backslash the can't do this; give zero result 454 > Used in section 439.
- < Complain that the user should have said \backslash mathaccent 1344 > Used in section 1343.
- < Compleat the incompleat noad 1363 > Used in section 1362.
- < Complete a potentially long \backslash show command 1477 > Used in section 1471*.
- < Compute $f = \lfloor 2^{28}(1 + p/q) + \frac{1}{2} \rfloor$ 113 > Used in section 112.
- < Compute $p = \lfloor qf/2^{28} + \frac{1}{2} \rfloor - q$ 116 > Used in section 114.
- < Compute $f = \lfloor xn/d + \frac{1}{2} \rfloor$ 1801 > Used in section 1800.
- < Compute result of *multiply* or *divide*, put it in *cur_val* 1418 > Used in section 1414.
- < Compute result of *register* or *advance*, put it in *cur_val* 1416 > Used in section 1414.
- < Compute the amount of skew 917 > Used in section 914.
- < Compute the badness, *b*, of the current page, using *awful_bad* if the box is too full 1184 > Used in section 1182.
- < Compute the badness, *b*, using *awful_bad* if the box is too full 1152 > Used in section 1151.
- < Compute the demerits, *d*, from *r* to *cur_p* 1035 > Used in section 1031.
- < Compute the discretionary *break_width* values 1016 > Used in section 1013.

- ⟨ Compute the hash code h 280 ⟩ Used in section 278.
- ⟨ Compute the magic offset 941 ⟩ Used in section 1518*.
- ⟨ Compute the mark pointer for mark type t and class cur_val 1825 ⟩ Used in section 412.
- ⟨ Compute the minimum suitable height, w , and the corresponding number of extension steps, n ; also set $width(b)$ 890 ⟩ Used in section 889.
- ⟨ Compute the new line width 1026 ⟩ Used in section 1011.
- ⟨ Compute the primitive code h 283 ⟩ Used in section 281.
- ⟨ Compute the register location l and its type p ; but **return** if invalid 1415 ⟩ Used in section 1414.
- ⟨ Compute the sum of two glue specs 1417 ⟩ Used in section 1416.
- ⟨ Compute the sum or difference of two glue specs 1795 ⟩ Used in section 1793.
- ⟨ Compute the trie op code, v , and set $l \leftarrow 0$ 1142* ⟩ Used in section 1140*.
- ⟨ Compute the values of $break_width$ 1013 ⟩ Used in section 1012.
- ⟨ Consider a node with matching width; **goto found** if it's a hit 639 ⟩ Used in section 638.
- ⟨ Consider the demerits for a line from r to cur_p ; deactivate node r if it should no longer be active; then **goto continue** if a line from r to cur_p is infeasible, otherwise record a new feasible break 1027 ⟩ Used in section 1005.
- ⟨ Constants in the outer block 11*, 675, 679, 695, 721, 1632 ⟩ Used in section 4*.
- ⟨ Construct a box with limits above and below it, skewed by $delta$ 926 ⟩ Used in section 925*.
- ⟨ Construct a sub/superscript combination box x , with the superscript offset by $delta$ 935 ⟩ Used in section 932.
- ⟨ Construct a subscript box x when there is no superscript 933 ⟩ Used in section 932.
- ⟨ Construct a superscript box x 934 ⟩ Used in section 932.
- ⟨ Construct a vlist box for the fraction, according to $shift_up$ and $shift_down$ 923 ⟩ Used in section 919.
- ⟨ Construct an extensible character in a new box b , using recipe $rem_byte(q)$ and font f 889 ⟩ Used in section 886.
- ⟨ Contribute an entire group to the current parameter 425 ⟩ Used in section 418.
- ⟨ Contribute the recently matched tokens to the current parameter, and **goto continue** if a partial match is still in effect; but abort if $s = null$ 423 ⟩ Used in section 418.
- ⟨ Convert a final bin_noad to an ord_noad 905 ⟩ Used in sections 902 and 904.
- ⟨ Convert cur_val to a lower level 455 ⟩ Used in section 439.
- ⟨ Convert math glue to ordinary glue 908 ⟩ Used in section 906.
- ⟨ Convert $nucleus(q)$ to an hlist and attach the sub/superscripts 930 ⟩ Used in section 904.
- ⟨ Convert string s into a new pseudo file 1755 ⟩ Used in section 1754.
- ⟨ Copy the box $SyncTeX$ information 1936* ⟩ Used in sections 224* and 1734*.
- ⟨ Copy the medium sized node $SyncTeX$ information 1938* ⟩ Used in sections 224* and 1734*.
- ⟨ Copy the rule $SyncTeX$ information 1937* ⟩ Used in section 224*.
- ⟨ Copy the tabskip glue between columns 971 ⟩ Used in section 967.
- ⟨ Copy the templates from node cur_loop into node p 970 ⟩ Used in section 969.
- ⟨ Copy the token list 492 ⟩ Used in section 491.
- ⟨ Create a character node p for $nucleus(q)$, possibly followed by a kern node for the italic correction, and set $delta$ to the italic correction if a subscript is present 931 ⟩ Used in section 930.
- ⟨ Create a character node q for the next character, but set $q \leftarrow null$ if problems arise 1302 ⟩ Used in section 1301.
- ⟨ Create a new array element of type t with index i 1821 ⟩ Used in section 1820.
- ⟨ Create a new glue specification whose width is cur_val ; scan for its stretch and shrink components 488 ⟩ Used in section 487.
- ⟨ Create a page insertion node with $subtype(r) = qi(n)$, and include the glue correction for box n in the current page state 1186 ⟩ Used in section 1185.
- ⟨ Create an active breakpoint representing the beginning of the paragraph 1040 ⟩ Used in section 1039.
- ⟨ Create and append a discretionary node as an alternative to the unhyphenated word, and continue to develop both branches until they become equivalent 1091 ⟩ Used in section 1090.
- ⟨ Create equal-width boxes x and z for the numerator and denominator, and compute the default amounts $shift_up$ and $shift_down$ by which they are displaced from the baseline 920 ⟩ Used in section 919.

- ⟨ Create link annotations for the current hbox if needed 730 ⟩ Used in section 729*.
- ⟨ Create new active nodes for the best feasible breaks just found 1012 ⟩ Used in section 1011.
- ⟨ Create the *format_ident*, open the format file, and inform the user that dumping has begun 1509 ⟩ Used in section 1481*.
- ⟨ Create thread for the current vbox if needed 739 ⟩ Used in section 738*.
- ⟨ Current *mem* equivalent of glue parameter number *n* 242 ⟩ Used in sections 170* and 172.
- ⟨ Deactivate node *r* 1036 ⟩ Used in section 1027.
- ⟨ Declare ε -TeX procedures for expanding 1753, 1811, 1816, 1820 ⟩ Used in section 388*.
- ⟨ Declare ε -TeX procedures for scanning 1683, 1773, 1782, 1787, 1885* ⟩ Used in section 435.
- ⟨ Declare ε -TeX procedures for token lists 1684, 1754 ⟩ Used in section 490.
- ⟨ Declare ε -TeX procedures for tracing and input 306, 1662, 1663, 1757, 1758, 1775, 1777, 1778, 1822, 1824, 1838, 1839, 1840, 1841, 1842 ⟩ Used in section 290.
- ⟨ Declare ε -TeX procedures for use by *main_control* 1657, 1680, 1696 ⟩ Used in section 991.
- ⟨ Declare action procedures for use by *main_control* 1221, 1225, 1227*, 1228, 1229, 1232, 1238, 1239, 1242, 1247, 1248, 1253, 1257, 1262, 1264, 1269*, 1271, 1273, 1274, 1277, 1279, 1281, 1283, 1288, 1291, 1295, 1297, 1301, 1305, 1307, 1309, 1313*, 1314, 1316, 1320, 1329, 1333, 1337, 1338, 1341, 1343, 1350, 1352, 1354, 1359, 1369, 1372, 1378, 1389*, 1448, 1453*, 1457*, 1466, 1471*, 1481*, 1529*, 1625, 1940* ⟩ Used in section 1207.
- ⟨ Declare additional functions for MLTeX 1886* ⟩ Used in section 586*.
- ⟨ Declare additional routines for encTeX 1901* ⟩ Used in section 354*.
- ⟨ Declare additional routines for string recycling 1877*, 1878* ⟩ Used in section 47*.
- ⟨ Declare math construction procedures 910, 911, 912, 913, 914, 919, 925*, 928, 932, 938 ⟩ Used in section 902.
- ⟨ Declare procedures for preprocessing hyphenation patterns 1121*, 1125, 1126, 1130, 1134, 1136, 1137*, 1143* ⟩ Used in section 1119.
- ⟨ Declare procedures needed for displaying the elements of mlists 867, 868, 870 ⟩ Used in section 197.
- ⟨ Declare procedures needed for expressions 1783, 1788 ⟩ Used in section 487.
- ⟨ Declare procedures needed in *do_extension* 1530, 1531*, 1538, 1553, 1557, 1563, 1567, 1574, 1578, 1588, 1601 ⟩ Used in section 1529*.
- ⟨ Declare procedures needed in *hlist_out*, *vlist_out* 1616*, 1618*, 1621*, 1720, 1724 ⟩ Used in section 647*.
- ⟨ Declare procedures needed in *pdf_hlist_out*, *pdf_vlist_out* 727, 772, 778, 785, 1565, 1631, 1636, 1637, 1638* ⟩ Used in section 729*.
- ⟨ Declare procedures that need to be declared forward for pdfTeX 686, 689, 698, 699, 700, 703, 1546, 1556 ⟩ Used in section 190.
- ⟨ Declare procedures that scan font-related stuff 604*, 605 ⟩ Used in section 435.
- ⟨ Declare procedures that scan restricted classes of integers 459, 460, 461, 462, 463, 1812, 1874* ⟩ Used in section 435.
- ⟨ Declare subprocedures for *after_math* 1745 ⟩ Used in section 1372.
- ⟨ Declare subprocedures for *init_math* 1734*, 1739* ⟩ Used in section 1316.
- ⟨ Declare subprocedures for *line_break* 1002, 1005, 1053, 1072, 1119 ⟩ Used in section 991.
- ⟨ Declare subprocedures for *prefixed_command* 1393*, 1407, 1414, 1421, 1422, 1423, 1424, 1425, 1435*, 1443* ⟩ Used in section 1389*.
- ⟨ Declare subprocedures for *scan_expr* 1794, 1798, 1800 ⟩ Used in section 1783.
- ⟨ Declare subprocedures for *var_delimiter* 885, 887, 888 ⟩ Used in section 882.
- ⟨ Declare the function called *do_marks* 1826 ⟩ Used in section 1154.
- ⟨ Declare the function called *fin_mlist* 1362 ⟩ Used in section 1352.
- ⟨ Declare the function called *open_fmt_file* 550* ⟩ Used in section 1482*.
- ⟨ Declare the function called *reconstitute* 1083 ⟩ Used in section 1072.
- ⟨ Declare the procedure called *align_peek* 961 ⟩ Used in section 976.
- ⟨ Declare the procedure called *fire_up* 1189 ⟩ Used in section 1171.
- ⟨ Declare the procedure called *get_preamble_token* 958 ⟩ Used in section 950.
- ⟨ Declare the procedure called *handle_right_brace* 1246 ⟩ Used in section 1207.
- ⟨ Declare the procedure called *init_span* 963 ⟩ Used in section 962.
- ⟨ Declare the procedure called *insert_relax* 405 ⟩ Used in section 388*.

- ⟨ Declare the procedure called *macro_call* 415 ⟩ Used in section 388*.
- ⟨ Declare the procedure called *print_cmd_chr* 320 ⟩ Used in section 270*.
- ⟨ Declare the procedure called *print_skip_param* 243 ⟩ Used in section 197.
- ⟨ Declare the procedure called *runaway* 328* ⟩ Used in section 137.
- ⟨ Declare the procedure called *show_token_list* 314 ⟩ Used in section 137.
- ⟨ Decry the invalid character and **goto restart** 368 ⟩ Used in section 366.
- ⟨ Delete $c - "0"$ tokens and **goto continue** 88 ⟩ Used in section 84*.
- ⟨ Delete the page-insertion nodes 1196 ⟩ Used in section 1191.
- ⟨ Destroy the t nodes following q , and make r point to the following node 1059 ⟩ Used in section 1058.
- ⟨ Determine horizontal glue shrink setting, then **return** or **goto common_ending** 840 ⟩ Used in section 833.
- ⟨ Determine horizontal glue stretch setting, then **return** or **goto common_ending** 834 ⟩ Used in section 833.
- ⟨ Determine the displacement, d , of the left edge of the equation, with respect to the line size z , assuming that $l = false$ 1380 ⟩ Used in section 1377.
- ⟨ Determine the shrink order 841 ⟩ Used in sections 840, 852, and 972.
- ⟨ Determine the stretch order 835 ⟩ Used in sections 834, 849, and 972.
- ⟨ Determine the value of $height(r)$ and the appropriate glue setting; then **return** or **goto common_ending** 848 ⟩ Used in section 844.
- ⟨ Determine the value of $width(r)$ and the appropriate glue setting; then **return** or **goto common_ending** 833 ⟩ Used in section 823.
- ⟨ Determine vertical glue shrink setting, then **return** or **goto common_ending** 852 ⟩ Used in section 848.
- ⟨ Determine vertical glue stretch setting, then **return** or **goto common_ending** 849 ⟩ Used in section 848.
- ⟨ Discard erroneous prefixes and **return** 1390 ⟩ Used in section 1389*.
- ⟨ Discard the prefixes `\long` and `\outer` if they are irrelevant 1391 ⟩ Used in section 1389*.
- ⟨ Dispense with trivial cases of void or bad boxes 1155 ⟩ Used in section 1154.
- ⟨ Display $\rule{spec}{i}$ for whatsit node created by pdfTeX 1602 ⟩ Used in sections 1604*, 1604*, and 1604*.
- ⟨ Display adjustment p 215 ⟩ Used in section 201.
- ⟨ Display box p 202 ⟩ Used in section 201.
- ⟨ Display choice node p 871 ⟩ Used in section 866.
- ⟨ Display discretionary p 213 ⟩ Used in section 201.
- ⟨ Display fraction noad p 873 ⟩ Used in section 866.
- ⟨ Display glue p 207 ⟩ Used in section 201.
- ⟨ Display if this box is never to be reversed 1705 ⟩ Used in section 202.
- ⟨ Display insertion p 206 ⟩ Used in section 201.
- ⟨ Display kern p 209 ⟩ Used in section 201.
- ⟨ Display leaders p 208 ⟩ Used in section 207.
- ⟨ Display ligature p 211 ⟩ Used in section 201.
- ⟨ Display mark p 214 ⟩ Used in section 201.
- ⟨ Display math node p 210 ⟩ Used in section 201.
- ⟨ Display node p 201 ⟩ Used in section 200.
- ⟨ Display normal noad p 872 ⟩ Used in section 866.
- ⟨ Display penalty p 212 ⟩ Used in section 201.
- ⟨ Display rule p 205 ⟩ Used in section 201.
- ⟨ Display special fields of the unset node p 203 ⟩ Used in section 202.
- ⟨ Display the current context 334 ⟩ Used in section 333.
- ⟨ Display the insertion split cost 1188 ⟩ Used in section 1187.
- ⟨ Display the page break cost 1183 ⟩ Used in section 1182.
- ⟨ Display the token (m, c) 316 ⟩ Used in section 315.
- ⟨ Display the value of b 528 ⟩ Used in section 524.
- ⟨ Display the value of $glue.set(p)$ 204* ⟩ Used in section 202.
- ⟨ Display the whatsit node p 1604* ⟩ Used in section 201.
- ⟨ Display token p , and **return** if there are problems 315 ⟩ Used in section 314.

- ⟨ Do first-pass processing based on $type(q)$; **goto** *done_with_noad* if a noad has been fully processed, **goto** *check_dimensions* if it has been translated into *new_hlist(q)*, or **goto** *done_with_node* if a node has been fully processed 904 ⟩ Used in section 903.
- ⟨ Do ligature or kern command, returning to *main_lig_loop* or *main_loop_wrapup* or *main_loop_move* 1218 ⟩
Used in section 1216.
- ⟨ Do magic computation 342 ⟩ Used in section 314.
- ⟨ Do some work that has been queued up for **\write** 1623* ⟩ Used in section 1621*.
- ⟨ Do typesetting the DVI commands in virtual character packet 726 ⟩ Used in section 725.
- ⟨ Drop current token and complain that it was unmatched 1244 ⟩ Used in section 1242.
- ⟨ Dump MLTeX-specific data 1894* ⟩ Used in section 1481*.
- ⟨ Dump a couple more things and the closing check word 1507 ⟩ Used in section 1481*.
- ⟨ Dump constants for consistency check 1486* ⟩ Used in section 1481*.
- ⟨ Dump encTeX-specific data 1903* ⟩ Used in section 1481*.
- ⟨ Dump pdftex data 1505 ⟩ Used in section 1481*.
- ⟨ Dump regions 1 to 4 of *eqtb* 1494* ⟩ Used in section 1492.
- ⟨ Dump regions 5 and 6 of *eqtb* 1495* ⟩ Used in section 1492.
- ⟨ Dump the ε -TeX state 1655, 1759 ⟩ Used in section 1486*.
- ⟨ Dump the array info for internal font number k 1501* ⟩ Used in section 1499*.
- ⟨ Dump the dynamic memory 1490* ⟩ Used in section 1481*.
- ⟨ Dump the font information 1499* ⟩ Used in section 1481*.
- ⟨ Dump the hash table 1497* ⟩ Used in section 1492.
- ⟨ Dump the hyphenation tables 1503* ⟩ Used in section 1481*.
- ⟨ Dump the string pool 1488* ⟩ Used in section 1481*.
- ⟨ Dump the table of equivalents 1492 ⟩ Used in section 1481*.
- ⟨ Dump *xord*, *xchr*, and *xprn* 1875* ⟩ Used in section 1486*.
- ⟨ Either append the insertion node p after node q , and remove it from the current page, or delete *node(p)* 1199 ⟩ Used in section 1197.
- ⟨ Either insert the material specified by node p into the appropriate box, or hold it for the next page; also delete node p from the current page 1197 ⟩ Used in section 1191.
- ⟨ Either process **\ifcase** or set b to the value of a boolean condition 527* ⟩ Used in section 524.
- ⟨ Empty the last bytes out of *dvi_buf* 626* ⟩ Used in section 670*.
- ⟨ Enable ε -TeX, if requested 1649* ⟩ Used in section 1518*.
- ⟨ Ensure that box 255 is empty after output 1205 ⟩ Used in section 1203*.
- ⟨ Ensure that box 255 is empty before output 1192 ⟩ Used in section 1191.
- ⟨ Ensure that $trie_max \geq h + 256$ 1131 ⟩ Used in section 1130.
- ⟨ Enter a hyphenation exception 1116* ⟩ Used in section 1112.
- ⟨ Enter all of the patterns into a linked trie, until coming to a right brace 1138 ⟩ Used in section 1137*.
- ⟨ Enter as many hyphenation exceptions as are listed, until coming to a right brace; then **return** 1112 ⟩
Used in section 1111*.
- ⟨ Enter *skip_blanks* state, emit a space 371 ⟩ Used in section 369.
- ⟨ Error handling procedures 78, 81*, 82*, 93*, 94*, 95* ⟩ Used in section 4*.
- ⟨ Evaluate the current expression 1793 ⟩ Used in section 1784.
- ⟨ Examine node p in the hlist, taking account of its effect on the dimensions of the new box, or moving it to the adjustment list; then advance p to the next node 825 ⟩ Used in section 823.
- ⟨ Examine node p in the vlist, taking account of its effect on the dimensions of the new box; then advance p to the next node 845 ⟩ Used in section 844.
- ⟨ Expand a nonmacro 391 ⟩ Used in section 388*.
- ⟨ Expand macros in the token list and make *link(def_ref)* point to the result 1619* ⟩ Used in sections 727, 727, 1616*, and 1618*.
- ⟨ Expand the next part of the input 504 ⟩ Used in section 503.
- ⟨ Expand the token after the next token 392 ⟩ Used in section 391.
- ⟨ Explain that too many dead cycles have occurred in a row 1201 ⟩ Used in section 1189.

- ⟨Express astonishment that no number was here 472⟩ Used in section 470.
- ⟨Express consternation over the fact that no alignment is in progress 1306⟩ Used in section 1305.
- ⟨Express shock at the missing left brace; **goto found** 501⟩ Used in section 500.
- ⟨Feed the macro body and its parameters to the scanner 416*⟩ Used in section 415.
- ⟨Fetch a box dimension 446⟩ Used in section 439.
- ⟨Fetch a character code from some table 440*⟩ Used in section 439.
- ⟨Fetch a font dimension 451⟩ Used in section 439.
- ⟨Fetch a font integer 452⟩ Used in section 439.
- ⟨Fetch a penalties array element 1867⟩ Used in section 449.
- ⟨Fetch a register 453⟩ Used in section 439.
- ⟨Fetch a token list or font identifier, provided that $level = tok_val$ 441⟩ Used in section 439.
- ⟨Fetch an internal dimension and **goto attach_sign**, or fetch an internal integer 475⟩ Used in section 474.
- ⟨Fetch an item in the current node, if appropriate 450⟩ Used in section 439.
- ⟨Fetch something on the *page_so_far* 447⟩ Used in section 439.
- ⟨Fetch the *dead_cycles* or the *insert_penalties* 445⟩ Used in section 439.
- ⟨Fetch the *par_shape* size 449⟩ Used in section 439.
- ⟨Fetch the *prev_graf* 448⟩ Used in section 439.
- ⟨Fetch the *space_factor* or the *prev_depth* 444⟩ Used in section 439.
- ⟨Find an active node with fewest demerits 1050⟩ Used in section 1049.
- ⟨Find hyphen locations for the word in *hc*, or **return** 1100*⟩ Used in section 1072.
- ⟨Find optimal breakpoints 1039⟩ Used in section 991.
- ⟨Find the best active node for the desired looseness 1051⟩ Used in section 1049.
- ⟨Find the best way to split the insertion, and change $type(r)$ to *split_up* 1187⟩ Used in section 1185.
- ⟨Find the glue specification, *main_p*, for text spaces in the current font 1220⟩ Used in sections 1219 and 1221.
- ⟨Finish an alignment in a display 1384⟩ Used in section 988.
- ⟨Finish displayed math 1377⟩ Used in section 1372.
- ⟨Finish hlist *SyncTeX* information record 1929*⟩ Used in sections 647* and 729*.
- ⟨Finish issuing a diagnostic message for an overfull or underfull hbox 839⟩ Used in section 823.
- ⟨Finish issuing a diagnostic message for an overfull or underfull vbox 851⟩ Used in section 844.
- ⟨Finish line, emit a $\backslash par$ 373⟩ Used in section 369.
- ⟨Finish line, emit a space 370⟩ Used in section 369.
- ⟨Finish line, **goto switch** 372⟩ Used in section 369.
- ⟨Finish math in text 1374⟩ Used in section 1372.
- ⟨Finish sheet *SyncTeX* information record 1925*⟩ Used in section 666*.
- ⟨Finish shipping 759⟩ Used in section 751.
- ⟨Finish stream of page/form contents 760⟩ Used in section 759.
- ⟨Finish the PDF file 794⟩ Used in section 1514*.
- ⟨Finish the DVI file 670*⟩ Used in section 1514*.
- ⟨Finish the extensions 1627⟩ Used in section 1514*.
- ⟨Finish the natural width computation 1736⟩ Used in section 1324.
- ⟨Finish the reversed hlist segment and **goto done** 1730*⟩ Used in section 1729.
- ⟨Finish vlist *SyncTeX* information record 1927*⟩ Used in sections 657* and 738*.
- ⟨Finish *hlist_out* for mixed direction typesetting 1716⟩ Used in sections 647* and 729*.
- ⟨Fire up the user's output routine and **return** 1202⟩ Used in section 1189.
- ⟨Fix the reference count, if any, and negate *cur_val* if *negative* 456⟩ Used in section 439.
- ⟨Flush PDF mark lists 765⟩ Used in section 759.
- ⟨Flush resource lists 764⟩ Used in section 759.
- ⟨Flush the box from memory, showing statistics if requested 667⟩ Used in sections 666* and 750*.
- ⟨Flush the prototype box 1744⟩ Used in section 1377.
- ⟨Flush *pdf_start_link_node*'s created by *append_link* 783⟩ Used in section 782.
- ⟨Forbidden cases detected in *main_control* 1226, 1276, 1289, 1322⟩ Used in section 1223.
- ⟨Generate ProcSet if desired 768⟩ Used in section 762.

- ⟨Generate XObject resources 767⟩ Used in section 762.
- ⟨Generate a *down* or *right* command for *w* and **return** 637⟩ Used in section 634.
- ⟨Generate a *y0* or *z0* command in order to reuse a previous appearance of *w* 636⟩ Used in section 634.
- ⟨Generate all ε -TeX primitives 1650, 1658, 1664, 1667, 1670, 1673, 1676, 1685, 1687, 1690, 1693, 1698, 1702, 1748, 1760, 1763, 1771, 1779, 1802, 1806, 1810, 1862, 1865⟩ Used in section 1649*.
- ⟨Generate array of annotations or beads in page 771⟩ Used in section 769.
- ⟨Generate font resources 766⟩ Used in section 762.
- ⟨Generate parent pages object 770⟩ Used in section 769.
- ⟨Get ready to compress the trie 1129⟩ Used in section 1143*.
- ⟨Get ready to start line breaking 992, 1003, 1010, 1024⟩ Used in section 991.
- ⟨Get substitution information, check it, goto *found* if all is ok, otherwise goto *continue* 1890*⟩ Used in sections 1887* and 1888*.
- ⟨Get the first line of input and prepare to start 1518*⟩ Used in section 1513*.
- ⟨Get the next non-blank non-call token 432⟩ Used in sections 431, 467, 481, 529, 552*, 604*, 1223, 1770, 1785, and 1786.
- ⟨Get the next non-blank non-relax non-call token 430⟩ Used in sections 429, 552*, 1256, 1262, 1329, 1338, 1389*, 1404, and 1448.
- ⟨Get the next non-blank non-sign token; set *negative* appropriately 467⟩ Used in sections 466, 474, and 487.
- ⟨Get the next token, suppressing expansion 380⟩ Used in section 379*.
- ⟨Get user's advice and **return** 83⟩ Used in section 82*.
- ⟨Give diagnostic information, if requested 1208⟩ Used in section 1207.
- ⟨Give improper `\hyphenation` error 1113⟩ Used in section 1112.
- ⟨Global variables 13, 20*, 26*, 30*, 32*, 39*, 50, 54*, 73*, 76, 79, 96, 104*, 110, 117, 133, 134*, 135, 136, 142, 183*, 191, 199, 231*, 264, 271*, 274*, 275, 293*, 308, 319, 323*, 326*, 327, 330*, 331, 332, 355, 383, 389, 408, 413, 414, 436, 464, 473, 506, 515, 519, 538, 539*, 546*, 553, 558*, 565, 575*, 576*, 581, 619*, 622*, 632, 643, 676, 680, 687, 691, 696, 701, 704, 708, 710, 723, 774, 811, 818, 819, 821, 829, 837, 860, 895, 900, 940, 946, 990, 997, 999, 1001, 1004, 1009, 1015, 1023, 1048, 1069, 1077, 1082, 1084, 1098*, 1103*, 1120*, 1124*, 1127*, 1148, 1157, 1159, 1166, 1209, 1252, 1444, 1459, 1478, 1484*, 1512, 1523, 1526, 1544, 1548, 1551, 1558, 1560, 1571, 1584, 1629, 1634, 1641, 1653*, 1661*, 1706, 1751, 1774*, 1815, 1817, 1836, 1843, 1859, 1860, 1868*, 1870*, 1872*, 1879*, 1882*, 1883*, 1889*, 1897*, 1898*, 1907*, 1912*⟩ Used in section 4*.
- ⟨Go into display math mode 1323⟩ Used in section 1316.
- ⟨Go into ordinary math mode 1317*⟩ Used in sections 1316 and 1320.
- ⟨Go through the preamble list, determining the column widths and changing the alignrecords to dummy unset boxes 977⟩ Used in section 976.
- ⟨Grow more variable-size memory and **goto restart** 144⟩ Used in section 143*.
- ⟨Handle `\readline` and **goto done** 1762⟩ Used in section 509.
- ⟨Handle `\unexpanded` or `\detokenize` and **return** 1689⟩ Used in section 491.
- ⟨Handle a glue node for mixed direction typesetting 1700⟩ Used in sections 653, 735, and 1727.
- ⟨Handle a math node in *hlist_out* 1717⟩ Used in sections 650* and 732*.
- ⟨Handle non-positive logarithm 121⟩ Used in section 119.
- ⟨Handle saved items and **goto done** 1864⟩ Used in section 1288.
- ⟨Handle situations involving spaces, braces, changes of state 369⟩ Used in section 366.
- ⟨If a line number class has ended, create new active nodes for the best feasible breaks in that class; then **return** if $r = last_active$, otherwise compute the new *line_width* 1011⟩ Used in section 1005.
- ⟨If all characters of the family fit relative to *h*, then **goto found**, otherwise **goto not_found** 1132⟩ Used in section 1130.
- ⟨If an alignment entry has just ended, take appropriate action 364⟩ Used in section 363*.
- ⟨If an expanded code is present, reduce it and **goto start_cs** 377*⟩ Used in sections 376* and 378*.
- ⟨If dumping is not allowed, abort 1483⟩ Used in section 1481*.
- ⟨If instruction *cur_i* is a kern with *cur_c*, attach the kern after *q*; or if it is a ligature with *cur_c*, combine noads *q* and *p* appropriately; then **return** if the cursor has moved past a noad, or **goto restart** 929⟩ Used in section 928.

- ⟨ If no hyphens were found, **return** 1079 ⟩ Used in section 1072.
- ⟨ If node *cur_p* is a legal breakpoint, call *try_break*; then update the active widths by including the glue in *glue_ptr(cur_p)* 1044 ⟩ Used in section 1042.
- ⟨ If node *p* is a legal breakpoint, check if this break is the best known, and **goto** *done* if *p* is null or if the page-so-far is already too full to accept more stuff 1149 ⟩ Used in section 1147.
- ⟨ If node *q* is a style node, change the style and **goto** *delete_q*; otherwise if it is not a noad, put it into the hlist, advance *q*, and **goto** *done*; otherwise set *s* to the size of noad *q*, set *t* to the associated type (*ord_noad* .. *inner_noad*), and set *pen* to the associated penalty 937 ⟩ Used in section 936.
- ⟨ If node *r* is of type *delta_node*, update *cur_active_width*, set *prev_r* and *prev_prev_r*, then **goto** *continue* 1008 ⟩ Used in section 1005.
- ⟨ If the current list ends with a box node, delete it from the list and make *cur_box* point to it; otherwise set *cur_box* ← *null* 1258 ⟩ Used in section 1257.
- ⟨ If the current page is empty and node *p* is to be deleted, **goto** *done1*; otherwise use node *p* to update the state of the current page; if this node is an insertion, **goto** *contribute*; otherwise if this node is not a legal breakpoint, **goto** *contribute* or *update_heights*; otherwise set *pi* to the penalty associated with this breakpoint 1177 ⟩ Used in section 1174.
- ⟨ If the cursor is immediately followed by the right boundary, **goto** *reswitch*; if it's followed by an invalid character, **goto** *big_switch*; otherwise move the cursor one step to the right and **goto** *main_lig_loop* 1213* ⟩ Used in section 1211*.
- ⟨ If the next character is a parameter number, make *cur_tok* a *match* token; but if it is a left brace, store '*left_brace*, *end_match*', set *hash_brace*, and **goto** *done* 502 ⟩ Used in section 500.
- ⟨ If the preamble list has been traversed, check that the row has ended 968 ⟩ Used in section 967.
- ⟨ If the right-hand side is a token parameter or token register, finish the assignment and **goto** *done* 1405 ⟩ Used in section 1404.
- ⟨ If the string *hyph_word[h]* is less than *hc[1 .. hn]*, **goto** *not_found*; but if the two strings are equal, set *hyf* to the hyphen positions and **goto** *found* 1108* ⟩ Used in section 1107*.
- ⟨ If the string *hyph_word[h]* is less than or equal to *s*, interchange (*hyph_word[h]*, *hyph_list[h]*) with (*s*, *p*) 1118* ⟩ Used in section 1117*.
- ⟨ If there's a ligature or kern at the cursor position, update the data structures, possibly advancing *j*; continue until the cursor moves 1086 ⟩ Used in section 1083.
- ⟨ If there's a ligature/kern command relevant to *cur_l* and *cur_r*, adjust the text appropriately; exit to *main_loop_wrapup* 1216 ⟩ Used in section 1211*.
- ⟨ If this font has already been loaded, set *f* to the internal font number and **goto** *common_ending* 1438* ⟩ Used in section 1435*.
- ⟨ If this *sup_mark* starts an expanded character like \tilde{A} or $\overset{\sim}{df}$, then **goto** *reswitch*, otherwise set *state* ← *mid_line* 374 ⟩ Used in section 366.
- ⟨ If *tmp_k1* is not null then append that kern 1217 ⟩ Used in sections 1211* and 1216.
- ⟨ Ignore the fraction operation and complain about this ambiguous case 1361 ⟩ Used in section 1359.
- ⟨ Implement `\closeout` 1534 ⟩ Used in section 1529*.
- ⟨ Implement `\immediate` 1624 ⟩ Used in section 1529*.
- ⟨ Implement `\openout` 1532 ⟩ Used in section 1529*.
- ⟨ Implement `\pdfannot` 1559 ⟩ Used in section 1529*.
- ⟨ Implement `\pdfcatalog` 1580 ⟩ Used in section 1529*.
- ⟨ Implement `\pdfcolorstack` 1540 ⟩ Used in section 1529*.
- ⟨ Implement `\pdfdest` 1566 ⟩ Used in section 1529*.
- ⟨ Implement `\pdfendlink` 1562 ⟩ Used in section 1529*.
- ⟨ Implement `\pdfendthread` 1570 ⟩ Used in section 1529*.
- ⟨ Implement `\pdffakespace` 1597 ⟩ Used in section 1529*.
- ⟨ Implement `\pdffontattr` 1590 ⟩ Used in section 1529*.
- ⟨ Implement `\pdffontexpand` 1536 ⟩ Used in section 1529*.
- ⟨ Implement `\pdfglyptounicode` 1593 ⟩ Used in section 1529*.
- ⟨ Implement `\pdfincludechars` 1589 ⟩ Used in section 1529*.

- ⟨Implement `\pdfinfo` 1579⟩ Used in section 1529*.
- ⟨Implement `\pdfinterwordsoff` 1596⟩ Used in section 1529*.
- ⟨Implement `\pdfinterwordsoff` 1595⟩ Used in section 1529*.
- ⟨Implement `\pdfliteral` 1539⟩ Used in section 1529*.
- ⟨Implement `\pdfmapfile` 1591⟩ Used in section 1529*.
- ⟨Implement `\pdfmapline` 1592⟩ Used in section 1529*.
- ⟨Implement `\pdfnames` 1581⟩ Used in section 1529*.
- ⟨Implement `\pdfnobuiltintounicode` 1594⟩ Used in section 1529*.
- ⟨Implement `\pdfobj` 1545⟩ Used in section 1529*.
- ⟨Implement `\pdfoutline` 1564⟩ Used in section 1529*.
- ⟨Implement `\pdfprimitive` 394⟩ Used in section 391.
- ⟨Implement `\pdfrefobj` 1547⟩ Used in section 1529*.
- ⟨Implement `\pdfrefxform` 1550⟩ Used in section 1529*.
- ⟨Implement `\pdfrefximage` 1555⟩ Used in section 1529*.
- ⟨Implement `\pdfresettimer` 1587⟩ Used in section 1529*.
- ⟨Implement `\pdfrestore` 1543⟩ Used in section 1529*.
- ⟨Implement `\pdfrunninglinkoff` 1598⟩ Used in section 1529*.
- ⟨Implement `\pdfrunninglinkon` 1599⟩ Used in section 1529*.
- ⟨Implement `\pdfsavepos` 1577⟩ Used in section 1529*.
- ⟨Implement `\pdfsave` 1542⟩ Used in section 1529*.
- ⟨Implement `\pdfsetmatrix` 1541⟩ Used in section 1529*.
- ⟨Implement `\pdfsetrandomseed` 1586⟩ Used in section 1529*.
- ⟨Implement `\pdfsnaprefpoint` 1573⟩ Used in section 1529*.
- ⟨Implement `\pdfsnappycomp` 1576⟩ Used in section 1529*.
- ⟨Implement `\pdfsnappy` 1575⟩ Used in section 1529*.
- ⟨Implement `\pdfspacefont` 1600⟩ Used in section 1529*.
- ⟨Implement `\pdfstartlink` 1561⟩ Used in section 1529*.
- ⟨Implement `\pdfstartthread` 1569⟩ Used in section 1529*.
- ⟨Implement `\pdfthread` 1568⟩ Used in section 1529*.
- ⟨Implement `\pdftrailerid` 1583⟩ Used in section 1529*.
- ⟨Implement `\pdftrailer` 1582⟩ Used in section 1529*.
- ⟨Implement `\pdfxform` 1549⟩ Used in section 1529*.
- ⟨Implement `\pdfximage` 1554⟩ Used in section 1529*.
- ⟨Implement `\setlanguage` 1626⟩ Used in section 1529*.
- ⟨Implement `\special` 1535*⟩ Used in section 1529*.
- ⟨Implement `\write` 1533⟩ Used in section 1529*.
- ⟨Incorporate a whatsit node into a vbox 1607⟩ Used in section 845.
- ⟨Incorporate a whatsit node into an hbox 1608⟩ Used in section 825.
- ⟨Incorporate box dimensions into the dimensions of the hbox that will contain it 827⟩ Used in section 825.
- ⟨Incorporate box dimensions into the dimensions of the vbox that will contain it 846⟩ Used in section 845.
- ⟨Incorporate character dimensions into the dimensions of the hbox that will contain it, then move to the next node 828⟩ Used in section 825.
- ⟨Incorporate glue into the horizontal totals 832⟩ Used in section 825.
- ⟨Incorporate glue into the vertical totals 847⟩ Used in section 845.
- ⟨Increase the number of parameters in the last font 607⟩ Used in section 605.
- ⟨Increase k until x can be multiplied by a factor of 2^{-k} , and adjust y accordingly 120⟩ Used in section 119.
- ⟨Initialize additional fields of the first active node 1846⟩ Used in section 1040.
- ⟨Initialize bigger nodes with *SyncTeX* information 1917*⟩ Used in section 143*.
- ⟨Initialize for hyphenating a paragraph 1068⟩ Used in section 1039.
- ⟨Initialize syntex primitive 1914*⟩ Used in section 1513*.
- ⟨Initialize table entries (done by INITEX only) 182, 240*, 246, 250, 258*, 268, 277*, 578*, 672, 1064, 1123*, 1128*, 1394, 1480*, 1617, 1654, 1819, 1855*⟩ Used in section 8*.

- ⟨ Initialize the LR stack 1711 ⟩ Used in sections 823, 1715, and 1735.
- ⟨ Initialize the current page, insert the `\topskip` glue ahead of p , and `goto continue` 1178 ⟩ Used in section 1177.
- ⟨ Initialize the input routines 353* ⟩ Used in section 1518*.
- ⟨ Initialize the output routines 55, 61*, 554, 559 ⟩ Used in section 1513*.
- ⟨ Initialize the print *selector* based on *interaction* 75 ⟩ Used in sections 1443*, 1471*, and 1518*.
- ⟨ Initialize the special list heads and constant nodes 966, 973, 996, 1158, 1165* ⟩ Used in section 182.
- ⟨ Initialize variables as *pdf_ship_out* begins 752 ⟩ Used in section 751.
- ⟨ Initialize variables as *ship_out* begins 645* ⟩ Used in section 668*.
- ⟨ Initialize variables for PDF output 792 ⟩ Used in section 750*.
- ⟨ Initialize variables for ε -TeX compatibility mode 1813 ⟩ Used in sections 1654 and 1656.
- ⟨ Initialize variables for ε -TeX extended mode 1814 ⟩ Used in sections 1649* and 1656.
- ⟨ Initialize whatever TeX might access 8*, 1913* ⟩ Used in section 4*.
- ⟨ Initialize *hlist_out* for mixed direction typesetting 1715 ⟩ Used in sections 647* and 729*.
- ⟨ Initiate input from new pseudo file 1756* ⟩ Used in section 1754.
- ⟨ Initiate or terminate input from a file 404 ⟩ Used in section 391.
- ⟨ Initiate the construction of an hbox or vbox, then `return` 1261 ⟩ Used in section 1257.
- ⟨ Input and store tokens from the next line of the file 509 ⟩ Used in section 508.
- ⟨ Input for `\read` from the terminal 510* ⟩ Used in section 509.
- ⟨ Input from external file, `goto restart` if no input found 365* ⟩ Used in section 363*.
- ⟨ Input from token list, `goto restart` if end of list or if a parameter needs to be expanded 379* ⟩ Used in section 363*.
- ⟨ Input the first line of *read_file*[m] 511 ⟩ Used in section 509.
- ⟨ Input the next line of *read_file*[m] 512 ⟩ Used in section 509.
- ⟨ Insert LR nodes at the beginning of the current line and adjust the LR stack based on LR nodes in this line 1708 ⟩ Used in section 1056.
- ⟨ Insert LR nodes at the end of the current line 1710 ⟩ Used in section 1056.
- ⟨ Insert a delta node to prepare for breaks at *cur_p* 1019 ⟩ Used in section 1012.
- ⟨ Insert a delta node to prepare for the next active node 1020 ⟩ Used in section 1012.
- ⟨ Insert a dummy node to be sub/superscripted 1355 ⟩ Used in section 1354.
- ⟨ Insert a new active node from *best_place*[*fit_class*] to *cur_p* 1021 ⟩ Used in section 1012.
- ⟨ Insert a new control sequence after p , then make p point to it 279* ⟩ Used in section 278.
- ⟨ Insert a new pattern into the linked trie 1140* ⟩ Used in section 1138.
- ⟨ Insert a new primitive after p , then make p point to it 282 ⟩ Used in section 281.
- ⟨ Insert a new trie node between q and p , and make p point to it 1141* ⟩ Used in sections 1140*, 1856, and 1857.
- ⟨ Insert a token containing *frozen_endv* 401 ⟩ Used in section 388*.
- ⟨ Insert a token saved by `\afterassignment`, if any 1447 ⟩ Used in section 1389*.
- ⟨ Insert glue for *split_top_skip* and set $p \leftarrow null$ 1146 ⟩ Used in section 1145.
- ⟨ Insert hyphens as specified in *hyph_list*[h] 1109 ⟩ Used in section 1108*.
- ⟨ Insert macro parameter and `goto restart` 381 ⟩ Used in section 379*.
- ⟨ Insert the appropriate mark text into the scanner 412 ⟩ Used in section 391.
- ⟨ Insert the current list into its environment 988 ⟩ Used in section 976.
- ⟨ Insert the pair (s, p) into the exception table 1117* ⟩ Used in section 1116*.
- ⟨ Insert the $\langle v_j \rangle$ template and `goto restart` 965 ⟩ Used in section 364.
- ⟨ Insert token p into TeX's input 348 ⟩ Used in section 304.
- ⟨ Interpret code c and `return` if done 84* ⟩ Used in section 83.
- ⟨ Introduce new material from the terminal and `return` 87 ⟩ Used in section 84*.
- ⟨ Issue an error message if $cur_val = fmem_ptr$ 606 ⟩ Used in section 605.
- ⟨ Justify the line ending at breakpoint *cur_p*, and append it to the current vertical list, together with associated penalties and other insertions 1056 ⟩ Used in section 1053.
- ⟨ Last-minute procedures 1514*, 1516*, 1517, 1519* ⟩ Used in section 1511.
- ⟨ Lengthen the preamble periodically 969 ⟩ Used in section 968.

- < Let *cur_h* be the position of the first box, and set *leader_wd + lx* to the spacing between corresponding parts of boxes 655 > Used in sections 654 and 736.
- < Let *cur_v* be the position of the first box, and set *leader_ht + lx* to the spacing between corresponding parts of boxes 664 > Used in sections 663 and 745.
- < Let *d* be the natural width of node *p*; if the node is “visible,” **goto found**; if the node is glue that stretches or shrinks, set $v \leftarrow \text{max_dimen}$ 1325 > Used in section 1324.
- < Let *d* be the natural width of this glue; if stretching or shrinking, set $v \leftarrow \text{max_dimen}$; **goto found** in the case of leaders 1326 > Used in section 1325.
- < Let *d* be the width of the whatsit *p* 1609 > Used in section 1325.
- < Let *j* be the prototype box for the display 1741 > Used in section 1735.
- < Let *n* be the largest legal code value, based on *cur_chr* 1411 > Used in section 1410*.
- < Link node *p* into the current page and **goto done** 1175 > Used in section 1174.
- < Local variables for dimension calculations 476 > Used in section 474.
- < Local variables for finishing a displayed formula 1376, 1742 > Used in section 1372.
- < Local variables for formatting calculations 337 > Used in section 333.
- < Local variables for hyphenation 1078, 1089, 1099, 1106 > Used in section 1072.
- < Local variables for initialization 19*, 181, 1104 > Used in section 4*.
- < Local variables for line breaking 1038, 1070 > Used in section 991.
- < Look ahead for another character, or leave *lig_stack* empty if there’s none there 1215 > Used in section 1211*.
- < Look at all the marks in nodes before the break, and set the final link to *null* at the break 1156 > Used in section 1154.
- < Look at the list of characters starting with *x* in font *g*; set *f* and *c* whenever a better character is found; **goto found** as soon as a large enough variant is encountered 884* > Used in section 883.
- < Look at the other stack entries until deciding what sort of DVI command to generate; **goto found** if node *p* is a “hit” 638 > Used in section 634.
- < Look at the variants of (*z, x*); set *f* and *c* whenever a better character is found; **goto found** as soon as a large enough variant is encountered 883 > Used in section 882.
- < Look for parameter number or ## 505 > Used in section 503.
- < Look for the word *hc*[1 .. *hn*] in the exception table, and **goto found** (with *hyf* containing the hyphens) if an entry is found 1107* > Used in section 1100*.
- < Look up the characters of list *n* in the hash table, and set *cur_cs* 1769 > Used in section 1768.
- < Look up the characters of list *r* in the hash table, and set *cur_cs* 400 > Used in section 398*.
- < Make a copy of node *p* in node *r* 223 > Used in section 222.
- < Make a ligature node, if *ligature_present*; insert a null discretionary, if appropriate 1212 > Used in section 1211*.
- < Make a partial copy of the whatsit node *p* and make *r* point to it; set *words* to the number of initial words not yet copied 1605 > Used in sections 224* and 1734*.
- < Make a second pass over the *m*list, removing all noads and inserting the proper spacing and penalties 936 > Used in section 902.
- < Make final adjustments and **goto done** 603* > Used in section 588.
- < Make node *p* look like a *char_node* and **goto reswitch** 826 > Used in sections 650*, 732*, 825, and 1325.
- < Make sure that *f* is in the proper range 1791 > Used in section 1784.
- < Make sure that *page_max_depth* is not exceeded 1180 > Used in section 1174.
- < Make sure that *pi* is in the proper range 1007 > Used in section 1005.
- < Make the contribution list empty by setting its tail to *contrib_head* 1172 > Used in section 1171.
- < Make the first 256 strings 48 > Used in section 47*.
- < Make the height of box *y* equal to *h* 915 > Used in section 914.
- < Make the running dimensions in rule *q* extend to the boundaries of the alignment 982 > Used in section 981.
- < Make the unset node *r* into a *vlist_node* of height *w*, setting the glue as if the height were *t* 987 > Used in section 984.
- < Make the unset node *r* into an *hlist_node* of width *w*, setting the glue as if the width were *t* 986 > Used in section 984.

- ⟨ Make variable b point to a box for (f, c) 886 ⟩ Used in section 882.
- ⟨ Manufacture a control sequence name 398* ⟩ Used in section 391.
- ⟨ Math-only cases in non-math modes, or vice versa 1224 ⟩ Used in section 1223.
- ⟨ Merge the widths in the span nodes of q with those of p , destroying the span nodes of q 979 ⟩ Used in section 977.
- ⟨ Modify the end of the line to reflect the nature of the break and to include `\rightskip`; also set the proper value of `disc_break` 1057 ⟩ Used in section 1056.
- ⟨ Modify the glue specification in `main_p` according to the space factor 1222 ⟩ Used in section 1221.
- ⟨ Move down or output leaders 662 ⟩ Used in section 659.
- ⟨ Move down without outputting leaders 1639 ⟩ Used in section 1638*.
- ⟨ Move node p to the current page; if it is time for a page break, put the nodes following the break back onto the contribution list, and **return** to the user's output routine if there is one 1174 ⟩ Used in section 1171.
- ⟨ Move node p to the new list and go to the next node; or **goto** `done` if the end of the reflected segment has been reached 1725 ⟩ Used in section 1724.
- ⟨ Move pointer s to the end of the current list, and set `replace_count(r)` appropriately 1095 ⟩ Used in section 1091.
- ⟨ Move right or output leaders 653 ⟩ Used in section 650*.
- ⟨ Move the characters of a ligature node to `hu` and `hc`; but **goto** `done3` if they are not all letters 1075 ⟩ Used in section 1074.
- ⟨ Move the cursor past a pseudo-ligature, then **goto** `main_loop_lookahead` or `main_lig_loop` 1214* ⟩ Used in section 1211*.
- ⟨ Move the data into `trie` 1135* ⟩ Used in section 1143*.
- ⟨ Move the non-`char_node` p to the new list 1726* ⟩ Used in section 1725.
- ⟨ Move to next line of file, or **goto** `restart` if there is no next line, or **return** if a `\read` line has finished 382 ⟩ Used in section 365*.
- ⟨ Negate a boolean conditional and **goto** `reswitch` 1766 ⟩ Used in section 391.
- ⟨ Negate all three glue components of `cur_val` 457 ⟩ Used in sections 456 and 1781.
- ⟨ Nullify `width(q)` and the tabskip glue following this column 978 ⟩ Used in section 977.
- ⟨ Numbered cases for `debug_help` 1520* ⟩ Used in section 1519*.
- ⟨ Open `tfm_file` for input 589* ⟩ Used in section 588.
- ⟨ Open `vf_file`, return if not found 713 ⟩ Used in section 712.
- ⟨ Other local variables for `try_break` 1006, 1845 ⟩ Used in section 1005.
- ⟨ Output PDF outline entries 789 ⟩ Used in section 788.
- ⟨ Output a Form node in a hlist 1648 ⟩ Used in section 1646.
- ⟨ Output a Form node in a vlist 1645 ⟩ Used in section 1640.
- ⟨ Output a Image node in a hlist 1647 ⟩ Used in section 1646.
- ⟨ Output a Image node in a vlist 1644 ⟩ Used in section 1640.
- ⟨ Output a box in a vlist 660* ⟩ Used in section 659.
- ⟨ Output a box in an hlist 651* ⟩ Used in section 650*.
- ⟨ Output a leader box at `cur_h`, then advance `cur_h` by `leader_wd + lx` 656 ⟩ Used in section 654.
- ⟨ Output a leader box at `cur_v`, then advance `cur_v` by `leader_ht + lx` 665 ⟩ Used in section 663.
- ⟨ Output a rule in a vlist, **goto** `next_p` 661 ⟩ Used in section 659.
- ⟨ Output a rule in an hlist 652 ⟩ Used in section 650*.
- ⟨ Output a substitution, **goto** `continue` if not possible 1887* ⟩ Used in section 648*.
- ⟨ Output article threads 790 ⟩ Used in section 794.
- ⟨ Output fonts definition 801 ⟩ Used in section 794.
- ⟨ Output leaders in a vlist, **goto** `fin_rule` if a rule or to `next_p` if done 663 ⟩ Used in section 662.
- ⟨ Output leaders in an hlist, **goto** `fin_rule` if a rule or to `next_p` if done 654 ⟩ Used in section 653.
- ⟨ Output name tree 804 ⟩ Used in section 794.
- ⟨ Output node p for `hlist_out` and move to the next node, maintaining the condition `cur_v = base_line` 648* ⟩ Used in section 647*.

- ⟨Output node p for *pdf_hlist_out* and move to the next node, maintaining the condition $cur_v = base_line$ 731*⟩ Used in section 729*.
- ⟨Output node p for *pdf_vlist_out* and move to the next node, maintaining the condition $cur_h = left_edge$ 740⟩ Used in section 738*.
- ⟨Output node p for *vlist_out* and move to the next node, maintaining the condition $cur_h = left_edge$ 658⟩ Used in section 657*.
- ⟨Output outlines 788⟩ Used in section 794.
- ⟨Output pages tree 802⟩ Used in section 794.
- ⟨Output statistics about this job 1515*⟩ Used in section 1514*.
- ⟨Output the catalog object 806⟩ Used in section 794.
- ⟨Output the cross-reference stream dictionary 814⟩ Used in section 794.
- ⟨Output the current Pages object in this level 803⟩ Used in section 802.
- ⟨Output the current node in this level 805⟩ Used in section 804.
- ⟨Output the font definitions for all fonts that were used 671⟩ Used in section 670*.
- ⟨Output the font name whose internal number is f 630⟩ Used in section 629*.
- ⟨Output the non-*char_node* p for *hlist_out* and move to the next node 650*⟩ Used in section 648*.
- ⟨Output the non-*char_node* p for *pdf_hlist_out* and move to the next node 732*⟩ Used in section 731*.
- ⟨Output the non-*char_node* p for *pdf_vlist_out* 741⟩ Used in section 740.
- ⟨Output the non-*char_node* p for *vlist_out* 659⟩ Used in section 658.
- ⟨Output the trailer 815⟩ Used in section 794.
- ⟨Output the whatsit node p in a *vlist* 1614⟩ Used in section 659.
- ⟨Output the whatsit node p in an *hlist* 1615⟩ Used in section 650*.
- ⟨Output the whatsit node p in *pdf_hlist_out* 1646⟩ Used in section 732*.
- ⟨Output the whatsit node p in *pdf_vlist_out* 1640⟩ Used in section 741.
- ⟨Output the *obj_tab* 813⟩ Used in section 794.
- ⟨Pack all stored *hyph_codes* 1858⟩ Used in section 1143*.
- ⟨Pack the family into *trie* relative to h 1133⟩ Used in section 1130.
- ⟨Package an unset box for the current column and record its width 972⟩ Used in section 967.
- ⟨Package the display line 1747⟩ Used in section 1745.
- ⟨Package the preamble list, to determine the actual tabskip glue amounts, and let p point to this prototype box 980⟩ Used in section 976.
- ⟨Perform computations for last line and **goto found** 1847⟩ Used in section 1028.
- ⟨Perform the default output routine 1200⟩ Used in section 1189.
- ⟨Pontificate about improper alignment in display 1385⟩ Used in section 1384.
- ⟨Pop the condition stack 522⟩ Used in sections 524, 526, 535, and 536.
- ⟨Pop the expression stack and **goto found** 1790⟩ Used in section 1784.
- ⟨Prepare all the boxes involved in insertions to act as queues 1195⟩ Used in section 1191.
- ⟨Prepare for display after a non-empty paragraph 1735⟩ Used in section 1324.
- ⟨Prepare for display after an empty paragraph 1733⟩ Used in section 1323.
- ⟨Prepare new file *SyncTEX* information 1919*⟩ Used in section 563*.
- ⟨Prepare pseudo file *SyncTEX* information 1921*⟩ Used in section 1756*.
- ⟨Prepare terminal input *SyncTEX* information 1920*⟩ Used in section 350*.
- ⟨Prepare to deactivate node r , and **goto deactivate** unless there is a reason to consider lines of text from r to cur_p 1030⟩ Used in section 1027.
- ⟨Prepare to insert a token that matches *cur_group*, and print what it is 1243⟩ Used in section 1242.
- ⟨Prepare to move a box or rule node to the current page, then **goto contribute** 1179⟩ Used in section 1177.
- ⟨Prepare to move whatsit p to the current page, then **goto contribute** 1612⟩ Used in section 1177.
- ⟨Print a short indication of the contents of node p 193⟩ Used in sections 192* and 674.
- ⟨Print a symbolic description of the new break node 1022⟩ Used in section 1021.
- ⟨Print a symbolic description of this feasible break 1032⟩ Used in section 1031.
- ⟨Print additional data in the new active node 1853⟩ Used in section 1022.
- ⟨Print additional resources 763⟩ Used in section 762.

- ⟨Print character substitution tracing log 1891*⟩ Used in sections 1887* and 1888*.
- ⟨Print either ‘definition’ or ‘use’ or ‘preamble’ or ‘text’, and insert tokens that should lead to recovery 361*⟩ Used in section 360*.
- ⟨Print location of current line 335⟩ Used in section 334.
- ⟨Print newly busy locations 189⟩ Used in section 185.
- ⟨Print string *s* as an error message 1461*⟩ Used in section 1457*.
- ⟨Print string *s* on the terminal 1458*⟩ Used in section 1457*.
- ⟨Print the CreationDate key 809⟩ Used in section 807.
- ⟨Print the ModDate key 810⟩ Used in section 807.
- ⟨Print the Producer key 808⟩ Used in section 807.
- ⟨Print the banner line, including the date and time 562*⟩ Used in section 560*.
- ⟨Print the help information and **goto** *continue* 89⟩ Used in section 84*.
- ⟨Print the list between *printed_node* and *cur_p*, then set *printed_node* ← *cur_p* 1033⟩ Used in section 1032.
- ⟨Print the menu of available options 85⟩ Used in section 84*.
- ⟨Print the result of command *c* 498⟩ Used in section 496.
- ⟨Print two lines using the tricky pseudoprinted information 339⟩ Used in section 334.
- ⟨Print type of token list 336⟩ Used in section 334.
- ⟨Process an active-character control sequence and set *state* ← *mid_line* 375⟩ Used in section 366.
- ⟨Process an expression and **return** 1781⟩ Used in section 450.
- ⟨Process node-or-noad *q* as much as possible in preparation for the second pass of *mlist_to_hlist*, then move to the next item in the *mlist* 903⟩ Used in section 902.
- ⟨Process the font definitions 715⟩ Used in section 712.
- ⟨Process the preamble 714⟩ Used in section 712.
- ⟨Process whatsit *p* in *vert_break* loop, **goto** *not_found* 1613⟩ Used in section 1150.
- ⟨Prune the current list, if necessary, until it contains only *char_node*, *kern_node*, *hlist_node*, *vlist_node*, *rule_node*, and *ligature_node* items; set *n* to the length of the list, and set *q* to the list’s tail 1299⟩ Used in section 1297.
- ⟨Prune unwanted nodes at the beginning of the next line 1055⟩ Used in section 1053.
- ⟨Pseudoprint the line 340*⟩ Used in section 334.
- ⟨Pseudoprint the token list 341⟩ Used in section 334.
- ⟨Push the condition stack 521⟩ Used in section 524.
- ⟨Push the expression stack and **goto** *restart* 1789⟩ Used in section 1786.
- ⟨Put each of TeX’s primitives into the hash table 244, 248*, 256*, 266, 287*, 356, 402, 410, 437, 442, 494, 513, 517, 579, 956, 1160, 1230, 1236, 1249, 1266, 1285, 1292, 1319, 1334, 1347, 1356, 1366, 1386, 1397*, 1400*, 1408*, 1428, 1432, 1440, 1450, 1455, 1464, 1469, 1525*, 1909*⟩ Used in section 1517.
- ⟨Put help message on the transcript file 90⟩ Used in section 82*.
- ⟨Put the characters *hu*[*i* + 1 ..] into *post_break*(*r*), appending to this list and to *major_tail* until synchronization has been achieved 1093⟩ Used in section 1091.
- ⟨Put the characters *hu*[*l* .. *i*] and a hyphen into *pre_break*(*r*) 1092⟩ Used in section 1091.
- ⟨Put the fraction into a box with its delimiters, and make *new_hlist*(*q*) point to it 924⟩ Used in section 919.
- ⟨Put the \leftskip glue at the left and detach this line 1063⟩ Used in section 1056.
- ⟨Put the optimal current page into box 255, update *first_mark* and *bot_mark*, append insertions to their boxes, and put the remaining nodes back on the contribution list 1191⟩ Used in section 1189.
- ⟨Put the (positive) ‘at’ size into *s* 1437⟩ Used in section 1436.
- ⟨Put the \rightskip glue after node *q* 1062⟩ Used in section 1057.
- ⟨Read and check the font data; *abort* if the TFM file is malformed; if there’s no room for this font, say so and **goto** *done*; otherwise *incr*(*font_ptr*) and **goto** *done* 588⟩ Used in section 586*.
- ⟨Read box dimensions 598⟩ Used in section 588.
- ⟨Read character data 595⟩ Used in section 588.
- ⟨Read extensible character recipes 601⟩ Used in section 588.
- ⟨Read font parameters 602*⟩ Used in section 588.
- ⟨Read ligature/kern program 600*⟩ Used in section 588.

- ⟨ Read next line of file into *buffer*, or **goto restart** if the file has ended 384 ⟩ Used in section 382.
- ⟨ Read the first line of the new file 564 ⟩ Used in section 563*.
- ⟨ Read the other strings from the TEX.POOL file and return *true*, or give an error message and return *false* 51* ⟩ Used in section 47*.
- ⟨ Read the TFM header 594 ⟩ Used in section 588.
- ⟨ Read the TFM size fields 591 ⟩ Used in section 588.
- ⟨ Readjust the height and depth of *cur_box*, for **\vtop** 1265 ⟩ Used in section 1264.
- ⟨ Rebuild character using substitution information 1892* ⟩ Used in section 1887*.
- ⟨ Reconstitute nodes for the hyphenated word, inserting discretionary hyphens 1090 ⟩ Used in section 1080.
- ⟨ Record a new feasible break 1031 ⟩ Used in section 1027.
- ⟨ Record current point *SyncTeX* information 1931* ⟩ Used in sections 648* and 731*.
- ⟨ Record horizontal *rule_node* or *glue_node* *SyncTeX* information 1932* ⟩ Used in sections 650* and 732*.
- ⟨ Record void list *SyncTeX* information 1930* ⟩ Used in sections 651*, 660*, 733*, and 742*.
- ⟨ Record *kern_node* *SyncTeX* information 1933* ⟩ Used in sections 650* and 732*.
- ⟨ Record *math_node* *SyncTeX* information 1934* ⟩ Used in sections 650* and 732*.
- ⟨ Recover from an unbalanced output routine 1204 ⟩ Used in section 1203*.
- ⟨ Recover from an unbalanced write command 1620 ⟩ Used in section 1619*.
- ⟨ Recycle node *p* 1176 ⟩ Used in section 1174.
- ⟨ Reduce to the case that $a, c \geq 0$, $b, d > 0$ 123 ⟩ Used in section 122.
- ⟨ Reduce to the case that $f \geq 0$ and $q > 0$ 115 ⟩ Used in section 114.
- ⟨ Remove the last box, unless it's part of a discretionary 1259 ⟩ Used in section 1258.
- ⟨ Replace nodes *ha* .. *hb* by a sequence of nodes that includes the discretionary hyphens 1080 ⟩ Used in section 1072.
- ⟨ Replace the tail of the list by *p* 1365 ⟩ Used in section 1364.
- ⟨ Replace *z* by *z'* and compute α, β 599 ⟩ Used in section 598.
- ⟨ Report LR problems 1714 ⟩ Used in sections 1713 and 1731.
- ⟨ Report a runaway argument and abort 422 ⟩ Used in sections 418 and 425.
- ⟨ Report a tight hbox and **goto common_ending**, if this box is sufficiently bad 843 ⟩ Used in section 840.
- ⟨ Report a tight vbox and **goto common_ending**, if this box is sufficiently bad 854 ⟩ Used in section 852.
- ⟨ Report an extra right brace and **goto continue** 421 ⟩ Used in section 418.
- ⟨ Report an improper use of the macro and abort 424 ⟩ Used in section 423.
- ⟨ Report an overfull hbox and **goto common_ending**, if this box is sufficiently bad 842 ⟩ Used in section 840.
- ⟨ Report an overfull vbox and **goto common_ending**, if this box is sufficiently bad 853 ⟩ Used in section 852.
- ⟨ Report an underfull hbox and **goto common_ending**, if this box is sufficiently bad 836 ⟩ Used in section 834.
- ⟨ Report an underfull vbox and **goto common_ending**, if this box is sufficiently bad 850 ⟩ Used in section 849.
- ⟨ Report overflow of the input buffer, and abort 35* ⟩ Used in sections 31* and 1757.
- ⟨ Report that an invalid delimiter code is being changed to null; set *cur_val* $\leftarrow 0$ 1339 ⟩ Used in section 1338.
- ⟨ Report that the font won't be loaded 587* ⟩ Used in section 586*.
- ⟨ Report that this dimension is out of range 486 ⟩ Used in section 474.
- ⟨ Reset PDF mark lists 754 ⟩ Used in section 752.
- ⟨ Reset resource lists 753 ⟩ Used in sections 752 and 775.
- ⟨ Reset *cur_tok* for unexpandable primitives, goto restart 395 ⟩ Used in sections 439 and 466.
- ⟨ Restore resource lists 777 ⟩ Used in section 775.
- ⟨ Resume the page builder after an output routine has come to an end 1203* ⟩ Used in section 1278*.
- ⟨ Retrieve the prototype box 1743 ⟩ Used in sections 1372 and 1372.
- ⟨ Reverse an hlist segment and **goto reswitch** 1723* ⟩ Used in section 1718.
- ⟨ Reverse the complete hlist and set the subtype to *reversed* 1722* ⟩ Used in section 1715.
- ⟨ Reverse the linked list of Page and Pages objects 800 ⟩ Used in section 794.
- ⟨ Reverse the links of the relevant passive nodes, setting *cur_p* to the first breakpoint 1054 ⟩ Used in section 1053.
- ⟨ Save current position in DVI mode 1622 ⟩ Used in section 1621*.
- ⟨ Save current position to *pdf_last_x_pos*, *pdf_last_y_pos* 1642 ⟩ Used in sections 1640 and 1646.

- ⟨ Save current position to *pdf_snapx_refpos*, *pdf_snapy_refpos* 1643 ⟩ Used in sections 1640 and 1646.
- ⟨ Save resource lists 776 ⟩ Used in section 775.
- ⟨ Scan a control sequence and set *state* ← *skip_blanks* or *mid_line* 376* ⟩ Used in section 366.
- ⟨ Scan a factor *f* of type *o* or start a subexpression 1786 ⟩ Used in section 1784.
- ⟨ Scan a numeric constant 470 ⟩ Used in section 466.
- ⟨ Scan a parameter until its delimiter string has been found; or, if *s* = *null*, simply scan the delimiter string 418 ⟩ Used in section 417.
- ⟨ Scan a subformula enclosed in braces and **return** 1331 ⟩ Used in section 1329.
- ⟨ Scan ahead in the buffer until finding a nonletter; if an expanded code is encountered, reduce it and **goto** *start_cs*; otherwise if a multiletter control sequence is found, adjust *cur_cs* and *loc*, and **goto** *found* 378* ⟩ Used in section 376*.
- ⟨ Scan an alphabetic character code into *cur_val* 468 ⟩ Used in section 466.
- ⟨ Scan an optional space 469 ⟩ Used in sections 468, 474, 481, 705, 1378, 1545, 1557, 1557, 1559, and 1566.
- ⟨ Scan and build the body of the token list; **goto** *found* when finished 503 ⟩ Used in section 499.
- ⟨ Scan and build the parameter part of the macro definition 500 ⟩ Used in section 499.
- ⟨ Scan and evaluate an expression *e* of type *l* 1784 ⟩ Used in section 1783.
- ⟨ Scan decimal fraction 478 ⟩ Used in section 474.
- ⟨ Scan file name in the buffer 557 ⟩ Used in section 556*.
- ⟨ Scan for all other units and adjust *cur_val* and *f* accordingly; **goto** *done* in the case of scaled points 484 ⟩ Used in section 479.
- ⟨ Scan for **fil** units; **goto** *attach_fraction* if found 480 ⟩ Used in section 479.
- ⟨ Scan for **mu** units and **goto** *attach_fraction* 482 ⟩ Used in section 479.
- ⟨ Scan for units that are internal dimensions; **goto** *attach_sign* with *cur_val* set if found 481 ⟩ Used in section 479.
- ⟨ Scan preamble text until *cur_cmd* is *tab_mark* or *car_ret*, looking for changes in the tabskip glue; append an alignrecord to the preamble list 955 ⟩ Used in section 953.
- ⟨ Scan the argument for command *c* 497 ⟩ Used in section 496.
- ⟨ Scan the font size specification 1436 ⟩ Used in section 1435*.
- ⟨ Scan the next operator and set *o* 1785 ⟩ Used in section 1784.
- ⟨ Scan the parameters and make *link(r)* point to the macro body; but **return** if an illegal **\par** is detected 417 ⟩ Used in section 415.
- ⟨ Scan the preamble and record it in the *preamble* list 953 ⟩ Used in section 950.
- ⟨ Scan the template $\langle u_j \rangle$, putting the resulting token list in *hold_head* 959 ⟩ Used in section 955.
- ⟨ Scan the template $\langle v_j \rangle$, putting the resulting token list in *hold_head* 960 ⟩ Used in section 955.
- ⟨ Scan units and set *cur_val* to $x \cdot (cur_val + f/2^{16})$, where there are *x* sp per unit; **goto** *attach_sign* if the units are internal 479 ⟩ Used in section 474.
- ⟨ Search *eqtb* for equivalents equal to *p* 273 ⟩ Used in section 190.
- ⟨ Search *hyph.list* for pointers to *p* 1110 ⟩ Used in section 190.
- ⟨ Search *save_stack* for equivalents that point to *p* 307 ⟩ Used in section 190.
- ⟨ Select the appropriate case and **return** or **goto** *common_ending* 535 ⟩ Used in section 527*.
- ⟨ Set initial values of key variables 21, 23*, 24*, 74*, 77, 80, 97, 118, 184, 233*, 272, 276*, 294, 309, 390, 409, 465, 507, 516, 577*, 582, 620, 623, 633, 677, 681, 688, 697, 709, 711, 724, 820, 830, 838, 861, 947, 1105*, 1167, 1210, 1445, 1460, 1479, 1524, 1552, 1572, 1585, 1630, 1635, 1707, 1752, 1818, 1837, 1861, 1869*, 1880*, 1884*, 1899* ⟩ Used in section 8*.
- ⟨ Set line length parameters in preparation for hanging indentation 1025 ⟩ Used in section 1024.
- ⟨ Set the glue in all the unset boxes of the current list 981 ⟩ Used in section 976.
- ⟨ Set the glue in node *r* and change it from an unset node 984 ⟩ Used in section 983.
- ⟨ Set the unset box *q* and the unset boxes in it 983 ⟩ Used in section 981.
- ⟨ Set the value of *b* to the badness for shrinking the line, and compute the corresponding *fit_class* 1029 ⟩ Used in section 1027.
- ⟨ Set the value of *b* to the badness for stretching the line, and compute the corresponding *fit_class* 1028 ⟩ Used in section 1027.

- ⟨Set the value of b to the badness of the last line for shrinking, compute the corresponding *fit_class*, and **goto found 1849**⟩ Used in section 1847.
- ⟨Set the value of b to the badness of the last line for stretching, compute the corresponding *fit_class*, and **goto found 1848**⟩ Used in section 1847.
- ⟨Set the value of *output_penalty* 1190⟩ Used in section 1189.
- ⟨Set the value of x to the text direction before the display 1732⟩ Used in sections 1733 and 1735.
- ⟨Set up data structures with the cursor following position j 1085⟩ Used in section 1083.
- ⟨Set up the hlist for the display line 1746⟩ Used in section 1745.
- ⟨Set up the values of *cur_size* and *cur_mu*, based on *cur_style* 879⟩ Used in sections 896, 902, 903, 906, 930, 936, 938, and 939.
- ⟨Set variable c to the current escape character 261⟩ Used in section 63.
- ⟨Set variable w to indicate if this case should be reported 1776⟩ Used in sections 1775 and 1777.
- ⟨Ship box p out 668*⟩ Used in section 666*.
- ⟨Show equivalent n , in region 1 or 2 241⟩ Used in section 270*.
- ⟨Show equivalent n , in region 3 247⟩ Used in section 270*.
- ⟨Show equivalent n , in region 4 251⟩ Used in section 270*.
- ⟨Show equivalent n , in region 5 260⟩ Used in section 270*.
- ⟨Show equivalent n , in region 6 269⟩ Used in section 270*.
- ⟨Show the auxiliary field, a 237*⟩ Used in section 236.
- ⟨Show the box context 1682⟩ Used in section 1680.
- ⟨Show the box packaging info 1681⟩ Used in section 1680.
- ⟨Show the current contents of a box 1475*⟩ Used in section 1471*.
- ⟨Show the current meaning of a token, then **goto common_ending 1473***⟩ Used in section 1471*.
- ⟨Show the current value of some parameter or register, then **goto common_ending 1476***⟩ Used in section 1471*.
- ⟨Show the font identifier in *eqtb*[n] 252⟩ Used in section 251.
- ⟨Show the halfword code in *eqtb*[n] 253⟩ Used in section 251.
- ⟨Show the status of the current page 1163⟩ Used in section 236.
- ⟨Show the text of the macro being expanded 427*⟩ Used in section 415.
- ⟨Simplify a trivial box 897*⟩ Used in section 896.
- ⟨Skip to **\else** or **\fi**, then **goto common_ending 526**⟩ Used in section 524.
- ⟨Skip to node *ha*, or **goto done1** if no hyphenation should be attempted 1073⟩ Used in section 1071.
- ⟨Skip to node *hb*, putting letters into *hu* and *hc* 1074⟩ Used in section 1071.
- ⟨Sort p into the list starting at *rover* and advance p to *rlink*(p) 150⟩ Used in section 149.
- ⟨Sort the hyphenation op tables into proper order 1122*⟩ Used in section 1129.
- ⟨Split off part of a vertical box, make *cur_box* point to it 1260⟩ Used in section 1257.
- ⟨Squeeze the equation as much as possible; if there is an equation number that should go on a separate line by itself, set $e \leftarrow 0$ 1379⟩ Used in section 1377.
- ⟨Start a new current page 1168⟩ Used in section 1194.
- ⟨Start hlist *SyncTEX* information record 1928*⟩ Used in sections 647* and 729*.
- ⟨Start sheet *SyncTEX* information record 1924*⟩ Used in section 666*.
- ⟨Start stream of page/form contents 757⟩ Used in section 752.
- ⟨Start vlist *SyncTEX* information record 1926*⟩ Used in sections 657* and 738*.
- ⟨Store additional data for this feasible break 1851⟩ Used in section 1031.
- ⟨Store additional data in the new active node 1852⟩ Used in section 1021.
- ⟨Store *cur_box* in a box register 1255⟩ Used in section 1253.
- ⟨Store maximum values in the *hyf* table 1101*⟩ Used in section 1100*.
- ⟨Store *save_stack*[*save_ptr*] in *eqtb*[p], unless *eqtb*[p] holds a global value 305*⟩ Used in section 304.
- ⟨Store all current *lc_code* values 1857⟩ Used in section 1856.
- ⟨Store hyphenation codes for current language 1856⟩ Used in section 1137*.
- ⟨Store the current token, but **goto continue** if it is a blank space that would become an undelimited parameter 419⟩ Used in section 418.

- ⟨Store the packet being built 718⟩ Used in section 717.
- ⟨Subtract glue from *break_width* 1014⟩ Used in section 1013.
- ⟨Subtract the width of node *v* from *break_width* 1017⟩ Used in section 1016.
- ⟨Suppress expansion of the next token 393*⟩ Used in section 391.
- ⟨Swap the subscript and superscript into box *x* 918⟩ Used in section 914.
- ⟨Switch to a larger accent if available and appropriate 916*⟩ Used in section 914.
- ⟨Tell the user what has run away and try to recover 360*⟩ Used in section 358.
- ⟨Terminate the current conditional and skip to `\fi` 536⟩ Used in section 391.
- ⟨Test box register status 531⟩ Used in section 527*.
- ⟨Test if an integer is odd 530⟩ Used in section 527*.
- ⟨Test if two characters match 532⟩ Used in section 527*.
- ⟨Test if two macro texts match 534⟩ Used in section 533.
- ⟨Test if two tokens match 533⟩ Used in section 527*.
- ⟨Test relation between integers or dimensions 529⟩ Used in section 527*.
- ⟨The em width for *cur_font* 584⟩ Used in section 481.
- ⟨The x-height for *cur_font* 585⟩ Used in section 481.
- ⟨Tidy up the parameter just scanned, and tuck it away 426*⟩ Used in section 418.
- ⟨Transfer node *p* to the adjustment list 831⟩ Used in section 825.
- ⟨Transplant the post-break list 1060⟩ Used in section 1058.
- ⟨Transplant the pre-break list 1061⟩ Used in section 1058.
- ⟨Treat *cur_chr* as an active character 1330⟩ Used in sections 1329 and 1333.
- ⟨Try the final line break at the end of the paragraph, and **goto done** if the desired breakpoints have been found 1049⟩ Used in section 1039.
- ⟨Try to allocate within node *p* and its physical successors, and **goto found** if allocation was possible 145⟩ Used in section 143*.
- ⟨Try to break after a discretionary fragment, then **goto done5** 1045⟩ Used in section 1042.
- ⟨Try to get a different log file name 561⟩ Used in section 560*.
- ⟨Try to hyphenate the following word 1071⟩ Used in section 1042.
- ⟨Try to recover from mismatched `\right` 1370⟩ Used in section 1369.
- ⟨Types in the outer block 18, 25, 38*, 101, 109*, 131*, 168, 230, 291, 322*, 574*, 621, 694, 707, 722, 1097*, 1102*, 1628, 1633, 1679⟩ Used in section 4*.
- ⟨Undump ML \TeX -specific data 1895*⟩ Used in section 1482*.
- ⟨Undump a couple more things and the closing check word 1508*⟩ Used in section 1482*.
- ⟨Undump constants for consistency check 1487*⟩ Used in section 1482*.
- ⟨Undump enc \TeX -specific data 1904*⟩ Used in section 1482*.
- ⟨Undump pdfTeX data 1506⟩ Used in section 1482*.
- ⟨Undump regions 1 to 6 of *eqtb* 1496*⟩ Used in section 1493*.
- ⟨Undump the ε - \TeX state 1656⟩ Used in section 1487*.
- ⟨Undump the array info for internal font number *k* 1502*⟩ Used in section 1500*.
- ⟨Undump the dynamic memory 1491*⟩ Used in section 1482*.
- ⟨Undump the font information 1500*⟩ Used in section 1482*.
- ⟨Undump the hash table 1498*⟩ Used in section 1493*.
- ⟨Undump the hyphenation tables 1504*⟩ Used in section 1482*.
- ⟨Undump the string pool 1489*⟩ Used in section 1482*.
- ⟨Undump the table of equivalents 1493*⟩ Used in section 1482*.
- ⟨Undump *xord*, *xchr*, and *xprn* 1876*⟩ Used in section 1487*.
- ⟨Update the active widths, since the first active node has been deleted 1037⟩ Used in section 1036.
- ⟨Update the current height and depth measurements with respect to a glue or kern node *p* 1153⟩ Used in section 1149.
- ⟨Update the current marks for *fire_up* 1831⟩ Used in section 1191.
- ⟨Update the current marks for *vsplit* 1828⟩ Used in section 1156.

- ⟨ Update the current page measurements with respect to the glue or kern specified by node *p* 1181 ⟩ Used in section 1174.
- ⟨ Update the value of *printed_node* for symbolic displays 1034 ⟩ Used in section 1005.
- ⟨ Update the values of *first_mark* and *bot_mark* 1193 ⟩ Used in section 1191.
- ⟨ Update the values of *last_glue*, *last_penalty*, and *last_kern* 1173 ⟩ Used in section 1171.
- ⟨ Update the values of *max_h* and *max_v*; but if the page is too large, **goto done** 669 ⟩ Used in sections 668* and 751.
- ⟨ Update width entry for spanned columns 974 ⟩ Used in section 972.
- ⟨ Use code *c* to distinguish between generalized fractions 1360 ⟩ Used in section 1359.
- ⟨ Use node *p* to update the current height and depth measurements; if this node is not a legal breakpoint, **goto not_found** or *update_heights*, otherwise set *pi* to the associated penalty at the break 1150 ⟩ Used in section 1149.
- ⟨ Use size fields to allocate font information 592 ⟩ Used in section 588.
- ⟨ Wipe out the whatsit node *p* and **goto done** 1606 ⟩ Used in section 220*.
- ⟨ Wrap up the box specified by node *r*, splitting node *p* if called for; set *wait* ← *true* if node *p* holds a remainder after splitting 1198 ⟩ Used in section 1197.
- ⟨ Write out Form stream header 756 ⟩ Used in section 752.
- ⟨ Write out PDF annotations 781 ⟩ Used in section 780.
- ⟨ Write out PDF bead rectangle specifications 786 ⟩ Used in section 780.
- ⟨ Write out PDF link annotations 782 ⟩ Used in section 780.
- ⟨ Write out PDF mark destinations 784 ⟩ Used in section 780.
- ⟨ Write out page object 769 ⟩ Used in section 759.
- ⟨ Write out pending PDF marks 780 ⟩ Used in section 759.
- ⟨ Write out pending forms 775 ⟩ Used in section 761.
- ⟨ Write out pending images 779 ⟩ Used in section 761.
- ⟨ Write out pending raw objects 773 ⟩ Used in section 761.
- ⟨ Write out resource lists 761 ⟩ Used in section 759.
- ⟨ Write out resources dictionary 762 ⟩ Used in section 759.
- ⟨ syntex case for *print_param* 1910* ⟩ Used in section 255*.